



Product Specification

Revision: New
Issue Date: 05/12/2016

Amcor Item:

40002052-0

Product detail:

Customer:	Sega Pac Pty Ltd
Customer description:	N/A
Customer code:	NA
Material Structure description:	14µm PVdC PET/ Adhesive / 70µm PE
Amcor description:	SEG SL PVDC PET / 70UM PE 740mm
APN Barcode number:	NA

Printing Information and Specifications:

Printing Process:	N/A
Print Quality:	N/A
Print Rewind Direction to Customer:	PE Side Inside
Print Number Colours:	N/A
Total retain solvent:	N/A
Solid Colour Variation:	N/A
APN Bar Code Scan Quality:	N/A



Property Specifications and Tolerances (Minimum, Maximum or Range):

Opacity (White):	N/A
Optical density (Metallized):	N/A
Lam Bond strength 1 st Pass:	Min 200 gf/25mm
Heat Seal:	Min 1,000 gf/25mm (B/B seals)
WVTR: (38 deg C, 90% RH)	< 5 cc/m ² /day
OTR: (25 deg C, 0% RH)	< 10 cc/m ² /day
COF: External	0.20 – 0.40 (outside to outside)
COF: Internal	0.15 – 0.20 (inside to inside)
Thickness:	86um ± 10%
Yield: gsm	86 gsm ± 10%
Repeat length (± 1mm):	Plain
Slit width (± 1mm):	740mm

Other Information:

Odour:	The material supplied shall be free from excessive odour and shall not cause any deterioration in the organoleptic character of the food nor bring about any unacceptable change in the quality of the food.
General:	The material supplied shall be of an acceptable commercial standard free from bubbles, streaks, creasing, or foreign matter, any of which may preclude its satisfactory conversion or end use Application.
Product Stewardship and Recyclability:	This film covered by the specification can be classified under Plastics Identification Code 7 (OTHER). Flexible packaging cannot be disposed of currently in curbside collection although clean film can be recycled using industrial recyclers. Cardboard cores can be recycled by industrial recyclers if the film and tape is removed. Cardboard layer pads used as packaging on the pallet can be recycled using industrial recyclers. Where Amcor has suggested that our product and/or packaging can be Recycled Amcor can assist with identifying suitable recyclers.



Slitting, Packing, Transport, Storage Information:

Core:

Paper core ID 76 mm

Joins number:

1 max

Joins Tape:

Red tape

Stack roll on pallet:

25 rolls/layer, 1 layer per pallet

Position joins:

Butt/In register, Red tape flags on Left hand side or roll

Roll Label Information:

To contain Customer name, job details, roll ID, roll weight etc...

Roll size / length / weight:

180mm O/D, 220m, 15 kg max

Pallet Type:

Plain wood

General Packaging:

Pallet contents to be secured on pallet to withstand the rigours of transport, handling, and storage. Pallets contents at delivery must be in good condition and fit for intended use.

Slitting, Packing, Transport, Storage Information:

Storage:

1. Pouches, bags, rewind or laminate should be kept out of direct natural light/sunlight and in a well-ventilated area at temperatures less than 35 deg C, unless specified otherwise on labeling.
2. It is advantageous to condition the cartons or rolls to packing room temperature at least 24 hrs. prior to use.
3. At all times when not in use the carton should be sealed or rolls covered so performance is not impaired or contamination permitted.

Food Contact:

All resins, polymers and additives used in the manufacture of these Products conform to the following regulations:
PE Resin: 21CFR177.1520 (c) 3.2C and 21CFR177.1330
Adhesive: FDA 21CFR175.105
PET Film: 21CFR177.1630, 21CFR175.300
All inks are formulated to guidelines specified by the European Council of Paint, Printing Ink and Artists Colour Industry (CEPE) and the ingredients are listed in the raw materials used in the inks are listed in Ordinance of the Swiss FDHA (RS 817.023.21), section 8b Annex 6 April 2013 A and B lists. Inks are NOT approved for DIRECT contact with foods.



Approved by (Amcor):

Approved by (Customer):

Dennis Marazzato

Position: Process Engineering Manager
Date: Monday, December 05, 2016

Position:
Date: