



PRODUCT SPECIFICATION SHEET

Revision New

Code:

Issue Date: 2026-06-12

ITEM REF / CODE

ACP501-2

A. PRODUCT DETAILS

Customer Name:	Ochre Dough
Customer Description:	Home compostable packaging for food products
Customer Code:	OCD0
Material Structure:	Ink / Kraft Paper 50gsm / Adhesive / Metalised Cellulose 25um / PBS 60um
Internal Description:	Home Compostable Kraft Paper Based Metalised
APN Barcode:	NA

B. PRINTING SPECIFICATIONS

Printing Process:	Digital Printing
Print Quality Standard:	High-Definition Digital Print by HP Indigo 25000
Number Colours:	various
Retain Solvent Limit:	< 5.0 mg/m ²
Colour Variation:	$\Delta E < 2.0$
APN Barcode Quality:	Grade A

C. TECHNICAL ARTWORK PROOF



DESIGN 1



DESIGN 2



DESIGN 3

MULTI-DESIGN SYSTEM PROOFS
(3)

C. PHYSICAL PROPERTY SPECIFICATIONS & TOLERANCES

The following testing metrics reflect minimal threshold tolerances, ranges, or industrial packaging parameters:

Opacity (White Films):	N/A	Optical Density:	N/A
Lamination Bond Strength:	Min 200 gf/25mm	Heat Seal Strength:	Min 1,000 gf/25mm (B/B seals)
WVTR (Water Vapor):	< 10 cc/m ² /day (38°C, 90% RH)	OTR (Oxygen Gas):	< 10 cc/m ² /day (25°C, 0% RH)
COF External:	0.20 – 0.40 (outside to outside)	COF Internal:	0.15 – 0.20 (inside to inside)
Total Thickness (microns):	150um ± 10%	Laminate Yield (gsm):	173 gsm ± 10%
Repeat Length (± 1mm):	Plain	Slit Width (± 1mm):	740mm

D. OTHER TECHNICAL INFORMATION

Odour & Migration:	The material supplied shall be free from excessive odour and shall not cause any deterioration in the organoleptic character of the food nor bring about any unacceptable change in the quality of the food.
General Workmanship:	The material supplied shall be of an acceptable commercial standard free from bubbles, streaks, creasing, or foreign matter, any of which may preclude its satisfactory conversion or end use Application.
Product Stewardship & Sustainability:	Certified Industrial Compostable (Seed logo) under EN 13432 and ASTM D6400. Certified Home Compostable under the Australasian Bioplastics Association standard AS5810.  * The selected logo(s) can be added to the artwork for printing to represent the material used.

E. POUCH DIMENSIONS, FEATURES & PACKING INFORMATION

Pouch Shape / Format:	Stand Up Pouch
Pouch Dimensions (W × L):	N/A
Pouch Gusset Dimension:	N/A
Zipper & Reclosure Type:	Press-to-close zipper
Tear Notch Style:	Two tear notches
Hang Hole / Display Feature:	None
Pouch Carton Packing Layout:	50pc / bundle
Pallet Setup Type:	Ply wood
Carton & Transport Packaging:	Pallet contents to be secured on pallet to withstand the rigours of transport, handling, and storage. Pallet contents at delivery must be in good condition and fit for intended use.

F. STORAGE & REGULATORY COMPLIANCE INFORMATION

Storage and Handling Instruction:	1.Pouches, bags, rewind or laminate should be kept out of direct natural light/sunlight and in a well-ventilated area at temperatures less than 35 deg C, unless specified otherwise on labeling. 2.It is advantageous to condition the cartons or rolls to packing room temperature at least 24 hrs. prior to use. 3.At all times when not in use the carton should be sealed or rolls covered so performance is not impaired or contamination permitted.
Food Contact Regulatory Status:	All resins, polymers and additives used in the manufacture of these Products conform to the following regulations: PE Resin: 21CFR177.1520 (c) 3.2C and 21CFR177.1330 Adhesive: FDA 21CFR175.105 PET Film: 21CFR177.1630, 21CFR175.300 All inks are formulated to guidelines specified by the European Council of Paint, Printing Ink and Artists Colour Industry (CEPE) and the ingredients are listed in the raw materials used in the inks are listed in Ordinance of the Swiss FDHA (RS 817.023.21), section 8b Annex 6 April 2013 A and B lists. Inks are NOT approved for DIRECT contact with foods.

Technical Specifications Agreement

By signing below, both parties formally agree to the physical material tolerances, barrier criteria, slitting specifications, and packing setups documented in this 4-page technical specification sheet. No print alterations or material grade changes shall be executed without prior written consent.



APPROVED BY ACHIEVEPACK

Ryan Wong
Position: Export Sales Manager
Approval Date: Monday, December 05, 2025

APPROVED BY CUSTOMER

Pending Sign-off
Position: Technical Representative
Approval Date: N/A