

FACTORY INSPECTION REPORT / CERTIFICATE OF ANALYSIS

Sample Name: **Stand-up pouch zipper**

Customer Name: **Sega Pac Pty Ltd**

Customer Address:
Unit 4, 12 Technology Drive, Lane Cove NSW 2066, Australia

Material Composition:
MOPP-Double Electrification/Reinforced VMPET//Reinforced PE

Product Specs: **300*340+75 mm**

Test Conditions: **25/50**

Prod Date:
2025-07-08

Sampling Qty:
315 pcs

Batch No:
SC3340634

Delivery Qty:
10,500 pcs

Item Category	Inspection Item	Inspection Standard	Test Speed	Inspection Result	Conclusion
Appearance	Printing	The finished products are clean, without obvious dirt, defects, knife marks, or scratches. The text printing is clear and complete, with smooth edges of the imprints. The mesh pattern is clear and uniform, without obvious deformation or damage. The overprinting is basically accurate, with almost no color difference between the same colors, and the black layer has a glossy finish.	-	Conform to	Qualified
	Wrinkles	Minor wrinkles are allowed (for bags, minor wrinkles that do not penetrate the heat-sealed edges are permitted).	-	Conform to	Qualified
	Contamination marks	No foreign objects, oil stains, or other contaminants are allowed. Slight unevenness in adhesive application or marks caused by pressure rollers are permitted.	-	Conform to	Qualified
	Scratch, Scorch	No burns or holes in single-layer films are allowed, and no scratches are permitted.	-	Conform to	Qualified
	Perforation, Bubble	No perforations or bubbles that affect usability are allowed.	-	Conform to	Qualified
	Flatness of rolled film	The surface of the rolled film is flat, and the end face is basically neat.	-	Conform to	Qualified
Dimensional	Number of joints in rolled film	No more than 2 per kilometer; the joints must be firm, accurate, and marked.	-	Conform to	Qualified
	Length deviation	As per the customer's needs (Film > 0, Bag see Q/JHX01-2018)	-	Conform to	Qualified
	Width deviation	As per the customer's needs (Film ±2mm, Bag see Q/JHX01-2018)	-	Conform to	Qualified
	Thickness deviation	As per the customer's needs (Tolerance ±10%)	-	Conform to	Qualified
Physical & Mech	Tensile strength	≥30	250	101.1	Qualified
	Elongation at break	≥25	250	26.3	Qualified
	Peel strength	≥0.2	250	Cannot be peeled off	Qualified
	Heat-seal strength	≥7	300	63	Qualified
	Pressure resistance performance of the bag	No penetration, no rupture.	6h	Conform to	Qualified
	Drop performance of the bag	No penetration, no rupture.	-	Conform to	Qualified

OVERALL INSPECTION CONCLUSION

This batch of products has passed the inspection and is approved for delivery.

SIGNATURE OF ANALYST

Lin Fang

SIGNATURE OF FACTORY DIRECTOR


Xiongwei