

1. Create the LOC1 table with the following structure:

```
CREATE TABLE LOC1(  
  location_id number(6) PRIMARY KEY,  
  street varchar2(40),  
  postal_code varchar2(20),  
  city varchar2(20),  
  state varchar2(20)  
);
```

2. Create the DEPT1 table with the following structure:

```
CREATE TABLE DEPT1(  
  department_id number(6) PRIMARY KEY,  
  department_name varchar2(40),  
  manager_id number(6),  
  location_id number(6)  
);
```

3. Create the EMPL1 table with the following structure:

```
CREATE TABLE EMPL1(  
  employee_id number(8) PRIMARY KEY,  
  first_name char(30),  
  last_name char(40),  
  hire_date date,  
  salary number(8,2),  
  department_id number(6),  
  manager_id number(6)  
);
```

4. Insert rows into the tables created based on the following tables:

LOC1

insert all into LOC1

values (1400, '2014 Jabberwocky Rd', 26192, 'Southlake', 'Texas')

INTO LOC1 VALUES (1500, '2011 Interiors Blvd', 99236, 'South San Francisco', 'California')

INTO LOC1 VALUES (1700, '2004 Charade Rd', 98199, 'Seattle', 'Washington')

INTO LOC1 VALUES (1800, '460 Bloor St', 'On M551X8', 'Toronto', 'Ontario')

INTO LOC1 VALUES (2500, 'Magdalene Center', 'OX9 9ZB', 'Oxford', 'Oxford')

select 1 from dual;

DEPT1

insert all into DEPT1

values (10, 'Administration', 200, 1700)

INTO DEPT1 VALUES (20, 'Marketing', 201, 1800)

INTO DEPT1 VALUES (50, 'Shipping', 124, 1500)

INTO DEPT1 VALUES (60, 'IT', 103, 1400)

INTO DEPT1 VALUES (80, 'Sales', 149, 2500)

INTO DEPT1 VALUES (90, 'Executive', 100, 1700)

INTO DEPT1 VALUES (110, 'Accounting', 205, 1700)

INTO DEPT1 VALUES (190, 'Contracting', NULL, 1700)

select 1 from dual;

EMPL1

insert all into EMPL1

values (124, 'Kevin', 'Mourgos', '16-Nov-1999', 5800, 50, 100)

INTO EMPL1 VALUES (141, 'Trenna', 'Rajs', '17-Oct-1995', 3500, 50, 124)

INTO EMPL1 VALUES (142, 'Curtis', 'Davies', '29-Jan-1997', 3100, 50, 124)

INTO EMPL1 VALUES (143, 'Randall', 'Matos', '15-Mar-1998', 2600, 50, 124)

INTO EMPL1 VALUES (144, 'Peter', 'Vargas', '09-Jul-1998', 2500, 50, 124)

INTO EMPL1 VALUES (103, 'Alexander', 'Hunold', '03-Jan-1990', 9000, 60, 102)

INTO EMPL1 VALUES (104, 'Bruce', 'Ernst', '21-May-1991', 6000, 60, 103)

INTO EMPL1 VALUES (107, 'Diana', 'Lorentz', '07-Feb-1999', 4200, 60, 103)

INTO EMPL1 VALUES (149, 'Eleni', 'Zlotkey', '29-Jan-2000', 10500, 80, 100)

INTO EMPL1 VALUES (174, 'Ellen', 'Abel', '11-May-1996', 11000, 80, 149)

INTO EMPL1 VALUES (176, 'Jonathon', 'Taylor', '24-Mar-1998', 8600, 80, 149)

INTO EMPL1 VALUES (100, 'Steven', 'King', '17-Jun-1987', 24000, 90, NULL)

INTO EMPL1 VALUES (101, 'Neena', 'Kochhar', '21-Sep-1989', 17000, 90, 100)

INTO EMPL1 VALUES (102, 'Lex', 'De Haan', '13-Jan-1993', 17000, 90, 100)

select 1 from dual;

Use EMPL1, DEPT1 and LOC1 for the following:

1. Arrange all the employees using hire_date and display the first_name, the last_name and the salary.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
ORDER BY hire_date;
```

2. Display the minimum salary for employees having department_id=60 or 50.

```
SELECT MIN(salary)  
FROM EMPL1  
WHERE department_id IN (60, 50);
```

3. Display the first_name and the last_name in a single column for employees having department_id=50.

```
SELECT first_name || ' ' || last_name  
FROM EMPL1  
WHERE department_id = 50;
```

4. Display the first hired employee having department_id = 50.

```
SELECT first_name, last_name  
FROM EMPL1  
WHERE department_id = 50 AND hire_date = (SELECT MIN(hire_date) FROM EMPL1  
WHERE department_id = 50);
```

5. Increase the salary of employees having department_id=50 by 200 euros and display the salary, the last_name, the first_name and the new salary.

```
SELECT salary, last_name, first_name, salary + 200 AS new_salary  
FROM EMPL1  
WHERE department_id = 50;
```

6. Display the average salary for employees where department_id = 50 or 80 and round to two decimal places.

```
SELECT ROUND(AVG(salary), 2)  
FROM EMPL1  
WHERE department_id IN (50, 80);
```

7. Arrange in descending order according to last_name and display first_name, last_name, salary and hire_date for employees having department_id=80 and salary >6500.

```
SELECT first_name, last_name, salary, hire_date  
FROM EMPL1  
WHERE department_id = 80 AND salary>6500  
ORDER BY last_name DESC;
```

8. Increase the salary by 5% and display the first_name, the last_name, the salary, and the new salary.

```
SELECT first_name, last_name, salary, salary+salary*0.05  
FROM EMPL1  
WHERE department_id = 80 AND salary>6500  
ORDER BY last_name DESC;
```

9. Using a substitution variable for department_id, display the maximum salary for each department.

```
SELECT MAX(salary)  
FROM EMPL1  
WHERE department_id= :enter_department_id;
```

10. Display the latest hire date for department_id=80.

```
SELECT MAX(hire_date)  
FROM EMPL1  
WHERE department_id=80 AND hire_date = (SELECT MAX(hire_date) FROM EMPL1  
WHERE department_id = 80);
```

11. Display the last in the alphabetic list of names name for department_id=50.

```
SELECT last_name  
FROM EMPL1  
WHERE department_id=50  
ORDER BY last_name;
```

12. Display the last_name, first_name and the salary for employees having the salary greater than the average of salaries for employees having department_id=50.

```
SELECT last_name, first_name, salary  
FROM EMPL1  
WHERE salary > (SELECT min(salary) FROM EMPL1 Where department_id=50);
```

13. Display the first_name, the last_name, and the salary for employees hired before Rajs.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE hire_date < (SELECT hire_date FROM EMPL1 WHERE last_name = 'Rajs');
```

14. Display the first_name, the last_name, and the salary for employees who earn less than the average salaries for all the employees having department_id=50 or 80.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE salary < (SELECT AVG(salary) FROM EMPL1 WHERE department_id in (50, 80));
```

15. Display first_name, last_name, and the salary from employees who earn more than the minimum salaries for employees hired after Vargas.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE salary > (SELECT MIN(salary) FROM EMPL1 WHERE hire_date < (SELECT  
hire_date FROM EMPL1 WHERE last_name = 'Vargas'));
```

16. Display the first_name, the last_name, and the salary for employees hired before Vargas.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE hire_date < (SELECT hire_date FROM EMPL1 WHERE last_name = 'Vargas');
```

17. Display the first_name, the last_name, and the salary for employees who earn less than Hunold.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE salary < (SELECT salary FROM EMPL1 WHERE last_name = 'Hunold');
```

18. Display the first_name, the last_name, and the salary for employees having the same department_id as Matos.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name =  
'Matos');
```

19. Display all those employees who earn more than Lorentz and are in the same department as Zlotkey.

```
SELECT first_name, last_name, salary
FROM EMPL1
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name =
'Zlotkey' AND salary > (SELECT salary FROM EMPL1 WHERE last_name = 'Lorentz '));
```

20. Display all those employees who have the same department_id as Rajs and were hired before Zlotkey.

```
SELECT first_name, last_name, salary
FROM EMPL1
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name =
'Rajs ' AND hire_date < (SELECT hire_date FROM EMPL1 WHERE last_name = 'Zlotkey'));
```

21. Arrange all the employees having the same department as Zlotkey using salary, and display first_name, last_name and the salary.

```
SELECT first_name, last_name, salary
FROM EMPL1
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name =
'Zlotkey')
ORDER BY salary;
```

22. Increase the salary by 500 and display the first_name, the last_name, the salary, and the new salary for employees hired after Zlotkey.

```
SELECT first_name, last_name, salary, salary + 500
FROM EMPL1
WHERE hire_date > (SELECT hire_date FROM EMPL1 WHERE last_name = 'Zlotkey');
```

23. Display first_name, last_name, and the salary from employees who earn more than the minimum salaries for employees having department_id=50, 80 or 90.

```
SELECT first_name, last_name, salary
FROM EMPL1
WHERE salary > (SELECT MIN(salary) FROM EMPL1 WHERE department_id IN (50, 80,
90));
```

24. Display the first_name, the last_name, and the salary for employees who earn more than the maximum salaries for all the employees having department_id=50.

```
SELECT first_name, last_name, salary
FROM EMPL1
WHERE salary > (SELECT MAX(salary) FROM EMPL1 WHERE department_id IN (50));
```

25. Display first_name, last_name, and the salary from employees who earn more than the minimum salaries for employees hired after Matos.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE salary > (SELECT MIN(salary) FROM EMPL1 WHERE hire_date > (SELECT  
hire_date FROM EMPL1 WHERE last_name = 'Matos'));
```

26. Display the first_name, the last_name, and the salary for employees hired before Taylor.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE hire_date < (SELECT hire_date FROM EMPL1 WHERE last_name = 'Taylor');
```

27. Display all the information about employees having last_name starting with „M”.

```
SELECT *  
FROM EMPL1  
WHERE last_name LIKE 'M%';
```

28. Display first_name with capital letter, the last_name and the salary for employees having department_id =50 or 60.

```
SELECT UPPER(first_name), last_name, salary  
FROM EMPL1  
WHERE department_id IN (50, 60);
```

29. Display first_name, last_name, and the salary from employees who earn more than the minimum salaries for employees hired after Davies.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE salary > (SELECT MIN(salary) FROM EMPL1 WHERE hire_date > (SELECT  
hire_date FROM EMPL1 WHERE last_name = 'Davies'));
```

30. Create a join between the tables EMPL1 and DEPT1 and display all the information from both tables for employees having department_id=80.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE department_id =80;
```

31. Display the first_name, the last_name, and the salary for employees who earns more than the maximum salaries for all the employees having department_id=60.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE salary > (SELECT MAX(salary) FROM EMPL1 WHERE department_id =60);
```

32. Display the first_name, the last_name, and the salary for employees who earns more than Rajs.

```
SELECT first_name, last_name, salary  
FROM EMPL1  
WHERE salary > (SELECT salary FROM EMPL1 WHERE last_name = 'Rajs');
```

33. Display the first_name, the last_name, and the salary for employees having department_name=IT

```
SELECT first_name, last_name, salary  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE department_name='IT';
```

34. Display the first_name, the last_name, and the salary for employees having location_id=1500.

```
SELECT first_name, last_name, salary  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE location_id=1500;
```

35. Display the first_name, the last_name, the salary, the department_name and the location_id for employees having the same department_id as Rajs.

```
SELECT first_name, last_name, salary, department_name, location_id  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name =  
'Rajs');
```

36. Display first_name, last_name, the salary, the department_name, and the location_id for employees who earn more than Mourgos.

```
SELECT first_name, last_name, salary, department_name, location_id  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE salary > (SELECT salary FROM EMPL1 WHERE last_name = 'Mourgos');
```


37. Create a join between EMPL1 and DEPT1 using department_id and display all the information about employees who doesn't work in the same department as Rajs. Arrange all the employees using the last_name.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE department_id != (SELECT department_id FROM EMPL1 WHERE last_name =  
'Rajs')  
ORDER BY last_name;
```

38. Create a join between the tables EMPL1 and DEPT1 and display all the information from both tables for employees having department_id=80 or 50.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE department_id IN (80, 50);
```

39. Create a join between the tables LOC1 and DEPT1 using location_id and display all the information from both tables.

```
SELECT *  
FROM LOC1 JOIN DEPT1 USING (location_id);
```

40. Create a join between the tables EMPL1 and DEPT1 using department_id and display the first_name, last_name, department_name and location_id.

```
SELECT first_name, last_name, department_name, location_id  
FROM EMPL1 JOIN DEPT1 USING (department_id);
```

41. Create a join between the tables EMPL1, LOC1 and DEPT1 and display all the information for employees having department_id=80.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_id=80;
```

42. Create a join between EMPL1 and DEPT1 using department_id and display all the information about employees having department_name=IT.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE department_name='IT';
```

43. Display the first_name, last_name, the street, the city and the state for employees having the same department_id as Mourgos.

```
SELECT first_name, last_name, street, city, state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name =  
'Mourgos') ;
```

44. Create a cross join between the tables EMPL1 and DEPT1 and display all the information from both tables.

```
SELECT *  
FROM EMPL1 CROSS JOIN DEPT1;
```

45. Create a join between the tables EMPL1 and DEPT1 and display all the information from both tables for employees having department_id=90.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE department_id=90;
```

46. Create a join between the tables EMPL1 and DEPT1 using department_id and display all the information from both tables.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (department_id);
```

47. Create a join between the tables EMPL1 and DEPT1 using manager_id and display all the information from both tables.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (manager_id);
```

48. Create a join between the tables EMPL1 and DEPT1 and display all the information from both tables for employees having manager_id=124.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (manager_id)  
WHERE manager_id=124;
```

49. Create a join between the tables EMPL1, DEP1 and LOC1 and display all the information for employees having manager_id=124.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
WHERE manager_id=124;
```

50. Create a join between EMPL1 and DEPT1 using department_id, and display first_name, last_name, hire_date, department_name and department_id.

```
SELECT first_name, last_name, hire_date, department_name, department_id  
FROM EMPL1 JOIN DEPT1 USING (department_id);
```

51. Create a join between EMPL1 and DEPT1 using department_id, and display first_name, last_name, salary, hire_date, department_name and department_id for all employees departments 80 or 50.

```
SELECT first_name, last_name, salary, hire_date, department_name, department_id  
FROM EMPL1 JOIN DEPT1 USING (department_id)  
WHERE department_id IN (80, 50);
```

52. Join the LOC1 and DEPT1 table using the location_id column. Display all the information.

```
SELECT *  
FROM DEPT1 JOIN LOC1 USING (location_id);
```

53. Join the LOC1 and DEPT1 table using the location_id column. Limit the results to locations 1400 and 1700.

```
SELECT *  
FROM DEPT1 JOIN LOC1 USING (location_id)  
WHERE location_id BETWEEN 1400 AND 1700;
```

54. Create a join between the tables EMPL1, DEPT1 and LOC1 and display first_name, last_name, salary, department_name, street, city from employees hired after 01.01.1999.

```
SELECT first_name, last_name, salary, department_name, street, city  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
WHERE hire_date > '01-JAN-1999';
```

55. Create a join between the tables EMPL1, DEPT1 and LOC1 and display first_name, last_name, salary, department_name, street, city from employees having department_id=80.

```
SELECT first_name, last_name, salary, department_name, street, city  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_id=80;
```

56. Create a join between the tables EMPL1, DEPT1 and LOC1 and display first_name, last_name, salary, department_name, street, city from employees having manager_id=124.

```
SELECT first_name, last_name, salary, department_name, street, city  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
WHERE manager_id=124;
```

57. Display the first_name, the last_name and the salary for the last hired.

```
SELECT first_name, last_name, salary  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
ORDER BY hire_date DESC;
```

58. Display the first_name, the last_name, the hire_date, the department_name, and the location_id for the last hired.

```
SELECT first_name, last_name, hire_date, department_name, location_id  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
ORDER BY hire_date DESC;
```

59. Display the first_name, the last_name and the salary for employees having who earn less than the average of salaries for employees having department_id=50.

```
SELECT first_name, last_name, salary  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
WHERE salary < (SELECT AVG(salary) FROM EMPL1 WHERE department_id=50);
```

60. Display the first_name, the last_name, the salary, the department_name, and the location_id for employees having who earn less than the average of salaries for employees having department_id=50.

```
SELECT first_name, last_name, salary, department_name, location_id  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
WHERE salary < (SELECT AVG(salary) FROM EMPL1 WHERE department_id=50);
```

61. Display the first_name and the last_name in a single column for employees working in IT department.

```
SELECT first_name || ' ' || last_name  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
WHERE department_name='IT';
```

62. Display the first_name, the last_name in a single column, the salary, the department_name, the location_id, and the city for employees working in IT department.

```
SELECT first_name || ' ' || last_name, salary, department_name, location_id, city  
FROM EMPL1 JOIN DEPT1 USING (manager_id) JOIN LOC1 USING (location_id)  
WHERE department_name='IT';
```

63. Increase the salary of employees having department_id=50 by 200 euros and display the old salary, the last_name, the new salary, and the department_name.

```
SELECT salary, last_name, salary + 200, department_name  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_id=50;
```

64. Arrange in descending order according to last_name and display the last_name, the salary, the department_name, and the city for employees having department_id=80 and salary >6500.

```
SELECT last_name, salary, department_name, city  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_id=80 AND salary >6500  
ORDER BY last_name DESC;
```

65. Increase the salary by 5% and display the first_name, the last_name, the old salary, the new salary, and the department_name

```
SELECT first_name, last_name, salary, salary+salary*0.05, department_name  
FROM EMPL1 JOIN DEPT1 USING (department_id);
```

66. Display the last_name, the department_name, and the city for the last in the alphabetic list of names name for department_id=50.

```
SELECT last_name, department_name, city  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_id=50  
ORDER BY last_name;
```

67. Display the last_name, the salary, the department_name, the city, the street, the postal_code, and the state for employees havind the salary greater than the average of salaries.

```
SELECT last_name, salary, department_name, city, street, postal_code, state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE salary > (SELECT AVG(salary) FROM EMPL1);
```

68. Display the last_name, the hire_date, the department_name, and the location_id for employees hired before Rajs.

```
SELECT last_name, hire_date, department_name, location_id
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE hire_date > (SELECT hire_date FROM EMPL1 WHERE last_name = 'Rajs');
```

69. Display the last_name, the salary, the department_name, the location_id, the street, and the city for employees hired before Rajs.

```
SELECT last_name, salary, department_name, location_id, street, city
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE hire_date > (SELECT hire_date FROM EMPL1 WHERE last_name = 'Rajs');
```

70. Display the last_name, the salary, and the department_name for employees who earn less than the average salaries for all the employees having department_id=50 or 80.

```
SELECT last_name, salary, department_name
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE salary < (SELECT AVG(salary) FROM EMPL1 WHERE department_id IN (80, 50));
```

71. Display the last_name, the salary, the department_name, the city and the postal_code for employees who earn less than the average salaries for all the employees having department_id=50 or 80.

```
SELECT last_name, salary, department_name, city, postal_code
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE salary < (SELECT AVG(salary) FROM EMPL1 WHERE department_id IN (80, 50));
```

72. Display first_name, last_name, and the salary from employees who earn more than the minimum salaries for employees hired after Vargas.

```
SELECT first_name, last_name, salary
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE salary > (SELECT MIN(salary) FROM EMPL1 WHERE last_name = 'Vargas');
```

73. Display the last_name, the salary, the department_name and the location_id for employees hired before Vargas.

```
SELECT last_name, salary, department_name, location_id
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE hire_date < (SELECT hire_date FROM EMPL1 WHERE last_name = 'Vargas');
```

74. Display the last_name, the salary, the department_name, the location_id, the city and the street for employees hired after Vargas.

```
SELECT last_name, salary, department_name, location_id, city, street
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE hire_date > (SELECT hire_date FROM EMPL1 WHERE last_name = 'Vargas');
```

75. Display the first_name, the last_name, and the salary for employees who earn less than Hunold.

```
SELECT first_name, last_name, salary
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE salary < (SELECT salary FROM EMPL1 WHERE last_name = 'Hunold');
```

76. Display the first_name, the last_name, the salary, the department_name, the location_id, the city, and the street for employees having the same department_id as Matos.

```
SELECT first_name, last_name, salary, department_name, location_id, city, street
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name = 'Matos');
```

77. Display the department_name, the location_id, the city, the street, the postal_code, and the state for employees having the same department_id as Matos.

```
SELECT department_name, location_id, city, street, postal_code, state
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name = 'Matos');
```

78. Display the last_name, the salary, and the department_name for all those employees who earn more than Matos and having the same department_name as Mourgos.

```
SELECT last_name, salary, department_name
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)
WHERE department_name = (SELECT department_name FROM EMPL1 WHERE last_name = 'Mourgos' AND salary > (SELECT salary FROM EMPL1 JOIN DEPT1 USING (department_id) WHERE last_name = 'Matos '));
```

79. Display the first_name, the last_name, the salary, the department_name, the location_id, the city, and the street for all those employees who have the same department_id as Rajs and were hired before Zlotkey.

```
SELECT first_name, last_name, salary, department_name, location_id, city, street  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_id = (SELECT department_id FROM EMPL1 WHERE last_name =  
'Rajs ' AND hire_date < (SELECT hire_date FROM EMPL1 WHERE last_name = 'Zlotkey '));
```

80. Arrange all the employees having the same department_name as Zlotkey using salary, and display the last_name, the salary, the department_id, and the department_name.

```
SELECT last_name, salary, department_id, department_name  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
ORDER BY department_name;
```

81. Display the last_name, the salary, the department_name, the location_id, the city, and the state for all the employees having the same department_name as Zlotkey.

```
SELECT last_name, salary, department_name, location_id, city, state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_name = (SELECT department_name FROM EMPL1 WHERE  
last_name = 'Zlotkey');
```

82. Increase the salary by 500 and display the last_name, the salary, the old salary, the new salary, the hire_date, the department_name, the city, the street, the postal_code, and the state for employees hired after Zlotkey.

```
SELECT last_name, salary, salary + 500, hire_date, department_name, city, street,  
postal_code, state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE hire_date > (SELECT hire_date FROM EMPL1 WHERE last_name = 'Zlotkey');
```

83. Display the last_name, the salary, the department_id, and the department_name for employees who earn more than the minimum salaries for employees having department_id=50 or 80.

```
SELECT last_name, salary, department_id, department_name  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE salary > (SELECT MIN(salary) FROM EMPL1 WHERE department_id IN (50, 80));
```


84. Display the last_name, the salary, the department_id, the department_name, the location_id, the city, and the postal code for employees who earn more than the maximum salaries for all the employees having department_id=50.

```
SELECT last_name, salary, department_id, department_name, location_id, city,  
postal_code  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE salary > (SELECT MAX(salary) FROM EMPL1 WHERE department_id=50);
```

85. Display the last_name, the salary, the department_id, the department_name, the city, and the state from employees who earn more than the minimum salaries for employees hired after Rajs.

```
SELECT last_name, salary, department_name, city, state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE salary > (SELECT MIN(salary) FROM EMPL1 WHERE hire_date > (SELECT  
hire_date FROM EMPL1 WHERE last_name = 'Rajs'));
```

86. Display the first_name, the last_name, the salary, the department_name, and the department_id for employees hired before Taylor.

```
SELECT first_name, last_name, salary, department_name, department_id  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE hire_date < (SELECT hire_date FROM EMPL1 WHERE last_name = 'Taylor');
```

87. Display the last_name, the salary, the department_name, the department_id, the city, the street, the postal_code, and the state for employees having last_name starting with „M” or “T”.

```
SELECT last_name, salary, department_name, department_id, city, street, postal_code,  
state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE last_name LIKE 'M%' OR last_name LIKE 'T%';
```

88. Display last_name with capital letter and the salary in one column for employees having department_id =50 or 60. The format must be “RAJS earns 6945.23”.

```
SELECT UPPER(last_name) || ' earns ' || salary  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_id in (50, 60)
```

89. Display the last_name , the department_id in one column from employees who earn more than the minimum salaries for employees hired after Davies. The format must be “Matos works in department_id=50”.

```
SELECT last_name || ' works in department_id=' || department_id  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE salary > (SELECT MIN(salary) FROM EMPL1 WHERE hire_date > (SELECT  
hire_date FROM EMPL1 WHERE last_name = 'Davies'));
```

90. Display the first_name, the last_name, the salary, the department_name, the city, and the state for employees who earns more than the maximum salaries for all the employees having department_id=60.

```
SELECT first_name, last_name, salary, department_name, city, state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE salary > (SELECT MAX(salary) FROM EMPL1 WHERE department_id=60);
```

91. Display the first_name, the last_name, the salary, the department_name, the city, the street, the postal_code, and the state for employees who earns more than Rajs.

```
SELECT first_name, last_name, salary, department_name, city, street, postal_code,  
state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE salary > (SELECT salary FROM EMPL1 WHERE last_name = 'Rajs');
```

92. Display the last_name, the salary, the department_name, the city, and the postal_code for employees having department_name=IT

```
SELECT last_name, salary, department_name, city, postal_code  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE department_name='IT';
```

93. Display the last_name, the department_name, the city, the postal_code, and the state for employees having location_id=1500.

```
SELECT last_name, department_name, city, postal_code, state  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE location_id=1500;
```

94. Create a join between the tables LOC1 and DEPT1 using location_id and display all the information from both tables for location_id=1700 or 1500.

```
SELECT *  
FROM EMPL1 JOIN DEPT1 USING (department_id) JOIN LOC1 USING (location_id)  
WHERE location_id in (1500, 1700);
```