



M18.3 Solution Guide - Splunk Statistics

In this activity, you were tasked with creating several statistical reports and creating a new field for a specific use case.

1. Using the same Fortinet log file from the last activity, design SPL queries to display the following statistical reports.
 - Top 20 destination IP addresses:
 - Select `dest_ip`, then Top values.
 - SPL query:
 - `source="fortinet_IPS_logs.csv" | top limit=20 dest_ip`
 - Top 10 source IP addresses (with count and percent):
 - Select `src_ip`, then Top values.
 - Change the top limit from 20 to 10.
 - SPL query:
 - `source="fortinet_IPS_logs.csv" | top limit=10 src_ip`
 - Top 10 source IP addresses/source port combination (with count and percent):
 - Using the previous SPL query, add the source port to the search.
 - SPL query:
 - `source="fortinet_IPS_logs.csv" | top limit=10 src_ip, src_port`
2. Using `eval`, create a field called `DB_Type` to help identify a sensitive database (12.130.60.5) that contains customer data:
 - `source="fortinet_IPS_logs.csv" | eval DB_type = if(dest_ip == "12.130.60.5", "Customer DB", "Non-Customer DB")`
3. Display the results of this field in a statistical report:
 - `source="fortinet_IPS_logs.csv" | eval DB_type = if(dest_ip == "12.130.60.5", "Customer DB", "Non-Customer DB") | top limit=20 DB_type`