



Solution Guide: find Your Way

- The first step is to navigate into the `/03-student/day2/finding_your_way/PeanutButtery.net/` folder on your virtual machine. To complete this step, run the following command:
 - `cd /03-student/day2/finding_your_way/PeanutButtery.net/`
- The next step is to find all directories that have the word "secret" in their name. To do this, run:
 - `find -type d -iname *secret*`
 - Note the syntax:
 - `find` is the command-line command.
 - `-type` is the option for specifying whether you're searching for a file or a directory/
 - `d` is the required parameter for the `-type` option, indicating that you're searching for a directory.
 - `-iname` is the option indicating that you're searching for a specific case-insensitive value.
 - `*secret*` is the parameter indicating the value you're searching for. The two wildcards indicate that the value `secret` can be located anywhere in the file name.
- When you run the command, the results should return the following directory path, containing the value of `secret`: `./other/disregard/candysecretrecipes`.
 - This means the directory `candysecretrecipes` is within the `disregard` directory, within the `other` directory.
- Next, we need to find the files that contain the word "recipe." The command is:
 - `find -type f -iname *recipe*`
 - Note the syntax:
 - `find` is the command-line command.
 - `-type` is the option for specifying whether you're searching for a file or directory.
 - `f` is the required parameter for the `-type` option, indicating that you're searching for a file.
 - `-iname` is the option indicating that you're searching for a specific case-insensitive value.
 - `*recipe*` is the parameter specifying the value you're searching for. The two wildcards indicate that the value `recipe` can be located anywhere in the file name.

- The results of the command should return the following four files that have the value of `recipe` in the name:
 - `./other/disregard/candysecretrecipes/recipe_crunchybars`
 - `./other/disregard/candysecretrecipes/recipe_peanutballs`
 - `./other/disregard/candysecretrecipes/recipe_peanutsquares`
 - `./other/disregard/candysecretrecipes/recipe_yumbars`
- The four files are `recipe_yumbars`, `recipe_peanutsquares`, `recipe_peanutballs`, and `recipe_crunchybars`.

Bonus

You are asked to find files containing the words "recipe" and "peanut" in the name.

- To do this, use a conditional of `-a` to add an additional search. The command is as follows:
 - `find -type f -iname *recipe* -a -iname *peanut*`
 - Note the syntax:
 - `find` is the command-line command.
 - `-type` is the option for specifying whether you're searching for a file or directory.
 - `f` is the required parameter for the `-type` option, indicating that you're searching for a file.
 - `-iname` is the option indicating that you're searching for a specific case-insensitive value.
 - `*recipe*` is the parameter specifying the value you're searching for. The two wildcards indicate that the value of `recipe` can be located anywhere in the file name.
 - `-a` is the conditional statement that represents **AND**, which states that the next value must also be matched in the result.
 - `-o` can be used as an **OR** conditional, returning results that include either one of the specified values.
 - `-iname *peanut*` is the second value that needs to be found in a file name.
- When you run the command, the results show that the following two files that have the words "recipe" and "peanut" in their name:
 - `./other/disregard/candysecretrecipes/recipe_peanutballs`
 - `./other/disregard/candysecretrecipes/recipe_peanutsquares`