



Solution Guide: Sudo Wrestling

1. Print the name of your current user to the terminal.
 - Run: `whoami`
2. Determine what sudo privileges the sysadmin user has.
 - Run: `sudo -l`
3. Record in a text document inside your research folder what sudo access the users on the system have.
 - Run: `sudo -lU <username> >> ~/research/sudo_access.txt`
4. Find a user that has sudo access for the less command and complete the following:
 - Run: `sudo -lU <username>`.
 - Note: Alternatively, we can run `sudo grep less /etc/sudoers`.
 - Switch to that user by using the password you found in the previous activity.
 - Run: `sudo su max (password: welcome)`
 - Switch to that user's home directory.
 - Run: `cd ~`
 - Verify the vulnerability by dropping from less into a root shell.
 - Run `sudo less shopping_list.txt` then `!bash`.
 - Exit back to the command line.
 - Run `exit` to exit back into less. Run `q` to quit less.
 - Search this user's files for anything suspicious.
 - Run `ls -a /home/max` to reveal a copy of `.rev_shell.sh`
 - Exit that user.
 - Run: `exit`

Bonus

5. From the sysadmin user, switch to the root user.
 - Run: `sudo su`.
6. Check the sudoers file to determine if there are any users listed with sudo privileges.
 - Run: `less /etc/sudoers`
 - Note: `grep less /etc/sudoers` is a better command!
 - Note: Since we are root, we don't need sudo!
7. Edit the sudoers file so only the sysadmin user has access.

- Run `visudo` and remove user `max` from `sudo` access.
- You should remove the following line:
- `max ALL=(ALL) /usr/bin/less`

8. Check that your changes to the `sudoers` file worked.

- Run `su max` and attempt `sudo less somefile`.

Note: Remember, it's always better to use `sudo` as opposed to `su`. We use `su` here only as a demonstration.

-  Troubleshooting: If the `sudoers` file becomes damaged, it could stop you from using `sudo` at all. To troubleshoot this, follow the thread here: [Ask Ubuntu: How to modify an invalid etc sudoers file](#)