



Module 6 Day 2: Variables and If Statements

In the previous class, you created your first `bashrc` script, edited `$PATH` variables to create custom commands, and added aliases to your `~/ .bashrcrc` file.

Now, we will add variables and conditional `if` statements to our scripts.

`if` statements improve our scripts by allowing us to do the following:

- Check if a file or directory exists before we create it.
- Check what user has run the script.
- And more...

To complete this activity, you will create variables and if statements that satisfy given requirements and use them in your script.

Instructions

Consult this list of `bashrc` conditional operators while completing the activity:

- `=` : Checks if two items are `equal`.
- `!=` : Checks if two items are `not equal`.
- `-gt` : Checks if an integer is `greater than another`.
- `-lt` : Checks if an integer is `less than another`.
- `-d /path_to/directory` : Checks for the existence of a directory.
- `&&` : Both conditions have to be true to run.
- `||` : One condition has to be true to run.

Using Variables

1. Create a variable to hold the path of your output file.
 - Replace the output file path for each command with your variable.

Using If Statements

1. Create an `if` statement that checks for the existence of the `~/research` directory.
 - If the directory exists, do nothing. If the directory does not exist, create it.



Activity File

- Remove the line in your script that creates this directory.
- 2. Create an `if` statement that checks for the existence of the file `~/research/sys_info.txt`.
 - If the file does not exist, do nothing.
 - If the file does exist, remove it. (This will ensure that the script always creates a new file.)

Bonus Variables

If you have already completed the exercises above, see if you can complete the following:

1. Create a variable to hold the output of the command: `ip addr | grep inet | tail -2 | head -1`.
 - Replace this command in your script with your new variable.
2. Create a variable to hold the output of the command `find /home -type f -perm 777`.
 - Replace this command in your script with your new variable.

Bonus If Statement

1. Protect the script from root! Create an `if` statement that checks if the script was run using `sudo`.
 - If it was run with `sudo`, exit the script with a message that tells the user not to run the script using `sudo`.
-