



Solution Guide: Move and Create Directories

In this activity, you were tasked with setting up multiple directories for the Windows workstation.

1. Since we will eventually decommission the `Alex` user, move the `contracts` folder from Alex's desktop directory to `C:\`.
 - First, make sure you're working out of Alex's desktop directory:
 - Run `Set-Location C:\Users\Alex\Desktop` to change the directory.
 - This is the same as `cd` in Linux.
 - Next, move `contracts` to `C:\`:
 - Run `Move-Item contracts C:\` to move the `contracts` directory to the `C:\` directory.
 - This is the same as `mv` in Linux.
 - Verify `contracts` is no longer here:
 - Run `Get-ChildItem C:\` to get a list of the directories and files in `C:\`.
 - This is the same as `ls` in Linux.
2. Create `Backups` and `Scripts` directories in `C:\`.
 - Now, we want to work out of `C:\`.

- Run `Set-Location C:\`.
- Make the `Backups`, `Logs`, and `Scripts` directories:
 - Type `New-Item -Path "C:\" -Name "Logs" -ItemType "Directory"`, but don't run it yet.
 - When we use the `-ItemType "Directory"` parameters here, it changes the `New-Item` functionality from being like `touch` to `mkdir` in Linux.
- We can actually shorten this command a little and have it create both directories:
 - Edit the line to match the following:
 - Run `New-Item "Logs", "Backups", "Scripts" -ItemType "Directory" -Force`
 - This command will create all the directories in the current directory.
 - This is similar to using *brace expansion* with `mkdir`: `mkdir {Logs, Backups, Scripts}`.
 - The `-Force` parameter will ignore any errors if the directories already exist.

3. Check the contents of the `C:\` directory to make sure the `Logs`, `Backups`, and `Scripts` directories exist.

- Run `Get-ChildItem` to show `contracts`, `Logs`, `Backups`, and `Scripts` in `C:\`. We now have the following directories:
 - `C:\Backups`
 - `C:\Logs`
 - `C:\contracts`
 - `C:\Scripts`

Bonus

1. Use `Rename-Item` to capitalize the `contracts` directory if it is not already.
 - `Rename-Item contracts Contracts` seems like the correct option (if you recall `mv` in Bash), but the command actually errors out.
 - Instead, we use `Rename-Item` twice to change the directory name:
 - `Rename-Item contracts contracts1`
 - `Rename-Item contracts1 Contracts`
-