



Activity File: Recon-ng

- In this activity, you will continue to play the role of a pen tester conducting an engagement on MegaCorpOne.
- You are tasked with determining whether MegaCorpOne's domain server info is accessible using OSINT tools.
- You will use the Shodan API and Recon-ng to perform your tests, and then you'll summarize your findings in a report.

⚠ Reminder: Don't forget to save your findings, as you will add them to your report on Day 4!

Instructions

1. In Ubuntu, log in with the credentials `root:kali` and start Recon-ng.
 - In Recon-ng, run `modules search` to view all the currently installed modules.
 - Run `modules load recon/domains-hosts/hackertarget`.
 - This will load the `hackertarget` scanner module.
 - Modules need to be loaded before use.
2. In Recon-ng, type the command to view all the currently installed modules.
 - For this activity, we'll use the following two modules:
 - `recon/domains-hosts/hackertarget`
 - `reporting/html`
3. Type the command that will query hackertarget.com for a scan against megacorpone.com.
 - The results will automatically display verbosely in the terminal window.
4. Install the reporting module, then use the module.
 - `marketplace install reporting/html`

5. Type the command that shows which parameters need to be set.
 - The **CREATOR** and **CUSTOMER** parameters need to be set.
 - Set the parameters as follows:
 - **CREATOR**: Pentester
 - **CUSTOMER**: MegaCorpOne
 - Type the command that runs the query so the results are saved to **/root/.recon-ng/workspaces/default/results.html**.
 - Type the command that verifies whether the configuration took effect after setting the options.
6. View the report.
 - Generate the report so that it can be viewed as HTML in the web browser.
 - How many hosts did Recon-ng discover?