



Solution Guide: DNS Hijacking

To complete this activity, you created a DNS spoof record that will redirect any hacker trying to visit `acmetradesecrets.com` to a different website.

Access the DNS hosts file on a Linux server:

- On the Linux server, the hosts file is located at `/etc/hosts`.
- To get there, run `cd /etc` from the terminal.
- Run `ls` to confirm there is a file called `hosts`.

Modify the DNS hosts file to redirect the access of a website:

- Edit the file by entering `sudo nano hosts`.
- Add the following record to the bottom of the file:
`45.33.32.156 www.acmetradesecrets.org`
- Exit and save your changes by entering `Ctrl+X` and select `Y` when prompted to save the file.

Validate that the DNS spoofing works by going to `acmetradesecrets.com` and verifying that the site is redirected:

- Open a browser in your Linux host and enter www.acmetradesecrets.org.
- This should automatically redirect to the other website, which should be `scanme.nmap.org`.

Bonus

If you have a Windows machine or VM, research how to apply the same DNS spoof record on your Windows machine and do so. If you don't have access to a Windows machine, simply document the steps to create a DNS spoof record on a Windows system.

On a Windows machine:

- Edit the file using the same steps as in Linux, but find the hosts file at `C:\Windows\System32\drivers\etc`.
- Note: You must be an administrator to make this change.
- To become an administrator, right-click on the Notepad application and select Run as administrator.
- Copy and paste the whole hosts file, with your change, into the blank file.
- Save the file as Hosts in `C:\Windows\System32\drivers\etc`.
- Click OK to replace the current file.

Validate that the changes have taken place by going to www.acmetradesecrets.org in your browser in Windows.