

analyse_membres_RFRR

February 10, 2025

1 Analyse de la composition du Réseau Français pour la recherche reproductible

1.0.1 Library import

```
[27]: import seaborn as sns
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
import os
# save tables as images
from pandas.plotting import table
# save plots in true size
from matplotlib import rcParams
rcParams.update({'figure.autolayout': True})
```

1.0.2 Set style and color palette

```
[28]: # Minimalist design
sns.set_style("whitegrid")

# RFRR palette definition.
RFRR_palette = ["#35346b", "#a2dfd9", "#6943a4", "#b89ad3"]
color_codes_RFRR = ['dark_blue', 'light_blue', 'dark_purple', 'light_purple']

c = lambda x: RFRR_palette[color_codes_RFRR.index(x)]

#use example
#x=np.random.randn(100)
#g = sns.histplot(x, color=c("dark_purple"))

#plt.show()
```

1.0.3 Definition of custom functions

- Generate count and percentage dataframes

```
[29]: def count_percent(data, var, FoldPath, FileName):

#Subset a variable and compute counts and percentage and sort by counts
#data = data_members
#var = "Ville", "Région", "Statut_abrev", "Discipline"
#FoldPath='Results/'
#FileName="counts_percent_"

df=pd.DataFrame({'Count' :data.groupby(var).size()}).reset_index()
df= df.assign(Percentage = lambda x: (x['Count'] /df['Count'].sum() * 100)).
↳sort_values(by=['Count'], ascending=False)
#Save
filepath= os.path.join(FoldPath, FileName+var+".csv")
df.to_csv(filepath, sep=';', encoding='latin3', index=False, header=True)
print(df.head())
return (df)
```

- Barplots

```
[30]: def bargraphs_FR (df,var_quant, var, colour, metric, var_FR, FoldPath,↳
↳FileName):
#Barplot en français
#df = df_p (sortie de count_percent)
#var_quant= "Count" or "Percentage"
#var = "Ville", "Région", "Statut_abrev", "Discipline"
#color= "dark_purple"
#metric= "Nombre", "Pourcentage"
#var_FR= "Ville", "Région", "Statut_abrev", "Discipline"
#FoldPath='Results/Plots/'
#FileName="counts_" or "percentage"
bar=sns.barplot(data=df_p, x=var_quant, y=var, color=c(colour),↳
↳legend=False)
plt.xlabel(metric+" de membres par "+var_FR)
plt.ylabel(var_FR)
plt.title("Distribution des membres par "+var_FR)
#Save
filepath= os.path.join(FoldPath, FileName+var+"_FR.png")
bar.figure.savefig(filepath)
plt.show()
return(bar)
```

```
[31]: #Anglais
def bargraphs_EN (df,var_quant, var, colour, metric, var_EN, FoldPath,↳
↳FileName):
#Barplot en anglais
#df = df_p (sortie de count_percent)
#var_quant= "Count" or "Percentage"
```

```

#var = "Ville", "Région", "Statut_abrev", "Discipline"
#color= "dark_purple"
#metric= "Number", "Percentage"
#var_EN="City", "Region", "Discipline", "type of position"
#FoldPath='Results/Plots/'
#FileName="counts_" or "percentage"
    bar=sns.barplot(data=df_p, x=var_quant, y=var, color=c(colour),
↳legend=False)
    plt.xlabel(metric+" of members by "+var_EN)
    plt.ylabel(var_EN)
    plt.title("Distribution of members by "+var_EN)
    #Save
    filepath= os.path.join(FoldPath, FileName+var+"_EN.png")
    bar.figure.savefig(filepath)
    plt.show()
    return(bar)

```

- Save tables as images

```

[32]: def table_to_image (data, var, FoldPath, FileName) :

    ax = plt.subplot(111, frame_on=False) # no visible frame
    ax.xaxis.set_visible(False) # hide the x axis
    ax.yaxis.set_visible(False) # hide the y axis
    table=pd.plotting.table(ax, data, loc='center',
        cellLoc='center', colWidths=list([.2, .2]))
    filepath= os.path.join(FoldPath, FileName+var+".png")

    plt.savefig(filepath)
    plt.show()
    return(table)

```

1.1 Data import and summaries

1.1.1 Read data

```

[33]: data_members = pd.read_csv('Data/membres_anonyme.csv', sep="\t", header=0,
↳encoding = "latin3")
print(data_members.shape)
data_members.columns

```

(104, 7)

```

[33]: Index(['Ville', 'Département', 'Région', 'Statut', 'Statut_abrev',
'Discipline', 'Discipline secondaire'],
dtype='object')

```

```

[34]: data_members.head()

```

```
[34]:
```

	Ville	Département	Région \
0	Annecy	Haute-Savoie	Auvergne-Rhône-Alpes
1	Aubervilliers	Seine-Saint-Denis	Île-de-France
2	Aubière	Puy-de-Dôme	Auvergne-Rhône-Alpes
3	Aubière	Puy-de-Dôme	Auvergne-Rhône-Alpes
4	Aubière	Puy-de-Dôme	Auvergne-Rhône-Alpes

	Statut	Statut_abrev	Discipline \
0	Ingénieur de Recherche	IR	Physique
1	Ingénieur d'Études	IE	Géographie
2	Professeur des Universités	PU	Informatique
3	Doctorant	Doctorant	Informatique
4	Doctorant	Doctorant	Informatique

	Discipline secondaire
0	Data Science
1	NaN
2	Simulations stochastiques pour la Physique
3	Machine Learning
4	Reproductibilité

1.1.2 Statistical summary of the data:

All variables are categorical

```
[35]: data_members.describe()
```

```
[35]:
```

	Ville	Département	Région	Statut \
count	104	104	104	104
unique	34	30	15	21
top	Paris	Paris	Île-de-France	Ingénieur de Recherche
freq	19	19	31	31

	Statut_abrev	Discipline	Discipline secondaire
count	104	104	73
unique	14	23	66
top	IR	Informatique	Science ouverte
freq	43	23	3

Summary tables pour les villes, les status et la discipline

```
[36]: #Check variable names
print(data_members.columns)

# Save Ville summary
ville = data_members['Ville'].describe()

ax = plt.subplot(111, frame_on=False) # no visible frame
```

```

ax.xaxis.set_visible(False) # hide the x axis
ax.yaxis.set_visible(False) # hide the y axis
table=pd.plotting.table(ax, ville, loc='center',
                        cellLoc='center', colWidths=list([.2, .2]))

plt.savefig('Results/Tables/table_summary_ville_FR.png')
plt.show()

# Save Région summary
region = data_members['Région'].describe()

ax = plt.subplot(111, frame_on=False) # no visible frame
ax.xaxis.set_visible(False) # hide the x axis
ax.yaxis.set_visible(False) # hide the y axis
table=pd.plotting.table(ax, region, loc='center',
                        cellLoc='center', colWidths=list([.2, .2]))
plt.savefig('Results/Tables/table_summary_region_FR.png')
plt.show()

# Save Statut summary
statut = data_members['Statut_abrev'].describe()

ax = plt.subplot(111, frame_on=False) # no visible frame
ax.xaxis.set_visible(False) # hide the x axis
ax.yaxis.set_visible(False) # hide the y axis
table=pd.plotting.table(ax, statut, loc='center',
                        cellLoc='center', colWidths=list([.2, .2]))
plt.savefig('Results/Tables/table_summary_statut_FR.png')
plt.show()

# Save Discipline summary
discipline = data_members['Discipline'].describe()

ax = plt.subplot(111, frame_on=False) # no visible frame
ax.xaxis.set_visible(False) # hide the x axis
ax.yaxis.set_visible(False) # hide the y axis
table=pd.plotting.table(ax, discipline, loc='center',
                        cellLoc='center', colWidths=list([.2, .2]))

plt.savefig('Results/Tables/table_summary_discipline_FR.png')
plt.show()

Index(['Ville', 'Département', 'Région', 'Statut', 'Statut_abrev',
      'Discipline', 'Discipline secondaire'],
      dtype='object')

```

	Ville
count	104
unique	34
top	Paris
freq	19

	Région
count	104
unique	15
top	Île-de-France
freq	31

	Statut_abrev
count	104
unique	14
top	IR
freq	43

	Discipline
count	104
unique	23
top	Informatique
freq	23

Membres par région et par discipline


```
[37]: df=pd.DataFrame({'Count':data_members.groupby(["Région", "Discipline"]).
    ↳size()}).reset_index()

df.head()

df_heat = df.pivot(index="Discipline", columns="Région", values="Count")
plt.figure(figsize=(8, 8))
sns.heatmap(df_heat, linewidths=0.05, linecolor="lightgrey", square=True).
    ↳get_figure().savefig(('Results/Plots//heatmap_region_discipline_FR.png'))

#plt.yticks(rotation=15)

df.to_csv('Results/members_region_discipline.csv', sep=';', encoding='latin3',
    ↳index=False, header=True)
```



1.2 Network composition analysis


1.2.1 Disciplines


```
[38]: df_p=count_percent(data_members, "Discipline", "Results/", "counts_percent_")
```

	Discipline	Count	Percentage
8	Informatique	23	22.115385
0	Bioinformatique	11	10.576923
15	Physique	9	8.653846
1	Biologie	8	7.692308
2	Biostatistique	7	6.730769

Barplots du nombre de membres par discipline


```
[39]: #Français
barp= bargraphs_FR (df_p,"Count", "Discipline",
↪ "dark_purple", "Nombre", 'Discipline', 'Results/Plots/', "counts_")
#Anglais
barpEN= bargraphs_EN(df_p,"Count", "Discipline",
↪ "dark_purple", "Number", 'Discipline', 'Results/Plots/', "counts_")
```






Barplots de pourcentages

```
[40]: #Français
barp= bargraphs_FR (df_p,"Percentage", "Discipline",
↳"dark_purple","Pourcentage", 'Discipline', 'Results/Plots/',"percentage_")
#Anglais
barpEN= bargraphs_EN(df_p,"Percentage", "Discipline",
↳"dark_purple","Percentage", 'Discipline', 'Results/Plots/',"percentage_")
```





```
[41]: data_members.columns

df=pd.DataFrame(data_members['Discipline'].value_counts(normalize=False))
#df['Discipline']=df.index
ax = plt.subplot(111, frame_on=False) # no visible frame
ax.xaxis.set_visible(False) # hide the x axis
ax.yaxis.set_visible(False) # hide the y axis
table=pd.plotting.table(ax, df, loc='center',
                        cellLoc='center', colWidths=list([.2, .2]))

plt.savefig('Results/Tables/table_counts_discipline_FR.png')
plt.show()
print(df.head())
print(df.shape)

print(df.dtypes)
df.head()
```

	count
Informatique	23
Bioinformatique	11
Physique	9
Biologie	8
Mathématiques	7
Biostatistique	7
Statistique	5
Ingénierie	5
Neurosciences	5
Science Ouverte	5
Information	5
Géographie	3
Médicament	1
Epidemiologie	1
Médecine	1
Politique	1
Économie	1
Données	1
Histoire des Sciences	1
Psychologie	1
Sociologie	1
Écologie	1
Neurosciences	1

```

count
Discipline
Informatique      23
Bioinformatique   11
Physique          9
Biologie          8
Mathématiques     7
(23, 1)
count    int64
dtype: object

```

```

[41]:
count
Discipline
Informatique      23
Bioinformatique   11
Physique          9
Biologie          8
Mathématiques     7

```


1.2.2 Membres par statut professionnel


```
[42]: df_p=count_percent(data_members, "Statut_abrev", "Results/", "counts_percent_")  
# Save tables as images  
#table_to_image (data, var, FoldPath, FileName)
```

	Statut_abrev	Count	Percentage
10	IR	43	41.346154
4	CR	15	14.423077
9	IE	14	13.461538
12	PU	8	7.692308
11	MdC	7	6.730769

Barplots du nombre de membres par statut


```
[43]: #Français  
barp= bargraphs_FR (df_p,"Count", "Statut_abrev", "dark_purple","Nombre",  
↳'Statut', 'Results/Plots/', "counts_")  
#Anglais  
barpEN= bargraphs_EN(df_p,"Count", "Statut_abrev",  
↳"dark_purple", "Number", 'Position', 'Results/Plots/', "counts_")
```






Barplots de pourcentages

```
[44]: #Français
barp= bargraphs_FR (df_p,"Percentage", "Statut_abrev",□
↳"dark_purple","Pourcentage",'Statut','Results/Plots/',"percentage_")
#Anglais
barpEN= bargraphs_EN(df_p,"Percentage", "Statut_abrev",□
↳"dark_purple","Percentage",'Position','Results/Plots/',"percentage_")
```





```
[45]: data_members.columns

df=pd.DataFrame(data_members['Statut_abrev'].value_counts(normalize=False))
#rounded_df = df.round(decimals=2)

ax = plt.subplot(111, frame_on=False) # no visible frame
ax.xaxis.set_visible(False) # hide the x axis
ax.yaxis.set_visible(False) # hide the y axis
table=pd.plotting.table(ax, df, loc='center',
                        cellLoc='center', colWidths=list([.2, .2]))
plt.savefig('Results/Tables/table_counts_statut_FR.png')
plt.show()
print(df.head())
print(df.shape)

print(df.dtypes)
df.head()
```

	count
IR	43
CR	15
IE	14
PU	8
MdC	7
Doctorant	3
DR	3
CP	3
Postdoc	2
Data	2
ATER	1
CM	1
BS	1
Directeur	1

```

count
Statut_abrev
IR          43
CR          15
IE          14
PU           8
MdC         7
(14, 1)
count      int64
dtype: object

```

```

[45]:
count
Statut_abrev
IR          43
CR          15
IE          14
PU           8
MdC         7

```


1.2.3 Distribution spatiale du réseaux: Presence sur des villes


```
[46]: df_p=count_percent(data_members, "Ville", "Results/", "counts_percent_")
```

	Ville	Count	Percentage
22	Paris	19	18.269231
13	Lyon	14	13.461538
8	Grenoble	10	9.615385
32	Toulouse	6	5.769231
15	Montpellier	5	4.807692

Barplots du nombre de membres par ville


```
[47]: #Français
barp= bargraphs_FR (df_p,"Count", "Ville", "dark_purple","Nombre", 'Ville',
↳'Results/Plots/', "counts_")
#Anglais
barpEN= bargraphs_EN(df_p,"Count", "Ville", "dark_purple","Number",'City',
↳'Results/Plots/', "counts_")
```






Barplots de pourcentages

```
[48]: #Français
barp= bargraphs_FR (df_p,"Percentage", "Ville", "dark_purple","Pourcentage",
↳'Ville', 'Results/Plots/','percentage_')
#Anglais
barpEN= bargraphs_EN(df_p,"Percentage", "Ville",
↳"dark_purple","Percentage",'City', 'Results/Plots/','percentage_')
```






1.2.4 Distribution spatiale du réseaux: Presence sur les régions


```
[49]: df_p=count_percent(data_members, "Région", "Results/", "counts_percent_")
```

	Région	Count	Percentage
14	Île-de-France	31	29.807692
0	Auvergne-Rhône-Alpes	29	27.884615
9	Occitanie	13	12.500000
1	Bretagne	5	4.807692
8	Nouvelle-Aquitaine	5	4.807692

Barplots du nombre de membres par ville


```
[50]: #Français
barp= bargraphs_FR (df_p,"Count", "Région", "dark_purple","Nombre", 'Région',
↳ 'Results/Plots/', "counts_")
#Anglais
barpEN= bargraphs_EN(df_p,"Count", "Région", "dark_purple","Number", 'Region',
↳ 'Results/Plots/', "counts_")
```







Barplots de pourcentages

```
[51]: #Français
barp= bargraphs_FR (df_p,"Percentage", "Région", "dark_purple","Pourcentage",
↳"Région", 'Results/Plots/', "percentage_")
#Anglais
barpEN= bargraphs_EN(df_p,"Percentage", "Région",
↳"dark_purple", "Percentage", 'Region', 'Results/Plots/', "percentage_")
```





1.2.5 Distribution par ville et region

```
[52]: df=pd.DataFrame({'Count':data_members.groupby(["R  gion", "Ville"]).size()}).
      ↪reset_index()

df.head()

df_heat = df.pivot(index="Ville", columns="R  gion", values="Count")
plt.figure(figsize=(8, 8))
ht = sns.heatmap(df_heat, linewidths=0.05, linecolor="lightgrey", square=True).
      ↪get_figure().savefig('Results/Plots//heatmap_region_ville_FR.png')
plt.show(ht)
#plt.yticks(rotation=15)
```

