Chapter 17

 A Linked List is a dynamically allocated data structure that is linked together in memory

- A Linked List is a dynamically allocated data structure that is linked together in memory
- Linked lists have some advantages over an array or vector

- A Linked List is a dynamically allocated data structure that is linked together in memory
- Linked lists have some advantages over an array or vector
 - They can grow and shrink as needed

- A Linked List is a dynamically allocated data structure that is linked together in memory
- Linked lists have some advantages over an array or vector
 - They can grow and shrink as needed
 - The maximum size does not need to be known


- A Linked List is a dynamically allocated data structure that is linked together in memory
- Linked lists have some advantages over an array or vector
 - They can grow and shrink as needed
 - The maximum size does not need to be known
 - Speed of insertion
 - Inserting into the middle of a populated vector is time consuming


A Linked List consists of many nodes


A Linked List consists of many nodes


- A Linked List consists of many nodes
- Each node contains one or more members that hold data and a pointer to another node


- A Linked List consists of many nodes
- Each node contains one or more members that hold data and a pointer to another node













 A pointer to the first node in a non empty Linked List is called the 'head'



- A pointer to the first node in a non empty Linked List is called the 'head'
- All other nodes can be accessed through the head via iteration

- A pointer to the first node in a non empty Linked List is called the 'head'
- All other nodes can be accessed through the head via iteration
- Each node points to the 'next' node in the list
 - The 'head' node points to node 2 which points to node 3 which points to

- A pointer to the first node in a non empty Linked List is called the 'head'
- All other nodes can be accessed through the head via iteration
- Each node points to the 'next' node in the list
 - The 'head' node points to node 2 which points to node 3 which points to
 - The last node in the list will point to NULL



head

 A Linked List is created by placing all new nodes into the list in one of three locations

- A Linked List is created by placing all new nodes into the list in one of three locations
 - At the head of the list

- A Linked List is created by placing all new nodes into the list in one of three locations
 - At the head of the list
 - In between two existing nodes

- A Linked List is created by placing all new nodes into the list in one of three locations
 - At the head of the list
 - In between two existing nodes
 - At the end, or tail, of the list

- A Linked List is created by placing all new nodes into the list in one of three locations
 - At the head of the list
 - In between two existing nodes
 - At the end, or tail, of the list
- The choice of where to put the node depends on the structure
 - First In First Out (FIFO)
 - First In Last Out (FILO)

To traverse a Linked List:

- To traverse a Linked List:
 - Create a node pointer and set it to the head node

- To traverse a Linked List:
 - Create a node pointer and set it to the head node
 - while the node you are looking at is not the node you wanted AND the node is NOT NULL
 - set node to node's next pointer

Linked List Operations

A Linked List has a set of standard operations

Linked List Operations

- A Linked List has a set of standard operations
 - Adding
 - removing
 - traversing
 - destroying


 There are three cases for adding a node to a linked list

- There are three cases for adding a node to a linked list
 - At the head
 - At the tail
 - Between two nodes


- There are three cases for adding a node to a linked list
 - At the head
 - At the tail
 - Between two nodes
 - Care must be taken not to lose access to nodes when performing this operation

Adding at the head


Adding at the head




- Adding at the head
 - Set the new node's next equal to the head node




- Adding at the head
 - Set the new node's next equal to the head node
 - Set the head pointer to the new node




Adding a node between two nodes




- Adding a node between two nodes
 - Iterate to the first node (node that will point to the new node)




- Adding a node between two nodes
 - Iterate to the first node (node that will point to the new node)
 - Set the new node's next to the iterator nodes next




- Adding a node between two nodes
 - Iterate to the first node (node that will point to the new node)
 - Set the new node's next to the iterator nodes next
 Set the iterator's next to the new node



 How might we add a node at the head of the list?



 How might we add a node at the tail of the list?



 Deleting a node in a Linked List is very similar to adding

 How might we delete a node at the head of the list?



- How might we delete a node at the head of the list?
 - What if it is the only node in the list?



 How might we delete a node at the tail of the list?



 How might we delete a node that lies between two nodes?

Destroying a Linked List can be tricky

- Destroying a Linked List can be tricky
 - All nodes must be deleted without cutting off access to another node

- Destroying a Linked List can be tricky
 - All nodes must be deleted without cutting off access to another node
 - If the nodes contain pointers, then that data must also be cleaned up

 How might we clean up a Linked List such as this?



Linked List Template

 It is also possible to use templates in the Linked List implementation

Linked List Template

- It is also possible to use templates in the Linked List implementation
 - This is done just like a normal template class

Linked List Template

```
template<class T>
class LinkedListNode
     public:
     private
          T m_data;
           LinkedListNode* m pNext;
```

 Recursion is a power tool, especially for Linked List functions

- Recursion is a power tool, especially for Linked List functions
- Most of the operations described before can be implemented using recursion

 How might we implement a 'size' function for determining the number of elements in the Linked List?

 How might we implement a 'size' function for determining the number of elements in the Linked List?

```
int size(LinkedListNode* pNode){
    if (pNode == NULL)
        return 0;
    else
        return 1 + size(pNode->getNext());
}
```

 How might we implement a 'insert' function for adding a node to the list?

 How might we implement a 'remove' function for adding a node to the list?

 How might we destruct our list using recursion?

 So far, the Linked List implementation has been a 'singly linked list'

- So far, the Linked List implementation has been a 'singly linked list'
 - This means that each node has a single pointer that points to the next node in the list

- So far, the Linked List implementation has been a 'singly linked list'
 - This means that each node has a single pointer that points to the next node in the list
- There are other variations of a Linked List

A 'doubly Linked List'

- A 'doubly Linked List'
 - Each node contains a pointer to the next node in the list

- A 'doubly Linked List'
 - Each node contains a pointer to the next node in the list
 - Each node also contains a pointer to the previous node in the list

A 'circular Linked List'

- A 'circular Linked List'
 - The same as a singly linked list, except the last node points to the first node

- A 'circular Linked List'
 - The same as a singly linked list, except the last node points to the first node

 What problems might this cause on our function definitions, iterations, ...?