# INFO8006 Introduction to Artificial Intelligence

Exercise session 7: Making decisions and reinforcement learning

## Recap

### Making decisions

*Markov decision processes.* A *Markov decision process* (MDP) is a tuple $(\mathcal{S}, \mathcal{A}, P, R)$ of *states* $s \in \mathcal{S}$, *actions* $a \in \mathcal{A}$, a *transition model* $P(s' \mid s, a)$ and a *reward function* $R(s)$, with a *discount factor* $0 < \gamma \leq 1$.

*Utilities and policies.* A *policy* $\pi : \mathcal{S} \to \mathcal{A}$ has the expected utility

$$V^\pi(s) = \mathbb{E}\left[\sum_{t \geq 0} \gamma^t R(s_t) \mid s_0 = s, \pi\right].$$

The *optimal policy* $\pi^*$ maximizes it, the *value* of a state is $V(s) = V^{\pi^*}(s)$, and $\pi^*(s) = \arg\max_a \sum_{s'} P(s' \mid s, a) V(s')$.

*Bellman equation.*

$$V(s) = R(s) + \gamma \max_a \sum_{s'} P(s' \mid s, a) V(s'),$$

or, with rewards on transitions, $V(s) = \max_a \sum_{s'} P(s' \mid s, a)[R(s, a, s') + \gamma V(s')]$.

*Value iteration.* From $V_0$, repeat the *Bellman update*

$$V_{i+1}(s) = R(s) + \gamma \max_a \sum_{s'} P(s' \mid s, a) V_i(s')$$

until convergence, guaranteed for $\gamma < 1$, and for $\gamma = 1$ when every policy reaches a terminal state.

*Policy iteration.* Alternate *policy evaluation*, solving $V_i(s) = R(s) + \gamma \sum_{s'} P(s' \mid s, \pi_i(s)) V_i(s')$, and *policy improvement*, $\pi_{i+1}(s) = \arg\max_a \sum_{s'} P(s' \mid s, a) V_i(s')$. *Modified policy iteration* replaces the evaluation by a few updates $V_{i+1}(s) = R(s) + \gamma \sum_{s'} P(s' \mid s, \pi_i(s)) V_i(s')$.

*Partially observable MDPs.* The agent perceives $e$ through a sensor model $P(e \mid s)$ and maintains a *belief state* $b$ over the states. After doing $a$ and perceiving $e$,

$$b' = \alpha \mathbf{P}(e \mid S') \sum_s \mathbf{P}(S' \mid s, a) b(s).$$

A POMDP is an MDP over belief states, with the reward $\rho(b) = \sum_s b(s) R(s)$.

**Reinforcement learning**

*Reinforcement learning.* $P$ and $R$ are unknown; the agent observes transitions $(s, r, a, s')$, with $r = R(s)$. In *passive RL*, the policy $\pi$ is fixed and the agent learns $V^\pi$; in *active RL*, it learns $\pi^*$. A *model-based* agent estimates $\hat{P}(s' \mid s, a)$ and $\hat{R}(s)$ and solves the resulting MDP. *Direct utility estimation* approximates $V^\pi(s)$ by the average of the observed rewards-to-go from $s$.

*Temporal-difference learning.* For each transition $(s, r, a = \pi(s), s')$, with the *learning rate* $\alpha$,

$$V^\pi(s) \leftarrow V^\pi(s) + \alpha(r + \gamma V^\pi(s') - V^\pi(s)).$$

*Exploration.* An *$\epsilon$-greedy* agent acts randomly with probability $\epsilon$. An *exploration function*, such as $f(v, n) = v + K/n$, is optimistic about actions tried $n$ times only: $V^+_{i+1}(s) = R(s) + \gamma \max_a f\left(\sum_{s'} P(s' \mid s, a) V^+_i(s'), N(s, a)\right)$.

*Q-Learning.* The *state-action-value* $Q(s, a)$ is the expected utility of doing $a$ in $s$ and acting optimally thereafter, so that $V(s) = \max_a Q(s, a)$ and $\pi^*(s) = \arg\max_a Q(s, a)$. For each transition $(s, r, a, s')$,

$$Q(s, a) \leftarrow Q(s, a) + \alpha(r + \gamma \max_{a'} Q(s', a') - Q(s, a)),$$

which converges to the optimal Q-values provided the agent explores enough. In *approximate Q-Learning*, $Q(s, a) = \sum_k w_k f_k(s, a)$ and $w_k \leftarrow w_k + \alpha(r + \gamma \max_{a'} Q(s', a') - Q(s, a)) f_k(s, a)$.

## Exercises

*In session:* exercises 1, 2 (a)–(b) and 4 (December 3), 5 (a) and 6 (December 10).

**Exercise 1 Micro-Blackjack** (CS188, Spring 2014)
A card-playing program plays Micro-Blackjack. It repeatedly draws a card (with replacement), equally likely to be a 2, 3 or 4, and adds its value to its score, which starts at 0. At each step, if the score is lower than 6, the program can either "draw" ($d$) or "cash" ($c$). Otherwise, it can only cash. When it cashes, the game stops and its utility is equal to its score (up to 5) plus 1, or zero if the score is 6 or higher. Until it cashes and after it, it receives no reward. There is no discount ($\gamma = 1$).

(a) Formalize Micro-Blackjack as an MDP.

*Solution.* A state $s = (s_1, s_2)$ holds the score $s_1 \in \{0, 2, 3, 4, 5, 6+\}$ (all scores of 6 or more behave alike) and whether the program has cashed, $s_2 \in \{0, 1\}$. The states with $s_2 = 1$ are terminal. The available actions are

$$\mathcal{A}(s) = \begin{cases} \{d, c\} & \text{if } s_1 < 6 \text{ and } s_2 = 0, \\ \{c\} & \text{if } s_1 \geq 6 \text{ and } s_2 = 0, \\ \{\} & \text{otherwise,} \end{cases}$$

and the transition model and the reward function are

$$P(s' = (s'_1, s'_2) \mid s = (s_1, s_2), a) = \begin{cases} 1 & \text{if } a = c,\ s'_1 = s_1 \text{ and } s'_2 = 1, \\ \frac{1}{3} & \text{if } a = d,\ s'_1 - s_1 \in \{2, 3, 4\} \text{ and } s'_2 = 0, \\ 0 & \text{otherwise,} \end{cases}$$

$$R(s = (s_1, s_2)) = \begin{cases} s_1 + 1 & \text{if } s_1 < 6 \text{ and } s_2 = 1, \\ 0 & \text{otherwise.} \end{cases}$$

(b) Derive the optimal policy for this MDP.

*Solution.* The value $V(s)$ of a state, its maximum expected utility, satisfies the Bellman equation

$$V(s) = R(s) + \gamma \max_{a \in \mathcal{A}(s)} \sum_{s'} P(s' \mid s, a) V(s'),$$

and the optimal policy is $\pi^*(s) = \arg\max_{a \in \mathcal{A}(s)} \sum_{s'} P(s' \mid s, a) V(s')$. Since no action is available in the terminal states, their value is their reward, $V((s_1, 1)) = R((s_1, 1))$. We can apply either value iteration or policy iteration.

- In value iteration, we start from $V_0(s) = R(s)$ and repeat the Bellman update

$$V_{i+1}(s) = R(s) + \gamma \max_{a \in \mathcal{A}(s)} \sum_{s'} P(s' \mid s, a) V_i(s')$$

until convergence ($V_{i+1} = V_i$). Although $\gamma = 1$, it converges, since every game ends: every policy reaches a terminal state within four steps. For example, for the first state of the first iteration, we have

$$\begin{aligned} V_1((0,0)) &= R((0,0)) + \gamma \max \left\{ \underbrace{V_0((0,1))}_{a=c},\ \underbrace{\tfrac{1}{3} V_0((2,0)) + \tfrac{1}{3} V_0((3,0)) + \tfrac{1}{3} V_0((4,0))}_{a=d} \right\} \\ &= 0 + \max\{1,\ 0\} = 1. \end{aligned}$$

| $s_2$ | 0 | | | | | | 1 | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| $s_1$ | 0 | 2 | 3 | 4 | 5 | 6+ | 0 | 2 | 3 | 4 | 5 | 6+ |
| $V_0(s)$ | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 3 | 4 | 5 | 6 | 0 |
| $V_1(s)$ | 1 | 3 | 4 | 5 | 6 | 0 | 1 | 3 | 4 | 5 | 6 | 0 |
| $V_2(s)$ | 4 | $\frac{11}{3}$ | 4 | 5 | 6 | 0 | 1 | 3 | 4 | 5 | 6 | 0 |
| $V_3(s)$ | $\frac{38}{9}$ | $\frac{11}{3}$ | 4 | 5 | 6 | 0 | 1 | 3 | 4 | 5 | 6 | 0 |
| $V_4(s)$ | $\frac{38}{9}$ | $\frac{11}{3}$ | 4 | 5 | 6 | 0 | 1 | 3 | 4 | 5 | 6 | 0 |

Each iteration takes $\mathcal{O}(|\mathcal{S}|^2|\mathcal{A}|)$ operations. The optimal policy follows from the values:

| $s_2$ | 0 | | | | | | 1 | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| $s_1$ | 0 | 2 | 3 | 4 | 5 | 6+ | 0 | 2 | 3 | 4 | 5 | 6+ |
| $\pi^*(s)$ | $d$ | $d$ | $c$ | $c$ | $c$ | $c$ | | | | – | | |

- In policy iteration, we start from a policy $\pi_0$, evaluate it by solving the linear equations

$$V^{\pi_i}(s) = R(s) + \gamma \sum_{s'} P(s' \mid s, \pi_i(s)) V^{\pi_i}(s'),$$


and improve it with $\pi_{i+1}(s) = \arg\max_{a \in \mathcal{A}(s)} \sum_{s'} P(s' \mid s, a) V^{\pi_i}(s')$, until the policy no longer changes. Here, the equations are triangular, since the score only increases, and are solved from the highest score down.
With $\pi_0(s) = c$ everywhere, $V^{\pi_0}((s_1, 0)) = s_1 + 1$ for $s_1 < 6$ and $V^{\pi_0}((6+, 0)) = 0$. Improving it, drawing from $(0, 0)$ is worth $\frac{1}{3}(3 + 4 + 5) = 4 > 1$, from $(2, 0)$ it is worth $\frac{1}{3}(5 + 6 + 0) = \frac{11}{3} > 3$, and from $(3, 0)$ only $\frac{1}{3}(6 + 0 + 0) = 2 < 4$; drawing from $(4, 0)$ or $(5, 0)$ always busts. Hence $\pi_1 = (d, d, c, c, c, c)$ for $s_1 = 0, 2, 3, 4, 5, 6+$.
Evaluating $\pi_1$ from the highest score down gives $V^{\pi_1}((5, 0)) = 6$, $V^{\pi_1}((4, 0)) = 5$, $V^{\pi_1}((3, 0)) = 4$, $V^{\pi_1}((2, 0)) = \frac{1}{3}(5 + 6 + 0) = \frac{11}{3}$ and $V^{\pi_1}((0, 0)) = \frac{1}{3}(\frac{11}{3} + 4 + 5) = \frac{38}{9}$. Improving $\pi_1$ changes no action ($\frac{38}{9} > 1$, $\frac{11}{3} > 3$, $2 < 4$), so that $\pi_2 = \pi_1 = \pi^*$, the policy found by value iteration.
For large problems, solving the linear equations exactly costs $\mathcal{O}(|\mathcal{S}|^3)$ operations; *modified* policy iteration then replaces the exact evaluation by a few simplified Bellman updates $V_{j+1}(s) = R(s) + \gamma \sum_{s'} P(s' \mid s, \pi_i(s)) V_j(s')$.

## Exercise 2 Overheating machine

A maintenance robot looks after a machine that may overheat. It cannot measure the temperature directly: every hour, it only checks whether the machine's alarm is on, and decides whether to cool the machine for the next hour. The alarm is on with probability 0.8 when the machine is overheating, and with probability 0.1 when it is not. Cooling costs 5 (energy), whereas leaving an overheating machine without cooling for an hour costs 10 (wear). Between two checks, a machine that is not overheating starts overheating with probability 0.2, an overheating machine that is not cooled keeps overheating, and a machine that has been cooled is no longer overheating at the next check. When the robot starts, the machine is overheating with probability 0.5.

(a) Draw the dynamic decision network of this problem, as well as its conditional probability tables and its reward function.

*Solution.* Let $H_t \in \{0, 1\}$ indicate whether the machine is overheating at time $t$, $E_t \in \{0, 1\}$ whether the alarm is on, and $F_t \in \{0, 1\}$ whether the robot cools the machine. The reward is $R_t \in \{0, -5, -10\}$. The alarm is observed, and the decision depends on it.




| $H_t$ | $P(E_t = 1 \mid H_t)$ |
|---|---|
| 0 | 0.1 |
| 1 | 0.8 |

| $H_t$ | $F_t$ | $P(H_{t+1} = 1 \mid H_t, F_t)$ | $R_t(H_t, F_t)$ |
|---|---|---|---|
| 0 | 0 | 0.2 | 0 |
| 1 | 0 | 1 | −10 |
| 0 | 1 | 0 | −5 |
| 1 | 1 | 0 | −5 |

For completeness we also have to define the prior $P(H_0 = 1) = 0.5$. Note that $R_t$ is a deterministic function of $H_t$ and $F_t$.

(b) Give the sequence of belief states if the robot observes the alarm and acts as follows: $(e_t, f_t) = (0, 0)$, $(1, 1)$, $(0, 0)$, $(0, 0)$ for $t = 0, 1, 2, 3$.

*Solution.* The environment is only partially observable (POMDP): the robot does not know the current state $s = H_t$, but perceives $e = E_t$ through the sensor model $P(e \mid s)$ and acts $a = F_t$. If $b$ is the current belief state and the robot does $a$ and then perceives $e'$, the next belief state is

$$b'(s') = \alpha P(e' \mid s') \sum_s P(s' \mid s, a) b(s).$$

Here, this gives

$$b_{t+1}(h_{t+1}) = \alpha P(e_{t+1} \mid h_{t+1}) \sum_{h_t} P(h_{t+1} \mid h_t, f_t) b_t(h_t),$$

with the initial belief

$$b_0 = P(H_0 \mid e_0) = \alpha P(e_0 \mid H_0) P(H_0).$$

With $e_{0:3} = f_{0:3} = (0, 1, 0, 0)$ and beliefs written as $(b(0), b(1))$, we have

$$b_0 = \alpha_0 \begin{pmatrix} 0.9 & 0 \\ 0 & 0.2 \end{pmatrix} \begin{pmatrix} 0.5 \\ 0.5 \end{pmatrix} \approx \begin{pmatrix} 0.8182 \\ 0.1818 \end{pmatrix}$$
$$b_1 = \alpha_1 \begin{pmatrix} 0.1 & 0 \\ 0 & 0.8 \end{pmatrix} \begin{pmatrix} 0.8 & 0 \\ 0.2 & 1 \end{pmatrix} b_0 \approx \begin{pmatrix} 0.1915 \\ 0.8085 \end{pmatrix}$$
$$b_2 = \alpha_2 \begin{pmatrix} 0.9 & 0 \\ 0 & 0.2 \end{pmatrix} \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} b_1 = \begin{pmatrix} 1 \\ 0 \end{pmatrix}$$
$$b_3 = \alpha_3 \begin{pmatrix} 0.9 & 0 \\ 0 & 0.2 \end{pmatrix} \begin{pmatrix} 0.8 & 0 \\ 0.2 & 1 \end{pmatrix} b_2 \approx \begin{pmatrix} 0.9474 \\ 0.0526 \end{pmatrix}.$$

(c) From the sequence of belief states, determine the sequence of expected rewards.

*Solution.* The expected reward of a belief state $b$ is $\rho(b) = \sum_s b(s)R(s)$. Here, the reward also depends on the action:


$$\rho_t = \sum_{h_t} R_t(h_t, f_t) b_t(h_t).$$

Then,

$$\rho_0 = \begin{pmatrix} 0 & -10 \end{pmatrix} b_0 \approx -1.818$$
$$\rho_1 = \begin{pmatrix} -5 & -5 \end{pmatrix} b_1 = -5$$
$$\rho_2 = \begin{pmatrix} 0 & -10 \end{pmatrix} b_2 = 0$$
$$\rho_3 = \begin{pmatrix} 0 & -10 \end{pmatrix} b_3 \approx -0.526.$$

**Exercise 3 Pursuit evasion** (CS188, Spring 2014)

Pacman is trapped in the 2 by 2 maze below with a hungry ghost. When it is its turn to move, Pacman must move one step horizontally or vertically to a neighboring square. When it is the ghost's turn, it must also move one step horizontally or vertically. The ghost and Pacman alternate moves. After every move (by either the ghost or Pacman), if Pacman and the ghost occupy the same square, Pacman is eaten and receives a utility of $-100$. Otherwise, it receives a utility of 1. The ghost attempts to minimize the utility that Pacman receives. Pacman makes the first move. The game is not guaranteed to terminate.



For example, with a discount factor of $\gamma = 1$, if Pacman moves right, ghost moves down, then Pacman moves left, Pacman earns a reward of 1 initially ($R(s_0)$) and after the first two moves and $-100$ after the last move, for a total utility of $-97$.

(a) Assume a discount factor $\gamma = 0.5$, where the discount factor is applied once every time either Pacman or the ghost moves. What is the Minimax value of the complete (infinite) game?

*Solution.* If we assume the game starts from the displayed state $s_0$, Pacman always has an action to get out of reach of the ghost. Hence, if Pacman is optimal, which is true by definition in Minimax, it never gets eaten. Therefore, we can compute the initial state value

$$V(s_0) = \sum_{t=0}^{\infty} \gamma^t \underbrace{R(s_t)}_{1} = \lim_{t\to\infty} \frac{1-\gamma^{t+1}}{1-\gamma} = \frac{1}{1-\gamma} = 2,$$

without actually building the (infinite) Minimax tree.

(b) Why are the value/policy iteration algorithms superior to Minimax for solving this game?

*Solution.* If $\gamma < 1$, we know that the value/policy iteration algorithms converge toward a fixed point, even if the game does not terminate. Conversely, Minimax is not guaranteed to terminate due to its recursivity.

This game is similar to an MDP because rewards are earned at every timestep. However, it is also an adversarial game involving decisions by two agents. Let $s$ be the state (*e.g.* the positions of Pacman and the ghost and who is playing) and let $\mathcal{A}(s)$ be the set of actions available to the player in state $s$. Let $s' = T(s, a)$ denote the successor of a state $s$ resulting from the action $a$. Finally, let $R(s)$ denote the utility received after moving to state $s$.


(c) Write down an expression (analogous to Bellman equation) for $V(s)$, the value of the current state if it is Pacman's turn.

*Solution.*

$$V(s) = R(s) + \gamma \max_{a\in\mathcal{A}(s)} \left[ R(T(s,a)) + \gamma \min_{a'\in\mathcal{A}(T(s,a))} V(T(T(s,a),a')) \right]$$

## Exercise 4 Passive reinforcement learning

Consider the grid-world below and an agent that follows a fixed, possibly stochastic, policy $\pi$, whose expected utilities $V^\pi$ it learns (passive reinforcement learning). The agent starts from the bottom-left corner and can take the actions `north` ($N$), `south` ($S$), `west` ($W$) and `east` ($E$). Rewards are only awarded for reaching the terminal (shaded) states.




You observe the following trials, whose trajectories are sequences of tuples $(s_t^i, r_t^i, a_t^i, s_{t+1}^i)$.

| $t$ | Trial 1 | Trial 2 | Trial 3 | Trial 4 | Trial 5 |
|---|---|---|---|---|---|
| 0 | $(1,1), 0, N, (1,2)$ | $(1,1), 0, N, (1,2)$ | $(1,1), 0, N, (1,2)$ | $(1,1), 0, N, (1,2)$ | $(1,1), 0, N, (1,2)$ |
| 1 | $(1,2), 0, E, (2,2)$ | $(1,2), 0, E, (2,2)$ | $(1,2), 0, E, (2,2)$ | $(1,2), 0, E, (2,2)$ | $(1,2), 0, E, (2,2)$ |
| 2 | $(2,2), 0, N, (2,3)$ | $(2,2), 0, E, (3,2)$ | $(2,2), 0, S, (2,1)$ | $(2,2), 0, E, (3,2)$ | $(2,2), 0, E, (3,2)$ |
| 3 | $(2,3), -1, \varnothing, \varnothing$ | $(3,2), 0, N, (3,3)$ | $(2,1), -8, \varnothing, \varnothing$ | $(3,2), 0, W, (2,2)$ | $(3,2), 0, S, (3,1)$ |
| 4 | | $(3,3), +5, \varnothing, \varnothing$ | | $(2,2), 0, N, (2,3)$ | $(3,1), +3, \varnothing, \varnothing$ |
| 5 | | | | $(2,3), -1, \varnothing, \varnothing$ | |

Assuming a discount factor $\gamma = 1$,

(a) Perform direct utility estimation of the expected utilities $V^\pi(s)$, given the first four trials, averaging the rewards-to-go observed at every visit of each state.

*Solution.* In this setting, the transition model $P(s' \mid s, a)$ and the reward function $R(s)$ are unknown. We wish to learn the expected utility $V^\pi$ of the policy $\pi$ without modeling the environment, *i.e.* without building approximates $\hat{P}(s' \mid s, a)$ and $\hat{R}(s)$. The principle of direct utility estimation is to approximate $V^\pi(s)$ by the average utility $\hat{V}(s)$ of the state $s$ within all trial trajectories, *i.e.*

$$\hat{V}(s) = \frac{1}{N(s)} \sum_{(i,j)\in I(s)} \sum_{t=0}^{\infty} \gamma^t r^i_{j+t} \approx V^\pi(s) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t R(s_t)\right]\Bigg|_{s_0=s}$$

where $I(s) = \{(i,j) : s^i_j = s\}$ indexes the occurrences of $s$ and $N(s) = |I(s)|$ is the number of occurrences of $s$. For example, in our case and excluding the fifth trial,

$$\begin{aligned}
I((1,1)) &= \{(1,0),(2,0),(3,0),(4,0)\} \\
\hat{V}((1,1)) &\approx \frac{1}{4}\left(-1\,\gamma^3 + 5\,\gamma^4 - 8\,\gamma^3 - 1\,\gamma^5\right) = \frac{-5}{4} \\
I((2,2)) &= \{(1,2),(2,2),(3,2),(4,2),(4,4)\} \\
\hat{V}((2,2)) &\approx \frac{1}{5}\left(-1\,\gamma^1 + 5\,\gamma^2 - 8\,\gamma^1 - 1\,\gamma^3 - 1\,\gamma^1\right) = \frac{-6}{5} \\
I((2,3)) &= \{(1,3),(4,5)\} \\
\hat{V}((2,3)) &\approx \frac{1}{2}\left(-1\,\gamma^0 - 1\,\gamma^0\right) = -1.
\end{aligned}$$

Importantly, since the agent has not reached the states $(1,3)$ and $(3,1)$ yet, it is not possible to estimate their expected utility. Instead, we assume a default value of 0.

| | | | |
|---|---|---|---|
| 3 | 0 | −1 | +5 |
| 2 | $-\frac{5}{4}$ | $-\frac{6}{5}$ | +2 |
| 1 | $-\frac{5}{4}$ | −8 | 0 |
| | 1 | 2 | 3 |

(b) Update the estimated expected utilities with respect to the fifth trial using temporal-difference learning. Assume a learning rate $\alpha = 0.5$.

*Solution.* Direct utility estimation misses the fact that the expected utilities for different states are not independent, since they obey the Bellman equation for a fixed policy

$$V^\pi(s) = R(s) + \gamma \sum_{s'} P(s' \mid s, \pi(s)) V^\pi(s').$$

Then, we would like our estimates $V^\pi(s)$ to verify the Bellman equation, *i.e.* to minimize

$$L = \mathop{\mathbb{E}}_{s'|s}\left[\left(R(s) + \gamma V^\pi(s') - V^\pi(s)\right)^2\right].$$

One way to reach this objective is to follow the opposite of its gradient

$$\nabla L = 2 \mathop{\mathbb{E}}_{s'|s}\left[V^\pi(s) - R(s) - \gamma V^\pi(s')\right]$$

with respect to $V^\pi(s)$, *i.e.* to perform *gradient descent*. Unfortunately, due to the expectation, we don't have access to the true gradient. Instead, we use a *stochastic* approximation of the gradient from observed[1] tuples $(s, r, a, s')$ and update $V^\pi(s)$ as

$$\begin{aligned} V^\pi(s) &\leftarrow V^\pi(s) - \alpha(V^\pi(s) - r - \gamma V^\pi(s')) \\ &\leftarrow (1-\alpha)V^\pi(s) + \alpha(r + \gamma V^\pi(s')) \end{aligned}$$

where $\alpha$ is the learning rate. For a fixed learning rate, the average of $V^\pi(s)$ converges towards (oscillates around) the true expected utility $V^\pi(s)$. For a (slowly) decreasing learning rate, $V^\pi(s)$ itself converges to $V^\pi(s)$. For historical reasons, this algorithm is called temporal-difference (TD) learning.

Following the trajectory of the fifth trial, we perform the updates

$$\begin{aligned} V^\pi((1,1)) &\leftarrow (1-\alpha)V^\pi((1,1)) + \alpha(0 + \gamma V^\pi((1,2))) = \frac{1}{2}\frac{-5}{4} + \frac{1}{2}\frac{-5}{4} = \frac{-5}{4} \\ V^\pi((1,2)) &\leftarrow (1-\alpha)V^\pi((1,2)) + \alpha(0 + \gamma V^\pi((2,2))) = \frac{1}{2}\frac{-5}{4} + \frac{1}{2}\frac{-6}{5} = \frac{-49}{40} \\ V^\pi((2,2)) &\leftarrow (1-\alpha)V^\pi((2,2)) + \alpha(0 + \gamma V^\pi((3,2))) = \frac{1}{2}\frac{-6}{5} + \frac{1}{2}2 = \frac{2}{5} \\ V^\pi((3,2)) &\leftarrow (1-\alpha)V^\pi((3,2)) + \alpha(0 + \gamma V^\pi((3,1))) = \frac{1}{2}2 + \frac{1}{2}0 = +1 \\ V^\pi((3,1)) &\leftarrow (1-\alpha)V^\pi((3,1)) + \alpha(3 + 0) = \frac{1}{2}0 + \frac{1}{2}3 = \frac{+3}{2}. \end{aligned}$$

| | | | |
|---|---|---|---|
| 3 | 0 | $-1$ | $+5$ |
| 2 | $-\frac{49}{40}$ | $+\frac{2}{5}$ | $+1$ |
| 1 | $-\frac{5}{4}$ | $-8$ | $+\frac{3}{2}$ |
| | 1 | 2 | 3 |

## Exercise 5 Q-Learning

An agent is in an unknown environment where there are three states $\{A, B, C\}$ and two actions $\{0, 1\}$. We are given the following transitions, generated by taking actions in the environment. Here, the reward depends on the transition, $r = R(s, a, s')$, so that each tuple $(s, a, r, s')$ lists the state, the action, the reward received for the transition and the next state.

| $s$ | $a$ | $r$ | $s'$ |
|---|---|---|---|
| $A$ | 0 | $+2$ | $A$ |
| $C$ | 1 | $-2$ | $A$ |
| $B$ | 1 | $+1$ | $B$ |
| $A$ | 0 | $-1$ | $B$ |
| $B$ | 1 | $-2$ | $C$ |
| $C$ | 0 | $+4$ | $B$ |
| $B$ | 0 | $+1$ | $A$ |

Assuming a discount factor $\gamma = 0.5$ and a learning rate $\alpha = 0.75$,

[1] We are not limited to one update for each tuple $(s, r, a, s')$. Indeed, as we assume the policy to be stationary, past trials are as likely to happen again as more recent ones. Therefore, reusing tuples several times (in other orders) is a good way to improve estimates while generating fewer trials.

(a) Apply the Q-Learning algorithm to obtain state-action-value $Q(s,a)$ estimates, processing the transitions once, in order. Estimates are initialized to 0.

*Solution.* As seen in the previous exercise, given trial trajectories of some policy $\pi$, it is possible to estimate its expected utility $V^\pi$ even without knowing the transition model $P(s' \mid s,a)$ or the reward function. However, estimating $V^\pi$ only evaluates the quality of $\pi$, but does not describe how to improve it.

If we knew the state-action-value $Q(s,a)$ of taking action $a$ in state $s$, we would be able to select the optimal action $\pi^*(s) = \arg\max_a Q(s,a)$ without the transition model, where, with rewards on transitions,

$$Q(s,a) = \sum_{s'} P(s' \mid s,a) \Big[ R(s,a,s') + \gamma \max_{a'} Q(s',a') \Big].$$

Q-Learning learns these values in a model-free fashion, with the update

$$Q(s,a) \leftarrow (1-\alpha) Q(s,a) + \alpha \Big( r + \gamma \max_{a'} Q(s',a') \Big)$$

for each observed transition $(s,a,r,s')$. In our case, the sequence of updates is

$$\begin{aligned}
Q(A,0) &\leftarrow \tfrac{1}{4} \cdot 0 + \tfrac{3}{4} \Big( +2 + \tfrac{1}{2} \max\{Q(A,0), Q(A,1)\} \Big) = \frac{3}{2} \\
Q(C,1) &\leftarrow \tfrac{1}{4} \cdot 0 + \tfrac{3}{4} \Big( -2 + \tfrac{1}{2} \max\{Q(A,0), Q(A,1)\} \Big) = -\frac{15}{16} \\
Q(B,1) &\leftarrow \tfrac{1}{4} \cdot 0 + \tfrac{3}{4} \Big( +1 + \tfrac{1}{2} \max\{Q(B,0), Q(B,1)\} \Big) = \frac{3}{4} \\
Q(A,0) &\leftarrow \tfrac{1}{4} \cdot \frac{3}{2} + \tfrac{3}{4} \Big( -1 + \tfrac{1}{2} \max\{Q(B,0), Q(B,1)\} \Big) = -\frac{3}{32} \\
Q(B,1) &\leftarrow \tfrac{1}{4} \cdot \frac{3}{4} + \tfrac{3}{4} \Big( -2 + \tfrac{1}{2} \max\{Q(C,0), Q(C,1)\} \Big) = -\frac{21}{16} \\
Q(C,0) &\leftarrow \tfrac{1}{4} \cdot 0 + \tfrac{3}{4} \Big( +4 + \tfrac{1}{2} \max\{Q(B,0), Q(B,1)\} \Big) = 3 \\
Q(B,0) &\leftarrow \tfrac{1}{4} \cdot 0 + \tfrac{3}{4} \Big( +1 + \tfrac{1}{2} \max\{Q(A,0), Q(A,1)\} \Big) = \frac{3}{4}.
\end{aligned}$$

Hence $Q(A,0) = -\frac{3}{32}$, $Q(A,1) = 0$, $Q(B,0) = \frac{3}{4}$, $Q(B,1) = -\frac{21}{16}$, $Q(C,0) = 3$ and $Q(C,1) = -\frac{15}{16}$, so that the greedy policy is $\pi(A) = 1$, $\pi(B) = 0$, $\pi(C) = 0$. As for temporal-difference learning, we are not limited to one update for each tuple: reusing the tuples several times (in other orders) is a good way to reach convergence faster while generating fewer trials.

(b) We now switch to a feature-based estimator $Q(s,a) = w_0 + w_1 f_1(s,a)$, with $f_1(s,a) = 2a - 1$. Starting from weights $w_0 = w_1 = 0$, update the weights according to the approximate Q-Learning algorithm, processing the transitions once, in order.

*Solution.* We would like our estimates $Q(s,a)$ to satisfy the Bellman equation, *i.e.* to minimize

$$L = \mathop{\mathbb{E}}_{s'|s,a} \left[ \Big( R(s,a,s') + \gamma \max_{a'} Q(s',a') - Q(s,a) \Big)^2 \right].$$

To reach this objective we follow the opposite of its gradient with respect to the weights[2] $\mathbf{w} = (w_0, w_1)$ of $Q(s,a)$. Due to the expectation, we use a stochastic approximation of the gradient from each observed transition $(s,a,r,s')$, and update the weights as

$$\mathbf{w} \leftarrow \mathbf{w} + \alpha \Big( r + \gamma \max_{a'} Q(s',a') - Q(s,a) \Big) \nabla_{\mathbf{w}} Q(s,a),$$

where $\nabla_{\mathbf{w}} Q(s,a) = (1, f_1(s,a)) = (1, 2a-1)$. For instance, the first two updates are

$$\mathbf{w} \leftarrow \begin{pmatrix} 0 \\ 0 \end{pmatrix} + \frac{3}{4}\left(2 + \frac{1}{2}\max\{0,0\} - 0\right)\begin{pmatrix} 1 \\ -1 \end{pmatrix} = \begin{pmatrix} \frac{3}{2} \\ -\frac{3}{2} \end{pmatrix},$$
$$\mathbf{w} \leftarrow \begin{pmatrix} \frac{3}{2} \\ -\frac{3}{2} \end{pmatrix} + \frac{3}{4}\left(-2 + \frac{1}{2}\max\{3,0\} - 0\right)\begin{pmatrix} 1 \\ 1 \end{pmatrix} = \begin{pmatrix} \frac{9}{8} \\ -\frac{15}{8} \end{pmatrix},$$

since then $Q(A,0) = w_0 - w_1 = 3$, $Q(A,1) = 0$ and $Q(C,1) = w_0 + w_1 = 0$. All the updates are, with the target $r + \gamma \max_{a'} Q(s',a')$:

| $(s,a,r,s')$ | $f_1(s,a)$ | $Q(s,a)$ | Target | $w_0$ | $w_1$ |
|---|---|---|---|---|---|
| $(A,0,+2,A)$ | $-1$ | $0$ | $2$ | $\frac{3}{2}$ | $-\frac{3}{2}$ |
| $(C,1,-2,A)$ | $+1$ | $0$ | $-\frac{1}{2}$ | $\frac{9}{8}$ | $-\frac{15}{8}$ |
| $(B,1,+1,B)$ | $+1$ | $-\frac{3}{4}$ | $\frac{5}{2}$ | $\frac{57}{16}$ | $\frac{9}{16}$ |
| $(A,0,-1,B)$ | $-1$ | $3$ | $\frac{17}{16}$ | $\frac{135}{64}$ | $\frac{129}{64}$ |
| $(B,1,-2,C)$ | $+1$ | $\frac{33}{8}$ | $\frac{1}{16}$ | $-\frac{15}{16}$ | $-\frac{33}{32}$ |
| $(C,0,+4,B)$ | $-1$ | $\frac{3}{32}$ | $\frac{259}{64}$ | $\frac{519}{256}$ | $-\frac{1023}{256}$ |
| $(B,0,+1,A)$ | $-1$ | $\frac{771}{128}$ | $\frac{1027}{256}$ | $\frac{531}{1024}$ | $-\frac{2547}{1024}$ |

(c) Why can this estimator not represent the Q-values of (a)?

*Solution.* The feature $f_1(s,a) = 2a - 1$ ignores the state: the estimator gives the same value $w_0 - w_1$ to action 0 in every state, and $w_0 + w_1$ to action 1, whereas the Q-values of (a) differ from one state to another. Its greedy policy takes the same action everywhere. Features that depend on $s$ are needed to tell the states apart.

## Exercise 6 Robot football

ULiège's robot football team plays against UCL's robots in a RoboCup match next week. After a lot of losses this season, the team needs a better attack strategy, and its coaching program models the attack as a Markov decision process. It considers four states `close` (`C`), `away` (`A`), `fail` (`F`), and `goal` (`G`), the last two being terminal, and two actions `pass` (`P`) and `shoot` (`S`). Although the transition probabilities are unknown, the possible transitions $(s,a,s')$ are known, and to each transition is associated a reward $R(s,a,s')$.

| $s$ | $a$ | $s'$ | $R(s,a,s')$ |
|---|---|---|---|
| C | P | C | $+1$ |
| C | P | A | $-1$ |
| C | P | F | $-2$ |
| C | S | C | $+3$ |
| C | S | F | $-5$ |
| C | S | G | $+10$ |
| A | P | C | $+2$ |
| A | P | A | $0$ |
| A | P | F | $-3$ |
| A | S | C | $+3$ |
| A | S | F | $-10$ |
| A | S | G | $+20$ |

[2]The target $r + \gamma \max_{a'} Q(s',a')$ is treated as a constant when taking the gradient. In practice, it is not, since modifying the weights of a parametric function $Q$ modifies all state-action pairs $(s,a)$ at once, which can make approximate Q-Learning unstable.

The current strategy of the team is to always shoot. Last match, the robots had several attack opportunities, resulting in the following transitions.

| $s$ | C | C | C | C | A | A | A | A |
|---|---|---|---|---|---|---|---|---|
| $a$ | S | S | S | S | S | S | S | S |
| $s'$ | G | C | G | F | F | C | F | F |

Assuming a discount factor $\gamma = 0.75$ and a learning rate $\alpha = 0.25$,

(a) Build an estimator of the transition model $P(s' \mid s, a)$ and, from it, determine the expected utility $V^\pi$ of the team's current policy $\pi$.

*Solution.* Given the previous table, we can estimate the transition probabilities for $s \in \{\texttt{C}, \texttt{A}\}$ and $a = \texttt{S}$.

| $s$ | $a$ | $P(s' \mid s, a)$ | | | |
|---|---|---|---|---|---|
| | | C | A | F | G |
| C | S | 0.25 | 0 | 0.25 | 0.5 |
| A | S | 0.25 | 0 | 0.75 | 0 |

We can now determine the expected utility $V^\pi$ of the team's current policy $\pi(s) = \texttt{S}$, with rewards on transitions, by iterating

$$V^\pi_{i+1}(s) = \sum_{s'} P(s' \mid s, \pi(s)) \big[R(s, \pi(s), s') + \gamma V^\pi_i(s')\big],$$

with $V^\pi_0(s) = 0$ for all states $s$. Because the states F and G are terminal, their expected utility remains constant and we only have to update C and A. For the first iteration,

$$\begin{aligned} V^\pi_1(\texttt{C}) &= \sum_{s'} P(s' \mid \texttt{C}, \texttt{S}) \big[R(\texttt{C}, \texttt{S}, s') + \gamma V^\pi_0(s')\big] \\ &= 0.25(3 + \gamma\, 0) + 0.25(-5 + \gamma\, 0) + 0.5(10 + \gamma\, 0) = 4.5 \end{aligned}$$

and

$$\begin{aligned} V^\pi_1(\texttt{A}) &= \sum_{s'} P(s' \mid \texttt{A}, \texttt{S}) \big[R(\texttt{A}, \texttt{S}, s') + \gamma V^\pi_0(s')\big] \\ &= 0.25(3 + \gamma\, 0) + 0.75(-10 + \gamma\, 0) = -6.75. \end{aligned}$$

We repeat the same procedure until $V^\pi_{i+1}(s) \approx V^\pi_i(s)$ for all states $s$ (values rounded to four decimals).

| $s$ | C | A | F | G |
|---|---|---|---|---|
| $V^\pi_0(s)$ | 0 | 0 | 0 | 0 |
| $V^\pi_1(s)$ | 4.5 | -6.75 | 0 | 0 |
| $V^\pi_2(s)$ | 5.3438 | −5.9062 | 0 | 0 |
| $V^\pi_3(s)$ | 5.5020 | −5.7480 | 0 | 0 |
| $V^\pi_4(s)$ | 5.5316 | −5.7184 | 0 | 0 |
| ⋮ | ⋮ | ⋮ | ⋮ | ⋮ |
| $V^\pi_8(s)$ | 5.5385 | −5.7115 | 0 | 0 |

Since the policy is fixed, the values also solve the linear equations $V^\pi(\texttt{C}) = 4.5 + 0.1875\, V^\pi(\texttt{C})$ and $V^\pi(\texttt{A}) = -6.75 + 0.1875\, V^\pi(\texttt{C})$, hence exactly $V^\pi(\texttt{C}) = \frac{72}{13} \approx 5.5385$ and $V^\pi(\texttt{A}) = -\frac{297}{52} \approx -5.7115$.

The coaching program finds the logs of the previous season, when the team had much more success, and selects the following instructive transitions.

| $s$ | C | C | A | A | C | A | A | C |
|---|---|---|---|---|---|---|---|---|
| $a$ | S | S | S | P | P | P | S | P |
| $s'$ | G | C | F | C | C | C | F | F |

(b) Given the selected transitions, apply the Q-Learning algorithm to obtain state-action-value $Q(s, a)$ estimates, processing the transitions once, in order. Estimates are initialized to 0.

*Solution.* In Q-Learning, the state-action-value estimates are updated following

$$Q(s,a) \leftarrow (1-\alpha)Q(s,a) + \alpha\Big(r + \gamma \max_{a'} Q(s',a')\Big)$$

for each observed transition $(s, a, s')$, with the reward $r = R(s, a, s')$ given by the table. The terminal states keep $Q(\mathtt{F}, \cdot) = Q(\mathtt{G}, \cdot) = 0$. In the order of the selected transitions, we have

$$\begin{aligned}
Q(\mathtt{C},\mathtt{S}) &\leftarrow (1-\alpha)Q(\mathtt{C},\mathtt{S}) + \alpha\Big(R(\mathtt{C},\mathtt{S},\mathtt{G}) + \gamma \max_{a'} Q(\mathtt{G},a')\Big)\\
&\leftarrow 0.75 \times 0 + 0.25(10 + 0) = 2.5\\
Q(\mathtt{C},\mathtt{S}) &\leftarrow (1-\alpha)Q(\mathtt{C},\mathtt{S}) + \alpha\Big(R(\mathtt{C},\mathtt{S},\mathtt{C}) + \gamma \max_{a'} Q(\mathtt{C},a')\Big)\\
&\leftarrow 0.75 \times 2.5 + 0.25(3 + 0.75 \max\{2.5, 0\}) = 3.094\\
Q(\mathtt{A},\mathtt{S}) &\leftarrow (1-\alpha)Q(\mathtt{A},\mathtt{S}) + \alpha\Big(R(\mathtt{A},\mathtt{S},\mathtt{F}) + \gamma \max_{a'} Q(\mathtt{F},a')\Big)\\
&\leftarrow 0.75 \times 0 + 0.25(-10 + 0) = -2.5\\
Q(\mathtt{A},\mathtt{P}) &\leftarrow (1-\alpha)Q(\mathtt{A},\mathtt{P}) + \alpha\Big(R(\mathtt{A},\mathtt{P},\mathtt{C}) + \gamma \max_{a'} Q(\mathtt{C},a')\Big)\\
&\leftarrow 0.75 \times 0 + 0.25(2 + 0.75 \max\{0, 3.094\}) = 1.080\\
Q(\mathtt{C},\mathtt{P}) &\leftarrow 0.75 \times 0 + 0.25(R(\mathtt{C},\mathtt{P},\mathtt{C}) + 0.75 \max\{0, 3.094\}) = 0.25(1 + 2.320) = 0.830\\
Q(\mathtt{A},\mathtt{P}) &\leftarrow 0.75 \times 1.080 + 0.25(R(\mathtt{A},\mathtt{P},\mathtt{C}) + 0.75 \max\{0.830, 3.094\}) = 1.890\\
Q(\mathtt{A},\mathtt{S}) &\leftarrow 0.75 \times (-2.5) + 0.25(R(\mathtt{A},\mathtt{S},\mathtt{F}) + 0) = -4.375\\
Q(\mathtt{C},\mathtt{P}) &\leftarrow 0.75 \times 0.830 + 0.25(R(\mathtt{C},\mathtt{P},\mathtt{F}) + 0) = 0.123.
\end{aligned}$$

Hence $Q(\mathtt{C},\mathtt{S}) = 3.094$, $Q(\mathtt{C},\mathtt{P}) = 0.123$, $Q(\mathtt{A},\mathtt{S}) = -4.375$ and $Q(\mathtt{A},\mathtt{P}) = 1.890$.

(c) Determine the optimal policy according to the state-action-value estimates.

*Solution.* Taking the action of highest $Q(s, a)$ in each state, since $3.094 > 0.123$ and $1.890 > -4.375$,

$$\pi(s) = \begin{cases} \mathtt{S} & \text{if } s = \mathtt{C} \\ \mathtt{P} & \text{if } s = \mathtt{A} \end{cases}$$

(d) None of the selected transitions is a goal scored from away, $(\mathtt{A}, \mathtt{S}, \mathtt{G})$, worth +20. Should the team trust the policy of (c) in state A? How could the coaching program learn more?

*Solution.* Not entirely. All the observed shots from A failed, so that $Q(\mathtt{A},\mathtt{S})$ is negative, and a robot that follows the greedy policy $\pi(\mathtt{A}) = \mathtt{P}$ will never shoot from away again: it will never observe the goal worth +20 that a shot from A can score, and its estimate of $Q(\mathtt{A},\mathtt{S})$ will never improve. Q-Learning converges to the optimal Q-values only if every action keeps being tried. The program should therefore explore, for instance by acting $\epsilon$-greedily (shooting from A with a small probability $\epsilon$), or with an exploration function such as $f(v, n) = v + K/n$, which makes it optimistic about the actions it has tried only $n$ times.

**Exercise 7 Contraction of the Bellman update** (AIMA ch. 17)
Let $B$ denote the Bellman update, which maps a utility function $V$ to the function

$$(BV)(s) = R(s) + \gamma \max_{a \in \mathcal{A}(s)} \sum_{s'} P(s' \mid s, a) V(s').$$

The Bellman update is a contraction, which guarantees the convergence of value iteration for $\gamma < 1$.

(a) Show that, for any two functions $f : \mathcal{X} \to \mathbb{R}$ and $g : \mathcal{X} \to \mathbb{R}$ over a finite set $\mathcal{X}$,

$$|\max_x f(x) - \max_x g(x)| \leq \max_x |f(x) - g(x)|.$$

*Solution.* Suppose, without loss of generality, that $\max_x f(x) \geq \max_x g(x)$, and let $x^*$ be a maximizer of $f$. Then

$$|\max_x f(x) - \max_x g(x)| = f(x^*) - \max_x g(x) \leq f(x^*) - g(x^*) \leq \max_x |f(x) - g(x)|.$$

(b) Apply the previous result to prove that the Bellman update is a contraction of factor $\gamma$, that is, for any two utility functions $V, V' : \mathcal{S} \to \mathbb{R}$,

$$\|BV - BV'\|_\infty \leq \gamma \|V - V'\|_\infty,$$

where $\|V\|_\infty = \max_s |V(s)|$.

*Solution.* The rewards cancel, and (a) applies to the maximum over the actions:

$$\begin{aligned}
\|BV - BV'\|_\infty &= \gamma \max_s |\max_a \sum_{s'} P(s' \mid s, a) V(s') - \max_a \sum_{s'} P(s' \mid s, a) V'(s')| \\
&\leq \gamma \max_s \max_a |\sum_{s'} P(s' \mid s, a)(V(s') - V'(s'))| \\
&\leq \gamma \max_s \max_a \sum_{s'} P(s' \mid s, a) |V(s') - V'(s')| \\
&\leq \gamma \max_s \max_a \sum_{s'} P(s' \mid s, a) \|V - V'\|_\infty = \gamma \|V - V'\|_\infty,
\end{aligned}$$

since the probabilities $P(s' \mid s, a)$ sum to 1 over $s'$.

**Exercise 8 Value iteration** (AIMA ch. 17)
Consider the $3 \times 3$ world below, where each square is labelled with its reward. The upper right square is a terminal state. In each state, the agent can move north, south, east or west: 80% of the time it goes in the direction it selects, and the rest of the time it moves at right angles to the intended direction (10% on each side). A move into a wall leaves the agent where it is.

| | | |
|---|---|---|
| $r$ | $-1$ | $+10$ |
| $-1$ | $-1$ | $-1$ |
| $-1$ | $-1$ | $-1$ |

Apply value iteration for this world for each value of $r$ below, with a discount factor $\gamma = 0.99$. Show the policy obtained in each case. Explain intuitively why the value of $r$ leads to each policy.

(a) $r = -100$

*Solution.* The agent avoids the upper left square at all costs: from below it, it even moves south, away from the goal, since moving north could end there.

| | | |
|---|---|---|
| → | → | +10 |
| ↓ | → | ↑ |
| → | → | ↑ |

(b) $r = -3$

*Solution.* Every step costs, the upper left square a little more: the agent heads for the goal along the shortest path, east then north, and leaves the upper left square at once.

| | | |
|---|---|---|
| → | → | +10 |
| → | → | ↑ |
| → | → | ↑ |

(c) $r = 0$

*Solution.* The upper left square is free: the agent goes north first, to the top row, which costs nothing on its first square, then east to the goal.

| | | |
|---|---|---|
| → | → | +10 |
| ↑ | ↑ | ↑ |
| ↑ | ↑ | ↑ |


(d) $r = +3$

*Solution.* Staying in the upper left square forever earns 3 at every step, worth about $3/(1 - 0.99) = 300$, much more than the +10 of the goal: the agent heads for the upper left square and stays there by bumping into the walls (north or west), and moves away from the goal wherever it might slip into it.

| | | |
|---|---|---|
| ↑← | ← | +10 |
| ↑ | ← | ↓ |
| ↑ | ← | ← |

**Exercise 9 Discount factor** (AIMA ch. 17)

Consider the $101 \times 3$ world below. In the start state, of reward 0, the agent has a choice of two deterministic actions, `up` or `down`, but in the other states the agent has one deterministic action, `right`, until it leaves the world at the right end. Assuming a discounted reward function, compute the utility of each action as a function of $\gamma$. For what values of the discount factor $\gamma$ should the agent choose `up` and for which `down`?




*Solution.* Going `up`, the agent receives $+50$ after one step, then $-1$ at each of the next 100 steps; going `down`, it receives the opposite rewards. Hence

$$V(\texttt{up}) = 50\gamma - \sum_{t=2}^{101} \gamma^t = 50\gamma - \gamma^2 \frac{1-\gamma^{100}}{1-\gamma}, \qquad V(\texttt{down}) = -V(\texttt{up}).$$

The agent should choose `up` when $V(\texttt{up}) > 0$, that is when $50 > \gamma(1-\gamma^{100})/(1-\gamma)$, which holds for $\gamma < 0.9844$ (solved numerically), and `down` for $\gamma > 0.9844$. A short-sighted agent takes the immediate $+50$; a far-sighted one accepts the immediate $-50$ for the hundred $+1$ that follow.

**Exercise 10 Policy iteration** (AIMA ch. 17)
Consider an undiscounted MDP having three states, $(1, 2, 3)$, with rewards $-1$, $-2$, 0, respectively. State 3 is a terminal state. In states 1 and 2 there are two possible actions: $a$ and $b$. The transition model is as follows:

- In state 1, action $a$ moves the agent to state 2 with probability 0.8 and makes the agent stay put with probability 0.2.
- In state 2, action $a$ moves the agent to state 1 with probability 0.8 and makes the agent stay put with probability 0.2.
- In either state 1 or state 2, action $b$ moves the agent to state 3 with probability 0.1 and makes the agent stay put with probability 0.9.

Answer the following questions:

(a) What can be determined *qualitatively* about the optimal policy in states 1 and 2?

*Solution.* Intuitively, the agent wants to get to state 3 as soon as possible, because it will pay a cost for each time step it spends in states 1 and 2. However, the only action that reaches state 3 (action b) succeeds with low probability, so the agent should minimize the cost it incurs while trying to reach the terminal state. This suggests that the agent should definitely try action $b$ in state 1, but, in state 2, it might be better to try action $a$ to get to state 1, rather than aiming directly for state 3. The decision in state 2 involves a numerical trade-off.

(b) Apply policy iteration, showing each step in full, to determine the optimal policy and the values of states 1 and 2. Assume that the initial policy has action $b$ in both states.

*Solution.*

- Initialization: $R \leftarrow \langle -1, -2, 0\rangle, \pi_0 \leftarrow \langle b, b\rangle$.
- Value determination:

$$\begin{aligned} V(s_1) &= -1 + 0.1V(s_3) + 0.9V(s_1) \\ V(s_2) &= -2 + 0.1V(s_3) + 0.9V(s_2) \\ V(s_3) &= 0 \end{aligned}$$

This simple example actually reflects many real-world situations in which one must weigh the value of an immediate action versus the potential long-term consequences, such as choosing to dump pollutants into a lake.

That is, $V(s_1) = -10$ and $V(s_2) = -20$. Policy update:

- In state 1, $\pi_1(s_1) = a$ leads to $\sum_{i\in\{1,2,3\}} P(s_i \mid s_1, a)V(s_i) = 0.8\times -20+0.2\times -10 = -18$ and $\pi_1(s_1) = b$ leads $\sum_{i\in\{1,2,3\}} P(s_i \mid s_1, b)V(s_i) = 0.1 \times 0 + 0.9 \times -10 = -9$, thus $\pi_1(s_1) = b$.
- In state 2, $\pi_1(s_2) = a$ leads to $\sum_{i\in\{1,2,3\}} P(s_i \mid s_2, a)V(s_i) = 0.2\times -20+0.8\times -10 = -12$ and $\pi_1(s_2) = b$ leads $\sum_{i\in\{1,2,3\}} P(s_i \mid s_2, b)V(s_i) = 0.1 \times 0 + 0.9 \times -20 = -18$, thus $\pi_1(s_2) = a$.

- Value determination:

$$\begin{aligned} V(s_1) &= -1 + 0.1V(s_3) + 0.9V(s_1) \\ V(s_2) &= -2 + 0.8V(s_1) + 0.2V(s_2) \\ V(s_3) &= 0 \end{aligned}$$

That is, $V(s_1) = -10$ and $V(s_2) = -12.5$. Policy update:

- In state 1, $\pi_2(s_1) = a$ leads to $\sum_{i\in\{1,2,3\}} P(s_i \mid s_1, a)V(s_i) = 0.8 \times -12.5 + 0.2 \times -10 = -12$ and $\pi_2(s_1) = b$ leads $\sum_{i\in\{1,2,3\}} P(s_i \mid s_1, b)V(s_i) = 0.1\times 0+0.9\times -10 = -9$, thus $\pi_2(s_1) = b$.
- In state 2, $\pi_2(s_2) = a$ leads to $\sum_{i\in\{1,2,3\}} P(s_i \mid s_2, a)V(s_i) = 0.2 \times -12.5 + 0.8 \times -10 = -10.5$ and $\pi_2(s_2) = b$ leads $\sum_{i\in\{1,2,3\}} P(s_i \mid s_2, b)V(s_i) = 0.1 \times 0 + 0.9 \times -12.5 = -11.25$, thus $\pi_2(s_2) = a$.

- Unchanged, which implies convergence.

(c) What happens to policy iteration if the initial policy has action $a$ in both states? Does discounting help? Does the optimal policy depend on the discount factor?

*Solution.* An initial policy with action $a$ in both states leads to an unsolvable problem. The initial value determination problem has the form

$$\begin{aligned} u_1 &= -1 + 0.2u_1 + 0.8u_2 \\ u_2 &= -2 + 0.8u_1 + 0.2u_2 \\ u_3 &= 0 \end{aligned}$$

and the first two equations are inconsistent. If we were to try to solve them iteratively, we would find the values tending to $-\infty$. Discounting leads to well-defined solutions by bounding the penalty (expected discounted cost) an agent can incur at either state. However, the choice of discount factor will affect the policy that results. For $\gamma$ small, the cost incurred in the distant future plays a negligible role in the value computation, because $\gamma^n$ is near 0. As a result, an agent could choose action $b$ in state 2 because the discounted short-term cost of remaining in the non-terminal states (states 1 and 2) outweighs the discounted long-term cost of action $b$ failing repeatedly and leaving the agent in state 2.

## Quiz

1. Which of the following is true? In Markov Decision Processes, ...
   - ◯ the closer the discount factor $\gamma$ to 0, the higher the utility of future rewards.
   - ◯ the closer the discount factor $\gamma$ to 0, the longer Value Iteration may take to converge.
   - ◯ the closer the discount factor $\gamma$ to 1, the greedier the optimal agent.
   - ◉ the closer the discount factor $\gamma$ to 1, the longer Value Iteration may take to converge.
2. Q-Learning ...
   - ◯ is a model-based reinforcement learning algorithm.
   - ◯ is an on-policy reinforcement learning algorithm.
   - ◯ converges to an optimal policy, but only when acting optimally.
   - ◉ requires enough exploration (*e.g.* $\epsilon$-greedy) to converge to an optimal policy.

3. Assume that we run $\epsilon$-greedy Q-Learning until convergence. What is the optimal policy $\pi^*$ we obtain for an arbitrary state $s$?

   ○ $\pi^*(s) = \arg\max_s V(s)$

   ○ $\pi^*(s) = \begin{cases} \arg\max_a Q(s,a) & \text{with probability } 1-\epsilon \\ \text{random action} & \text{with probability } \epsilon \end{cases}$

   ● $\pi^*(s) = \arg\max_a Q(s,a)$

   ○ $\pi^*(s) = \arg\max_s Q(s,a)$

4. Let us consider a robot wandering around at the Montefiore Institute. Which of the following is true?

   ● The robot and its environment can be modeled as a partially observable MDP.

   ○ The Kalman filter can be used for determining accurately its past trajectory in the building.

   ○ A convolutional neural network would be too large to fit in the robot's memory.

   ○ Value iteration (with an admissible heuristic) can be used for decoding the speech of its visitors.

5. The Bellman equations $Q(s,a) = R(s) + \gamma \sum_{s'} P(s' \mid s,a) \max_{a'} Q(s',a')$ form a system of $n$ non-linear equations with as many unknowns. Which of the following is true?

   ○ $n$ is the size of the action space $\mathcal{A}$.

   ○ $n$ is the size of the state space $\mathcal{S}$.

   ● $n$ is the size of the state-action space $\mathcal{S} \times \mathcal{A}$.

   ○ $n$ is the sum of the sizes of the action and state spaces.

6. In DQN (Mnih et al., 2015), a reinforcement learning agent is trained ...

   ○ to classify images.

   ○ to control a robot in a simulated environment.

   ● to play Atari video games.

   ○ to play the game of Go.

7. In DQN (Mnih et al., 2015), the Q-table is approximated with ...

   ○ a hash table.

   ○ a transposition table.

   ○ a linear regression model.

   ● a convolutional neural network.