

INFO8006 Introduction to Artificial Intelligence

Exercise session 1: Solving problems by searching

RECAP

Search problem

A *search problem* is defined by a representation of the *states*, an *initial state* s_0 , the *actions* $\text{actions}(s)$ available in a state s , a *transition model* $s' = \text{result}(s, a)$ and a *goal test*. Together, these define the *state space*, the set of states reachable from s_0 . A *solution* is an action sequence $a_1, \dots, a_T$ leading from s_0 to a goal state s_T ; an *optimal solution* has the lowest *path cost* $\sum_{t=1}^T c(s_{t-1}, a_t, s_t)$, a sum of positive *step costs* c .

Search algorithm

Tree search expands the nodes of the *fringe* until a goal state is reached. *Graph search* also keeps the set of expanded states, the *closed* set, which avoids repeated states and cycles.

Search strategies

A *strategy* is the order in which the fringe is expanded, where $g(n)$ is the path cost from s_0 to n , $h(n)$ a heuristic and $f(n) = g(n) + h(n)$. Below, b is the maximum branching factor, d the depth of the least-cost solution, m the maximum path length (possibly infinite), C^* the optimal path cost and $\epsilon > 0$ a lower bound on the step costs.

Strategy	Fringe	Complete	Optimal	Time	Space
Depth-first (DFS)	LIFO stack	if no cycles	no	$O(b^m)$	$O(bm)$
Breadth-first (BFS)	FIFO queue	yes	if c uniform	$O(b^d)$	$O(b^d)$
Iterative deepening	DFS, depth 1, 2, ...	yes	if c uniform	$O(b^d)$	$O(bd)$
Uniform-cost (UCS)	priority $g(n)$	if $c \geq \epsilon$	yes	$O(b^{C^*/\epsilon})$	$O(b^{C^*/\epsilon})$
Greedy	priority $h(n)$	if no cycles	no	$O(b^m)$	$O(b^m)$
A*	priority $f(n)$	yes	if h admissible	$O(b^m)$	$O(b^m)$

Heuristics

A *heuristic* $h(n) \geq 0$ estimates the cost of the cheapest path from n to a goal state, with $h(n) = 0$ at a goal state, often as the exact cost of a *relaxed problem*. Let $h^*(n)$ be the true cost from n to a nearest goal.

- *Admissible*: $h(n) \leq h^*(n)$ for all n , i.e. h never overestimates. Tree-search A* is then optimal.
- *Consistent*: $h(n) \leq c(n, a, n') + h(n')$ for every n and every successor n' generated by an action a . Then h is admissible, f is non-decreasing along any path and graph-search A* is optimal.
- *Dominance*: if h_1 and h_2 are admissible and $h_2(n) \geq h_1(n)$ for all n , then h_2 dominates h_1 and is better for search. $\max(h_a, h_b)$ is admissible and dominates both.

In session: exercises 1, 3 (a)–(c), 5.

Exercise 1 Path finding

Tram'Ardent maintains the green areas along the Liège tram line with a new robot. This robot's goal is to convey the grass cuttings left by the gardeners to a container as fast as possible. Assuming that

- the fuel cost used by the robot is negligible
- the robot can only navigate on guides that are placed in a rectangular grid configuration and can locate itself on the grid
- there is only one pile and one container by zone (*i.e.* by grid) for which positions are known by the robot
- the speed of the robot is constant and the grass loading/unloading is instantaneous
- the robot can only carry a limited weight of grass at once
- the robot can know the initial weight of grass on the pile.

For a given grid

- (a) Formulate a corresponding search problem.

Solution. **State representation:** Assuming a $H \times W$ grid, the state is represented by the position $(i, j) \in \{1, \dots, W\} \times \{1, \dots, H\}$ of the robot, the remaining weight of grass w_G and a flag L indicating whether the robot is loaded or not. Following other assumptions, we also define the location of the pile and the container respectively by $P = (i_p, j_p)$ and $C = (i_c, j_c)$ as well as the weight limit of the robot $w_{\max}$.

Initial state: No specific information is given, we can assume it starts anywhere on the grid, unloaded. $s_0 = (i_0, j_0, w_{G0}, \text{False})$

Actions: $a \in \{LEFT, UP, RIGHT, DOWN\}$

Transition model:

$$(i, j)' = \begin{cases} (i + 1, j) & \text{if } a = RIGHT \text{ and } i < W \\ (i, j + 1) & \text{if } a = UP \text{ and } j < H \\ (i - 1, j) & \text{if } a = LEFT \text{ and } i > 1 \\ (i, j - 1) & \text{if } a = DOWN \text{ and } j > 1 \\ (i, j) & \text{otherwise} \end{cases}$$

$$w'_G = \begin{cases} w_G - \min(w_G, w_{\max}) & \text{if } \neg L \text{ and } (i, j)' = P \\ w_G & \text{otherwise} \end{cases}$$

$$L' = \begin{cases} \text{True} & \text{if } L \text{ and } (i, j)' \neq C \\ \text{True} & \text{if } w_G > 0 \text{ and } (i, j)' = P \\ \text{False} & \text{otherwise} \end{cases}$$

Goal test: $goal(s)$ is true if $\neg L$ and $w_G = 0$.

Step cost: Under the given assumptions, every step from one node to another is equivalent. Then $c(s, a, s') = 1$ is relevant. Note that it could be any constant step cost.

- (b) Knowing that the terrain can be rugged at specific places, causing slow down of the robot, propose an admissible heuristic which estimates the remaining cost at any node.

Solution. As usual in grid problems, the Manhattan or the Euclidean distance is admissible as long as every step costs at least 1¹. However, the robot can go back and forth if $w_G > w_{\max}$. Then an admissible heuristic would be

$$h(s) = \begin{cases} 0 & \text{if } \neg L \text{ and } w_G = 0 \\ |i_c - i| + |j_c - j| + 2\lceil \frac{w_G}{w_{\max}} \rceil (|i_c - i_p| + |j_c - j_p|) & \text{if } L \\ |i_p - i| + |j_p - j| + (2\lceil \frac{w_G}{w_{\max}} \rceil - 1)(|i_c - i_p| + |j_c - j_p|) & \text{if } \neg L \end{cases}$$

which would have been the true remaining cost if the terrain was not rugged.


- (c) The robot can now also move diagonally, a diagonal step costing $\sqrt{2}$. Is your heuristic still admissible? If not, what should you change? What if the robot is twice as fast diagonally, so that a diagonal step costs $\sqrt{2}/2$?

Solution. The Manhattan distance cannot be used anymore, only the Euclidean distance would be admissible (amongst the previous proposals) or any other function dominated by the Euclidean distance.

If the robot is twice as fast diagonally, a unit of length costs at least 1/2, so the Euclidean distance divided by 2 is admissible. The most limiting case is a perfect diagonal going from P to C .

Exercise 2 The hive (CS188, Spring 2019)

The hive of insects needs your help. You control an insect in a rectangular maze-like environment of size $M \times N$, as shown in the figure below. At each time-step, the insect can move into a free adjacent cell or stay in its current location. All actions have a unit cost.



In this particular case, the insect must pass through a series of partially flooded tunnels, as illustrated by the gray cells on the map. The insect can hold its breath for A time-steps in a row. Moving into a flooded cell requires your insect to consume 1 unit of air, while moving into a free cell refills its air supply.

- (a) Give a minimal state space for this problem (do not include extra information). You should answer for a general instance of the problem, not the specific map above.

Solution. The position of the insect as well as the number of units of air it has left, $s = (x, y, u_a) \in \{1, \dots, M\} \times \{1, \dots, N\} \times \{0, \dots, A\}$. The air supply is A in a free cell and drops to 0 after A moves through flooded cells.

- (b) Give the size of your state space.

Solution. $M \times N \times (A + 1)$, since the air left takes the $A + 1$ values $0, 1, \dots, A$.

¹Choosing a constant step cost $K > 1$ does not break admissibility in this case. If $K \in]0, 1[$, then $h(s)$ is not admissible but $Kh(s)$ is.


Exercise 3 Graph search

For each of the following search algorithms, apply the GRAPH-SEARCH algorithm (lecture 2, slide 62) to the undirected graph below and give the order in which the states are expanded, as well as the final path returned by the algorithm. Ties are broken by alphabetical order on the states and, between two nodes of the same state, in favour of the one inserted first in the fringe. The goal test is applied when a node leaves the fringe, so the goal state is returned without ever being expanded.

```

function GRAPH-SEARCH(problem, fringe) returns a solution, or failure
  closed  $\leftarrow$  an empty set
  fringe  $\leftarrow$  INSERT(MAKE-NODE(INITIAL-STATE[problem]), fringe)
  loop do
    if fringe is empty then return failure
    node  $\leftarrow$  REMOVE-FRONT(fringe)
    if GOAL-TEST(problem, STATE[node]) then return node
    if STATE[node] is not in closed then
      add STATE[node] to closed
      fringe  $\leftarrow$  INSERTALL(EXPAND(node, problem), fringe)
  end

```



(a) Depth-first search (DFS)

Solution. We use a Last-In First-Out (LIFO) fringe, *i.e.* a *stack*, to perform the search. In this stack, we keep track of the states that are reachable from the visited (closed) states. These states are annotated with the state they were expanded from, which allows to reconstruct the path at the end. At each step, the state at the *top* of the stack is *popped*. If it was not visited previously, it is expanded, which consists in *pushing* its neighbors to the *top* of the stack.

In the tables below, each row corresponds to one node leaving the fringe, the next one to leave being the rightmost. A node whose state is already closed is not inserted, and a node whose state gets closed while it waits in the fringe is discarded when it leaves it.

Fringe (LIFO stack)	Closed
S	
C(S) B(S) A(S)	S
C(S) B(S) B(A)	S A
C(S) B(S) E(B) D(B) C(B)	S A B
C(S) B(S) E(B) D(B)	S A B C
C(S) B(S) E(B) G(D) E(D)	S A B C D
C(S) B(S) E(B) G(D) G(E)	S A B C D E

Expansion: S, A, B, C, D, E. Path: S, A, B, D, E, G.

(b) Breadth-first search (BFS)

Solution. We use a First-In First-Out (FIFO) fringe, *i.e.* a *queue*, to keep track of the reachable states. At each step, the state at the *front* of the queue is popped. If it was not visited previously, it is expanded, which consists in pushing its neighbors to the *back* of the queue.

Fringe (FIFO queue)	Closed
S	
C(S) B(S) A(S)	S
B(A) C(S) B(S)	S A
E(B) D(B) C(B) B(A) C(S)	S A B
E(B) D(B) C(B) B(A)	S A B C
E(B) D(B) C(B)	S A B C
E(B) D(B)	S A B C
G(D) E(D) E(B)	S A B C D
G(E) G(D) E(D)	S A B C D E
G(E) G(D)	S A B C D E

Expansion: S, A, B, C, D, E. Path: S, B, D, G.

(c) Uniform-cost search (UCS)

Solution. The fringe is a *priority* queue. The priority of a node n in the queue is its cumulative cost $g(n)$.

Fringe (priority queue)	Closed
S(0)	
B(S, 4) C(S, 3) A(S, 1)	S
B(A, 6) B(S, 4) C(S, 3)	S A
B(A, 6) B(C, 5) B(S, 4)	S A C
D(B, 11) E(B, 9) B(A, 6) B(C, 5)	S A C B
D(B, 11) E(B, 9) B(A, 6)	S A C B
D(B, 11) E(B, 9)	S A C B
G(E, 29) D(B, 11) D(E, 10)	S A C B E
G(E, 29) G(D, 20) D(B, 11)	S A C B E D
G(E, 29) G(D, 20)	S A C B E D

Expansion: S, A, C, B, E, D. Path: S, B, E, D, G.

(d) Greedy search

Solution. The fringe is also a *priority* queue, but the priority of a node n in the queue is its *heuristic* cost $h(n)$.

Fringe (priority queue)	Closed
S(11)	
A(S, 20) B(S, 12) C(S, 10)	S
A(S, 20) B(C, 12) B(S, 12)	S C
A(B, 20) A(S, 20) E(B, 19) B(C, 12) D(B, 3)	S C B
A(B, 20) A(S, 20) E(D, 19) E(B, 19) B(C, 12) G(D, 0)	S C B D

Expansion: S, C, B, D. Path: S, B, D, G.

(e) A*

Solution. The priority of a node n is the *estimated* cost $f(n) = g(n) + h(n)$ of the cheapest solution through n .

- Is the heuristic admissible? If not, make it admissible.

Solution. A heuristic h is admissible if $0 \leq h(n) \leq h^*(n)$, where $h^*(n)$ is the true forward cost of n . In the graph, $h(E) = 19$ is larger than $h^*(E) = 11$, making h

non-admissible. This costs the optimal path: D is expanded before E and A* returns S, B, D, G, of cost 21, instead of S, B, E, D, G, of cost 20.

Setting $h(E) = 11$ is sufficient to make h admissible.

- ii. Is the heuristic consistent? If not, can we apply GRAPH-SEARCH?

Solution. A heuristic h is consistent if $h(n) \leq c(n, a, n') + h(n')$ for every node n and every successor n' generated by an action a . Because this graph is undirected, consistency requires $c(n, a, n') \geq |h(n) - h(n')|$ for every pair of neighbors, which does not hold here: $h(A) = 20 > c(A, a, S) + h(S) = 1 + 11$. Correcting $h(E)$ to 11 does not help, as this edge still violates the condition.

This is problematic as it could create situations where a node has been expanded within a path that is not optimal, and cannot be re-expanded later on within the optimal one. Hence, the algorithm loses its optimality.

Fortunately, there is a modification of GRAPH-SEARCH that can handle inconsistent heuristics. If we annotate the nodes in the closed set with the priority at which they were expanded, we can re-expand a node if it has a better (lower) priority than before. The priority in the closed set is then updated.

- iii. Apply A* with the admissible heuristic, using the variant of GRAPH-SEARCH that re-expands a closed state reached with a lower priority.


Solution. For readability, nodes that are already in the closed set with a lower priority are not added to the fringe. The re-expansion is shown in red.

Fringe (priority queue)	Closed
S(11)	
A(S, 21) B(S, 16) C(S, 13)	S(11)
A(S, 21) B(C, 17) B(S, 16)	S(11) C(13)
A(B, 29) A(S, 21) E(B, 20) B(C, 17) D(B, 14)	S(11) C(13) B(16)
A(B, 29) E(D, 23) G(D, 21) A(S, 21) E(B, 20) B(C, 17)	S(11) C(13) B(16) D(14)
A(B, 29) E(D, 23) G(D, 21) A(S, 21) E(B, 20)	S(11) C(13) B(16) D(14)
G(E, 29) A(B, 29) E(D, 23) G(D, 21) A(S, 21) D(E, 13)	S(11) C(13) B(16) D(14) E(20)
G(E, 29) A(B, 29) E(D, 23) G(D, 21) A(S, 21) G(D, 20)	S(11) C(13) B(16) D(13) E(20)

Expansion: S, C, B, D, E, D. Path: S, B, E, D, G.

Exercise 4 Search algorithms

Apply the GRAPH-SEARCH algorithm to the graph below, with the conventions of exercise 3.



- (a) Apply iterative deepening, with a depth limit growing from 1. In which order are the states expanded, which path is returned, and is it optimal?

Solution. With a depth limit of 1, S is expanded and generates A and G at depth 1. A leaves the fringe first (alphabetical order), is not a goal and cannot be expanded at the depth limit; G leaves the fringe next and passes the goal test.

Expansion: S. Path: S, G, of cost 12. It is not optimal, the cheapest path being S, A, C, G, of cost 4. Like breadth-first search, iterative deepening returns the shallowest goal, which is the cheapest one only when the path cost is non-decreasing with the depth.

- (b) Consider the following heuristics:

State	h_1	h_2
S	5	4
A	3	2
B	6	6
C	2	1
D	3	3
G	0	0

which one is not admissible? Why?

Solution. The heuristic h_1 is not admissible because the real cost from S to G is 4 which is smaller than 5.

- (c) Is the admissible heuristic consistent? Does it matter here?

Solution. No: $h_2(S) = 4 > c(S, a, A) + h_2(A) = 1 + 2$, so h_2 is admissible but not consistent. It does not matter on this graph, where no state is expanded before its cheapest path is found, so that graph-search A^* still returns the optimal path. Consistency is what guarantees this in general.

- (d) Apply A^* with the admissible heuristic.


Solution. Expansion: S, A, C. Path: S, A, C, G.

- (e) Which of these strategies are guaranteed to return the optimal path on this graph?

Solution. Uniform-cost search, and A^* with an admissible heuristic in tree search or a consistent one in graph search, since they order the fringe by cost. Depth-first search and greedy search give no guarantee. Breadth-first search and iterative deepening return the shallowest goal, S, G here, which is not the cheapest one because the step costs differ.

Exercise 5 Maze car (CS188, Spring 2014)

Consider a car agent which has to exit a maze. At all time-steps, the agent points at direction $d \in \{N, S, E, W\}$. With a single action, the agent can either move forward at an adjustable velocity $v \in [0, V]$ or turn. The turning actions are **left** and **right**, which change the agent's direction by 90 degrees. Turning is only permitted when the velocity is zero (and leaves it at zero). The moving actions are **faster** and **slower**. The action **faster** increments the velocity by 1 and **slower** decrements the velocity by 1; in both cases the agent then moves a number of squares equal to its *new* velocity. Any action that would result in a collision with a wall is illegal. Any action that would reduce v below 0 or above a maximum speed V is also illegal. The agent's goal is to find a plan which parks it (stationary) on the exit square using as few actions (time steps) as possible.



As an example, in the maze above, if the agent is initially stationary, it might first turn to the east using **right**, then move one square east using **faster**, then two more squares east using **faster** again. However, the agent will have to slow to take the turn.

- (a) For a grid of size $M \times N$, what is the size of the state space? Assume that all configurations are reachable from the starting state.

Solution. $N \times M \times 4 \times (V + 1)$

- (b) What is the maximum branching factor of this problem? Assume that illegal actions are simply not returned by the successor function.

Solution. The maximum branching factor is 3, and this happens when the agent is stationary. While stationary, it can take the following 3 actions: **faster**, **left**, **right**.

- (c) Is the Manhattan distance from the agent's location to the exit's location admissible?

Solution. No because it does not take the velocity of the agent into account. For instance, in a long straight path, the number of steps could be smaller than the number of squares.

- (d) If we used an inadmissible heuristic in A* tree search, could it change the completeness of the search? And the optimality?

Solution. With an inadmissible heuristic, A* will still find a final state if there exists a reachable one (complete), but it could stop the search before finding the optimal one (non optimal).

- (e) State and motivate a non-trivial admissible heuristic for this problem.

Solution. Some examples of admissible heuristics are:

- The Manhattan distance to the exit divided by the maximum speed V , since the agent covers at most V squares per action.
- The current velocity v , since the agent needs v actions of **slower** to park on the exit.
- The maximum of the two, $\max\{\frac{\text{Manhattan}}{V}, v\}$, which *dominates* both and is still admissible, as both are lower bounds on the true forward cost. Their *sum* is not admissible: two squares away from the exit at velocity $v = 2$, parking takes 2 actions (**slower** twice), while the sum gives $2/V + 2 > 2$.

- (f) Give a general advantage that an inadmissible heuristic might have over an admissible one.

Solution. The time to solve an A* tree search problem is a function of two factors: the number of nodes expanded, and the time spent per node.

- An inadmissible heuristic may be faster to compute, leading to a solution that is obtained faster due to less time spent per node.
- Admissible heuristics are sometimes too conservative (well below h^*). An inadmissible heuristic could be a better estimate of the true forward cost h^* (although it will overestimate at times), thus expanding fewer nodes.

We lose the guarantee of optimality by using an inadmissible heuristic. However, sometimes, we may be okay with finding a suboptimal solution faster.

Exercise 6 Imperfect heuristic (CS188, Spring 2019)

Consider a graph search problem where all edges have a unit cost and the optimal solution has cost C^* . Let $h(n)$ be a heuristic which is $\max\{h^*(n) - k, 0\}$, where $h^*(n)$ is the true forward cost of n and $k \leq C^*$ is a non-negative constant.

- (a) Is h admissible?

Solution. Yes. If $h^* \geq k$, $h^* - k \leq h^*$, otherwise $0 \leq h^*$.

- (b) Which of the following is the most reasonable description of how much more work will be done, *i.e.* how many more nodes will be expanded, with heuristic h compared to h^* , as a function of k ?

- ☐ Constant in k
- ☐ Linear in k


- Exponential in k
- Unbounded

Solution. A^* expands a node n when $f(n) = g(n) + h(n) \leq C^*$. With $h(n) = \max\{h^*(n) - k, 0\}$, this happens as soon as $g(n) + h^*(n) \leq C^* + k$, *i.e.* as soon as the cheapest path through n costs at most k more than the optimal one. Since all edges have a unit cost, such a path is at most k steps longer than the optimal path, and there are $O(b^k)$ of them in the worst case, for a branching factor b . The additional work is therefore exponential in k .


Exercise 7 Pacmen (Exam, January 2023)

Pacman and his friends have decided to combine forces and go on the offensive, and are now chasing ghosts! In a grid of size $M \times N$, Pacman and $P - 1$ of his friends are moving around to collectively eliminate all of the ghosts in the grid by stepping on the same square as each of them. Moving into the same square as a ghost will eliminate it from the grid. At every turn, Pacman and his friends may choose one of the four (**north**, **south**, **east**, **west**) actions but may not collide with each other. In other words, any action that would result in two or more Pacmen occupying the same square will result in no movement for either of the Pacmen. Additionally, Pacman and his friends are *indistinguishable* from each other. There are a total of G ghosts, which are also indistinguishable from each other and cannot move.

Treating this as a search problem, we consider each configuration of the grid to be a state, and the goal state to be the configuration where all ghosts have been eliminated from the board. The cost of each turn (all Pacmen move once) is 1. Below is an example starting state, as well as an example of goal state.



Initial state example



Final state example

Suppose that Pacman has no friends ($P = 1$).

- (a) What is the size of the minimal state space representation? Explain your answer.

Solution. The state s is fully described with the position of Pacman and a boolean for each ghost (eaten or not). The size of the state space is therefore $M \times N \times 2^G$. We don't need to save the position of the ghosts within the state because they never change.

- (b) Explain whether each of the following heuristics is admissible, consistent, neither, or both.

- $h_1(s)$ = the sum of the Manhattan distances from Pacman to every remaining ghost.
- $h_2(s)$ = the number of ghosts times the maximum Manhattan distance between Pacman and any of the ghosts.
- $h_3(s)$ = the number of remaining ghosts.

Solution. A heuristic h is admissible if $0 \leq h(s) \leq h^*(s)$, where $h^*(s)$ is the true forward cost of s . It is consistent if $h(s) \leq c(s, a, s') + h(s')$ for every successor $s' = \text{result}(s, a)$. Note that a non-admissible heuristic cannot be consistent.

In the following state s , $h_1(s) = 2+3+4 = 9$ and $h_2(s) = 3 \times 4 = 12$ are larger than $h^*(s) = 4$ (not admissible). Moving Pacman one cell to the right leads to s' , for which $h_1(s') = 6$ and

$h_2(s') = 3 \times 3 = 9$, so that $h_1(s) > c(s, a, s') + h_1(s') = 7$ and $h_2(s) > c(s, a, s') + h_2(s') = 10$ (not consistent).



Conversely, for any state s , $h_3(s)$ is a lower bound on the number of remaining turns (admissible) and a single action removes at most one ghost, so that $h_3(s) \leq c(s, a, s') + h_3(s')$ with $c(s, a, s') = 1$ (consistent).

Suppose that Pacman has exactly one less friend than the number of ghosts ($P = G$).

(c) What is the size of the minimal state space representation? Explain your answer.

Solution. The Pacmen are indistinguishable and occupy distinct squares, so a state is a *set* of P positions together with a boolean for each ghost: $\binom{MN}{P} \times 2^G$ states. Both $(M \times N)^P \times 2^G$, which distinguishes the Pacmen, and $2^{M \times N} \times 2^G$, which represents the Pacmen by one boolean per square and thus allows any number of them, are larger.

(d) Explain whether each of the following heuristics is admissible, consistent, neither, or both.

- $h_4(s)$ = the largest of the Manhattan distances between each Pacman and its closest ghost.
- $h_5(s)$ = the smallest of the Manhattan distances between each Pacman and its closest ghost.
- $h_6(s)$ = the number of remaining ghosts.
- $h_7(s)$ = the number of remaining ghosts divided by P .

Solution. Since P Pacmen move at every turn, up to P ghosts disappear per turn, which breaks the two heuristics that count turns as if a single Pacman were chasing.

- h_4 is not admissible, hence not consistent. Put two ghosts next to the same Pacman and the remaining Pacmen far away: two turns are enough ($h^* = 2$), while h_4 is the distance of the farthest Pacman to its closest ghost, which can be arbitrarily large.
- h_6 is not admissible either, hence not consistent. If every ghost is adjacent to a different Pacman, one turn ends the game ($h^* = 1$) while $h_6 = G > 1$.
- h_5 is admissible, as some Pacman must reach the ghost closest to it, which takes at least $h_5(s)$ turns, and consistent, as a turn changes each distance by at most 1.
- h_7 is admissible, as at least G/P turns are needed to eliminate G ghosts, and consistent, as a turn decreases the number of remaining ghosts by at most P .

QUIZ

1. An agent is rational if ...

- ☐ its actions always lead to the best possible outcome.
- ☐ it knows the state s_t of the environment at all times.
- ☒ its policy maximizes $\mathbb{E}[V(s_{1:T}) \mid \pi]$, given its percepts and prior knowledge.
- ☐ it maximizes the performance measure that its designer had in mind.

2. As a task environment, poker is ...

- ☐ discrete, multi-agent and deterministic.
- ☒ partially observable, stochastic and multi-agent.
- ☐ partially observable, episodic and single-agent.
- ☐ None of the above.

3. In a stochastic environment, a simple reflex agent ($a_t = \pi(e_t)$) given the same percept twice will ...
 - ☒ take the same action every time.
 - ☐ take a different action every time.
 - ☐ take a different action most of the time.
 - ☐ take the same action most of the time.
4. A goal-based agent ...
 - ☐ selects its action from the current percept e_t only.
 - ☒ searches its transition model for an action sequence that reaches a state of G .
 - ☐ prefers a fast and safe route over a slow and risky one.
 - ☐ maximizes the expected performance $\mathbb{E}[V(s_{1:T}) \mid e_{1:t}, a_t]$ of its actions.
5. The A* algorithm, in its graph version (GRAPH-SEARCH, without re-expansion) is ...
 - ☐ always optimal.
 - ☐ always optimal if the heuristic is admissible.
 - ☒ always optimal if the heuristic is consistent.
 - ☐ never optimal when there are cycles.
6. Which of the following statements about heuristics is true?
 - ☐ $h(n) = 0 \ \forall n$ can speed up A* compared to UCS.
 - ☐ If a heuristic is admissible, it is guaranteed to be consistent.
 - ☐ The average step cost $h(n) = \frac{1}{|\text{actions}(n)|} \sum_a c(n, a, \text{result}(n, a))$ is admissible.
 - ☒ The true remaining cost dominates all admissible heuristics.
7. Iterative deepening is often preferred to breadth-first search because it ...
 - ☐ expands strictly fewer nodes.
 - ☒ finds a solution at the same depth d with $O(bd)$ memory, instead of $O(b^d)$.
 - ☐ is optimal even when the step costs differ.
 - ☐ never expands the same state twice.
8. In GRAPH-SEARCH, keeping a closed set ...
 - ☒ makes depth-first search complete on a finite state space.
 - ☐ makes any admissible heuristic consistent.
 - ☐ guarantees that A* is optimal whenever h is admissible.
 - ☐ is only useful when the state space is infinite.