

Deep Learning

Lecture 0: Introduction

Prof. Gilles Louppe
g.louppe@uliege.be



Why learning?



What do you see?



Sheepdog or mop?



Chihuahua or muffin?


The (human) brain is so good at interpreting visual information that the **gap** between raw data and its semantic interpretation is difficult to assess intuitively:



This is a mushroom.



This is a mushroom.



This is a mushroom.

```
array([[[0.03921569, 0.03529412, 0.02352941, 1.        ],
       [0.2509804 , 0.1882353 , 0.20392157, 1.        ],
       [0.4117647 , 0.34117648, 0.37254903, 1.        ],
       ...,
       [0.20392157, 0.23529412, 0.17254902, 1.        ],
       [0.16470589, 0.18039216, 0.12156863, 1.        ],
       [0.18039216, 0.18039216, 0.14117648, 1.        ]],

      [[0.1254902 , 0.11372549, 0.09411765, 1.        ],
       [0.2901961 , 0.2509804 , 0.24705882, 1.        ],
       [0.21176471, 0.2       , 0.20392157, 1.        ],
       ...,
       [0.1764706 , 0.24705882, 0.12156863, 1.        ],
       [0.10980392, 0.15686275, 0.07843138, 1.        ],
       [0.16470589, 0.20784314, 0.11764706, 1.        ]],


      [[0.14117648, 0.12941177, 0.10980392, 1.        ],
       [0.21176471, 0.1882353 , 0.16862746, 1.        ],
       [0.14117648, 0.13725491, 0.12941177, 1.        ],
       ...,
       [0.10980392, 0.15686275, 0.08627451, 1.        ],
       [0.0627451 , 0.08235294, 0.05098039, 1.        ],
       [0.14117648, 0.2       , 0.09803922, 1.        ]],

      ...]
```


This is a mushroom.

Writing a computer program that sees?









Extracting semantic information requires models of **high complexity**, which cannot be designed by hand.

However, one can write a program that **learns** the task of extracting semantic information.



Techniques used in practice consist of:

- defining a parametric model with high capacity,
- optimizing its parameters, by "making it work" on the training data.

This is similar to **biological systems** for which the model (e.g., brain structure) is DNA-encoded, and parameters (e.g., synaptic weights) are tuned through experiences.

Deep learning encompasses software technologies to **scale-up** to billions of model parameters and as many training examples.

Applications and successes



YOLOv3



Watch later



Share



Real-time object detection (Redmon and Farhadi, 2018)



ICNet for Real-Time Semantic Segmentation ...



Watch later



Share



Segmentation (Hengshuang et al, 2017)



Realtime Multi-Person 2D Human Pose Estim...



Watch later

Share



Pose estimation (Cao et al, 2017)



Google DeepMind's Deep Q-learning playing A...



Watch later



Share



Reinforcement learning (Mnih et al, 2014)



AlphaStar Agent Visualisation



Watch later Share



Strategy games (Deepmind, 2016-2018)



Google's DeepMind AI Just Taught Itself To W...



Watch later



Share



Learning to walk (2017)



NVIDIA Autonomous Car



Watch later



Share



Autonomous cars (NVIDIA, 2016)



Full Self-Driving



Watch later



Share



Autopilot (Tesla, 2019)



Tesla Autopilot Predicts Car Crash before it h...



Watch later



Share



... while preventing accidents.



Watch later



Share



So, that one change that particular breakthrough increased
recognition rates by approximately thirty percent, that's a big
deal.
That's the difference between going

Recognizability: 98%

Speech recognition, translation and synthesis (Microsoft, 2012)




NeuralTalk and Walk, recognition, text descrip...

a row of bikes parked next to each other



Watch later

Share



Auto-captioning (2015)




Google Assistant will soon be able to call rest...



Watch later



Share



Speech synthesis and question answering (Google, 2018)



Artistic style transfer for videos



Watch later



Share

Sintel movie, III



Artistic style transfer (Ruder et al, 2016)



A Style-Based Generator Architecture for Gen...



Watch later



Share



Image generation (Karras et al, 2018)



GTC Japan 2017 Part 9: AI Creates Original M...



Watch later



Share



Music composition (NVIDIA, 2017)



Behind the Scenes: Dali Lives



Watch later



Share




Dali Lives (2019)



*"ACM named **Yoshua Bengio**, **Geoffrey Hinton**, and **Yann LeCun** recipients of the **2018 ACM A.M. Turing Award** for conceptual and engineering breakthroughs that have made deep neural networks a critical component of computing."*

Why does it work now?

Algorithms (old and new)



More data



Software



theano



Faster compute engines



Building on the shoulders of giants


Five decades of research in machine learning provided

- a taxonomy of ML concepts (classification, generative models, clustering, kernels, linear embeddings, etc.),
- a sound statistical formalization (Bayesian estimation, PAC),
- a clear picture of fundamental issues (bias/variance dilemma, VC dimension, generalization bounds, etc.),
- a good understanding of optimization issues,
- efficient large-scale algorithms.


Deep learning

From a practical perspective, deep learning


- lessens the need for a deep mathematical grasp,
- makes the design of large learning architectures a system/software development task,
- allows to leverage modern hardware (clusters of GPUs),
- does not plateau when using more data,
- makes large trained networks a commodity.




	TFlops (10^{12})	Price	GFlops per \$
Intel i7-6700K	0.2	\$344	0.6
AMD Radeon R7 240	0.5	\$55	9.1
NVIDIA GTX 750 Ti	1.3	\$105	12.3
AMD RX 480	5.2	\$239	21.6
NVIDIA GTX 1080	8.9	\$699	12.7



The typical cost of a 4Tb hard disk is less than 100 USD (February 2020).



AlexNet to AlphaGo Zero: A 300,000x Increase in Compute (Log Scale)



1 petaflop/s-day
= 10^{15} neural net operations per second for one day
= 10^{20} operations
 ≈ 100 GPUs for one day
 $\approx 500\text{kWh}$

The end.

References

- LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *nature*, 521(7553), 436-444.