Z80 is the sole SRAM address/write master(/BUSAK_N). Pico injects instructions with SRAM reads inhibited(/BUSACK_N) directly joins Pico and Z80 at 3.3V.

MEMORY BOARD

CORE BOARD

PERIPHERAL BOARD

RESET_N

[BOOT_READ_DISABLE BOOT_READ_DISABLE_5V IO_RESET_N]

ADDRESS

DATA

PICO_DATA

HCT_TO_CPU

PICO_TO_BUFFER

CPU_TO_BUFFERS

BUFFERED_CONTROLS

HCT_TO_SRAM

CPU_MONITOR

PICO_MONITOR

PORT_MONITOR

DATA_CONTROL

R17 R18 R19 R20 R21 R22 R23

10k

C1 C2 C3 C4 C5 C6 C7 C8 C9 C10 C11

100n

22µ

RN1 RN2 RN3 RN4

8x10k isolated

Native KiCad 10 schematic generated from the verified README pin map

Z80ROMlessSBC

Sheet: /

File: z80_romless_sbc.kicad_sch

Title: Z80ROMlessSBC — Exact Breadboard Electrical Schematic

Size: A0 | Date: 2026-08-23 | Rev: 1

KiCad 10.0.1 | Id: 1/1