CRM

Metric	Description / calculation	Required table(s)	Required fields in the CRM DB
crm_deals_open	Count deals whose current stage is qualification, discover, propose, or negotiate.	crm.deals	id, organization_id, stage; created_at for period filtering; contact_id for per-contact calculation
crm_deals_won	Count deals whose current stage is closed_won.	crm.deals	id, organization_id, stage; closed_at for closure-period filtering; contact_id for per-contact calculation
crm_deals_lost	Count deals whose current stage is closed_lost.	crm.deals	id, organization_id, stage; closed_at for closure-period filtering; contact_id for per-contact calculation
crm_inbound_emails_count	Count contact activities where type = 'email' and email_direction = 'inbound'.	crm.contact_activities	id, organization_id, contact_id, type, email_direction; created_at for period filtering
crm_calls_count	Count activities where type = 'call' across contact and deal activities.	crm.contact_activities, crm.deal_activities; crm.deals only when resolving a deal activity to a contact	Both activity tables: id, organization_id, type, created_at. Contact activity: contact_id. Deal activity: deal_id. Per-contact join: crm.deals.id, crm.deals.contact_id

crm_meetings_count	Count activities where type = 'meeting' across contact and deal activities. Appointments are excluded to avoid mixing the separate appointment KPI into this metric.	crm.contact_activities, crm.deal_activities; crm.deals only when resolving a deal activity to a contact	Both activity tables: id, organization_id, type, created_at. Contact activity: contact_id. Deal activity: deal_id. Per-contact join: crm.deals.id, crm.deals.contact_id
crm_tasks_count	Count activities where type = 'task' across contact and deal activities. Use task_status only when the metric must be split into open, in-progress, or completed tasks.	crm.contact_activities, crm.deal_activities; crm.deals only when resolving a deal activity to a contact	Both activity tables: id, organization_id, type, created_at. crm.contact_activities. task_status is available. Contact activity: contact_id. Deal activity: deal_id. Per-contact join: crm.deals.id, crm.deals.contact_id
crm_appointments_booked_count	Count appointment records by their booking/creation time. For “currently scheduled” appointments, additionally filter status = 'scheduled'.	crm.appointments	id, organization_id, contact_id, created_at, status
crm_appointments_completed_count	Count appointments where status = 'completed'; use completed_at for the completion reporting period.	crm.appointments	id, organization_id, contact_id, status, completed_at
crm_quotes_sent_count	Count quotes with a non-null sent_at. This continues to count a quote after its current status	crm.quotes	id, organization_id, deal_id, sent_at; status for optional current-status

	changes from sent to accepted or rejected.		reporting. Per-contact join: crm.deals.id, crm.deals.contact_id
crm_invoices_issued_count	Count invoices with a non-null issue_date.	crm.invoices	id, organization_id, issue_date; status for optional current-status reporting; deal_id or order_id for customer/deal attribution
crm_orders_count	Count stored sales orders. If only business-confirmed orders should count, filter status to confirmed or fulfilled and use confirmed_at for the reporting period.	crm.sales_orders	id, organization_id, contact_id, status, created_at, confirmed_at
crm_last_order_total	Select the most recent applicable sales order and return its total. For confirmed orders, order by confirmed_at; otherwise use created_at.	crm.sales_orders	id, organization_id, contact_id, total, currency, status, confirmed_at, created_at
crm_total_won_revenue	Sum amount for deals where stage = 'closed_won'. Use closed_at for a closure-period calculation.	crm.deals	organization_id, stage, amount, closed_at; contact_id for per-contact calculation
crm_largest_deal_value	Return the maximum non-null amount among the deals in scope.	crm.deals	organization_id, amount; stage for an optional stage filter; created_at for period filtering; contact_id for per-contact calculation

Campaign

Metric	Description / calculation	Required table(s)	Required fields in the campaign DB
cmp_total_campaigns_sent_count	Count distinct campaigns that have at least one send batch with status = 'sent'.	campaign.campaign_send_batches	organization_id, campaign_id, status
cmp_messages_sent_count_l15	Count recipient rows with status = 'sent' during the last 15 days.	campaign.campaign_send_recipients	id, organization_id, campaign_id, contact_id, status; updated_at is the available time proxy
cmp_messages_failed_count	Count recipient rows with status = 'failed'.	campaign.campaign_send_recipients	id, organization_id, campaign_id, contact_id, status, skip_fail_reason; updated_at for an approximate failure period
cmp_engagement_rate	Unique engagement rate: sent recipient rows having either opened_at or clicked_at, divided by sent recipient rows, multiplied by 100.	campaign.campaign_send_recipients	id, organization_id, campaign_id, contact_id, status, opened_at, clicked_at

cmp_open_rate	Sent recipient rows with a non-null opened_at, divided by sent recipient rows, multiplied by 100.	campaign.campaign_send_recipients	id, organization_id, campaign_id, contact_id, status, opened_at
cmp_click_rate	Sent recipient rows with a non-null clicked_at, divided by sent recipient rows, multiplied by 100.	campaign.campaign_send_recipients	id, organization_id, campaign_id, contact_id, status, clicked_at
cmp_click_to_open_rate	Sent recipient rows with a non-null clicked_at, divided by sent recipient rows with a non-null opened_at, multiplied by 100. Return null when there are no opened rows.	campaign.campaign_send_recipients	id, organization_id, campaign_id, contact_id, status, opened_at, clicked_at

cmp_channels_targeted	Count distinct configured channel values in the selected organization or campaign.	campaign.campaign_channels	organization_id, campaign_id, channel; status when only ready/scheduled channel configurations should count
cmp_days_since_last_open	Calculate the number of days between the current date/time and the latest non-null opened_at in scope.	campaign.campaign_send_recipients	organization_id, campaign_id, contact_id, opened_at
cmp_avg_opens_per_send	Sum open_count for sent recipient rows and divide by the number of sent recipient rows.	campaign.campaign_send_recipients	id, organization_id, campaign_id, contact_id, status, open_count
cmp_avg_clicks_per_send	Sum click_count for sent recipient rows and divide by the number of sent recipient rows.	campaign.campaign_send_recipients	id, organization_id, campaign_id, contact_id, status, click_count

CCaaS

CCAAS-Views	Description / calculation	Required table(s)	Required fields in the CCaaS DB
cca_conversations_count_l15	Count conversations whose created_at falls within the last 15 days.	ccass.conversations	id, organization_id, contact_id, created_at
cca_conversations_resolved	Count conversations with a non-null resolved_at. This retains the resolved event even if the current status later changes to closed.	ccass.conversations	id, organization_id, contact_id, resolved_at; status for optional current-status reporting
cca_messages_inbound-l15	Count messages where direction = 'inbound' and created_at falls within the last 15 days.	ccass.conversation_messages, ccass.conversations	Message table: id, organization_id, conversation_id, direction, created_at. Conversation table for per-contact calculation: id, contact_id
cca_messages_outbound-l15	Count messages where direction = 'outbound' and created_at falls within the last 15 days.	ccass.conversation_messages, ccass.conversations	Message table: id, organization_id, conversation_id, direction, created_at. Conversation table for per-contact calculation: id, contact_id

cca_handoff_rate	Count conversations with a non-null handoff_reason, divide by all conversations in scope, and multiply by 100.	ccass.conversations	id, organization_id, contact_id, handoff_reason; created_at for period filtering
cca_missed_contacts	Count missed-contact records.	ccass.agent_missed_contacts	id, organization_id, contact_id, conversation_id, channel, reason, missed_at
cca_callback_attempts	Count proactive callback-attempt records. Optionally group or filter by their current status.	ccass.proactive_callback_attempts	id, organization_id, contact_id, conversation_id, missed_contact_id, status, created_at
cca_avg_conversation_duration_min	Average the elapsed minutes between created_at and ended_at for conversations having a non-null ended_at.	ccass.conversations	id, organization_id, contact_id, created_at, ended_at
cca_negative_sentiment_rate	For each conversation, select its latest analyzed sentiment turn. Divide conversations whose latest customer_label is negative or very_negative by conversations having an analyzed sentiment, then multiply by 100.	ccass.conversation_sentiment_turns, ccass.conversations	Sentiment table: id, organization_id, conversation_id, customer_label, customer_score, created_at. Conversation table for per-contact calculation: id, contact_id

cca_last_channel	Return channel from the most recent conversation in scope.	ccass.conversations	id, organization_id, contact_id, channel, created_at
cca_last_sentiment	Return the latest available customer sentiment label and score, ordered by the sentiment turn's created_at.	ccass.conversation_sentiment_turns, ccass.conversations	Sentiment table: id, organization_id, conversation_id, customer_label, customer_score, created_at. Conversation table for per-contact calculation: id, contact_id
cca_last_handoff_reason	Return the latest non-null conversation handoff_reason.	ccass.conversations	id, organization_id, contact_id, handoff_reason, created_at; transferred_at when populated
cca_last_disposition_code	Return the disposition_code from the latest conversation having a non-null code.	ccass.conversations	id, organization_id, contact_id, disposition_code, created_at
cca_last_resolution_summary	Return the resolution_summary from the latest conversation having a non-null summary.	ccass.conversations	id, organization_id, contact_id, resolution_summary, resolved_at, created_at
cca_last_conversation_at	Return the maximum conversation created_at in scope.	ccass.conversations	organization_id, contact_id, created_at

cca_channels_used	Count distinct non-null conversation channels in scope.	ccass.conversations	organization_id, contact_id, channel
cca_preferred_channel	Return the most frequently used conversation channel in scope. For a frequency tie, choose the channel used by the latest conversation.	ccass.conversations	id, organization_id, contact_id, channel, created_at

WebTracking

#	Metric	Description	Calculation / Source	Required Table
1	`total_sessions`	Total distinct browsing sessions for the visitor on the website	`uniqExact(session_id)` grouped by `visitor_id`, `website_id`	`dim_sessions`
2	`avg_session_duration`	Average length of a session in seconds	`avg(duration_seconds)` per visitor	`dim_sessions`
3	`bounce_rate`	Percentage of sessions with only one page view	`countIf(is_bounce = 1 AND pageview_count > 0) / countIf(pageview_count > 0) * 100`	`dim_sessions`
4	`last_entry_page`	Landing page of the visitor's most recent session	`argMax(entry_page, started_at)`	`dim_sessions` / `fact_page_views`
5	`last_exit_page`	Last page viewed in the visitor's most recent session	`argMax(page_path, created_at)` for latest session	`fact_page_views`

6	`top_pages_viewed`	Pages viewed most frequently by the visitor	Group by `page_path`, count views, order by count DESC	`fact_page_views`
7	`products_viewed`	Products the visitor interacted with	Group by `product_id`, `product_name`	`fact_product_interactions`
8	`product_categories_viewed`	Product categories viewed by the visitor	`SELECT DISTINCT product_category`	`fact_product_interactions`
9	`conversions_count`	Number of conversion/goal events	`count()` on conversion events	`fact_conversion_events`
10	`total_conversion_value`	Total monetary/scored value of conversions	`sum(value)`	`fact_conversion_events`
11	`last_utm_source`	UTM source from the visitor's latest attributed session	`argMax(utm_source, started_at)`	`dim_sessions`

12	`last_utm_campaign`	UTM campaign from the visitor's latest session	`argMax(utm_campaign, started_at)`	`dim_sessions`
13	`last_device`	Device type from the latest session	`argMax(device, started_at)`	`dim_sessions`
14	`last_country`	Country from the latest session/event	`argMax(country, started_at)`	`dim_sessions` / `fact_page_views`
15	`rage_clicks_count`	Number of rage-click frustration events	`countIf(event_type = 'rage_click')`	`fact_interaction_events`
16	`days_since_last_visit`	Number of days since the visitor's last activity	`dateDiff('day', max(last_seen_at), today())`	`dim_visitors` / `fact_page_views`
17	`avg_time_on_page`	Average time spent on a page in seconds	`avg(time_on_page_sec)` where value > 0	`fact_page_views`
18	`max_scroll_depth`	Maximum scroll depth reached by the visitor	`max(max_scroll_depth / scroll_depth)`	`fact_page_views` / `fact_interaction_events`

#	Metric	Description	Calculation	Required Table
1	`web_total_sessions`	Distinct sessions in the last 15 days	`uniqExact(session_id)`	`dim_sessions`
2	`web_total_pageviews_l15`	Total page views in the last 15 days	`count()`	`fact_page_views`
3	`web_clicks`	Standard clicks in the last 15 days	`countIf(event_type = 'click')`	`fact_interaction_events`
4	`web_form_submissions`	Form submissions in the last 15 days	`countIf(event_type = 'form_submit')`	`fact_form_events`
5	`web_avg_session_duration_sec`	Average session duration in the last 15 days	`avg(duration_seconds)`	`dim_sessions`

6	`web_avg_scroll_depth`	Average scroll depth in the last 15 days	`avg(max_scroll_depth)` excluding zeros	`fact_page_views`
7	`web_bounce_rate`	Bounce rate in the last 15 days	Bounce formula using `is_bounce` and `pageview_count`	`dim_sessions`

Ticketing

Metric	Description / calculation	Required table(s)	Required fields in the ticketing DB
total_tickets_last30days	Count tickets whose created_at falls within the last 30 days.	ticketing.tickets	id, organization_id, customer_id, created_at
tickets_open	Count tickets whose current status is non-terminal. Join the ticket status to the organization-specific status definition and filter is_terminal = false.	ticketing.tickets, ticketing.ticket_statuses	Tickets: id, organization_id, customer_id, status. Status definitions: organization_id, status, is_terminal, active
tickets_resolved	Count tickets with a non-null resolved_at.	ticketing.tickets	id, organization_id, customer_id, resolved_at
tickets_reopened	Count distinct tickets having an audit event where action = 'ticket.status_changed' and meta ->> 'to' = 'Reopened'.	ticketing.audit_events	id, organization_id, ticket_id, action, meta, created_at
tickets_overdue	Count tickets whose due_at is earlier than the current time and whose current status is non-terminal.	ticketing.tickets, ticketing.ticket_statuses	Tickets: id, organization_id, customer_id, status, due_at. Status definitions: organization_id, status, is_terminal

tickets_by_priority_urgent	Count tickets where the text value in priority is urgent.	ticketing.tickets	id, organization_id, customer_id, priority; created_at for period filtering
portal_logins_last15_days	Count customer portal sessions created during the last 15 days.	ticketing.customer_portal_sessions	id, organization_id, customer_id, created_at
avg_resolution_hours	Average the elapsed hours between created_at and resolved_at for tickets having a non-null resolved_at.	ticketing.tickets	id, organization_id, customer_id, created_at, resolved_at
avg_csat_score	Average non-null ticket csat_score values in scope.	ticketing.tickets	id, organization_id, customer_id, csat_score, csat_rated_at
last_csat_score	Return the csat_score from the latest ticket having both a score and rating timestamp, ordered by csat_rated_at descending.	ticketing.tickets	id, organization_id, customer_id, csat_score, csat_rated_at
resolution_rate	Divide tickets with a non-null resolved_at by all tickets in scope and multiply by 100.	ticketing.tickets	id, organization_id, customer_id, resolved_at; created_at for cohort or period filtering

reopen_rate	Divide distinct tickets having a recorded transition to Reopened by distinct tickets having a recorded transition to Resolved, then multiply by 100.	ticketing.audit_events	organization_id, ticket_id, action, meta, created_at
sla_breach_rate	Resolution-deadline proxy: count tickets that resolved after due_at, plus unresolved non-terminal tickets currently past due_at; divide by tickets having a non-null due_at and multiply by 100.	ticketing.tickets, ticketing.ticket_statuses	Tickets: id, organization_id, customer_id, status, due_at, resolved_at. Status definitions: organization_id, status, is_terminal
dominant_ticket_category	Return the most frequent non-null category in scope. Define a deterministic tie-breaker, such as the category used by the latest ticket.	ticketing.tickets	id, organization_id, customer_id, category, created_at
last_ticket_at	Return the maximum ticket created_at in scope.	ticketing.tickets	organization_id, customer_id, created_at
last_resolved_at	Return the maximum non-null ticket resolved_at in scope.	ticketing.tickets	organization_id, customer_id, resolved_at
days_since_last_ticket	Calculate elapsed days between the current date/time and the	ticketing.tickets	organization_id, customer_id, created_at

	maximum ticket created_at in scope.		
priority_mix	Group tickets by priority and return each priority's count or percentage of all tickets in scope.	ticketing.tickets	id, organization_id, customer_id, priority
channel_mix	Group tickets by channel and return each channel's count or percentage of all tickets in scope.	ticketing.tickets	id, organization_id, customer_id, channel
csat_response_rate	Divide tickets with a non-null csat_score by resolved tickets in scope, then multiply by 100.	ticketing.tickets	id, organization_id, customer_id, csat_score, csat_rated_at, resolved_at