基于集成学习与条件 Copula 的啤酒风味预测及受约束风格迁移

摘 要

本文研究啤酒感官预测、关键化合物分析和风格迁移，重点处理化学测量缺失、成分相关性强及部分风格样本较少的问题。按啤酒编号核对附件，选取 250 款啤酒的 45 项感官属性作为研究对象；第一、二问使用 231 维化学输入，第三问使用 69 项校准量与 157 项相对量。现有感官标签为标准化连续值，无法从附件恢复原始 0—6 评分，故在给定尺度上建模和评价。

第一问采用训练折中位数补值、缺失指示与多输出 ExtraTrees，五折折外 MAE 为 0.3409、RMSE 为 0.4862、宏平均 R^2 为 0.2146，RMSE 较均值基线降低 15.36%；额外随机隐藏 20%测试特征后，RMSE 增加 2.67%。第二问复核附件相关矩阵后采用 Spearman 相关，在绝对相关阈值 0.7 下得到 231 个节点、109 条边，并为 45 项感官属性选出 135 个 Top-3 关联位置。200 次 Bootstrap 中仅 14 个位置的入选频率达到 0.8，去风格均值后 21 项感官的 Top-3 完全变化。

第三问比较收缩 Copula、局部边缘 Copula 和平滑混合，通过嵌套验证选择生成方法。Kriek、Lambic 的能量差异较基准分别降低 20.5%、23.4%，Tripel 略有变差；三种目标风格共生成 900 条化学谱并预测感官画像。Pils/Lager 向 Tripel 迁移时，同时限制四项缺陷浓度和 Stale hops 预测增量。固定树、中央候选池的余量优先方案有 10/11 款通过模型检查，所选化学谱到目标风格的距离缩短幅度中位数为 57.74%；几何优先的探索性方案为 70.08%。由于 Stale hops 跨风格预测仍弱，上述结果有待新样本检测和盲品验证。

关键词：啤酒风味；多输出预测；关联网络；条件 Copula；受约束迁移

目 录

1 问题重述.....1
2 数据核验与统一处理.....1
3 问题分析与技术路线.....2
4 模型假设与符号.....3
5 缺失条件下的感官预测.....4
5.1 预测目标与评分量尺.....4
5.2 折内缺失处理与多输出 ExtraTrees.....5
5.3 折外验证与模型比较.....5
5.4 缺失压力与极端外推诊断.....6
5.5 逐维表现与应用边界.....7
5.6 补充对照与未见风格验证.....7
6 化合物关联网络与关键候选.....9
6.1 Spearman 关联网络.....9
6.2 感官 Top-3 候选与重抽样稳定性.....9
6.3 方法与风格敏感性.....10
6.4 化学依据与解释边界.....11
6.5 折外置换与预测依赖.....12
7 风格条件生成与受约束迁移.....14
7.1 混合化学表示与高斯秩映射.....14
7.2 共享信息的条件 Copula 基准.....14
7.3 局部边缘 Copula 与平滑混合.....14
7.4 嵌套选择、生成质量与感官画像.....15
7.5 距离、支持域与中央候选池.....17
7.6 化学阈值与最低改善要求.....17
7.7 Stale hops 预测及 beer 81 误差诊断.....19
7.8 配对预测筛选与留出模型复核.....19
7.9 两种排序的迁移结果.....20
7.10 方案选择与后续验证.....21
8 结果检验与模型评价.....21
9 结论与建议.....22
参考文献.....23
使用声明.....24
附录 A 感官字段及逐维精度.....25
附录 B 完整 Top 3 候选.....27
附录 C 逐源迁移检查.....46
附录 D 软件环境与运行方法.....52
附录 E 完整计算机源程序.....54

1 问题重述

啤酒的香气与风味由多类化合物共同形成，原料、发酵和陈化过程都会改变其组成。化学成分与感官强度并非一一对应，混合物作用及风格差异增加了预测和解释的难度。本题以原研究的商用啤酒化学测量、训练品评及相关数据[1]为基础，要求完成评分预测、关键化合物分析和风格生成。

第一问保留化学测量存在缺失的样本，预测 Aroma 与 Flavour 属性。题目要求 0—6 评分，而实际监督标签已标准化，需先核实评分量尺。第二问利用化合物相关矩阵构建网络，为每项感官属性选择 Top-3 候选，并检验其稳定性和化学依据。

第三问生成 Tripel、Kriek 和 Lambic 的化学谱及感官画像，再将 Pils/Lager 向 Tripel 迁移，限制 DMS、Diacetyl、4VG、trans-2-nonenal 和 Stale hops 等缺陷恶化。评价包括生成分布质量、目标风格接近度和逐款约束检查。

2 数据核验与统一处理

2.1 样本范围与感官目标

对附件逐表读取并按 beer 核对，附件 1、4、7 均包含 250 个唯一啤酒编号，覆盖 22 个风格。附件 1 除三个身份或类别字段外有 231 个数值特征；附件 4 有 50 项感官属性，依据附件 8 的名称字典，选取 Aroma 15 项与 Taste 30 项，共 45 项作为本题目标，排除 alcohol、aftertaste、body、co2 和 overall。Tripel、Kriek、Lambic 和 Pils/Lager 分别有 28、10、11 和 11 款。题面背景的 226 款与实际文件不一致，本文以可一一核对的 250 款为计算样本，不按文字数量截断。

表 2-1 主要附件的实际范围及用途

附件	实际数据范围	本文用途
1.csv	250 款 × 231 个数值特征	第一问输入与第二问候选分析
2.csv	231 × 231 相关矩阵	化合物关联网络与数值复核
3.xlsx	12 张评分卡及汇总公式	确定评分规则与名称映射
4.csv	250 款 × 50 个感官属性	筛选 45 维连续监督目标
5.csv 与 6.csv	50 × 50 及 44 × 50	描述性矩阵核验，不作折外筛选先验
7.csv	250 款 × 186 个描述词变量	辅助诊断，未作为生成谱的预测输入
8.xlsx	校准量、阈值及名称等工作表	字段、单位与化学阈值核实

按 beer 编号一对一关联各表。附件 4、7 的条码均只剩 96 个不同值，不能作为主键；编号和条码也不作为模型输入。附件 3 的 12 张评分卡均未填写，汇总公式的缓存零值不算实测评分。

2.2 缺失值、尺度与异常值

附件 1 有 73 个化学缺失单元，占 250×231 的 0.1264%，分布于 9 列、63 款酒（25.2%样本），最高单列缺失率为 10.8%。保留全部 250 款，仅用训练数据估计补值参数。45 项感官目标均无缺失。化学表包含对数或相对测量及理化量，负值不能一律删除，各列也不能统一取指数还原浓度。

与附件 8 校准量对照，37 个基础字段在有效比较范围内符合以 10 为底的对数关系，零值曾以最小正值的一半替代；其余重叠 GC-MS 字段不满足统一直接 log10 关系。第一、二问保留给定数值表示；第三问删除五项汇总或派生量，并以 69 项匹配校准字段替换，形成 69 维校准量与 157 维相对量的 226 维混合表示。校准数据中的 3 个负值转为缺失，混合表共保留 72 个缺失单元。相对量没有统一浓度单位，化学阈值只在核实过的校准字段上执行。

极端观测通过定位和模型对照处理。beer 156 的输入极值影响线性外推，beer 81 的高 Stale hops 评分难以由化学近邻解释，均未发现足以删除记录的证据。原始附件保留不变，处理过程和结果来源另存核验记录。

2.3 相关矩阵及信息边界

对附件 2 逐对复算 Spearman 相关，最大绝对差为 6.66×10^{-16}；与 Pearson 的差异明显。因此，本文依据附件矩阵采用 Spearman 相关，题面所述 Pearson 相关与该矩阵不符。附件 5、6 也可由对应样本的 Spearman 相关复现。附件 6 实际仅 44 个化学指标，不代替完整化学数据。

附件 2、5、6 均由本批样本导出，用于描述性分析；预测交叉验证前不使用这些矩阵或附件 8 的 GBM 重要性、SHAP 筛选变量。论坛表缺少评论全文、时间和批次信息，无法补充真实品评标签。

3 问题分析与技术路线

三问使用同一套样本键和字段字典，评价对象各有不同：第一问评价真实啤酒样本的折外预测误差；第二问分析本批样本的关联与风格混杂；第三问检验生成分布，再搜索满足约束的迁移谱。

预测采用多输出树，并与均值和岭回归比较；解释采用可直接复算的秩相关；生成采用经验边缘与收缩依赖结构。迁移先检查化学浓度与训练支持范围，再检查预测缺陷变化，比较接近目标风格的程度与满足保护约束之间的取舍。




图 1 三问的数据处理、模型与验证流程。第一问使用 231 维原表示；第三问使用 69 维校准量与 157 维相对量组成的 226 维混合表示。迁移训练排除全部 11 款 Pils。

第一问采用随机五折；生成方法在训练集内选择，再由外层留出数据评价；Stale hops 按非 Pils 风格分组验证。Pils 标签已多次用于开发诊断，不能再视为独立测试集。迁移失败的源酒始终保留在通过率分母中。

4 模型假设与符号

4.1 建模假设及影响

假设一，现有风格混合中的啤酒可作为随机五折的评价单位，训练与测试按编号隔离。不同批次或全新风格的预测能力需另行验证。

假设二，附件的 45 维连续感官值在本批样本间可比。预测沿用该标准化尺度；缺少逐人评分及转换参数时，不推定其与原始 0—6 分存在已知映射。

假设三，经验边缘和收缩秩相关可近似小样本风格分布，通过留出分布距离、零频率、方差和近邻指标检验；生产可行性另需实测。

假设四，附件阈值可作为化学缺陷的参考。用阈值均值、中位数及扰动情景检查敏感性；Stale hops 没有单一化学对应项，另用感官预测约束。

4.2 主要符号

表 4-1 主要符号及含义

符号	含义	尺度或范围
n，p，K	样本数、化学维数、感官维数	n=250；p=231 或 226；K=45
x_i，y_i，s_i	化学向量、感官向量、风格标签	化学量按字段；感官为标准化值
T，m_j,T，d_{ij}	训练集、训练中位数、缺失指示	$d_{ij}\in\{0,1\}$
ρ_{jl}，τ，π_{jk}	秩相关、网络阈值、入选频率	$\tau\in\{0.6,0.7,0.8\}$；$\pi\in[0,1]$
F_j，Φ，z(x)	经验边缘、标准正态 CDF、高斯秩向量	无量纲
μ_s，Σ_s，R_s	风格秩中心、协方差、相关矩阵	秩空间参数
c_d，T_d，e_d	缺陷浓度、感官阈值、超阈程度	浓度与阈值单位一致；e_d 无量纲
d(x)，$r_i(x)$，$G_i(x)$	目标距离、修改幅度、距离改善率	秩空间距离；G 为相对改善
f_b，Δ_b，$Q_{0.95}$	第 b 个代理、配对预测差、95%分位数	标准化感官尺度

5 缺失条件下的感官预测

5.1 预测目标与评分量尺

以 250 款酒的 231 维化学表示预测 15 项 Aroma 和 30 项 Taste 属性。按 beer 连接化学与感官表，编号、条码及风格标签不作为输入。保留全部样本，在训练管线中处理化学缺失值。

部分描述符在原评分卡上以勾选记录，选中后继承所属类别的总体强度；经标准化和汇总，附件标签均为连续值，因此采用回归。

题目要求预测 0—6 等级，但附件 4 提供的是标准化连续值。原研究先按品评员中心化、除以标准差，再汇总[1]。设 s_{itk} 为啤酒 i、品评员 t、属性 k 的原评分，T_i 为参与该酒品评的人员集合，则

$$y_{ik}=\frac{1}{|T_i|}\sum_{t\in T_i}\frac{s_{itk}-\mu_{tk}}{\sigma_{tk}}. \tag{5-1}$$

附件未提供逐人评分、μ_{tk}、σ_{tk} 及完整参与关系，附件 3 的评分输入也均为空。若在允许范围内令 $s'=a_ks+b_k$、$\mu'=a_k\mu+b_k$、$\sigma'=a_k\sigma$，$a_k>0$，式（5-1）不变，原量尺的原点与单位却可改变。仅凭最终均值、标准差或[0,6]范围不能确定逆变换。因此本问输出可

核查的 45 维连续预测，并在附件尺度计算误差；原始 0—6 等级尚未完成。可信校准需要与本批 beer 编号对应的真实评分，或逐人评分、转换参数和参与记录，不能用分位分级或线性拉伸代替。

5.2 折内缺失处理与多输出 ExtraTrees

设外层训练集为 T，$d_{ij}=1$ 表示第 j 个化学值缺失，$d_{ij}=0$ 表示已观测，$m_{j,T}$ 为训练集该列已观测值的中位数。采用中位数补值并附加缺失指示，使模型区分实测中位水平与缺失后填入的中位水平：

$$\tilde{x}_{ij}=x_{ij}\ (d_{ij}=0),\quad \tilde{x}_{ij}=m_{j,T}\ (d_{ij}=1). \tag{5-2}$$

仅对训练时出现缺失的列 J_T 附加指示，训练中全空的列按 0 保留。测试时使用训练所得中位数和指示列，不重新拟合；树模型不再标准化化学特征。

补值保留对极端观测的稳健性，缺失指示保留检测缺失的信息。两者均在划分后估计。

采用多输出极端随机树集成 ExtraTrees[2]。每个节点随机抽取特征和候选阈值，以子节点损失之和最小为准划分；各输出共享树结构，叶节点保存目标均值。对节点样本集 A，45 维联合平方误差定义为

$$L(A)=\sum_{i\in A}\sum_{k=1}^{45}(y_{ik}-\bar{y}_{Ak})^2. \tag{5-3}$$

$$\hat{y}_k(x)=\frac{1}{B}\sum_{b=1}^{B}\frac{1}{|L_b(x)|}\sum_{i\in L_b(x)}y_{ik},\quad B=300. \tag{5-4}$$

其中 L_b(x)为样本 x 在第 b 棵树中的叶节点。固定 300 棵树、叶节点至少 3 个样本，每次划分随机使用 70%的输入特征。叶均值和集成平均可减少极端线性外推。

45 个输出共享划分，不逐目标调参。汇总后的目标方差并不完全相同，因此联合训练的权重与逐维等权评价不同，需同时报告总体和逐维误差。

5.3 折外验证与模型比较

固定随机种子 20261023，将 250 款酒随机分为五折，每次 200 款训练、50 款测试，合并每款酒仅在未参与训练时得到的折外预测。均值基线只使用训练折目标均值。普通岭回归[3]在补值后标准化输入与输出，并在各外层训练集内用四折选择 $\alpha\in\{0.1,1,10,100,1000,10^4,10^5,10^6\}$；补值和标准化在每个内层训练折重新拟合。ExtraTrees 参数固定，不参加上述内层搜索。

$$RMSE=\sqrt{\frac{1}{250\times45}\sum_{i=1}^{250}\sum_{k=1}^{45}(y_{ik}-\hat{y}_{ik}^{OOF})^2}. \tag{5-5}$$

$$R^2_{macro}=\frac{1}{45}\sum_{k=1}^{45}\left[1-\frac{\sum_i(y_{ik}-\hat{y}_{ik}^{OOF})^2}{\sum_i(y_{ik}-\bar{y}_k)^2}\right]. \tag{5-6}$$

表 5-1 45 维标准化感官预测的折外指标

模型	MAE	RMSE	宏平均 R^2
训练折均值	0.409634	0.574456	-0.007574
普通岭回归	0.406092	0.589966	-0.065285
ExtraTrees	0.340851	0.486220	0.214638
1%/99%裁剪岭回归	0.352513	0.499179	0.185784

ExtraTrees 的 RMSE 较均值降低 15.36%，五个测试折均改善，降幅 11.60%—17.91%。普通岭回归 MAE 略低，但 RMSE 高于均值 2.70%，受少数大误差影响。训练 1%—99%分位裁剪后的岭回归 RMSE 为 0.499179，仍高于 ExtraTrees，故采用后者。裁剪对照在检查原五折误差后提出，复用了该划分，属于探索性比较。

MAE 反映平均绝对偏差，RMSE 更重视大误差，宏平均 R^2 使 45 个目标等权。负 R^2 表示折外误差大于该目标相对全样本均值的平方离差，不代表分类准确率。

5.4 缺失压力与极端外推诊断

在每折已观测测试特征中额外随机隐藏 10%或 20%，训练模型保持不变。两种遮蔽使用同组随机数，10%掩码是 20%掩码的子集，模型间使用相同掩码。结果见表 5-2。

表 5-2 新增随机缺失下的 RMSE

模型	无新增缺失	隐藏 10%	隐藏 20%	20%相对变化
普通岭回归	0.589966	0.590951	0.564464	-4.32%
ExtraTrees	0.486220	0.490987	0.499218	+2.67%
裁剪岭回归	0.499179	0.507932	0.514142	+3.00%

ExtraTrees 在 20%情景下 RMSE 增加 2.67%，裁剪岭回归增加 3.00%。普通岭回归的下降主要来自 beer 156：其 X2.methyltetrahydrofuran.3.one 为 12596.43287，对应训练折最大值仅 31.25344；acetic 预测为 12.00039，实测为−0.28048，该酒 45 维平均平方误差为 8.651434。

20%掩码恰好隐藏该极端单元格，补值后该酒误差降至 0.721929，其他 249 款的合计误差反而增加。ExtraTrees 和裁剪岭回归对此酒的误差为 0.597805、0.635978。该结果反映极端外推，不能解释为缺失有益；没有证据认定记录错误，仍保留该酒。

裁剪边界在每个内层训练折估计。beer 156 所在外层折中，该特征训练 99%分位数为 19.311161，因此能够减小极端外推的影响；但裁剪也可能压缩真实稀有成分。一次随机遮蔽未覆盖检出限删失或成组仪器故障。

5.5 逐维表现与应用边界

ExtraTrees 有 44 项 R^2 为正、29 项超过 0.1；Taste 和 Aroma 宏平均 R^2 分别为 0.235783、0.172350。acidity、lactic、acetic、bitternes 的 R^2 为 0.708844、0.651877、0.646041、0.553414；A_esters_fruity、stale_hops、dms 仅为−0.010524、0.018091、0.038774，逐维差异明显。

A_esters_fruity 和 stale_hops 的折外 Spearman 相关也仅为 0.015752、0.153261。现有数据不能分离标签稀疏、风格差异与化学覆盖不足的影响，这些预测较弱的维度尚不足以支持对实际感官效果的可靠判断。

裁剪岭回归在 16 项上优于 ExtraTrees，但不依据同批折外结果逐维选择最优模型再组合，以免高估预测性能。最终用 250 款拟合 ExtraTrees 供新样本预测，训练内拟合值不计入精度。上述结果适用于现有风格混合，未证明对全新风格的预测能力。附件制作者已做的全局标准化无法撤销，评价以该表示为条件。




图 2 第一问四种方法的五折折外误差、宏平均 R^2 及 ExtraTrees 缺失压力结果。裁剪 Ridge 为稳健性对照；额外隐藏 20%已观测特征后，ExtraTrees 的 RMSE 由 0.4862 增至 0.4992。

5.6 补充对照与未见风格验证

主结果完成后增加固定参数三折对照，用于比较模型类型并考察适用范围；这是同一批 250 款酒上的补充分析，不作为独立外部测试，也不替换表 5-1 的五折指标。四种模型使用相同随机划分，所有补值均只在训练折估计。ExtraTrees 沿用 300 树、叶节

点至少 3 样本及 0.7 特征比例；GBR 逐目标拟合 100 棵深度 2 的树，学习率 0.05、叶节点至少 5 样本；HGB 逐目标迭代 100 次，学习率 0.05、最多 7 叶、叶节点至少 10 样本、正则系数 1。未根据该结果调参，也未逐目标选择最优模型后组合。

表 5-3 固定参数补充对照与整风格留出

验证	模型	RMSE	宏平均 R^2
随机三折	训练折均值	0.5743	-0.0067
随机三折	ExtraTrees	0.4900	0.2043
随机三折	逐目标 GBR	0.4948	0.1786
随机三折	逐目标 HGB	0.4951	0.1775
整风格三折	训练折均值	0.5878	-0.0461
整风格三折	ExtraTrees	0.5084	0.1516

整风格划分由 GroupKFold 按类别样本数平衡，三个测试折为 83、83、84 款，训练与测试风格互斥。与训练样本量接近的随机三折相比，ExtraTrees 的 RMSE 增加 3.76%。这反映未见风格预测更困难，不能将随机划分下的精度直接推广至新风格。固定参数提升树没有整体优势，故保留 ExtraTrees 主方案。

对同一随机三折模型再施加 20 组配对测试掩码：10%掩码的 RMSE 均值为 0.4956、掩码间标准差为 0.0013；20%掩码的 RMSE 均值为 0.5037、掩码间标准差为 0.0022。这里的波动仅来自测试掩码，不含重新分折或重训的不确定性，也不模拟检出限删失和整组仪器失效。

另按原五折、原模型参数及原测试掩码进行缺失指示消融，仅切换是否附加指示列，不根据结果重新选择参数。63 款原始有缺失和 187 款原始完整的分组在新增遮蔽前确定，结果见表 5-4。有指示分支的三组折外预测与原保存结果逐值一致。

表 5-4 原始缺失分组下的指示变量消融

样本组	款数	有指示 RMSE	无指示 RMSE	差值（有−无）
全部样本	250	0.486220	0.486310	-0.000090
原始有缺失	63	0.494276	0.494855	-0.000578
原始完整	187	0.483476	0.483398	+0.000078

新增 10%缺失时，整体有、无指示的 RMSE 为 0.490987、0.491344；20%时为 0.499218、0.498925。原始有缺失组在三种情景下均略有改善，原始完整组则均略差，说明收益很小且依赖样本和遮蔽情景。添加指示也改变有效输入维数及随机候选特征数，不能把差异解释为缺失模式的因果作用。此处复用原五折的一组配对掩码，与上述三折 20 组掩码的波动含义不同。

6 化合物关联网络与关键候选

本问分析全部 250 款啤酒，用化合物共变网络观察冗余和共同来源，再按化合物—感官边际关联提出候选。网络结构、候选稳定性和化学气味证据分别报告；候选清单仅描述相关性，不能据此推断因果效应或独立测试性能。

6.1 Spearman 关联网络

逐项核对附件 2 与附件 1 重算矩阵后，二者 Spearman 相关最大绝对差为 6.66×10^{-16}，说明附件 2 对应秩相关。设两个化学变量在共同非缺失样本中的平均秩向量为 R_j、R_l，则相关系数及无向邻接矩阵定义为

$$\rho_{jl}=corr(R_j,R_l),\quad a_{jl}=1(|\rho_{jl}|\geq\tau),\quad j\neq l. \tag{6-1}$$

并列值取平均秩，缺失值按变量对删除。主阈值 $\tau=0.7$ 时保留 231 个节点、109 条无向边，边均为正相关，150 个节点孤立。阈值改为 0.6 或 0.8 时，边数为 266 或 39，孤立节点为 101 或 194。节点度数及加权度数反映共变邻居数量与强度；孤立不表示没有气味作用。

全图保留颜色、pH 等综合参数以描述样本结构；Top-3 则排除这类非单一化合物指标。τ 只控制图的稀疏程度，不是显著性或气味阈值。

同来源成分可能随原料、发酵和风格共同变化，网络连边不能解释为化学反应或感官贡献。全样本网络只用于本问描述；若用于预测筛选，须在训练折内重建。

6.2 感官 Top-3 候选与重抽样稳定性

从 231 项中排除五项派生汇总量及颜色、pH 等共 13 项综合参数，保留 218 项候选，对 45 个感官目标计算 9810 个关联。每项目标按 $|\rho_{jk}|$ 降序取前三项，保留正负号，并列按附件顺序处理。135 个候选位置涉及 60 种化合物，不根据事后查阅的文献或预计算 GBM/SHAP 结果调整候选。

化学—感官相关也使用共同观测样本，附表给出有效样本数。负相关仅表示化学值的秩与感官评分秩反向，不等于抑制作用。相对峰面积及变换值不能直接与浓度阈值比较。

为判断排名对样本扰动的依赖，固定种子进行 B=200 次全样本行 Bootstrap，每次重新计算相关并选择前三项。设 $S_k^{(b)}$ 为第 b 次的入选集合，频率定义为

$$\pi_{jk}=\frac{1}{B}\sum_{b=1}^{B}1(j\in S_k^{(b)}). \tag{6-2}$$

135 个位置的平均入选频率为 0.455，中位数 0.400，14 个达到 0.8。频率的最大蒙特卡洛标准误约 0.035，小差异不宜过度解释。全样本行重采样没有固定风格比例，也不提供筛选后的显著性保证。

另在 22 种风格内分别有放回抽取原样本数，固定混合比例重做 200 次 Bootstrap。原 135 项的平均频率由 0.455 变为 0.484，达到 0.8 的位置由 14 变为 19。乙酸乙酯对应感官的频率为 0.985，4VG 为 0.890。该补充分析不改变全样本相关排名的前三项；固定风格比例仍保留风格之间的差异，不能视为已消除混杂。200 次频率的小幅差别亦受蒙特卡洛误差影响。




图 3 化学关联网络及稳定性。(a) 实际|Spearman ρ|≥0.7 网络，保留全部 231 节点和 109 条正相关边；81 个非孤立节点采用固定种子 20261023 的分量内力导向布局及分量打包，并进行显示避碰，150 个孤立节点在外围环逐点保留，节点面积随度增加。A—H 为度最高八个节点，图内列简名；布局距离不表示化学浓度或因果关系。(b) 三个阈值下的边数。(c) 135 个 Top-3 位置的 200 次配对重抽样入选频率，其中 14 个达到 0.8；频率区间左闭右开，最后一组包含 1。

6.3 方法与风格敏感性

以 Pearson 替代 Spearman，并对化学与感官变量同时减去所属风格均值后重新计算秩相关。令 s(i)为啤酒 i 的风格，该检查为

$$\tilde{x}_{ij}=x_{ij}-\bar{x}_{s(i),j},\quad \tilde{y}_{ik}=y_{ik}-\bar{y}_{s(i),k}. \tag{6-3}$$

用 Jaccard 衡量两份 Top-3 集合的一致性：

$$J(S,T)=\frac{|S\cap T|}{|S\cup T|}. \tag{6-4}$$

Spearman 与 Pearson 的平均 Jaccard 为 0.222；全样本与去风格均值后的平均为 0.160，21 项感官的两份清单完全不重合。候选名单随关联定义和风格构成明显变化。去均值只移除当前表示下的风格均值，不能控制风格内工艺、品牌等混杂。

22 种风格的样本量介于 3 至 31 款，去均值后的剩余变异也不相同。因此保留敏感性分析中的变化，不据预期机制替换原排名；Bootstrap 频率只说明本批样本构成下的排名稳定性。

表 6-1 既有 Top-3 代表候选的稳定性与证据判断

感官—化合物	全样本 ρ	入选频率	去风格 ρ	证据判断
酯味指甲油(F)—乙酸乙酯	0.503	0.980	0.270	气味相符[1][4]
酯香香蕉(A)—乙酸异戊酯	0.283	0.650	0.300	气味相符[5]
酒花柑橘香(A)—香茅醇	0.370	0.590	0.281	混合物协同[6]
4VG 感官—4-乙烯基愈创木酚	0.473	0.875	0.428	气味相符[5]
苦味—辛酸乙酯	0.593	0.985	0.465	同源间接关联[1]
麦芽总体味(F)—乙醇	0.472	0.960	-0.011	风格共变标记
酯香香蕉(A)—正己醇	0.340	0.945	0.237	山楂样背景[7]
麦芽焦糖味(F)—乙醛	0.433	0.970	0.142	生青味标准[7]
丁香味—柠檬烯	0.342	0.915	0.340	柑橘背景[8]
橙味—樟脑	0.367	0.865	0.312	花香协同背景[9]
DMS 感官—松油烯-4-醇	-0.196	0.190	-0.126	目标机制未验证
陈旧酒花—2-十一醇	0.300	0.645	0.129	目标机制未验证

6.4 化学依据与解释边界

表 6-1 中，乙酸乙酯的果香/溶剂样气味[1][4]、乙酸异戊酯的香蕉气味及 4VG 的丁香气味[5]与相应描述一致。香茅醇的依据来自与香叶醇、芳樟醇共同存在时的柑橘协同[6]，不能把单变量相关换算为独立贡献。辛酸乙酯—苦味虽有 0.985 的入选频率，原研究也只提出复杂感官联系的可能解释[1]；该研究与附件共享样本，不能作为外部重复验证。

高入选频率也可能对应不匹配的气味。独立鲜啤 GC-O/AEDA 研究把正己醇描述为山楂样，并以乙醛作为生青味训练标准[7]，没有证明二者分别产生香蕉酯香和麦芽焦糖味。Amarillo 酿造对照中的柠檬烯等成分随柑橘/花香共同改变[8]；芫荽啤酒实验报告樟脑在过量芳樟醇下增强花香[9]。这些结果补充了候选背景，仍不能解释本题柠檬烯—丁香味或樟脑—橙味的直接作用。

对未入选 Top-3 的已知缺陷化合物另按名称列出对照，结果见表 6-2，原候选清单保持不变。DMS 和双乙酰分别具有卷心菜样与黄油样气味；啤酒加标试验还发现乙酸

乙酯、乙酸异戊酯和芳樟醇对其感知有不同方向、浓度相关的影响[4]。这些试验说明基质交互确实存在，但不能据此断言它就是本样本弱相关的原因。

表 6-2 已知缺陷化合物的名称对照（不改变 Top-3）

感官—化合物	n/候选秩	全样本 ρ	去风格 ρ	入选频率	气味依据与样本结果
DMS 感官—DMS	250/85	0.088	0.032	0.005	气味已知[4]；本样本弱相关
双乙酰感官—双乙酰	241/80	-0.101	-0.049	0.000	气味已知[4]；本样本弱相关
4VG 感官—4VG	250/1	0.473	0.428	0.875	气味相符[5]；入选稳定
t2n 感官—反式-2-壬烯醛	250/16	-0.151	-0.0005	0.050	纸板味依据[10]；本样本反向

表 6-2 沿用 218 项候选中的绝对相关排名和同一 Bootstrap 结果。双乙酰有 241 对有效观测，其余三项为 250 对；DMS、双乙酰的相关区间跨零，t2n 对应化合物的负相关在去风格后接近零。因此，气味已知不保证商业样本中的单调相关，也不能用文献强行修正数据符号。反式-2-壬烯醛的老化纸板味有同位素研究支持[10]，但它不等于 Stale hops。附件未单列游离异戊酸，不能把异戊酸乙酯当作同一种缺陷物；陈旧酒花 Top-3 的直接机制仍未证实。

铁与金属味的联系也需结合试验条件解释：二价铁盐溶液的人体感官试验观察到持续金属感[11]，但盐种、浓度及基质不同于本题的啤酒总铁测量，故只列一般背景，不移用试验浓度作为啤酒阈值。

附录 B-2 逐项给出 135 个候选位置的化学名称、附件来源类别、单位、阈值、证据说明与引用。10 项有相符的直接气味依据，36 项仅有一般背景，29 项属间接关联，60 项仍未验证；一般背景不表示相应目标机制已经成立。缺失阈值保持空缺，也不以外部试验阈值替换附件值。后续宜优先验证兼具排名稳定、风格内同向和匹配气味依据的候选，采用加标、重组或省略试验检验其实际贡献。

6.5 折外置换与预测依赖

为区分边际关联与模型使用的信息，按第一问原五折划分和固定 ExtraTrees 参数重拟合，本次折外 RMSE 为 0.486219；主表原保存值为 0.486220。在每个验证折中分别置换一个输入变量，连同其缺失指示一起移动，其他输入和模型固定；每折重复 5 次。记 f_fk 为第 f 折对第 k 目标的预测器，V_f 为验证样本集合、n_f 为其大小，π 为该折随机排列，置换引起的误差变化为

$$\Delta_{jk}^{(f,r)}=\frac{1}{n_f}\sum_{i\in V_f}\left[\left(y_{ik}-f_{fk}\left(x_i^{\pi_{j,r}}\right)\right)^2-\left(y_{ik}-f_{fk}\left(x_i\right)\right)^2\right]. \tag{6-5}$$

先对每折 5 次取均值，再按验证样本数合并；负值保留，不截为零。表 6-3 列出代表性化合物，标准差按五个折均值计算，正值折数只作稳定性描述，不作为显著性检

验。对全部 231 项输入计算后，仅在与相关分析相同的 218 项化学候选中排序，完整 45 项结果见表 B-3。

表 6-3 代表候选的折外置换结果

感官—化合物	置换名次	平均 ΔMSE	折间标准差	正值折数
酯味指甲油(F)—乙酸乙酯	2	0.00235	0.00204	4/5
4VG 感官—4VG	1	0.00624	0.00299	5/5
麦芽总体味(F)—乙醇	5	0.00248	0.00121	5/5
陈旧酒花—乙酸乙酯	1	0.00084	0.00074	4/5

置换前三与相关前三的平均 Jaccard 为 0.080，30/45 个目标没有共同候选。两种排名回答不同问题，故并列保留。4VG 在边际相关、风格内相关、气味依据及预测依赖上均有支持；乙酸乙酯亦被预测器使用。麦芽总体—乙醇虽有预测依赖，风格内相关却近零，仍可能只是风格或共同工艺的标记。陈旧酒花的置换首项不在原相关前三中，其误差增量也小，不能据此提出加料因果方案。

相关输入可能相互替代，逐项置换还会打破真实化学组合。为检查这一问题，每个训练折独立重建|Spearman|≥0.7 网络，并将连通分量整体置换；五折分别形成 165、167、166、169、167 个分量。成员和逐折误差随附件保存，不将成员不同的分量混作同一对象求平均。这些分析提供模型依赖证据，均不能用于识别因果效应。第一问使用 231 维附件表示，第三问改用 69 维校准量与 157 维相对量并另训代理；本问候选没有直接作为第三问的生成约束，三问之间仅通过证据核对和缺陷变量解释建立联系。

以乙酸乙酯对酯味指甲油（F_esters_ethac）的依赖为例，表 6-4 列出逐折单项及模块置换。整个模块五折的误差增量均为正，单项仅四折为正，表明相邻输入可能共同承载预测信息。模块成员跨折变化，完整成员见表 B-4，不将模块与单项增量之差视作乙酸乙酯的独立贡献。

表 6-4 乙酸乙酯及其相关模块的逐折预测依赖

折	模块成员数	单项 ΔMSE	模块 ΔMSE
1	11	+0.00267	+0.03963
2	12	-0.00124	+0.02359
3	9	+0.00340	+0.02915
4	11	+0.00368	+0.03234
5	27	+0.00322	+0.02776

模块联合置换保留组内组合，仍会打破模块与其余输入之间的联系，因此不同于给定邻域后的条件置换。现有 Bootstrap 重算的是相关排名，不能用于声称条件重要性已经稳定。4VG 在五折中均为单节点，其模块置换不提供额外的群组证据。

7 风格条件生成与受约束迁移

第三问先学习目标风格的化学联合分布，再将 Pils/Lager 向 Tripel 迁移。生成部分评价分布接近程度及新组合，迁移部分则在化学与感官约束下比较可行候选。两部分分别评价。

7.1 混合化学表示与高斯秩映射

依据附件及原研究的数据框架[1]，删除五项汇总或派生变量，保留 226 维输入：69 维以附件 8 的校准量替换，157 维沿用附件 1 的相对表示，按 beer 连接。校准负值转为缺失，相对量负值保留。填补与经验分布只在当前训练集估计；迁移训练排除 11 款 Pils，保留 239 款。

采用 Gaussian Copula 分离边缘分布与依赖结构[12]。对第 j 维的不同观测值 v，记小于 v 的样本数为 $N_{<v}$、等于 v 的样本数为 $N_{=v}$，用中点经验概率处理零值和并列值：

$$\hat{F}_j^{mid}(v)=\frac{N_{<v}+N_{=v}/2}{n}. \tag{7-1}$$

$$z_j=\Phi^{-1}\left(\hat{F}_j^{mid}(x_j)\right),\quad x_j^{*}=\hat{F}_j^{-1}\left(\Phi(z_j^{*})\right). \tag{7-2}$$

训练值使用中点概率，中间输入按线性插值评分，概率截在[0.5/n,1−0.5/n]。逆变换按经验 CDF 阶梯取值，生成新的联合组合，但单列取值仍来自训练观测。

7.2 共享信息的条件 Copula 基准

样本较少的风格不足以稳定估计 226 维协方差。基准模型共用全局经验边缘，将风格中心向全局中心收缩，局部协方差向合并风格内协方差收缩。协方差采用 Ledoit–Wolf 估计并加入小对角项。对 n_s 款风格样本，

$$a_s=\frac{n_s}{n_s+5},\quad b_s=\frac{n_s}{n_s+20},\quad \tilde{\mu}_s=a_s\bar{z}_s+(1-a_s)\bar{z}. \tag{7-3}$$

$$\tilde{\Sigma}_s=b_s\hat{\Sigma}_s+(1-b_s)\hat{\Sigma}_{within},\quad z^{*}\sim N(\tilde{\mu}_s,\tilde{\Sigma}_s). \tag{7-4}$$

合并协方差由各风格减去自身中心后的残差估计。收缩降低估计波动，也可能减弱 Kriek、Lambic 特征，故再比较局部边缘方法。

7.3 局部边缘 Copula 与平滑混合

各风格分别建立经验边缘和高斯秩。缺失用该风格训练中位数填补，整列缺失时改用全局训练中位数。正则协方差经对角标准化得到相关矩阵，再混合局部 R_s 与合并局部秩所得 R 共享。记风格秩样本为 z_{si}，

$$\tilde{R}_s=\frac{n_s}{n_s+10}R_s+\frac{10}{n_s+10}R_{shared},\ \varepsilon\sim N(0,\tilde{R}_s). \tag{7-5}$$

$$z^{*}_{copula}=\varepsilon,\quad z^{*}_{mixture}=z_{sI}+0.45\varepsilon,\quad I\sim Unif\{1,\dots,n_s\}. \tag{7-6}$$

两者均用风格经验逆 CDF 还原。局部 Copula 使用单位边际高斯噪声，平滑混合在随机训练秩中心附近加固定强度扰动。前者在期望上保留经验零频率，后者须另行检查；两者都无法补充未观测到的尾部分布信息。

7.4 嵌套选择、生成质量与感官画像

采用两次三折风格分层外层验证，各训练集内部以两折选择三个候选。评价坐标统一由当前训练集基准 Copula 及五维 PCA 确定，再除以训练主成分标准差。每种方法生成 300 条，重复两个模拟种子。主指标为真实留出谱 u 与生成谱 v 的经验能量差异：

$$\widehat{E}(U,V)=2A_{UV}-A_{UU}-A_{VV},\quad A_{UV}=\frac{1}{ml}\sum_{i=1}^{m}\sum_{k=1}^{l}\|u_i-v_k\|_2. \tag{7-7}$$

A_{uu}、A_{vv} 为组内全部有序对距离均值，包含零对角项；式（7-7）为未开平方的 V 统计量，越小越好。内层每折须满足：补缺后整行复制率、仅比较原有观测格的复制率均为零，生成与真实留出谱的最近邻距离中位数比≥0.35，最近训练行相等特征比例中位数≤0.95。满足条件后按平均能量差异选择方法，再由外层验证评价整个选择流程。

表 7-1 风格生成的外层能量差异与全量拟合方法

风格	基准 Copula	嵌套选择器	风格重采样	全量拟合方法
Tripel	0.2866	0.2939	0.3218	收缩 Copula
Kriek	0.9528	0.7575	0.7434	局部边缘 Copula
Lambic	0.8701	0.6669	0.6304	平滑混合
Pils/Lager（对照）	0.8098	0.5001	0.5736	局部边缘 Copula

Kriek、Lambic 的能量差异较基准降低 20.5%、23.4%，Tripel 增加约 2.5%。前两者仍略逊于直接重采样。全量拟合后，三种指定风格各生成 300 条，另生成 300 条 Pils 对照；1200 条均无完整训练行复制。

按训练四分位距归一的边缘 Wasserstein 距离，其跨特征中位数在 Kriek 由 0.5345 降至 0.4701，Lambic 由 0.4913 降至 0.4114。不过 Kriek 的跨特征均值由 94.16 升至 153.19，反映极端变量影响；相关差异也未同步改善，故不能认定联合分布全面优于基准。重复划分复用同一批酒，折间波动不作独立样本置信区间。

生成谱的 44 项感官由 226 维全量多输出树预测，Stale hops 改用 239 款非 Pils 训练的固定单目标树。报告均值及 5%、95%分位数，表示生成谱之间的预测差异，均保留附件标准化尺度。




图 4 三种风格的生成能量差异。柱为外层六折均值，误差线为折间标准差，非置信区间；每折先平均两个模拟种子。




图 5 三种风格的 12 维代表感官画像。点为预测均值，线为每风格 300 条生成谱的 5%—95%范围，并非预测置信区间。Stale hops 用非 Pils 单目标树，其余维度用 226 维多输出代理；均为标准化尺度。

7.5 距离、支持域与中央候选池

迁移沿用 239 款训练酒拟合的高斯秩变换及 Tripel 的几何表示，使各方案的距离可比。记 z(x)为秩映射，目标距离 d 与改动 r 为

$$d(x)=\sqrt{\frac{(z(x)-\tilde{\mu}_T)^{T}\,\tilde{\Sigma}_T^{-1}\,(z(x)-\tilde{\mu}_T)}{p}},\quad p=226. \tag{7-8}$$

$$r_i(x)=\frac{\|\,z(x)-z(x_i)\|_2}{\sqrt{p}},\quad G_i(x)=1-\frac{d(x)}{d(x_i)}. \tag{7-9}$$

候选须在非 Pils 训练逐维范围内，且到真实 Tripel 的最近邻秩空间 RMS 距离不超过 Tripel 内部留一最近邻距离的 95%分位数；另要求 $r_i\ge 0.05$。该支持范围为经验规则，没有卡方概率标定。

将已保存的前 500 条 Tripel 生成谱映射至秩空间，按 $c\in\{0.2,0.4,0.6\}$ 向收缩中心移动并逆变换，得到 1500 条中央目标谱。与源谱按 $\gamma\in\{0.25,0.5,0.75,1\}$ 插值，另加四条朝真实 Tripel 中位谱插值的候选：

$$z_{kc}^{central}=\tilde{\mu}_T+c\{z(t_k)-\tilde{\mu}_T\},\quad t_{kc}^{central}=\hat{F}^{-1}\{\Phi(z_{kc}^{central})\}. \tag{7-10}$$

$$x'_{ikc\gamma}=(1-\gamma)x_i+\gamma\ t_{kc}^{central}. \tag{7-11}$$

中央池含 1500×4+4=6004 个候选，与原 1500 条目标谱的 6004 池等量比较；另设原 500 条谱的 2004 池。中央目标谱均唯一，投影后仍逐源检查重复和支持范围，不能把候选数当作独立观测数。

投影只截断四项缺陷浓度，使其不低于零且不超过情景交集上界，其余维度保留插值结果。截断后重新计算距离、支持范围和感官预测，以检查联合结构是否仍合理。

7.6 化学阈值与最低改善要求

DMS、双乙酰、4VG 分别采用附件阈值均值和中位数，各乘 0.8、0.9、1.0、1.1、1.2，形成十个情景。各情景下均要求超阈程度不增加：

$$\max(0,x'_d-T_{ds})\le\max(0,x_{id}-T_{ds})\ (\forall\ s). \tag{7-12}$$

$$0\le\ x'_d\le\min_s\max(T_{ds},x_{id})=\max\{\min_s T_{ds},x_{id}\}. \tag{7-13}$$

最严格阈值为 DMS 13.8 μg/L、双乙酰 0.072 mg/L、4VG 0.16 mg/L。源浓度已超阈时不得增加，未超阈时允许在阈值内变化。附件未给 trans-2-nonenal 阈值，故直接要求其浓度不增加。四项源值均采用观测校准量。

以每款源酒此前保存的迁移谱改善幅度 G_i 锚为参照，要求保留至少 80%，且绝对改善不低于 10%：

$$G_i(x')\ge\max\{0.10,\ 0.80\,G_i^{anchor}\}. \tag{7-14}$$

敏感性比较另设保留 100%原改善及绝对 10%、30%、50%、60%下限。两种预测模型、三个候选池、六种下限、两种排序共 72 组，均以 11 款源酒为通过率分母。

表 7-2 五项缺陷的变量及保护范围

缺陷	表示与单位	附件阈值	约束	解释边界
DMS	校准量，μg/L	均值 17.25；中位 19	十情景下超阈程度不增加	给定情景的化学保护
Diacetyl	校准量，mg/L	均值 0.29925；中位 0.09	同上	给定情景的化学保护
4VG	校准量，mg/L	均值 0.20633；中位 0.20	同上，依题面按缺陷处理	给定情景的化学保护
trans-2-nonenal	校准量，mg/L	附件空缺	候选浓度不大于源浓度	不保证低于感知阈值
Stale hops	标准化感官预测	无单一化学行及阈值	中心预测与配对差 Q95 不增加，预留模型复核	代理检查，需实际品评验证

表 7-3 展示余量优先主方案的三款代表源，11 款完整结果见表 C-3。上界取十个情景的交集，裕量为上界减迁移浓度。beer 81 的 DMS 从 8.858685 升至 13.8 μg/L，仍满足超阈程度不增加，因此，通过化学约束检查并不意味着四项浓度均下降。

表 7-3 代表源的迁移前后校准浓度

beer	化合物与单位	源浓度	迁移浓度	最严上界	剩余裕量	检查
124	DMS μg/L	14.296	14.296	14.296	0	通过
124	Diacetyl mg/L	0.0516208	0.0625324	0.072	0.0094676	通过
124	4VG mg/L	0	0	0.16	0.16	通过
124	trans-2-nonenal mg/L	0.000803907	0.000803907	0.000803907	0	通过
81	DMS μg/L	8.85868	13.8	13.8	0	通过
81	Diacetyl mg/L	0.284814	0.247202	0.284814	0.0376123	通过
81	4VG mg/L	0	0	0.16	0.16	通过
81	trans-2-nonenal mg/L	0.003422	0.003422	0.003422	0	通过
96	DMS μg/L	15.5585	15.5585	15.5585	0	通过
96	Diacetyl mg/L	0.523886	0.504705	0.523886	0.0191806	通过
96	4VG mg/L	0	0	0.16	0.16	通过

beer	化合物与单位	源浓度	迁移浓度	最严上界	剩余裕量	检查
96	trans-2-nonenal mg/L	0.011935	0.00598882	0.011935	0.00594619	通过

按绝对容差 10^{-10} 统计，DMS、双乙酰及 trans-2-nonenal 分别有 11、7、10 款达到上界；4VG 没有达到上界，11 款均处于零下界。这些是所选谱的边界分布，不能据此判断某化合物是唯一限制因素；约束对迁移幅度的影响还需单独放宽后的反事实比较。

7.7 Stale hops 预测及 beer 81 误差诊断

Stale hops 仅由化学输入预测。非 Pils 训练内按风格留出误差和响应稳定性选择 Ridge；四外层分组验证评价整个选择规则，RMSE 为 0.4200，同折多输出树为 0.4280。Pils 留出诊断中 Ridge 误差为 0.5614；实际用于迁移的固定单目标树、旧多输出树误差分别为 0.559206、0.526276。另以相同参数、不同种子重新拟合两种树作为选型对照，误差为 0.5429、0.5307，这两组数对应不同模型实例。尾部加权备选为 0.5157，但未通过非 Pils 精度门槛，Pils 的 R^2 也仅为−0.0007，因此，仅将其保留为备选诊断结果。

先排除精度未优于均值或预测近常数的配置，再在一标准误差容忍范围内比较训练响应稳定性。辅助感官方向和尾部权重均在训练折估计，推理仍只输入化学量。该容忍范围用于选型，不解释为参数置信区间。

beer 81 实测 Stale hops 为 1.6182，居 250 款第 5 高，239 款训练酒中仅 4 款达到此水平。其旧模型 25 近邻评分范围为[−0.3668,1.0643]，非负加权均值无法预测到该高值。核查未见身份错配、缺失或非法校准负值；Ridge 仍预测−0.0979，说明尾部信息及化学相似性尚不足以解释陈旧感。保留该酒，不改标签。Pils 标签已多次查看，此处属于开发诊断。

7.8 配对预测筛选与留出模型复核

分别用 Ridge 和固定单目标树预测 Stale hops，并保留旧多输出树作交叉检查。候选和源谱交由同一个 bootstrap 模型预测，形成配对差。要求当前 40 个筛选模型、旧 30 个筛选模型的差值 95%分位数均$\leqslant 0$，两个中心预测也均不增加：

$$\Delta_b^{(a)}(x',x_i)=f_b^{(a)}(x')-f_b^{(a)}(x_i),\quad a=new,old. \tag{7-15}$$

$$Q_{0.95}\{\Delta_b^{(new)}\}\leq 0,\quad Q_{0.95}\{\Delta_b^{(old)}\}\leq 0. \tag{7-16}$$

$$f_0^{(a)}(x')-f_0^{(a)}(x_i)\leq 0,\quad a=new,old. \tag{7-17}$$

另要求配对响应非零，池内平均响应标准差>10^{-6}，以排除近常数预测。旧中心为 45 输出树，旧 bootstrap 模型为单目标 120 树 ExtraTrees。选谱后，用预留当前 20 个模型和新种子旧协议 20 个模型复核；固定树另生成 20 个复核模型。失败后不重选谱。

旧历史 10 个模型仅作对照。模型均共享 239 款训练数据，分位数不是实际感官的 95%保证。

beer 96 说明化学保护与预测复核需分别检查：6004 个名义候选中有 13 个共同可行候选，选中谱通过十情景化学检查，但表 7-4 中预留当前模型有 2/20 个预测增量为正，Q95 变为+0.02100，因此最终失败。旧协议复核通过不能抵消该失败；未根据预留结果重新挑选候选。

表 7-4 beer 96 的配对预测筛选与预留复核

阶段	模型数	增量为正	配对差 Q95	Q95 检查
当前模型筛选	40	0	-0.02307	通过
旧协议模型筛选	30	1	-0.01048	通过
预留当前模型复核	20	2	+0.02100	未通过
预留旧协议模型复核	20	0	-0.04175	通过

正增量数按逐模型配对差大于零统计，Q95 不大于零为本表检查规则。少量正增量与 Q95 通过可能同时出现，不能把分位数筛选解释为所有模型均预测不增加。

7.9 两种排序的迁移结果

记两组筛选差值分位数为 q 新、q 旧。余量优先先最小化较差分位数，完全相等时再比较几何目标 J；几何优先直接最小化 J。以 h_i 为源谱到真实 Tripel 秩均值的 RMS 距离，

$$J_i(x') = \frac{d(x')}{d(x_i)} + 0.2\frac{r_i(x')}{h_i}. \tag{7-18}$$

$$x^*_{i,margin} = arglexmin_{x' \in C_i}(max(q_{new}, q_{old}), J_i(x')). \tag{7-19}$$

$$x^*_{i,geometry} = arg\,min_{x' \in C_i} J_i(x'). \tag{7-20}$$

表 7-5 保留原改善幅度至少 80%时的迁移结果

预测模型/候选池/排序	选出数	复核通过数	所选谱改善中位数	通过谱改善中位数
稳定 Ridge/中央 6004/余量优先	5/11	5/11	53.17%	53.17%
固定树/原 6004/余量优先	9/11	9/11	54.38%	54.38%
固定树/中央 6004/余量优先	11/11	10/11	57.74%	58.44%
固定树/中央 6004/几何优先	11/11	10/11	70.08%	70.08%

主比较采用固定树、中央 6004 池、余量优先。相对原 6004 池，通过数从 9 增至 10，所选谱改善中位数从 54.38%增至 57.74%；后者包含复核失败的谱，通过谱中位数为 58.44%。beer 96 在两种排序下均因当前复核分位数+0.0210 失败。

两种预测模型使用相同源酒、候选数、化学情景及接近下限，可行集合的差别来自模型响应。是否存在可行候选与是否通过最终复核分别报告；固定树通过数较高，并不说明其真实陈旧感预测更准确。




图 6 固定树、中央 6004 候选池与 retain80 条件下，11 款 Pils 源的所选谱目标距离改善。余量优先和几何优先均通过 10/11 款，beer 96 的审计失败保留；改善中位数分别为 57.74%与 70.08%，包括已选但失败的谱。几何优先为探索性应用示例，模型检查通过不代表实际品评成功。

7.10 方案选择与后续验证

固定树的几何优先方案同样有 10/11 款通过，改善中位数为 70.08%，可作应用示例。该方案在查看 72 组结果后提出，属于探索性选择；最初 Ridge 方案仍为 5/11。有限候选搜索不代表连续空间的全局最优。

化学保护仅覆盖给定十个阈值情景。迁移结果为化学目标谱和预测画像，10/11 表示通过模型检查的比例；实际品评效果及酿造可行性须通过新批次检测和盲品检验。

8 结果检验与模型评价

8.1 误差与稳定性证据的适用范围

第一问 RMSE 较均值降低 15.36%，新增 20%随机缺失后增加 2.67%，但逐维性能差异明显。Stale hops 及部分酯香描述符仍接近均值预测，不能将酸度等属性的预测效果推广至所有感官属性。主表使用一个随机五折种子；补充三折及整风格验证仍来自

同一批酒。缺失指示消融的整体 RMSE 差不足 0.0004，且在 20%遮蔽时转为不利，因此，缺失指示并未在所有情景下改善预测。

第二问的网络边数随阈值由 266 降至 109 再降至 39；Top-3 平均 Bootstrap 入选频率为 0.455，说明不少化合物可相互替代。去风格均值后 21 项感官的 Top-3 完全变化，表明全局相关受风格差异影响。统计稳定性与直接气味依据需分别判断。

第三问 Kriek、Lambic 的能量差异下降，但部分指标仍逊于直接重采样。生成方法在贴近分布与形成新组合之间存在取舍。感官画像的分位区间描述生成谱之间的差异，不是新酒预测误差的置信区间。

8.2 阈值与迁移策略敏感性

化学约束取阈值均值、中位数及各自±20%扰动的十个情景交集。浓度保护通过并不代表 Stale hops 感官检查通过，两者分别报告。

72 组迁移方案比较两种预测模型、三个候选池、六种接近下限和两种排序。主比较保持预测模型、检查规则、下限与候选数相同；几何优先结果作为探索性方案展示。逐源结果保留无候选的酒及 beer 96 失败。

固定树与稳定 Ridge 在相同候选空间分别有 10/11 和 5/11 款通过，说明可行方案依赖预测模型。Ridge 在非 Pils 分组验证中略好，却未改善 Pils 误差。预留重抽样模型的复核仍来自同一批训练酒，无法替代独立品评。

历史独立重建已复现三组主迁移比较的 33 条关键结果；全探索网格尚未逐项一致。792 条策略中 16 条候选编号、7 条状态及 4 条新旧模型一致通过标志不同；72 组汇总中 9 组计数变化，其中 4 组的一致通过数变化。部分选中结果的改善率差达 0.0820，不能全部归为末位浮点误差。本文保留已审查的原始保存结果，完整差异见随附重建核验记录。

8.3 方法优点与主要不足

本方法统一核对身份、字段、量尺与浓度单位，补值和选型限定在训练数据内。预测、关联、生成分别设置对照，迁移保留候选数、约束和失败记录，结果可以按样本追溯。

主要不足是原始 0—6 评分无法校准，部分风格的样本偏少，且多数化学候选尚缺直接机制证据。Stale hops 跨风格预测尤其薄弱；附件没有储存、批次及重复品评条件，无法据此解释误差来源。

9 结论与建议

基于 250 款啤酒，本文完成 45 维标准化感官预测、化合物关联分析和风格条件生成。ExtraTrees 五折 RMSE 为 0.4862；$|\rho|\geq 0.7$ 时网络有 109 条边，报告 135 个 Top-3 位置及其稳定性。三种指定风格各生成 300 条化学谱，并给出感官预测画像。

Pils/Lager 向 Tripel 迁移时，固定树、中央候选池和余量优先方案有 10/11 款通过模型检查，所选化学谱到目标风格的距离缩短幅度中位数为 57.74%；几何优先的探索性结果为 70.08%。这些结果支持进一步筛选化学目标谱，尚需理化检测和盲品验证。

后续应补充逐人原始评分及标准化参数，并对陈旧感高的酒收集储存时间、温度、包装、批次和重复品评记录。化学候选可通过加标、重组或省略试验检验；迁移方案应在新批次样本上重新测试。

参考文献

[1] Michiel Schreurs, Supinya Piampongsant, Miguel Roncoroni, et al. Predicting and improving complex beer flavor through machine learning[J]. Nature Communications, 15: 2368, 2024. DOI: 10.1038/s41467-024-46346-0.

[2] Pierre Geurts, Damien Ernst, Louis Wehenkel. Extremely randomized trees[J]. Machine Learning, 63: 3–42, 2006. DOI: 10.1007/s10994-006-6226-1.

[3] Arthur E. Hoerl, Robert W. Kennard. Ridge Regression: Biased Estimation for Nonorthogonal Problems[J]. Technometrics, 12(1): 55–67, 1970. DOI: 10.1080/00401706.1970.10488634.

[4] Stefan Hanke, V. Ditz, M. Herrmann, et al. Influence of Ethyl Acetate, Isoamyl Acetate and Linalool on off-flavour Perception in Beer[J]. BrewingScience, 63(7/8): 94–99, 2010.

https://brewingscience.de/index.php/brewingscience/article/view/456，访问日期 2026-10-23。

[5] Magdalena Müller, Martina Gastl, Thomas Becker. Key constituents, flavour profiles and specific sensory evaluation of wheat style non-alcoholic beers depending on their production method[J]. Journal of the Institute of Brewing, 127(3): 262–272, 2021. DOI: 10.1002/jib.663.

[6] Kiyoshi Takoi, Yutaka Itoga, Koichiro Koie, et al. The Contribution of Geraniol Metabolism to the Citrus Flavour of Beer: Synergy of Geraniol and β-Citronellol Under Coexistence with Excess Linalool[J]. Journal of the Institute of Brewing, 116(3): 251–260, 2010. DOI: 10.1002/j.2050-0416.2010.tb00428.x.

[7] Yu Zhang, Sinuo Li, Qi Meng, et al. Characterization of Key Odor-Active Compounds in Draft Beers for the Chinese Market Using Molecular Sensory Science Approaches[J]. Molecules, 29(11): 2537, 2024. DOI: 10.3390/molecules29112537.

[8] Ann Van Holle, Anita Van Landschoot, Isabel Roldán-Ruiz, et al. The brewing value of Amarillo hops (Humulus lupulus L.) grown in northwestern USA: A preliminary study of terroir significance[J]. Journal of the Institute of Brewing, 123(3): 312–318, 2017. DOI: 10.1002/jib.433.

[9] Kiyoshi Takoi, Haruna Kumamaru, Atsushi Tanigawa. Study on Characteristic Aroma in Special Beers Brewed with Coriander (Coriandrum sativum L.) Seeds: Profiling of Flavor Compounds Derived from Coriander Seeds in Different Growing Areas[J]. ACS Food Science & Technology, 4(10): 2439–2447, 2024. DOI: 10.1021/acsfoodscitech.4c00579.

[10] Sophie Noël, Catherine Liégeois, Guillaume Lermusieau, et al. Release of Deuterated Nonenal during Beer Aging from Labeled Precursors Synthesized in the Boiling Kettle[J]. Journal of Agricultural and Food Chemistry, 47(10): 4323–4326, 1999. DOI: 10.1021/jf990211r.

[11] Heidi Hai-Ling Yang, Harry T. Lawless. Time–intensity characteristics of iron compounds[J]. Food Quality and Preference, 17(5): 337–343, 2006. DOI: 10.1016/j.foodqual.2005.04.002.

[12] Han Liu, John Lafferty, Larry Wasserman. The Nonparanormal: Semiparametric Estimation of High Dimensional Undirected Graphs[J]. Journal of Machine Learning Research, 10: 2295–2328, 2009. https://www.jmlr.org/papers/v10/liu09a.html，访问日期 2026-10-23。

[13] OpenAI Codex，GPT-6.1 Sol，OpenAI，使用日期 2026-10-23 至 2026-10-27。

使用声明

本研究使用 OpenAI Codex（GPT-6.1 Sol）[13]辅助核对数据、编写与排查 Python 程序、复核计算结果、制作图表，以及修订论文文字和排版。论文中的数值以附件数据和程序运行结果为依据，原始数据未由生成内容替代；作者对提交内容及结论负责。

附录 A 感官字段及逐维精度

表 A-1 列出第一问 ExtraTrees 的全部 45 维折外误差。A_前缀表示香气，F_前缀为相应风味；其余字段按附件字典保留。所有值均为附件标准化尺度，完整 250×45 折外预测随电子附录保存。

表 A-1 全部感官维度的五折折外指标

目标字段	MAE	RMSE	R^2	Spearman
A_malt_all	0.4278	0.5503	0.4083	0.6341
A_malt_grain	0.3387	0.4497	0.0286	0.1604
A_malt_bread	0.3432	0.4939	0.1042	0.3733
A_malt_cara	0.3791	0.5131	0.3298	0.5875
A_malt_burn	0.3328	0.5678	0.3011	0.3431
A_hops_all	0.3943	0.5200	0.3773	0.6145
A_hops_citrus	0.3286	0.4374	0.1892	0.4410
A_hops_tropical	0.3423	0.5678	0.1331	0.3059
A_hops_noble	0.3459	0.4530	0.2832	0.5371
A_hops_woody	0.2653	0.3569	0.0640	0.2015
A_esters_all	0.4397	0.5517	0.1592	0.3962
A_esters_ethac	0.3752	0.4667	0.1207	0.3230
A_esters_isoaa	0.4169	0.5298	0.0298	0.1885
A_esters_flower	0.3128	0.4088	0.0674	0.2009
A_esters_fruity	0.3577	0.5062	-0.0105	0.0158
F_malt_all	0.3868	0.4900	0.4896	0.6906
F_malt_grain	0.3370	0.4385	0.0451	0.2367
F_malt_bread	0.3316	0.4334	0.2065	0.5242
F_malt_cara	0.3515	0.4731	0.3133	0.5737
F_malt_burn	0.3369	0.5217	0.4152	0.6102
F_hops_all	0.3944	0.4926	0.4943	0.7074
F_hops_citrus	0.3012	0.3931	0.2292	0.4205
F_hops_tropical	0.3062	0.4699	0.1467	0.3606
F_hops_noble	0.3717	0.4903	0.3564	0.5989
F_hops_woody	0.3080	0.4302	0.1411	0.4202
F_esters_all	0.4027	0.5124	0.2280	0.4983
F_esters_ethac	0.3354	0.4415	0.2069	0.4940
F_esters_isoaa	0.3967	0.5458	0.0712	0.3302

目标字段	MAE	RMSE	R^2	Spearman
F_esters_flower	0.2904	0.4123	0.0116	0.1955
F_esters_fruity	0.3370	0.4856	0.0732	0.2557
acidity	0.3025	0.4623	0.7088	0.4999
bitternes	0.3709	0.4875	0.5534	0.7504
sweetness	0.4324	0.5849	0.2583	0.5144
X4vg	0.3964	0.5929	0.1689	0.5123
diacetyl	0.3674	0.4928	0.0883	0.2703
dms	0.3708	0.4896	0.0388	0.2161
metallic	0.3604	0.4602	0.1028	0.3283
stale_hops	0.3062	0.4367	0.0181	0.1533
t2n	0.2960	0.3793	0.0989	0.2151
orange	0.3411	0.6428	0.1122	0.2533
coriander	0.2411	0.4295	0.0961	0.1420
clove	0.2521	0.5369	0.0749	0.3109
lactic	0.2093	0.4329	0.6519	0.4526
acetic	0.1939	0.4441	0.6460	0.3503
barnyard	0.3099	0.4420	0.0278	0.1741

附录 B 完整 Top 3 候选

表 B-1 沿用绝对 Spearman 相关排名，不根据事后查阅的文献调整候选。每项依次给出附件字段名、带符号相关 ρ 与 Bootstrap 入选频率 π。化学名称、来源、单位、阈值及逐行证据等级见表 B-2 及电子附件 chemical_evidence_final.csv；135 个位置涉及 60 种不同化合物。

表 B-1 45 项感官的全部 Top-3 关联候选

感官字段	第 1 项	第 2 项	第 3 项
A_malt_all	acetaldehyde ρ=0.361，π=0.565	methylpyrazine ρ=0.356，π=0.510	ethanol..v.v. ρ=0.335，π=0.325
A_malt_grain	terpinen.4.ol ρ=-0.265，π=0.620	beta.phellandrene ρ=-0.248，π=0.400	isoborneol ρ=-0.225，π=0.235
A_malt_bread	glycerol ρ=0.267，π=0.310	ethanol..v.v. ρ=0.260，π=0.260	terpinen.4.ol ρ=-0.250，π=0.270
A_malt_cara	acetaldehyde ρ=0.350，π=0.520	X2.ethyl.1.hexanol ρ=-0.317，π=0.375	ethanol..v.v. ρ=0.315，π=0.295
A_malt_burn	isobutanol ρ=0.249，π=0.350	DES ρ=0.243，π=0.320	ethanol..v.v. ρ=0.239，π=0.310
A_hops_all	ethyl_octanoate ρ=0.464，π=0.785	X.E..2.nonenal ρ=0.432，π=0.440	ethyl_decanoate ρ=0.428，π=0.410
A_hops_citrus	citronellol ρ=0.370，π=0.590	humulene.epoxide.II ρ=0.357，π=0.515	linalool ρ=0.327，π=0.265
A_hops_tropical	DMS ρ=0.314，π=0.720	X3.furanmethanol ρ=-0.259，π=0.280	methyl.geranate ρ=0.256，π=0.255
A_hops_noble	ethyl_octanoate ρ=0.482，π=0.925	ethyl_decanoate ρ=0.469，π=0.900	X.E..2.nonenal ρ=0.409，π=0.340
A_hops_woody	trans.dihydro.alpha.terpinyl.acetate ρ=0.279，π=0.255	alpha.calacorene ρ=0.273，π=0.175	ethyl.tetradecanoate ρ=0.267，π=0.165
A_esters_all	n.hexanol ρ=0.357，π=0.675	acetaldehyde ρ=0.353，π=0.710	ethyl_acetate ρ=0.321，π=0.435
A_esters_ethac	ethyl_acetate ρ=0.356，π=0.585	acetaldehyde ρ=0.335，π=0.400	ethanol..v.v. ρ=0.333，π=0.325
A_esters_isoaa	n.hexanol ρ=0.340，π=0.945	isopentyl_acetate ρ=0.283，π=0.650	isoamyl_alcohol ρ=0.223，π=0.145
A_esters_flower	beta.phellandrene ρ=0.196，π=0.280	isobutyl_acetate ρ=0.192，π=0.210	X1.alpha.terpineol ρ=0.184，π=0.155
A_esters_fruity	beta.phellandrene ρ=0.232，π=0.485	eugenol ρ=0.193，π=0.210	lactic_acid.mg.L. ρ=0.186，π=0.180
F_malt_all	ethanol..v.v. ρ=0.472，π=0.960	acetaldehyde ρ=0.471，π=0.935	MeSH ρ=0.356，π=0.190

感官字段	第 1 项	第 2 项	第 3 项
F_malt_grain	isoborneol ρ=-0.276，π=0.540	terpinen.4.ol.acetate ρ=-0.256，π=0.295	X.E..beta.ionone ρ=-0.249，π=0.320
F_malt_bread	acetaldehyde ρ=0.378，π=0.590	ethanol..v.v. ρ=0.372，π=0.480	glycerol ρ=0.367，π=0.445
F_malt_cara	acetaldehyde ρ=0.433，π=0.970	ethanol..v.v. ρ=0.387，π=0.795	ethyl.butyrate ρ=0.309，π=0.190
F_malt_burn	ethanol..v.v. ρ=0.431，π=0.900	MeSH ρ=0.403，π=0.690	glycerol ρ=0.364，π=0.320
F_hops_all	ethyl_octanoate ρ=0.501，π=0.745	X.E..2.nonenal ρ=0.456，π=0.315	ethyl_decanoate ρ=0.453，π=0.295
F_hops_citrus	humulene.epoxide.II ρ=0.285，π=0.355	ethyl.furoate ρ=-0.275，π=0.365	furfural ρ=-0.274，π=0.285
F_hops_tropical	geraniol ρ=0.285，π=0.445	hexyl.acetate ρ=0.281，π=0.420	DMS ρ=0.275，π=0.450
F_hops_noble	ethyl_octanoate ρ=0.505，π=0.970	ethyl_decanoate ρ=0.458，π=0.600	ethanol..v.v. ρ=0.434，π=0.335
F_hops_woody	ethyl.tetradecanoate ρ=0.346，π=0.460	ethyl_decanoate ρ=0.342，π=0.390	humulene.epoxide.II ρ=0.326，π=0.180
F_esters_all	acetaldehyde ρ=0.404，π=0.780	ethyl_acetate ρ=0.380，π=0.675	n.hexanol ρ=0.376，π=0.465
F_esters_ethac	ethyl_acetate ρ=0.503，π=0.980	ethanol..v.v. ρ=0.466，π=0.885	glycerol ρ=0.443，π=0.630
F_esters_isoaa	n.hexanol ρ=0.305，π=0.675	isopentyl_acetate ρ=0.274，π=0.465	acetaldehyde ρ=0.244，π=0.235
F_esters_flower	beta.phellandrene ρ=0.234，π=0.550	isopentyl.butanoate ρ=-0.201，π=0.280	terpinolene ρ=0.177，π=0.150
F_esters_fruity	DES ρ=-0.292，π=0.740	acetic_acid.g.L. ρ=0.244，π=0.325	humulene.epoxide.II ρ=-0.234，π=0.235
acidity	prenyl.isobutyrate ρ=0.435，π=0.565	ethyl.phenylacetate ρ=0.430，π=0.470	perillyl.acetate ρ=0.417，π=0.330
bitternes	ethyl_octanoate ρ=0.593，π=0.985	ethyl_decanoate ρ=0.559，π=0.720	MeSH ρ=0.511，π=0.285
sweetness	ethyl_decanoate ρ=-0.391，π=0.570	pentyl.octanoate ρ=-0.363，π=0.490	iron ρ=0.359，π=0.465
X4vg	X4VG ρ=0.473，π=0.875	delta.terpinyl.acetate ρ=0.399，π=0.450	neryl.formate ρ=-0.383，π=0.285
diacetyl	eugenol ρ=-0.323，π=0.690	ethyl_decanoate ρ=-0.283，π=0.410	alpha.calacorene ρ=-0.275，π=0.285
dms	terpinen.4.ol ρ=-0.196，π=0.190	E.nerolidol ρ=0.194，π=0.200	car.3.en.2.one ρ=0.186，π=0.180
metallic	ethyl_isovalerate ρ=-0.250，π=0.350	iron ρ=0.244，π=0.305	X6.methyl.5.hepten.2.one ρ=-0.237，π=0.210

感官字段	第 1 项	第 2 项	第 3 项
stale_hops	X2.undecanol ρ=0.300，π=0.645	alloaromadendrene.epoxide ρ=0.278，π=0.445	neryl.formate ρ=0.270，π=0.265
t2n	beta.phellandrene ρ=-0.214，π=0.270	terpinen.4.ol ρ=-0.204，π=0.160	geraniol ρ=-0.201，π=0.250
orange	camphor ρ=0.367，π=0.865	limonene ρ=0.296，π=0.380	ethanol..v.v. ρ=-0.292，π=0.315
coriander	X2.methyl.benzofuran ρ=0.238，π=0.240	E.ocimenone ρ=0.236，π=0.205	terpinen.4.ol ρ=0.235，π=0.190
clove	limonene ρ=0.342，π=0.915	eucalyptol ρ=0.236，π=0.285	camphor ρ=0.206，π=0.115
lactic	lactic_acid.mg.L. ρ=0.448，π=0.550	perillyl.acetate ρ=0.443，π=0.525	prenyl.isobutyrate ρ=0.429，π=0.360
acetic	prenyl.isobutyrate ρ=0.406，π=0.685	ethyl_isovalerate ρ=0.391，π=0.470	ethyl.phenylacetate ρ=0.385，π=0.370
barnyard	X2.undecanol ρ=0.285，π=0.545	neryl.formate ρ=0.280，π=0.375	alloaromadendrene.epoxide ρ=0.266，π=0.340

表 B-2 给出每个候选的化学名称、附件来源、量纲及文献支持范围。阈值仅与对应的校准浓度比较；缺失阈值保持空缺。一般背景与间接关联均不视为目标感官机制已经证实。

表 B-2 完整候选的化学信息及证据

感官与名次	化合物	来源与量纲	依据及适用范围
A_esters_all 第 1 项	正己醇 n.hexanol	酵母；mg/L 均值未给出；中位未给出	一般背景 [7] 鲜啤 GC-O/AEDA 检出有气味活性的正己醇，嗅闻描述为山楂样。 可补充果香背景，未检验本行香蕉香或酯类评分的直接来源。
A_esters_all 第 2 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
A_esters_all 第 3 项	乙酸乙酯 ethyl_acetate	酵母；mg/L 均值 24；中位 23	直接气味依据 [1];[4] 乙酸乙酯具有果香/溶剂样气味；啤酒加标亦显示其改变部分缺陷感知。 气味与酯类/指甲油样描述相符，但不验证本样本相关系数或单独剂量效应。
A_esters_ethac 第 1 项	乙酸乙酯 ethyl_acetate	酵母；mg/L 均值 24；中位 23	直接气味依据 [1];[4] 乙酸乙酯具有果香/溶剂样气味；啤酒加标亦显示其改变部分缺陷感知。 气味与酯类/指甲油样描述相符，但不验证本样本相关系数或单独剂量效应。

感官与名次	化合物	来源与量纲	依据及适用范围
A_esters_ethac 第 2 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
A_esters_ethac 第 3 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
A_esters_flower 第 1 项	Beta-phellandrene beta.phellandrene	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_esters_flower 第 2 项	乙酸异丁酯 isobutyl_acetate	酵母；mg/L 均值 1；中位 1	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_esters_flower 第 3 项	α-松油醇 X1.alpha.terpineol	酒花；mg/L 均值 1.5；中位 1.5	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_esters_fruity 第 1 项	Beta-phellandrene beta.phellandrene	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_esters_fruity 第 2 项	丁香酚 eugenol	香辛料；mg/L 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_esters_fruity 第 3 项	乳酸 lactic_acid.mg.L.	野生菌群；mg/L 均值 416.667；中位 400	一般背景 [1] 原研究说明乳酸贡献酸啤酒的酸味。 支持酸感官背景；非本行果香等其他描述的直接来源证明。
A_esters_isoaa 第 1 项	正己醇 n.hexanol	酵母；mg/L 均值未给出；中位未给出	一般背景 [7] 鲜啤 GC-O/AEDA 检出有气味活性的正己醇，嗅闻描述为山楂样。 可补充果香背景，未检验本行香蕉香或酯类评分的直接来源。
A_esters_isoaa 第 2 项	乙酸异戊酯 isopentyl_acetate	酵母；mg/L 均值 0.603333；中位 0.6	直接气味依据 [5] GC-O/MS 将乙酸异戊酯的气味标为香蕉。 相同气味描述的定性依据，非本样本关联的干预验证。

感官与名次	化合物	来源与量纲	依据及适用范围
A_esters_isoaa 第 3 项	异戊醇 isoamyl_alcohol	酵母；mg/L 均值 40.015；中位 45	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
A_hops_all 第 1 项	辛酸乙酯 ethyl_octanoate	酵母；mg/L 均值 0.7；中位 0.75	间接关联 [1];[5] GC-O/MS 报告果香/胶样气味；原研究报告同酒花感知和苦味的意外关联。 原研究与本题共享数据，非独立重复；未证明该酯直接产生酒花香或苦味。
A_hops_all 第 2 项	反式-2-壬烯醛 X.E..2.nonenal	其他；mg/L 均值未给出；中位未给出	一般背景 [10] 同位素研究支持老化期间反式-2-壬烯醛释放与纸板味相关。 本行目标为酒花感官，不能由纸板味证据解释其正相关，也不能与 Stale hops 等同。
A_hops_all 第 3 项	癸酸乙酯 ethyl_decanoate	酵母；mg/L 均值 1.035；中位 1.035	间接关联 [1] 原研究报告癸酸乙酯同其他发酵产物共变，并讨论同酒花感知和苦味的关联。 同源数据的背景说明，非独立的直接气味/抑制机制验证。
A_hops_citrus 第 1 项	香茅醇 citronellol	酒花；mg/L 均值 0.0245；中位 0.0245	直接气味依据 [6] 香叶醇、香茅醇与芳樟醇在啤酒中具有果香/柑橘协同；芳樟醇亦有 GC-O 花香/柑橘依据。 三组分交互依赖基质；不支持其他目标（如 t2n）的直接抑制机制。
A_hops_citrus 第 2 项	Humulene epoxide II humulene.epoxide.II	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_hops_citrus 第 3 项	芳樟醇 linalool	酒花；mg/L 均值 0.027285；中位 0.0045	直接气味依据 [6];[5] 香叶醇、香茅醇与芳樟醇在啤酒中具有果香/柑橘协同；芳樟醇亦有 GC-O 花香/柑橘依据。 三组分交互依赖基质；不支持其他目标（如 t2n）的直接抑制机制。
A_hops_noble 第 1 项	辛酸乙酯 ethyl_octanoate	酵母；mg/L 均值 0.7；中位 0.75	间接关联 [1];[5] GC-O/MS 报告果香/胶样气味；原研究报告同酒花感知和苦味的意外关联。 原研究与本题共享数据，非独立重复；未证明该酯直接产生酒花香或苦味。
A_hops_noble 第 2 项	癸酸乙酯 ethyl_decanoate	酵母；mg/L 均值 1.035；中位 1.035	间接关联 [1] 原研究报告癸酸乙酯同其他发酵产物共变，并讨论同酒花感知和苦味的关联。 同源数据的背景说明，非独立的直接气味/抑制机制验证。

感官与名次	化合物	来源与量纲	依据及适用范围
A_hops_noble 第 3 项	反式-2-壬烯醛 X.E..2.nonenal	其他；mg/L 均值未给出；中位未给出	一般背景 [10] 同位素研究支持老化期间反式-2-壬烯醛释放与纸板味相关。 本行目标为酒花感官，不能由纸板味证据解释其正相关，也不能与 Stale hops 等同。
A_hops_tropical 第 1 项	二甲基硫醚 DMS	麦芽；μg/L 均值 17.25；中位 19	一般背景 [4] DMS 具有卷心菜样气味，其感知受乙酸酯和芳樟醇改变。 没有直接验证 DMS 导致本行热带酒花感官。
A_hops_tropical 第 2 项	3-furanmethanol X3.furanmethanol	麦芽；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_hops_tropical 第 3 项	Methyl geranate methyl.geranate	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_hops_woody 第 1 项	Trans-dihydro-α-terpinyl acetate trans.dihydro.alpha.terpinyl.acetate	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_hops_woody 第 2 项	α-calacorene alpha.calacorene	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_hops_woody 第 3 项	Ethyl tetradecanoate ethyl.tetradecanoate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_malt_all 第 1 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
A_malt_all 第 2 项	Methylpyrazine methylpyrazine	麦芽；mg/L 均值 1；中位 1	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_malt_all 第 3 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。

感官与名次	化合物	来源与量纲	依据及适用范围
A_malt_bread 第 1 项	甘油 glycerol	酵母；g/L 均值 4.43333；中位 2	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
A_malt_bread 第 2 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
A_malt_bread 第 3 项	松油烯-4-醇 terpinen.4.ol	香辛料；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_malt_burn 第 1 项	异丁醇 isobutanol	酵母；mg/L 均值 80；中位 100	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
A_malt_burn 第 2 项	二乙基硫醚 DES	酵母；μg/L 均值 1.2；中位 1.2	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_malt_burn 第 3 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
A_malt_cara 第 1 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
A_malt_cara 第 2 项	2-乙基-1-己醇 X2.ethyl.1.hexanol	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_malt_cara 第 3 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
A_malt_grain 第 1 项	松油烯-4-醇 terpinen.4.ol	香辛料；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。

感官与名次	化合物	来源与量纲	依据及适用范围
A_malt_grain 第 2 项	Beta-phellandrene beta.phellandrene	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
A_malt_grain 第 3 项	异龙脑 isoborneol	其他；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_esters_all 第 1 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
F_esters_all 第 2 项	乙酸乙酯 ethyl_acetate	酵母；mg/L 均值 24；中位 23	直接气味依据 [1];[4] 乙酸乙酯具有果香/溶剂样气味；啤酒加标亦显示其改变部分缺陷感知。 气味与酯类/指甲油样描述相符，但不验证本样本相关系数或单独剂量效应。
F_esters_all 第 3 项	正己醇 n.hexanol	酵母；mg/L 均值未给出；中位未给出	一般背景 [7] 鲜啤 GC-O/AEDA 检出有气味活性的正己醇，嗅闻描述为山楂样。 可补充果香背景，未检验本行香蕉香或酯类评分的直接来源。
F_esters_ethac 第 1 项	乙酸乙酯 ethyl_acetate	酵母；mg/L 均值 24；中位 23	直接气味依据 [1];[4] 乙酸乙酯具有果香/溶剂样气味；啤酒加标亦显示其改变部分缺陷感知。 气味与酯类/指甲油样描述相符，但不验证本样本相关系数或单独剂量效应。
F_esters_ethac 第 2 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
F_esters_ethac 第 3 项	甘油 glycerol	酵母；g/L 均值 4.43333；中位 2	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
F_esters_flower 第 1 项	Beta-phellandrene beta.phellandrene	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_esters_flower 第 2 项	Isopentyl butanoate isopentyl.butanoate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。

感官与名次	化合物	来源与量纲	依据及适用范围
F_esters_flower 第 3 项	Terpinolene terpinolene	香辛料；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_esters_fruity 第 1 项	二乙基硫醚 DES	酵母；μg/L 均值 1.2；中位 1.2	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_esters_fruity 第 2 项	乙酸 acetic_acid.g.L.	野生菌群；g/L 均值 0.14025；中位 0.145	一般背景 [5] 啤酒 GC-O/MS 报告乙酸的酸气味。 不验证本行酯类果味的直接产生机制。
F_esters_fruity 第 3 项	Humulene epoxide II humulene.epoxide.II	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_esters_isoaa 第 1 项	正己醇 n.hexanol	酵母；mg/L 均值未给出；中位未给出	一般背景 [7] 鲜啤 GC-O/AEDA 检出有气味活性的正己醇，嗅闻描述为山楂样。 可补充果香背景，未检验本行香蕉香或酯类评分的直接来源。
F_esters_isoaa 第 2 项	乙酸异戊酯 isopentyl_acetate	酵母；mg/L 均值 0.603333；中位 0.6	直接气味依据 [5] GC-O/MS 将乙酸异戊酯的气味标为香蕉。 相同气味描述的定性依据，非本样本关联的干预验证。
F_esters_isoaa 第 3 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
F_hops_all 第 1 项	辛酸乙酯 ethyl_octanoate	酵母；mg/L 均值 0.7；中位 0.75	间接关联 [1];[5] GC-O/MS 报告果香/胶样气味；原研究报告同酒花感知和苦味的意外关联。 原研究与本题共享数据，非独立重复；未证明该酯直接产生酒花香或苦味。
F_hops_all 第 2 项	反式-2-壬烯醛 X.E..2.nonenal	其他；mg/L 均值未给出；中位未给出	一般背景 [10] 同位素研究支持老化期间反式-2-壬烯醛释放与纸板味相关。 本行目标为酒花感官，不能由纸板味证据解释其正相关，也不能与 Stale hops 等同。
F_hops_all 第 3 项	癸酸乙酯 ethyl_decanoate	酵母；mg/L 均值 1.035；中位 1.035	间接关联 [1] 原研究报告癸酸乙酯同其他发酵产物共变，并讨论同酒花感知和苦味的关联。 同源数据的背景说明，非独立的直接气味/抑制机制验证。

感官与名次	化合物	来源与量纲	依据及适用范围
F_hops_citrus 第 1 项	Humulene epoxide II humulene.epoxide.II	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_hops_citrus 第 2 项	呋喃甲酸乙酯 ethyl.furoate	麦芽；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_hops_citrus 第 3 项	糠醛 furfural	麦芽；mg/L 均值 60；中位 37.5	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_hops_noble 第 1 项	辛酸乙酯 ethyl_octanoate	酵母；mg/L 均值 0.7；中位 0.75	间接关联 [1];[5] GC-O/MS 报告果香/胶样气味；原研究报告同酒花感知和苦味的意外关联。 原研究与本题共享数据，非独立重复；未证明该酯直接产生酒花香或苦味。
F_hops_noble 第 2 项	癸酸乙酯 ethyl_decanoate	酵母；mg/L 均值 1.035；中位 1.035	间接关联 [1] 原研究报告癸酸乙酯同其他发酵产物共变，并讨论同酒花感知和苦味的关联。 同源数据的背景说明，非独立的直接气味/抑制机制验证。
F_hops_noble 第 3 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
F_hops_tropical 第 1 项	香叶醇 geraniol	酒花；mg/L 均值 0.0315；中位 0.023	一般背景 [6] 香叶醇、香茅醇与芳樟醇在啤酒中具有果香/柑橘协同；芳樟醇亦有 GC-O 花香/柑橘依据。 三组分交互依赖基质；不支持其他目标（如 t2n）的直接抑制机制。
F_hops_tropical 第 2 项	乙酸己酯 hexyl.acetate	酵母；mg/L 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_hops_tropical 第 3 项	二甲基硫醚 DMS	麦芽；μg/L 均值 17.25；中位 19	一般背景 [4] DMS 具有卷心菜样气味，其感知受乙酸酯和芳樟醇改变。 没有直接验证 DMS 导致本行热带酒花感官。
F_hops_woody 第 1 项	Ethyl tetradecanoate ethyl.tetradecanoate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。

感官与名次	化合物	来源与量纲	依据及适用范围
F_hops_woody 第 2 项	癸酸乙酯 ethyl_decanoate	酵母；mg/L 均值 1.035；中位 1.035	间接关联 [1] 原研究报告癸酸乙酯同其他发酵产物共变，并讨论同酒花感知和苦味的关联。 同源数据的背景说明，非独立的直接气味/抑制机制验证。
F_hops_woody 第 3 项	Humulene epoxide II humulene.epoxide.II	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_malt_all 第 1 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
F_malt_all 第 2 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
F_malt_all 第 3 项	甲硫醇 MeSH	酵母；μg/L 均值未给出；中位未给出	一般背景 [1] 原研究描述甲硫醇在高浓度下呈硫臭、腐烂卷心菜样气味。 未证明本行麦芽或苦味由甲硫醇直接产生；来源与本题共享数据。
F_malt_bread 第 1 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
F_malt_bread 第 2 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
F_malt_bread 第 3 项	甘油 glycerol	酵母；g/L 均值 4.43333；中位 2	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
F_malt_burn 第 1 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。

感官与名次	化合物	来源与量纲	依据及适用范围
F_malt_burn 第 2 项	甲硫醇 MeSH	酵母；μg/L 均值未给出；中位未给出	一般背景 [1] 原研究描述甲硫醇在高浓度下呈硫臭、腐烂卷心菜样气味。 未证明本行麦芽或苦味由甲硫醇直接产生；来源与本题共享数据。
F_malt_burn 第 3 项	甘油 glycerol	酵母；g/L 均值 4.43333；中位 2	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
F_malt_cara 第 1 项	乙醛 acetaldehyde	酵母；mg/L 均值 50；中位 50	一般背景 [7] 鲜啤感官实验以乙醛作生青味训练标准。 该训练标准未验证乙醛对本行麦芽、焦糖或酯香描述的直接作用。
F_malt_cara 第 2 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
F_malt_cara 第 3 项	丁酸乙酯 ethyl.butyrate	酵母；mg/L 均值 0.45；中位 0.45	一般背景 [5] GC-O/MS 对 3-甲基丁酸乙酯及丁酸乙酯报告果香/甜果香描述。 不验证本行醋酸、金属或麦芽焦糖感官的直接作用。
F_malt_grain 第 1 项	异龙脑 isoborneol	其他；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_malt_grain 第 2 项	Terpinen-4-ol acetate terpinen.4.ol.acetate	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
F_malt_grain 第 3 项	反式-β-紫罗兰酮 X.E..beta.ionone	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
X4vg 第 1 项	4-乙烯基愈创木酚 X4VG	酵母；mg/L 均值 0.206333；中位 0.2	直接气味依据 [5] 啤酒 GC-O/MS 识别 4-乙烯基愈创木酚为丁香样气味。 定性气味依据，不代表预测关系或统一风格阈值已验证。
X4vg 第 2 项	Terpiryl acetate delta.terpinyl.acetate	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。

感官与名次	化合物	来源与量纲	依据及适用范围
X4vg 第 3 项	Neryl formate neryl.formate	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
acetic 第 1 项	Prenyl isobutyrate prenyl.isobutyrate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
acetic 第 2 项	异戊酸乙酯 ethyl_isovalerate	其他；mg/L 均值 0.1；中位 0.1	一般背景 [5] GC-O/MS 对 3-甲基丁酸乙酯及丁酸乙酯报告果香/甜果香描述。 不验证本行醋酸、金属或麦芽焦糖感官的直接作用。
acetic 第 3 项	苯乙酸乙酯 ethyl.phenylacetate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
acidity 第 1 项	Prenyl isobutyrate prenyl.isobutyrate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
acidity 第 2 项	苯乙酸乙酯 ethyl.phenylacetate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
acidity 第 3 项	Perillyl acetate perillyl.acetate	香辛料；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
barnyard 第 1 项	2-十一醇 X2.undecanol	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
barnyard 第 2 项	Neryl formate neryl.formate	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
barnyard 第 3 项	Allo-aromadendrene epoxide alloaromadendrene.epoxide	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
bitternes 第 1 项	辛酸乙酯 ethyl_octanoate	酵母；mg/L 均值 0.7；中位 0.75	间接关联 [1];[5] GC-O/MS 报告果香/胶样气味；原研究报告同酒花感知和苦味的意外关联。 原研究与本题共享数据，非独立重复；未证明该酯直接产生酒花香或苦味。

感官与名次	化合物	来源与量纲	依据及适用范围
bitternes 第 2 项	癸酸乙酯 ethyl_decanoate	酵母；mg/L 均值 1.035；中位 1.035	间接关联 [1] 原研究报告癸酸乙酯同其他发酵产物共变，并讨论同酒花感知和苦味的关联。 同源数据的背景说明，非独立的直接气味/抑制机制验证。
bitternes 第 3 项	甲硫醇 MeSH	酵母；μg/L 均值未给出；中位未给出	一般背景 [1] 原研究描述甲硫醇在高浓度下呈硫臭、腐烂卷心菜样气味。 未证明本行麦芽或苦味由甲硫醇直接产生；来源与本题共享数据。
clove 第 1 项	柠檬烯 limonene	酒花；未给出 均值未给出；中位未给出	一般背景 [8] Amarillo 单酒花酿造对照中，柠檬烯等萜类与柑橘/花香谱共同变化。 非柠檬烯单体加标，不支持丁香机制，也未隔离本行橙味效应。
clove 第 2 项	桉叶油醇 eucalyptol	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
clove 第 3 项	樟脑 camphor	香辛料；未给出 均值未给出；中位未给出	一般背景 [9] 芫荽啤酒实验检出樟脑，并报告其与过量芳樟醇下的花香协同。 混合物花香不等于单体橙味或丁香味；本行关联仍未获直接验证。
coriander 第 1 项	2-methyl-benzofuran X2.methyl.benzofuran	麦芽；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
coriander 第 2 项	Ocimenone E.ocimenone	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
coriander 第 3 项	松油烯-4-醇 terpinen.4.ol	香辛料；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
diacetyl 第 1 项	丁香酚 eugenol	香辛料；mg/L 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
diacetyl 第 2 项	癸酸乙酯 ethyl_decanoate	酵母；mg/L 均值 1.035；中位 1.035	一般背景 [1] 原研究报告癸酸乙酯同其他发酵产物共变，并讨论同酒花感知和苦味的关联。 同源数据的背景说明，非独立的直接气味/抑制机制验证。

感官与名次	化合物	来源与量纲	依据及适用范围
diacetyl 第 3 项	α-calacorene alpha.calacorene	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
dms 第 1 项	松油烯-4-醇 terpinen.4.ol	香辛料；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
dms 第 2 项	反式橙花叔醇 E.nerolidol	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
dms 第 3 项	Car-3-en-2-one car.3.en.2.one	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
lactic 第 1 项	乳酸 lactic_acid.mg.L.	野生菌群；mg/L 均值 416.667；中位 400	直接气味依据 [1] 原研究说明乳酸贡献酸啤酒的酸味。 支持酸感官背景；非本行果香等其他描述的直接来源证明。
lactic 第 2 项	Perillyl acetate perillyl.acetate	香辛料；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
lactic 第 3 项	Prenyl isobutyrate prenyl.isobutyrate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
metallic 第 1 项	异戊酸乙酯 ethyl_isovalerate	其他；mg/L 均值 0.1；中位 0.1	一般背景 [5] GC-O/MS 对 3-甲基丁酸乙酯及丁酸乙酯报告果香/甜果香描述。 不验证本行醋酸、金属或麦芽焦糖感官的直接作用。
metallic 第 2 项	铁（总量字段） iron	其他；mg/L 均值 0.1；中位 0.1	一般背景 [11] 二价铁盐溶液的时间—强度实验观察到持续金属感。 盐种、价态、基质与啤酒总铁不同；只作背景，不外推阈值或甜味机制。
metallic 第 3 项	Methyl heptenone X6.methyl.5.hepten.2.one	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
orange 第 1 项	樟脑 camphor	香辛料；未给出 均值未给出；中位未给出	一般背景 [9] 芫荽啤酒实验检出樟脑，并报告其与过量芳樟醇下的花香协同。 混合物花香不等于单体橙味或丁香味；本行关联仍未获直接验证。

感官与名次	化合物	来源与量纲	依据及适用范围
orange 第 2 项	柠檬烯 limonene	酒花；未给出 均值未给出；中位未给出	一般背景 [8] Amarillo 单酒花酿造对照中，柠檬烯等萜类与柑橘/花香谱共同变化。 非柠檬烯单体加标，不支持丁香机制，也未隔离本行橙味效应。
orange 第 3 项	乙醇 ethanol..v.v.	酵母；v/v 均值 1.75726；中位 1.7372	间接关联 [1] 原研究将酯类及多种醇类作为共同发酵来源讨论；可形成工艺/风格共变标记。 间接共变解释，不证明本行麦芽或酯类具体气味由该物质直接产生。
stale_hops 第 1 项	2-十一醇 X2.undecanol	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
stale_hops 第 2 项	Allo-aromadendrene epoxide alloaromadendrene.epoxide	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
stale_hops 第 3 项	Neryl formate neryl.formate	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
sweetness 第 1 项	癸酸乙酯 ethyl_decanoate	酵母；mg/L 均值 1.035；中位 1.035	一般背景 [1] 原研究报告癸酸乙酯同其他发酵产物共变，并讨论同酒花感知和苦味的关联。 同源数据的背景说明，非独立的直接气味/抑制机制验证。
sweetness 第 2 项	Pentyl octanoate pentyl.octanoate	酵母；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
sweetness 第 3 项	铁（总量字段） iron	其他；mg/L 均值 0.1；中位 0.1	一般背景 [11] 二价铁盐溶液的时间—强度实验观察到持续金属感。 盐种、价态、基质与啤酒总铁不同；只作背景，不外推阈值或甜味机制。
t2n 第 1 项	Beta-phellandrene beta.phellandrene	酒花；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。
t2n 第 2 项	松油烯-4-醇 terpinen.4.ol	香辛料；未给出 均值未给出；中位未给出	尚未证实 本次核实文献未提供该化合物—感官项的直接证据。 仅保留统计候选，不作直接机制解释。

感官与名次	化合物	来源与量纲	依据及适用范围
t2n 第 3 项	香叶醇 geraniol	酒花；mg/L 均值 0.0315；中位 0.023	一般背景 [6] 香叶醇、香茅醇与芳樟醇在啤酒中具有果香/柑橘协同；芳樟醇亦有 GC-O 花香/柑橘依据。 三组分交互依赖基质；不支持其他目标（如 t2n）的直接抑制机制。

表 B-3 给出 218 项化学候选中的预测依赖前三，各项标出平均 ΔMSE 与正值折数。J 为与原边际相关前三的 Jaccard；原表 B-1 保持不变。完整 231 项置换结果、五折相关模块及分层 Bootstrap 结果随支撑材料保存。

表 B-3　全部感官的折外置换候选

感官	置换第 1 项	第 2 项	第 3 项	J
A_malt_all	lactic_acid.mg.L. Δ=0.0103；4/5	X4.ethyl.phenol Δ=0.00403；4/5	beta.phellandrene Δ=0.00341；5/5	0.00
A_malt_grain	cis.dihydro.beta.terpineol Δ=0.00156；5/5	ethyl_isovalerate Δ=0.00101；4/5	CS2 Δ=0.000621；4/5	0.00
A_malt_bread	lactic_acid.mg.L. Δ=0.00263；4/5	E.cinnamaldehyde Δ=0.00115；4/5	ethyl_acetate Δ=0.00101；3/5	0.00
A_malt_cara	lactic_acid.mg.L. Δ=0.00581；4/5	ethyl_isovalerate Δ=0.00329；4/5	X4.ethyl.phenol Δ=0.00199；4/5	0.00
A_malt_burn	lactic_acid.mg.L. Δ=0.00845；5/5	alpha.muurolol Δ=0.00216；4/5	ethyl.furoate Δ=0.00192；4/5	0.00
A_hops_all	ethyl_isovalerate Δ=0.0221；5/5	lactic_acid.mg.L. Δ=0.0117；5/5	ethyl_octanoate Δ=0.00838；5/5	0.20
A_hops_citrus	ethyl_isovalerate Δ=0.0044；4/5	lactic_acid.mg.L. Δ=0.00143；3/5	cis.dihydro.beta.terpineol Δ=0.00132；4/5	0.00
A_hops_tropical	ethyl_isovalerate Δ=0.0123；5/5	lactic_acid.mg.L. Δ=0.0093；4/5	isopentyl.butanoate Δ=0.00354；5/5	0.00
A_hops_noble	ethyl_isovalerate Δ=0.0103；5/5	ethyl_octanoate Δ=0.00527；5/5	ethyl_decanoate Δ=0.00378；5/5	0.50
A_hops_woody	ethyl_isovalerate Δ=0.00252；5/5	cis.dihydro.beta.terpineol Δ=0.000737；2/5	X1.octen.3.ol Δ=0.000352；5/5	0.00
A_esters_all	ethyl_acetate Δ=0.00411；5/5	ethyl_decanoate Δ=0.00157；4/5	ethyl_octanoate Δ=0.00146；4/5	0.20
A_esters_ethac	ethyl_acetate Δ=0.00124；4/5	X2E.6Z.farnesal Δ=0.000951；4/5	glycerol Δ=0.000707；5/5	0.20
A_esters_isoaa	beta.phellandrene Δ=0.00188；4/5	ethyl_acetate Δ=0.00178；5/5	ethyl.hexadecanoate Δ=0.00133；3/5	0.00
A_esters_flower	beta.phellandrene Δ=0.00192；5/5	X4.ethyl.guaiacol Δ=0.00115；4/5	ethyl_isovalerate Δ=0.00103；3/5	0.20

感官	置换第 1 项	第 2 项	第 3 项	J
A_esters_fruity	beta.phellandrene Δ=0.00227；5/5	ethyl_isovalerate Δ=0.000667；3/5	X.E..alpha.ionone Δ=0.000477；3/5	0.20
F_malt_all	lactic_acid.mg.L. Δ=0.0179；5/5	X4.ethyl.phenol Δ=0.00538；4/5	X4.ethyl.guaiacol Δ=0.00395；4/5	0.00
F_malt_grain	cis.dihydro.beta.terpineol Δ=0.00202；3/5	ethyl_isovalerate Δ=0.00104；3/5	geraniol Δ=0.000468；5/5	0.00
F_malt_bread	lactic_acid.mg.L. Δ=0.00422；5/5	glycerol Δ=0.00137；5/5	cis.dihydro.beta.terpineol Δ=0.00136；5/5	0.20
F_malt_cara	lactic_acid.mg.L. Δ=0.00818；5/5	ethyl_isovalerate Δ=0.00362；5/5	X4.ethyl.phenol Δ=0.00193；4/5	0.00
F_malt_burn	lactic_acid.mg.L. Δ=0.0175；5/5	ethyl.furoate Δ=0.00485；5/5	cis.dihydro.beta.terpineol Δ=0.00425；3/5	0.00
F_hops_all	ethyl_isovalerate Δ=0.0283；5/5	lactic_acid.mg.L. Δ=0.0184；5/5	cis.dihydro.beta.terpineol Δ=0.0145；5/5	0.00
F_hops_citrus	ethyl_isovalerate Δ=0.0034；4/5	lactic_acid.mg.L. Δ=0.00303；4/5	cis.dihydro.beta.terpineol Δ=0.00213；4/5	0.00
F_hops_tropical	ethyl_isovalerate Δ=0.00692；5/5	lactic_acid.mg.L. Δ=0.00635；5/5	cis.dihydro.beta.terpineol Δ=0.00188；3/5	0.00
F_hops_noble	ethyl_isovalerate Δ=0.0153；5/5	cis.dihydro.beta.terpineol Δ=0.00812；4/5	lactic_acid.mg.L. Δ=0.00683；5/5	0.00
F_hops_woody	ethyl_isovalerate Δ=0.00753；5/5	lactic_acid.mg.L. Δ=0.00204；3/5	methyl.geranate Δ=0.000755；3/5	0.00
F_esters_all	ethyl_acetate Δ=0.00521；5/5	ethyl_isovalerate Δ=0.00392；3/5	ethanol..v.v. Δ=0.00329；4/5	0.20
F_esters_ethac	ethanol..v.v. Δ=0.00247；4/5	ethyl_acetate Δ=0.00235；4/5	ethyl_octanoate Δ=0.00204；5/5	0.50
F_esters_isoaa	lactic_acid.mg.L. Δ=0.00221；4/5	beta.phellandrene Δ=0.0022；4/5	ethyl_acetate Δ=0.00208；5/5	0.00
F_esters_flower	beta.phellandrene Δ=0.0016；5/5	E.cinnamaldehyde Δ=0.00155；4/5	X4.ethyl.guaiacol Δ=0.000996；4/5	0.20
F_esters_fruity	MeSH Δ=0.00118；4/5	X.E..alpha.ionone Δ=0.00085；3/5	ethyl_acetate Δ=0.000756；5/5	0.00
acidity	lactic_acid.mg.L. Δ=0.134；5/5	X4.ethyl.phenol Δ=0.0115；3/5	X4.ethyl.guaiacol Δ=0.0115；4/5	0.00
bitternes	lactic_acid.mg.L. Δ=0.0273；5/5	cis.dihydro.beta.terpineol Δ=0.0208；5/5	ethyl_isovalerate Δ=0.0137；5/5	0.00
sweetness	E.cinnamaldehyde Δ=0.00832；5/5	ethyl_isovalerate Δ=0.00532；4/5	ethyl_octanoate Δ=0.00482；4/5	0.00
X4vg	X4VG Δ=0.00624；5/5	lactic_acid.mg.L. Δ=0.00556；4/5	ethyl_isovalerate Δ=0.00383；4/5	0.20
diacetyl	E.cinnamaldehyde Δ=0.00323；4/5	lactic_acid.mg.L. Δ=0.00298；4/5	ethyl_isovalerate Δ=0.00249；5/5	0.00

感官	置换第 1 项	第 2 项	第 3 项	J
dms	cis.dihydro.beta.terpineol Δ=0.000687；4/5	methyl.geranate Δ=0.000541；5/5	X2.butyloctanoate Δ=0.000523；5/5	0.00
metallic	ethyl_isovalerate Δ=0.0079；5/5	lactic_acid.mg.L. Δ=0.00266；4/5	ethyl_octanoate Δ=0.00175；4/5	0.20
stale_hops	ethyl_acetate Δ=0.000843；4/5	heptyl.acetate Δ=0.000664；3/5	beta.phellandrene Δ=0.000553；3/5	0.00
t2n	ethyl_isovalerate Δ=0.00217；4/5	cis.dihydro.beta.terpineol Δ=0.000953；4/5	ethyl_acetate Δ=0.000943；4/5	0.00
orange	linalool Δ=0.00574；5/5	ethyl_isovalerate Δ=0.0056；3/5	ethyl..E..linalool Δ=0.0052；4/5	0.00
coriander	ethyl_isovalerate Δ=0.00478；3/5	geraniol Δ=0.00176；4/5	X1.alpha.terpineol Δ=0.00152；4/5	0.00
clove	cis.dihydro.beta.terpineol Δ=0.00462；3/5	limonene Δ=0.00354；5/5	alpha.muurolol Δ=0.00242；4/5	0.20
lactic	lactic_acid.mg.L. Δ=0.0868；5/5	ethyl_isovalerate Δ=0.00547；3/5	E.cinnamaldehyde Δ=0.00503；3/5	0.20
acetic	lactic_acid.mg.L. Δ=0.0891；5/5	ethyl_isovalerate Δ=0.00927；4/5	X4.ethyl.phenol Δ=0.00865；4/5	0.20
barnyard	ethyl_acetate Δ=0.00096；4/5	heptyl.acetate Δ=0.000697；3/5	beta.phellandrene Δ=0.000601；3/5	0.00

表 B-4 逐折列出表 6-4 所用乙酸乙酯模块的全部成员。模块只使用该折训练数据构建，大小及成员会变化；该表不表示五折识别出了同一个固定化学组。

表 B-4　乙酸乙酯相关模块的逐折成员

折与成员数	成员字段
第 1 折 11 项	ethyl_acetate | ethyl_decanoate | ethyl_hexanoate | ethyl_octanoate | isobutyl_acetate | isopentyl_acetate | phenethyl_acetate | glycerol | ethanol..v.v. | kcalperc | esters_sum
第 2 折 12 项	acetaldehyde | ethyl_acetate | ethyl_decanoate | ethyl_hexanoate | ethyl_octanoate | isobutyl_acetate | isopentyl_acetate | phenethyl_acetate | glycerol | ethanol..v.v. | kcalperc | esters_sum
第 3 折 9 项	ethyl_acetate | ethyl_hexanoate | isobutyl_acetate | isopentyl_acetate | phenethyl_acetate | glycerol | ethanol..v.v. | kcalperc | esters_sum
第 4 折 11 项	acetaldehyde | ethyl_acetate | ethyl_decanoate | ethyl_hexanoate | ethyl_octanoate | isobutyl_acetate | isopentyl_acetate | glycerol | ethanol..v.v. | kcalperc | esters_sum
第 5 折 27 项	acetaldehyde | ethyl_acetate | ethyl_decanoate | ethyl_hexanoate | ethyl_octanoate | isobutyl_acetate | isopentyl_acetate | phenethyl_acetate | glycerol | ethanol..v.v. | kcalperc | isobutyl.hexanoate | nerol.oxide | isopentyl.hexanoate | trans.dihydro.alpha.terpinyl.acetate | X2.butyloctanoate | X2.phenyl.ethyl.butyrate | X.Z..beta.farnesene | pentyl.octanoate | X2.methylbutyl.octanoate | X1.2.dihydro.8.hydroxy..2E..linalool | ethyl.tetradecanoate | ethyl.pentadecanoate | Z.Z.geranyl.linalool | ethyl.hexadecanoate | ethyl.octadecanoate | esters_sum

附录 C 逐源迁移检查

表 C-1 采用固定树、中央 6004 池、retain80、余量优先口径。两个 Q95 分别为预留当前模型、新种子旧协议模型的配对预测差分位数；任一大于零均记为失败。改善率已包含所有选中谱，同时保留未通过复核的 beer 96。完整 72 点策略网格及十情景化学检查随电子附录保存。

表 C-1 全部 11 款源的余量优先迁移检查

beer	距离改善	保留锚幅度	当前 Q95	旧协议 Q95	审计结果
124	59.14%	235.85%	-0.04880	-0.03263	通过
81	63.76%	90.04%	-0.08334	-0.15091	通过
218	65.02%	101.31%	-0.20229	-0.10714	通过
96	47.35%	163.70%	+0.02100	-0.04175	未通过
230	57.74%	87.86%	-0.07386	-0.09737	通过
185	66.46%	275.68%	-0.00883	-0.05151	通过
139	56.25%	85.21%	-0.05956	-0.06710	通过
209	38.78%	177.04%	-0.04141	-0.06655	通过
119	56.75%	86.27%	-0.10962	-0.14841	通过
90	35.11%	166.18%	-0.03585	-0.03919	通过
28	69.35%	101.80%	-0.29602	-0.32845	通过

表 C-2 全部 72 组迁移策略结果

模型	候选集	接近下限	排序	选出	通过	改善中位数
固定树	收缩 6004	≥10%	几何	11/11	10/11	70.08%
固定树	收缩 6004	≥10%	余量	11/11	10/11	56.75%
固定树	收缩 6004	≥30%	几何	11/11	10/11	70.08%
固定树	收缩 6004	≥30%	余量	11/11	10/11	56.75%
固定树	收缩 6004	≥50%	几何	10/11	10/11	70.08%
固定树	收缩 6004	≥50%	余量	10/11	10/11	57.95%
固定树	收缩 6004	≥60%	几何	10/11	10/11	70.08%
固定树	收缩 6004	≥60%	余量	10/11	10/11	66.75%
固定树	收缩 6004	保留 100%	几何	11/11	10/11	70.08%
固定树	收缩 6004	保留 100%	余量	11/11	10/11	66.46%
固定树	收缩 6004	保留 80%	几何	11/11	10/11	70.08%
固定树	收缩 6004	保留 80%	余量	11/11	10/11	57.74%
固定树	原 2004	≥10%	几何	9/11	7/11	64.18%

模型	候选集	接近下限	排序	选出	通过	改善中位数
固定树	原 2004	≥10%	余量	9/11	7/11	21.90%
固定树	原 2004	≥30%	几何	6/11	6/11	65.75%
固定树	原 2004	≥30%	余量	6/11	6/11	55.18%
固定树	原 2004	≥50%	几何	6/11	6/11	65.75%
固定树	原 2004	≥50%	余量	6/11	6/11	60.88%
固定树	原 2004	≥60%	几何	5/11	5/11	65.78%
固定树	原 2004	≥60%	余量	5/11	5/11	65.78%
固定树	原 2004	保留 100%	几何	8/11	6/11	64.95%
固定树	原 2004	保留 100%	余量	8/11	6/11	64.95%
固定树	原 2004	保留 80%	几何	9/11	7/11	64.18%
固定树	原 2004	保留 80%	余量	9/11	7/11	54.38%
固定树	原 6004	≥10%	几何	9/11	7/11	64.18%
固定树	原 6004	≥10%	余量	9/11	8/11	20.53%
固定树	原 6004	≥30%	几何	7/11	7/11	65.72%
固定树	原 6004	≥30%	余量	7/11	7/11	54.38%
固定树	原 6004	≥50%	几何	6/11	6/11	65.75%
固定树	原 6004	≥50%	余量	6/11	6/11	60.88%
固定树	原 6004	≥60%	几何	5/11	5/11	65.78%
固定树	原 6004	≥60%	余量	5/11	5/11	65.78%
固定树	原 6004	保留 100%	几何	8/11	6/11	64.95%
固定树	原 6004	保留 100%	余量	8/11	8/11	64.95%
固定树	原 6004	保留 80%	几何	9/11	7/11	64.18%
固定树	原 6004	保留 80%	余量	9/11	9/11	54.38%
岭回归	收缩 6004	≥10%	几何	7/11	5/11	57.13%
岭回归	收缩 6004	≥10%	余量	7/11	7/11	32.63%
岭回归	收缩 6004	≥30%	几何	7/11	5/11	57.13%
岭回归	收缩 6004	≥30%	余量	7/11	6/11	32.64%
岭回归	收缩 6004	≥50%	几何	5/11	4/11	57.70%
岭回归	收缩 6004	≥50%	余量	5/11	5/11	53.17%
岭回归	收缩 6004	≥60%	几何	2/11	2/11	70.10%
岭回归	收缩 6004	≥60%	余量	2/11	2/11	63.12%
岭回归	收缩 6004	保留 100%	几何	3/11	2/11	66.55%
岭回归	收缩 6004	保留 100%	余量	3/11	3/11	66.13%
岭回归	收缩 6004	保留 80%	几何	5/11	3/11	57.70%

模型	候选集	接近下限	排序	选出	通过	改善中位数
岭回归	收缩 6004	保留 80%	余量	5/11	5/11	53.17%
岭回归	原 2004	≥10%	几何	8/11	6/11	26.85%
岭回归	原 2004	≥10%	余量	8/11	7/11	15.93%
岭回归	原 2004	≥30%	几何	2/11	2/11	49.14%
岭回归	原 2004	≥30%	余量	2/11	2/11	49.82%
岭回归	原 2004	≥50%	几何	1/11	1/11	68.12%
岭回归	原 2004	≥50%	余量	1/11	1/11	68.12%
岭回归	原 2004	≥60%	几何	1/11	1/11	68.12%
岭回归	原 2004	≥60%	余量	1/11	1/11	68.12%
岭回归	原 2004	保留 100%	几何	3/11	2/11	27.22%
岭回归	原 2004	保留 100%	余量	3/11	2/11	27.22%
岭回归	原 2004	保留 80%	几何	3/11	2/11	27.22%
岭回归	原 2004	保留 80%	余量	3/11	1/11	27.22%
岭回归	原 6004	≥10%	几何	9/11	8/11	28.55%
岭回归	原 6004	≥10%	余量	9/11	7/11	18.21%
岭回归	原 6004	≥30%	几何	4/11	4/11	31.09%
岭回归	原 6004	≥30%	余量	4/11	4/11	30.75%
岭回归	原 6004	≥50%	几何	1/11	1/11	68.12%
岭回归	原 6004	≥50%	余量	1/11	1/11	68.12%
岭回归	原 6004	≥60%	几何	1/11	1/11	68.12%
岭回归	原 6004	≥60%	余量	1/11	1/11	68.12%
岭回归	原 6004	保留 100%	几何	3/11	2/11	29.23%
岭回归	原 6004	保留 100%	余量	3/11	2/11	27.22%
岭回归	原 6004	保留 80%	几何	4/11	3/11	25.18%
岭回归	原 6004	保留 80%	余量	4/11	3/11	22.28%

改善中位数按全部选中谱计算，包括复核未通过者；无候选时记为横线。每组分母均为 11，不以选出的条数代替源样本总数。逐化合物十情景检查及全部数值文件随支撑材料提交。

表 C-3 列出余量优先主方案全部 11 款源的 44 项浓度检查。每行上界为十情景中最严值，剩余裕量为上界减迁移浓度，单位与该行校准浓度相同；源浓度超过阈值时，上界可以高于感知阈值。化学检查不代替表 C-1 的 Stale hops 模型复核。

表 C-3 全部源的迁移前后校准浓度与保护裕量

beer	化合物与单位	源浓度	迁移浓度	最严上界	剩余裕量	检查
124	DMS μg/L	14.296	14.296	14.296	0	通过
124	Diacetyl mg/L	0.0516208	0.0625324	0.072	0.0094676	通过
124	4VG mg/L	0	0	0.16	0.16	通过
124	trans-2-nonenal mg/L	0.000803907	0.000803907	0.000803907	0	通过
81	DMS μg/L	8.85868	13.8	13.8	0	通过
81	Diacetyl mg/L	0.284814	0.247202	0.284814	0.0376123	通过
81	4VG mg/L	0	0	0.16	0.16	通过
81	trans-2-nonenal mg/L	0.003422	0.003422	0.003422	0	通过
218	DMS μg/L	26.675	26.675	26.675	0	通过
218	Diacetyl mg/L	0.0569595	0.072	0.072	0	通过
218	4VG mg/L	0	0	0.16	0.16	通过
218	trans-2-nonenal mg/L	0.00111066	0.00111066	0.00111066	0	通过
96	DMS μg/L	15.5585	15.5585	15.5585	0	通过
96	Diacetyl mg/L	0.523886	0.504705	0.523886	0.0191806	通过
96	4VG mg/L	0	0	0.16	0.16	通过
96	trans-2-nonenal mg/L	0.011935	0.00598882	0.011935	0.00594619	通过
230	DMS μg/L	15.1128	15.1128	15.1128	0	通过
230	Diacetyl mg/L	0.0417431	0.072	0.072	0	通过
230	4VG mg/L	0.0194032	0	0.16	0.16	通过
230	trans-2-nonenal mg/L	0.00149942	0.00149942	0.00149942	0	通过

beer	化合物与单位	源浓度	迁移浓度	最严上界	剩余裕量	检查
185	DMS μg/L	6.6631	13.8	13.8	0	通过
185	Diacetyl mg/L	0.0357731	0.072	0.072	0	通过
185	4VG mg/L	0	0	0.16	0.16	通过
185	trans-2-nonenal mg/L	0.00174338	0.00174338	0.00174338	0	通过
139	DMS μg/L	20.1596	20.1596	20.1596	0	通过
139	Diacetyl mg/L	0.0325513	0.072	0.072	0	通过
139	4VG mg/L	0	0	0.16	0.16	通过
139	trans-2-nonenal mg/L	0.00201172	0.00201172	0.00201172	0	通过
209	DMS μg/L	14.0721	14.0721	14.0721	0	通过
209	Diacetyl mg/L	0.0261853	0.072	0.072	0	通过
209	4VG mg/L	0	0	0.16	0.16	通过
209	trans-2-nonenal mg/L	0.00271219	0.00271219	0.00271219	0	通过
119	DMS μg/L	16.6615	16.6615	16.6615	0	通过
119	Diacetyl mg/L	0	0.0625324	0.072	0.0094676	通过
119	4VG mg/L	0.143755	0	0.16	0.16	通过
119	trans-2-nonenal mg/L	0.00483768	0.00483768	0.00483768	0	通过
90	DMS μg/L	7.93311	13.8	13.8	0	通过
90	Diacetyl mg/L	0.236137	0.236137	0.236137	0	通过
90	4VG mg/L	0	0	0.16	0.16	通过
90	trans-2-nonenal mg/L	0.00181628	0.00181628	0.00181628	0	通过
28	DMS μg/L	27.3576	27.3576	27.3576	0	通过

beer	化合物与单位	源浓度	迁移浓度	最严上界	剩余裕量	检查
28	Diacetyl mg/L	0	0.072	0.072	0	通过
28	4VG mg/L	0	0	0.16	0.16	通过
28	trans-2-nonenal mg/L	0.0115304	0.0115304	0.0115304	0	通过

附录 D 软件环境与运行方法

模型原计算环境为 Python 3.13，精确依赖列于表 D-1。程序采用 UTF-8 文本、正斜杠相对路径和固定换行规则，支持 Windows。原始赛题附件与 solution_a 文件夹并列，保持官方目录名；数据不重复打包。建模计算、结果绘图及数值检验源码全文列于附录 E。

表 D-1 计算依赖版本

软件包	版本
cloudpickle	3.1.2
contourpy	1.4.0
cycler	0.12.1
et_xmlfile	2.0.0
fonttools	4.67.0
joblib	1.6.0
kiwisolver	1.5.1
matplotlib	3.11.2
narwhals	2.27.1
numpy	2.5.4
openpyxl	3.1.5
packaging	26.3
pandas	3.1.0
pillow	13.0.0
pyparsing	3.3.3
pypdf	6.21.2
python-dateutil	3.0.0
scikit-learn	1.9.1
scipy	1.18.1
six	1.17.0
threadpoolctl	3.7.0
tzdata	2026.5

在 Windows PowerShell 中进入解压后的根目录，建立独立环境并安装依赖：

```
py -3.13 -m venv .venv
.\.venv\Scripts\python.exe -m pip install -r solution_a/requirements-lock.txt
```

对包含完整 outputs 的仓库，默认只核查现有结果，不重新训练或改写冻结记录：

```
.\.venv\Scripts\python.exe -X utf8 solution_a/run_all.py
```

支撑材料中的 paper_results 和 supplement_results 为引用结果副本，不作为训练输出目录。首次完整重建时，在新解压的目录中执行：

```
.\.venv\Scripts\python.exe -X utf8 solution_a/run_all.py --rebuild
```

重建须保留全部原始附件，依次执行数据核验、预测、关联分析、风格生成、迁移及补充验证。程序不会覆盖非空的历史或补充输出目录；重新试验时应另建副本。补充验证源码与结果位于 supplement 目录，run_supplement.py 可单独核查。计算耗时随硬件变化。历史独立重建中，主方案关键比较一致，全探索网格仍有候选与计数差异，具体范围见第 8.2 节及核验记录。

附录 E 完整计算机源程序

本附录按文件给出建模计算、结果绘图及数值检验所用源程序。源代码以可选取的文本排印，左侧为原文件行号；长行折行处不另编号。运行时使用支撑包中的同名文件，避免 PDF 阅读器复制时丢失缩进。文件清单、源码全文和支撑包采用同一份程序目录。

表 E-1 源程序目录

文件（相对 solution_a）	行数
paper/make_figures.py	468
run_all.py	52
run_q3.py	10
run_q3_domain.py	38
run_q3_optimized.py	37
run_q3_refined.py	40
run_supplement.py	31
src/01_audit.py	467
src/02_q1_baseline.py	173
src/02b_q1_robust.py	93
src/03_q2_network.py	246
src/04_stage_summary.py	131
src/05_verify_outputs.py	111
src/06_q3_sensory.py	230
src/07_q3_generation.py	419
src/08_q3_transfer.py	320
src/09_q3_report.py	271
src/10_q3_verify.py	543
src/11_q3_generation_optimized.py	288
src/12_q3_stale_optimized.py	241
src/12b_q3_stale_fixed.py	217
src/13_q3_transfer_optimized.py	335
src/14_q3_optimization_report.py	293
src/15_q3_optimized_verify.py	732
src/16_q3_stale_domain.py	323
src/17_q3_transfer_domain.py	337
src/18_q3_domain_report.py	513

文件（相对 **solution_a**）	行数
src/19_q3_domain_verify.py	566
src/20_q3_transfer_consensus.py	21
src/21_q3_beer81_audit.py	453
src/22_q3_stale_refined.py	406
src/23_q3_transfer_balanced.py	328
src/24_q3_refinement_report.py	188
src/25_q3_refined_verify.py	728
src/common.py	73
src/platform_selfcheck.py	118
src/q3_copula.py	152
src/q3_data.py	122
src/q3_generator_optimized.py	222
src/q3_stale_domain.py	158
src/q3_stale_optimized.py	180
src/q3_stale_refined.py	205
supplement/q1_additional_checks.py	67
supplement/q1_comparison.py	151
supplement/q1_indicator_ablation.py	306
supplement/q2_permutation.py	189
supplement/q2_stratified_bootstrap.py	191
supplement/reference_tables.py	331
supplement/verify_supplement.py	170

paper/make_figures.py

SHA-256: 9afa35400e3fb8c506fd2bd9652115f0fa7f6def743d654aa9afce88c368314e

```
"""Render source-backed, 16 cm research figures without changing experiment ou
tputs."""
from __future__ import annotations

import json
import os
from pathlib import Path

import matplotlib

matplotlib.use("Agg")
import matplotlib.pyplot as plt
from matplotlib import font_manager
from matplotlib.font_manager import FontProperties
from matplotlib.patches import FancyArrowPatch, Rectangle
from matplotlib.text import Text
import numpy as np
import pandas as pd


PAPER = Path(__file__).resolve().parent
SOLUTION = PAPER.parent
OUTPUT = SOLUTION / "outputs"
FIGURES = PAPER / "figures"
font_candidates = [os.environ.get("MATHORCUP_FONT", ""),
                   "C:/Windows/Fonts/simsun.ttc",
                   "/System/Library/Fonts/Supplemental/Songti.ttc",
                   "/usr/share/fonts/opentype/noto/NotoSerifCJK-Regular.ttc"]
CJK_FONT = next((Path(f) for f in font_candidates if f and Path(f).is_file()),
 None)
if CJK_FONT is None:
    raise FileNotFoundError("Set MATHORCUP_FONT to an installed Chinese font f
ile.")
font_manager.fontManager.addfont(str(CJK_FONT))
FONT = FontProperties(fname=str(CJK_FONT))
BLUE = "#315F82"
GOLD = "#A98039"
GREY = "#A3A8AC"
DARK = "#30383D"
LIGHT = "#E5E8EA"
FAIL = "#A14D40"
WIDTH_CM = 16.0
plt.rcParams.update({
    "font.family": FONT.get_name(), "font.size": 9,
    "axes.labelsize": 9, "axes.titlesize": 10,
    "xtick.labelsize": 8.5, "ytick.labelsize": 8.5,
    "legend.fontsize": 8.5, "axes.unicode_minus": False,
    "axes.edgecolor": "#69737A", "axes.linewidth": 0.6,
    "text.color": DARK, "axes.labelcolor": DARK,
    "xtick.color": DARK, "ytick.color": DARK,
    "svg.fonttype": "path", "savefig.facecolor": "white",
    "figure.facecolor": "white", "axes.spines.top": False,
    "axes.spines.right": False,
})


def read_csv(relative: str) -> pd.DataFrame:
    return pd.read_csv(OUTPUT / relative)

```

```

def new_figure(height_cm: float):
    return plt.figure(figsize=(WIDTH_CM / 2.54, height_cm / 2.54), dpi=150)


def save(figure, name: str):
    # Apply an explicit font file to every text object, including tick labels.
    for text in figure.findobj(match=Text):
        text.set_fontproperties(FontProperties(
            fname=str(CJK_FONT), size=text.get_fontsize(), weight=text.get_fon
tweight()))
    figure.savefig(FIGURES / f"{name}.png", dpi=300)
    figure.savefig(FIGURES / f"{name}.svg")
    plt.close(figure)


def grid(axis, direction="x"):
    axis.set_axisbelow(True)
    axis.grid(axis=direction, color=LIGHT, linewidth=0.6)
    axis.tick_params(length=2.5, width=0.6)


def figure1():
    fig = new_figure(11.2)
    ax = fig.add_axes([0.025, 0.025, 0.95, 0.95])
    ax.set(xlim=(0, 1), ylim=(0, 1))
    ax.axis("off")

    def box(x, y, w, h, text, highlighted=False):
        ax.add_patch(Rectangle((x, y), w, h,
                               facecolor="#F0F4F7" if highlighted else "white",
                               edgecolor=BLUE if highlighted else "#89959D", li
newidth=0.8))
        ax.text(x + w / 2, y + h / 2, text, ha="center", va="center", fontsize
=9,
                linespacing=1.35)

    def arrow(start, end):
        ax.add_patch(FancyArrowPatch(start, end, arrowstyle="-|>", mutation_sc
ale=8,
                                     linewidth=0.7, color="#6C7A84"))

    box(0.06, 0.864, 0.88, 0.105,
        "250 款啤酒 / 22 种风格：化学测量、标准化感官评分、校准量与阈值", True)
    box(0.11, 0.717, 0.78, 0.105,
        "按 beer 精确连接；区分相对表示与浓度；在训练折内拟合预处理")
    arrow((0.5, 0.864), (0.5, 0.823))
    centers = [0.163, 0.5, 0.837]
    xs = [0.01, 0.347, 0.684]
    top = ["问题一：感官预测\n231 维化学 → 45 维感官",
           "问题二：化学关联\n231 个节点 / 218 个候选",
           "问题三：生成与迁移\n226 维：69 校准 + 157 相对"]
    mid = ["ExtraTrees 与基线\n训练折补值和缺失指示",
           "Spearman 网络与 Top-3\n200 次配对重抽样",
           "风格自适应分布与嵌套选择\n三风格 900 谱 + 对照 300 谱"]
    bottom = ["五折折外评价\n缺失压力检查",
              "135 个关联位置\n稳定性与风格敏感性",
              "排除全部 Pils：239 款训练\n11 款源谱向 Tripel 迁移"]
    for i, x in enumerate(xs):
        arrow((centers[i], 0.717), (centers[i], 0.657))
        box(x, 0.53, 0.306, 0.125, top[i], True)
        box(x, 0.34, 0.306, 0.13, mid[i])
```

```
        box(x, 0.15, 0.306, 0.13, bottom[i])
        arrow((centers[i], 0.53), (centers[i], 0.471))
        arrow((centers[i], 0.34), (centers[i], 0.281))
    box(0.355, 0.004, 0.632, 0.103,
        "迁移检查：十情景浓度保护 + 支持域 + 接近幅度\n双模型筛选 → 预留模型审计；失败源保留")
    arrow((0.837, 0.15), (0.837, 0.108))
    save(fig, "figure1_workflow")


def figure2():
    base = read_csv("q1/metrics_overall.csv").set_index("model")
    robust = read_csv("q1_robust/metrics_overall.csv").set_index("model")
    table = pd.concat([base.loc[["mean", "ridge"]], robust.loc[["ridge_winsor"]],
                       base.loc[["extra_trees"]]])
    fig = new_figure(11.2)
    axes = fig.subplots(2, 2)
    fig.subplots_adjust(left=0.17, right=0.975, top=0.93, bottom=0.17,
                        hspace=0.68, wspace=0.65)
    labels = ["均值基线", "Ridge", "裁剪 Ridge", "ExtraTrees"]
    colors = [GREY, GREY, GOLD, BLUE]
    for ax, metric, title in zip(axes.flat[:3], ["rmse", "mae", "macro_r2"],
                                 ["(a) RMSE", "(b) MAE", "(c) 宏平均 $R^2$"]):
        values = table[metric].to_numpy()
        y = np.arange(4)
        ax.barh(y, values, height=0.56, color=colors)
        ax.set_yticks(y, labels)
        ax.invert_yaxis()
        ax.set_title(title, loc="left", pad=5)
        if metric == "macro_r2":
            ax.set_xlim(-0.1, 0.31)
            ax.axvline(0, color="#69737A", linewidth=0.65)
        else:
            ax.set_xlim(0, 0.72 if metric == "rmse" else 0.52)
        for pos, value in zip(y, values):
            label_x = 0.014 if value < 0 else value + (0.012 if metric == "rmse" else 0.009)
            ax.text(label_x, pos,
                    f"{value:.3f}", va="center", fontsize=8.5)
        grid(ax)
    ax = axes[1, 1]
    rates = np.array([0, 10, 20])
    values = np.array([base.loc["extra_trees", "rmse"],
                       base.loc["extra_trees_mask10", "rmse"],
                       base.loc["extra_trees_mask20", "rmse"]])
    ax.plot(rates, values, "o-", color=BLUE, markersize=4, linewidth=1.2)
    ax.set_title("(d) ExtraTrees 缺失压力", loc="left", pad=5)
    ax.set(xlim=(-1.5, 21.5), ylim=(0.47, 0.525), xticks=rates,
           xlabel="额外隐藏已观测特征（%）", ylabel="RMSE")
    for rate, value in zip(rates, values):
        ax.annotate(f"{value:.4f}", (rate, value), xytext=(0, 6),
                    textcoords="offset points", ha="center", fontsize=8.5)
    grid(ax, "y")
    fig.text(0.5, 0.025,
             f"五折折外评价；20% 缺失压力下 RMSE 上升 {(values[2]/values[0]-1)*100:.2f}%",
             ha="center", fontsize=8.5)
    save(fig, "figure2_q1")


NETWORK_SHORT_NAMES = {
```

```
    "ethyl.tetradecanoate": "十四酸乙酯", "pentyl.octanoate": "辛酸戊酯",
    "X1.2.dihydro.8.hydroxy..2E..linalool": "二氢羟基芳樟醇",
    "X2.methylbutyl.octanoate": "辛酸2-甲基丁酯",
    "X2.phenyl.ethyl.butyrate": "丁酸苯乙酯",
    "X.Z..beta.farnesene": "Z-β-法呢烯",
    "ethyl.pentadecanoate": "十五酸乙酯", "isopentyl.hexanoate": "己酸异戊酯",
}


def spring_layout(adjacency, seed=20261023):
    """Force layout within one connected component."""
    count = len(adjacency)
    pos = np.random.default_rng(seed).normal(size=(count, 2))
    pos /= max(np.linalg.norm(pos, axis=1).max(), 1e-8)
    degree = (adjacency > 0).sum(axis=1)
    repulsion = 1 + 0.12 * (degree[:, None] + degree[None, :])
    scale = np.sqrt(1 / count)
    for step in range(550):
        delta = pos[:, None, :] - pos[None, :, :]
        distance = np.maximum(np.linalg.norm(delta, axis=2), 1e-4)
        forces = ((repulsion * scale**2 / distance**2
                   - adjacency * distance / scale)[:, :, None] * delta).sum(ax
is=1)
        forces -= 0.06 * pos
        length = np.maximum(np.linalg.norm(forces, axis=1), 1e-8)
        temperature = 0.075 * (1 - step / 550) + 0.001
        pos += forces * (np.minimum(length, temperature) / length)[:, None]
        pos -= pos.mean(axis=0)
    return 0.76 * pos / np.linalg.norm(pos, axis=1).max()


def network_layout(adjacency, seed=20261023):
    """Pack connected-component force layouts without shrinking their edges aw
ay."""
    seen, components = set(), []
    for node in range(len(adjacency)):
        if node in seen:
            continue
        pending, component = [node], []
        while pending:
            current = pending.pop()
            if current in seen:
                continue
            seen.add(current)
            component.append(current)
            pending.extend(np.flatnonzero(adjacency[current] > 0).tolist())
        components.append(sorted(component))
    components.sort(key=lambda component: (-len(component), component[0]))
    candidates = np.array(np.meshgrid(np.arange(-0.9, 0.901, 0.02),
                                      np.arange(-0.9, 0.901, 0.02))).reshape(2
, -1).T
    order = np.argsort(np.linalg.norm(candidates, axis=1), kind="stable")
    candidates = candidates[order]
    positions = np.empty((len(adjacency), 2))
    circles = []
    radius_by_count = {15: 0.33, 11: 0.235, 6: 0.16, 4: 0.125, 3: 0.105, 2: 0.
078}
    for number, component in enumerate(components):
        radius = radius_by_count[len(component)]
        valid = np.linalg.norm(candidates, axis=1) + radius <= 0.90
        for center, old_radius in circles:
            valid &= np.linalg.norm(candidates - center, axis=1) >= radius + o
```

```
ld_radius + 0.022
        if not valid.any():
            raise ValueError("No room to display all connected components")
        center = candidates[np.flatnonzero(valid)[0]]
        local = radius * spring_layout(adjacency[np.ix_(component, component)]
, seed + number) / 0.76
        # Dense correlated hubs otherwise overlap after component normalizatio
n.
        # This collision pass changes display coordinates only.
        for _ in range(260):
            for i in range(len(component)):
                for j in range(i):
                    delta = local[i] - local[j]
                    distance = np.linalg.norm(delta)
                    if distance < 0.115:
                        direction = delta / max(distance, 1e-8)
                        shift = 0.51 * (0.115 - distance) * direction
                        local[i] += shift
                        local[j] -= shift
            norm = np.linalg.norm(local, axis=1)
            local *= np.minimum(1, radius / np.maximum(norm, 1e-8))[:, None]
        positions[component] = center + local
        circles.append((center, radius))
    return positions


def figure3():
    summary = json.loads((OUTPUT / "q2/summary.json").read_text(encoding="utf-
8"))
    top3 = read_csv("q2/top3_compounds.csv")
    nodes = read_csv("q2/network_nodes.csv")
    edges = read_csv("q2/network_edges_rho_0.7.csv")
    active = nodes[nodes["degree_0.7"].gt(0)].copy().set_index("field")
    isolated = nodes[nodes["degree_0.7"].eq(0)]
    assert len(nodes) == 231 and len(active) == 81 and len(isolated) == 150
    assert len(edges) == 109 and edges.sign.eq(1).all()
    lookup = {field: i for i, field in enumerate(active.index)}
    adjacency = np.zeros((len(active), len(active)))
    for row in edges.itertuples():
        i, j = lookup[row.source], lookup[row.target]
        adjacency[i, j] = adjacency[j, i] = row.absolute_weight
    np.testing.assert_array_equal((adjacency > 0).sum(axis=1), active["degree_
0.7"])
    positions = network_layout(adjacency)
    fig = new_figure(11.8)
    network = fig.add_axes([0.015, 0.28, 0.605, 0.65])
    network.set(xlim=(-1.19, 1.19), ylim=(-1.27, 1.22), aspect="equal")
    network.axis("off")
    network.set_title("(a) 化学关联网络（|ρ|≥0.7）", loc="left", fontsize=9.5, pa
d=10)
    for row in edges.itertuples():
        pair = positions[[lookup[row.source], lookup[row.target]]]
        network.plot(pair[:, 0], pair[:, 1], color=BLUE, alpha=0.40, linewidth
=0.6, zorder=1)
    network.scatter(positions[:, 0], positions[:, 1], color=BLUE,
                    s=12 + 5 * active["degree_0.7"].to_numpy(), zorder=2)
    angle = np.linspace(0, 2 * np.pi, len(isolated), endpoint=False)
    network.scatter(1.02 * np.cos(angle), 1.02 * np.sin(angle),
                    s=5.5, color=GREY, zorder=2)
    network.text(0, 1.13, "外围：150 个孤立节点逐点保留", ha="center", fontsize=8.
5)
    network.text(0, -1.17, "内部：81 个非孤立节点；109 条边均为正相关", ha="center",
```

```
 fontsize=8.5)
    ranked = active.reset_index().sort_values(["degree_0.7", "field"],
                                              ascending=[False, True]).head(8)
    for number, row in enumerate(ranked.itertuples()):
        label = chr(ord("A") + number)
        x, y = positions[lookup[row.field]]
        network.text(x, y, label, ha="center", va="center", fontsize=8,
                     color="white", zorder=3)
        fig.text(0.035 + (number % 4) * 0.245, 0.165 - (number // 4) * 0.047,
                 f"{label}  {NETWORK_SHORT_NAMES[row.field]}", ha="left", font
size=8.3)

    threshold_ax = fig.add_axes([0.715, 0.66, 0.26, 0.24])
    thresholds = [row["absolute_rho_threshold"] for row in summary["networks"]
]
    edge_counts = [row["edges"] for row in summary["networks"]]
    threshold_ax.bar(range(3), edge_counts, color=[GREY, BLUE, GREY], width=0.
55)
    threshold_ax.set(xticks=range(3), xticklabels=[f"{v:.1f}" for v in thresho
lds],
                     ylim=(0, 315), xlabel="|ρ| 下限", ylabel="无向边数")
    threshold_ax.set_title("(b) 阈值敏感性", loc="left", fontsize=9.5)
    for x, value in enumerate(edge_counts):
        threshold_ax.text(x, value + 9, str(value), ha="center", fontsize=8.5)
    grid(threshold_ax, "y")
    stability_ax = fig.add_axes([0.715, 0.295, 0.26, 0.205])
    frequencies = top3.bootstrap_top3_frequency.to_numpy()
    bins = np.array([0, 0.2, 0.4, 0.6, 0.8, 1.00001])
    count, _ = np.histogram(frequencies, bins=bins)
    assert len(frequencies) == 135 and int((frequencies >= 0.8).sum()) == 14
    stability_ax.bar(np.arange(5), count, color=[GREY] * 4 + [BLUE], width=0.7
5)
    stability_ax.set(xticks=np.arange(5), xticklabels=["0", ".2", ".4", ".6",
".8"],
                     xlabel="频率区间下界（组距 0.2）", ylabel="关联位置数",
                     ylim=(0, max(count) + 12))
    stability_ax.set_title("(c) Top-3 入选稳定性", loc="left", fontsize=9.5)
    for x, value in enumerate(count):
        stability_ax.text(x, value + 1.5, str(value), ha="center", fontsize=8.
5)
    grid(stability_ax, "y")
    fig.text(0.5, 0.065, "A–H 为度最高的八个节点；节点面积随度增加；布局位置不代表浓度",
 ha="center", fontsize=8.5)
    fig.text(0.5, 0.02, "200 次配对重抽样；14/135 个关联位置的入选频率达到 0.8", ha="
center", fontsize=8.5)
    save(fig, "figure3_q2")


def figure4():
    summary = read_csv("q3_optimized/generation/cv_summary.csv")
    styles = ["Tripel", "Kriek", "Lambic"]
    methods = ["legacy_copula", "nested_selected", "style_bootstrap"]
    names = ["基准 Copula", "嵌套选择器", "风格重采样"]
    fig = new_figure(8.6)
    ax = fig.add_axes([0.105, 0.21, 0.87, 0.67])
    width = 0.23
    for k, (method, name, color) in enumerate(zip(methods, names, [GREY, BLUE,
 GOLD])):
        part = summary[summary.method.eq(method)].set_index("style").loc[style
s]
        ax.bar(np.arange(3) + (k - 1) * width, part.energy_pca5_mean, width=wi
dth,
```

```
                color=color, label=name, yerr=part.energy_pca5_std,
                error_kw={"ecolor": DARK, "capsize": 2.5, "elinewidth": 0.7, "capthick": 0.7})
    ax.set(xticks=np.arange(3), xticklabels=["Tripel（n=28）", "Kriek（n=10）", "Lambic（n=11）"],
           ylabel="五维 PCA 能量差异", ylim=(0, 1.4))
    grid(ax, "y")
    fig.legend(loc="upper center", bbox_to_anchor=(0.54, 0.99), ncol=3, frameon=False,
               handlelength=1.5, columnspacing=1.2)
    fig.text(0.5, 0.07, "外层两次三折；每次生成 300 条、两个模拟种子", ha="center", fontsize=8.5)
    fig.text(0.5, 0.025, "误差线为六个折均值的折间标准差，不是置信区间；指标越低越好", ha="center", fontsize=8.5)
    save(fig, "figure4_generation")


PROFILE_TARGETS = [
    ("A_malt_all", "麦芽香气"), ("A_hops_all", "酒花香气"),
    ("A_esters_fruity", "水果酯香"), ("F_malt_all", "麦芽风味"),
    ("F_hops_all", "酒花风味"), ("acidity", "酸度"),
    ("bitternes", "苦度"), ("sweetness", "甜度"),
    ("X4vg", "4VG 酚味"), ("stale_hops", "陈旧酒花"),
    ("lactic", "乳酸味"), ("barnyard", "畜棚气味"),
]


def figure5():
    summary = read_csv("q3_optimized/generated_sensory_summary.csv")
    fig = new_figure(12.7)
    axes = fig.subplots(1, 3, sharex=True, sharey=True)
    fig.subplots_adjust(left=0.17, right=0.98, top=0.90, bottom=0.27, wspace=0.15)
    keys, labels = zip(*PROFILE_TARGETS)
    y = np.arange(len(keys))
    for ax, style in zip(axes, ["Tripel", "Kriek", "Lambic"]):
        part = summary[summary["style"].eq(style)].set_index("target").loc[list(keys)]
        assert np.all(part.predicted_p05 <= part.predicted_mean)
        assert np.all(part.predicted_mean <= part.predicted_p95)
        ax.axvline(0, color="#7C858C", linewidth=0.6)
        ax.axhspan(8.55, 9.45, color="#F0F2F3", zorder=-1)
        ax.hlines(y, part.predicted_p05, part.predicted_p95, color=BLUE, alpha=0.6, linewidth=2.4)
        ax.scatter(part.predicted_mean, y, color=BLUE, s=15, zorder=3)
        ax.set_title(style, pad=8)
        ax.set(xlim=(-1.3, 2.85), xticks=[-1, 0, 1, 2], yticks=y, yticklabels=labels,
               ylim=(11.6, -0.6))
        ax.tick_params(axis="y", length=0)
        grid(ax)
    fig.text(0.58, 0.19, "标准化感官值", ha="center", fontsize=9)
    fig.text(0.5, 0.12, "圆点：生成谱预测均值；线段：5%–95% 分位范围（每风格 300 条）", ha="center", fontsize=8.5)
    fig.text(0.5, 0.075, "该范围描述生成分布，不是预测置信区间，也不是原始 0–6 分", ha="center", fontsize=8.5)
    fig.text(0.5, 0.025, "灰行陈旧酒花使用非 Pils 单目标代理；其余维度使用全量多输出代理", ha="center", fontsize=8.5)
    save(fig, "figure5_profiles")


def figure6():
```

```
    summary = read_csv("q3_refined/transfer/transfer_summary.csv")
    part = summary[summary.arm.eq("fixed") & summary.pool.eq("contracted_6004")
                   & summary.bound.eq("retain80")]
    source_order = [124, 81, 218, 96, 230, 185, 139, 209, 119, 90, 28]
    margin = part[part.ranking.eq("margin")].set_index("source_beer").loc[source_order]
    geometry = part[part.ranking.eq("geometry")].set_index("source_beer").loc[source_order]
    assert len(margin) == len(geometry) == 11
    assert margin.fresh_consistency_passed.sum() == geometry.fresh_consistency_passed.sum() == 10
    assert margin.loc[~margin.fresh_consistency_passed].index.tolist() == [96]
    assert geometry.loc[~geometry.fresh_consistency_passed].index.tolist() == [96]
    fig = new_figure(10.3)
    ax = fig.add_axes([0.16, 0.28, 0.80, 0.60])
    y = np.arange(11)
    m = margin.target_improvement.to_numpy() * 100
    g = geometry.target_improvement.to_numpy() * 100
    ax.hlines(y, m, g, color="#A7B1B8", linewidth=1)
    ax.scatter(m, y, color=BLUE, marker="o", s=25, label="余量优先", zorder=3)
    ax.scatter(g, y, edgecolor=GOLD, facecolor="white", marker="^", linewidth=1.1,
               s=35, label="几何优先", zorder=3)
    failed_y = source_order.index(96)
    ax.scatter([m[failed_y]], [failed_y], color=FAIL, marker="x", s=55, linewidth=1.4,
               label="审计未通过", zorder=4)
    ax.set(yticks=y, yticklabels=[str(beer) + (" *" if beer == 96 else "") for beer in source_order],
           ylim=(10.7, -0.7), xlim=(0, 85), xticks=[0, 20, 40, 60, 80],
           xlabel="向 Tripel 的目标距离改善（%）", ylabel="源 beer 编号")
    grid(ax)
    ax.legend(loc="upper center", bbox_to_anchor=(0.5, 1.17), ncol=3, frameon=False,
              handletextpad=0.4, columnspacing=1.0)
    fig.text(0.5, 0.12, "固定树 / 中央 6004 候选 / retain80；两种排序均为 10/11 通过", ha="center", fontsize=8.5)
    fig.text(0.5, 0.07, "所选谱改善中位数：余量优先 57.74%，几何优先 70.08%", ha="center", fontsize=8.5)
    fig.text(0.5, 0.02, "* beer 96 的审计失败保留；通过数为模型检查结果，不是实际品评成功数", ha="center", fontsize=8.5)
    save(fig, "figure6_transfer")


def main(only=None):
    FIGURES.mkdir(parents=True, exist_ok=True)
    for number, draw in enumerate([figure1, figure2, figure3, figure4, figure5, figure6], 1):
        if only is None or number == only:
            draw()
    descriptions = [
        ("figure1_workflow", "图1 三问的数据处理、模型与验证流程。第一问使用231维原表示；第三问使用69维校准量与157维相对量组成的226维混合表示。迁移训练排除全部11款Pils。", 11.2,
         ["outputs/q1/summary.json", "outputs/q2/summary.json", "outputs/q3_optimized/generation/summary.json", "outputs/q3_refined/stale/summary.json", "src/q3_data.py"]),
        ("figure2_q1", "图2 第一问四种方法的五折折外误差、宏平均R²及ExtraTrees缺失压力结果。裁剪Ridge为稳健性对照；额外隐藏20%已观测特征后，ExtraTrees的RMSE由0.4862增至0.4992。", 11.2,
         ["outputs/q1/metrics_overall.csv", "outputs/q1/missingness_stress.csv
```

```
", "outputs/q1_robust/metrics_overall.csv"]),
        ("figure3_q2", "图3 化学关联网络及稳定性。(a) 实际|Spearman ρ|≥0.7网络，保留全部231节点和109条正相关边；81个非孤立节点采用固定种子20261023的分量内力导向布局及分量打包，并进行显示避碰，150个孤立节点在外围环逐点保留，节点面积随度增加。A–H为度最高八个节点，图内列简名；布局距离不表示化学浓度或因果关系。(b) 三个阈值下的边数。(c) 135个Top-3位置的200次配对重抽样入选频率，其中14个达到0.8；频率区间左闭右开，最后一组包含1。", 11.8,
         ["outputs/q2/network_nodes.csv", "outputs/q2/network_edges_rho_0.7.csv", "outputs/q2/summary.json", "outputs/q2/top3_compounds.csv"]),
        ("figure4_generation", "图4 三种目标风格的生成能量差异，比较基准Copula、完整嵌套选择器及重采样对照。柱为外层六个折均值的平均值，误差线为其标准差；每折先平均两个模拟种子。折间标准差不是置信区间，真实样本数列于横轴。", 8.6,
         ["outputs/q3_optimized/generation/cv_summary.csv", "outputs/q3_optimized/generation/cv_fold_means.csv", "outputs/q2/summary.json"]),
        ("figure5_profiles", "图5 三种风格在列示的12个代表感官维度上的生成画像。圆点为每风格300条谱的预测均值，线段为5%–95%生成分布范围，三个面板使用共同横轴。陈旧酒花来自239款非Pils训练的固定单目标树，其余维度来自226维全量多输出代理；区间不是校准预测置信区间，数值不是原始0–6分。", 12.7,
         ["outputs/q3_optimized/generated_sensory_summary.csv", "outputs/q3_optimized/generation/summary.json", "outputs/q3_optimized/stale_fixed/summary.json"]),
        ("figure6_transfer", "图6 固定树、中央6004候选池与retain80条件下，11款Pils源的所选谱目标距离改善。余量优先和几何优先均通过10/11款，beer 96的审计失败保留；改善中位数分别为57.74%与70.08%，包括已选但失败的谱。几何优先为探索性应用示例，模型检查通过不代表实际品评成功。", 10.3,
         ["outputs/q3_refined/transfer/transfer_summary.csv", "outputs/q3_refined/transfer/frontier.csv"]),
    ]
    manifest = {
        "renderer": "matplotlib", "font_file": str(CJK_FONT), "dpi": 300,
        "widthcm": WIDTH_CM, "source_root": "solution_a", "sources_mutated": False,
        "figures": [{"id": index, "caption": caption,
                     "relativepath": f"figures/{name}.png",
                     "svg_relativepath": f"figures/{name}.svg",
                     "widthcm": WIDTH_CM, "heightcm": height,
                     "sources": sources}
                    for index, (name, caption, height, sources) in enumerate(descriptions, 1)],
        "profile_targets": [{"target": key, "label": label} for key, label in PROFILE_TARGETS],
        "verification": {
            "figure3_nodes": 231, "figure3_edges": 109,
            "figure3_active_nodes": 81, "figure3_isolated_nodes": 150,
            "figure3_all_edges_positive": True, "figure3_layout_seed": 20261023,
            "figure3_top3_positions": 135, "figure3_frequency_at_least_0_8": 14,
            "figure6_sources": 11, "figure6_passed_each_ranking": 10,
            "figure6_failed_source_each_ranking": 96,
        },
    }
    for figure in manifest["figures"]:
        assert all((SOLUTION / source).is_file() for source in figure["sources"])
    (PAPER / "figure_manifest.json").write_text(
        json.dumps(manifest, ensure_ascii=False, indent=2) + "\n", encoding="utf-8")
    print(f"Saved {'six figure pairs' if only is None else 'figure ' + str(only)} and figure_manifest.json in {PAPER}")


if __name__ == "__main__":
```

```
    import argparse

    parser = argparse.ArgumentParser(description=__doc__)
    parser.add_argument("--only", type=int, choices=range(1, 7), help="Render
one figure only")
    main(parser.parse_args().only)
```

run_all.py

SHA-256: e8fef69f625466acc22b552ec490bc6c5bda3836423deca6cc993a21704c57fd

```
"""Check saved experiments, or explicitly rebuild them in a clean copy."""
import argparse
import os
from pathlib import Path
import subprocess
import sys

HERE = Path(__file__).resolve().parent


def run(script, *arguments):
    env = os.environ.copy()
    env["PYTHONUTF8"] = "1"
    env["PYTHONIOENCODING"] = "utf-8"
    path = HERE / (script if script.startswith("run_") else "src/" + script)
    print(f"Running {script}", flush=True)
    subprocess.run([sys.executable, "-X", "utf8", str(path), *map(str, argumen
ts)],
                   check=True, env=env)


def main():
    parser = argparse.ArgumentParser(description=__doc__)
    parser.add_argument("--rebuild", action="store_true",
                        help="Train all experiments; requires an absent or emp
ty outputs directory.")
    parser.add_argument("--report-dir", type=Path, default=HERE / "review/veri
fication",
                        help="Reports from saved-result checks (outside frozen
 experiment folders).")
    args = parser.parse_args()
    outputs = HERE / "outputs"
    if args.rebuild:
        supplement = HERE / "supplement/results"
        if (outputs.exists() and any(outputs.iterdir())) or (supplement.exists
() and any(supplement.iterdir())):
            parser.error("--rebuild requires a clean copy with no existing out
puts; saved results were left unchanged.")
        for script in ["01_audit.py", "02_q1_baseline.py", "02b_q1_robust.py",
                       "03_q2_network.py", "04_stage_summary.py"]:
            run(script)
        run("05_verify_outputs.py", "--output", outputs / "verification.json")
        for script in ["run_q3.py", "run_q3_optimized.py", "run_q3_domain.py",
 "run_q3_refined.py"]:
            run(script)
        run("run_supplement.py", "--rebuild")
    else:
        if not (outputs / "q3_refined/verification.json").is_file():
            parser.error("Saved experiments are incomplete; use --rebuild in a
 clean copy with the original attachments.")
        if args.report_dir.resolve().is_relative_to(outputs.resolve()):
            parser.error("--report-dir must be outside outputs to preserve the
 cited experiments.")
        run("platform_selfcheck.py")
        run("05_verify_outputs.py", "--output", args.report_dir / "q1_q2.json"
)
        run("25_q3_refined_verify.py", "--output", args.report_dir / "q3_refin
ed.json")
        run("run_supplement.py")
```

```
49
50
51 if __name__ == "__main__":
52     main()
```

run_q3.py

SHA-256: 943fd76e3cc904583cf6ba12f559700aa052be0a6ac698e9467b80eac2f78d13

```
"""Reproduce the conditional generation and constrained transfer experiments."""
from pathlib import Path
import subprocess
import sys

HERE = Path(__file__).resolve().parent
for script in ["06_q3_sensory.py", "07_q3_generation.py", "08_q3_transfer.py",
               "09_q3_report.py", "10_q3_verify.py"]:
    print(f"Running {script}", flush=True)
    subprocess.run([sys.executable, "-X", "utf8", str(HERE / "src" / script)], check=True)
```

run_q3_domain.py

SHA-256: 6a8ebd9be8e7a3e9e47ca878daa3d5f25e7dccd5f64d092f6efc8d32ba38a3c4

```
"""Reproduce style-held-out prediction and joint committee transfer checks."""
import hashlib
import json
from pathlib import Path
import subprocess
import sys

from run_q3_optimized import preserve_baseline

HERE = Path(__file__).resolve().parent
PREVIOUS = HERE / "outputs/q3_optimized"
SNAPSHOT = HERE / "outputs/q3_domain/previous_hashes.json"


def preserve_previous():
    preserve_baseline()
    if not (PREVIOUS / "verification.json").exists():
        raise RuntimeError("Run run_q3_optimized.py before the style-held-out experiment.")
    files = [{"path":path.relative_to(PREVIOUS).as_posix(),"bytes":path.stat().st_size,
              "sha256":hashlib.sha256(path.read_bytes()).hexdigest()}
             for path in sorted(PREVIOUS.rglob("*")) if path.is_file()]
    files.sort(key=lambda row: row["path"])
    if SNAPSHOT.exists():
        if files != json.loads(SNAPSHOT.read_text(encoding="utf-8"))["files"]:
            raise RuntimeError("The frozen optimization has changed; restore it or use a separate experiment copy.")
    else:
        SNAPSHOT.parent.mkdir(parents=True,exist_ok=True)
        SNAPSHOT.write_text(json.dumps({"baseline_directory":"solution_a/outputs/q3_optimized",
            "hash_algorithm":"sha256","file_count":len(files),"files":files},
            ensure_ascii=False,indent=2)+"\n",encoding="utf-8", newline="\n")


if __name__ == "__main__":
    preserve_previous()
    for script in ["16_q3_stale_domain.py","17_q3_transfer_domain.py","20_q3_transfer_consensus.py",
                   "18_q3_domain_report.py","19_q3_domain_verify.py"]:
        print(f"Running {script}",flush=True)
        subprocess.run([sys.executable, "-X", "utf8", str(HERE/"src"/script)], check=True)
```

run_q3_optimized.py

SHA-256: a50fb056c91889f873e63b720329ace2a32d8d8e5dcc55f962c1e778b8e1ab7f

```
"""Reproduce the optimization while preserving the frozen first-round baseline."""
import hashlib
import json
from pathlib import Path
import subprocess
import sys

HERE = Path(__file__).resolve().parent
BASELINE = HERE / "outputs/q3"
SNAPSHOT = HERE / "outputs/q3_optimized/baseline_hashes.json"


def preserve_baseline():
    paths = sorted(path for path in BASELINE.rglob("*") if path.is_file())
    if not (BASELINE / "verification.json").exists():
        raise RuntimeError("Run the original third-question experiment before the optimization.")
    rows = [{"path": path.relative_to(BASELINE).as_posix(), "bytes": path.stat().st_size,
             "sha256": hashlib.sha256(path.read_bytes()).hexdigest()} for path in paths]
    rows.sort(key=lambda row: row["path"])
    if SNAPSHOT.exists():
        expected = json.loads(SNAPSHOT.read_text(encoding="utf-8"))
        if rows != expected["files"]:
            raise RuntimeError("The frozen baseline has changed. Restore it or run a separate experiment copy.")
    else:
        SNAPSHOT.parent.mkdir(parents=True, exist_ok=True)
        record = {"baseline_directory": "solution_a/outputs/q3", "hash_algorithm": "sha256",
                  "file_count": len(rows), "files": rows}
        SNAPSHOT.write_text(json.dumps(record, ensure_ascii=False, indent=2) + "\n", encoding="utf-8", newline="\n")


if __name__ == "__main__":
    preserve_baseline()
    for script in ["11_q3_generation_optimized.py", "12_q3_stale_optimized.py",
                   "12b_q3_stale_fixed.py", "13_q3_transfer_optimized.py",
                   "14_q3_optimization_report.py", "15_q3_optimized_verify.py"]:
        print(f"Running {script}", flush=True)
        subprocess.run([sys.executable, "-X", "utf8", str(HERE / "src" / script)], check=True)
```

run_q3_refined.py

SHA-256: e5fde50e937cde776f4f878aa08b680d22ca9950d8f6dc004e37920c3a335176

```
"""Reproduce beer81 diagnosis and balanced transfer without changing prior runs."""
import hashlib
import json
from pathlib import Path
import subprocess
import sys

from run_q3_domain import preserve_previous

HERE=Path(__file__).resolve().parent
PRIOR=HERE/"outputs/q3_domain"
SNAPSHOT=HERE/"outputs/q3_refined/previous_hashes.json"


def preserve_refined():
    preserve_previous()
    if not (PRIOR/"verification.json").exists():
        raise RuntimeError("Run run_q3_domain.py before the refinement experiment.")
    files=[{"path":path.relative_to(PRIOR).as_posix(),"bytes":path.stat().st_size,
            "sha256":hashlib.sha256(path.read_bytes()).hexdigest()}
           for path in sorted(PRIOR.rglob("*")) if path.is_file()]
    files.sort(key=lambda row: row["path"])
    if SNAPSHOT.exists():
        if files!=json.loads(SNAPSHOT.read_text(encoding="utf-8"))["files"]:
            raise RuntimeError("The frozen domain experiment changed; restore it or use a separate copy.")
    else:
        SNAPSHOT.parent.mkdir(parents=True,exist_ok=True)
        SNAPSHOT.write_text(json.dumps({"baseline_directory":"solution_a/outputs/q3_domain",
            "hash_algorithm":"sha256","file_count":len(files),"files":files},ensure_ascii=False,indent=2)+"\n",encoding="utf-8", newline="\n")


if __name__=="__main__":
    preserve_refined()
    for name in ["21_q3_beer81_audit.py","22_q3_stale_refined.py","23_q3_transfer_balanced.py",
                 "24_q3_refinement_report.py","25_q3_refined_verify.py"]:
        print(f"Running {name}",flush=True)
        command = [sys.executable, "-X", "utf8", str(HERE/"src"/name)]
        if name == "25_q3_refined_verify.py":
            command += ["--output", str(HERE/"outputs/q3_refined/verification.json")]
        subprocess.run(command, check=True)
```

run_supplement.py

SHA-256: b2f0a50147b4339ee2b0745332648b111427164eb6066b54d8e5727b0db67659

```
"""Build or check the supplementary post-hoc analyses in their own directory."
""
import argparse
from pathlib import Path
import subprocess
import sys

HERE = Path(__file__).resolve().parent


def run(name):
    subprocess.run([sys.executable, "-X", "utf8", str(HERE / "supplement" / na
me)], check=True)


def main():
    parser = argparse.ArgumentParser(description=__doc__)
    parser.add_argument("--rebuild", action="store_true")
    args = parser.parse_args()
    folder = HERE / "supplement/results"
    if args.rebuild:
        if folder.exists() and any(folder.iterdir()):
            parser.error("Supplementary results already exist; rebuild in a cl
ean copy.")
        for name in ["q1_comparison.py", "q1_additional_checks.py", "q2_strati
fied_bootstrap.py", "q2_permutation.py",
                     "q1_indicator_ablation.py", "reference_tables.py"]:
            run(name)
    elif not (folder / "q2_permutation/summary.json").exists():
        parser.error("Supplementary results are missing; run --rebuild after t
he main experiments.")
    run("verify_supplement.py")


if __name__ == "__main__":
    main()
```

src/01_audit.py

SHA-256: b81848d6eaf8c0a4b6aebe881c519837e154a84f52f285fa6f3be55c65d41c80

```
#!/usr/bin/env python3
"""Read-only, reproducible audit of the eight Track A attachments.

No original file is modified; no network request is made. Findings have not
been independently verified by a human. Uses pandas/numpy and read-only
openpyxl; does not require scipy, and does not author any workbook.
"""

from __future__ import annotations

import argparse
import hashlib
import json
import platform
from pathlib import Path

import numpy as np
import pandas as pd
import openpyxl


ATTRIBUTION = "本地附件结构、数值一致性与来源完整性审计。"
KEYS = ["beer", "beer_id", "tasting_category_fine"]


def normalize_label(value: object) -> str:
    return " ".join(str(value).replace("_x000D_", "").split())


def number(value: object) -> float | None:
    return float(value) if pd.notna(value) and np.isfinite(float(value)) else None


def sha256(path: Path) -> str:
    return hashlib.sha256(path.read_bytes()).hexdigest()


def profile(frame: pd.DataFrame, source: str) -> list[dict]:
    records = []
    for column in frame.columns:
        series = frame[column]
        numeric = pd.api.types.is_numeric_dtype(series)
        row = {
            "source": source, "column": str(column), "dtype": str(series.dtype),
            "rows": len(series), "missing": int(series.isna().sum()),
            "missing_rate": float(series.isna().mean()) if len(series) else None,
            "unique_nonmissing": int(series.nunique(dropna=True)),
            "all_missing": bool(series.isna().all()),
            "constant_nonmissing": bool(series.nunique(dropna=True) == 1),
        }
        if numeric:
            finite = series[np.isfinite(series)]
            q1, q3 = finite.quantile([0.25, 0.75]) if len(finite) else (np.nan, np.nan)
            iqr = q3 - q1
            row.update({
```

```
                "min": number(finite.min()), "q01": number(finite.quantile(0.0
1)),
                "q25": number(q1), "median": number(finite.median()),
                "q75": number(q3), "q99": number(finite.quantile(0.99)),
                "max": number(finite.max()), "mean": number(finite.mean()),
                "std_ddof1": number(finite.std(ddof=1)),
                "negative_count": int((series < 0).sum()),
                "zero_count": int((series == 0).sum()),
                "infinite_count": int(np.isinf(series).sum()),
                "tukey_outside_1_5_iqr": int(((finite < q1 - 1.5 * iqr) | (fin
ite > q3 + 1.5 * iqr)).sum()),
            })
        records.append(row)
    return records


def table_summary(frame: pd.DataFrame) -> dict:
    numeric = frame.select_dtypes(include=np.number)
    return {
        "rows": len(frame), "columns": len(frame.columns),
        "column_names": list(map(str, frame.columns)),
        "missing_cells": int(frame.isna().sum().sum()),
        "exact_duplicate_rows": int(frame.duplicated().sum()),
        "numeric_columns": len(numeric.columns),
        "infinite_cells": int(np.isinf(numeric).sum().sum()),
    }


def main() -> None:
    parser = argparse.ArgumentParser(description=__doc__)
    parser.add_argument("--data-dir", type=Path)
    parser.add_argument("--output-dir", type=Path)
    args = parser.parse_args()
    project = Path(__file__).resolve().parents[2]
    if args.data_dir:
        data_dir = args.data_dir.resolve()
    else:
        candidates = list(project.glob("**/*赛道A初赛/附件"))
        if len(candidates) != 1:
            raise RuntimeError("Expected exactly one Track A attachment direct
ory; use --data-dir.")
        data_dir = candidates[0]
    output = args.output_dir or project / "solution_a/outputs/audit"
    output.mkdir(parents=True, exist_ok=True)
    report_path = project / "solution_a/docs/data_audit.md"
    report_path.parent.mkdir(parents=True, exist_ok=True)

    paths = [data_dir / f"{i}.{'xlsx' if i in (3, 8) else 'csv'}" for i in ran
ge(1, 9)]
    paths.append(data_dir / "数据说明.txt")
    hashes_before = {path.name: sha256(path) for path in paths}
    csv = {i: pd.read_csv(data_dir / f"{i}.csv") for i in (1, 2, 4, 5, 6, 7)}
    xlsx = {i: pd.read_excel(data_dir / f"{i}.xlsx", sheet_name=None) for i in
 (3, 8)}
    frames = {f"{i}.csv": frame for i, frame in csv.items()}
    for i, sheets in xlsx.items():
        frames.update({f"{i}.xlsx::{name}": frame for name, frame in sheets.it
ems()})
    records = [row for source, frame in frames.items() for row in profile(fram
e, source)]
    columns = pd.DataFrame(records)
    columns.to_csv(output / "column_profile.csv", index=False, lineterminator=
```

```
    "\n")
    columns.loc[columns.missing > 0].to_csv(output / "missingness.csv", index=False, lineterminator="\n")
    pd.DataFrame([{"source": path.name, "bytes": path.stat().st_size,
                   "sha256": hashes_before[path.name]} for path in paths]).to_csv(output / "source_files.csv", index=False, lineterminator="\n")

    chemical = csv[1].set_index("beer")
    sensory = csv[4].set_index("beer")
    comments = csv[7].set_index("beer")
    calibrated = xlsx[8]["Calibrated chemical dataset"].set_index("beer")
    prices = xlsx[8]["Beer Prices"].set_index("beer")
    shap = xlsx[8]["GBM SHAP Values"]
    concentrations = shap.loc[shap.data == "concentration"].set_index("beer")
    shap_values = shap.loc[shap.data == "SHAP"].set_index("beer")
    keyed = {
        "1.csv": chemical, "4.csv": sensory, "7.csv": comments,
        "8.xlsx::Calibrated chemical dataset": calibrated,
        "8.xlsx::Beer Prices": prices,
        "8.xlsx::GBM SHAP Values::concentration": concentrations,
        "8.xlsx::GBM SHAP Values::SHAP": shap_values,
    }
    checks, id_discrepancies = [], []
    for source, frame in keyed.items():
        common = chemical.index.intersection(frame.index)
        aligned = frame.reindex(chemical.index)
        row = {
            "source": source, "rows": len(frame), "unique_beer": int(frame.index.nunique()),
            "duplicate_beer_rows": int(frame.index.duplicated(keep=False).sum()),
            "missing_beer_rows": int(frame.index.isna().sum()),
            "unique_beer_id": int(frame.beer_id.nunique()),
            "duplicate_beer_id_rows": int(frame.beer_id.duplicated(keep=False).sum()),
            "beer_overlap_with_1": len(common),
            "beer_missing_from_1": len(frame.index.difference(chemical.index)),
            "beer_missing_in_source": len(chemical.index.difference(frame.index)),
            "same_order_as_1": frame.index.equals(chemical.index),
            "beer_id_mismatches_with_1": int((aligned.beer_id != chemical.beer_id).sum()),
            "category_mismatches_with_1": int((aligned.tasting_category_fine != chemical.tasting_category_fine).sum())
                if "tasting_category_fine" in aligned else None,
        }
        checks.append(row)
        for beer in common:
            if frame.at[beer, "beer_id"] != chemical.at[beer, "beer_id"]:
                id_discrepancies.append({"source": source, "beer": beer,
                    "beer_id_in_1": str(chemical.at[beer, "beer_id"]),
                    "beer_id_in_source": str(frame.at[beer, "beer_id"])})
    pd.DataFrame(checks).to_csv(output / "key_checks.csv", index=False, lineterminator="\n")
    pd.DataFrame(id_discrepancies).to_csv(output / "beer_id_discrepancies.csv", index=False, lineterminator="\n")

    # Chemical labels follow 2.csv's order. The complete Spearman reconciliation
    # below checks this positional correspondence, rather than assuming it.
    m2, m5, m6 = [csv[i].set_index(csv[i].columns[0]) for i in (2, 5, 6)]
```

```
    chem_columns = list(csv[1].columns[3:])
    chem_map = dict(zip(m2.columns, chem_columns, strict=True))
    names = xlsx[8]["Sensory names"]
    panel_names = names.loc[names.dataset == "Trained panel"]
    panel_metadata = panel_names.set_index("R_name")
    selected_45 = panel_names.loc[panel_names.Category_Paper.isin(["Aroma", "T
aste"]), "R_name"].tolist()
    sensory_lookup = {normalize_label(row.CleanName_PanelFeedback): row.R_name
                      for row in panel_names.itertuples(index=False)}
    sen_map = {name: sensory_lookup[normalize_label(name)] for name in m5.colu
mns}
    thresholds = xlsx[8]["Sensory thresholds"].set_index("field_name_R")
    feature_map = []
    for display, field in chem_map.items():
        feature_map.append({"domain": "chemical", "field": field, "matrix_labe
l": display,
            "source": "1.csv; 2.csv; 8.xlsx::Sensory thresholds",
            "map_basis": "2.csv order; all Spearman matrix entries reproduced"
,
            "metadata_name": thresholds.at[field, "chemical_name"],
            "unit": thresholds.at[field, "unit"],
            "in_cross_matrix_6": display in m6.index,
            "in_calibrated_dataset": field in calibrated.columns})
    for display, field in sen_map.items():
        feature_map.append({"domain": "sensory", "field": field, "matrix_label
": display,
            "source": "4.csv; 5.csv; 8.xlsx::Sensory names",
            "map_basis": "Sensory names: R_name <-> CleanName_PanelFeedback",
            "category_paper": panel_metadata.at[field, "Category_Paper"],
            "selected_aroma_taste_45": field in selected_45})
    pd.DataFrame(feature_map).to_csv(output / "feature_name_map.csv", index=Fa
lse, lineterminator="\n")

    reconcile = []
    matrices = {}
    for name, given in [("2.csv", m2), ("5.csv", m5), ("6.csv", m6)]:
        values = given.to_numpy(dtype=float)
        square = values.shape[0] == values.shape[1]
        matrices[name] = {
            "numeric_shape": list(values.shape), "row_labels_unique": bool(giv
en.index.is_unique),
            "column_labels_unique": bool(given.columns.is_unique),
            "min": float(values.min()), "max": float(values.max()),
            "symmetry_max_error": float(np.max(np.abs(values - values.T))) if
square else None,
            "diagonal_max_error_from_1": float(np.max(np.abs(np.diag(values) -
 1))) if square else None,
        }
        for method in ("pearson", "spearman"):
            if name == "2.csv":
                recalculated = chemical[[chem_map[x] for x in given.columns]].
corr(method=method).to_numpy()
                observations = chemical[[chem_map[x] for x in given.columns]].
notna().astype(int)
                n_pairs = observations.T @ observations
            elif name == "5.csv":
                recalculated = sensory[[sen_map[x] for x in given.columns]].co
rr(method=method).to_numpy()
                observations = sensory[[sen_map[x] for x in given.columns]].no
tna().astype(int)
                n_pairs = observations.T @ observations
            else:
```

```
                left = chemical[[chem_map[x] for x in given.index]]
                right = sensory[[sen_map[x] for x in given.columns]]
                combined = pd.concat([left, right], axis=1)
                recalculated = combined.corr(method=method).to_numpy()[:len(le
ft.columns), len(left.columns):]
                n_pairs = left.notna().astype(int).T @ right.notna().astype(in
t)
            error = np.abs(recalculated - values)
            reconcile.append({"matrix": name, "method": method, "entries": val
ues.size,
                "pair_n_min": int(n_pairs.min().min()), "pair_n_max": int(n_pa
irs.max().max()),
                "max_abs_error": float(np.max(error)), "mean_abs_error": float
(np.mean(error)),
                "entries_with_error_gt_1e_10": int((error > 1e-10).sum()),
                "matches_at_1e_10": bool(np.all(error <= 1e-10))})
    pd.DataFrame(reconcile).to_csv(output / "matrix_reconciliation.csv", index
=False, lineterminator="\n")

    concentration_error = chemical[chem_columns] - concentrations.loc[chemical
.index, chem_columns]
    calibration_check = []
    for field in calibrated.columns[2:]:
        comparison = pd.concat([chemical[field], calibrated[field]], axis=1)
        raw = calibrated[field]
        min_positive_half = raw.loc[raw > 0].min() / 2
        replaced = raw.where(raw != 0, min_positive_half)
        log10_values = pd.Series(np.nan, index=raw.index)
        valid_log10 = replaced > 0
        log10_values.loc[valid_log10] = np.log10(replaced.loc[valid_log10])
        log10_error = (chemical[field] - log10_values).abs()
        calibration_check.append({"field": field, "n_pairwise_complete": int(c
omparison.notna().all(axis=1).sum()),
            "spearman_with_1": float(comparison.corr(method="spearman").iloc[0
, 1]),
            "missing_1": int(chemical[field].isna().sum()), "missing_calibrate
d": int(calibrated[field].isna().sum()),
            "negative_calibrated": int((calibrated[field] < 0).sum()),
            "unit_metadata": thresholds.at[field, "unit"],
            "transformation_group": "first_37_basic" if field in chem_columns[
:37] else "remaining_33_GCMS_overlap",
            "calibrated_zero_count": int((raw == 0).sum()),
            "zero_replacement_min_positive_half": number(min_positive_half),
            "n_log10_comparable": int(log10_error.notna().sum()),
            "log10_max_abs_error": number(log10_error.max()),
            "log10_matches_at_1e_7": bool(log10_error.max() < 1e-7),
        })
    pd.DataFrame(calibration_check).to_csv(output / "calibrated_comparison.csv
", index=False, lineterminator="\n")

    negative_calibrated = []
    for field in calibrated.columns[2:]:
        for beer, value in calibrated[field][calibrated[field] < 0].items():
            negative_calibrated.append({"beer": beer, "field": field, "value":
 value,
                "unit_metadata": thresholds.at[field, "unit"]})
    pd.DataFrame(negative_calibrated).to_csv(output / "negative_calibrated_val
ues.csv", index=False, lineterminator="\n")
    extreme = []
    for source, frame in [("1.csv", chemical), ("4.csv", sensory), ("7.csv", c
omments)]:
        for field in frame.columns[2:]:
```

```
            valid = frame[field].dropna()
            if not len(valid):
                continue
            q1, q3 = valid.quantile([0.25, 0.75])
            iqr = q3 - q1
            for beer, value in valid.loc[(valid < q1 - 3 * iqr) | (valid > q3 + 3 * iqr)].items():
                extreme.append({"source": source, "beer": beer, "field": field, "value": value,
                                "q25": q1, "q75": q3, "rule": "outside [q25-3IQR,q75+3IQR]; flag only, not error verdict"})
    pd.DataFrame(extreme).to_csv(output / "extreme_value_flags.csv", index=False, lineterminator="\n")

    # Inspect formula-bearing forms read-only, so cached zeros are not mistaken
    # for observations or 12 additional beers.
    workbook3 = openpyxl.load_workbook(data_dir / "3.xlsx", read_only=True, data_only=False)
    template_formulas = {sheet.title: sum(cell.data_type == "f" for row in sheet for cell in row)
                         for sheet in workbook3.worksheets}
    workbook3.close()
    price_cols = [col for col in prices if col.startswith("Price_")]
    prices[price_cols].notna().sum().rename("available_beers").to_csv(output / "price_availability.csv", lineterminator="\n")
    category_counts = chemical.tasting_category_fine.value_counts().rename_axis("style").reset_index(name="beers")
    category_counts.to_csv(output / "style_counts.csv", index=False, lineterminator="\n")
    category_map = pd.concat([chemical.tasting_category_fine.rename("category_1"),
                              prices.tasting_category.rename("category_prices")], axis=1)
    category_map.groupby(["category_1", "category_prices"]).size().reset_index(name="beers").to_csv(
        output / "price_category_map.csv", index=False, lineterminator="\n")
    missing_primary = {str(i): {name: int(count) for name, count in csv[i].isna().sum().items() if count}
                       for i in (1, 4, 7)}
    assertions = {
        "all_1_4_7_beer_unique_and_same_set": all(frame.index.is_unique and set(frame.index) == set(chemical.index)
                                                  for frame in (chemical, sensory, comments)),
        "all_three_matrices_reproduce_spearman": all(row["matches_at_1e_10"] for row in reconcile if row["method"] == "spearman"),
        "concentration_block_matches_1_values_and_missingness": bool(np.nanmax(np.abs(concentration_error.to_numpy())) < 1e-10
            and chemical[chem_columns].isna().equals(concentrations.loc[chemical.index, chem_columns].isna())),
        "source_hashes_unchanged": hashes_before == {path.name: sha256(path) for path in paths},
        "first_37_basic_match_log10_on_valid_pairs": all(row["log10_matches_at_1e_7"]
            for row in calibration_check if row["transformation_group"] == "first_37_basic"),
        "aroma_taste_metadata_select_exactly_45": len(selected_45) == 45 and set(selected_45).issubset(sensory.columns),
    }
    basic_log10 = [row for row in calibration_check if row["transformation_group"] == "first_37_basic"]
```

```
    summary = {
        "attribution": ATTRIBUTION,
        "audit_date": "2026-10-23", "source_directory": data_dir.relative_to(project).as_posix() if data_dir.is_relative_to(project) else str(data_dir),
        "environment": {"python": platform.python_version(), "pandas": pd.__version__, "numpy": np.__version__, "openpyxl": openpyxl.__version__},
        "source_sha256": hashes_before, "tables": {name: table_summary(frame) for name, frame in frames.items()},
        "documentation_discrepancies": [
            {"location": "题面第1页", "claim": "226种不同啤酒", "observed": "附件1/4/7各250个唯一beer"},
            {"location": "题面第3页附件2说明", "claim": "皮尔逊相关系数", "observed": "附件2/5/6精确复现Spearman"},
            {"location": "题面附件6说明", "claim": "46×50", "observed": "44×50数值矩阵"},
            {"location": "题面附件7说明", "claim": "250×187", "observed": "250×186数值字段，另3列标识/类别"},
        ],
        "primary_missingness": missing_primary, "key_checks": checks, "matrix_shapes": matrices,
        "matrix_reconciliation": reconcile, "assertions": assertions,
        "feature_counts": {"chemical": len(chem_columns), "panel": len(sensory.columns) - 2,
                           "panel_aroma_taste_45": len(selected_45),
                           "review_derived": len(comments.columns) - 2,
                           "review_usable_nonempty": int(comments.iloc[:, 2:].notna().any().sum()),
                           "calibrated_chemical": len(calibrated.columns) - 2},
        "template_formula_counts": template_formulas,
        "supplementary": {
            "shap_data_counts": shap.data.value_counts().to_dict(),
            "concentration_block_max_abs_difference_from_1": float(np.nanmax(np.abs(concentration_error.to_numpy()))),
            "calibrated_missing_cells": int(calibrated.iloc[:, 2:].isna().sum().sum()),
            "calibrated_negative_cells": len(negative_calibrated),
            "calibrated_rank_rho_min": min(row["spearman_with_1"] for row in calibration_check),
            "basic_log10_fields": len(basic_log10),
            "basic_log10_comparable_values": sum(row["n_log10_comparable"] for row in basic_log10),
            "basic_log10_max_abs_error": max(row["log10_max_abs_error"] for row in basic_log10),
            "basic_log10_zero_replacement_count": sum(row["calibrated_zero_count"] for row in basic_log10),
            "basic_log10_excluded_negative_values": sum(row["negative_calibrated"] for row in basic_log10),
            "basic_log10_excluded_calibrated_missing_values": sum(row["missing_calibrated"] for row in basic_log10),
            "remaining_33_not_direct_log10": all(not row["log10_matches_at_1e_7"]
                for row in calibration_check if row["transformation_group"] == "remaining_33_GCMS_overlap"),
            "prices_all_missing_beers": int(prices[price_cols].isna().all(axis=1).sum()),
            "price_missing_cells": int(prices[price_cols].isna().sum().sum()),
        },
        "limitations": ["No raw review text, panel individual ratings, measurement dates or preprocessing recipe supplied.",
                        "No independent human verification; no source data edited or uploaded.",
```

```
                        "Outlier flags are descriptive; they do not prove measurement errors.",
                        "Provided MDI/SHAP and full-sample matrices must not be used as supervised-selection inputs before CV splitting."],
    }
    (output / "audit_summary.json").write_text(json.dumps(summary, ensure_ascii=False, indent=2, allow_nan=False) + "\n", encoding="utf-8", newline="\n")
    report_path.write_text(make_report(summary, csv, xlsx, reconcile, checks, negative_calibrated), encoding="utf-8", newline="\n")
    if not all(assertions.values()):
        raise RuntimeError(f"Audit invariants failed: {assertions}")
    print(json.dumps({"status": "completed", "report": str(report_path), "output_directory": str(output),
                      "assertions": assertions}, ensure_ascii=False, indent=2))


def make_report(summary: dict, csv: dict, xlsx: dict, reconcile: list, checks: list, negatives: list) -> str:
    rows = []
    for i in (1, 2, 4, 5, 6, 7):
        d = csv[i]
        meaning = {1: "250啤酒×231化学特征，另3列标识/类别", 2: "231×231化学相关矩阵，另1列行标签",
                   4: "250啤酒×50品评特征，另3列标识/类别", 5: "50×50品评相关矩阵，另1列行标签",
                   6: "44×50化学–品评相关子矩阵，另1列行标签",
                   7: "250啤酒×186评论派生特征，另3列标识/类别"}[i]
        rows.append(f"| {i}.csv | {len(d)}×{len(d.columns)} | {int(d.isna().sum().sum())} | {meaning} |")
    sheet_rows = [f"| {name} | {len(frame)}×{len(frame.columns)} | {int(frame.isna().sum().sum())} |"
                  for name, frame in xlsx[8].items()]
    corr_rows = [f"| {row['matrix']} | {row['method']} | {row['pair_n_min']}–{row['pair_n_max']} | {row['max_abs_error']:.6g} | {row['mean_abs_error']:.6g} | {row['matches_at_1e_10']} |"
                 for row in reconcile]
    key4 = next(row for row in checks if row["source"] == "4.csv")
    missing_rows = [f"| {name} | {count} | {count / 250:.1%} |" for name, count in summary["primary_missingness"]["1"].items()]
    neg_rows = [f"| {row['beer']} | {row['field']} | {row['value']:.8g} | {row['unit_metadata'] if pd.notna(row['unit_metadata']) else '未提供'} |" for row in negatives]
    supplementary = summary["supplementary"]
    return f"""# A题附件数据审计

审计日期：2026-10-23。{ATTRIBUTION}

本次仅检查附件本身的可用性、关联键、缺失、数值尺度和相关矩阵口径。原始文件保持不变；未联网、未上传数据。可复现脚本为 `solution_a/src/01_audit.py`，机器证据保存在 `solution_a/outputs/audit/`。脚本执行成功并不等同于人工审核。

## 1. 可用于建模的实际数据

原始附件1、4、7各有 **250个唯一啤酒样本**；可以通过 `beer` 一对一合并。化学变量231列，感官变量50列，论坛评论派生变量186列（其中3列全空，非空变量183列）。不得未经依据将250样本裁剪为226样本。题面/说明的文字口径应与这些实测结构分开记录，需参赛队确认官方是否另有筛选规则。

其中，附件8 `Sensory names` 标为Aroma的15项和Taste的30项恰好组成题目要求的45维；排除的是 `alcohol, aftertaste, body, co2, overall`。完整50字段与45维建模目标须分别统计，字段选择见 `feature_name_map.csv` 的 `selected_aroma_taste_45`。感官量尺和模板细节参见同目录 `sensory_mapping_review.md`；本审计不把附件4的连续值解释成原始0–6分。
```

题面第1页写“测量了226种不同啤酒的化学特性”，附件数据说明则写250个啤酒样品；本次附件实测支持250。题面对附件6写46×50、附件7写250×187，实测分别为44×50、250×186个数值字段。论文应逐项披露这些冲突，并说明采用实际附件范围的理由，不应静默改写题意。

文件	读取尺寸（含表头对应列）	缺失单元格	实际含义
{chr(10).join(rows)}

CSV均为UTF-8可读取，三个样本级CSV没有完全重复记录；数值列未检测到正负无穷。`beer` 覆盖1–250；样本顺序并非编号顺序，因此应显式按键关联。类别共22种，最小类别Faro为3例，最大类别Blond为31例，分组验证和类别比较须考虑样本不平衡。

附件3含12张 `beer_1`–`beer_12` 品评模板，每张读取为100×33，以及12×52的 `summary`。`summary` 中除编号外612个值全为缓存零，且对应612个公式；`beer_1` 中有54个公式。它是品评表设计，**不是12条额外观测**，也不是缺失的逐人评分记录。表头出现的 `A_ester_fruity`、`F_ester_fruity`、`4vg` 等与附件4名称不完全一致，不能无检查拼接。

2. 关联键：必须使用beer

高风险、证据充分：附件4和7的 `beer_id` 已损失精度。 两表各仅有{key4['unique_beer_id']}个不同条码，{key4['duplicate_beer_id_rows']}行处于重复条码组；分别有{key4['beer_id_mismatches_with_1']} / 250条记录与附件1的条码不一致。例如beer=10：附件1为5410228202929，附件4/7为5410230000000。按条码关联会丢行或产生多对多扩张。

附件1/4/7的 `beer` 集合、行序及类别逐条一致。附件8的标定数据、SHAP的两个区块、价格表均覆盖相同250个 `beer`；其条码与附件1一致。推荐保留附件1的原始条码作为展示信息，合并时使用 `validate='one_to_one'`；不要把已截断条码当作独立产品。价格表按beer排序，与附件1顺序不同。价格类别有 `wit`→`Wheat`、`bruin`→`Brown`、`oud bruin`→`Flanders old brown` 等别名，映射见 `price_category_map.csv`。

证据：`key_checks.csv`、`beer_id_discrepancies.csv`。条码应按字符串保存；已经丢失的末位不能靠格式化恢复。

3. 2/5/6的相关系数实测复核

三张给定矩阵均精确复现Spearman，不能称为Pearson。 复算按共有 `beer` 对齐、逐变量配对删除缺失；Spearman使用平均秩处理并列值，比较容差为1e-10。

题面第3页附件2说明写“单元格为皮尔逊相关系数”，与附件数据说明的Spearman表述矛盾；以下数值复核支持后者。

矩阵	复算方法	每对样本数	最大绝对误差	平均绝对误差	容差内一致
{chr(10).join(corr_rows)}

化学名称从附件2顺序映射到附件1，并由整张矩阵精确复现交叉验证；231个字段在附件8 `Sensory thresholds.field_name_R` 中均可找到。感官名称按附件8 `Sensory names` 的 `R_name` 与 `CleanName_PanelFeedback` 显式匹配。**附件4尾部的 `aftertaste, body, co2` 与附件5的 `Carbonation, Aftertaste, Body` 顺序不同**；按位置直接对齐会制造错误差异。

附件2、5的行列标签唯一、矩阵对称且对角为1。附件6仅包含44个化学指标，不代表全231个化学指标。建模及机制分析如需其余指标，应从样本级数据重新计算。任何基于相关性进行的特征筛选都应在训练折内重算；本节全样本复核只用于审计，不应充当验证折未知信息。

证据：`matrix_reconciliation.csv`、`feature_name_map.csv`；JSON同时记录矩阵形状、范围、对称误差。

4. 缺失与数值异常

附件1共73个缺失，占250×231数值单元的0.1264%，分布于以下9列。缺失比例不高，但不能无条件删去所有含缺失样本；插补参数须仅在训练折拟合。

化学字段	缺失数	样本缺失率
{chr(10).join(missing_rows)}

附件4无缺失。附件7中 `palate_acetaldehyde`、`palate_acetate`、`palate_dentist` 各250个缺失；其余183列无缺失。建议在派生数据中记录并剔除这3列，保留原始附件。

中风险、尺度不统一的证据充分：不能假定附件1全部已做标准z变换。 存在负值且各列样本标准差从约0.003123到796.633，均值也不统一为零。`X2.methyltetrahydrofuran.3.one` 最大12596.43287（beer=156），`gamma.nonalactone` 最大7256.135876（beer=181），`X.E..beta.damascenone` 最大5991.012523（beer=151）。附件8的concentration区块复现同样值，因此这不是本次CSV解析偶然错误；仍不能仅据此判定测量错误。主模型应比较训练折内标准化/稳健缩放等处理；不要把这些数直接解释为mg/L，也不要无依据删除极端样本。已核实的37列log10关系和其余字段的限制见第6节。

`column_profile.csv` 给出全字段缺失、分位数、均值、标准差、负值、零值、IQR标记。`extreme_value_flags.csv` 使用3IQR规则提供定位；IQR=0或稀疏词汇会产生很多标记，**标记不等于异常测量**。没有时间列、采集日期和历史版本，本审计不对时效性、批次漂移或随时间变化作推断。

5. 附件7的含义边界

附件7是按 `aroma_`、`palate_`、`taste_` 三个前缀组织、每组62词的数值表。附件8 `Sensory names.dataset` 中把相应描述词来源标为Ratebeer。没有评论正文、用户、逐条评分、评论日期或评论数，也没有 `ave_score_5` 字段（虽在名称字典中出现）。因此可把它作为论坛描述词派生特征，不能伪称已做原始评论分词、情感分析，亦不能把该表任何一列未经定义当成消费者总体评分。现有文件没有提供这些数值的完整归一化/变换说明。

6. 附件8的补充信息及使用限制

工作表	尺寸	缺失单元格
{chr(10).join(sheet_rows)}

- `Sensory thresholds` 是261条化学字段元数据，包含单位、阈值、来源等；部分文本有编码显示问题，阈值和单位需逐项核对后才能用于配方约束。字段元数据不能支持把全表采用同一个逆变换。
- `Sensory names` 有101条名称/类别记录，包含50个trained panel指标及Ratebeer字段；字典中出现不代表样本表实际存在。
- `Calibrated chemical dataset` 是250样本×70个标定数值，另3列标识/类别；有{supplementary['calibrated_missing_cells']}个缺失。与附件1共有字段的Spearman最小约{supplementary['calibrated_rank_rho_min']:.6f}，但并非全为1；37个基础理化字段与33个GCMS重叠字段需分别处理，不能全表取指数。若要估计现实添加量，应优先核对该页单位和阈值，再定义处理方案。
- `GBM importance MDI` 是已有模型的231项重要性，第一列是重要性数值、第二列是字段名；`GBM SHAP Values` 的500行是250条SHAP与250条concentration，不是500种啤酒。后者与附件1数值最大差{supplementary['concentration_block_max_abs_difference_from_1']:.3g}。这些是既有模型派生结果，训练数据和建模过程未完整给出；不能当成新的独立样本或在交叉验证之前据此筛选特征。
- `Beer Prices` 有7个渠道价格列，共{supplementary['price_missing_cells']}个价格缺失；{supplementary['prices_all_missing_beers']}种啤酒所有渠道价格均缺失。不同国家、渠道、计价单位和日期未在该页完整说明，不能直接平均作为原料成本或跨币种价格目标。`Sheet2` 为空表。

37个基础字段的底数已由本地数值复核为10。 附件1从 `acetaldehyde` 到 `kcalperc` 的前37个数值字段满足 `x=log10(c)`；校准值为0时先用该列最小正值的一半替代。共有{supplementary['basic_log10_comparable_values']}个可比较值，包含{supplementary['basic_log10_zero_replacement_count']}个零值替代，最大绝对误差{supplementary['basic_log10_max_abs_error']:.6g}。此范围明确排除了{supplementary['basic_log10_excluded_calibrated_missing_values']}个校准缺失和{supplementary['basic_log10_excluded_negative_values']}个负值，不能宣称它们也通过直接log10验证。其余33个GCMS重叠字段全部不满足同一直接log10关系；不得对231列统一使用 `exp(x)` 或 `10**x` 后计算浓度/OAV。已知37列中，逆变换只能还原零值的替代量，也无法据此恢复真实检出量。逐列证据见 `calibrated_comparison.csv`。

```
标定数据还存在{len(negatives)}个负值，建议保留并核查检测/标定背景，勿擅自视为真实负浓度用于配方约束：

| beer | 字段 | 标定值 | 元数据单位 |
| ---: | --- | ---: | --- |
{chr(10).join(neg_rows)}

## 7. 建模交接与未决事项

1. 以250个 `beer` 为样本集，保留附件1的231个化学变量和附件4的50个品评字段。45维感官画像明确按元数据Aroma15项+Taste30项选定，不能把完整50字段与45维目标混为一谈；把 `beer`、`beer_id` 排除出预测特征。是否加入类别由研究问题和验证方案决定。
2. 模型评价采用严格训练/测试隔离，插补、缩放、降维、特征筛选均在训练折内完成；不要用附件2/5/6的全样本相关性或附件8的MDI/SHAP提前筛选后再报告无偏验证。
3. 可复现附件相关矩阵采用Spearman；如果问题明确要求Pearson，另外重算Pearson并明确二者差别。所有字段名和关联键均显式匹配。
4. 论坛数据只支持描述词数值特征分析；缺少原始评论和消费者整体评分时，应明确任务可识别边界。
5. 需要参赛队核对题面样本数冲突、预处理说明、标定单位、负浓度、官方勘误；现阶段不把待核实信息写成事实。

## 8. 复现与证据清单

在仓库根目录执行：

```bash
python solution_a/src/01_audit.py
```

也可用安装了pandas、numpy、openpyxl的Python执行同一脚本。可选 `--data-dir` 和 `--output-dir` 修改输入及审计证据目录；脚本不修改原始附件。环境版本保存在 `audit_summary.json`，SHA-256保存在 `source_files.csv`；本次执行前后哈希一致。

证据文件：`audit_summary.json`（总体结构与自动校验）、`source_files.csv`（输入哈希）、`column_profile.csv`（逐列画像）、`missingness.csv`、`key_checks.csv`、`beer_id_discrepancies.csv`、`feature_name_map.csv`、`matrix_reconciliation.csv`、`calibrated_comparison.csv`、`negative_calibrated_values.csv`、`extreme_value_flags.csv`、`style_counts.csv`、`price_availability.csv`、`price_category_map.csv`。所有结论来自本地附件；没有外部文献补充或人工审核声明。
"""

if __name__ == "__main__":
    main()
```

src/02_q1_baseline.py

SHA-256: 6357ece28220bd3567803a214e4b83d84c8192713622bbf0500ab58e6b0f94ab

```
"""Leakage-controlled prediction of 45 *standardized* sensory dimensions.

This is a starting baseline, NOT a recovered 0-6 sensory score. The attachment
does not provide the per-panelist inverse calibration needed for that recovery
.
"""
import json
from pathlib import Path
import platform

import joblib
import numpy as np
import pandas as pd
import sklearn
from scipy.stats import spearmanr
from sklearn.compose import TransformedTargetRegressor
from sklearn.dummy import DummyRegressor
from sklearn.ensemble import ExtraTreesRegressor
from sklearn.impute import SimpleImputer
from sklearn.linear_model import Ridge
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.model_selection import GridSearchCV, KFold
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import StandardScaler
from threadpoolctl import threadpool_limits

from common import SEED, SOLUTION, load_xy

OUT = SOLUTION / "outputs" / "q1"
ALPHAS = [0.1, 1.0, 10.0, 100.0, 1000.0, 10000.0, 100000.0, 1000000.0]


def ridge_pipeline():
    return Pipeline([
        ("imputer", SimpleImputer(strategy="median", add_indicator=True,
                                  keep_empty_features=True)),
        ("scale", StandardScaler()),
        ("model", TransformedTargetRegressor(
            regressor=Ridge(solver="svd"), transformer=StandardScaler())),
    ])


def make_search(seed):
    # Scaling/imputation, including y scaling, are refit in EVERY inner fold.
    return GridSearchCV(
        ridge_pipeline(), {"model__regressor__alpha": ALPHAS},
        cv=KFold(n_splits=4, shuffle=True, random_state=seed),
        scoring="neg_mean_squared_error", n_jobs=1, refit=True,
        error_score="raise",
    )


def tree_pipeline(seed):
    return Pipeline([
        ("imputer", SimpleImputer(strategy="median", add_indicator=True,
                                  keep_empty_features=True)),
        ("model", ExtraTreesRegressor(
            n_estimators=300, min_samples_leaf=3, max_features=0.7,
            random_state=seed, n_jobs=1)),
```

```
    ])


def scores(y, pred):
    return {
        "mae": float(mean_absolute_error(y, pred)),
        "rmse": float(np.sqrt(mean_squared_error(y, pred))),
        "macro_r2": float(r2_score(y, pred, multioutput="uniform_average")),
    }


def main():
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y = load_xy()
    targets = y.columns.tolist()
    # Prespecified nested five-fold baseline. IDs and styles are not predictors.
    outer = KFold(n_splits=5, shuffle=True, random_state=SEED)
    predictions = {name: np.full(y.shape, np.nan) for name in
                   ("mean", "ridge", "extra_trees", "ridge_mask10", "ridge_mask20",
                    "extra_trees_mask10", "extra_trees_mask20")}
    fold_ids = np.zeros(len(x), dtype=int)
    folds = []
    stress_counts = []
    for fold, (train, test) in enumerate(outer.split(x), start=1):
        fold_ids[test] = fold
        xtr, xte, ytr, yte = x.iloc[train], x.iloc[test], y.iloc[train], y.iloc[test]
        search = make_search(SEED + fold)
        search.fit(xtr, ytr)
        candidates = {
            "ridge": search.best_estimator_,
            "mean": DummyRegressor(strategy="mean").fit(xtr, ytr),
            # A fixed nonlinear comparison, not tuned on outer test outcomes.
            "extra_trees": tree_pipeline(SEED + fold).fit(xtr, ytr),
        }
        for name, model in candidates.items():
            pred = model.predict(xte)
            predictions[name][test] = pred
            folds.append({"fold": fold, "model": name, "train_n": len(train),
                          "test_n": len(test), **scores(yte, pred),
                          "ridge_alpha": search.best_params_["model__regressor__alpha"]
                          if name == "ridge" else None})
        # Deployment stress: randomly hide observed TEST covariates only.
        # Identical random uniforms make 10% masks a subset of the 20% masks.
        uniforms = np.random.default_rng(SEED + 100 + fold).random(xte.shape)
        for rate, suffix in [(0.1, "mask10"), (0.2, "mask20")]:
            mask = (uniforms < rate) & xte.notna().to_numpy()
            hidden = xte.mask(mask)
            stress_counts.append({"fold": fold, "rate": rate,
                                  "additional_hidden": int(mask.sum()),
                                  "original_observed": int(xte.notna().sum().sum())})
            for base in ("ridge", "extra_trees"):
                name = f"{base}_{suffix}"
                pred = candidates[base].predict(hidden)
                predictions[name][test] = pred
                folds.append({"fold": fold, "model": name, "train_n": len(train),
                              "test_n": len(test), **scores(yte, pred),
```

```
                                "ridge_alpha": search.best_params_["model__regressor__alpha"]
                                if base == "ridge" else None})
        print(f"Fold {fold}/5: alpha={search.best_params_['model__regressor__alpha']}, "
              f"ridge RMSE={scores(yte, predictions['ridge'][test])['rmse']:.4f}", flush=True)

    metric_rows, target_rows = [], []
    truth = y.to_numpy()
    for name, pred in predictions.items():
        if not np.isfinite(pred).all():
            raise AssertionError(f"Incomplete predictions: {name}")
        metric_rows.append({"model": name, **scores(truth, pred)})
        for j, target in enumerate(targets):
            target_rows.append({"model": name, "target": target,
                                **scores(truth[:, j], pred[:, j]),
                                "spearman": float(spearmanr(truth[:, j], pred[:, j]).statistic)})
        table = pd.concat([meta, pd.DataFrame({"fold": fold_ids}),
                           pd.DataFrame(pred, columns=targets)], axis=1)
        table.to_csv(OUT / f"oof_{name}.csv", index=False, lineterminator="\n")
    pd.DataFrame(metric_rows).to_csv(OUT / "metrics_overall.csv", index=False, lineterminator="\n")
    pd.DataFrame(target_rows).to_csv(OUT / "metrics_by_target.csv", index=False, lineterminator="\n")
    pd.DataFrame(folds).to_csv(OUT / "metrics_by_fold.csv", index=False, lineterminator="\n")
    pd.DataFrame(stress_counts).to_csv(OUT / "missingness_stress.csv", index=False, lineterminator="\n")

    # Full-data model is for later synthesis/inference; fitted values are not a test.
    final = make_search(SEED + 99)
    final.fit(x, y)
    joblib.dump({"pipeline": final.best_estimator_, "features": x.columns.tolist(),
                 "targets": targets, "target_scale": "attachment_4_standardized"},
                OUT / "ridge_model.joblib")
    fitted = final.predict(x)
    pd.concat([meta, pd.DataFrame(fitted, columns=targets)], axis=1).to_csv(
        OUT / "fitted_standardized_NOT_validation.csv", index=False, lineterminator="\n")
    pd.concat([meta, y], axis=1).to_csv(OUT / "observed_standardized.csv", index=False, lineterminator="\n")
    tree = tree_pipeline(SEED + 99).fit(x, y)
    joblib.dump({"pipeline": tree, "features": x.columns.tolist(), "targets": targets,
                 "target_scale": "attachment_4_standardized"}, OUT / "extra_trees_model.joblib")
    summary = {
        "seed": SEED, "samples": len(x), "features": x.shape[1], "targets": targets,
        "validation": "5 outer shuffled folds, 4 inner folds; one seed; no style/ID covariates",
        "unit": "attachment 4 standardized sensory values; NOT original 0-6 scores",
        "final_ridge_alpha": final.best_params_["model__regressor__alpha"],
        "alpha_grid": ALPHAS, "metrics": metric_rows,
        "limitations": [
```

```
            "Original 0-6 scale is not identifiable from blank cards and panel
ist-normalized means.",
            "Random CV estimates new beers in the existing style mixture, not
unseen-style transfer.",
            "Global preprocessing used by attachment creators cannot be undone
; metrics are conditional on supplied data.",
            "Missingness stress is synthetic random masking, not evidence abou
t detection-limit censoring.",
            "One split seed is a baseline, not completed robustness or uncerta
inty validation.",
        ],
        "versions": {"python": platform.python_version(), "numpy": np.__versio
n__,
                     "pandas": pd.__version__, "sklearn": sklearn.__version__}
,
    }
    (OUT / "summary.json").write_text(json.dumps(summary, ensure_ascii=False,
indent=2), encoding="utf-8", newline="\n")
    print(pd.DataFrame(metric_rows).to_string(index=False), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/02b_q1_robust.py

SHA-256: e7ea1f17106fdeabf52087e9532421927210e3ebbcb05c1dcf13b61bb14679f1

```
"""Exploratory robust Ridge follow-up after diagnosing extreme covariates.

Clipping bounds, imputation, X/Y scaling and alpha selection all stay inside
the training folds. The original split is reused: this is a robustness check,
not an untouched confirmatory test. No samples or targets are deleted.
"""
import importlib.util
import json
from pathlib import Path

import joblib
import numpy as np
import pandas as pd
from scipy.stats import spearmanr
from sklearn.model_selection import GridSearchCV, KFold
from sklearn.pipeline import Pipeline
from threadpoolctl import threadpool_limits

from common import QuantileClipper, SEED, SOLUTION, load_xy

spec = importlib.util.spec_from_file_location("baseline", Path(__file__).with_name("02_q1_baseline.py"))
baseline = importlib.util.module_from_spec(spec)
spec.loader.exec_module(baseline)
OUT = SOLUTION / "outputs" / "q1_robust"


def search(seed):
    plain = baseline.ridge_pipeline()
    model = Pipeline([("clip", QuantileClipper()), *plain.steps])
    return GridSearchCV(
        model, {"model__regressor__alpha": baseline.ALPHAS},
        cv=KFold(n_splits=4, shuffle=True, random_state=seed),
        scoring="neg_mean_squared_error", n_jobs=1, error_score="raise",
    )


def main():
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y = load_xy()
    pred = {name: np.full(y.shape, np.nan) for name in
            ("ridge_winsor", "ridge_winsor_mask10", "ridge_winsor_mask20")}
    fold_ids = np.zeros(len(x), dtype=int)
    fold_metrics = []
    clipping = []
    for fold, (train, test) in enumerate(KFold(5, shuffle=True, random_state=SEED).split(x), 1):
        fold_ids[test] = fold
        fitted = search(SEED + fold).fit(x.iloc[train], y.iloc[train])
        alpha = fitted.best_params_["model__regressor__alpha"]
        xte = x.iloc[test]
        bounds = fitted.best_estimator_.named_steps["clip"].bounds_
        counts = ((xte.to_numpy() < bounds[0]) | (xte.to_numpy() > bounds[1])).sum(axis=0)
        clipping.extend({"fold": fold, "feature": feature, "test_values_clipped": int(n),
                         "train_lower_01": float(bounds[0, j]), "train_upper_99": float(bounds[1, j])}
                        for j, (feature, n) in enumerate(zip(x.columns, counts
```

```
)))
        uniforms = np.random.default_rng(SEED + 100 + fold).random(xte.shape)
        for rate, name in [(0, "ridge_winsor"), (.1, "ridge_winsor_mask10"), (.2, "ridge_winsor_mask20")]:
            test_input = xte.mask((uniforms < rate) & xte.notna().to_numpy())
            pred[name][test] = fitted.predict(test_input)
            fold_metrics.append({"fold": fold, "model": name, "ridge_alpha": alpha,
                                 **baseline.scores(y.iloc[test], pred[name][test])})
        print(f"Robust fold {fold}/5: alpha={alpha}", flush=True)
    metrics, by_target = [], []
    for name, values in pred.items():
        assert np.isfinite(values).all()
        metrics.append({"model": name, **baseline.scores(y, values)})
        for j, target in enumerate(y.columns):
            by_target.append({"model": name, "target": target,
                              **baseline.scores(y.iloc[:, j], values[:, j]),
                              "spearman": float(spearmanr(y.iloc[:, j], values[:, j]).statistic)})
        pd.concat([meta, pd.DataFrame({"fold": fold_ids}), pd.DataFrame(values, columns=y.columns)], axis=1).to_csv(
            OUT / f"oof_{name}.csv", index=False, lineterminator="\n")
    pd.DataFrame(metrics).to_csv(OUT / "metrics_overall.csv", index=False, lineterminator="\n")
    pd.DataFrame(by_target).to_csv(OUT / "metrics_by_target.csv", index=False, lineterminator="\n")
    pd.DataFrame(fold_metrics).to_csv(OUT / "metrics_by_fold.csv", index=False, lineterminator="\n")
    pd.DataFrame(clipping).to_csv(OUT / "clipping_bounds.csv", index=False, lineterminator="\n")
    final = search(SEED + 99).fit(x, y)
    joblib.dump({"pipeline": final.best_estimator_, "features": x.columns.tolist(),
                 "targets": y.columns.tolist(), "target_scale": "attachment_4_standardized"},
                OUT / "ridge_winsor_model.joblib")
    summary = {
        "purpose": "Exploratory robustness follow-up; original five folds reused after anomaly diagnosis",
        "seed": SEED, "train_quantiles": [.01, .99], "samples_retained": len(x),
        "metrics": metrics, "final_alpha": final.best_params_["model__regressor__alpha"],
        "limitations": ["Not a fresh holdout test", "Fixed 1%/99% clipping can suppress genuine extremes",
                        "Original 0-6 scores still not identified", "One split seed only"],
    }
    (OUT / "summary.json").write_text(json.dumps(summary, ensure_ascii=False, indent=2), encoding="utf-8", newline="\n")
    print(pd.DataFrame(metrics).to_string(index=False), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/03_q2_network.py

SHA-256: 56e7858449d5aa25efd2ce581a083d6b477711991dd7f78a3c9552849cc5603b

```
#!/usr/bin/env python3
"""Q2 descriptive association baseline.

Run from any directory with the repository .venv Python. Data transformations,
selection rules, and validation scope are recorded in outputs/q2/README.md.
"""
from __future__ import annotations

import argparse
import json
from pathlib import Path

import numpy as np
import pandas as pd
from scipy.stats import pearsonr, rankdata, spearmanr


ROOT = Path(__file__).resolve().parents[2]
DATA = ROOT / "2026年第七届MathorCup数学应用挑战赛-大数据竞赛初赛赛题" / "2026年MathorCup大数据挑战赛-赛道A初赛" / "附件"
OUTPUT = ROOT / "solution_a" / "outputs" / "q2"
EXCLUDE_X = {
    "kcalperc", "esters_sum", "aroma_hops_sum", "acids_sum", "sulfur_sum",
    "bitterness", "color.EBC.", "pH", "protein.g.L.", "betaglucan.mg.L.",
    "GFS", "unfermentables", "CO2.PSI.",
}
EXCLUDE_Y = {"alcohol", "aftertaste", "body", "co2", "overall"}


def unit_columns(a: np.ndarray) -> np.ndarray:
    centered = a - a.mean(axis=0)
    denominator = np.sqrt(np.sum(centered * centered, axis=0))
    return np.divide(centered, denominator, out=np.zeros_like(centered), where=denominator > 0)


def cross_correlation(x: np.ndarray, y: np.ndarray, method: str) -> np.ndarray:
    """Pairwise-complete correlation, reranking y when an x column is missing.

    Every target must be observed. Ranking each x column independently is not
    sufficient for pairwise Spearman: y must also be reranked on the same rows.
    Constant columns are returned as NaN and cannot enter a Top-3.
    """
    if not np.isfinite(y).all():
        raise ValueError("Targets contain missing/nonfinite values; revise pairwise handling.")
    result = np.full((x.shape[1], y.shape[1]), np.nan)
    complete = np.isfinite(x).all(axis=0)
    xx, yy = x[:, complete], y
    if method == "spearman":
        xx, yy = rankdata(xx, axis=0), rankdata(yy, axis=0)
    result[complete] = unit_columns(xx).T @ unit_columns(yy)
    result[np.flatnonzero(complete)[np.ptp(xx, axis=0) == 0], :] = np.nan
    result[:, np.ptp(yy, axis=0) == 0] = np.nan
    for j in np.flatnonzero(~complete):
        keep = np.isfinite(x[:, j])
        if keep.sum() < 3:
```

```
            continue
        xx, yy = x[keep, j:j + 1], y[keep]
        if method == "spearman":
            xx, yy = rankdata(xx, axis=0), rankdata(yy, axis=0)
        if np.ptp(xx) == 0:
            continue
        result[j] = (unit_columns(xx).T @ unit_columns(yy))[0]
        result[j, np.ptp(yy, axis=0) == 0] = np.nan
    return np.clip(result, -1, 1)


def top3(correlation: np.ndarray) -> np.ndarray:
    """Stable input-order tie break; missing/constant correlations rank last."""
    if np.any(np.isfinite(correlation).sum(axis=0) < 3):
        raise ValueError("Fewer than three eligible candidates for a target.")
    return np.argsort(-np.nan_to_num(np.abs(correlation), nan=-1), axis=0, kind="stable")[:3]


def jaccard(a: np.ndarray, b: np.ndarray) -> float:
    aa, bb = set(a.tolist()), set(b.tolist())
    return len(aa & bb) / len(aa | bb)


def save_csv(frame: pd.DataFrame, name: str) -> None:
    frame.to_csv(OUTPUT / name, index=False, encoding="utf-8-sig", float_format="%.10g", lineterminator="\n")


def main(bootstraps: int, seed: int) -> None:
    OUTPUT.mkdir(parents=True, exist_ok=True)
    chemical = pd.read_csv(DATA / "1.csv")
    sensory = pd.read_csv(DATA / "4.csv")
    supplied = pd.read_csv(DATA / "2.csv", index_col=0)
    metadata = pd.read_excel(DATA / "8.xlsx", sheet_name="Sensory thresholds")
    metadata = metadata.dropna(subset=["field_name_R"]).drop_duplicates("field_name_R").set_index("field_name_R")
    features = chemical.columns[3:].tolist()
    targets = [c for c in sensory.columns[3:] if c not in EXCLUDE_Y]
    assert len(features) == 231 and len(targets) == 45
    assert chemical.beer.is_unique and sensory.beer.is_unique
    assert supplied.index.tolist() == supplied.columns.tolist()
    merged = chemical.merge(sensory[["beer", *targets]], on="beer", validate="one_to_one", how="inner")
    assert len(merged) == len(chemical) == len(sensory) == 250
    # Attachments retain the same numeric feature order; verify using every pair.
    actual_spearman = chemical[features].corr(method="spearman").to_numpy()
    actual_pearson = chemical[features].corr(method="pearson").to_numpy()
    r = supplied.to_numpy(dtype=float)
    upper = np.triu_indices(len(features), 1)
    delta_s = np.abs(actual_spearman[upper] - r[upper])
    delta_p = np.abs(actual_pearson[upper] - r[upper])
    assert float(np.nanmax(delta_s)) < 1e-10, "Attachment order/definition changed."
    pretty = dict(zip(features, supplied.index.astype(str)))
    candidates = [c for c in features if c not in EXCLUDE_X]
    x, y = merged[candidates].to_numpy(float), merged[targets].to_numpy(float)
    rho = cross_correlation(x, y, "spearman")
    pearson = cross_correlation(x, y, "pearson")
    # Check the optimized pairwise routine against scipy, including missingnes
```

```
s.
    check_columns = np.unique(np.r_[np.arange(5), np.flatnonzero(~np.isfinite(
x).all(axis=0))])
    max_check_error = 0.0
    for j in check_columns:
        keep = np.isfinite(x[:, j])
        for t in [0, 20, 44]:
            for matrix, function in [(rho, spearmanr), (pearson, pearsonr)]:
                reference = function(x[keep, j], y[keep, t]).statistic
                max_check_error = max(max_check_error, abs(float(reference - m
atrix[j, t])))
    assert max_check_error < 1e-12

    node_table = pd.DataFrame({"field": features, "chemical_name": [pretty[f]
for f in features], "eligible_top3": [f in candidates for f in features]})
    for col in ["origin_paper", "unit", "calibrated", "off_flavors", "threshol
d_mean", "threshold_median"]:
        node_table[col] = metadata[col].reindex(features).to_numpy()
    network_summary = []
    for threshold in [0.6, 0.7, 0.8]:
        adjacency = np.abs(r) >= threshold
        np.fill_diagonal(adjacency, False)
        left, right = np.where(np.triu(adjacency, 1))
        weights = r[left, right]
        save_csv(pd.DataFrame({
            "source": np.asarray(features)[left], "target": np.asarray(feature
s)[right],
            "source_name": supplied.index.to_numpy()[left], "target_name": sup
plied.index.to_numpy()[right],
            "spearman_rho": weights, "absolute_weight": np.abs(weights), "sign
": np.sign(weights).astype(int),
        }), f"network_edges_rho_{threshold:.1f}.csv")
        node_table[f"degree_{threshold:.1f}"] = adjacency.sum(axis=1)
        node_table[f"strength_{threshold:.1f}"] = (np.abs(r) * adjacency).sum(
axis=1)
        network_summary.append({"absolute_rho_threshold": threshold, "edges":
len(weights), "positive_edges": int((weights > 0).sum()), "negative_edges": in
t((weights < 0).sum()), "isolated_nodes": int((adjacency.sum(axis=1) == 0).sum
())})
    save_csv(node_table, "network_nodes.csv")

    initial_top = top3(rho)
    pearson_top = top3(pearson)
    # This is a sensitivity check, not a causal adjustment or formal partial r
ho.
    within_x = merged[candidates] - merged.groupby("tasting_category_fine")[ca
ndidates].transform("mean")
    within_y = merged[targets] - merged.groupby("tasting_category_fine")[targe
ts].transform("mean")
    within_rho = cross_correlation(within_x.to_numpy(float), within_y.to_numpy
(float), "spearman")
    within_top = top3(within_rho)
    rng = np.random.default_rng(seed)
    selections = np.zeros_like(rho, dtype=int)
    draws = np.empty((bootstraps, *rho.shape), dtype=float)
    for b in range(bootstraps):
        rows = rng.integers(0, len(merged), len(merged))
        draws[b] = cross_correlation(x[rows], y[rows], "spearman")
        winners = top3(draws[b])
        selections[winners, np.arange(len(targets))] += 1
        if (b + 1) % 50 == 0:
            print(f"bootstrap {b + 1}/{bootstraps}", flush=True)
```

```
    frequency = selections / bootstraps
    assert np.all(selections.sum(axis=0) == 3 * bootstraps)
    lower, upper_ci = np.nanquantile(draws, [0.025, 0.975], axis=0)
    valid_draws = np.isfinite(draws).sum(axis=0)
    sign_agreement = ((np.sign(draws) == np.sign(rho)[None]) & np.isfinite(draws)).sum(axis=0) / valid_draws
    global_ranks = np.empty_like(initial_top, shape=rho.shape)
    within_ranks = np.empty_like(global_ranks)
    for t in range(len(targets)):
        global_ranks[np.argsort(-np.abs(rho[:, t]), kind="stable"), t] = np.arange(1, len(candidates) + 1)
        within_ranks[np.argsort(-np.abs(within_rho[:, t]), kind="stable"), t] = np.arange(1, len(candidates) + 1)
    rows = []
    method_rows = []
    for t, target in enumerate(targets):
        method_rows.append({
            "sensory_target": target,
            "spearman_top3": " | ".join(candidates[j] for j in initial_top[:, t]),
            "pearson_top3": " | ".join(candidates[j] for j in pearson_top[:, t]),
            "within_style_top3": " | ".join(candidates[j] for j in within_top[:, t]),
            "jaccard_spearman_pearson": jaccard(initial_top[:, t], pearson_top[:, t]),
            "jaccard_global_within_style": jaccard(initial_top[:, t], within_top[:, t]),
        })
        for j, candidate in enumerate(candidates):
            rows.append({
                "sensory_target": target, "rank": int(global_ranks[j, t]), "compound": candidate,
                "chemical_name": pretty[candidate], "n_observed_pairs": int(np.isfinite(x[:, j]).sum()),
                "spearman_rho": rho[j, t], "pearson_r": pearson[j, t],
                "bootstrap_top3_count": int(selections[j, t]), "bootstrap_top3_frequency": frequency[j, t],
                "bootstrap_rho_lower_95": lower[j, t], "bootstrap_rho_upper_95": upper_ci[j, t],
                "bootstrap_sign_agreement": sign_agreement[j, t], "bootstrap_valid_draws": int(valid_draws[j, t]),
                "within_style_spearman_rho": within_rho[j, t], "within_style_rank": int(within_ranks[j, t]),
                "is_pearson_top3": bool(j in pearson_top[:, t]),
                "is_within_style_top3": bool(j in within_top[:, t]),
            })
    scores = pd.DataFrame(rows).sort_values(["sensory_target", "rank"])
    top_table = scores[scores["rank"] <= 3].copy()
    top_table = top_table.merge(node_table, left_on="compound", right_on="field", how="left", validate="many_to_one", suffixes=("", "_network")).drop(columns=["field", "chemical_name_network"])
    methods = pd.DataFrame(method_rows)
    save_csv(scores, "all_candidate_stability.csv")
    save_csv(top_table, "top3_compounds.csv")
    save_csv(methods, "method_sensitivity.csv")
    summary = {
        "scope": "Full-sample descriptive associations; neither causal evidence nor held-out predictive validation.",
        "n_beers": len(merged), "n_features": len(features), "n_candidate_compounds": len(candidates),
        "n_sensory_targets": len(targets), "bootstrap_draws": bootstraps, "see
```

```
d": seed,
        "excluded_compounds": sorted(EXCLUDE_X), "excluded_sensory_targets": sorted(EXCLUDE_Y),
        "correlation_audit": {"supplied_vs_spearman_max_abs_error": float(np.nanmax(delta_s)), "supplied_vs_spearman_mean_abs_error": float(np.nanmean(delta_s)), "supplied_vs_pearson_mean_abs_error": float(np.nanmean(delta_p)), "supplied_vs_pearson_max_abs_error": float(np.nanmax(delta_p)), "optimized_routine_vs_scipy_max_abs_error": max_check_error},
        "networks": network_summary,
        "top3_stability": {"mean_selection_frequency": float(top_table.bootstrap_top3_frequency.mean()), "median_selection_frequency": float(top_table.bootstrap_top3_frequency.median()), "number_frequency_at_least_0_8": int((top_table.bootstrap_top3_frequency >= .8).sum()), "total_selected": len(top_table), "max_frequency_monte_carlo_standard_error": float(np.sqrt(.25 / bootstraps))},
        "mean_jaccard_spearman_pearson": float(methods.jaccard_spearman_pearson.mean()),
        "mean_jaccard_global_within_style": float(methods.jaccard_global_within_style.mean()),
        "targets_with_no_global_within_overlap": int((methods.jaccard_global_within_style == 0).sum()),
        "style_counts": {str(k): int(v) for k, v in merged.tasting_category_fine.value_counts().items()},
        "limitations": ["No causal interpretation", "No per-candidate mechanism literature verification yet", "All-sample network is not an external independent prior", "Global row bootstrap does not fix style composition", "Mean-centered within-style rank correlation is a sensitivity analysis, not full confounding control", "Continuous standardized targets do not supply raw 0-6 calibration", "Graph provides structure/context; this baseline ranks marginal correlations and does not fit a graph-regularized predictive model"],
    }
    (OUTPUT / "summary.json").write_text(json.dumps(summary, ensure_ascii=False, indent=2) + "\n", encoding="utf-8", newline="\n")
    (OUTPUT / "README.md").write_text(f"""# 第二问首轮关联分析

本目录由 `solution_a/src/03_q2_network.py` 生成，计算结果与 scipy 成对相关计算进行数值核对。重跑：

```bash
.venv/bin/python solution_a/src/03_q2_network.py --bootstraps {bootstraps} --seed {seed}
```

数据为按 beer 一对一连接的 250 款啤酒；全图 231 节点、Top-3 候选 218 项、感官目标 45 项。所有计算在附件既有数值表示上进行，没有统一取指数或把连续标签伪还原为 0–6 分。

文件	用途
network_nodes.csv	全节点名映射、来源/单位/阈值及各阈值度数、加权度数
network_edges_rho_*.csv	绝对相关阈值 0.6/0.7/0.8 的有符号网络
top3_compounds.csv	每个感官维度按绝对 Spearman 相关选择的 3 个候选
all_candidate_stability.csv	全部 218×45 候选的相关、bootstrap 入选频率、分位区间和风格敏感性
method_sensitivity.csv	Pearson 替代和去风格均值后的 Top-3/Jaccard
summary.json	样本、阈值、网络、稳定性、数值校验及限制摘要

2.csv 与全样本 Spearman 矩阵最大差 {np.nanmax(delta_s):.3g}，故它是当前样本导出的描述性网络；预测交叉验证时必须仅在训练折重建。全样本图可解释 Top-3 的邻域和相关冗余，但本轮未拟合图正则化模型。阈值 0.6/0.7/0.8 是稀疏化参数，不是显著性阈值。

Bootstrap 为 {bootstraps} 次全样本行重采样，重新排名，固定种子 {seed}，频率最大蒙特卡洛标准误 {np.sqrt(.25 / bootstraps):.4f}。并列时按附件特征顺序打破。区间为相关系数的描述性 bootstrap 分位数，不是选择后推断保证。去风格均值对 X、Y 都在当前表示上按风格减均值后计算 S
```

```
pearman，只检查风格间均值混杂。
233
234 本目录结论是**关联候选，不是因果因素**；稳定性不等于化学合理性。`8.xlsx` 元信息仅作附件证据，逐条机制文献验证尚未完成。`5.csv/6.csv` 和预计算 GBM/SHAP 未用于筛选。Top-3 的所有 135 项中，入选频率 ≥0.8 的有 {summary['top3_stability']['number_frequency_at_least_0_8']} 项；Spearman/Pearson 平均 Jaccard 为 {summary['mean_jaccard_spearman_pearson']:.3f}，去风格均值前后为 {summary['mean_jaccard_global_within_style']:.3f}。这些是全样本解释稳定性，不是未见啤酒预测性能。
235 """, encoding="utf-8", newline="\n")
236     print(json.dumps(summary, ensure_ascii=False, indent=2))
237
238
239 if __name__ == "__main__":
240     parser = argparse.ArgumentParser(description=__doc__)
241     parser.add_argument("--bootstraps", type=int, default=200)
242     parser.add_argument("--seed", type=int, default=20261023)
243     args = parser.parse_args()
244     if args.bootstraps < 1:
245         parser.error("--bootstraps must be positive")
246     main(args.bootstraps, args.seed)
```

src/04_stage_summary.py

SHA-256: 79ef7338a76e6ec46e81e86782c902bc295b1606754c986c18b36d76e3ded45d

```python
"""Render inspectable first-round research figures and a generated progress note.

All displayed quantitative results are read from saved experiment outputs.
"""
import json

import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd

from common import SOLUTION


def main():
    base = pd.read_csv(SOLUTION / "outputs/q1/metrics_overall.csv").set_index("model")
    robust = pd.read_csv(SOLUTION / "outputs/q1_robust/metrics_overall.csv").set_index("model")
    q2 = json.loads((SOLUTION / "outputs/q2/summary.json").read_text(encoding="utf-8"))
    targets = pd.read_csv(SOLUTION / "outputs/q1/metrics_by_target.csv")
    tree_targets = targets[targets.model == "extra_trees"]
    figures = SOLUTION / "outputs/figures"
    figures.mkdir(parents=True, exist_ok=True)
    plt.rcParams.update({"font.family": "DejaVu Sans", "font.size": 10,
                         "axes.spines.top": False, "axes.spines.right": False,
                         "savefig.facecolor": "white", "figure.facecolor": "white"})
    fig, axes = plt.subplots(1, 2, figsize=(11.2, 5.2), gridspec_kw={"width_ratios": [1, 1]})
    labels = ["Mean baseline", "Ridge", "Robust Ridge*", "ExtraTrees"]
    values = [base.loc["mean", "rmse"], base.loc["ridge", "rmse"],
              robust.loc["ridge_winsor", "rmse"], base.loc["extra_trees", "rmse"]]
    axes[0].barh(labels, values, color=["#A3A8AE", "#A3A8AE", "#C98A27", "#2674A4"], height=.6)
    axes[0].invert_yaxis()
    axes[0].set_xlim(0, max(values) * 1.24)
    axes[0].set_xlabel("Pooled out-of-fold RMSE")
    axes[0].set_title("45 sensory dimensions | 250 beers", loc="left", pad=16)
    for i, value in enumerate(values):
        axes[0].text(value + .01, i, f"{value:.4f}", va="center")
    rates = [0, 10, 20]
    tree_values = base.loc[["extra_trees", "extra_trees_mask10", "extra_trees_mask20"], "rmse"].to_numpy()
    robust_values = robust.loc[["ridge_winsor", "ridge_winsor_mask10", "ridge_winsor_mask20"], "rmse"].to_numpy()
    axes[1].plot(rates, tree_values, "o-", color="#2674A4", label="ExtraTrees", linewidth=1.7)
    axes[1].plot(rates, robust_values, "s--", color="#C98A27", label="Robust Ridge*", linewidth=1.7)
    axes[1].axhline(base.loc["mean", "rmse"], color="#666666", linestyle=":", label="Mean baseline")
    axes[1].set_xticks(rates)
    axes[1].set_ylim(0, .65)
    axes[1].set_xlabel("Additional random test-feature masking (%)")
```

```
    axes[1].set_ylabel("Pooled out-of-fold RMSE")
    axes[1].set_title("Missing-feature stress experiment", loc="left", pad=16)
    axes[1].legend(frameon=False, fontsize=9, loc="lower right")
    for rate, value in zip(rates, tree_values):
        axes[1].annotate(f"{value:.4f}", (rate, value), xytext=(0, -17),
                         textcoords="offset points", ha="center", color="#2674
A4", fontsize=9)
    for ax in axes:
        ax.grid(axis="x" if ax is axes[0] else "y", color="#E6E8EB", linewidth
=.7)
        ax.set_axisbelow(True)
    fig.suptitle("A track: first-round sensory prediction", x=.08, ha="left",
fontsize=16, fontweight="bold")
    fig.text(.08, .025,
             "Targets: attachment 4 standardized values, not original 0-6 scor
es. One fixed five-fold split.\n"
             "*Robust Ridge is a post-diagnosis check using the same folds; bo
unds are fitted within training folds.",
             fontsize=9, color="#50555B", va="bottom")
    fig.subplots_adjust(left=.16, right=.97, top=.80, bottom=.24, wspace=.44)
    fig.savefig(figures / "q1_baseline_and_missingness.png", dpi=300)
    fig.savefig(figures / "q1_baseline_and_missingness.svg")
    plt.close(fig)

    combined = pd.concat([base.loc[["mean", "ridge", "extra_trees"]], robust.l
oc[["ridge_winsor"]]])
    rows = "\n".join(f"| {name} | {row.mae:.4f} | {row.rmse:.4f} | {row.macro_
r2:.4f} |"
                     for name, row in combined.iterrows())
    gain = (1 - base.loc["extra_trees", "rmse"] / base.loc["mean", "rmse"]) *
100
    stress = (base.loc["extra_trees_mask20", "rmse"] / base.loc["extra_trees",
 "rmse"] - 1) * 100
    weak = tree_targets[tree_targets.macro_r2 < .05].sort_values("macro_r2")
    weak_text = ", ".join(f"{r.target} ({r.macro_r2:.3f})" for r in weak.itert
uples())
    text = f"""# A题首轮阶段结果

更新日期：2026-10-23。本文件保存开题与首轮实验的历史结果；第三问后续实验见 [第三问结果](q3_
results.md)。

## 已确认的数据口径

- 250 款啤酒、231 个化学/理化特征，22 个风格；建模以 `beer` 一对一合并。
- 45 维 Aroma/Flavour = Aroma 15 + Taste 30；4.csv 另有 4 个 Palate 和 1 个 Overa
ll 项。
- 3.xlsx 是 12 张空白评分卡。4.csv 是品评员标准化后聚合的连续标签。现有附件及已检查的作者
公开包中，尚未识别出恢复真实 0–6 分所需的原始评分/参数。
- 2/5/6.csv 的矩阵均可由 Spearman 重现。全样本相关矩阵不能直接用作预测交叉验证的折外先验。
- 37 个基础指标的 log10 关系已实测；其余 GCMS 字段不能统一逆对数得到浓度。完整证据见 `dat
a_audit.md` 和 `sensory_mapping_review.md`。

## 第一问：连续感官预测基线

所有指标均在附件既有连续尺度上计算。外层 5 折，岭回归内层 4 折选择正则强度；中位数补值、X/Y
标准化及稳健裁剪均只拟合训练折。`beer/beer_id/风格` 没有进入预测特征。ExtraTrees 使用固定
参数，未用外层结果调参。

| 模型 | MAE | RMSE | 宏平均 R² |
|---|---:|---:|---:|
{rows}

```

ExtraTrees 的 RMSE 比均值基线降低 **{gain:.2f}%**。附加随机遮蔽20%测试特征时，RMSE 为 **{base.loc['extra_trees_mask20', 'rmse']:.4f}**，较原实验上升 **{stress:.2f}%** 。这只是一次随机缺失压力实验，不代表检出限导致的非随机缺失。

![第一问基线与缺失压力实验](../outputs/figures/q1_baseline_and_missingness.png)

弱预测维度（ExtraTrees R^2<0.05）：{weak_text}。尤其 `stale_hops` 的预测能力很弱，第三问不能凭该模型就宣称实际缺陷已经受到可靠控制。

原岭回归被 beer=156 的极端化合物值严重影响；随机遮蔽20%时恰好隐藏该特征，造成误差降低。不得将其解释为“缺失更多提升模型”。稳健岭回归保留全部250款酒，在每个训练折内部按1%/99%分位裁剪后重跑。此实验由诊断触发、复用原划分，属于探索性稳健性检查，仍需新划分/重复验证。

第二问：网络、Top-3与稳定性

网络含231节点，$|\rho|\geq0.6/0.7/0.8$分别有266/109/39条边。排除汇总和非单一化合物指标后，218候选×45目标共9,810条关联记录，完成200次配对行bootstrap。

135个Top-3位置中，入选频率≥0.8的仅 **{q2['top3_stability']['number_frequency_at_least_0_8']}** 项；平均频率 **{q2['top3_stability']['mean_selection_frequency']:.3f}**。Spearman/Pearson平均Jaccard为 **{q2['mean_jaccard_spearman_pearson']:.3f}**，去风格均值前后为 **{q2['mean_jaccard_global_within_style']:.3f}**，其中 **{q2['targets_with_no_global_within_overlap']}** 个维度完全没有交集。

这些结果表明风格混杂、相关化合物替代和尺度影响需要进一步处理，不能把当前Top-3直接写成因果因素。下一轮应验证模块代表性、风格内分层bootstrap，并逐条核实气味机制。结果见 `../outputs/q2/top3_compounds.csv` 与 `../outputs/q2/README.md`。

第三问：首轮时点的设计方案

首轮拟采用小样本条件收缩Gaussian copula，以目标风格重采样为基线。后续已完成生成与迁移实验，完整结果见 [第三问结果](q3_results.md)。设计要求是对Tripel/Kriek/Lambic做训练折内拟合和留出分布验证，报告边缘距离、联合结构、多样性和最近邻记忆程度。

迁移必须逐项检查DMS/Diacetyl/4VG/trans-2-nonenal/Stale hops。对已知阈值项约束超阈程度不增加；对缺失阈值或未核验变换项另列更强替代约束和不可验证项。Stale hops只有感官代理，当前预测较弱。70个校准字段与其余相对量可以构成混合表示，但必须用同一表示重训感官模型，不能直接塞进本轮模型。详细公式与验证方案见 `q2_q3_design_review.md`。

下一轮优先顺序

1. 明确0–6评分的可识别性边界；取得原始评分/校准数据，或有依据地声明相对等级的定义，分别验证连续值与等级误差。
2. 在新划分或重复交叉验证中比较ExtraTrees与稳健线性模型，加入与现有/未见风格相匹配的验证，评估维度级不确定性和弱缺陷目标。
3. 改善第二问的风格混杂与模块解释，完成化学机制文献核验。
4. 实现第三问并报告有效迁移与失败案例，随后整理完整论文和支撑材料。

来源与复现

原始附件保持原样，哈希记录在 `../outputs/audit/source_files.csv`。一键复现命令及文件索引见 `../README.md`。官方原研究为 [Schreurs等，Nature Communications 15,2368 (2024)](https://doi.org/10.1038/s41467-024-46346-0)，公开数据见 [Zenodo 10653704](https://zenodo.org/records/10653704)。来源对应核验详情已记录于感官映射报告。
"""
    (SOLUTION / "docs/stage1_results.md").write_text(text, encoding="utf-8", newline="\n")
    print(f"Saved {figures / 'q1_baseline_and_missingness.png'} and docs/stage1_results.md")

if __name__ == "__main__":

```
131     main()
```

src/05_verify_outputs.py

SHA-256: 34ba31074ee8d2133c5d57dda035e9d14ea5726396991e8ca04d99cc96980810

```
"""Check provenance, sample alignment, saved metrics and graph invariants.

These checks assess numerical consistency and saved-output integrity.
"""
import hashlib
import json
from pathlib import Path

import joblib
import numpy as np
import pandas as pd
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score

from common import SOLUTION, data_dir, load_xy


def main(output_path=None):
    checks = []
    meta, x, y = load_xy()
    sources = pd.read_csv(SOLUTION / "outputs/audit/source_files.csv")
    for row in sources.itertuples():
        actual = hashlib.sha256((data_dir() / row.source).read_bytes()).hexdig
est()
        assert actual == row.sha256, f"Source changed: {row.source}"
    checks.append(f"Original source SHA-256 unchanged: {len(sources)} files")

    reference_fold = None
    models_checked = 0
    for directory in ["q1", "q1_robust"]:
        folder = SOLUTION / "outputs" / directory
        metrics = pd.read_csv(folder / "metrics_overall.csv")
        for row in metrics.itertuples():
            oof = pd.read_csv(folder / f"oof_{row.model}.csv")
            assert oof.beer.is_unique and oof.beer.tolist() == meta.beer.tolis
t()
            assert (oof.tasting_category_fine == meta.tasting_category_fine).a
ll()
            assert set(oof.fold) == set(range(1, 6))
            if reference_fold is None:
                reference_fold = oof.fold.to_numpy()
            np.testing.assert_array_equal(oof.fold, reference_fold)
            prediction = oof[y.columns].to_numpy()
            assert np.isfinite(prediction).all()
            np.testing.assert_allclose(
                [row.mae, row.rmse, row.macro_r2],
                [mean_absolute_error(y, prediction),
                 np.sqrt(mean_squared_error(y, prediction)),
                 r2_score(y, prediction, multioutput="uniform_average")],
                rtol=1e-10, atol=1e-12,
            )
            models_checked += 1
    checks.append(f"Sample alignment, folds and independently recomputed metri
cs: {models_checked} OOF tables")

    naive = pd.read_csv(SOLUTION / "outputs/q1/oof_mean.csv")
    for fold in range(1, 6):
        test = reference_fold == fold
        expected = np.tile(y.loc[~test].mean().to_numpy(), (test.sum(), 1))
        np.testing.assert_allclose(naive.loc[test, y.columns], expected, atol=
```

```
1e-12)
    checks.append("Mean baseline equals the training-fold target mean for ever
y held-out beer")

    bounds = pd.read_csv(SOLUTION / "outputs/q1_robust/clipping_bounds.csv")
    for fold in range(1, 6):
        stored = bounds[bounds.fold == fold].set_index("feature").loc[x.column
s]
        actual = np.nanquantile(x.loc[reference_fold != fold], [.01, .99], axi
s=0)
        np.testing.assert_allclose(stored[["train_lower_01", "train_upper_99"]
].to_numpy().T,
                                   actual, rtol=1e-10, atol=1e-12)
    checks.append("Saved outer-fold clipping bounds match only the correspondi
ng training rows")

    for filename in ["q1/ridge_model.joblib", "q1/extra_trees_model.joblib",
                     "q1_robust/ridge_winsor_model.joblib"]:
        saved = joblib.load(SOLUTION / "outputs" / filename)
        assert saved["features"] == x.columns.tolist() and saved["targets"] ==
 y.columns.tolist()
        prediction = saved["pipeline"].predict(x.iloc[:2])
        assert prediction.shape == (2, 45) and np.isfinite(prediction).all()
    checks.append("All three saved models reload and predict using the recorde
d feature/target order")

    q2 = SOLUTION / "outputs/q2"
    all_scores = pd.read_csv(q2 / "all_candidate_stability.csv")
    top = pd.read_csv(q2 / "top3_compounds.csv")
    nodes = pd.read_csv(q2 / "network_nodes.csv")
    summary = json.loads((q2 / "summary.json").read_text(encoding="utf-8"))
    assert len(all_scores) == 218 * 45 and len(top) == 3 * 45 and len(nodes) =
= 231
    assert not all_scores.duplicated(["sensory_target", "compound"]).any()
    assert (top.groupby("sensory_target").size() == 3).all()
    np.testing.assert_allclose(all_scores.groupby("sensory_target").bootstrap_
top3_frequency.sum(), 3)
    assert all_scores.bootstrap_top3_frequency.between(0, 1).all()
    assert (all_scores.bootstrap_valid_draws == summary["bootstrap_draws"]).al
l()
    for threshold in [.6, .7, .8]:
        edges = pd.read_csv(q2 / f"network_edges_rho_{threshold:.1f}.csv")
        assert not (edges.source == edges.target).any()
        assert not edges.duplicated(["source", "target"]).any()
        assert (edges.absolute_weight >= threshold - 1e-10).all()
        assert int(nodes[f"degree_{threshold:.1f}"].sum()) == 2 * len(edges)
    checks.append("Q2 candidate counts, bootstrap frequencies and undirected g
raph degree sums reconcile")

    for path in ["docs/stage1_results.md", "docs/data_audit.md", "docs/sensory
_mapping_review.md",
                 "docs/q1_validation_review.md", "docs/q2_q3_design_review.md"
,
                 "outputs/figures/q1_baseline_and_missingness.png", "README.md
"]:
        assert (SOLUTION / path).is_file(), f"Missing deliverable: {path}"
    checks.append("Stage notes, independent review and chart files exist")
    result = {"status": "passed", "checks": checks,
              "scope": "Saved-output integrity and numerical consistency; not
proof of model adequacy"}
    if output_path is not None:
        output_path = Path(output_path)
```

```
        output_path.parent.mkdir(parents=True, exist_ok=True)
        output_path.write_text(json.dumps(result, ensure_ascii=False, indent=2) + "\n", encoding="utf-8", newline="\n")
    print(json.dumps(result, ensure_ascii=False, indent=2))


if __name__ == "__main__":
    import argparse
    parser = argparse.ArgumentParser(description=__doc__)
    parser.add_argument("--output", type=Path, help="Optional report path; existing results are read-only by default.")
    main(parser.parse_args().output)
```

src/06_q3_sensory.py

SHA-256: d4e7e5cc71284e24318acffa44983de164adef4a2c24523606ed20d1dcbc78d9

```
"""Train and validate the hybrid-representation sensory proxy for question 3.

Predictions are attachment-standardized values, not recovered 0--6 scores.
Bootstrap paired differences constrain a fitted proxy, not actual taste.
"""
from __future__ import annotations

import json
import platform
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
import sklearn
from scipy.stats import spearmanr
from sklearn.ensemble import ExtraTreesRegressor
from sklearn.impute import SimpleImputer
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.model_selection import KFold
from sklearn.pipeline import Pipeline
from threadpoolctl import threadpool_limits

from common import SEED, SOLUTION
from q3_data import DEFECTS, load_q3_data

OUT = SOLUTION / "outputs" / "q3" / "sensory"
N_BOOTSTRAP = 40
BOOTSTRAP_TREES = 120


def tree_pipeline(seed: int, n_estimators: int = 300) -> Pipeline:
    return Pipeline([
        ("imputer", SimpleImputer(strategy="median", add_indicator=True,
                                  keep_empty_features=True)),
        ("model", ExtraTreesRegressor(
            n_estimators=n_estimators, min_samples_leaf=3, max_features=0.7,
            random_state=seed, n_jobs=1)),
    ])


def scores(y, pred) -> dict:
    return {
        "mae": float(mean_absolute_error(y, pred)),
        "rmse": float(np.sqrt(mean_squared_error(y, pred))),
        "macro_r2": float(r2_score(y, pred, multioutput="uniform_average")),
    }


def main() -> None:
    started = perf_counter()
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y, manifest = load_q3_data()
    # Input artifacts preserve missingness; imputation is fitted by each model
.
    meta.to_csv(OUT / "meta.csv", index=False, lineterminator="\n")
    x.to_csv(OUT / "hybrid_features.csv", index=False, lineterminator="\n")
    y.to_csv(OUT / "y45.csv", index=False, lineterminator="\n")
    manifest.to_csv(OUT / "feature_manifest.csv", index=False, lineterminator=
```

```
"\n")
    (OUT / "defect_thresholds.json").write_text(
        json.dumps(DEFECTS, ensure_ascii=False, indent=2, allow_nan=False), en
coding="utf-8", newline="\n")

    predictions = {name: np.full(y.shape, np.nan) for name in ("mean", "extra_
trees")}
    fold_ids = np.zeros(len(x), dtype=int)
    fold_metrics = []
    for fold, (train, test) in enumerate(
            KFold(5, shuffle=True, random_state=SEED).split(x), 1):
        fold_ids[test] = fold
        model = tree_pipeline(SEED + fold).fit(x.iloc[train], y.iloc[train])
        predictions["extra_trees"][test] = model.predict(x.iloc[test])
        predictions["mean"][test] = y.iloc[train].mean().to_numpy()
        for name, values in predictions.items():
            fold_metrics.append({"fold": fold, "model": name, "train_n": len(t
rain),
                                 "test_n": len(test), **scores(y.iloc[test], v
alues[test])})
        print(f"Q3 sensory OOF fold {fold}/5: "
              f"RMSE={scores(y.iloc[test], predictions['extra_trees'][test])['
rmse']:.6f}", flush=True)

    metric_rows, target_rows = [], []
    for name, values in predictions.items():
        if not np.isfinite(values).all():
            raise AssertionError(f"Incomplete OOF predictions: {name}")
        metric_rows.append({"model": name, **scores(y, values)})
        for j, target in enumerate(y):
            target_rows.append({"model": name, "target": target,
                                **scores(y.iloc[:, j], values[:, j]),
                                "spearman": float(spearmanr(y.iloc[:, j], valu
es[:, j]).statistic)})
        pd.concat([meta, pd.DataFrame({"fold": fold_ids}),
                   pd.DataFrame(values, columns=y.columns)], axis=1).to_csv(
                       OUT / f"oof_{name}.csv", index=False, lineterminator="\
n")
    pd.DataFrame(metric_rows).to_csv(OUT / "metrics_overall.csv", index=False,
 lineterminator="\n")
    pd.DataFrame(target_rows).to_csv(OUT / "metrics_by_target.csv", index=Fals
e, lineterminator="\n")
    pd.DataFrame(fold_metrics).to_csv(OUT / "metrics_by_fold.csv", index=False
, lineterminator="\n")
    pd.concat([meta, y], axis=1).to_csv(OUT / "observed_standardized.csv", ind
ex=False, lineterminator="\n")

    # A full-data inference model is distinct from held-out evaluation above.
    final = tree_pipeline(SEED + 99).fit(x, y)
    artifact = {"pipeline": final, "features": x.columns.tolist(),
                "targets": y.columns.tolist(), "target_scale": "attachment_4_s
tandardized",
                "representation": "69_calibrated_plus_157_relative", "seed": S
EED}
    joblib.dump(artifact, OUT / "sensory_model.joblib", compress=3)
    pd.concat([meta, pd.DataFrame(final.predict(x), columns=y.columns)], axis=
1).to_csv(
        OUT / "fitted_standardized_NOT_validation.csv", index=False, linetermi
nator="\n")

    # Migration sources must not appear in their own proxy's training set.
    source_mask = meta["tasting_category_fine"].eq("Pils/Lager").to_numpy()
```

```
    transfer_train = np.flatnonzero(~source_mask)
    transfer_test = np.flatnonzero(source_mask)
    if (len(transfer_train), len(transfer_test)) != (239, 11):
        raise ValueError("Expected 239 non-Pils training samples and 11 held-o
ut sources")
    transfer_model = tree_pipeline(SEED + 199).fit(x.iloc[transfer_train], y.i
loc[transfer_train])
    transfer_artifact = {
        "pipeline": transfer_model, "features": x.columns.tolist(), "targets":
 y.columns.tolist(),
        "target_scale": "attachment_4_standardized", "representation": "69_cal
ibrated_plus_157_relative",
        "seed": SEED, "excluded_style": "Pils/Lager", "train_global_indices":
transfer_train,
        "heldout_global_indices": transfer_test, "source_exclusion_reason": "p
revent_source_memorization",
    }
    joblib.dump(transfer_artifact, OUT / "transfer_proxy.joblib", compress=3)
    heldout_pred = transfer_model.predict(x.iloc[transfer_test])
    heldout_mean = np.broadcast_to(y.iloc[transfer_train].mean().to_numpy(), h
eldout_pred.shape)
    heldout_metrics, heldout_targets = [], []
    for name, values in [("transfer_proxy", heldout_pred), ("non_pils_mean", h
eldout_mean)]:
        heldout_metrics.append({"model": name, "test_n": len(transfer_test),
                                **scores(y.iloc[transfer_test], values)})
        for j, target in enumerate(y):
            heldout_targets.append({"model": name, "target": target,
                                    **scores(y.iloc[transfer_test, j], values[
:, j])})
    pd.concat([meta.iloc[transfer_test].reset_index(drop=True),
               pd.DataFrame(heldout_pred, columns=y.columns)], axis=1).to_csv(
                   OUT / "transfer_pils_heldout_predictions.csv", index=False,
 lineterminator="\n")
    pd.concat([meta.iloc[transfer_test].reset_index(drop=True),
               y.iloc[transfer_test].reset_index(drop=True)], axis=1).to_csv(
                   OUT / "transfer_pils_heldout_observed.csv", index=False, li
neterminator="\n")
    pd.DataFrame(heldout_metrics).to_csv(OUT / "transfer_pils_heldout_metrics.
csv", index=False, lineterminator="\n")
    pd.DataFrame(heldout_targets).to_csv(OUT / "transfer_pils_heldout_metrics_
by_target.csv", index=False, lineterminator="\n")

    # Row-paired bootstrap: one fitted model predicts BOTH source and candidat
e.
    # Every Pils/Lager source is excluded. Save global resample positions so
    # exclusion and the train/select-audit split can be independently checked.
    rng = np.random.default_rng(SEED + 2000)
    models, indices = [], []
    for b in range(N_BOOTSTRAP):
        index = rng.choice(transfer_train, size=len(transfer_train), replace=T
rue)
        fitted = tree_pipeline(SEED + 3000 + b, BOOTSTRAP_TREES).fit(
            x.iloc[index], y["stale_hops"].iloc[index])
        models.append(fitted)
        indices.append(index)
        if (b + 1) % 10 == 0:
            print(f"Q3 stale_hops bootstrap {b + 1}/{N_BOOTSTRAP}", flush=True
)
    bootstrap = {"models": models, "bootstrap_indices": indices,
                 "features": x.columns.tolist(), "target": "stale_hops",
                 "target_scale": "attachment_4_standardized", "seed": SEED,
```

```
                  "bootstrap_seed": SEED + 2000, "paired_quantile": 0.95,
                  "pairing": "same_model_source_candidate_difference",
                  "train_global_indices": transfer_train,
                  "excluded_global_indices": transfer_test,
                  "excluded_style": "Pils/Lager",
                  "selection_model_indices": list(range(30)),
                  "audit_model_indices": list(range(30, N_BOOTSTRAP)),
                  "audit_protocol": "screen_with_first_30; audit_last_10_once_without_reselection",
                  "interpretation": "model_proxy_uncertainty_only_not_taste_guarantee"}
    joblib.dump(bootstrap, OUT / "stale_bootstrap.joblib", compress=3)
    np.savez_compressed(OUT / "stale_bootstrap_indices.npz", indices=np.asarray(indices),
                        source_beer=meta["beer"].to_numpy())
    bootstrap_predictions = np.vstack([model.predict(x) for model in models])
    pd.concat([meta, pd.DataFrame({
        "bootstrap_mean": bootstrap_predictions.mean(axis=0),
        "bootstrap_q025": np.quantile(bootstrap_predictions, 0.025, axis=0),
        "bootstrap_q975": np.quantile(bootstrap_predictions, 0.975, axis=0),
        "observed_stale_hops": y["stale_hops"],
    })], axis=1).to_csv(OUT / "stale_bootstrap_fitted_NOT_validation.csv", index=False, lineterminator="\n")

    # Reuse of the established Q1 folds is explicitly checked if available.
    reference_path = SOLUTION / "outputs" / "q1" / "oof_extra_trees.csv"
    identical_q1_folds = None
    if reference_path.exists():
        reference = pd.read_csv(reference_path)
        identical_q1_folds = bool(np.array_equal(reference["beer"], meta["beer"])
                                  and np.array_equal(reference["fold"], fold_ids))
        if not identical_q1_folds:
            raise AssertionError("Q3 OOF does not match existing Q1 folds")
    overall = pd.DataFrame(metric_rows).set_index("model")
    stale = [row for row in target_rows if row["target"] == "stale_hops"]
    summary = {
        "seed": SEED, "samples": len(x), "features": x.shape[1], "targets": y.shape[1],
        "representation_counts": manifest["representation"].value_counts().to_dict(),
        "calibrated_negatives_invalidated": int(manifest["negative_invalid_count"].sum()),
        "hybrid_missing_values": int(x.isna().sum().sum()),
        "validation": "fixed 5-fold shuffled KFold shared with Q1; fold-local median imputation",
        "identical_q1_folds": identical_q1_folds,
        "parameters": {"n_estimators": 300, "min_samples_leaf": 3, "max_features": 0.7,
                       "n_jobs": 1, "imputer": "median_with_missing_indicator"},
        "metrics": metric_rows, "stale_hops_metrics": stale,
        "rmse_reduction_vs_mean": float(1 - overall.loc["extra_trees", "rmse"] /
                                        overall.loc["mean", "rmse"]),
        "bootstrap": {"repeats": N_BOOTSTRAP, "n_estimators": BOOTSTRAP_TREES,
                      "target": "stale_hops", "row_resampling": "paired X/y iid with replacement",
                      "population": "239 non-Pils/Lager samples; all 11 Pils sources excluded",
                      "selection_models": 30, "independent_audit_models": 10,
```

```
                        "audit_protocol": "no reselection after audit",
                        "paired_difference_quantile": 0.95,
                        "coverage_calibrated": False,
                        "audit": "stale_bootstrap_indices.npz and saved bootstrap_indices"},
        "transfer_proxy": {"train_n": len(transfer_train), "heldout_n": len(transfer_test),
                           "excluded_style": "Pils/Lager", "metrics": heldout_metrics,
                           "stale_hops_metrics": [row for row in heldout_targets
                                                  if row["target"] == "stale_hops"],
                           "limitations": "11 held-out sources in one style; not a calibrated transfer test"},
        "defect_thresholds": DEFECTS,
        "limitations": [
            "Targets are attachment-standardized sensory values, not original 0-6 scores.",
            "Random folds assess new samples in the observed style mixture, not unseen-style transfer.",
            "Attachment-level preprocessing and calibration cannot be re-estimated within folds.",
            "Optimization candidates may be out of distribution despite passing chemical constraints.",
            "Stale hops no-increase is a model-proxy constraint, not an actual tasting guarantee.",
            "40 iid row bootstrap models give descriptive paired-model uncertainty; the upper 95% "
            "quantile has neither calibrated coverage nor a physical causal interpretation.",
            "Full-data fitted predictions and bootstrap fitted bands are not validation.",
        ],
        "versions": {"python": platform.python_version(), "numpy": np.__version__,
                     "pandas": pd.__version__, "sklearn": sklearn.__version__},
        "elapsed_seconds": perf_counter() - started,
    }
    (OUT / "summary.json").write_text(
        json.dumps(summary, ensure_ascii=False, indent=2, allow_nan=False), encoding="utf-8", newline="\n")
    print(pd.DataFrame(metric_rows).to_string(index=False), flush=True)
    print("stale_hops:", json.dumps(stale, ensure_ascii=False), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/07_q3_generation.py

SHA-256: 32ad2b7003ef0525a4cdd5d722f3713697d9fa59a3eed5a82555060e80bc166e

```
"""Run Q3 generation using fixed hyperparameters and repeated held-out validation."""
import os

for _thread_variable in ("OPENBLAS_NUM_THREADS", "OMP_NUM_THREADS", "MKL_NUM_THREADS",
                         "VECLIB_MAXIMUM_THREADS", "NUMEXPR_NUM_THREADS"):
    os.environ[_thread_variable] = "1"

import json
from pathlib import Path
import time

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist, pdist
from scipy.stats import rankdata, wasserstein_distance
from sklearn.decomposition import PCA
from sklearn.model_selection import StratifiedKFold
from threadpoolctl import threadpool_limits

from common import SEED, SOLUTION
from q3_copula import ConditionalGaussianCopula
from q3_data import load_q3_data


OUT = SOLUTION / "outputs" / "q3" / "generation"
STYLES = ["Tripel", "Kriek", "Lambic", "Pils/Lager"]
MAIN_PARAMS = (5.0, 20.0)
SENSITIVITY_PARAMS = [(2.0, 5.0), MAIN_PARAMS, (10.0, 50.0)]
REPEAT_SEEDS = [SEED, SEED + 1000]
N_GENERATED = 300
MC_REPEATS = 3
METRICS = ["marginal_w1_iqr", "marginal_w1_iqr_median", "energy_pca5", "spearman_mae",
           "generated_nn_style_median", "holdout_nn_style_median", "nn_ratio",
           "copy_rate", "unique_fraction", "variance_ratio_median",
           "variance_coverage_0p5_2", "style_training_range_fraction"]


def safe_style(style):
    return style.replace("/", "-")


def training_scale(values):
    iqr = np.subtract(*np.percentile(values, [75, 25], axis=0))
    span = np.ptp(values, axis=0)
    scale = np.where(iqr > 1e-12, iqr, np.where(span > 1e-12, span, 1.0))
    return scale, np.where(iqr > 1e-12, "iqr", np.where(span > 1e-12, "range", "one"))


def pca_coordinates(model, x_train):
    z = model.transform(x_train)
    pca = PCA(n_components=min(5, len(z) - 1, z.shape[1]), svd_solver="full").fit(z)
    # Each component is measured in its training standard deviation.
    scale = np.maximum(np.sqrt(pca.explained_variance_), 1e-8)
```

```
    return pca, scale


def energy_distance(a, b):
    # Empirical V-statistic; biased upward at tiny held-out n, but same real
    # rows and same generated n are used for every comparison.
    return float(2 * cdist(a, b).mean() - cdist(a, a).mean() - cdist(b, b).mea
n())


def rank_correlation(values):
    ranks = rankdata(values, axis=0)
    ranks -= ranks.mean(axis=0)
    norms = np.sqrt(np.sum(ranks ** 2, axis=0))
    standardized = np.divide(ranks, norms, out=np.zeros_like(ranks), where=nor
ms > 0)
    return standardized.T @ standardized


def evaluate(model, x_train, style_train, heldout, generated, pca, pc_scale):
    training = model.impute(x_train)
    reference = model.impute(style_train)
    real = model.impute(heldout)
    fake = model.impute(generated)
    scale, _ = training_scale(training)
    marginal = np.array([wasserstein_distance(real[:, j], fake[:, j]) / scale[
j]
                         for j in range(real.shape[1])])
    real_z, fake_z = model.transform(heldout), model.transform(generated)
    reference_z = model.transform(style_train)
    real_pc = pca.transform(real_z) / pc_scale
    fake_pc = pca.transform(fake_z) / pc_scale
    nn_generated = cdist(fake_z, reference_z).min(axis=1) / np.sqrt(real.shape
[1])
    nn_real = cdist(real_z, reference_z).min(axis=1) / np.sqrt(real.shape[1])
    valid_corr = (np.ptp(real, axis=0) > 1e-12) & (np.ptp(reference, axis=0) >
 1e-12)
    if valid_corr.sum() > 1:
        real_corr = rank_correlation(real[:, valid_corr])
        fake_corr = rank_correlation(fake[:, valid_corr])
        upper = np.triu_indices(len(real_corr), k=1)
        corr_error = float(np.mean(np.abs(real_corr[upper] - fake_corr[upper])
))
    else:
        corr_error = float("nan")
    reference_var = np.var(reference, axis=0, ddof=1)
    fake_var = np.var(fake, axis=0, ddof=1)
    variable = reference_var > 1e-20
    ratios = fake_var[variable] / reference_var[variable]
    return {
        "marginal_w1_iqr": float(marginal.mean()),
        "marginal_w1_iqr_median": float(np.median(marginal)),
        "energy_pca5": energy_distance(real_pc, fake_pc),
        "spearman_mae": corr_error,
        "correlation_features": int(valid_corr.sum()),
        "generated_nn_style_median": float(np.median(nn_generated)),
        "holdout_nn_style_median": float(np.median(nn_real)),
        "nn_ratio": float(np.median(nn_generated) / max(np.median(nn_real), 1e
-12)),
        "copy_rate": float(np.mean(nn_generated < 1e-12)),
        "unique_fraction": float(len(np.unique(fake, axis=0)) / len(fake)),
        "variance_ratio_median": float(np.median(ratios)),
```

```
        "variance_coverage_0p5_2": float(np.mean((ratios >= 0.5) & (ratios <=
2))),
        "variance_reference_features": int(variable.sum()),
        "style_training_range_fraction": float(np.mean(
            (fake >= reference.min(axis=0)) & (fake <= reference.max(axis=0)))
),
    }, marginal


def summarize_validation(records):
    # First average Monte Carlo replicates so one data split is one unit in
    # the descriptive fold SD. Repeated folds are dependent: this is not a CI.
    fold = records.groupby(["repeat", "fold", "style", "method"], as_index=Fal
se)[METRICS].mean()
    summary = fold.groupby(["style", "method"])[METRICS].agg(["mean", "std"])
    summary.columns = [f"{metric}_{stat}" for metric, stat in summary.columns]
    return fold, summary.reset_index()


def run_validation(x, styles):
    records, sensitivity, assignments, marginal_records, support_records = [],
 [], [], [], []
    for repeat, split_seed in enumerate(REPEAT_SEEDS, start=1):
        splitter = StratifiedKFold(n_splits=3, shuffle=True, random_state=spli
t_seed)
        for fold, (train, test) in enumerate(splitter.split(x, styles), start=
1):
            print(f"Generation validation repeat={repeat}, fold={fold}", flush
=True)
            x_train = x.iloc[train]
            train_styles = styles.iloc[train]
            x_test = x.iloc[test]
            test_styles = styles.iloc[test]
            assignments.extend({"repeat": repeat, "fold": fold, "row_index": i
nt(i),
                                "role": "test", "style": str(styles.iloc[i])}
for i in test)
            for mean_strength, cov_strength in SENSITIVITY_PARAMS:
                model = ConditionalGaussianCopula(mean_strength, cov_strength)
.fit(x_train, train_styles)
                pca, pc_scale = pca_coordinates(model, x_train)
                main = (mean_strength, cov_strength) == MAIN_PARAMS
                for style_index, style in enumerate(STYLES):
                    style_train = x_train.loc[train_styles == style]
                    heldout = x_test.loc[test_styles == style]
                    if len(heldout) == 0:
                        raise AssertionError(f"Missing evaluation style {style
}")
                    if main:
                        heldout_latent = model.transform(heldout)
                        train_latent = model.transform(style_train)
                        near = cdist(heldout_latent, train_latent).min(axis=1)
 / np.sqrt(x.shape[1])
                        latent_distance = model.distance(heldout, style)
                        support_records.extend({"repeat": repeat, "fold": fold
,
                            "row_index": int(i), "style": style,
                            "latent_distance": float(distance), "nn_train_styl
e": float(nn)}
                            for i, distance, nn in zip(heldout.index, latent_d
istance, near))
                    mc_count = MC_REPEATS if main else 1
```

```
                    for mc in range(mc_count):
                        sample_seed = split_seed + fold * 10000 + style_index * 100 + mc
                        draws = {"conditional_copula": model.sample(style, N_GENERATED, sample_seed)}
                        if main:
                            indices = np.random.default_rng(sample_seed).integers(0, len(style_train), N_GENERATED)
                            draws["style_bootstrap"] = pd.DataFrame(
                                model.impute(style_train)[indices], columns=x.columns)
                            draws["unconditional_copula"] = model.sample(None, N_GENERATED, sample_seed)
                        for method, generated in draws.items():
                            metrics, marginal = evaluate(model, x_train, style_train, heldout,
                                                         generated, pca, pc_scale)
                            record = {"repeat": repeat, "fold": fold, "mc": mc,
                                      "split_seed": split_seed, "sample_seed": sample_seed,
                                      "style": style, "method": method,
                                      "train_n": len(x_train), "style_train_n": len(style_train),
                                      "holdout_style_n": len(heldout), "generated_n": len(generated),
                                      "mean_strength": mean_strength, "cov_strength": cov_strength,
                                      **metrics}
                            if main:
                                records.append(record)
                                if mc == 0:
                                    marginal_records.extend({"repeat": repeat, "fold": fold,
                                                             "style": style, "method": method, "feature": feature,
                                                             "w1_iqr": float(value)}
                                                            for feature, value in zip(x.columns, marginal))
                            else:
                                sensitivity.append(record)
    return (pd.DataFrame(records), pd.DataFrame(sensitivity),
            pd.DataFrame(assignments), pd.DataFrame(marginal_records), pd.DataFrame(support_records))


def support_diagnostics(model, x, labels):
    z = model.transform(x)
    rows, thresholds = [], []
    for style in sorted(labels.unique()):
        indices = np.flatnonzero(np.asarray(labels) == style)
        style_x = x.iloc[indices]
        distances = model.distance(style_x, style)
        pairwise = cdist(z[indices], z[indices]) / np.sqrt(z.shape[1])
        np.fill_diagonal(pairwise, np.inf)
        nn = pairwise.min(axis=1)
        rows.extend({"row_index": int(i), "style": style,
                     "latent_distance": float(distance),
                     "leave_one_out_nn_style": float(near)}
                    for i, distance, near in zip(indices, distances, nn))
        thresholds.append({"style": style, "n": len(indices),
```

```
            "latent_distance_q50": float(np.quantile(distances, 0.5)),
            "latent_distance_q95": float(np.quantile(distances, 0.95)),
            "latent_distance_max": float(distances.max()),
            "loo_nn_style_q50": float(np.quantile(nn, 0.5)),
            "loo_nn_style_q95": float(np.quantile(nn, 0.95)),
            "loo_nn_style_max": float(nn.max()),
            "calibration": "full_fit_in_sample_style_distance_and_loo_nn_descr
iptive"})
    return pd.DataFrame(rows), pd.DataFrame(thresholds)


def generated_diagnostics(model, generated, style, x, labels, support, cv_supp
ort):
    fake_z, all_z = model.transform(generated), model.transform(x)
    target_z = all_z[np.asarray(labels) == style]
    all_nn = cdist(fake_z, all_z).min(axis=1) / np.sqrt(fake_z.shape[1])
    target_nn = cdist(fake_z, target_z).min(axis=1) / np.sqrt(fake_z.shape[1])
    distances = model.distance(generated, style)
    thresholds = support.set_index("style").loc[style]
    cv_thresholds = cv_support.set_index("style").loc[style]
    return pd.DataFrame({"sample_id": np.arange(1, len(generated) + 1), "style
": style,
        "latent_distance": distances, "nn_all": all_nn, "nn_target_style": tar
get_nn,
        "exact_training_copy": all_nn < 1e-12,
        "within_latent_style_q95": distances <= thresholds.latent_distance_q95
,
        "within_loo_nn_style_q95": target_nn <= thresholds.loo_nn_style_q95,
        "within_cv_latent_style_q95": distances <= cv_thresholds.latent_distan
ce_q95,
        "within_cv_nn_style_q95": target_nn <= cv_thresholds.nn_train_style_q9
5})


def write_report(summary, sensitivity, full_diagnostics, support, elapsed, x,
labels):
    lines = [
        "# 第三问：风格条件生成运行报告", "",
        "运行日期：2026-10-23。", "",
        "## 数据、模型与固定参数", "",
        f"使用 {len(x)} 款啤酒、{x.shape[1]} 个混合表示特征及 {labels.nunique()} 个
风格。"
        "其中 69 个字段使用附件校准值，157 个使用原文件相对表示；去除 5 个派生汇总列。"
        "负校准值视为缺失，保留真实零，按训练折中位数补缺。原始附件不作修改。", "",
        "逐列用训练经验分布中秩映射到正态潜在空间。风格均值以 n/(n+5) 向全局均值收缩；"
        "协方差以 n/(n+20) 混合风格 Ledoit-Wolf 协方差与全体训练样本去风格均值后的 "
        "Ledoit-Wolf 共享协方差，另加微小对角项以保证正定。固定参数 (5,20) 在查看验证结
果前声明，"
        "不以外层验证选择参数。用 (2,5) 与 (10,50) 单独做敏感性比较。", "",
        "生成逆映射采用离散经验逆分布，单列取值来自补缺后的训练支持；零及检出限在逆分布中拥
有"
        "非零宽度的概率区间。条件潜在分布及高斯近似会改变实际生成的零频率，"
        "不保证它精确等于全局或目标风格的经验零频率；差异另存 `generated_zero_diagnosti
cs.csv`。"
        "新颖性来自不同列的新组合。连续潜在高斯模型仍只是对点质量依赖关系的近似。"
        "该方法输出化学目标谱，未包含配料、温度、时间或发酵控制，因此不构成可执行酿造配方。"
, "",
        "## 无泄漏验证与结果", "",
        "对全部 22 个风格做 2 次独立随机种子的分层 3 折划分，逐折重拟合补缺、经验分布、"
        "风格中心和协方差；评价 Tripel、Kriek、Lambic、Pils/Lager。每法每折 300 个生成
样本，"
        "3 个 Monte Carlo 种子。比较条件 copula、目标风格训练样本 bootstrap、无条件 c
```

```
opula。"
        "下表先平均同折 Monte Carlo 次数，再对 6 个划分取均值；折间标准差见 CSV，"
        "由于折及重复间数据有重叠，该标准差不是独立实验置信区间。", "",
        "|风格|方法|平均边缘 W1↓|边缘W1中位数↓|五维能量距离↓|Spearman差↓|复制率|方差覆盖率|", "|---|---|---:|---:|---:|---:|---:|---:|",
    ]
    method_names = {"conditional_copula": "条件copula", "style_bootstrap": "风格bootstrap",
                    "unconditional_copula": "无条件copula"}
    for _, row in summary.iterrows():
        lines.append(f"|{row['style']}|{method_names[row['method']]}|"
            f"{row['marginal_w1_iqr_mean']:.4f}|{row['marginal_w1_iqr_median_mean']:.4f}|{row['energy_pca5_mean']:.4f}|"
            f"{row['spearman_mae_mean']:.4f}|{row['copy_rate_mean']:.1%}|"
            f"{row['variance_coverage_0p5_2_mean']:.1%}|")
    lines.extend(["", "边缘 W1 以全部训练行各列 IQR 标准化；零 IQR 依次回退训练极差、常数 1。"
        "均值保留了所有极端值的影响，另报跨特征中位数。Kriek 的均值尤其受相对特征 "
        "`X2.methyltetrahydrofuran.3.one` 的极端值支配，因此不能据平均 W1 的单项改善宣称全面优越。"
        "五维能量距离在训练 Gaussian 空间拟合的 PCA 中计算，各轴以训练标准差缩放，"
        "使用经验 V 统计量。Spearman 差为测试及风格训练中均非恒定的列之间相关系数的平均绝对差，"
        "生成恒定列的相关记 0。方差覆盖率为生成方差/目标风格训练方差落在 [0.5,2] 的特征比例，"
        "排除目标训练中恒定列；它衡量风格训练方差再现程度，不代表包含真实总体方差的置信覆盖。", ""])
    for style in STYLES:
        table = summary.loc[summary["style"] == style].set_index("method")
        cond = table.loc["conditional_copula"]
        boot = table.loc["style_bootstrap"]
        uncond = table.loc["unconditional_copula"]
        w1change = (cond.marginal_w1_iqr_mean / boot.marginal_w1_iqr_mean - 1) * 100
        energychange = (cond.energy_pca5_mean / boot.energy_pca5_mean - 1) * 100
        lines.append(f"- {style}：条件模型相对风格 bootstrap 的边缘 W1 变化 {w1change:+.1f}%，"
                     f"能量距离变化 {energychange:+.1f}%；相对无条件模型能量距离变化 "
                     f"{(cond.energy_pca5_mean / uncond.energy_pca5_mean - 1) * 100:+.1f}%。")
    lines.extend(["", "bootstrap 直接复制风格训练行，复制率 100%，作为高保真但无新颖性的基线；"
        "不得将条件模型在部分指标劣于 bootstrap 的结果删除。300 是每次模拟样本数，"
        "并没有将 Kriek 的 10 款真实样本扩充成 300 个独立证据；Kriek/Lambic/Pils-Lager "
        "每折测试仅约 3–4 款，Tripel 每折约 9–10 款，边缘尾部、相关性与能量距离估计均很不稳定。"
        "尤其相关矩阵有 226 维，其留出比较只作探索性诊断。需要新增真实啤酒及实测品评验证。", "",
        "## 全量拟合生成及支持域", "",
        "在全部数据重新拟合后，为 Tripel、Kriek、Lambic、Pils/Lager 各保存 300 行生成谱；"
        "输出不是折外性能估计。每行另存相对风格中心的正则 Mahalanobis 距离、"
        "到所有/目标风格训练啤酒的 Gaussian 均方根近邻距离、完全复制标记。", "",
        "|风格|完全复制率|距离处于全量训练95%参考内|近邻处于LOO95%参考内|距离处于CV留出95%参考内|", "|---|---:|---:|---:|---:|"])
    for style, rows in full_diagnostics.groupby("style"):
        lines.append(f"|{style}|{rows.exact_training_copy.mean():.1%}|"
                     f"{rows.within_latent_style_q95.mean():.1%}|{rows.within_loo_nn_style_q95.mean():.1%}|"
```

```
                        f"{rows.within_cv_latent_style_q95.mean():.1%}|")
    lines.extend(["", "支持阈值由全量风格样本的拟合距离 95% 分位数及风格内留一近邻距离 95% 分位数构成，"
          "用于跨风格候选的描述性筛选。它们不是覆盖率保证或独立校准阈值；中心和距离使用全量拟合，"
          "小样本阈值有明显不确定性，应同时报告候选的连续距离与是否越界。"
          "本轮全部生成谱都超过全量训练距离95%阈值，反映高维小样本模型的训练内距离明显乐观。"
          "另存折外真实样本距离和 `cv_support_thresholds.csv`，用作较宽的对照参考；"
          "它来自不同折模型，将其用于全量模型候选也没有严格覆盖率保证。"
          "所有阈值版本均保留，避免在看到通过率后隐藏不利诊断。", "",
          "## 参数敏感性与复现", "",
          "敏感性仅用每折相同的第一个 Monte Carlo 种子，比对已预先声明的三对固定参数。"
          "不得把敏感性最好的外层结果重新报告为无偏的调参后精度。", "",
          "|均值收缩强度|协方差收缩强度|平均边缘 W1|平均能量距离|", "|---:|---:|---:|---:|"])
    for _, row in sensitivity.iterrows():
        lines.append(f"|{row.mean_strength:g}|{row.cov_strength:g}|{row.marginal_w1_iqr:.4f}|{row.energy_pca5:.4f}|")
    lines.extend(["", f"本次运行耗时约 {elapsed:.1f} 秒，线性代数线程数固定为 1。",
        "", "```bash", ".venv/bin/python solution_a/src/07_q3_generation.py", "```", "",
        "模型类接口：`ConditionalGaussianCopula(5,20).fit(X, styles)`；"
        "`sample(style,n,seed)` 返回同列顺序 DataFrame；`transform(X)` 返回 Gaussian 潜在矩阵；"
        "`inverse_transform(Z)` 返回离散经验逆映射；`distance(X,style)` 返回按特征数归一的正则 "
        "Mahalanobis 距离。全量模型保存为 `outputs/q3/generation/fitted_model.joblib`。", "",
        "主要输出：`cv_metrics.csv`、`cv_summary.csv`、`cv_fold_means.csv`、`cv_mc_variability.csv`、"
        "`cv_assignments.csv`、`cv_marginal_w1_by_feature.csv`、`sensitivity_metrics.csv`、"
        "`sensitivity_summary.csv`、`generated_*.csv`、`generated_diagnostics.csv`、"
        "`full_style_support_metrics.csv`、`full_style_support_thresholds.csv`、"
        "`cv_holdout_support_metrics.csv`、`cv_support_thresholds.csv`、`generated_zero_diagnostics.csv` 与 `summary.json`。", ""])
    mc_variability = pd.read_csv(OUT / "cv_mc_variability.csv")
    conditional_mc = mc_variability.loc[mc_variability.method == "conditional_copula", "energy_pca5_std"]
    lines.extend(["条件生成能量距离在固定划分内的 3 次 Monte Carlo 标准差："
                  f"中位数 {conditional_mc.median():.4f}，最大值 {conditional_mc.max():.4f}。"
                  "它仅反映有限生成次数的随机波动，不覆盖真实风格样本少带来的估计误差。", ""])
    (SOLUTION / "docs" / "q3_generation.md").write_text("\n".join(lines), encoding="utf-8", newline="\n")


def main():
    start = time.perf_counter()
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, _, _ = load_q3_data()
    labels = meta.tasting_category_fine.reset_index(drop=True)
    x = x.reset_index(drop=True)
    if min(labels.value_counts()) < 3:
        raise ValueError("Repeated 3-fold validation requires at least 3 rows per style")
    records, sensitivity, assignments, marginal, cv_support_rows = run_validation(x, labels)
    records.to_csv(OUT / "cv_metrics.csv", index=False, lineterminator="\n")
```

```
    sensitivity.to_csv(OUT / "sensitivity_metrics.csv", index=False, linetermi
nator="\n")
    assignments.insert(3, "beer", assignments.row_index.map(meta.beer))
    assignments.to_csv(OUT / "cv_assignments.csv", index=False, lineterminator
="\n")
    marginal.to_csv(OUT / "cv_marginal_w1_by_feature.csv", index=False, linete
rminator="\n")
    cv_support_rows.insert(3, "beer", cv_support_rows.row_index.map(meta.beer)
)
    cv_support_rows.to_csv(OUT / "cv_holdout_support_metrics.csv", index=False
, lineterminator="\n")
    cv_support = cv_support_rows.groupby("style").agg(
        reference_rows=("row_index", "size"), unique_beers=("beer", "nunique")
,
        latent_distance_q95=("latent_distance", lambda v: v.quantile(0.95)),
        nn_train_style_q95=("nn_train_style", lambda v: v.quantile(0.95))).res
et_index()
    cv_support["calibration"] = "repeated_3fold_heldout_descriptive_not_formal
_fullfit_coverage"
    cv_support.to_csv(OUT / "cv_support_thresholds.csv", index=False, lineterm
inator="\n")
    mc_variability = records.groupby(["repeat", "fold", "style", "method"])[ME
TRICS].agg(["mean", "std"])
    mc_variability.columns = [f"{metric}_{stat}" for metric, stat in mc_variab
ility.columns]
    mc_variability.reset_index().to_csv(OUT / "cv_mc_variability.csv", index=F
alse, lineterminator="\n")
    folds, summary = summarize_validation(records)
    folds.to_csv(OUT / "cv_fold_means.csv", index=False, lineterminator="\n")
    summary.to_csv(OUT / "cv_summary.csv", index=False, lineterminator="\n")
    sensitivity_all = pd.concat([sensitivity, records.loc[
        (records.method == "conditional_copula") & (records.mc == 0)]], ignore
_index=True)
    sensitivity_summary = sensitivity_all.groupby(["mean_strength", "cov_stren
gth"], as_index=False)[
        ["marginal_w1_iqr", "marginal_w1_iqr_median", "energy_pca5", "spearman
_mae", "copy_rate",
         "variance_coverage_0p5_2"]].mean()
    sensitivity_summary.to_csv(OUT / "sensitivity_summary.csv", index=False, l
ineterminator="\n")
    model = ConditionalGaussianCopula(*MAIN_PARAMS).fit(x, labels)
    joblib.dump(model, OUT / "fitted_model.joblib")
    pd.DataFrame(model.fit_diagnostics_).to_csv(OUT / "fit_diagnostics.csv", i
ndex=False, lineterminator="\n")
    _, scale_source = training_scale(model.impute(x))
    pd.DataFrame({"feature": x.columns, "scaling_source": scale_source,
                  "imputation_median": model.median_}).to_csv(OUT / "full_prep
rocessing.csv", index=False, lineterminator="\n")
    support_rows, support = support_diagnostics(model, x, labels)
    support_rows.insert(1, "beer", support_rows.row_index.map(meta.beer))
    support_rows.to_csv(OUT / "full_style_support_metrics.csv", index=False, l
ineterminator="\n")
    support.to_csv(OUT / "full_style_support_thresholds.csv", index=False, lin
eterminator="\n")
    full_diagnostics, zero_diagnostics = [], []
    for index, style in enumerate(STYLES):
        generated = model.sample(style, N_GENERATED, SEED + 100000 + index)
        generated.insert(0, "sample_id", [f"{safe_style(style)}_{i:03d}" for i
 in range(1, N_GENERATED + 1)])
        generated.insert(1, "target_style", style)
        generated.to_csv(OUT / f"generated_{safe_style(style)}.csv", index=Fal
se, lineterminator="\n")
```

```
        diag = generated_diagnostics(model, generated[x.columns], style, x, labels, support, cv_support)
        diag["sample_id"] = generated.sample_id
        full_diagnostics.append(diag)
        style_x = x.loc[labels == style]
        imputed_full = model.impute(x)
        imputed_style = model.impute(style_x)
        for j, feature in enumerate(x.columns):
            zero_diagnostics.append({"style": style, "feature": feature,
                "full_observed_zero_fraction": float(x[feature].eq(0).sum() / x[feature].notna().sum()),
                "style_observed_zero_fraction": float(style_x[feature].eq(0).sum() / style_x[feature].notna().sum()),
                "full_imputed_zero_fraction": float(np.mean(imputed_full[:, j] == 0)),
                "style_imputed_zero_fraction": float(np.mean(imputed_style[:, j] == 0)),
                "generated_zero_fraction": float(generated[feature].eq(0).mean())})
    full_diagnostics = pd.concat(full_diagnostics, ignore_index=True)
    full_diagnostics.to_csv(OUT / "generated_diagnostics.csv", index=False, lineterminator="\n")
    pd.DataFrame(zero_diagnostics).to_csv(OUT / "generated_zero_diagnostics.csv", index=False, lineterminator="\n")
    elapsed = time.perf_counter() - start
    summary_json = {
        "date": "2026-10-23",
        "n_real": len(x), "n_features": x.shape[1], "n_styles": labels.nunique(),
        "mean_strength": MAIN_PARAMS[0], "cov_strength": MAIN_PARAMS[1],
        "parameter_policy": "prespecified_fixed_main_and_separate_sensitivity_no_outer_selection",
        "cv_repeat_seeds": REPEAT_SEEDS, "cv_folds": 3, "mc_repeats": MC_REPEATS,
        "generated_n_each_draw": N_GENERATED, "validation_records": len(records),
        "validation_test_style_n_min": int(records.holdout_style_n.min()),
        "validation_test_style_n_max": int(records.holdout_style_n.max()),
        "full_generation_rows": len(full_diagnostics),
        "full_generation_copy_rate": float(full_diagnostics.exact_training_copy.mean()),
        "full_generation_within_insample_latent_q95": float(full_diagnostics.within_latent_style_q95.mean()),
        "full_generation_within_cv_latent_q95": float(full_diagnostics.within_cv_latent_style_q95.mean()),
        "minimum_style_cov_eigenvalue": float(min(d["minimum_cov_eigenvalue"] for d in model.fit_diagnostics_)),
        "elapsed_seconds": elapsed,
        "limits": ["Tiny style samples; 300 generated rows are Monte Carlo, not independent real evidence",
                   "Shared empirical margins and shrinkage may dilute style-specific distributions",
                   "Full-fit support thresholds are descriptive, not independently calibrated",
                   "Chemical target spectra are not brewing recipes or sensory panel validation"],
    }
    (OUT / "summary.json").write_text(json.dumps(summary_json, ensure_ascii=False, indent=2), encoding="utf-8", newline="\n")
    write_report(summary, sensitivity_summary, full_diagnostics, support, elapsed, x, labels)
    print(json.dumps(summary_json, ensure_ascii=False, indent=2), flush=True)
```

```
415
416
417 if __name__ == "__main__":
418     with threadpool_limits(limits=1):
419         main()
```

src/08_q3_transfer.py

SHA-256: fb99a8dff4c78fd0d705507e65f3a64c9855e18a4462dd2ba53a0df578405cd5

```python
"""Constrained Pils/Lager -> Tripel target-spectrum search.

Source beers are excluded from fitted copula and sensory proxy training. The
bootstrap quantiles are model diagnostics, not calibrated outcome guarantees.
"""
from __future__ import annotations

import json

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from threadpoolctl import threadpool_limits

from common import SEED, SOLUTION
from q3_copula import ConditionalGaussianCopula
from q3_data import load_q3_data, read_defect_thresholds

OUT = SOLUTION / "outputs/q3/transfer"
SOURCE_STYLE = "Pils/Lager"
TARGET_STYLE = "Tripel"
N_GENERATED = 500
LAMBDAS = [0.05, 0.2, 1.0]
DEFAULT_LAMBDA = 0.2
MIN_TARGET_IMPROVEMENT = 0.10
MIN_LATENT_RMS_CHANGE = 0.05
SUPPORT_QUANTILE = 0.95
TOL = 1e-10


def paired_deltas(models, candidates, source):
    return np.column_stack([
        np.asarray(model.predict(candidates)).reshape(-1)
        - float(np.asarray(model.predict(source)).reshape(-1)[0])
        for model in models
    ])


def defect_caps(source, defects, threshold_kind):
    caps = {}
    for name, rule in defects.items():
        value = float(source[rule["feature"]].iloc[0])
        threshold = rule[f"threshold_{threshold_kind}"]
        caps[rule["feature"]] = max(value, float(threshold)) if pd.notna(thres
hold) else value
    return caps


def chemical_check(frame, caps):
    good = np.ones(len(frame), dtype=bool)
    for feature, cap in caps.items():
        values = frame[feature].to_numpy(float)
        good &= np.isfinite(values) & (values >= 0) & (values <= cap + TOL)
    return good


def excess(value, threshold):
    return max(value / threshold - 1, 0) if pd.notna(threshold) else np.nan
```

```


def main():
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y, manifest = load_q3_data()
    source_rows = np.flatnonzero(meta.tasting_category_fine.eq(SOURCE_STYLE))
    training_rows = np.flatnonzero(~meta.tasting_category_fine.eq(SOURCE_STYLE))
    defects = read_defect_thresholds()
    proxy = joblib.load(SOLUTION / "outputs/q3/sensory/transfer_proxy.joblib")
    ensemble = joblib.load(SOLUTION / "outputs/q3/sensory/stale_bootstrap.joblib")
    assert proxy["features"] == x.columns.tolist() == ensemble["features"]
    assert proxy["targets"] == y.columns.tolist()
    assert len(ensemble["models"]) == 40
    selection_models, audit_models = ensemble["models"][:30], ensemble["models"][30:]
    for indices in ensemble["bootstrap_indices"]:
        assert not np.isin(indices, source_rows).any(), "Source beer entered bootstrap training"

    # All eleven transfer source rows are kept out of empirical marginals too.
    copula = ConditionalGaussianCopula(mean_strength=5.0, cov_strength=20.0)
    copula.fit(x.iloc[training_rows], meta.tasting_category_fine.iloc[training_rows])
    target_rows = np.flatnonzero(meta.tasting_category_fine.eq(TARGET_STYLE))
    target = x.iloc[target_rows]
    target_z = copula.transform(target)
    p = x.shape[1]
    target_pairs = cdist(target_z, target_z) / np.sqrt(p)
    np.fill_diagonal(target_pairs, np.inf)
    target_loo_nn = target_pairs.min(axis=1)
    support_limit = float(np.quantile(target_loo_nn, SUPPORT_QUANTILE))
    # This is an empirical support rule, not a coverage or production guarantee.
    center = target_z.mean(axis=0)
    train_min = x.iloc[training_rows].min().to_numpy()
    train_max = x.iloc[training_rows].max().to_numpy()
    base_pool = copula.sample(TARGET_STYLE, N_GENERATED, seed=SEED + 301)
    target_median = target.median().to_numpy()
    records, candidate_metrics, chemical_records = [], [], []
    spectra, profiles, changes, paired_audit_records = [], [], [], []
    source_spectra = pd.concat([meta.iloc[source_rows].reset_index(drop=True),
                                x.iloc[source_rows].reset_index(drop=True)], axis=1)
    source_spectra.to_csv(OUT / "source_spectra.csv", index=False, lineterminator="\n")

    for source_no, row_index in enumerate(source_rows):
        beer = int(meta.beer.iloc[row_index])
        raw_source = x.iloc[[row_index]].copy()
        complete_defects = all(np.isfinite(raw_source[rule["feature"]].iloc[0])
                               and raw_source[rule["feature"]].iloc[0] >= 0
                               for rule in defects.values())
        if not complete_defects:
            for weight in LAMBDAS:
                records.append({"source_beer": beer, "source_style": SOURCE_STYLE,
                                "target_style": TARGET_STYLE, "mode": "protected",
                                "status": "source_defect_unverifiable", "lambd
```

```
a": weight,
                                    "is_default_policy": weight == DEFAULT_LAMBDA,
                                    "all_model_checks_passed": False})
                continue
            # Other missing features may be filled using training medians; four
            # protected source values above must always be directly observed.
            source = raw_source.fillna(x.iloc[training_rows].median())
            source_z = copula.transform(source)
            before_distance = float(copula.distance(source, TARGET_STYLE)[0])
            before_nn = float(cdist(source_z, target_z).min() / np.sqrt(p))
            center_scale = max(float(np.linalg.norm(source_z[0] - center) / np.sqr
t(p)), 1e-8)
            caps_median = defect_caps(raw_source, defects, "median")
            caps_mean = defect_caps(raw_source, defects, "mean")
            actual_target_feasible = int(chemical_check(target, caps_median).sum()
)

            # Fixed search design: conditional samples and interpolation towards t
hem.
            # Same pool for all sources and lambdas; no post-result relaxation.
            source_values = source.to_numpy()[0]
            blocks, descriptions = [], []
            for gamma in [0.25, 0.5, 0.75, 1.0]:
                values = (1 - gamma) * source_values + gamma * base_pool.to_numpy(
)
                blocks.append(values)
                descriptions.extend(("copula_interpolation", gamma, j) for j in ra
nge(len(values)))
            for gamma in [0.25, 0.5, 0.75, 1.0]:
                blocks.append(((1 - gamma) * source_values + gamma * target_median
)[None])
                descriptions.append(("target_median_interpolation", gamma, -1))
            unprojected = pd.DataFrame(np.vstack(blocks), columns=x.columns)
            projected = unprojected.copy()
            for feature, cap in caps_median.items():
                projected[feature] = projected[feature].clip(lower=0, upper=cap)

            z = copula.transform(projected)
            distances = copula.distance(projected, TARGET_STYLE)
            nn = cdist(z, target_z).min(axis=1) / np.sqrt(p)
            change = np.linalg.norm(z - source_z, axis=1) / np.sqrt(p)
            marginal_support = ((projected.to_numpy() >= train_min - TOL)
                                & (projected.to_numpy() <= train_max + TOL)).all(a
xis=1)
            support = (nn <= support_limit + TOL) & marginal_support
            improvement = 1 - distances / max(before_distance, 1e-8)
            chemical_ok = chemical_check(projected, caps_median)
            delta_selection = paired_deltas(selection_models, projected, source)
            selection_q95 = np.quantile(delta_selection, .95, axis=1)
            proxy_ok = selection_q95 <= TOL
            nontrivial = change >= MIN_LATENT_RMS_CHANGE
            target_ok = improvement >= MIN_TARGET_IMPROVEMENT
            eligible = support & nontrivial & target_ok & chemical_ok & proxy_ok
            mean_ok = chemical_check(projected, caps_mean)

            unprojected_z = copula.transform(unprojected)
            unprojected_dist = copula.distance(unprojected, TARGET_STYLE)
            unprojected_change = np.linalg.norm(unprojected_z - source_z, axis=1)
/ np.sqrt(p)
            unprojected_nn = cdist(unprojected_z, target_z).min(axis=1) / np.sqrt(
p)
            unconstrained_support = (unprojected_nn <= support_limit + TOL) & (
```

```
            (unprojected.to_numpy() >= train_min - TOL)
            & (unprojected.to_numpy() <= train_max + TOL)).all(axis=1)
        baseline_eligible = (unconstrained_support & (unprojected_change >= MIN_LATENT_RMS_CHANGE)
                             & (1 - unprojected_dist / max(before_distance, 1e-8) >= MIN_TARGET_IMPROVEMENT))
        baseline_chemical = chemical_check(unprojected, caps_median)
        base_source_profile = proxy["pipeline"].predict(source)[0]
        for j in range(len(projected)):
            method, gamma, pool_row = descriptions[j]
            candidate_metrics.append({
                "source_beer": beer, "candidate_index": j, "method": method,
                "gamma": gamma, "pool_row": pool_row,
                "target_distance": float(distances[j]), "target_improvement": float(improvement[j]),
                "change_latent_rms": float(change[j]), "target_nn_rms": float(nn[j]),
                "marginal_support": bool(marginal_support[j]), "support_ok": bool(support[j]),
                "chemical_median_ok": bool(chemical_ok[j]), "chemical_mean_ok": bool(mean_ok[j]),
                "selection_paired_delta_q95": float(selection_q95[j]), "selection_proxy_ok": bool(proxy_ok[j]),
                "target_improvement_ok": bool(target_ok[j]), "nontrivial": bool(nontrivial[j]),
                "selection_feasible": bool(eligible[j]),
            })

        for weight in LAMBDAS:
            objective = distances / max(before_distance, 1e-8) + weight * change / center_scale
            baseline_objective = unprojected_dist / max(before_distance, 1e-8) + weight * unprojected_change / center_scale
            choices = [("unconstrained_baseline", baseline_eligible, baseline_objective,
                        unprojected, unprojected_dist, unprojected_nn, unprojected_change),
                       ("protected", eligible, objective, projected, distances, nn, change)]
            for mode, allowed, criterion, pool, pool_dist, pool_nn, pool_change in choices:
                label = f"beer_{beer}_{mode}_lambda_{weight:g}"
                common = {"source_beer": beer, "source_style": SOURCE_STYLE, "target_style": TARGET_STYLE,
                          "mode": mode, "lambda": weight, "is_default_policy": weight == DEFAULT_LAMBDA,
                          "n_candidates": len(pool), "n_selection_feasible": int(allowed.sum()),
                          "n_chemical_feasible": int((chemical_ok if mode == "protected" else baseline_chemical).sum()),
                          "n_support_feasible": int((support if mode == "protected" else unconstrained_support).sum()),
                          "n_real_target_chemical_feasible": actual_target_feasible,
                          "target_distance_before": before_distance, "target_nn_before": before_nn,
                          "support_nn_limit": support_limit,
                          "source_missing_nondefect": int(raw_source.isna().sum().sum()),
                          "transfer_id": label}
                if not allowed.any():
                    records.append({**common, "status": "no_candidate_found",
```

```
    "all_model_checks_passed": False})
                    continue
                candidate_index = int(np.flatnonzero(allowed)[np.argmin(criter
ion[allowed])])
                selected = pool.iloc[[candidate_index]]
                selection_delta = paired_deltas(selection_models, selected, so
urce)[0]
                audit_delta = paired_deltas(audit_models, selected, source)[0]
                sq95 = float(np.quantile(selection_delta, .95))
                aq95 = float(np.quantile(audit_delta, .95))
                chem_median = bool(chemical_check(selected, caps_median)[0])
                chem_mean = bool(chemical_check(selected, caps_mean)[0])
                audit_ok = aq95 <= TOL
                profile_after = proxy["pipeline"].predict(selected)[0]
                # Audit models do not affect candidate selection. A failed aud
it
                # is retained in outputs; candidates are never reselected usin
g it.
                status = ("model_checks_passed" if audit_ok else "resampling_a
udit_failed") if mode == "protected" else "baseline_only"
                records.append({**common, "candidate_index": candidate_index,
                                "status": status,
                                "all_model_checks_passed": bool(mode == "prote
cted" and audit_ok and chem_median),
                                "target_distance_after": float(pool_dist[candi
date_index]),
                                "target_improvement": float(1 - pool_dist[cand
idate_index] / max(before_distance, 1e-8)),
                                "target_nn_after": float(pool_nn[candidate_ind
ex]),
                                "change_latent_rms": float(pool_change[candida
te_index]),
                                "objective": float(criterion[candidate_index])
,
                                "chemical_median_ok": chem_median, "chemical_m
ean_ok": chem_mean,
                                "selection_paired_delta_q95": sq95, "audit_pai
red_delta_q95": aq95,
                                "audit_proxy_ok": audit_ok,
                                "stale_prediction_before": float(base_source_p
rofile[y.columns.get_loc("stale_hops")]),
                                "stale_prediction_after": float(profile_after[
y.columns.get_loc("stale_hops")])})
                spectra.append({"transfer_id": label, "source_beer": beer, "mo
de": mode,
                                "lambda": weight, **selected.iloc[0].to_dict()
})
                for phase, profile in [("source", base_source_profile), ("tran
sferred", profile_after)]:
                    profiles.append({"transfer_id": label, "source_beer": beer
, "mode": mode,
                                     "lambda": weight, "phase": phase,
                                     **dict(zip(y.columns, map(float, profile)
))})
                for k, deltas in [("selection", selection_delta), ("audit", au
dit_delta)]:
                    paired_audit_records.extend({"transfer_id": label, "ensemb
le": k,
                                                 "model_index": b, "paired_del
ta": float(value)}
                                                for b, value in enumerate(delt
as))
```

```
                for name, rule in defects.items():
                    feature = rule["feature"]
                    before = float(raw_source[feature].iloc[0])
                    after = float(selected[feature].iloc[0])
                    chemical_records.append({"transfer_id": label, "source_bee
r": beer,
                                             "mode": mode, "lambda": weight, "
defect": name,
                                             "feature": feature, "unit": rule[
"unit"],
                                             "before": before, "after": after,
                                             "threshold_median": rule["thresho
ld_median"],
                                             "threshold_mean": rule["threshold
_mean"],
                                             "median_upper_bound": caps_median
[feature],
                                             "mean_upper_bound": caps_mean[fea
ture],
                                             "median_excess_before": excess(be
fore, rule["threshold_median"]),
                                             "median_excess_after": excess(aft
er, rule["threshold_median"]),
                                             "mean_excess_before": excess(befo
re, rule["threshold_mean"]),
                                             "mean_excess_after": excess(after
, rule["threshold_mean"]),
                                             "concentration_change": after - b
efore})
                for feature in x.columns:
                    before = float(source[feature].iloc[0])
                    after = float(selected[feature].iloc[0])
                    if abs(after - before) > 1e-12:
                        changes.append({"transfer_id": label, "feature": featu
re,
                                        "before": before, "after": after, "cha
nge": after - before})
        print(f"Transfer {source_no + 1}/{len(source_rows)} beer={beer}: "
              f"{eligible.sum()}/{len(eligible)} selection-feasible candidates
", flush=True)

    tables = {
        "transfer_summary.csv": records, "candidate_diagnostics.csv": candidat
e_metrics,
        "transferred_spectra.csv": spectra, "sensory_before_after.csv": profil
es,
        "defect_checks.csv": chemical_records, "feature_changes.csv": changes,
        "stale_paired_deltas.csv": paired_audit_records,
    }
    for filename, rows in tables.items():
        pd.DataFrame(rows).to_csv(OUT / filename, index=False, lineterminator=
"\n")
    result = pd.DataFrame(records)
    default = result[result["is_default_policy"].fillna(False) & result["mode"
].eq("protected")]
    n_selected = int(default.status.isin(["model_checks_passed", "resampling_a
udit_failed"]).sum())
    n_checked = int(default.all_model_checks_passed.sum())
    mean_sensitivity = default.get("chemical_mean_ok", pd.Series(False, index=
default.index))
    mean_threshold_all_checks = int((default.all_model_checks_passed
                                     & mean_sensitivity.fillna(False)).sum())
```

```
    summary = {
        "seed": SEED, "source_style": SOURCE_STYLE, "target_style": TARGET_STY
LE,
        "source_beers": list(map(int, meta.beer.iloc[source_rows])), "n_traini
ng_beers": len(training_rows),
        "source_exclusion": "All Pils/Lager rows excluded from fitted copula,
sensory proxy and bootstrap models",
        "n_base_generated": N_GENERATED, "n_candidates_per_source": N_GENERATE
D * 4 + 4,
        "lambdas": LAMBDAS, "default_lambda": DEFAULT_LAMBDA,
        "minimum_target_improvement": MIN_TARGET_IMPROVEMENT,
        "minimum_latent_rms_change": MIN_LATENT_RMS_CHANGE,
        "support": {"metric": "full-226-dimensional Gaussian-rank RMS nearest
Tripel distance",
                    "reference": "Tripel training leave-one-out nearest-neighb
or distances",
                    "quantile": SUPPORT_QUANTILE, "limit": support_limit,
                    "additional_rule": "All features within non-source trainin
g marginal support"},
        "constraints": defects, "selection_bootstrap_models": len(selection_mo
dels),
        "audit_bootstrap_models": len(audit_models),
        "default_policy": {"n_sources": len(source_rows), "n_candidates_select
ed": n_selected,
                           "n_model_checks_passed": n_checked,
                           "n_audit_failed": int(default.status.eq("resampling
_audit_failed").sum()),
                           "n_no_candidate": int(default.status.eq("no_candida
te_found").sum()),
                           "n_source_unverifiable": int(default.status.eq("sou
rce_defect_unverifiable").sum()),
                           "n_all_checks_also_pass_mean_thresholds_same_spectr
a": mean_threshold_all_checks},
        "limitations": [
            "Model checks passed does not mean verified sensory or brewing suc
cess.",
            "Bootstrap quantiles after candidate search are uncalibrated model
 diagnostics, not 95% outcome guarantees.",
            "The 10 audit models share real training data; separate resampling
 is not an independent experiment.",
            "No audit-based reselection or post-result relaxation of improveme
nt/support thresholds.",
            "Trans-2-nonenal has no supplied threshold: its concentration may
not increase.",
            "The 45 sensory outputs remain on attachment 4 standardized scale,
 not raw 0-6.",
            "Hybrid relative features do not imply measured absolute concentra
tions or a realizable brewing recipe.",
        ],
    }
    (OUT / "summary.json").write_text(json.dumps(summary, ensure_ascii=False,
indent=2), encoding="utf-8", newline="\n")
    joblib.dump({"copula": copula, "features": x.columns.tolist(),
                 "training_rows": training_rows, "source_rows": source_rows},
OUT / "transfer_copula.joblib")
    pd.DataFrame({"beer": meta.beer.iloc[target_rows].to_numpy(), "loo_nn_rms"
: target_loo_nn}).to_csv(
        OUT / "target_support_reference.csv", index=False, lineterminator="\n"
)
    print(json.dumps(summary["default_policy"], ensure_ascii=False, indent=2),
 flush=True)

```

```
317
318 if __name__ == "__main__":
319     with threadpool_limits(limits=1):
320         main()
```

src/09_q3_report.py

SHA-256: 3621f641847b101cc18abd754d6e7ce9ff6bfb9be162ec0572a66060ec4509d6

```
"""Build Q3 sensory profiles, research figures and a source-backed result note."""
import json

import joblib
import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd

from common import SOLUTION
from q3_data import load_q3_data

OUT = SOLUTION / "outputs/q3"
FIGURES = OUT / "figures"
STYLES = ["Tripel", "Kriek", "Lambic", "Pils/Lager"]
COLORS = {"conditional_copula": "#2876A5", "style_bootstrap": "#9B9FA5",
          "unconditional_copula": "#C88B27"}
STATUS_NAMES = {"model_checks_passed": "通过模型检查",
                "resampling_audit_failed": "重抽样审计未通过",
                "no_candidate_found": "未找到合格候选",
                "source_defect_unverifiable": "源缺陷不可核验"}


def main():
    FIGURES.mkdir(parents=True, exist_ok=True)
    meta, x, y, manifest = load_q3_data()
    generation = OUT / "generation"
    cv = pd.read_csv(generation / "cv_summary.csv")
    gs = json.loads((generation / "summary.json").read_text(encoding="utf-8"))
    ss = json.loads((OUT / "sensory/summary.json").read_text(encoding="utf-8"))
    ts = json.loads((OUT / "transfer/summary.json").read_text(encoding="utf-8"))
    transfer = pd.read_csv(OUT / "transfer/transfer_summary.csv")
    default = transfer[(transfer["mode"] == "protected") & transfer.is_default_policy].copy()
    default = default.sort_values("source_beer")
    selected = default[default.candidate_index.notna()]
    diagnostics = pd.read_csv(generation / "generated_diagnostics.csv")
    model = joblib.load(OUT / "sensory/sensory_model.joblib")
    assert model["features"] == x.columns.tolist()
    profiles, summary_profiles = [], []
    for style in STYLES:
        frame = pd.read_csv(generation / f"generated_{style.replace('/', '-')}.csv")
        predicted = model["pipeline"].predict(frame[x.columns])
        diag = diagnostics[diagnostics["style"] == style].reset_index(drop=True)
        profile = pd.DataFrame(predicted, columns=y.columns)
        profile.insert(0, "target_style", style)
        profile.insert(0, "sample_id", frame.sample_id)
        profile["within_loo_nn_style_q95"] = diag.within_loo_nn_style_q95.to_numpy()
        profile["within_cv_latent_style_q95"] = diag.within_cv_latent_style_q95.to_numpy()
        profiles.append(profile)
        for j, target in enumerate(y.columns):
```

```
            summary_profiles.append({"style": style, "target": target,
                                     "generated_n": len(profile), "predicted_m
ean": float(predicted[:, j].mean()),
                                     "predicted_p05": float(np.quantile(predic
ted[:, j], .05)),
                                     "predicted_p95": float(np.quantile(predic
ted[:, j], .95)),
                                     "real_observed_mean": float(y.loc[meta.ta
sting_category_fine.eq(style), target].mean()),
                                     "scale": "attachment_4_standardized",
                                     "interval_meaning": "spread_across_genera
ted_spectra_not_confidence_interval"})
    pd.concat(profiles, ignore_index=True).to_csv(OUT / "generated_sensory_pro
files.csv", index=False, lineterminator="\n")
    profiles_summary = pd.DataFrame(summary_profiles)
    profiles_summary.to_csv(OUT / "generated_sensory_summary.csv", index=False
, lineterminator="\n")

    plt.rcParams.update({"font.family": "DejaVu Sans", "font.size": 10,
                         "axes.spines.top": False, "axes.spines.right": False,
                         "figure.facecolor": "white", "savefig.facecolor": "wh
ite"})
    fig, ax = plt.subplots(figsize=(10.4, 5.4))
    positions = np.arange(len(STYLES))
    for offset, method in zip([-.24, 0, .24], COLORS):
        rows = cv[cv.method.eq(method)].set_index("style").loc[STYLES]
        ax.bar(positions + offset, rows.energy_pca5_mean, width=.22,
               yerr=rows.energy_pca5_std, capsize=3, color=COLORS[method],
               label={"conditional_copula": "Conditional copula", "style_boots
trap": "Style bootstrap",
                      "unconditional_copula": "Unconditional copula"}[method],
               error_kw={"elinewidth": 1, "ecolor": "#555555"})
    ax.set_xticks(positions, STYLES)
    ax.set_ylabel("Five-dimensional energy discrepancy (V-statistic)")
    ax.set_title("Style generation: held-out distribution comparison", loc="le
ft", fontsize=14, pad=16)
    ax.grid(axis="y", color="#E5E7EA", linewidth=.7)
    ax.set_axisbelow(True)
    ax.legend(frameon=False, ncol=3, loc="upper center", bbox_to_anchor=(.5, 1
.015), fontsize=9)
    fig.text(.11, .025, "Mean and fold SD over 2 repeats x 3 stratified folds;
 3 simulation seeds per fold.\n"
             "Lower is better. Fold SD is descriptive, not a confidence interv
al; each held-out style has 3-10 real beers.",
             fontsize=9, color="#555B62")
    fig.subplots_adjust(left=.11, right=.98, top=.83, bottom=.20)
    fig.savefig(FIGURES / "generation_validation.png", dpi=300)
    fig.savefig(FIGURES / "generation_validation.svg")
    plt.close(fig)

    keys = ["A_malt_all", "F_malt_all", "A_hops_all", "F_hops_all", "A_esters_
all",
            "F_esters_all", "acidity", "bitternes", "sweetness"]
    means, labels = [], []
    for style in STYLES[:3]:
        rows = profiles_summary[profiles_summary["style"] == style].set_index(
"target").loc[keys]
        means.extend([rows.real_observed_mean.to_numpy(), rows.predicted_mean.
to_numpy()])
        labels.extend([f"{style}: observed", f"{style}: generated"])
    values = np.array(means)
    fig, ax = plt.subplots(figsize=(11.8, 5.4))
```

```
    limit = max(float(np.max(np.abs(values))), .5)
    im = ax.imshow(values, cmap="RdBu_r", vmin=-limit, vmax=limit, aspect="auto")
    ax.set_yticks(np.arange(len(labels)), labels)
    ax.set_xticks(np.arange(len(keys)), ["Malt\naroma", "Malt\nflavour", "Hops\naroma", "Hops\nflavour",
                                         "Esters\naroma", "Esters\nflavour", "Acidity", "Bitterness", "Sweetness"])
    for (i, j), value in np.ndenumerate(values):
        ax.text(j, i, f"{value:.2f}", ha="center", va="center",
                color="white" if abs(value) > limit * .65 else "#25272B", fontsize=9)
    ax.set_title("Relative sensory fingerprints", loc="left", fontsize=14, pad=14)
    fig.colorbar(im, ax=ax, shrink=.85, label="Attachment-standardized sensory value")
    fig.text(.20, .02, "Generated rows use a fitted sensory predictor; 300 spectra per style. Values are not original 0-6 scores.\n"
             "Observed rows summarize the existing panel data; this figure is descriptive rather than validation.", fontsize=9, color="#555B62")
    fig.subplots_adjust(left=.20, right=.96, top=.86, bottom=.20)
    fig.savefig(FIGURES / "generated_sensory_fingerprints.png", dpi=300)
    fig.savefig(FIGURES / "generated_sensory_fingerprints.svg")
    plt.close(fig)

    fig, axes = plt.subplots(1, 2, figsize=(12.0, 6.2), gridspec_kw={"width_ratios": [1.05, 1]})
    for position, row in enumerate(default.itertuples()):
        axes[0].scatter(row.target_distance_before, position, color="#9B9FA5", marker="o", s=32,
                        label="Source" if position == 0 else None, zorder=3)
        if pd.notna(row.candidate_index):
            color = "#2876A5" if row.all_model_checks_passed else "#C88B27"
            axes[0].plot([row.target_distance_after, row.target_distance_before], [position, position],
                         color=color, linewidth=1.5)
            axes[0].scatter(row.target_distance_after, position, color=color, marker="s", s=30, zorder=3)
        else:
            axes[0].annotate("No candidate", (row.target_distance_before, position),
                             xytext=(-8, -11), textcoords="offset points", ha="right", fontsize=8)
    axes[0].set_yticks(range(len(default)), [f"Beer {b}" for b in default.source_beer])
    axes[0].invert_yaxis()
    axes[0].set_xlabel("Distance to Tripel model centre\n(normalized Mahalanobis)")
    axes[0].set_title("Source and selected target spectrum", loc="left", pad=14)
    axes[0].grid(axis="x", color="#E5E7EA", linewidth=.7)
    axes[0].set_axisbelow(True)
    positions = np.arange(len(selected))
    colors = ["#2876A5" if v else "#C88B27" for v in selected.all_model_checks_passed]
    axes[1].barh(positions, selected.audit_paired_delta_q95, color=colors, height=.65)
    axes[1].scatter(selected.selection_paired_delta_q95, positions, color="#25272B", marker="x", s=35,
                    label="Selection-model upper quantile", zorder=3)
    axes[1].axvline(0, color="#555B62", linewidth=1)
    axes[1].set_yticks(positions, [f"Beer {b}" for b in selected.source_beer])
```

```
    axes[1].invert_yaxis()
    axes[1].set_xlabel("Stale hops: paired predicted change\n(upper 0.95 quant
ile)")
    axes[1].set_title("Resampling audit of selected candidates", loc="left", p
ad=14)
    axes[1].grid(axis="x", color="#E5E7EA", linewidth=.7)
    axes[1].set_axisbelow(True)
    fig.suptitle("Pils/Lager to Tripel | fixed policy lambda = 0.2", x=.09, ha
="left", fontsize=15)
    fig.text(.09, .025, "Bars: audit upper quantile; crosses: selection upper
quantile. Blue: model checks passed; gold: audit failed.\n"
             "All 11 sources were excluded from training. The weak Stale hops
proxy does not establish actual sensory protection.\n"
             "Only 1 of 11 sources also passes the mean-threshold recheck of t
he same selected spectra; no reselection.",
             fontsize=9, color="#555B62")
    fig.subplots_adjust(left=.09, right=.98, top=.84, bottom=.24, wspace=.42)
    fig.savefig(FIGURES / "transfer_checks.png", dpi=300)
    fig.savefig(FIGURES / "transfer_checks.svg")
    plt.close(fig)

    # Present the exact metric, not its square root, to match the saved runs.
    comparison_lines = []
    for style in STYLES:
        rows = cv[cv["style"] == style].set_index("method")
        main_row, boot_row = rows.loc["conditional_copula"], rows.loc["style_b
ootstrap"]
        gain = 100 * (1 - main_row.energy_pca5_mean / boot_row.energy_pca5_mea
n)
        comparison_lines.append(f"| {style} | {main_row.energy_pca5_mean:.4f}
| {boot_row.energy_pca5_mean:.4f} | "
                                f"{rows.loc['unconditional_copula'].energy_pca
5_mean:.4f} | {gain:+.1f}% | "
                                f"{main_row.marginal_w1_iqr_median_mean:.4f} /
 {boot_row.marginal_w1_iqr_median_mean:.4f} |")
    transfer_lines = []
    for row in default.itertuples():
        gain = f"{100 * row.target_improvement:.1f}%" if pd.notna(row.candidat
e_index) else "–"
        audit = f"{row.audit_paired_delta_q95:+.4f}" if pd.notna(row.candidate
_index) else "–"
        mean_pass = "是" if row.all_model_checks_passed and row.chemical_mean_o
k == True else "否"
        transfer_lines.append(f"| {row.source_beer} | {STATUS_NAMES[row.status
]} | {gain} | {audit} | {mean_pass} |")
    defects = ts["constraints"]
    defect_lines = "\n".join(f"| {name} | `{r['feature']}` | {r['unit']} | {r[
'threshold_median'] if r['threshold_median'] is not None else '缺失'} | "
                             f"{r['threshold_mean'] if r['threshold_mean'] is
 not None else '缺失'} |"
                             for name, r in defects.items())
    default_counts = ts["default_policy"]
    q_stale = next(r for r in ss["stale_hops_metrics"] if r["model"] == "extra
_trees")
    h_stale = next(r for r in ss["transfer_proxy"]["stale_hops_metrics"] if r[
"model"] == "transfer_proxy")
    passed = default[default.all_model_checks_passed]
    mean_safe = passed[passed.chemical_mean_ok.eq(True)]
    improvement_range = (f"{passed.target_improvement.min() * 100:.1f}%–{passe
d.target_improvement.max() * 100:.1f}%"
                         if len(passed) else "未找到通过样本")
    report = f"""# 第三问：风格生成与跨风格迁移实验
```

日期：2026-10-23。全部数字由保存的模型、谱与验证表计算。复现入口为 `../run_q3.py`。

1. 运行结果

已生成 Tripel、Kriek、Lambic、Pils/Lager 各300条谱，共 **{gs['full_generation_rows']}** 条，并给出45维连续感官画像。生成谱的69个校准字段均为非负，未出现完整训练行的直接复制；157个未校准字段保留相对量标记。

对11款Pils/Lager源样本进行Tripel方向迁移。默认λ=0.2、中位阈值口径下，**{default_counts['n_candidates_selected']}**款找到筛选合格候选，**{default_counts['n_model_checks_passed']}**款通过全部模型检查，**{default_counts['n_audit_failed']}**款在保留的重抽样模型审计中未通过，**{default_counts['n_no_candidate']}**款未找到候选。同一选定谱改用均值阈值复核时，仅 **{len(mean_safe)}/11** 仍通过全部检查。

这里的“通过”指本次明确定义的数值与模型检查。Stale hops预测较弱，结果需要实际品评检验后才能判断真实缺陷是否得到控制。

2. 统一数据表示

使用226维输入：原1.csv的231维去掉5项派生汇总，其中69维替换为8.xlsx按beer对应的校准原值，剩余157维保留原相对表示。3个负校准观测设为缺失，共72个缺失值；补值在每个训练折内部拟合。原始零值保留，未校准的负值保留原含义。每列来源、表示、单位与缺失记录见 `../outputs/q3/sensory/feature_manifest.csv`。

感官预测器按同一226维表示重新训练，五折折外RMSE为 **0.4865**。画像保持附件4的标准化尺度，尚不能解释成原始0–6分。生成谱的5%–95%预测分位数描述300条谱之间的分布范围，不是预测置信区间。

3. 风格条件生成

训练经验分布中秩映射到高斯空间；风格均值以n/(n+5)向全局均值收缩，协方差以n/(n+20)混合风格与共享风格内Ledoit–Wolf协方差。所有矩阵加微小对角正则以保证正定。经验逆CDF生成新的联合组合，单列仍取训练支持中的值。零值在逆CDF中有概率区间，但生成零频率不保证与经验频率完全一致，另有逐字段诊断。

固定主参数(5,20)，单独报告(2,5)、(10,50)敏感性；未用外层结果选择主参数。对22风格分层做2次重复×3折验证，每次比较条件生成、目标风格重采样、无条件生成；每法300条、3个模拟种子。每个风格的真实留出样本只有3–10款，模拟300条不能增加真实证据量。分割重叠，折间标准差属于描述性波动。

能量差异指标在训练折拟合的5维PCA标准化空间中计算：


`E = 2 mean||a-b|| - mean||a-a'|| - mean||b-b'||`。

它是包含对角项的经验V统计量，未开平方；越小越好。W1按训练IQR标准化，零IQR回退到训练range，再回退1。跨特征中位数作为稳健补充，完整均值与逐字段结果同时保存。

风格	条件生成E	重采样E	无条件E	相对重采样改善	W1跨特征中位数：条件/重采样
{chr(10).join(comparison_lines)}

条件模型仅在Tripel的此项指标上优于重采样，其他风格未显示同样优势。重采样复制率为1，条件生成复制率为0，体现新颖性与分布保真性的权衡。Kriek的平均W1被极端化合物值支配，因此不能只凭平均W1判断模型优劣。模型适合提供可检查的候选谱，当前证据不足以宣称所有风格都已获得高保真生成。

相对画像中，Kriek与Lambic的酸度明显向中部收缩，反映小样本条件分布收缩和感官预测误差的共同影响；画像不能取代真实品评。



训练内Mahalanobis距离参考较乐观，全部生成谱都超过训练内95%距离分位；采用重复留出真实样本的参考范围时结果明显不同。两种标记均保留在generated_diagnostics.csv，属于描述性参考，不构成已校准的可行性保证。未用事后放宽支持规则来改变迁移结果。

222
223 ![相对感官画像](../outputs/q3/figures/generated_sensory_fingerprints.png)
224
225 ## 4. 缺陷保护迁移
226
227 全部11款源Pils/Lager排除出迁移Copula、45维感官代理和40个Stale hops重抽样模型训练。迁移训练集239款；源的四项缺陷浓度均有原始校准观测。若缺失，流程返回不可核验，不用插补值充当保护依据。
228
229 | 缺陷 | 字段 | 单位 | 中位阈值 | 均值阈值 |
230 |---|---|---|---:|---:|
231 {defect_lines}
232
233 有阈值项约束`max(c'/T-1,0) <= max(c_source/T-1,0)`，等价为`c' <= max(T,c_source)`。trans-2-nonenal未提供阈值，采用浓度不得增加的替代约束。4VG按题面列出的保护项执行，不据此推论它在所有风格中都属于缺陷。
234
235 每源固定500条条件谱×4个插值比例，加4个目标中位谱插值，共2004个候选；投影后重新计算全部距离及预测。通过条件为：四项化学约束、目标距离至少改善10%、全226维高斯秩空间的目标最近邻距离不超过Tripel训练LOO距离95%分位、所有字段处于非源训练边缘范围、改动RMS至少0.05，以及30个选择模型的配对预测差上0.95分位≤0。
236
237 在可行集合内最小化`目标距离/源目标距离 + λ × 改动RMS/源到目标中心RMS`。固定λ为0.05、0.2、1.0，默认0.2；后10个重抽样模型只审计已选谱，不参与重选。两组模型共享真实训练数据，其分位数是模型诊断，既不是独立实验，也没有经过95%覆盖校准。
238
239 | 源beer | 默认方案状态 | 目标距离改善 | 审计配对差Q95 | 同谱均值阈值也全部通过 |
240 |---|---|---:|---:|---|
241 {chr(10).join(transfer_lines)}
242
243 通过模型检查的源编号为 **{', '.join(map(str, passed.source_beer))}**，目标距离改善范围 **{improvement_range}**。同谱均值阈值也通过的编号为 **{', '.join(map(str, mean_safe.source_beer)) or '无'}**。DMS均值阈值17.25低于中位阈值19，故阈值口径会改变结果，不能省略这项敏感性。
244
245 ![迁移检查](../outputs/q3/figures/transfer_checks.png)
246
247 ## 5. 适用边界
248
249 Stale hops五折R^2为 **{q_stale['macro_r2']:.4f}**，RMSE **{q_stale['rmse']:.4f}**；整风格留出11款Pils时R^2为 **{h_stale['macro_r2']:.4f}**，RMSE **{h_stale['rmse']:.4f}**。这一关键代理预测能力有限，总体45维预测表现不能替代缺陷目标的验证。候选搜索后的模型上分位约束也不能转化为真实风味不恶化的概率保证。
250
251 在28款真实Tripel中，对9个源样本没有真实目标酒同时符合四项化学保护上界，说明目标风格与保护条件存在张力。投影生成的是化学目标谱，尚未给出可实现该谱的配料或发酵控制方案。当前验证不包含生产实验、质量守恒或真实迁移后的品评。
252
253 ## 6. 文件与复现
254
255 - `../outputs/q3/generation/generated_Tripel.csv`、`generated_Kriek.csv`、`generated_Lambic.csv`、`generated_Pils-Lager.csv`：各300条226维谱。
256 - `../outputs/q3/generated_sensory_profiles.csv`：全部1200条谱的45维画像；`generated_sensory_summary.csv`含均值、分位与真实风格均值。
257 - `../outputs/q3/transfer/transferred_spectra.csv`：三种λ下的保护方案及未加缺陷保护的基线谱；失败候选仍保留状态，不作为成功样本。
258 - `../outputs/q3/transfer/defect_checks.csv`、`sensory_before_after.csv`、`feature_changes.csv`：逐项缺陷、感官与特征改动。
259 - `../outputs/q3/transfer/candidate_diagnostics.csv`、`stale_paired_deltas.csv`：候选筛选与审计原始证据。
260 - `q3_generation.md`、`q3_representation.md`、`q3_method_review.md`：模型、数据表示及数值审查；`../outputs/q3/verification.json`为程序一致性检查。

```
261
262 在仓库根目录执行：`.venv/bin/python solution_a/run_q3.py`。本轮参数、源排除与候选判据
    均随代码保存。
263
264 数据来源为赛题附件1/4/8。协方差实现参照 [scikit-learn LedoitWolf文档](https://scikit-
    learn.org/stable/modules/generated/sklearn.covariance.LedoitWolf.html)，边缘距离
    使用 [SciPy Wasserstein-1实现](https://docs.scipy.org/doc/scipy/reference/genera
    ted/scipy.stats.wasserstein_distance.html)。风格收缩、迁移约束及候选审计是本题明确写出
    的建模选择，未声称由上述文档直接保证其效果。
265 """
266     (SOLUTION / "docs/q3_results.md").write_text(report, encoding="utf-8", new
    line="\n")
267     print(f"Saved {len(pd.concat(profiles))} sensory profiles, three figures,
    and docs/q3_results.md")
268
269
270 if __name__ == "__main__":
271     main()
```

src/10_q3_verify.py

SHA-256: f7ef0ef5732cfbfe61c9332d751840568b11c3742400f4e7e74f741e2f5be563

```
"""Recompute question-3 provenance, saved metrics and transfer constraints."""
from __future__ import annotations

import hashlib
import json
from pathlib import Path
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from scipy.stats import spearmanr
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.model_selection import KFold, StratifiedKFold
from threadpoolctl import threadpool_limits

from common import KEYS, SEED, SOLUTION, data_dir, load_xy


OUT = SOLUTION / "outputs" / "q3"
DERIVED = {"kcalperc", "esters_sum", "aroma_hops_sum", "acids_sum", "sulfur_sum"}
DEFECT_FIELDS = ("DMS", "X2.3.butanedione", "X4VG", "X.E..2.nonenal")
GENERATION_STYLES = ("Tripel", "Kriek", "Lambic", "Pils/Lager")
TOL = 1e-10


def close(actual, expected, label="numeric comparison", *, atol=1e-11):
    try:
        np.testing.assert_allclose(np.asarray(actual, dtype=float),
                                   np.asarray(expected, dtype=float),
                                   rtol=1e-9, atol=atol, equal_nan=True)
    except AssertionError as error:
        raise AssertionError(label) from error


def read_json(path):
    return json.loads(Path(path).read_text(encoding="utf-8"))


def score(y, prediction):
    return {
        "mae": float(mean_absolute_error(y, prediction)),
        "rmse": float(np.sqrt(mean_squared_error(y, prediction))),
        "macro_r2": float(r2_score(y, prediction, multioutput="uniform_average")),
    }


def same_table(actual, expected, keys, values, label):
    assert not actual.duplicated(keys).any(), f"Duplicate rows: {label}"
    left = actual.set_index(keys).sort_index()
    right = expected.set_index(keys).sort_index()
    assert left.index.equals(right.index), f"Row keys differ: {label}"
    close(left[values], right[values], label)


def check_hashes():
```

```
    table = pd.read_csv(SOLUTION / "outputs/audit/source_files.csv")
    assert len(table) == 9 and table.source.is_unique
    for row in table.itertuples(index=False):
        raw = (data_dir() / row.source).read_bytes()
        assert len(raw) == row.bytes, f"Source byte count changed: {row.source}"
        assert hashlib.sha256(raw).hexdigest() == row.sha256, f"Source changed: {row.source}"
    return {"files": len(table), "hash_algorithm": "sha256", "unchanged": True}


def load_contract():
    meta, original, y = load_xy()
    calibrated = pd.read_excel(data_dir() / "8.xlsx", sheet_name="Calibrated chemical dataset")
    assert calibrated.beer.is_unique and set(calibrated.beer) == set(meta.beer)
    calibrated = calibrated.set_index("beer").loc[meta.beer].reset_index()
    assert calibrated.tasting_category_fine.equals(meta.tasting_category_fine)
    features = [column for column in original if column not in DERIVED]
    calibrated_features = [column for column in calibrated if column not in set(KEYS) | DERIVED]
    assert len(features) == 226 and len(calibrated_features) == 69
    assert set(calibrated_features).issubset(features)
    expected = original[features].copy()
    negative_count = 0
    for feature in calibrated_features:
        values = calibrated[feature].copy()
        negative_count += int(values.lt(0).sum())
        expected[feature] = values.mask(values.lt(0)).to_numpy()
    assert expected.shape == (250, 226) and y.shape == (250, 45)
    folder = OUT / "sensory"
    stored = pd.read_csv(folder / "hybrid_features.csv")
    assert stored.columns.tolist() == features
    close(stored, expected, "Saved hybrid features differ from original attachments")
    saved_meta = pd.read_csv(folder / "meta.csv", dtype={"beer_id": str})
    pd.testing.assert_frame_equal(saved_meta, meta, check_dtype=False)
    close(pd.read_csv(folder / "y45.csv"), y, "Saved targets differ from attachment 4")
    manifest = pd.read_csv(folder / "feature_manifest.csv")
    assert manifest.feature.tolist() == features and manifest.position.tolist() == list(range(226))
    assert manifest.representation.value_counts().to_dict() == {"relative": 157, "calibrated": 69}
    assert set(manifest.loc[manifest.representation.eq("calibrated"), "feature"]) == set(calibrated_features)
    assert not set(features) & DERIVED
    for row in manifest.itertuples(index=False):
        raw = calibrated[row.feature] if row.feature in calibrated_features else original[row.feature]
        invalid = int(raw.lt(0).sum()) if row.feature in calibrated_features else 0
        assert row.original_missing_count == int(raw.isna().sum())
        assert row.original_1csv_missing_count == int(original[row.feature].isna().sum())
        assert row.negative_invalid_count == invalid
        assert row.final_missing_count == int(expected[row.feature].isna().sum())
        assert row.zero_count == int(expected[row.feature].eq(0).sum())
    assert int(manifest.negative_invalid_count.sum()) == negative_count
```

```
    assert not np.isinf(expected.to_numpy()).any()
    calibrated_values = expected[calibrated_features].to_numpy()
    assert (calibrated_values[np.isfinite(calibrated_values)] >= 0).all()
    assert stored.isna().equals(expected.isna())
    context = {"meta": meta, "x": expected, "y": y,
               "features": features, "calibrated_features": calibrated_feature
s}
    return context, {"rows": len(expected), "features": len(features),
                     "calibrated": len(calibrated_features), "relative": 157,
                     "negative_calibrated_invalidated": negative_count,
                     "missing_cells_preserved": int(expected.isna().sum().sum(
))}


def supported(values, empirical):
    positions = np.searchsorted(empirical, values)
    left = empirical[np.clip(positions - 1, 0, len(empirical) - 1)]
    right = empirical[np.clip(positions, 0, len(empirical) - 1)]
    return np.isclose(values, left, rtol=1e-9, atol=1e-11) | np.isclose(
        values, right, rtol=1e-9, atol=1e-11)


def check_generation(context):
    x, features = context["x"], context["features"]
    folder = OUT / "generation"
    summary = read_json(folder / "summary.json")
    model = joblib.load(folder / "fitted_model.joblib")
    assert model.columns_ == features and model.n_samples_ == len(x)
    close(model.median_, np.nanmedian(x, axis=0), "Full-fit median differs fro
m training data")
    training = x.fillna(pd.Series(model.median_, index=features)).to_numpy()
    for j in range(len(features)):
        close(model.empirical_values_[j], np.unique(training[:, j]), "Empirica
l support differs from training")
    tables, copies, rows = [], 0, 0
    for style in GENERATION_STYLES:
        frame = pd.read_csv(folder / f"generated_{style.replace('/', '-')}.csv
")
        assert len(frame) == 300 and frame.sample_id.is_unique
        assert frame.target_style.eq(style).all()
        assert frame.columns.tolist() == ["sample_id", "target_style"] + featu
res
        fake = frame[features].to_numpy()
        assert np.isfinite(fake).all()
        assert frame[context["calibrated_features"]].ge(0).all().all()
        assert (fake >= training.min(axis=0) - TOL).all()
        assert (fake <= training.max(axis=0) + TOL).all()
        for j in range(len(features)):
            assert supported(fake[:, j], model.empirical_values_[j]).all(), f"
Outside empirical support: {style}/{features[j]}"
        copied = np.any(np.all(np.isclose(fake[:, None, :], training[None, :,
:],
                                          rtol=1e-10, atol=1e-12), axis=2), axis
=1)
        copies += int(copied.sum())
        rows += len(frame)
        assert not copied.any(), f"Whole training-row copy generated for {styl
e}"
        tables.append(frame)
    generated = pd.concat(tables, ignore_index=True)
    assert generated.sample_id.is_unique and rows == summary["full_generation_
rows"]
```

```
    close(copies / rows, summary["full_generation_copy_rate"], "Generation cop
y-rate summary")
    diagnostics = pd.read_csv(folder / "generated_diagnostics.csv")
    assert set(diagnostics.sample_id) == set(generated.sample_id)
    assert not diagnostics.exact_training_copy.any()
    context["generated"] = generated
    return {"styles": list(GENERATION_STYLES), "rows_per_style": 300, "rows":
rows,
            "whole_training_row_copies": copies, "calibrated_nonnegative": Tru
e,
            "marginal_training_support": True, "discrete_empirical_support": T
rue}


def check_generation_cv(context):
    folder = OUT / "generation"
    meta, x = context["meta"], context["x"]
    summary = read_json(folder / "summary.json")
    assignments = pd.read_csv(folder / "cv_assignments.csv")
    metrics = pd.read_csv(folder / "cv_metrics.csv")
    assert assignments.role.eq("test").all()
    assert not assignments.duplicated(["repeat", "row_index"]).any()
    assert set(assignments.repeat) == {1, 2} and set(assignments.fold) == {1,
2, 3}
    assert len(assignments) == 2 * len(meta)
    assert (assignments.groupby(["repeat", "row_index"]).size() == 1).all()
    assert assignments.beer.tolist() == assignments.row_index.map(meta.beer).t
olist()
    assert assignments["style"].tolist() == assignments.row_index.map(meta.tas
ting_category_fine).tolist()
    methods = {"conditional_copula", "style_bootstrap", "unconditional_copula"
}
    keys = ["repeat", "fold", "mc", "style", "method"]
    assert not metrics.duplicated(keys).any()
    assert set(metrics.method) == methods and set(metrics["style"]) == set(GEN
ERATION_STYLES)
    assert set(metrics.mc) == {0, 1, 2}
    assert len(metrics) == 2 * 3 * 3 * len(GENERATION_STYLES) * len(methods)
    assert (metrics.groupby(["repeat", "fold", "style", "method"]).size() == 3
).all()
    assert metrics.generated_n.eq(300).all()
    assert metrics.mean_strength.eq(summary["mean_strength"]).all()
    assert metrics.cov_strength.eq(summary["cov_strength"]).all()
    for repeat, seed in enumerate(summary["cv_repeat_seeds"], 1):
        splitter = StratifiedKFold(3, shuffle=True, random_state=seed)
        for fold, (train, test) in enumerate(splitter.split(x, meta.tasting_ca
tegory_fine), 1):
            stored = assignments[assignments.repeat.eq(repeat) & assignments.f
old.eq(fold)]
            assert set(stored.row_index) == set(test)
            group = metrics[metrics.repeat.eq(repeat) & metrics.fold.eq(fold)]
            assert group.train_n.eq(len(train)).all() and group.split_seed.eq(
seed).all()
            for style in GENERATION_STYLES:
                part = group[group["style"].eq(style)]
                assert part.style_train_n.eq(meta.tasting_category_fine.iloc[t
rain].eq(style).sum()).all()
                assert part.holdout_style_n.eq(meta.tasting_category_fine.iloc
[test].eq(style).sum()).all()
    fold_table = pd.read_csv(folder / "cv_fold_means.csv")
    fold_keys = ["repeat", "fold", "style", "method"]
    value_columns = [column for column in fold_table if column not in fold_key
```

```
s]
    assert np.isfinite(metrics[value_columns].to_numpy()).all()
    expected_fold = metrics.groupby(fold_keys, as_index=False)[value_columns].mean()
    same_table(fold_table, expected_fold, fold_keys, value_columns, "CV Monte Carlo fold means")
    expected_summary = expected_fold.groupby(["style", "method"])[value_columns].agg(["mean", "std"])
    expected_summary.columns = [f"{metric}_{stat}" for metric, stat in expected_summary.columns]
    expected_summary = expected_summary.reset_index()
    stored_summary = pd.read_csv(folder / "cv_summary.csv")
    same_table(stored_summary, expected_summary, ["style", "method"],
               [column for column in expected_summary if column not in {"style", "method"}],
               "CV six-split summary")
    assert summary["validation_records"] == len(metrics)
    return {"repeats": 2, "folds": 3, "mc_per_method_fold": 3,
            "every_sample_test_once_per_repeat": True, "metric_records": len(metrics),
            "fold_and_overall_summaries_reconciled": True,
            "scope": "Saved split assignments, schema and aggregation; no claim of independent real experiments"}


def check_sensory(context):
    meta, x, y = context["meta"], context["x"], context["y"]
    folder = OUT / "sensory"
    overall = pd.read_csv(folder / "metrics_overall.csv")
    by_target = pd.read_csv(folder / "metrics_by_target.csv")
    by_fold = pd.read_csv(folder / "metrics_by_fold.csv")
    expected_folds = np.zeros(len(x), dtype=int)
    for fold, (_, test) in enumerate(KFold(5, shuffle=True, random_state=SEED).split(x), 1):
        expected_folds[test] = fold
    targets, folds = [], []
    for row in overall.itertuples(index=False):
        frame = pd.read_csv(folder / f"oof_{row.model}.csv", dtype={"beer_id": str})
        pd.testing.assert_frame_equal(frame[KEYS], meta, check_dtype=False)
        np.testing.assert_array_equal(frame.fold, expected_folds)
        predictions = frame[y.columns].to_numpy()
        assert np.isfinite(predictions).all()
        values = score(y, predictions)
        close([row.mae, row.rmse, row.macro_r2], list(values.values()), f"OOF metrics: {row.model}")
        for j, target in enumerate(y):
            targets.append({"model": row.model, "target": target,
                            **score(y.iloc[:, j], predictions[:, j]),
                            "spearman": float(spearmanr(y.iloc[:, j], predictions[:, j]).statistic)})
        for fold in range(1, 6):
            test = expected_folds == fold
            folds.append({"model": row.model, "fold": fold,
                          **score(y.loc[test], predictions[test])})
            if row.model == "mean":
                close(predictions[test], np.broadcast_to(y.loc[~test].mean(), predictions[test].shape),
                      "Mean OOF baseline must use training-fold targets")
    same_table(by_target, pd.DataFrame(targets), ["model", "target"],
               ["mae", "rmse", "macro_r2", "spearman"], "Sensory target OOF metrics")
```

```
    same_table(by_fold, pd.DataFrame(folds), ["model", "fold"],
               ["mae", "rmse", "macro_r2"], "Sensory fold OOF metrics")
    sources = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    proxy = joblib.load(folder / "transfer_proxy.joblib")
    ensemble = joblib.load(folder / "stale_bootstrap.joblib")
    np.testing.assert_array_equal(proxy["train_global_indices"], train)
    np.testing.assert_array_equal(proxy["heldout_global_indices"], sources)
    np.testing.assert_array_equal(ensemble["train_global_indices"], train)
    np.testing.assert_array_equal(ensemble["excluded_global_indices"], sources
)
    assert len(train) == 239 and len(sources) == 11 and len(ensemble["models"]
) == 40
    assert proxy["features"] == ensemble["features"] == x.columns.tolist()
    assert proxy["targets"] == y.columns.tolist()
    indices = np.asarray(ensemble["bootstrap_indices"])
    assert indices.shape == (40, len(train)) and np.isin(indices, train).all()
    assert not np.isin(indices, sources).any()
    assert ensemble["selection_model_indices"] == list(range(30))
    assert ensemble["audit_model_indices"] == list(range(30, 40))
    with np.load(folder / "stale_bootstrap_indices.npz") as saved:
        np.testing.assert_array_equal(saved["indices"], indices)
        np.testing.assert_array_equal(saved["source_beer"], meta.beer)
    heldout_prediction = proxy["pipeline"].predict(x.iloc[sources])
    heldout = pd.read_csv(folder / "transfer_pils_heldout_predictions.csv")
    np.testing.assert_array_equal(heldout.beer, meta.beer.iloc[sources])
    close(heldout[y.columns], heldout_prediction, "Transfer proxy saved source
 predictions")
    heldout_metrics = pd.read_csv(folder / "transfer_pils_heldout_metrics.csv"
).set_index("model")
    for name, prediction in [("transfer_proxy", heldout_prediction),
                             ("non_pils_mean", np.broadcast_to(y.iloc[train].m
ean(), heldout_prediction.shape))]:
        close(heldout_metrics.loc[name, ["mae", "rmse", "macro_r2"]],
              list(score(y.iloc[sources], prediction).values()), "Held-out Pil
s sensory metrics")
    context.update({"source_rows": sources, "transfer_train": train,
                    "proxy": proxy, "ensemble": ensemble})
    stale = pd.DataFrame(targets)
    stale = stale[stale.target.eq("stale_hops")].set_index("model")
    return {"oof_models": len(overall), "oof_folds": 5, "targets": len(y.colum
ns),
            "excluded_sources": len(sources), "transfer_training_rows": len(tr
ain),
            "bootstrap_models": len(ensemble["models"]),
            "bootstrap_resample_shape": list(indices.shape),
            "stale_hops_oof_r2": float(stale.loc["extra_trees", "macro_r2"]),
            "stale_hops_oof_rmse": float(stale.loc["extra_trees", "rmse"]),
            "stale_hops_oof_mean_rmse": float(stale.loc["mean", "rmse"])}


def chemical_caps(source, thresholds, kind):
    result = {}
    for feature in DEFECT_FIELDS:
        value = float(source[feature].iloc[0])
        threshold = thresholds.at[feature, f"threshold_{kind}"]
        result[feature] = max(value, float(threshold)) if pd.notna(threshold)
else value
    return result


def chemical_flags(frame, caps):
```

```
    values = frame[list(caps)].to_numpy()
    limits = np.array(list(caps.values()))
    return np.isfinite(values).all(axis=1) & (values >= 0).all(axis=1) & (valu
es <= limits + TOL).all(axis=1)


def check_transfer(context):
    meta, x, y = context["meta"], context["x"], context["y"]
    source_rows, train = context["source_rows"], context["transfer_train"]
    folder = OUT / "transfer"
    summary = read_json(folder / "summary.json")
    saved = joblib.load(folder / "transfer_copula.joblib")
    copula = saved["copula"]
    np.testing.assert_array_equal(saved["training_rows"], train)
    np.testing.assert_array_equal(saved["source_rows"], source_rows)
    assert copula.columns_ == x.columns.tolist() and copula.n_samples_ == len(
train)
    close(copula.median_, np.nanmedian(x.iloc[train], axis=0), "Source-exclude
d copula medians")
    thresholds = pd.read_excel(data_dir() / "8.xlsx", sheet_name="Sensory thre
sholds").set_index("field_name_R")
    assert pd.isna(thresholds.at["X.E..2.nonenal", "threshold_median"])
    target_rows = np.flatnonzero(meta.tasting_category_fine.eq(summary["target
_style"]))
    target = x.iloc[target_rows]
    target_z = copula.transform(target)
    dimensions = x.shape[1]
    target_pairs = cdist(target_z, target_z) / np.sqrt(dimensions)
    np.fill_diagonal(target_pairs, np.inf)
    loo_nn = target_pairs.min(axis=1)
    support_limit = float(np.quantile(loo_nn, summary["support"]["quantile"]))
    close(support_limit, summary["support"]["limit"], "Transfer target support
 limit")
    support_csv = pd.read_csv(folder / "target_support_reference.csv")
    np.testing.assert_array_equal(support_csv.beer, meta.beer.iloc[target_rows
])
    close(support_csv.loo_nn_rms, loo_nn, "Tripel leave-one-out support refere
nce")
    report = pd.read_csv(folder / "transfer_summary.csv")
    spectra = pd.read_csv(folder / "transferred_spectra.csv").set_index("trans
fer_id")
    candidates = pd.read_csv(folder / "candidate_diagnostics.csv")
    paired_csv = pd.read_csv(folder / "stale_paired_deltas.csv")
    chemicals = pd.read_csv(folder / "defect_checks.csv")
    profiles = pd.read_csv(folder / "sensory_before_after.csv")
    source_spectra = pd.read_csv(folder / "source_spectra.csv")
    np.testing.assert_array_equal(source_spectra.beer, meta.beer.iloc[source_r
ows])
    close(source_spectra[x.columns], x.iloc[source_rows], "Transfer raw source
 spectra")
    assert not report.duplicated(["source_beer", "mode", "lambda"]).any()
    assert spectra.index.is_unique
    selected_report = report[report.candidate_index.notna()].copy()
    assert set(spectra.index) == set(selected_report.transfer_id)
    assert np.isfinite(spectra[x.columns].to_numpy()).all()
    assert spectra[context["calibrated_features"]].ge(0).all().all()
    assert set(report.source_beer) == set(meta.beer.iloc[source_rows])
    assert set(report["lambda"]) == set(summary["lambdas"])
    assert report.is_default_policy.equals(report["lambda"].eq(summary["defaul
t_lambda"]))
    models = context["ensemble"]["models"]
    source_frame = x.iloc[source_rows].fillna(x.iloc[train].median())
```

```
    source_predictions = np.vstack([model.predict(source_frame) for model in m
odels])
    selected_predictions = np.vstack([model.predict(spectra[x.columns]) for mo
del in models])
    source_lookup = {int(meta.beer.iloc[index]): position for position, index
in enumerate(source_rows)}
    center = target_z.mean(axis=0)
    training_min, training_max = x.iloc[train].min().to_numpy(), x.iloc[train]
.max().to_numpy()
    max_quantile_error = 0.0
    max_distance_error = 0.0
    max_nn_error = 0.0
    argmin_checks = 0
    for source_beer, group in candidates.groupby("source_beer"):
        assert len(group) == summary["n_candidates_per_source"]
        assert set(group.candidate_index) == set(range(summary["n_candidates_p
er_source"]))
        flags = (group.support_ok & group.nontrivial & group.target_improvemen
t_ok
                 & group.chemical_median_ok & group.selection_proxy_ok)
        assert flags.equals(group.selection_feasible)
        assert group.selection_proxy_ok.equals(group.selection_paired_delta_q9
5.le(TOL))
        assert group.nontrivial.equals(group.change_latent_rms.ge(summary["min
imum_latent_rms_change"]))
        assert group.target_improvement_ok.equals(group.target_improvement.ge(
summary["minimum_target_improvement"]))
        assert group.support_ok.equals(group.target_nn_rms.le(support_limit +
TOL) & group.marginal_support)
    for _, row in selected_report.iterrows():
        selected = spectra.loc[[row.transfer_id], x.columns]
        source_position = source_lookup[int(row.source_beer)]
        source = source_frame.iloc[[source_position]]
        source_z, selected_z = copula.transform(source), copula.transform(sele
cted)
        original_source = x.iloc[[source_rows[source_position]]]
        assert original_source[list(DEFECT_FIELDS)].notna().all().all()
        caps_median = chemical_caps(original_source, thresholds, "median")
        caps_mean = chemical_caps(original_source, thresholds, "mean")
        chemical_median = bool(chemical_flags(selected, caps_median)[0])
        chemical_mean = bool(chemical_flags(selected, caps_mean)[0])
        assert chemical_median == row.chemical_median_ok and chemical_mean ==
row.chemical_mean_ok
        position = spectra.index.get_loc(row.transfer_id)
        deltas = selected_predictions[:, position] - source_predictions[:, sou
rce_position]
        selection_q95, audit_q95 = float(np.quantile(deltas[:30], .95)), float
(np.quantile(deltas[30:], .95))
        max_quantile_error = max(max_quantile_error, abs(selection_q95 - row.s
election_paired_delta_q95),
                                 abs(audit_q95 - row.audit_paired_delta_q95))
        close([selection_q95, audit_q95],
              [row.selection_paired_delta_q95, row.audit_paired_delta_q95], "S
elected paired quantiles")
        assert bool(audit_q95 <= TOL) == row.audit_proxy_ok
        for ensemble_name, values in [("selection", deltas[:30]), ("audit", de
ltas[30:])]:
            saved_deltas = paired_csv[paired_csv.transfer_id.eq(row.transfer_i
d)
                                      & paired_csv.ensemble.eq(ensemble_name)].
sort_values("model_index")
            np.testing.assert_array_equal(saved_deltas.model_index, np.arange(
```

```
    len(values)))
            close(saved_deltas.paired_delta, values, "Saved per-model paired d
ifferences")
        before = float(copula.distance(source, summary["target_style"])[0])
        after = float(copula.distance(selected, summary["target_style"])[0])
        near = float(cdist(selected_z, target_z).min() / np.sqrt(dimensions))
        change = float(np.linalg.norm(selected_z - source_z) / np.sqrt(dimensi
ons))
        improvement = 1 - after / max(before, 1e-8)
        max_distance_error = max(max_distance_error, abs(after - row.target_di
stance_after))
        max_nn_error = max(max_nn_error, abs(near - row.target_nn_after))
        close([before, after, near, change, improvement],
              [row.target_distance_before, row.target_distance_after, row.targ
et_nn_after,
               row.change_latent_rms, row.target_improvement], "Selected trans
fer geometry")
        assert near <= support_limit + TOL
        assert (selected.to_numpy() >= training_min - TOL).all()
        assert (selected.to_numpy() <= training_max + TOL).all()
        assert improvement >= summary["minimum_target_improvement"]
        assert change >= summary["minimum_latent_rms_change"]
        scale = max(float(np.linalg.norm(source_z[0] - center) / np.sqrt(dimen
sions)), 1e-8)
        close(after / max(before, 1e-8) + row["lambda"] * change / scale, row.
objective,
              "Selected fixed objective")
        if row["mode"] == "protected":
            assert chemical_median and selection_q95 <= TOL
            assert bool(audit_q95 <= TOL) == row.all_model_checks_passed
            expected_status = "model_checks_passed" if audit_q95 <= TOL else "
resampling_audit_failed"
            assert row.status == expected_status
            feasible = candidates[candidates.source_beer.eq(row.source_beer) &
 candidates.selection_feasible]
            objective = feasible.target_distance / max(before, 1e-8) + row["la
mbda"] * feasible.change_latent_rms / scale
            expected_index = int(feasible.iloc[np.argmin(objective)].candidate
_index)
            assert int(row.candidate_index) == expected_index, "Audit changed
the selected candidate"
            argmin_checks += 1
        else:
            assert row.status == "baseline_only" and not row.all_model_checks_
passed
        check_rows = chemicals[chemicals.transfer_id.eq(row.transfer_id)].set_
index("feature")
        assert set(check_rows.index) == set(DEFECT_FIELDS)
        for feature in DEFECT_FIELDS:
            close([check_rows.at[feature, "before"], check_rows.at[feature, "a
fter"],
                   check_rows.at[feature, "median_upper_bound"], check_rows.at
[feature, "mean_upper_bound"]],
                  [original_source[feature].iloc[0], selected[feature].iloc[0]
,
                   caps_median[feature], caps_mean[feature]], "Defect concentr
ation audit")
            for kind in ["median", "mean"]:
                threshold = thresholds.at[feature, f"threshold_{kind}"]
                for phase, value in [("before", original_source[feature].iloc[
0]),
                                     ("after", selected[feature].iloc[0])]:
```

```
                    excess = max(value / threshold - 1, 0) if pd.notna(thresho
ld) else np.nan
                    close(check_rows.at[feature, f"{kind}_excess_{phase}"], ex
cess, "Defect excess audit")
        for phase, values in [("source", source), ("transferred", selected)]:
            stored_profile = profiles[profiles.transfer_id.eq(row.transfer_id)
 & profiles.phase.eq(phase)]
            assert len(stored_profile) == 1
            close(stored_profile[y.columns], context["proxy"]["pipeline"].pred
ict(values),
                  "Transfer relative sensory profile")
    assert len(paired_csv) == len(spectra) * 40 and len(chemicals) == len(spec
tra) * 4
    assert len(profiles) == len(spectra) * 2
    for _, row in report[report.candidate_index.isna()].iterrows():
        if row.status == "no_candidate_found":
            assert not candidates[candidates.source_beer.eq(row.source_beer)].
selection_feasible.any()
        elif row.status == "source_defect_unverifiable":
            original = x.iloc[[source_rows[source_lookup[int(row.source_beer)]
]]][list(DEFECT_FIELDS)]
            assert original.isna().any().any() or original.lt(0).any().any()
        else:
            raise AssertionError(f"Unrecognized missing-candidate status: {row
.status}")
    default = report[report.is_default_policy & report["mode"].eq("protected")
]
    default_counts = {
        "n_sources": len(default),
        "n_candidates_selected": int(default.status.isin(["model_checks_passed
", "resampling_audit_failed"]).sum()),
        "n_model_checks_passed": int(default.all_model_checks_passed.sum()),
        "n_audit_failed": int(default.status.eq("resampling_audit_failed").sum
()),
        "n_no_candidate": int(default.status.eq("no_candidate_found").sum()),
        "n_source_unverifiable": int(default.status.eq("source_defect_unverifi
able").sum()),
        "n_all_checks_also_pass_mean_thresholds_same_spectra": int(
            (default.all_model_checks_passed & default.chemical_mean_ok.fillna
(False)).sum()),
    }
    assert default_counts == summary["default_policy"], "Default transfer summ
ary differs from CSV"
    assert len(default) == len(source_rows)
    context["default_transfer_counts"] = default_counts
    return {"selected_spectra_checked": len(spectra), "source_training_rows":
len(train),
            "protected_fixed_argmin_checks": argmin_checks,
            "selection_models": 30, "audit_models": 10,
            "maximum_paired_quantile_error": max_quantile_error,
            "maximum_target_distance_error": max_distance_error,
            "maximum_full_space_nn_error": max_nn_error,
            "default_policy": default_counts,
            "scope": "Chemical constraints and uncalibrated model diagnostics;
 no actual taste guarantee"}


def check_report_artifacts(context):
    path = OUT / "generated_sensory_profiles.csv"
    assert path.is_file(), f"Missing deliverable: {path}"
    report = SOLUTION / "docs/q3_results.md"
    assert report.is_file() and report.stat().st_size > 100, f"Missing or empt
```

```
y deliverable: {report}"
    generated, y = context["generated"], context["y"]
    profiles = pd.read_csv(path)
    assert len(profiles) == len(generated) and profiles.sample_id.is_unique
    assert set(profiles.sample_id) == set(generated.sample_id)
    assert set(y.columns).issubset(profiles.columns)
    final = joblib.load(OUT / "sensory/sensory_model.joblib")
    assert final["features"] == context["features"] and final["targets"] == y.columns.tolist()
    expected = final["pipeline"].predict(generated[context["features"]])
    actual = profiles.set_index("sample_id").loc[generated.sample_id, y.columns]
    assert np.isfinite(actual.to_numpy()).all()
    close(actual, expected, "Generated frozen-model sensory profiles")
    return {"generated_sensory_rows": len(profiles), "sensory_dimensions": len(y.columns),
            "frozen_model_predictions_reconciled": True, "results_report_exists": True}


def main():
    start = perf_counter()
    checks = []
    result = {"status": "running", "checks": checks,
              "scope": "Source provenance, saved-output integrity and independently recomputed numerical consistency"}
    active_check = "source_hashes_before"
    try:
        checks.append({"name": active_check, "status": "passed", "details": check_hashes()})
        active_check = "hybrid_data_contract"
        context, details = load_contract()
        checks.append({"name": active_check, "status": "passed", "details": details})
        for name, operation in [("generation_training_support", check_generation),
                                ("generation_repeated_cv", check_generation_cv),
                                ("sensory_oof_and_source_exclusion", check_sensory),
                                ("transfer_constraints_and_selection", check_transfer),
                                ("report_and_generated_sensory", check_report_artifacts)]:
            active_check = name
            details = operation(context)
            checks.append({"name": name, "status": "passed", "details": details})
            print(f"Verified: {name}", flush=True)
        active_check = "source_hashes_after"
        checks.append({"name": active_check, "status": "passed", "details": check_hashes()})
        result["status"] = "passed"
        result["limitations"] = [
            "Numerical consistency does not establish model adequacy or physical brewing feasibility.",
            "Bootstrap selection and audit groups share real training data and have no calibrated outcome coverage.",
            "Sensory values are relative attachment-standardized predictions, not recovered raw 0-6 panel scores.",
        ]
    except Exception as error:
```

```
        result["status"] = "failed"
        result["failed_check"] = active_check
        result["error"] = f"{type(error).__name__}: {error}"
        raise
    finally:
        result["elapsed_seconds"] = perf_counter() - start
        OUT.mkdir(parents=True, exist_ok=True)
        (OUT / "verification.json").write_text(
            json.dumps(result, ensure_ascii=False, indent=2, allow_nan=False)
+ "\n", encoding="utf-8", newline="\n")
        print(json.dumps(result, ensure_ascii=False, indent=2, allow_nan=False
), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/11_q3_generation_optimized.py

SHA-256: 4ec959714acc717e509e415faa4401c093c7c3b783edf08bf790c8e5bad498fe

```
"""Evaluate nested, style-margin generation against frozen method baselines."""
import os

for _thread_variable in ("OPENBLAS_NUM_THREADS", "OMP_NUM_THREADS", "MKL_NUM_THREADS",
                         "VECLIB_MAXIMUM_THREADS", "NUMEXPR_NUM_THREADS"):
    os.environ[_thread_variable] = "1"

import importlib
import json
import time

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from sklearn.model_selection import StratifiedKFold
from threadpoolctl import threadpool_limits

from common import SOLUTION
from q3_data import load_q3_data
from q3_generator_optimized import (CANDIDATE_METHODS, EVALUATION_STYLES,
                                    MAX_INNER_MATCH_FRACTION, MIN_INNER_NN_RATIO,
                                    OptimizedStyleGenerator, SMOOTHING_NOISE)


REFERENCE = importlib.import_module("07_q3_generation")
OUT = SOLUTION / "outputs" / "q3_optimized" / "generation"
OUTER_SEEDS = [20261123, 20262123]
N_GENERATED = 300
MC_REPEATS = 2
METHODS = ["nested_selected", *CANDIDATE_METHODS, "style_bootstrap"]
METRICS = [*REFERENCE.METRICS, "zero_rate_mae", "zero_rate_mae_training_zero_features",
           "zero_rate_mae_calibrated", "nearest_equal_feature_fraction",
           "nearest_equal_feature_fraction_p95", "generated_pair_nn_median",
           "observed_training_copy_rate"]


def extra_metrics(reference, train, heldout, generated, calibrated_columns):
    training = reference.impute(train)
    real = reference.impute(heldout)
    fake = reference.impute(generated)
    zero_error = np.abs(np.mean(real == 0, axis=0) - np.mean(fake == 0, axis=0))
    has_training_zero = np.any(training == 0, axis=0)
    calibrated_indices = [generated.columns.get_loc(c) for c in calibrated_columns]
    fake_z, training_z = reference.transform(generated), reference.transform(train)
    distances = cdist(fake_z, training_z) / np.sqrt(fake_z.shape[1])
    closest = distances.argmin(axis=1)
    equal_fraction = np.isclose(fake, training[closest], rtol=1e-10, atol=1e-12).mean(axis=1)
    pairwise = cdist(fake_z, fake_z) / np.sqrt(fake_z.shape[1])
    np.fill_diagonal(pairwise, np.inf)
    observed = train.to_numpy(dtype=float)
```

```
    copied_observed = (np.isclose(fake[:, None, :], observed[None, :, :],
                                  rtol=1e-10, atol=1e-12)
                       | np.isnan(observed)[None, :, :]).all(axis=2).any(axis=1)
    return {"zero_rate_mae": float(zero_error.mean()),
            "zero_rate_mae_training_zero_features": float(zero_error[has_training_zero].mean())
            if has_training_zero.any() else 0.0,
            "training_zero_features": int(has_training_zero.sum()),
            "zero_rate_mae_calibrated": float(zero_error[calibrated_indices].mean()),
            "nearest_equal_feature_fraction": float(np.median(equal_fraction)),
            "nearest_equal_feature_fraction_p95": float(np.quantile(equal_fraction, 0.95)),
            "observed_training_copy_rate": float(copied_observed.mean()),
            "generated_pair_nn_median": float(np.median(pairwise.min(axis=1)))}


def fold_summary(records):
    folds = records.groupby(["repeat", "fold", "style", "method"], as_index=False)[METRICS].mean()
    summary = folds.groupby(["style", "method"])[METRICS].agg(["mean", "std"])
    summary.columns = [f"{metric}_{stat}" for metric, stat in summary.columns]
    return folds, summary.reset_index()


def nested_validation(meta, x, styles, calibrated):
    records, assignments, selections, inner_details, margins = [], [], [], [], []
    for repeat, seed in enumerate(OUTER_SEEDS, start=1):
        outer = StratifiedKFold(n_splits=3, shuffle=True, random_state=seed)
        for fold, (train, test) in enumerate(outer.split(x, styles), start=1):
            print(f"Optimized generation repeat={repeat}, fold={fold}", flush=True)
            train_x, train_labels = x.iloc[train], styles.iloc[train]
            selection_seed = seed + fold * 100000
            generator = OptimizedStyleGenerator(selection_seed=selection_seed).fit(train_x, train_labels)
            reference = generator.fitted_candidates_["legacy_copula"]
            pca, pc_scale = REFERENCE.pca_coordinates(reference, train_x)
            for row in generator.selection_table_:
                selections.append({"repeat": repeat, "fold": fold, "selection_seed": selection_seed, **row})
            details = generator.inner_scores_.copy()
            details.insert(0, "outer_repeat", repeat)
            details.insert(1, "outer_fold", fold)
            inner_details.append(details)
            assignments.extend({"repeat": repeat, "fold": fold, "row_index": int(i),
                "beer": meta.beer.iloc[i], "style": styles.iloc[i], "role": "test"} for i in test)
            for style_index, style in enumerate(EVALUATION_STYLES):
                style_train = train_x.loc[train_labels == style]
                heldout = x.iloc[test].loc[styles.iloc[test] == style]
                for mc in range(MC_REPEATS):
                    sample_seed = seed + fold * 10000 + style_index * 100 + mc
                    draws = {method: model.sample(style, N_GENERATED, sample_seed)
                             for method, model in generator.fitted_candidates_.items()}
```

```
                    draws["nested_selected"] = draws[generator.selected_methods_[style]]
                    bootstrap_indices = np.random.default_rng(sample_seed).integers(0, len(style_train), N_GENERATED)
                    draws["style_bootstrap"] = pd.DataFrame(reference.impute(style_train)[bootstrap_indices], columns=x.columns)
                    for method in METHODS:
                        generated = draws[method]
                        metrics, marginal = REFERENCE.evaluate(reference, train_x, style_train, heldout,
                                                               generated, pca, pc_scale)
                        records.append({"repeat": repeat, "fold": fold, "style": style,
                            "method": method, "selected_method": generator.selected_methods_[style]
                            if method == "nested_selected" else method,
                            "outer_seed": seed, "selection_seed": selection_seed,
                            "mc": mc, "sample_seed": sample_seed,
                            "train_n": len(train_x), "style_train_n": len(style_train),
                            "holdout_style_n": len(heldout), "generated_n": len(generated),
                            **metrics, **extra_metrics(reference, style_train, heldout, generated, calibrated)})
                        if mc == 0 and method in ("nested_selected", "legacy_copula", "style_bootstrap"):
                            margins.extend({"repeat": repeat, "fold": fold, "style": style,
                                "method": method, "feature": feature, "w1_iqr": float(value)}
                                for feature, value in zip(x.columns, marginal))
    return (pd.DataFrame(records), pd.DataFrame(assignments), pd.DataFrame(selections),
            pd.concat(inner_details, ignore_index=True), pd.DataFrame(margins))


def build_report(summary, selections, full_model, full_diag, elapsed):
    lines = ["# 第三问生成模型优化：局部风格边缘与嵌套选择", "",
        "运行日期：2026-10-23。使用 250 款啤酒、226 个混合特征（69 个校准字段与 157 个相对字段）。"
        "旧第三问结果完整保留，本轮文件单独位于 `outputs/q3_optimized/generation/`。", "",
        "## 优化针对的问题", "",
        "旧模型对全部风格共用单列经验边缘，并把小风格均值向全局收缩。Kriek、Lambic "
        "分别只有 10、11 款真实样本，风格差异可能在这两步被稀释。本轮把风格边缘与相关结构分开处理，"
        "保持小风格的观测边缘，仍用收缩相关矩阵共享信息。", "",
        "在查看本轮外层结果前固定三个候选：", "",
        "1. `style_margin_copula`：各风格分别拟合经验边缘和中秩正态分数；局部 Ledoit-Wolf "
        "相关以 n/(n+10) 的权重混合全部训练风格正态分数的共享相关。相关矩阵对角归一到 1，"
        "从零均值 Gaussian 抽样后用风格局部离散经验逆分布输出。",
        "2. `style_smoothed_mixture`：使用相同边缘和相关，从风格训练行的正态分数中抽一个中心，"
        "加标准差固定为 0.45 的相关 Gaussian 噪声；该噪声强度固定，不搜索近零扰动。",
        "3. `legacy_copula`：旧条件 copula 固定参数 (5,20)，作为可被内层选择的保守退路。", "",
        "各风格中位数补缺，风格某列全缺失时回退全部训练行中位数；所有统计量均只用当前训练折
```

```
。"
        "局部逆分布中的零拥有概率区间，Gaussian 候选在标准正态边缘下按期望再现风格训练零频率，"
        "平滑混合候选不保证相同频率。相对字段中的数值零也可能只是原表示的基准，不能全解释为物质不存在。", "",
        "## 训练内选择与外层检验", "",
        "外层采用预先固定的 20261123、20262123 两个种子的 22 风格分层 3 折划分。每个外层训练集"
        "再按全部训练风格做分层 2 折，分别为四个评价风格按内层平均五维能量距离选方法。"
        f"候选必须在每个内折都无整行复制、生成/真实留出近邻距离中位数比至少 {MIN_INNER_NN_RATIO:g}，"
        f"且与最近训练行相等的特征比例中位数不超过 {MAX_INNER_MATCH_FRACTION:.0%}；"
        "bootstrap 只作基准，不参与选择。复制检查同时比较完整补缺向量，以及仅比较训练行原本有观测"
        "的各列，避免不同中位数补缺掩盖原观测的整行复制。若无方法通过则退回旧模型，并保留失败诊断。", "",
        "内层和外层中，同一数据划分的所有候选、被选方法及 bootstrap 均使用同一旧 copula 在该训练折"
        "拟合的全局 rank 变换、五维 PCA 和 PCA 标准差作评价坐标。没有用各候选自己的局部 CDF 或 PCA "
        "计算可比较能量距离。每个外层方法每风格生成 300 行，使用两个 Monte Carlo 种子；"
        "先平均同折的 Monte Carlo，再汇总 6 个划分。", "",
        "本轮重新划分仍使用同一批已经分析过的 250 款啤酒。嵌套选择避免把本轮外层行直接用于选方法，"
        "但新种子不等于新增独立验证数据；不能把探索后的新划分称为独立确认性检验。", "",
        "|风格|方法|五维能量距离↓|平均边缘W1↓|边缘W1中位数↓|校准零频差↓|NN距离比|复制率|方差覆盖|",
        "|---|---|---:|---:|---:|---:|---:|---:|---:|"]
    names = {"nested_selected": "训练内选择", "legacy_copula": "旧copula", "style_bootstrap": "风格bootstrap",
             "style_margin_copula": "局部边缘copula", "style_smoothed_mixture": "平滑混合"}
    for _, row in summary.iterrows():
        lines.append(f"|{row['style']}|{names[row['method']]}|{row.energy_pca5_mean:.4f}|"
            f"{row.marginal_w1_iqr_mean:.4f}|{row.marginal_w1_iqr_median_mean:.4f}|"
            f"{row.zero_rate_mae_calibrated_mean:.4f}|{row.nn_ratio_mean:.3f}|"
            f"{row.copy_rate_mean:.1%}|{row.variance_coverage_0p5_2_mean:.1%}|")
    lines.extend(["", "边缘 W1 各列按外层全部训练行 IQR 标准化，零 IQR 回退训练极差、再回退 1。"
        "原始极端值仍会支配跨列均值，因此同时保留跨列中位数。能量距离使用经验 V 统计量，"
        "小留出集下偏高；所有方法的留出行和生成样本数相同。方差覆盖为生成/风格训练方差比处于"
        "[0.5,2] 的列占比，排除训练恒定列，并非总体方差置信覆盖。Spearman 相关差、"
        "最近训练行特征匹配比例与生成内近邻距离另存 CSV。", ""])
    for style in EVALUATION_STYLES:
        rows = summary.loc[summary['style'] == style].set_index('method')
        chosen, old, bootstrap = rows.loc['nested_selected'], rows.loc['legacy_copula'], rows.loc['style_bootstrap']
        change = (chosen.energy_pca5_mean / old.energy_pca5_mean - 1) * 100
        boot_change = (chosen.energy_pca5_mean / bootstrap.energy_pca5_mean - 1) * 100
        lines.append(f"- {style}：训练内选择相对旧 copula 的能量距离变化 {change:+.1f}%，"
                     f"相对 bootstrap 变化 {boot_change:+.1f}%；"
                     f"边缘 W1 中位数由 {old.marginal_w1_iqr_median_mean:.4f} 变为 {chosen.marginal_w1_iqr_median_mean:.4f}。")
    lines.extend(["", "## 选择稳定性与新颖性", "",
        "|风格|各外层训练集所选方法次数|全量训练内选择|", "|---|---|---|"])
```

```
    selected_rows = selections.loc[selections.selected]
    for style in EVALUATION_STYLES:
        counts = selected_rows.loc[selected_rows['style'] == style, 'method'].value_counts()
        count_text = "; ".join(f"{names[k]} {v}/6" for k, v in counts.items())
        lines.append(f"|{style}|{count_text}|{names[full_model.selected_methods_[style]]}|")
    lines.extend(["", "300 行只增加模拟精度，不增加真实风格证据。低复制率也不证明没有记忆训练分布，"
        "因此同时报告最近训练行距离、相等特征比例、生成内近邻距离和方差覆盖。"
        "内层新颖性门槛不能保证外层或全量抽样也通过；下面保留实测结果。", "",
        "|风格|全量所选方法|完全复制率|NN距离中位数|最近行匹配比例中位数|生成内NN中位数|",
        "|---|---|---:|---:|---:|---:|"])
    for style, group in full_diag.groupby('style'):
        lines.append(f"|{style}|{names[full_model.selected_methods_[style]]}|{group.exact_training_copy.mean():.1%}|"
                     f"{group.nn_target_style.median():.4f}|{group.equal_fraction_nearest_train.median():.3f}|"
                     f"{group.nn_generated.median():.4f}|")
    lines.extend(["", "## 使用与限制", "",
        "全量模型使用同样的训练内选择，保存为 `fullmodel.joblib`，接口为 "
        "`OptimizedStyleGenerator().fit(X,styles)` 及 `sample(style,n,seed)`，返回原 226 列顺序。"
        "另存四风格各 300 行生成谱（含 sample_id、target_style 元信息）、完整内层与外层记录、"
        "所有候选的外层比较，以及生成零频率诊断。", "",
        "全量 250 行模型只用于生成画像。迁移验证应在去除源风格之后重新拟合，不能复用这个全量"
        "生成器；迁移风格距离仍由旧模型定义，保证新旧比较的量尺一致。", "",
        "风格局部经验边缘不外推，也无法补足未观测的尾部；小风格中每列只有数个取值，"
        "相关与零频率估计不稳定。生成谱是化学目标组合，仍需酿造可行性、理化检测和感官实测验证。", "",
        "```bash", ".venv/bin/python solution_a/src/11_q3_generation_optimized.py", "```", "",
        f"运行耗时约 {elapsed:.1f} 秒，线性代数线程固定为 1。", ""])
    (SOLUTION / 'docs' / 'q3_generation_optimized.md').write_text('\n'.join(lines), encoding='utf-8', newline="\n")


def main():
    started = time.perf_counter()
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, _, manifest = load_q3_data()
    styles = meta.tasting_category_fine
    calibrated = manifest.loc[manifest.representation == 'calibrated', 'feature'].tolist()
    records, assignments, selections, inner_details, margins = nested_validation(meta, x, styles, calibrated)
    records.to_csv(OUT / 'cv_metrics.csv', index=False, lineterminator="\n")
    assignments.to_csv(OUT / 'cv_assignments.csv', index=False, lineterminator="\n")
    selections.to_csv(OUT / 'inner_selection_outer.csv', index=False, lineterminator="\n")
    inner_details.to_csv(OUT / 'inner_scores_outer.csv', index=False, lineterminator="\n")
    margins.to_csv(OUT / 'cv_marginal_w1_by_feature.csv', index=False, lineterminator="\n")
    folds, summary = fold_summary(records)
    folds.to_csv(OUT / 'cv_fold_means.csv', index=False, lineterminator="\n")
    summary.to_csv(OUT / 'cv_summary.csv', index=False, lineterminator="\n")
    mc = records.groupby(['repeat', 'fold', 'style', 'method'])[METRICS].std()
```

```
.reset_index()
    mc.to_csv(OUT / 'cv_monte_carlo_std.csv', index=False, lineterminator="\n"
)
    print('Fitting final optimized generator on all 250 rows', flush=True)
    full_model = OptimizedStyleGenerator(selection_seed=OUTER_SEEDS[0]).fit(x,
 styles)
    joblib.dump(full_model, OUT / 'fullmodel.joblib', compress=3)
    full_model.inner_scores_.to_csv(OUT / 'inner_scores_full.csv', index=False
, lineterminator="\n")
    pd.DataFrame(full_model.selection_table_).to_csv(OUT / 'inner_selection_fu
ll.csv', index=False, lineterminator="\n")
    pd.DataFrame([{'style': style, 'method': method} for style, method in full
_model.selected_methods_.items()]).to_csv(
        OUT / 'full_selected_methods.csv', index=False, lineterminator="\n")
    reference = full_model.fitted_candidates_['legacy_copula']
    full_diags, zero_rows = [], []
    for i, style in enumerate(EVALUATION_STYLES):
        generated = full_model.sample(style, N_GENERATED, OUTER_SEEDS[0] + 900
000 + i)
        generated.insert(0, 'sample_id', [f"optimized_{REFERENCE.safe_style(st
yle)}_{j:03d}" for j in range(1, N_GENERATED+1)])
        generated.insert(1, 'target_style', style)
        generated.to_csv(OUT / f'generated_{REFERENCE.safe_style(style)}.csv',
 index=False, lineterminator="\n")
        style_x = x.loc[styles == style]
        generated_x = generated[x.columns]
        fake_z, style_z = reference.transform(generated_x), reference.transfor
m(style_x)
        pairwise = cdist(fake_z, fake_z) / np.sqrt(x.shape[1])
        np.fill_diagonal(pairwise, np.inf)
        target_distances = cdist(fake_z, style_z) / np.sqrt(x.shape[1])
        nn = target_distances.argmin(axis=1)
        equal = np.isclose(reference.impute(generated_x), reference.impute(sty
le_x)[nn],
                           rtol=1e-10, atol=1e-12).mean(axis=1)
        raw = style_x.to_numpy(dtype=float)
        observed_copy = (np.isclose(generated_x.to_numpy()[:, None, :], raw[No
ne, :, :],
                                    rtol=1e-10, atol=1e-12)
                         | np.isnan(raw)[None, :, :]).all(axis=2).any(axis=1)
        full_diags.append(pd.DataFrame({'sample_id': generated.sample_id, 'sty
le': style,
            'method': full_model.selected_methods_[style], 'nn_target_style':
target_distances.min(axis=1),
            'nn_generated': pairwise.min(axis=1), 'equal_fraction_nearest_trai
n': equal,
            'latent_style_distance': reference.distance(generated_x, style),
            'observed_training_copy': observed_copy,
            'exact_training_copy': target_distances.min(axis=1) < 1e-12}))
        for feature in x:
            zero_rows.append({'style': style, 'feature': feature,
                'style_observed_zero_fraction': float(style_x[feature].eq(0).s
um() / style_x[feature].notna().sum()),
                'generated_zero_fraction': float(generated[feature].eq(0).mean
())})
    full_diag = pd.concat(full_diags, ignore_index=True)
    full_diag.to_csv(OUT / 'generated_diagnostics.csv', index=False, linetermi
nator="\n")
    pd.DataFrame(zero_rows).to_csv(OUT / 'generated_zero_diagnostics.csv', ind
ex=False, lineterminator="\n")
    elapsed = time.perf_counter() - started
    result = {'date': '2026-10-23', 'n_real': len(x), 'n_features': x.shape[1]
```

```
,
        'outer_seeds': OUTER_SEEDS, 'outer_folds': 3, 'inner_folds': 2,
        'mc_repeats': MC_REPEATS, 'generated_n_each_draw': N_GENERATED,
        'candidate_methods': list(CANDIDATE_METHODS), 'smoothing_noise': SMOOTHING_NOISE,
        'selection_uses_outer_test': False, 'selection_metric': 'shared_training_reference_pca5_energy',
        'novelty_gates': {'minimum_inner_nn_ratio': MIN_INNER_NN_RATIO,
                          'maximum_inner_nearest_equal_fraction': MAX_INNER_MATCH_FRACTION,
                          'maximum_inner_copy_rate': 0.0,
                          'maximum_inner_observed_training_copy_rate': 0.0},
        'cv_records': len(records), 'full_generation_rows': len(full_diag),
        'full_selected_methods': {s: full_model.selected_methods_[s] for s in EVALUATION_STYLES},
        'full_generation_copy_rate': float(full_diag.exact_training_copy.mean()),
        'full_generation_observed_copy_rate': float(full_diag.observed_training_copy.mean()),
        'elapsed_seconds': elapsed,
        'limits': ['New outer seeds still reuse the previously explored real dataset',
                   'Small style samples and unstable inner selection',
                   'Local-margin methods use style-imputed support; legacy uses global training support',
                   'Chemical spectra are not validated brewing recipes']}
    (OUT / 'summary.json').write_text(json.dumps(result, ensure_ascii=False, indent=2), encoding='utf-8', newline="\n")
    build_report(summary, selections, full_model, full_diag, elapsed)
    print(json.dumps(result, ensure_ascii=False, indent=2), flush=True)


if __name__ == '__main__':
    with threadpool_limits(limits=1):
        main()
```

src/12_q3_stale_optimized.py

SHA-256: 56b2e4c89b7616ca459a26b21db244597ffd51d1e2993f13e79121d2cbced3ef

```
"""Repeated nested validation and source-excluded stale-hops transfer proxy.""
"
from __future__ import annotations

import json
import platform
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
import sklearn
from sklearn.model_selection import KFold
from threadpoolctl import threadpool_limits

from common import SOLUTION, data_dir
from q3_data import load_q3_data
from q3_stale_optimized import (
    AUDIT_BOOTSTRAP_SEED, OUTER_SEEDS, SELECTION_BOOTSTRAP_SEED,
    TRANSFER_CV_SEED, VARIANCE_RATIO_MIN, candidate_specs, choose_candidate,
    inner_compare, make_pipeline, predict_1d, raw_tree_pipeline, scores,
)

OUT = SOLUTION / "outputs" / "q3_optimized" / "stale"
TARGET = "stale_hops"


def write_json(path, value):
    path.write_text(json.dumps(value, ensure_ascii=False, indent=2, allow_nan=
False), encoding="utf-8", newline="\n")


def main():
    started = perf_counter()
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y45, manifest = load_q3_data()
    y = y45[TARGET]
    features = x.columns.tolist()
    calibrated = manifest.loc[manifest.representation.eq("calibrated"), "featu
re"].tolist()
    metadata = pd.read_excel(data_dir() / "8.xlsx", sheet_name="Sensory thresh
olds")
    aging = [feature for feature in features
             if feature in set(metadata.loc[metadata.aging.notna(), "field_nam
e_R"])]
    specs = candidate_specs()
    spec_map = {spec["name"]: spec for spec in specs}
    families = sorted({spec["family"] for spec in specs})
    write_json(OUT / "run_manifest.json", {
        "target": TARGET, "features": features, "calibrated_features": calibra
ted,
        "aging_features": aging, "aging_rule": "8.xlsx Sensory thresholds agin
g nonmissing; exact field match",
        "candidate_specs": specs, "outer_seeds": list(OUTER_SEEDS), "outer_fol
ds": 5,
        "inner_folds": 3, "inner_objective": "OOF RMSE subject to prediction v
ariance ratio >=0.05",
        "nonconstant_variance_ratio_min": VARIANCE_RATIO_MIN,
        "fallback": "lowest RMSE if no nonconstant candidate; flagged unqualif
```

```
ied",
        "outer_outcomes_not_used_for_final_config": True,
        "transfer_cv_seed": TRANSFER_CV_SEED,
        "selection_bootstrap_seed": SELECTION_BOOTSTRAP_SEED,
        "audit_bootstrap_seed": AUDIT_BOOTSTRAP_SEED,
        "forbidden_predictors": ["other observed sensory targets", "attachment
 7 comments", "identity keys", "style"],
    })
    pd.DataFrame({"feature": aging}).to_csv(OUT / "predeclared_aging_features.
csv", index=False, lineterminator="\n")
    all_inner, choices, fold_metrics, oof_rows, metrics_rows = [], [], [], [],
 []
    methods = ["mean", "old_multioutput_extra_trees", "fixed_single_extra_tree
s", "nested_selected"]
    methods += [f"nested_family_{family}" for family in families]
    for repeat, outer_seed in enumerate(OUTER_SEEDS, 1):
        predictions = {method: np.full(len(x), np.nan) for method in methods}
        fold_ids = np.zeros(len(x), dtype=int)
        for fold, (train, test) in enumerate(KFold(5, shuffle=True, random_sta
te=outer_seed).split(x), 1):
            inner_seed = outer_seed + 100 * fold
            rows, _ = inner_compare(x.iloc[train], y.iloc[train], specs, featu
res, calibrated, aging, inner_seed)
            for row in rows:
                all_inner.append({"repeat": repeat, "outer_seed": outer_seed,
"outer_fold": fold,
                                  "inner_seed": inner_seed, **row})
            selected = {"nested_selected": choose_candidate(rows)}
            selected.update({f"nested_family_{family}": choose_candidate(rows,
 family) for family in families})
            fitted_cache = {}
            for method, row in selected.items():
                candidate = row["candidate"]
                if candidate not in fitted_cache:
                    fitted_cache[candidate] = make_pipeline(
                        spec_map[candidate], features, calibrated, aging, inne
r_seed + 90).fit(x.iloc[train], y.iloc[train])
                predictions[method][test] = predict_1d(fitted_cache[candidate]
, x.iloc[test])
                choices.append({"repeat": repeat, "outer_seed": outer_seed, "o
uter_fold": fold,
                                "method": method, "selected_candidate": candid
ate,
                                "inner_oof_rmse": row["rmse"],
                                "inner_oof_variance_ratio": row["prediction_va
riance_ratio"],
                                "nonconstant_qualified": row["nonconstant_qual
ified"]})
            old = raw_tree_pipeline(inner_seed + 90).fit(x.iloc[train], y45.il
oc[train])
            predictions["old_multioutput_extra_trees"][test] = old.predict(x.i
loc[test])[:, y45.columns.get_loc(TARGET)]
            single = raw_tree_pipeline(inner_seed + 90).fit(x.iloc[train], y.i
loc[train])
            predictions["fixed_single_extra_trees"][test] = predict_1d(single,
 x.iloc[test])
            predictions["mean"][test] = float(y.iloc[train].mean())
            fold_ids[test] = fold
            for method in methods:
                fold_metrics.append({"repeat": repeat, "outer_seed": outer_see
d, "fold": fold,
                                     "method": method, **scores(y.iloc[test],
```

```
predictions[method][test])})
            pd.DataFrame(all_inner).to_csv(OUT / "nested_inner_cv_results.csv", index=False, lineterminator="\n")
            pd.DataFrame(choices).to_csv(OUT / "nested_selected_configs.csv", index=False, lineterminator="\n")
            print(f"Stale nested repeat {repeat}/2 fold {fold}/5: {selected['nested_selected']['candidate']}; "
                  f"outer RMSE={scores(y.iloc[test], predictions['nested_selected'][test])['rmse']:.6f}", flush=True)
        for method, pred in predictions.items():
            if not np.isfinite(pred).all():
                raise AssertionError(f"Incomplete OOF: repeat={repeat}, {method}")
            metrics_rows.append({"scope": "per_seed", "repeat": repeat, "outer_seed": outer_seed,
                                 "method": method, **scores(y, pred)})
            oof_rows.append(pd.concat([
                meta, pd.DataFrame({"repeat": repeat, "outer_seed": outer_seed, "fold": fold_ids,
                                    "method": method, "observed": y, "prediction": pred})], axis=1))
    oof = pd.concat(oof_rows, ignore_index=True)
    for method in methods:
        rows = oof[oof.method.eq(method)]
        metrics_rows.append({"scope": "pooled_repeated_oof", "repeat": 0, "outer_seed": 0,
                             "method": method, **scores(rows.observed, rows.prediction)})
    metrics = pd.DataFrame(metrics_rows)
    oof.to_csv(OUT / "oof_predictions.csv", index=False, lineterminator="\n")
    metrics.to_csv(OUT / "metrics.csv", index=False, lineterminator="\n")
    pd.DataFrame(fold_metrics).to_csv(OUT / "metrics_by_fold.csv", index=False, lineterminator="\n")
    summary_metrics = metrics[metrics.scope.eq("pooled_repeated_oof")].set_index("method")
    mean_rmse = float(summary_metrics.loc["mean", "rmse"])

    # Only these 239 rows participate in transfer configuration selection.
    excluded = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    transfer_train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    if (len(transfer_train), len(excluded)) != (239, 11):
        raise ValueError("Expected all 11 Pils/Lager sources held out")
    transfer_rows, transfer_inner_pred = inner_compare(
        x.iloc[transfer_train], y.iloc[transfer_train], specs, features, calibrated, aging, TRANSFER_CV_SEED)
    pd.DataFrame(transfer_rows).to_csv(OUT / "transfer_inner_cv_results.csv", index=False, lineterminator="\n")
    selected = choose_candidate(transfer_rows)
    selected_spec = spec_map[selected["candidate"]]
    transfer_baseline = np.full(len(transfer_train), np.nan)
    for train_local, test_local in KFold(3, shuffle=True, random_state=TRANSFER_CV_SEED).split(transfer_train):
        transfer_baseline[test_local] = y.iloc[transfer_train[train_local]].mean()
    transfer_baseline_rmse = scores(y.iloc[transfer_train], transfer_baseline)["rmse"]
    qualified = bool(selected["nonconstant_qualified"] and selected["rmse"] < transfer_baseline_rmse)
    final = make_pipeline(selected_spec, features, calibrated, aging, TRANSFER_CV_SEED + 90).fit(
        x.iloc[transfer_train], y.iloc[transfer_train])
```

```
    artifact = {"pipeline": final, "features": features, "target": TARGET,
                "target_scale": "attachment_4_standardized", "selected_config"
: selected_spec,
                "qualified_for_proxy": qualified,
                "inner_oof_variance_ratio": selected["prediction_variance_rati
o"],
                "inner_oof_rmse": selected["rmse"], "inner_mean_baseline_rmse"
: transfer_baseline_rmse,
                "train_global_indices": transfer_train, "excluded_global_indic
es": excluded,
                "excluded_style": "Pils/Lager", "selection_seed": TRANSFER_CV_
SEED,
                "qualification_scope": "training_only_inner_CV; not holdout or
 counterfactual validation",
                "qualification_rule": "training-only inner OOF variance ratio
>=0.05 and RMSE < inner mean baseline"}
    joblib.dump(artifact, OUT / "transfer_stale_model.joblib", compress=3)
    pd.concat([meta.iloc[transfer_train].reset_index(drop=True), pd.DataFrame(
{
        "observed": y.iloc[transfer_train].to_numpy(),
        "selected_inner_oof_prediction": transfer_inner_pred[selected["candida
te"]],
        "mean_inner_oof_prediction": transfer_baseline})], axis=1).to_csv(
            OUT / "transfer_selected_inner_oof.csv", index=False, lineterminat
or="\n")

    # Source holdout is evaluated only after configuration selection/fitting.
    heldout = pd.concat([meta.iloc[excluded].reset_index(drop=True), pd.DataFr
ame({
        "observed": y.iloc[excluded].to_numpy(), "prediction": predict_1d(fina
l, x.iloc[excluded]),
        "mean_baseline_prediction": y.iloc[transfer_train].mean()})], axis=1)
    heldout.to_csv(OUT / "pils_style_holdout_predictions.csv", index=False, li
neterminator="\n")
    holdout_metrics = [{"model": "optimized_single_target", **scores(heldout.o
bserved, heldout.prediction)},
                       {"model": "non_pils_mean", **scores(heldout.observed, h
eldout.mean_baseline_prediction)}]
    old_path = SOLUTION / "outputs" / "q3" / "sensory" / "transfer_proxy.jobli
b"
    if old_path.exists():
        old = joblib.load(old_path)
        if set(old["train_global_indices"]) & set(excluded):
            raise AssertionError("Old transfer proxy leaks Pils source rows")
        old_pred = old["pipeline"].predict(x.iloc[excluded])[:, old["targets"]
.index(TARGET)]
        holdout_metrics.append({"model": "old_multioutput_transfer_proxy", **s
cores(heldout.observed, old_pred)})
    pd.DataFrame(holdout_metrics).to_csv(OUT / "pils_style_holdout_metrics.csv
", index=False, lineterminator="\n")

    models, bootstrap_indices, bootstrap_seeds, estimator_seeds = [], [], [],
[]
    for b in range(60):
        seed = SELECTION_BOOTSTRAP_SEED + b if b < 40 else AUDIT_BOOTSTRAP_SEE
D + (b - 40)
        index = np.random.default_rng(seed).choice(transfer_train, size=len(tr
ansfer_train), replace=True)
        estimator_seed = seed + 10000
        model = make_pipeline(selected_spec, features, calibrated, aging, esti
mator_seed).fit(x.iloc[index], y.iloc[index])
        models.append(model)
```

```
        bootstrap_indices.append(index)
        bootstrap_seeds.append(seed)
        estimator_seeds.append(estimator_seed)
        if (b + 1) % 10 == 0:
            print(f"Stale optimized bootstrap {b + 1}/60", flush=True)
    ensemble = {"models": models, "bootstrap_indices": bootstrap_indices,
                "features": features, "target": TARGET, "target_scale": "attac
hment_4_standardized",
                "selected_config": selected_spec, "qualified_for_proxy": quali
fied,
                "qualification_scope": "training_only_inner_CV; not holdout or
 counterfactual validation",
                "inner_oof_variance_ratio": selected["prediction_variance_rati
o"],
                "inner_oof_rmse": selected["rmse"],
                "train_global_indices": transfer_train, "excluded_global_indic
es": excluded,
                "selection_model_indices": list(range(40)), "audit_model_indic
es": list(range(40, 60)),
                "bootstrap_seeds": bootstrap_seeds, "estimator_seeds": estimat
or_seeds,
                "pairing": "same_model_candidate_minus_source", "paired_quanti
le": 0.95,
                "hyperparameter_uncertainty_included": False,
                "audit_protocol": "40 screening models; 20 separate bootstrap
draws for one-time audit; no reselection",
                "interpretation": "model proxy bootstrap quantiles; not calibr
ated confidence bounds"}
    joblib.dump(ensemble, OUT / "bootstrap_ensemble.joblib", compress=3)
    np.savez_compressed(OUT / "bootstrap_indices.npz", indices=np.asarray(boot
strap_indices),
                        bootstrap_seeds=np.asarray(bootstrap_seeds), estimator
_seeds=np.asarray(estimator_seeds))
    assert np.asarray(bootstrap_indices).shape == (60, 239)
    assert all(not set(index) & set(excluded) for index in bootstrap_indices)
    assert set(ensemble["selection_model_indices"]).isdisjoint(ensemble["audit
_model_indices"])
    assert np.isfinite(predict_1d(final, x)).all()
    selected_metrics = summary_metrics.loc["nested_selected"].to_dict()
    summary = {
        "samples": len(x), "features": len(features), "target": TARGET,
        "outer_seeds": list(OUTER_SEEDS), "outer_folds": 5, "inner_folds": 3,
        "candidate_count": len(specs), "nonconstant_variance_ratio_min": VARIA
NCE_RATIO_MIN,
        "main_result": "nested selection algorithm; not post-hoc best outer fa
mily",
        "pooled_repeat_metrics": [{"method": method, **summary_metrics.loc[met
hod].to_dict()} for method in methods],
        "nested_rmse_reduction_vs_mean": 1 - selected_metrics["rmse"] / mean_r
mse,
        "transfer_selected_config": selected_spec, "transfer_qualified_for_pro
xy": qualified,
        "transfer_qualification_scope": "training_only_inner_CV; not holdout o
r counterfactual validation",
        "pils_holdout_improves_mean": holdout_metrics[0]["rmse"] < holdout_met
rics[1]["rmse"],
        "transfer_inner_oof_metrics": selected,
        "transfer_inner_mean_baseline_rmse": transfer_baseline_rmse,
        "pils_holdout_metrics": holdout_metrics,
        "bootstrap": {"models": 60, "selection": 40, "audit": 20, "population"
: "239 non-Pils only",
                      "selected_config_fixed": True, "hyperparameter_uncertain
```

```
ty_included": False},
        "limitations": [
            "Only chemical features available to generated profiles are used; no other sensory labels or comments are predictors.",
            "The old multi-output comparator uses 45 labels only during its training, never as prediction features.",
            "Repeated OOF rows are correlated repeats of 250 samples, not 500 independent beers.",
            "The candidate grid and variance gate are fixed; family outer metrics do not select the transfer configuration.",
            "All transfer tuning, preprocessing and bootstrap sampling exclude all 11 Pils/Lager sources.",
            "Pils style holdout has 11 samples in one style and is not used to choose the model.",
            "Bootstrap fixes the training-only selected configuration and does not include hyperparameter-selection uncertainty.",
            "Disjoint bootstrap draws share the same observed training data; the audit is not independent experimental validation.",
            "Passing paired model-proxy differences cannot guarantee improved real stale-hops taste or causal chemical effects.",
            "Attachment-standardized target values cannot be interpreted as original 0-6 sensory scores.",
        ],
        "verification": {"bootstrap_source_exclusion": True, "selection_audit_disjoint": True,
                         "final_predictions_finite": True, "bootstrap_indices_shape": [60, 239]},
        "versions": {"python": platform.python_version(), "numpy": np.__version__,
                     "pandas": pd.__version__, "sklearn": sklearn.__version__},
        "elapsed_seconds": perf_counter() - started,
    }
    # Pandas integer dtypes in to_dict are normal Python values here.
    write_json(OUT / "summary.json", summary)
    print(summary_metrics[["rmse", "r2", "spearman", "prediction_variance_ratio"]].to_string(), flush=True)
    print("Transfer chosen:", selected_spec, "qualified:", qualified, flush=True)
    print("Pils holdout:", json.dumps(holdout_metrics, ensure_ascii=False), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/12b_q3_stale_fixed.py

SHA-256: d7202fbaca1f8f67063ae5084a57a8669a170005c9195d9857033ef88b16cbdc

```
"""Fixed single-target forest follow-up on two additional internal splits.

Parameters are not tuned. This follows exploratory algorithm comparisons on
the same 250 samples and is not an independent external confirmation dataset.
"""
from __future__ import annotations

import json
import platform
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
import sklearn
from sklearn.model_selection import KFold
from threadpoolctl import threadpool_limits

from common import SOLUTION
from q3_data import load_q3_data
from q3_stale_optimized import VARIANCE_RATIO_MIN, predict_1d, raw_tree_pipeline, scores

OUT = SOLUTION / "outputs" / "q3_optimized" / "stale_fixed"
TARGET = "stale_hops"
SEEDS = (20263123, 20264123)
TRANSFER_CV_SEED = 20266123
SELECTION_BOOTSTRAP_SEED = 20267123
AUDIT_BOOTSTRAP_SEED = 20268123


def write_json(path, value):
    path.write_text(json.dumps(value, ensure_ascii=False, indent=2, allow_nan=False), encoding="utf-8", newline="\n")


def paired_cluster_bootstrap(oof, repeats=2000, seed=20269123):
    """Resample beers, after averaging each beer's repeated squared errors."""
    errors = oof.assign(squared_error=(oof.prediction-oof.observed)**2)
    per_beer = errors.groupby(["beer", "method"], sort=True).squared_error.mean().unstack("method")
    fixed = per_beer["fixed_single_extra_trees"].to_numpy()
    old = per_beer["old_multioutput_extra_trees"].to_numpy()
    draws = np.random.default_rng(seed).integers(0, len(per_beer), size=(repeats, len(per_beer)))
    fixed_rmse, old_rmse = np.sqrt(fixed[draws].mean(axis=1)), np.sqrt(old[draws].mean(axis=1))
    difference, reduction = fixed_rmse-old_rmse, 1-fixed_rmse/old_rmse
    return {"seed": seed, "repeats": repeats, "independent_resampling_unit": "beer",
        "beers": len(per_beer), "pre_aggregation": "mean squared error within beer and method across two repeats",
        "comparison": "fixed single-target ExtraTrees minus old multi-output ExtraTrees",
        "point_rmse_difference": float(np.sqrt(fixed.mean())-np.sqrt(old.mean())),
        "rmse_difference_percentile95": np.quantile(difference, [.025, .975]).tolist(),
        "point_relative_rmse_reduction": float(1-np.sqrt(fixed.mean())/np.sqrt
```

```
(old.mean())),
50          "relative_rmse_reduction_percentile95": np.quantile(reduction, [.025,
.975]).tolist(),
51          "bootstrap_fraction_rmse_difference_below_zero": float(np.mean(differe
nce<0)),
52          "interpretation": "sampling uncertainty conditional on saved OOF predi
ctions; not a selection-adjusted external-validation interval",
53          "limitations": ["Same-data algorithm exploration/selection is not resa
mpled or accounted for",
54                          "Models are not refitted within these 2000 resamples",
55                          "Shared training folds create dependencies beyond the
repeated-beer clustering"]}
56
57
58  def main():
59      started = perf_counter()
60      OUT.mkdir(parents=True, exist_ok=True)
61      meta, x, y45, _ = load_q3_data()
62      y = y45[TARGET]
63      features = x.columns.tolist()
64      selected_config = {"name": "fixed_single_extra_trees_300", "family": "extr
a_trees",
65                         "feature_set": "all226", "representation": "raw_hybrid"
,
66                         "params": {"n_estimators": 300, "min_samples_leaf": 3,
67                                    "max_features": 0.7, "n_jobs": 1},
68                         "bootstrap_n_estimators": 120, "tuning": "none"}
69      write_json(OUT / "run_manifest.json", {
70          "selected_config": selected_config, "outer_seeds": list(SEEDS), "outer
_folds": 5,
71          "transfer_cv_seed": TRANSFER_CV_SEED, "selection_bootstrap_seed": SELE
CTION_BOOTSTRAP_SEED,
72          "audit_bootstrap_seed": AUDIT_BOOTSTRAP_SEED, "features": features,
73          "preprocessing": "raw hybrid; training-only median imputation with mis
sing indicators",
74          "status": "fixed follow-up after exploratory algorithm comparison on t
he same data",
75          "not_independent_external_confirmation": True, "parameter_tuning": Fal
se,
76      })
77      methods = ["mean", "old_multioutput_extra_trees", "fixed_single_extra_tree
s"]
78      oof_rows, metric_rows, fold_rows = [], [], []
79      stale_position = y45.columns.get_loc(TARGET)
80      for repeat, seed in enumerate(SEEDS, 1):
81          predictions = {name: np.full(len(x), np.nan) for name in methods}
82          folds = np.zeros(len(x), dtype=int)
83          for fold, (train, test) in enumerate(KFold(5, shuffle=True, random_sta
te=seed).split(x), 1):
84              model_seed = seed + fold
85              old = raw_tree_pipeline(model_seed).fit(x.iloc[train], y45.iloc[tr
ain])
86              single = raw_tree_pipeline(model_seed).fit(x.iloc[train], y.iloc[t
rain])
87              predictions["old_multioutput_extra_trees"][test] = old.predict(x.i
loc[test])[:, stale_position]
88              predictions["fixed_single_extra_trees"][test] = predict_1d(single,
 x.iloc[test])
89              predictions["mean"][test] = y.iloc[train].mean()
90              folds[test] = fold
91              for method in methods:
92                  fold_rows.append({"repeat": repeat, "outer_seed": seed, "fold"
```

```
: fold,
                                     "method": method, **scores(y.iloc[test], predictions[method][test])})
            print(f"Stale fixed repeat {repeat}/2 fold {fold}/5: "
                  f"single RMSE={scores(y.iloc[test], predictions['fixed_single_extra_trees'][test])['rmse']:.6f}", flush=True)
        for method, pred in predictions.items():
            assert np.isfinite(pred).all()
            metric_rows.append({"scope": "per_seed", "repeat": repeat, "outer_seed": seed,
                                "method": method, **scores(y, pred)})
            oof_rows.append(pd.concat([meta, pd.DataFrame({"repeat": repeat, "outer_seed": seed,
                "fold": folds, "method": method, "observed": y, "prediction": pred})], axis=1))
    oof = pd.concat(oof_rows, ignore_index=True)
    for method in methods:
        group = oof[oof.method.eq(method)]
        metric_rows.append({"scope": "pooled_repeated_oof", "repeat": 0, "outer_seed": 0,
                            "method": method, **scores(group.observed, group.prediction)})
    metrics = pd.DataFrame(metric_rows)
    oof.to_csv(OUT / "oof_predictions.csv", index=False, lineterminator="\n")
    metrics.to_csv(OUT / "metrics.csv", index=False, lineterminator="\n")
    pd.DataFrame(fold_rows).to_csv(OUT / "metrics_by_fold.csv", index=False, lineterminator="\n")
    cluster_result = paired_cluster_bootstrap(oof)
    write_json(OUT / "paired_cluster_bootstrap.json", cluster_result)
    pooled = metrics[metrics.scope.eq("pooled_repeated_oof")].set_index("method")

    excluded = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    train_global = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    assert len(excluded) == 11 and len(train_global) == 239
    train_oof, mean_oof = np.full(len(train_global), np.nan), np.full(len(train_global), np.nan)
    for fold, (tr, te) in enumerate(KFold(3, shuffle=True, random_state=TRANSFER_CV_SEED).split(train_global), 1):
        model = raw_tree_pipeline(TRANSFER_CV_SEED + fold).fit(x.iloc[train_global[tr]], y.iloc[train_global[tr]])
        train_oof[te] = predict_1d(model, x.iloc[train_global[te]])
        mean_oof[te] = y.iloc[train_global[tr]].mean()
    train_metrics, mean_metrics = scores(y.iloc[train_global], train_oof), scores(y.iloc[train_global], mean_oof)
    qualified = bool(train_metrics["prediction_variance_ratio"] >= VARIANCE_RATIO_MIN
                     and train_metrics["rmse"] < mean_metrics["rmse"])
    final = raw_tree_pipeline(TRANSFER_CV_SEED + 90).fit(x.iloc[train_global], y.iloc[train_global])
    common_metadata = {"features": features, "target": TARGET,
        "target_scale": "attachment_4_standardized", "selected_config": selected_config,
        "qualified_for_proxy": qualified, "inner_oof_variance_ratio": train_metrics["prediction_variance_ratio"],
        "inner_oof_rmse": train_metrics["rmse"], "inner_mean_baseline_rmse": mean_metrics["rmse"],
        "train_global_indices": train_global, "excluded_global_indices": excluded,
        "excluded_style": "Pils/Lager", "qualification_scope": "training_only_fixed_model_CV; not holdout or counterfactual validation",
```

```
        "qualification_rule": "training-only OOF variance ratio >=0.05 and RMSE < same-fold mean baseline",
        "parameter_tuning": False}
    artifact = {"pipeline": final, **common_metadata}
    joblib.dump(artifact, OUT / "transfer_stale_model.joblib", compress=3)
    pd.concat([meta.iloc[train_global].reset_index(drop=True), pd.DataFrame({"observed": y.iloc[train_global].to_numpy(),
        "fixed_inner_oof_prediction": train_oof, "mean_inner_oof_prediction": mean_oof})], axis=1).to_csv(
            OUT / "transfer_inner_oof.csv", index=False, lineterminator="\n")
    heldout = pd.concat([meta.iloc[excluded].reset_index(drop=True), pd.DataFrame({
        "observed": y.iloc[excluded].to_numpy(), "prediction": predict_1d(final, x.iloc[excluded]),
        "mean_baseline_prediction": y.iloc[train_global].mean()})], axis=1)
    old_artifact = joblib.load(SOLUTION / "outputs" / "q3" / "sensory" / "transfer_proxy.joblib")
    assert not set(old_artifact["train_global_indices"]) & set(excluded)
    heldout["old_multioutput_prediction"] = old_artifact["pipeline"].predict(x.iloc[excluded])[:, stale_position]
    heldout.to_csv(OUT / "pils_style_holdout_predictions.csv", index=False, lineterminator="\n")
    heldout_metrics = [{"model": name, **scores(heldout.observed, heldout[column])} for name, column in [
        ("fixed_single_extra_trees", "prediction"), ("non_pils_mean", "mean_baseline_prediction"),
        ("old_multioutput_transfer_proxy", "old_multioutput_prediction")]]
    pd.DataFrame(heldout_metrics).to_csv(OUT / "pils_style_holdout_metrics.csv", index=False, lineterminator="\n")

    models, indices, seeds = [], [], []
    for b in range(60):
        seed = SELECTION_BOOTSTRAP_SEED + b if b < 40 else AUDIT_BOOTSTRAP_SEED + b - 40
        index = np.random.default_rng(seed).choice(train_global, size=len(train_global), replace=True)
        model = raw_tree_pipeline(seed + 10000, n_estimators=120).fit(x.iloc[index], y.iloc[index])
        models.append(model)
        indices.append(index)
        seeds.append(seed)
        if (b + 1) % 20 == 0:
            print(f"Stale fixed bootstrap {b + 1}/60", flush=True)
    ensemble = {"models": models, "bootstrap_indices": indices, **common_metadata,
        "bootstrap_seeds": seeds, "estimator_seeds": [seed + 10000 for seed in seeds],
        "selection_model_indices": list(range(40)), "audit_model_indices": list(range(40, 60)),
        "pairing": "same_model_candidate_minus_source", "paired_quantile": 0.95,
        "bootstrap_n_estimators": 120, "final_n_estimators": 300,
        "hyperparameter_uncertainty_included": False,
        "audit_protocol": "40 screening models; 20 separate bootstrap draws for one-time audit; no reselection",
        "interpretation": "fixed single-target forest proxy; quantiles are not calibrated confidence bounds"}
    joblib.dump(ensemble, OUT / "bootstrap_ensemble.joblib", compress=3)
    np.savez_compressed(OUT / "bootstrap_indices.npz", indices=np.asarray(indices), bootstrap_seeds=np.asarray(seeds))
    assert np.asarray(indices).shape == (60, 239)
    assert all(not set(index) & set(excluded) for index in indices)
```

```
    assert len(set(seeds)) == 60
    assert np.isfinite(predict_1d(final, x)).all()
    summary = {
        "status": "fixed follow-up after exploratory model comparisons on the same dataset",
        "samples": len(x), "features": len(features), "target": TARGET,
        "outer_seeds": list(SEEDS), "outer_folds": 5, "parameter_tuning": False,
        "selected_config": selected_config,
        "pooled_repeat_metrics": [{"method": method, **pooled.loc[method].to_dict()} for method in methods],
        "rmse_reduction_vs_mean": float(1-pooled.loc['fixed_single_extra_trees', 'rmse']/pooled.loc['mean', 'rmse']),
        "rmse_reduction_vs_old_multioutput": float(1-pooled.loc['fixed_single_extra_trees', 'rmse']/pooled.loc['old_multioutput_extra_trees', 'rmse']),
        "paired_cluster_bootstrap": cluster_result,
        "transfer_qualified_for_proxy": qualified, "transfer_inner_oof_metrics": train_metrics,
        "transfer_inner_mean_metrics": mean_metrics, "transfer_cv_seed": TRANSFER_CV_SEED,
        "transfer_qualification_scope": common_metadata["qualification_scope"],
        "pils_holdout_metrics": heldout_metrics,
        "pils_holdout_improves_mean": heldout_metrics[0]["rmse"] < heldout_metrics[1]["rmse"],
        "pils_holdout_improves_old": heldout_metrics[0]["rmse"] < heldout_metrics[2]["rmse"],
        "bootstrap": {"models": 60, "selection": 40, "audit": 20, "trees_per_model": 120,
                      "final_trees": 300, "population": "239 non-Pils only", "structure_fixed": True},
        "limitations": [
            "Additional split seeds reuse the same 250 samples; the exploratory algorithm choice is not independently externally confirmed.",
            "No parameter tuning or family search is performed in this follow-up.",
            "The 500 repeated OOF predictions do not constitute 500 independent beers.",
            "All transfer preprocessing, fitting and bootstrap sampling exclude every Pils/Lager source.",
            "Source-style holdout is reported after the fixed model is trained and never changes the chosen algorithm.",
            "The 0.05 OOF variance-ratio gate does not prove candidate chemical perturbation responsiveness.",
            "Bootstrap uses 120-tree approximations to the 300-tree final forest, with fixed parameters and no algorithm-selection uncertainty.",
            "Separate screening/audit bootstrap draws share the same observed training population and are not independent experimental validation.",
            "Passing paired proxy quantiles cannot establish real stale-hops taste or causal effects; original 0-6 scores remain unavailable.",
        ],
        "verification": {"bootstrap_indices_shape": [60, 239], "source_exclusion": True,
                         "bootstrap_seeds_unique": True, "predictions_finite": True},
        "versions": {"python": platform.python_version(), "numpy": np.__version__,
                     "pandas": pd.__version__, "sklearn": sklearn.__version__},
        "elapsed_seconds": perf_counter()-started,
    }
    write_json(OUT / "summary.json", summary)
```

```
    print(pooled[["rmse", "r2", "spearman", "prediction_std_ratio"]].to_string(), flush=True)
    print("Fixed transfer qualified:", qualified, "holdout:", json.dumps(heldout_metrics, ensure_ascii=False), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/13_q3_transfer_optimized.py

SHA-256: bdc28b4229fee67fb8e0d5a6ad87cd259c42dbb5081902162dbea3b2eea3a9d0

```python
"""Threshold-robust transfer with matched generation budgets and proxy audits."""
from __future__ import annotations

import json

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from threadpoolctl import threadpool_limits

from common import SEED, SOLUTION
from q3_data import load_q3_data, read_defect_thresholds
from q3_generator_optimized import OptimizedStyleGenerator

OUT = SOLUTION / "outputs/q3_optimized/transfer"
OLD = SOLUTION / "outputs/q3"
ROOT_OUT = SOLUTION / "outputs/q3_optimized"
N_GENERATED = 500
FACTORS = [0.8, 0.9, 1.0, 1.1, 1.2]
LAMBDAS = [0.05, 0.2, 1.0]
DEFAULT_LAMBDA = 0.2
DEFAULT_POOL = "optimized_generator"
TOL = 1e-10


def scenarios(defects):
    return [{"scenario": f"{statistic}_x{factor:.1f}", "statistic": statistic,
             "factor": factor,
             "thresholds": {rule["feature"]: (float(rule[f"threshold_{statistic}"]) * factor
                                              if rule[f"threshold_{statistic}"] is not None else None)
                            for rule in defects.values()}}
            for statistic in ["median", "mean"] for factor in FACTORS]


def robust_caps(source, defects, scenario_list):
    caps = {}
    for rule in defects.values():
        field = rule["feature"]
        observed = float(source[field].iloc[0])
        values = [item["thresholds"][field] for item in scenario_list]
        finite = [value for value in values if value is not None]
        caps[field] = max(observed, min(finite)) if finite else observed
    return caps


def chemical_feasible(frame, source, scenario):
    good = np.ones(len(frame), dtype=bool)
    for field, threshold in scenario["thresholds"].items():
        source_value = float(source[field].iloc[0])
        cap = max(source_value, threshold) if threshold is not None else source_value
        value = frame[field].to_numpy(float)
        good &= np.isfinite(value) & (value >= 0) & (value <= cap + TOL)
    return good

```

```

def paired(models, frame, source):
    return np.column_stack([
        np.asarray(model.predict(frame)).reshape(-1)
        - float(np.asarray(model.predict(source)).reshape(-1)[0])
        for model in models
    ])


def build_pool(source, old_draws, new_draws, target_median):
    blocks, descriptions = [], []
    for family, draws in [("old_copula", old_draws), ("optimized", new_draws)]
:
        for gamma in [.25, .5, .75, 1.0]:
            values = (1 - gamma) * source.to_numpy()[0] + gamma * draws.to_num
py()
            blocks.append(values)
            descriptions.extend({"family": family, "gamma": gamma, "draw": j}
                                for j in range(len(values)))
    for gamma in [.25, .5, .75, 1.0]:
        blocks.append(((1 - gamma) * source.to_numpy()[0] + gamma * target_med
ian)[None])
        descriptions.append({"family": "shared_target_median", "gamma": gamma,
 "draw": -1})
    return pd.DataFrame(np.vstack(blocks), columns=source.columns), pd.DataFra
me(descriptions)


def main():
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y, manifest = load_q3_data()
    defects = read_defect_thresholds()
    scenario_list = scenarios(defects)
    (OUT / "threshold_scenarios.json").write_text(json.dumps(scenario_list, in
dent=2), encoding="utf-8", newline="\n")
    source_rows = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    target_rows = np.flatnonzero(meta.tasting_category_fine.eq("Tripel"))
    # Keep exactly the baseline geometry; changing the yardstick would make
    # an improvement in target distance difficult to interpret.
    geometry = joblib.load(OLD / "transfer/transfer_copula.joblib")
    np.testing.assert_array_equal(geometry["training_rows"], train)
    reference = geometry["copula"]
    old_draws = reference.sample("Tripel", N_GENERATED, seed=SEED + 301)
    generator = OptimizedStyleGenerator().fit(x.iloc[train], meta.tasting_cate
gory_fine.iloc[train])
    new_draws = generator.sample("Tripel", N_GENERATED, seed=SEED + 301)
    assert old_draws.columns.tolist() == new_draws.columns.tolist() == x.colum
ns.tolist()
    joblib.dump({"generator": generator, "training_rows": train, "source_rows"
: source_rows,
                 "features": x.columns.tolist()}, OUT / "transfer_generator.jo
blib", compress=3)
    new_draws.to_csv(OUT / "optimized_base_draws.csv", index=False, linetermin
ator="\n")
    old_draws.to_csv(OUT / "old_base_draws.csv", index=False, lineterminator="
\n")

    stale_model = joblib.load(ROOT_OUT / "stale_fixed/transfer_stale_model.job
lib")
    ensemble = joblib.load(ROOT_OUT / "stale_fixed/bootstrap_ensemble.joblib")
    assert ensemble["features"] == stale_model["features"] == x.columns.tolist
```

```
()
    assert len(ensemble["models"]) == 60
    np.testing.assert_array_equal(stale_model["train_global_indices"], train)
    for indices in ensemble["bootstrap_indices"]:
        assert not np.isin(indices, source_rows).any()
    selection_models, audit_models = ensemble["models"][:40], ensemble["models
"][40:]
    qualified = bool(stale_model["qualified_for_proxy"])
    old_ensemble = joblib.load(OLD / "sensory/stale_bootstrap.joblib")
    profile_model = joblib.load(OLD / "sensory/transfer_proxy.joblib")
    target_z = reference.transform(x.iloc[target_rows])
    p = x.shape[1]
    pairwise = cdist(target_z, target_z) / np.sqrt(p)
    np.fill_diagonal(pairwise, np.inf)
    support_limit = float(np.quantile(pairwise.min(axis=1), .95))
    target_center = target_z.mean(axis=0)
    minimum, maximum = x.iloc[train].min().to_numpy(), x.iloc[train].max().to_
numpy()
    medians = x.iloc[train].median()
    target_median = x.iloc[target_rows].median().to_numpy()

    records, diag_rows, spectra, threshold_rows, delta_rows, profiles = [], []
, [], [], [], []
    for number, index in enumerate(source_rows, 1):
        beer = int(meta.beer.iloc[index])
        raw_source = x.iloc[[index]]
        complete = all(np.isfinite(raw_source[rule["feature"]].iloc[0])
                       and raw_source[rule["feature"]].iloc[0] >= 0 for rule i
n defects.values())
        if not complete:
            for pool in ["old_generator", "optimized_generator", "combined_poo
l"]:
                for weight in LAMBDAS:
                    records.append({"source_beer": beer, "pool": pool, "lambda
": weight,
                                    "is_default_policy": pool == DEFAULT_POOL
and weight == DEFAULT_LAMBDA,
                                    "status": "source_defect_unverifiable", "a
ll_model_checks_passed": False,
                                    "cross_proxy_checks_passed": False})
            continue
        source = raw_source.fillna(medians)
        values, descriptions = build_pool(source, old_draws, new_draws, target
_median)
        caps = robust_caps(raw_source, defects, scenario_list)
        for field, cap in caps.items():
            values[field] = values[field].clip(lower=0, upper=cap)
        z, source_z = reference.transform(values), reference.transform(source)
        distance = reference.distance(values, "Tripel")
        before = float(reference.distance(source, "Tripel")[0])
        nn = cdist(z, target_z).min(axis=1) / np.sqrt(p)
        change = np.linalg.norm(z - source_z, axis=1) / np.sqrt(p)
        center_scale = max(float(np.linalg.norm(source_z[0] - target_center) /
 np.sqrt(p)), 1e-8)
        target_improvement = 1 - distance / max(before, 1e-8)
        support = (nn <= support_limit + TOL) & (
            (values.to_numpy() >= minimum - TOL) & (values.to_numpy() <= maxim
um + TOL)).all(axis=1)
        chemical = np.column_stack([chemical_feasible(values, raw_source, scen
ario)
                                    for scenario in scenario_list]).all(axis=1
)
```

```
        unique_values, inverse = np.unique(values.to_numpy(), axis=0, return_i
nverse=True)
        candidate_delta = paired(selection_models, pd.DataFrame(unique_values,
 columns=x.columns), source)[inverse]
        q95 = np.quantile(candidate_delta, .95, axis=1)
        nonzero_delta = np.any(np.abs(candidate_delta) > 1e-8, axis=1)
        eligible = (support & chemical & (change >= .05) & (target_improvement
 >= .10)
                    & (q95 <= TOL) & nonzero_delta)
        pool_masks = {
            "old_generator": descriptions.family.isin(["old_copula", "shared_t
arget_median"]).to_numpy(),
            "optimized_generator": descriptions.family.isin(["optimized", "sha
red_target_median"]).to_numpy(),
            "combined_pool": np.ones(len(values), dtype=bool),
        }
        # Full candidate matrices are reproducible from the two saved base
        # draws, source rows, fixed interpolation fractions and robust caps.
        for j in range(len(values)):
            diag_rows.append({"source_beer": beer, "candidate_index": j,
                              **descriptions.iloc[j].to_dict(), "target_distan
ce": float(distance[j]),
                              "target_improvement": float(target_improvement[j
]),
                              "target_nn_rms": float(nn[j]), "change_latent_rm
s": float(change[j]),
                              "support_ok": bool(support[j]), "all_thresholds_
chemical_ok": bool(chemical[j]),
                              "selection_q95": float(q95[j]), "nonzero_paired_
signal": bool(nonzero_delta[j]),
                              "selection_feasible": bool(eligible[j])})

        before_profile = profile_model["pipeline"].predict(source)[0]
        before_stale = float(np.asarray(stale_model["pipeline"].predict(source
)).reshape(-1)[0])
        audit_cache = {}
        for pool, pool_mask in pool_masks.items():
            variation = float(np.std(candidate_delta[pool_mask].mean(axis=1)))
            zero_fraction = float(np.mean(np.all(np.abs(candidate_delta[pool_m
ask]) <= 1e-8, axis=1)))
            allowed = eligible & pool_mask
            for weight in LAMBDAS:
                transfer_id = f"beer_{beer}_{pool}_lambda_{weight:g}"
                common = {"transfer_id": transfer_id, "source_beer": beer, "so
urce_style": "Pils/Lager",
                          "target_style": "Tripel", "pool": pool, "lambda": we
ight,
                          "is_default_policy": pool == DEFAULT_POOL and weight
 == DEFAULT_LAMBDA,
                          "n_candidates": int(pool_mask.sum()), "n_selection_f
easible": int(allowed.sum()),
                          "target_distance_before": before, "support_nn_limit"
: support_limit,
                          "proxy_qualified": qualified, "candidate_mean_delta_
sd": variation,
                          "candidate_zero_paired_fraction": zero_fraction,
                          "all_model_checks_passed": False, "cross_proxy_check
s_passed": False}
                if not allowed.any():
                    records.append({**common, "status": "no_candidate_found"})
                    continue
                objective = distance / max(before, 1e-8) + weight * change / c
```

```
enter_scale
                chosen = int(np.flatnonzero(allowed)[np.argmin(objective[allow
ed])])
                selected = values.iloc[[chosen]]
                select_delta = candidate_delta[chosen]
                cache_key = selected.to_numpy().tobytes()
                if cache_key not in audit_cache:
                    audit_cache[cache_key] = {
                        "audit_delta": paired(audit_models, selected, source)[
0],
                        "old_delta": paired(old_ensemble["models"], selected,
source)[0],
                        "after_stale": float(np.asarray(stale_model["pipeline"
].predict(selected)).reshape(-1)[0]),
                        "after_profile": profile_model["pipeline"].predict(sel
ected)[0],
                    }
                cached = audit_cache[cache_key]
                audit_delta = cached["audit_delta"]
                audit_q95 = float(np.quantile(audit_delta, .95))
                audit_ok = audit_q95 <= TOL
                # The frozen first-round committee is an architecture check,
                # never a way of choosing a different candidate after the audi
t.
                old_delta = cached["old_delta"]
                old_selection_q95 = float(np.quantile(old_delta[:30], .95))
                old_audit_q95 = float(np.quantile(old_delta[30:], .95))
                old_consensus = old_selection_q95 <= TOL and old_audit_q95 <=
TOL
                informative = variation > 1e-6 and nonzero_delta[chosen]
                passed = bool(qualified and informative and audit_ok)
                status = ("proxy_not_qualified" if not qualified else "proxy_u
ninformative" if not informative
                          else "model_checks_passed" if audit_ok else "resampl
ing_audit_failed")
                after_stale = cached["after_stale"]
                records.append({**common, "candidate_index": chosen, "status":
 status,
                                "objective": float(objective[chosen]),
                                "target_distance_after": float(distance[chosen
]),
                                "target_improvement": float(target_improvement
[chosen]),
                                "target_nn_after": float(nn[chosen]), "change_
latent_rms": float(change[chosen]),
                                "all_thresholds_chemical_ok": True,
                                "selection_q95": float(q95[chosen]), "audit_q9
5": audit_q95,
                                "all_model_checks_passed": passed,
                                "old_selection_q95": old_selection_q95, "old_a
udit_q95": old_audit_q95,
                                "old_proxy_consensus": bool(old_consensus),
                                "cross_proxy_checks_passed": bool(passed and o
ld_consensus),
                                "stale_before": before_stale, "stale_after": a
fter_stale})
                spectra.append({"transfer_id": transfer_id, "source_beer": bee
r,
                                "pool": pool, "lambda": weight, **selected.ilo
c[0].to_dict()})
                after_profile = cached["after_profile"]
                for phase, profile, stale_value in [("source", before_profile,
```

```
 before_stale),
                                                        ("transferred", after_pro
file, after_stale)]:
                    profile_values = dict(zip(y.columns, map(float, profile)))
                    profile_values["stale_hops"] = stale_value
                    profiles.append({"transfer_id": transfer_id, "phase": phas
e,
                                     **profile_values})
                for group, delta in [("selection", select_delta), ("audit", au
dit_delta),
                                     ("old_selection", old_delta[:30]), ("old_
audit", old_delta[30:])]:
                    delta_rows.extend({"transfer_id": transfer_id, "ensemble":
 group,
                                       "model_index": k, "paired_delta": float
(value)}
                                      for k, value in enumerate(delta))
                for scenario in scenario_list:
                    for name, rule in defects.items():
                        field = rule["feature"]
                        threshold = scenario["thresholds"][field]
                        old_value = float(raw_source[field].iloc[0])
                        new_value = float(selected[field].iloc[0])
                        cap = max(old_value, threshold) if threshold is not No
ne else old_value
                        threshold_rows.append({"transfer_id": transfer_id, "so
urce_beer": beer,
                                               "pool": pool, "lambda": weight,
                                               "scenario": scenario["scenario"
], "statistic": scenario["statistic"],
                                               "factor": scenario["factor"], "
defect": name,
                                               "feature": field, "unit": rule[
"unit"], "threshold": threshold,
                                               "source": old_value, "transferr
ed": new_value,
                                               "upper_bound": cap, "robust_upp
er_bound": caps[field],
                                               "passed": new_value <= cap + TO
L})
        print(f"Optimized transfer {number}/11 beer={beer}, eligible={eligible
.sum()}/{len(values)}", flush=True)

    frames = {"transfer_summary.csv": records, "candidate_diagnostics.csv": di
ag_rows,
              "transferred_spectra.csv": spectra, "threshold_sensitivity.csv":
 threshold_rows,
              "stale_paired_deltas.csv": delta_rows, "sensory_before_after.csv
": profiles}
    for name, rows in frames.items():
        pd.DataFrame(rows).to_csv(OUT / name, index=False, lineterminator="\n"
)

    # Recheck the unchanged first-round selections on the same threshold grid.
    archived = pd.read_csv(OLD / "transfer/transfer_summary.csv")
    archived = archived[archived["mode"].eq("protected") & archived.is_default
_policy]
    archived_spectra = pd.read_csv(OLD / "transfer/transferred_spectra.csv").s
et_index("transfer_id")
    old_checks = []
    for row in archived.itertuples():
        if pd.isna(row.candidate_index):
```

```
            continue
        source = x.loc[meta.beer.eq(row.source_beer)]
        selected = archived_spectra.loc[[row.transfer_id], x.columns]
        for scenario in scenario_list:
            old_checks.append({"source_beer": row.source_beer, "transfer_id":
row.transfer_id,
                               "scenario": scenario["scenario"], "old_model_ch
ecks_passed": row.all_model_checks_passed,
                               "chemical_passed": bool(chemical_feasible(selec
ted, source, scenario)[0])})
    archived_checks = pd.DataFrame(old_checks)
    archived_checks.to_csv(OUT / "archived_threshold_recheck.csv", index=False
, lineterminator="\n")
    result = pd.DataFrame(records)
    policy_rows = []
    for (pool, weight), part in result.groupby(["pool", "lambda"]):
        policy_rows.append({"pool": pool, "lambda": float(weight), "sources":
len(part),
                            "selected": int(part.candidate_index.notna().sum()
) if "candidate_index" in part else 0,
                            "model_checks_passed": int(part.all_model_checks_p
assed.sum()),
                            "cross_proxy_checks_passed": int(part.cross_proxy_
checks_passed.sum()),
                            "audit_failed": int(part.status.eq("resampling_aud
it_failed").sum()),
                            "no_candidate": int(part.status.eq("no_candidate_f
ound").sum())})
    pd.DataFrame(policy_rows).to_csv(OUT / "policy_summary.csv", index=False,
lineterminator="\n")
    archived_robust = archived_checks.groupby("source_beer").chemical_passed.a
ll()
    old_passed_beers = archived.loc[archived.all_model_checks_passed, "source_
beer"]
    old_all_grid = int(archived_robust.reindex(old_passed_beers, fill_value=Fa
lse).sum())
    default = result[result.is_default_policy]
    summary = {
        "seed": SEED, "source_beers": list(map(int, meta.beer.iloc[source_rows
])), "training_n": len(train),
        "geometry": "Frozen first-round 239-source-excluded copula; unchanged
full-rank NN support",
        "threshold_scenarios": scenario_list, "threshold_robustness": "simulta
neous intersection of all 10 scenarios",
        "target_improvement_minimum": .1, "latent_rms_change_minimum": .05,
        "support_nn_q95": support_limit, "lambdas": LAMBDAS,
        "default_pool": DEFAULT_POOL, "default_lambda": DEFAULT_LAMBDA,
        "matched_pool_candidates": N_GENERATED * 4 + 4, "combined_candidates":
 N_GENERATED * 8 + 4,
        "base_draws_equal": bool(np.array_equal(old_draws.to_numpy(), new_draw
s.to_numpy())),
        "proxy_experiment": "fixed_single_target_extra_trees_followup",
        "proxy_qualified": qualified, "selection_models": 40, "audit_models":
20,
        "default_policy": {"sources": len(default),
                           "selected": int(default.candidate_index.notna().sum
()) if "candidate_index" in default else 0,
                           "model_checks_passed_all_thresholds": int(default.a
ll_model_checks_passed.sum()),
                           "cross_proxy_checks_passed_all_thresholds": int(def
ault.cross_proxy_checks_passed.sum()),
                           "audit_failed": int(default.status.eq("resampling_a
```

```
udit_failed").sum()),
                                "no_candidate": int(default.status.eq("no_candidate
_found").sum())},
        "archived_baseline": {"model_checks_passed_median_only": int(archived.
all_model_checks_passed.sum()),
                                    "model_checks_passed_all_thresholds_same_spectra
": old_all_grid},
        "limitations": [
            "All ten chemical thresholds are enforced by construction; robustn
ess outside this grid is not established.",
            "Proxy audit quantiles are uncalibrated and do not certify actual
tasting outcomes.",
            "New random splits reuse the same 250 beers and are not independen
t external validation.",
            "Proxy family choice is an exploratory follow-up; repeated splits
do not replace an external test set.",
            "The old committee is a frozen architecture-consistency check, nev
er used to reselect candidates.",
            "Combined-pool gains are reported separately from matched-budget g
enerator comparisons.",
        ],
    }
    (OUT / "summary.json").write_text(json.dumps(summary, ensure_ascii=False,
indent=2), encoding="utf-8", newline="\n")
    print(json.dumps(summary["default_policy"], ensure_ascii=False, indent=2),
 flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/14_q3_optimization_report.py

SHA-256: 285c5096f0b8863567c4b0d03f5334353c6dbf5c5d8e88c79b844ebf4879340c

```
"""Summarize nested generation, weak-proxy experiments and robust transfer."""
import json

import joblib
import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd

from common import SOLUTION
from q3_data import load_q3_data

OUT = SOLUTION / "outputs/q3_optimized"
OLD = SOLUTION / "outputs/q3"
STYLES = ["Tripel", "Kriek", "Lambic", "Pils/Lager"]


def read_json(path):
    return json.loads(path.read_text(encoding="utf-8"))


def main():
    meta, x, y, manifest = load_q3_data()
    figures = OUT / "figures"
    figures.mkdir(parents=True, exist_ok=True)
    generation = read_json(OUT / "generation/summary.json")
    search = read_json(OUT / "stale/summary.json")
    fixed = read_json(OUT / "stale_fixed/summary.json")
    transfer = read_json(OUT / "transfer/summary.json")
    gen_cv = pd.read_csv(OUT / "generation/cv_summary.csv")
    transfer_table = pd.read_csv(OUT / "transfer/transfer_summary.csv")
    default = transfer_table[transfer_table.is_default_policy].sort_values("so
urce_beer")
    interval = fixed["paired_cluster_bootstrap"]
    fixed_metrics = pd.DataFrame(fixed["pooled_repeat_metrics"]).set_index("me
thod")
    search_metrics = pd.DataFrame(search["pooled_repeat_metrics"]).set_index("
method")
    source_holdout = pd.DataFrame(fixed["pils_holdout_metrics"]).set_index("mo
del")
    profile_model = joblib.load(OLD / "sensory/sensory_model.joblib")
    stale_model = joblib.load(OUT / "stale_fixed/transfer_stale_model.joblib")
    profiles, profile_rows = [], []
    for style in STYLES:
        generated = pd.read_csv(OUT / f"generation/generated_{style.replace('/
', '-')}.csv")
        pred = profile_model["pipeline"].predict(generated[x.columns])
        pred[:, y.columns.get_loc("stale_hops")] = stale_model["pipeline"].pre
dict(generated[x.columns])
        profile = pd.DataFrame(pred, columns=y.columns)
        profile.insert(0, "target_style", style)
        profile.insert(0, "sample_id", generated.sample_id)
        profiles.append(profile)
        for j, target in enumerate(y.columns):
            profile_rows.append({"style": style, "target": target,
                                 "predicted_mean": float(pred[:, j].mean()),
                                 "predicted_p05": float(np.quantile(pred[:, j]
, .05)),
```

```
                                    "predicted_p95": float(np.quantile(pred[:, j], .95)),
                                    "real_observed_mean": float(y.loc[meta.tasting_category_fine.eq(style), target].mean()),
                                    "scale": "attachment_4_standardized",
                                    "prediction_model": "fixed_stale_forest_239_non_pils" if target == "stale_hops"
                                                        else "original_45_output_forest_250",
                                    "interval_meaning": "generated_spectrum_spread_not_confidence_interval"})
    pd.concat(profiles, ignore_index=True).to_csv(OUT / "generated_sensory_profiles.csv", index=False, lineterminator="\n")
    new_profiles = pd.DataFrame(profile_rows)
    new_profiles.to_csv(OUT / "generated_sensory_summary.csv", index=False, lineterminator="\n")
    old_profiles = pd.read_csv(OLD / "generated_sensory_summary.csv")

    # Aggregate chemical rechecks independently of the proxy model counts.
    old_grid = pd.read_csv(OUT / "transfer/archived_threshold_recheck.csv")
    new_grid = pd.read_csv(OUT / "transfer/threshold_sensitivity.csv")
    scenario_rows = []
    for scenario in transfer["threshold_scenarios"]:
        name = scenario["scenario"]
        archived = old_grid[old_grid.scenario.eq(name)]
        current = new_grid[new_grid.scenario.eq(name)].groupby("transfer_id").passed.all()
        current_checks = default.transfer_id.map(current).fillna(False)
        scenario_rows.append({"scenario": name, "statistic": scenario["statistic"], "factor": scenario["factor"],
                              "old_model_checks_and_chemical": int((archived.old_model_checks_passed & archived.chemical_passed).sum()),
                              "new_chemical_only": int(current_checks.sum()),
                              "new_model_checks_and_chemical": int((current_checks & default.all_model_checks_passed).sum()),
                              "cross_proxy_checks_and_chemical": int((current_checks & default.cross_proxy_checks_passed).sum())})
    scenario_counts = pd.DataFrame(scenario_rows)
    scenario_counts.to_csv(OUT / "transfer/threshold_pass_counts.csv", index=False, lineterminator="\n")

    plt.rcParams.update({"font.family": "DejaVu Sans", "font.size": 10,
                         "axes.spines.top": False, "axes.spines.right": False,
                         "figure.facecolor": "white", "savefig.facecolor": "white"})
    fig, axes = plt.subplots(1, 2, figsize=(12, 5.4))
    for offset, method, label, color in [(-.24, "legacy_copula", "Old copula", "#9CA1A8"),
                                         (0, "nested_selected", "Optimized selection", "#2877A6"),
                                         (.24, "style_bootstrap", "Style bootstrap", "#C68B2B")]:
        part = gen_cv[gen_cv.method.eq(method)].set_index("style").loc[["Kriek", "Lambic"]]
        axes[0].bar(np.arange(2) + offset, part.energy_pca5_mean, .22, color=color,
                    yerr=part.energy_pca5_std, capsize=3, label=label,
                    error_kw={"elinewidth": 1, "ecolor": "#555B62"})
    axes[0].set_xticks([0, 1], ["Kriek", "Lambic"])
    axes[0].set_ylabel("Energy discrepancy (V-statistic)")
    axes[0].set_title("Style generation on matched outer splits", loc="left", pad=34)
```

```
    axes[0].legend(frameon=False, fontsize=8, ncol=3, loc="lower center", bbox_to_anchor=(.5, 1.005))
    method_specs = [("mean", "Mean", "#C4C7CC"),
                    ("old_multioutput_extra_trees", "Old 45-output", "#9CA1A8"),
                    ("fixed_single_extra_trees", "Dedicated tree", "#2877A6")]
    for offset, (method, label, color) in zip([-.24, 0, .24], method_specs):
        values = [search_metrics.loc[method, "rmse"], fixed_metrics.loc[method, "rmse"]]
        axes[1].bar(np.arange(2) + offset, values, .22, color=color, label=label)
        for i, value in enumerate(values):
            axes[1].text(i + offset, value + .001, f"{value:.4f}", ha="center", va="bottom", fontsize=8)
    axes[1].set_xticks([0, 1], ["Search-stage splits", "Follow-up splits"])
    axes[1].set_ylabel("Stale hops pooled repeated OOF RMSE")
    axes[1].set_ylim(0, .52)
    axes[1].set_title("Prediction gains remain uncertain", loc="left", pad=34)
    axes[1].legend(frameon=False, fontsize=8, ncol=3, loc="lower center", bbox_to_anchor=(.5, 1.005))
    for ax in axes:
        ax.grid(axis="y", color="#E5E8EC", linewidth=.7)
        ax.set_axisbelow(True)
    fig.text(.08, .025, "Generation: 2 x 3 outer folds, training-only method selection; bars show mean and descriptive fold SD.\n"
             "Prediction: two repeated five-fold splits per stage. Dedicated-tree advantage has a paired interval crossing zero.",
             fontsize=9, color="#555B62")
    fig.subplots_adjust(left=.08, right=.98, top=.79, bottom=.23, wspace=.35)
    fig.savefig(figures / "generation_and_prediction.png", dpi=300)
    fig.savefig(figures / "generation_and_prediction.svg")
    plt.close(fig)

    fig, ax = plt.subplots(figsize=(11.4, 5.6))
    positions = np.arange(len(scenario_counts))
    for field, label, color, marker in [
        ("old_model_checks_and_chemical", "Archived selection + original proxy", "#969DA5", "o"),
        ("new_model_checks_and_chemical", "Robust chemical + new proxy checks", "#2877A6", "s"),
        ("cross_proxy_checks_and_chemical", "Robust chemical + both proxy committees", "#C68B2B", "D")]:
        ax.plot(positions, scenario_counts[field], marker=marker, color=color, linewidth=1.6, label=label)
    ax.set_xticks(positions, [f"{r.statistic}\nx{r.factor:g}" for r in scenario_counts.itertuples()])
    ax.set_ylim(-.4, 11.5)
    ax.set_yticks(range(0, 12))
    ax.set_ylabel("Sources passing the specified checks / 11")
    ax.set_title("One selected spectrum per source, checked across ten threshold scenarios", loc="left", fontsize=13, pad=17)
    ax.axvline(4.5, color="#D8DDE3", linewidth=1)
    ax.legend(frameon=False, fontsize=9, loc="upper right")
    ax.grid(axis="y", color="#E5E8EC", linewidth=.7)
    ax.set_axisbelow(True)
    fig.text(.09, .025, "Same 2004-candidate budget; the robust method enforces the intersection of all chemical scenarios before selection.\n"
             "Proxy checks are uncalibrated diagnostics; weaker cross-style prediction has not been resolved. No audit-based reselection.",
             fontsize=9, color="#555B62")
    fig.subplots_adjust(left=.09, right=.98, top=.85, bottom=.24)
    fig.savefig(figures / "threshold_stability.png", dpi=300)
```

```
    fig.savefig(figures / "threshold_stability.svg")
    plt.close(fig)

    attributes = ["A_malt_all", "F_malt_all", "A_hops_all", "F_hops_all", "A_esters_all",
                  "F_esters_all", "acidity", "bitternes", "sweetness"]
    values, labels = [], []
    for style in ["Kriek", "Lambic"]:
        old_part = old_profiles[old_profiles["style"].eq(style)].set_index("target").loc[attributes]
        new_part = new_profiles[new_profiles["style"].eq(style)].set_index("target").loc[attributes]
        values.extend([old_part.predicted_mean, new_part.predicted_mean, new_part.real_observed_mean])
        labels.extend([f"{style}: old", f"{style}: optimized", f"{style}: observed"])
    values = np.asarray(values)
    bound = max(np.abs(values).max(), .5)
    fig, ax = plt.subplots(figsize=(11.8, 5.2))
    im = ax.imshow(values, cmap="RdBu_r", vmin=-bound, vmax=bound, aspect="auto")
    ax.set_yticks(np.arange(len(labels)), labels)
    ax.set_xticks(np.arange(len(attributes)), ["Malt\naroma", "Malt\nflavour", "Hops\naroma", "Hops\nflavour",
                                               "Esters\naroma", "Esters\nflavour", "Acidity", "Bitterness", "Sweetness"])
    for (i, j), value in np.ndenumerate(values):
        ax.text(j, i, f"{value:.2f}", ha="center", va="center", fontsize=9,
                color="white" if abs(value) > bound * .65 else "#25282D")
    ax.set_title("Generated sensory fingerprints: old and optimized", loc="left", fontsize=14, pad=15)
    fig.colorbar(im, ax=ax, shrink=.85, label="Attachment-standardized value")
    fig.text(.19, .025, "300 spectra per style. Old and optimized rows are model predictions; observed rows summarize existing panel scores.\n"
             "This descriptive fingerprint is not independent sensory validation and is not the original 0-6 scale.",
             fontsize=9, color="#555B62")
    fig.subplots_adjust(left=.19, right=.96, top=.85, bottom=.24)
    fig.savefig(figures / "sensory_fingerprint_comparison.png", dpi=300)
    fig.savefig(figures / "sensory_fingerprint_comparison.svg")
    plt.close(fig)

    generation_rows = []
    gains = {}
    for style in STYLES:
        table = gen_cv[gen_cv["style"].eq(style)].set_index("method")
        old, new, bootstrap = table.loc["legacy_copula"], table.loc["nested_selected"], table.loc["style_bootstrap"]
        gain = 1 - new.energy_pca5_mean / old.energy_pca5_mean
        gains[style] = float(gain)
        generation_rows.append(f"| {style} | {old.energy_pca5_mean:.4f} | {new.energy_pca5_mean:.4f} | "
                               f"{gain * 100:+.1f}% | {bootstrap.energy_pca5_mean:.4f} | "
                               f"{old.marginal_w1_iqr_median_mean:.4f} → {new.marginal_w1_iqr_median_mean:.4f} |")
    stale_rows = []
    for label, table in [("模型搜索阶段", search_metrics), ("固定方案后续复核", fixed_metrics)]:
        for method, name in [("old_multioutput_extra_trees", "旧45目标森林"),
                             ("fixed_single_extra_trees", "固定单目标森林")]:
            row = table.loc[method]
```

```
            stale_rows.append(f"| {label} | {name} | {row.rmse:.4f} | {row.r2:.4f} | "
                              f"{row.spearman:.4f} | {row.prediction_std_ratio:.3f} |")
    status_names = {"model_checks_passed": "新代理审计通过", "resampling_audit_failed": "新代理审计未通过",
                    "no_candidate_found": "未找到候选", "proxy_not_qualified": "代理训练内资格不足",
                    "proxy_uninformative": "代理对候选缺少响应", "source_defect_unverifiable": "源缺陷不可核验"}
    transfer_rows = []
    for row in default.itertuples():
        improvement = f"{100 * row.target_improvement:.1f}%" if pd.notna(row.candidate_index) else "—"
        transfer_rows.append(f"| {row.source_beer} | {status_names[row.status]} | {improvement} | "
                             f"{row.audit_q95:+.4f} | {'是' if row.cross_proxy_checks_passed else '否'} |")
    counts = transfer["default_policy"]
    ci = interval["rmse_difference_percentile95"]
    delta = interval["point_rmse_difference"]
    report = f"""# 第三问优化：风格保真性、缺陷预测与阈值稳健迁移

日期：2026-10-23。原始第三问65个结果文件已冻结并逐文件校验；优化结果另存 `../outputs/q3_optimized/`。

## 1. 本轮结论

- Kriek、Lambic的嵌套选择生成算法，在匹配外层划分和共同评价坐标下，能量差异指标较旧模型分别降低 **{100 * gains['Kriek']:.1f}%**、**{100 * gains['Lambic']:.1f}%**。两者仍略逊于重采样，不能称所有质量指标全面胜出。
- Stale hops专用树在后续重复切分中，RMSE由 **{fixed_metrics.loc['old_multioutput_extra_trees', 'rmse']:.4f}** 降为 **{fixed_metrics.loc['fixed_single_extra_trees', 'rmse']:.4f}**，下降 **{fixed['rmse_reduction_vs_old_multioutput'] * 100:.2f}%**。按beer配对重采样的差异区间跨零，且Pils整风格留出更差，**尚未证实稳定的预测提升**。
- 默认迁移在10个预定阈值情景下同时约束化学保护，11款源均找到候选，**{counts['model_checks_passed_all_thresholds']}**款通过新代理检查，**{counts['cross_proxy_checks_passed_all_thresholds']}**款同时通过旧冻结代理检查。旧固定谱在同一完整阈值网格下通过全部模型与化学检查的数量为 **{transfer['archived_baseline']['model_checks_passed_all_thresholds_same_spectra']}**。

模型检查仅定义本次候选筛查的通过范围，不证明实际品评结果。阈值稳健性与感官预测准确性分别报告。

## 2. 生成模型：保留风格局部边缘

旧模型采用全局经验边缘并向全局均值收缩，会削弱小样本风格的独特分布。本轮预声明三个候选：风格局部边缘copula、风格中心平滑混合、旧copula。局部模型保留目标风格边缘支持；平滑混合使用固定0.45噪声强度。内层使用新颖性门槛，避免以近似复制训练行制造误差下降。

外层为2×3折风格分层切分，种子20261123、20262123；每个训练集内2折选择方法，所有候选统一在该训练折旧copula的高斯秩空间及5维PCA参考坐标下评价。每折每法300条、2个模拟种子。内层选择不读取外层目标数据；这些新划分仍复用同一250款酒，属于重复内部验证。

| 风格 | 旧模型能量差异 | 嵌套选择能量差异 | 相对下降 | 重采样对照 | W1跨特征中位数：旧→新 |
|---|---:|---:|---:|---:|---:|
{chr(10).join(generation_rows)}

能量指标为未开平方的经验V统计量，越小越好。平均W1、相关差异、零频率、多样性和复制检查也完整保存；Kriek平均W1仍被极端化合物支配，不能只看某一项指标。外层折与重复并不独立，折间标准差不是置信区间。
```

全250款重新训练后的风格选择为 `{json.dumps(generation['full_selected_methods'], ensure_ascii=False)}`。四风格各生成300条谱，原始完整行及忽略训练缺失格后的观测行复制率均为0。

![生成与预测对照](../outputs/q3_optimized/figures/generation_and_prediction.png)

3. Stale hops：比较失败与有限改善均保留

18个配置包括稳健线性、PLS、SVR和树模型；特征限于226个化学指标及附件aging元数据确定的子集，不使用实际其他感官评分或评论特征。处理、筛选和调参均在训练折内部。内层预测方差比至少0.05才进入合格配置，再按RMSE选择。

搜索算法本身的嵌套结果为RMSE **{search_metrics.loc['nested_selected', 'rmse']:.4f}**，劣于同划分旧森林的 **{search_metrics.loc['old_multioutput_extra_trees', 'rmse']:.4f}**。因此没有把外层表现最好的家族直接替代为“无偏最优模型”。

固定单目标森林保留原基线的300树、min_leaf=3、max_features=0.7参数，不再调参；在额外种子20263123、20264123的5折切分复核。这个后续算法选择由前一轮结果触发，因此仍是探索性复核，并非全新独立测试。

阶段	模型	重复OOF RMSE	R^2	Spearman	预测SD/实际SD
{chr(10).join(stale_rows)}

固定方案两次切分一好一坏。先按beer平均两次切分平方误差，再对250款酒做2000次配对重采样：`新RMSE−旧RMSE` 点差 **{delta:+.5f}**，95%分位区间 **[{ci[0]:+.5f}, {ci[1]:+.5f}]**，包含零。它只描述已保存OOF误差的抽样波动，不包含模型选择过程，也没有重拟合模型。

Pils整风格留出11款时，专用树RMSE为 **{source_holdout.loc['fixed_single_extra_trees', 'rmse']:.4f}**，劣于均值 **{source_holdout.loc['non_pils_mean', 'rmse']:.4f}** 和旧代理 **{source_holdout.loc['old_multioutput_transfer_proxy', 'rmse']:.4f}**。这说明内部小幅改善未转化为跨风格预测提升。迁移代理资格门槛仅来自239款非Pils训练内验证，不等于已经通过源风格外推验证。

4. 同时保护10种阈值情景

定义情景集合为中位数/均值两种口径分别乘以0.8、0.9、1.0、1.1、1.2。对每个缺陷要求所有情景的超阈程度均不增加：

`c'_d ≤ min_s max(T[d,s], c_source[d]) = max(min_s T[d,s], c_source[d])`。

相应最严格阈值为DMS **13.8 μg/L**、Diacetyl **0.072 mg/L**、4VG **0.16 mg/L**。trans-2-nonenal没有附件阈值，继续采用浓度不得增加。保护依据为源的观测校准值，不以插补值替代。

迁移仍排除全部11款Pils训练数据，使用冻结的原239款训练几何和完整226维最近邻支持规则；目标距离至少改善10%、改动RMS至少0.05的条件保持不变。新旧生成器各500条、4个插值比例加4个共同目标中位谱，匹配预算均为2004候选；合并池4004候选单独报告。

239款重新训练的Tripel生成方法仍为旧copula，相同种子的新旧基础池完全一致：**{transfer['base_draws_equal']}**。因此本轮Tripel迁移改善不能归因于生成器更换，主要改变来自同时阈值约束和专用代理筛选；Kriek、Lambic的生成改善是独立结果。

专用代理有60个固定结构bootstrap模型，前40个筛选，后20个仅审计已选谱；方差和候选差异门槛用于识别近常数代理。旧30/10委员会仅对已选谱做冻结架构一致性检查，不参与重选。所有模型均排除全部11款源；不同模型仍共享239款真实训练数据，分位数不是95%真实风味保证。

源beer	默认方案状态	目标距离改善	新代理审计Q95	同时通过旧代理
{chr(10).join(transfer_rows)}

默认有 **{counts['model_checks_passed_all_thresholds']}/11** 通过新代理检查、**{counts['cross_proxy_checks_passed_all_thresholds']}/11** 通过新旧代理共同检查，其化学保护在全部10个阈值情景中保持通过。这里的稳定性来自预先施加的情景交集约束，不能外推为任意未知阈

值下都稳定。

![阈值稳定性](../outputs/q3_optimized/figures/threshold_stability.png)

5. 画像与结果文件

![风格画像对照](../outputs/q3_optimized/figures/sensory_fingerprint_comparison.png)

四种风格各300条谱及1200×45画像已保存。其他44维使用原全量感官预测器，Stale hops由本轮239款非Pils专用树输出；没有把它们描述为全45维新训练模型。感官尺度仍为附件标准化数值，不能当作恢复的原始0–6分。

- 生成谱与完整分布验证：`../outputs/q3_optimized/generation/`。
- 18配置嵌套搜索：`../outputs/q3_optimized/stale/`；固定专用树复核：`../outputs/q3_optimized/stale_fixed/`。
- 逐项情景保护、候选筛选、审计及三种λ结果：`../outputs/q3_optimized/transfer/`。
- 画像：`../outputs/q3_optimized/generated_sensory_profiles.csv` 和 `generated_sensory_summary.csv`。
- 实现：`11_q3_generation_optimized.py`、`12_q3_stale_optimized.py`、`12b_q3_stale_fixed.py`、`13_q3_transfer_optimized.py`。
- 一键复现：仓库根目录执行 `.venv/bin/python solution_a/run_q3_optimized.py`。原第三问对照已冻结，此入口不重写旧结果。

方法与审查详见 `q3_generation_optimized.md`、`q3_stale_optimized.md`、`q3_optimization_review.md`。数值校验见 `../outputs/q3_optimized/verification.json`。当前结果不包含真实酿造或迁移后的品评实验，Stale hops预测可靠性仍是主要瓶颈。
"""
    (SOLUTION / "docs/q3_optimization_results.md").write_text(report, encoding="utf-8", newline="\n")
    summary = {"generation_energy_reduction_vs_matched_legacy": gains,
               "fixed_stale_rmse_reduction_vs_matched_old": fixed["rmse_reduction_vs_old_multioutput"],
               "paired_rmse_difference_interval": ci,
               "stale_improvement_stably_established": False,
               "source_style_prediction_improved": fixed["pils_holdout_improves_old"],
               "default_transfer": counts, "base_draws_equal": transfer["base_draws_equal"]}
    (OUT / "results_summary.json").write_text(json.dumps(summary, ensure_ascii=False, indent=2), encoding="utf-8", newline="\n")
    print(json.dumps(summary, ensure_ascii=False, indent=2), flush=True)

if __name__ == "__main__":
    main()

src/15_q3_optimized_verify.py

SHA-256: 237c77ca0ffc4b5d22df880087508302ffae20567b106bfd84844b8e977ff17c

```
"""Verify preserved baselines, nested selection and robust transfer outputs.""
"
from __future__ import annotations

import hashlib
import importlib
import json
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from scipy.stats import spearmanr
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.model_selection import KFold, StratifiedKFold
from threadpoolctl import threadpool_limits

from common import SOLUTION, data_dir

BASE = importlib.import_module("10_q3_verify")
OUT = SOLUTION / "outputs/q3_optimized"
TOL = 1e-10


def score(truth, prediction):
    truth, prediction = np.asarray(truth, float), np.asarray(prediction, float
)
    tv, pv = np.var(truth), np.var(prediction)
    tr = np.quantile(truth, .95) - np.quantile(truth, .05)
    pr = np.quantile(prediction, .95) - np.quantile(prediction, .05)
    return {"mae": mean_absolute_error(truth, prediction),
            "rmse": np.sqrt(mean_squared_error(truth, prediction)),
            "r2": r2_score(truth, prediction),
            "spearman": spearmanr(truth, prediction).statistic if pv > 1e-20 e
lse np.nan,
            "prediction_variance": pv, "target_variance": tv,
            "prediction_variance_ratio": pv / tv,
            "prediction_std_ratio": np.sqrt(pv / tv),
            "prediction_range90": pr, "target_range90": tr,
            "prediction_range90_ratio": pr / tr, "mean_bias": np.mean(predicti
on - truth)}


def check_baseline():
    manifest = BASE.read_json(OUT / "baseline_hashes.json")
    baseline = SOLUTION / "outputs/q3"
    expected = {row["path"] for row in manifest["files"]}
    actual = {path.relative_to(baseline).as_posix() for path in baseline.rglob
("*") if path.is_file()}
    assert actual == expected and len(actual) == manifest["file_count"]
    for row in manifest["files"]:
        raw = (baseline / row["path"]).read_bytes()
        assert len(raw) == row["bytes"] and hashlib.sha256(raw).hexdigest() ==
 row["sha256"], row["path"]
    return {"unchanged_files": len(actual), "hash_algorithm": "sha256"}


def winner(rows):
```

```
    qualified = rows[rows.nonconstant_qualified]
    accepted = qualified if len(qualified) else rows
    return accepted.sort_values(["rmse", "candidate"]).iloc[0]


def check_pipeline_training(pipeline, training, calibrated):
    chemical = pipeline.named_steps["chemical"]
    names = chemical.selected_features_
    values = training[names].to_numpy().copy()
    scales = np.ones(len(names))
    for j, name in enumerate(names):
        if name in calibrated:
            positives = values[:, j][np.isfinite(values[:, j]) & (values[:, j]
 > 0)]
            scales[j] = np.median(positives) if len(positives) else 1.0
            values[:, j] = np.log1p(values[:, j] / scales[j])
    BASE.close(chemical.positive_scales_, scales, "Training-only positive scal
es")
    bounds = np.nanquantile(values, [.01, .99], axis=0)
    BASE.close(chemical.bounds_, bounds, "Training-only clipping bounds")
    clipped = np.clip(values, bounds[0], bounds[1])
    medians = np.nanmedian(clipped, axis=0)
    medians = np.nan_to_num(medians, nan=0.0)
    imputer = pipeline.named_steps["imputer"]
    BASE.close(imputer.statistics_, medians, "Training-only imputation medians
")
    indicators = np.flatnonzero(np.isnan(clipped).any(axis=0))
    np.testing.assert_array_equal(imputer.indicator_.features_, indicators)
    filled = np.where(np.isnan(clipped), medians, clipped)
    filled = np.column_stack([filled, np.isnan(clipped)[:, indicators]])
    BASE.close(pipeline.named_steps["scale"].mean_, filled.mean(axis=0), "Trai
ning-only scaling means")
    BASE.close(pipeline.named_steps["scale"].var_, filled.var(axis=0), "Traini
ng-only scaling variances")


def check_stale(context):
    folder = OUT / "stale"
    meta, x, y45 = context["meta"], context["x"], context["y"]
    y = y45.stale_hops
    manifest = BASE.read_json(folder / "run_manifest.json")
    summary = BASE.read_json(folder / "summary.json")
    oof = pd.read_csv(folder / "oof_predictions.csv")
    stored_metrics = pd.read_csv(folder / "metrics.csv")
    stored_folds = pd.read_csv(folder / "metrics_by_fold.csv")
    choices = pd.read_csv(folder / "nested_selected_configs.csv")
    inner = pd.read_csv(folder / "nested_inner_cv_results.csv")
    specs = {spec["name"]: spec for spec in manifest["candidate_specs"]}
    assert manifest["features"] == x.columns.tolist() and len(specs) == summar
y["candidate_count"]
    assert not oof.duplicated(["repeat", "method", "beer"]).any()
    methods = sorted(oof.method.unique())
    metrics, folds = [], []
    for repeat, seed in enumerate(manifest["outer_seeds"], 1):
        expected_fold = np.zeros(len(x), int)
        for fold, (_, test) in enumerate(KFold(manifest["outer_folds"], shuffl
e=True, random_state=seed).split(x), 1):
            expected_fold[test] = fold
        for method in methods:
            group = oof[oof.repeat.eq(repeat) & oof.method.eq(method)].set_ind
ex("beer").loc[meta.beer]
            assert len(group) == len(x) and group.outer_seed.eq(seed).all()
```

```
            np.testing.assert_array_equal(group.fold, expected_fold)
            BASE.close(group.observed, y, "Repeated OOF observed labels")
            assert np.isfinite(group.prediction).all()
            metrics.append({"scope": "per_seed", "repeat": repeat, "method": m
ethod,
                            **score(group.observed, group.prediction)})
            for fold in range(1, manifest["outer_folds"] + 1):
                test = expected_fold == fold
                folds.append({"repeat": repeat, "fold": fold, "method": method
,
                              **score(y.loc[test], group.prediction.to_numpy()
[test])})
                if method == "mean":
                    BASE.close(group.prediction.to_numpy()[test], y.loc[~test]
.mean(), "Fold-mean stale baseline")
    for method in methods:
        group = oof[oof.method.eq(method)]
        metrics.append({"scope": "pooled_repeated_oof", "repeat": 0, "method":
 method,
                        **score(group.observed, group.prediction)})
    columns = list(score(y, y))
    BASE.same_table(stored_metrics, pd.DataFrame(metrics), ["scope", "repeat",
 "method"], columns,
                    "Repeated nested stale metrics")
    BASE.same_table(stored_folds, pd.DataFrame(folds), ["repeat", "fold", "met
hod"], columns,
                    "Nested stale fold metrics")
    gate = manifest["nonconstant_variance_ratio_min"]
    assert inner.nonconstant_qualified.equals(inner.prediction_variance_ratio.
ge(gate))
    assert set(inner.candidate) == set(specs)
    for row in choices.itertuples(index=False):
        candidates = inner[inner.repeat.eq(row.repeat) & inner.outer_fold.eq(r
ow.outer_fold)]
        if row.method.startswith("nested_family_"):
            candidates = candidates[candidates.family.eq(row.method.removepref
ix("nested_family_"))]
        selected = winner(candidates)
        assert row.selected_candidate == selected.candidate
        assert row.nonconstant_qualified == selected.nonconstant_qualified
        BASE.close(row.inner_oof_rmse, selected.rmse, "Training-only nested ca
ndidate choice")
        assert row.outer_seed in manifest["outer_seeds"]
    excluded = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    training = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    artifact = joblib.load(folder / "transfer_stale_model.joblib")
    ensemble = joblib.load(folder / "bootstrap_ensemble.joblib")
    transfer_inner = pd.read_csv(folder / "transfer_inner_cv_results.csv")
    selected = winner(transfer_inner)
    assert artifact["selected_config"] == specs[selected.candidate] == ensembl
e["selected_config"]
    inner_oof = pd.read_csv(folder / "transfer_selected_inner_oof.csv")
    np.testing.assert_array_equal(inner_oof.beer, meta.beer.iloc[training])
    BASE.close(inner_oof.observed, y.iloc[training], "Transfer inner observed
labels")
    selected_score = score(inner_oof.observed, inner_oof.selected_inner_oof_pr
ediction)
    BASE.close([selected[name] for name in columns], [selected_score[name] for
 name in columns],
               "Transfer selected inner OOF metrics")
    expected_mean = np.empty(len(training))
    for train, test in KFold(manifest["inner_folds"], shuffle=True, random_sta
```

```
te=manifest["transfer_cv_seed"]).split(training):
155         expected_mean[test] = y.iloc[training[train]].mean()
156     BASE.close(inner_oof.mean_inner_oof_prediction, expected_mean, "Transfer i
    nner fold-mean baseline")
157     mean_rmse = score(y.iloc[training], expected_mean)["rmse"]
158     qualified = bool(selected.prediction_variance_ratio >= gate and selected.r
    mse < mean_rmse)
159     assert qualified == artifact["qualified_for_proxy"] == ensemble["qualified
    _for_proxy"]
160     assert qualified == summary["transfer_qualified_for_proxy"]
161     for saved in [artifact, ensemble]:
162         np.testing.assert_array_equal(saved["train_global_indices"], training)
163         np.testing.assert_array_equal(saved["excluded_global_indices"], exclud
    ed)
164         assert saved["features"] == x.columns.tolist()
165     check_pipeline_training(artifact["pipeline"], x.iloc[training], context["c
    alibrated_features"])
166     indices = np.asarray(ensemble["bootstrap_indices"])
167     assert indices.shape == (60, len(training)) and not np.isin(indices, exclu
    ded).any()
168     assert np.isin(indices, training).all()
169     assert ensemble["selection_model_indices"] == list(range(40))
170     assert ensemble["audit_model_indices"] == list(range(40, 60))
171     assert ensemble["hyperparameter_uncertainty_included"] is False
172     with np.load(folder / "bootstrap_indices.npz") as saved:
173         np.testing.assert_array_equal(saved["indices"], indices)
174         np.testing.assert_array_equal(saved["bootstrap_seeds"], ensemble["boot
    strap_seeds"])
175         np.testing.assert_array_equal(saved["estimator_seeds"], ensemble["esti
    mator_seeds"])
176     for i, (model, index, seed) in enumerate(zip(ensemble["models"], indices,
    ensemble["bootstrap_seeds"])):
177         expected_seed = manifest["selection_bootstrap_seed"] + i if i < 40 els
    e manifest["audit_bootstrap_seed"] + i - 40
178         assert seed == expected_seed
179         expected_index = np.random.default_rng(seed).choice(training, size=len
    (training), replace=True)
180         np.testing.assert_array_equal(index, expected_index)
181         check_pipeline_training(model, x.iloc[index], context["calibrated_feat
    ures"])
182     heldout = pd.read_csv(folder / "pils_style_holdout_predictions.csv")
183     np.testing.assert_array_equal(heldout.beer, meta.beer.iloc[excluded])
184     BASE.close(heldout.observed, y.iloc[excluded], "Pils holdout observed labe
    ls")
185     BASE.close(heldout.prediction, np.asarray(artifact["pipeline"].predict(x.i
    loc[excluded])).reshape(-1),
186                "Pils holdout frozen model predictions")
187     holdout_metrics = pd.read_csv(folder / "pils_style_holdout_metrics.csv").s
    et_index("model")
188     for method, pred in [("optimized_single_target", heldout.prediction),
189                          ("non_pils_mean", heldout.mean_baseline_prediction)]:
190         BASE.close(holdout_metrics.loc[method, columns], list(score(heldout.ob
    served, pred).values()),
191                    "Pils source holdout metrics")
192     context.update({"optimized_stale": artifact, "optimized_ensemble": ensembl
    e,
193                     "optimized_train": training, "optimized_sources": excluded
    })
194     main = stored_metrics[stored_metrics.scope.eq("pooled_repeated_oof")].set_
    index("method")
195     return {"outer_seeds": manifest["outer_seeds"], "outer_folds": manifest["o
    uter_folds"],
```

```
            "candidate_count": len(specs), "nested_choices_recomputed": len(ch
oices),
            "transfer_config": artifact["selected_config"], "qualified_for_pro
xy": qualified,
            "training_rows": len(training), "excluded_sources": len(excluded),
            "bootstrap_shape": list(indices.shape), "preprocessing_training_ch
ecks": 61,
            "nested_selected_rmse": float(main.loc["nested_selected", "rmse"])
,
            "old_multioutput_same_split_rmse": float(main.loc["old_multioutput
_extra_trees", "rmse"]),
            "fixed_single_tree_rmse": float(main.loc["fixed_single_extra_trees
", "rmse"]),
            "pils_holdout_rmse": float(holdout_metrics.loc["optimized_single_t
arget", "rmse"]),
            "pils_holdout_mean_rmse": float(holdout_metrics.loc["non_pils_mean
", "rmse"])}


def check_generation(context):
    folder = OUT / "generation"
    meta, x = context["meta"], context["x"]
    summary = BASE.read_json(folder / "summary.json")
    assignments = pd.read_csv(folder / "cv_assignments.csv")
    metrics = pd.read_csv(folder / "cv_metrics.csv")
    inner = pd.read_csv(folder / "inner_scores_outer.csv")
    choices = pd.read_csv(folder / "inner_selection_outer.csv")
    assert not assignments.duplicated(["repeat", "row_index"]).any()
    assert len(assignments) == len(meta) * len(summary["outer_seeds"])
    assert not metrics.duplicated(["repeat", "fold", "style", "method", "mc"])
.any()
    expected_n = len(summary["outer_seeds"]) * summary["outer_folds"] * 4 * 5
* summary["mc_repeats"]
    assert len(metrics) == expected_n == summary["cv_records"]
    for repeat, seed in enumerate(summary["outer_seeds"], 1):
        for fold, (train, test) in enumerate(StratifiedKFold(3, shuffle=True,
random_state=seed).split(x, meta.tasting_category_fine), 1):
            assigned = assignments[assignments.repeat.eq(repeat) & assignments
.fold.eq(fold)]
            assert set(assigned.row_index) == set(test)
            assert assigned.beer.tolist() == assigned.row_index.map(meta.beer)
.tolist()
            subset = metrics[metrics.repeat.eq(repeat) & metrics.fold.eq(fold)
]
            assert subset.train_n.eq(len(train)).all()
            assert subset.generated_n.eq(summary["generated_n_each_draw"]).all
()
            assert set(subset.mc) == set(range(summary["mc_repeats"]))
            for style in BASE.GENERATION_STYLES:
                assert subset.loc[subset["style"].eq(style), "holdout_style_n"
].eq(
                    meta.tasting_category_fine.iloc[test].eq(style).sum()).all
()
    gates = summary["novelty_gates"]
    expected_eligible = (inner.copy_rate.eq(0) & inner.observed_training_copy_
rate.eq(0)
                         & inner.nn_ratio.ge(gates["minimum_inner_nn_ratio"])
                         & inner.nearest_equal_feature_fraction.le(gates["maxi
mum_inner_nearest_equal_fraction"]))
    assert inner.eligible.equals(expected_eligible)
    selected_lookup = {}
    for (repeat, fold, style), group in inner.groupby(["outer_repeat", "outer_
```

```
    fold", "style"]):
239         assert len(group) == 2 * len(summary["candidate_methods"])
240         grouped = group.groupby("method").agg(energy_pca5=("energy_pca5", "mea
    n"),
241                                               eligible=("eligible", "all"))
242         acceptable = grouped[grouped.eligible]
243         selected = acceptable.energy_pca5.idxmin() if len(acceptable) else "le
    gacy_copula"
244         actual = choices[choices.repeat.eq(repeat) & choices.fold.eq(fold) & c
    hoices["style"].eq(style)]
245         assert len(actual) == len(summary["candidate_methods"]) and actual.sel
    ected.sum() == 1
246         assert actual.loc[actual.selected, "method"].iloc[0] == selected
247         BASE.close(actual.set_index("method").loc[grouped.index, "energy_pca5"
    ], grouped.energy_pca5,
248                    "Generation training-only inner energy")
249         selected_lookup[(repeat, fold, style)] = selected
250     folds = pd.read_csv(folder / "cv_fold_means.csv")
251     keys = ["repeat", "fold", "style", "method"]
252     columns = [column for column in folds if column not in keys]
253     for row in metrics[metrics.method.eq("nested_selected")].itertuples(index=
    False):
254         method = selected_lookup[(row.repeat, row.fold, row.style)]
255         assert row.selected_method == method
256         match = metrics[metrics.repeat.eq(row.repeat) & metrics.fold.eq(row.fo
    ld)
257                         & metrics["style"].eq(row.style) & metrics.mc.eq(row.m
    c) & metrics.method.eq(method)]
258         assert len(match) == 1
259         BASE.close([getattr(row, column) for column in columns], match[columns
    ].iloc[0],
260                    "Nested outer outcome must equal its training-selected cand
    idate")
261     expected_fold = metrics.groupby(keys, as_index=False)[columns].mean()
262     BASE.same_table(folds, expected_fold, keys, columns, "Optimized generation
     MC fold means")
263     expected_summary = expected_fold.groupby(["style", "method"])[columns].agg
    (["mean", "std"])
264     expected_summary.columns = [f"{metric}_{stat}" for metric, stat in expecte
    d_summary.columns]
265     expected_summary = expected_summary.reset_index()
266     BASE.same_table(pd.read_csv(folder / "cv_summary.csv"), expected_summary,
    ["style", "method"],
267                     [column for column in expected_summary if column not in {"
    style", "method"}],
268                     "Optimized generation summary")
269     model = joblib.load(folder / "fullmodel.joblib")
270     assert model.columns_ == x.columns.tolist()
271     reference = model.fitted_candidates_["legacy_copula"]
272     BASE.close(reference.median_, np.nanmedian(x, axis=0), "Full optimized ref
    erence medians")
273     generated_tables, copy_count = [], 0
274     for i, style in enumerate(BASE.GENERATION_STYLES):
275         generated = pd.read_csv(folder / f"generated_{style.replace('/', '-')}
    .csv")
276         assert len(generated) == summary["generated_n_each_draw"] and generate
    d.sample_id.is_unique
277         assert generated.target_style.eq(style).all()
278         fake = generated[x.columns].to_numpy()
279         assert np.isfinite(fake).all() and generated[context["calibrated_featu
    res"]].ge(0).all().all()
280         selected = model.selected_methods_[style]
```

```
        assert selected == summary["full_selected_methods"][style]
        candidate = model.fitted_candidates_[selected]
        support = candidate.empirical_values_ if selected == "legacy_copula" e
lse candidate.tables_[style][0]
        for j in range(x.shape[1]):
            assert BASE.supported(fake[:, j], support[j]).all(), f"Unsupported
 optimized value: {style}/{x.columns[j]}"
        BASE.close(fake, model.sample(style, len(generated), summary["outer_se
eds"][0] + 900000 + i),
                   "Saved optimized generation replay")
        raw = x.to_numpy()
        copied = np.any(np.all(np.isclose(fake[:, None, :], raw[None, :, :], r
tol=1e-10, atol=1e-12)
                               | np.isnan(raw)[None, :, :], axis=2), axis=1)
        copy_count += int(copied.sum())
        assert not copied.any(), f"Observed-field training-row copy generated:
 {style}"
        generated_tables.append(generated)
    assert copy_count == 0 and summary["full_generation_observed_copy_rate"] =
= 0
    context["optimized_generated"] = pd.concat(generated_tables, ignore_index=
True)
    return {"cv_records": len(metrics), "inner_records": len(inner),
            "inner_choices_recomputed": len(selected_lookup), "generated_rows"
: sum(map(len, generated_tables)),
            "observed_training_row_copies": copy_count, "full_selected_methods
": summary["full_selected_methods"],
            "training_empirical_support": True, "nested_outcomes_match_selecte
d_methods": True}


def check_fixed_stale(context):
    folder = OUT / "stale_fixed"
    meta, x, y = context["meta"], context["x"], context["y"].stale_hops
    manifest = BASE.read_json(folder / "run_manifest.json")
    summary = BASE.read_json(folder / "summary.json")
    assert manifest["parameter_tuning"] is False and manifest["not_independent
_external_confirmation"] is True
    oof = pd.read_csv(folder / "oof_predictions.csv")
    rows, fold_rows = [], []
    columns = list(score(y, y))
    for repeat, seed in enumerate(manifest["outer_seeds"], 1):
        fold_ids = np.zeros(len(x), int)
        for fold, (_, test) in enumerate(KFold(5, shuffle=True, random_state=s
eed).split(x), 1):
            fold_ids[test] = fold
        for method in oof.method.unique():
            group = oof[oof.repeat.eq(repeat) & oof.method.eq(method)].set_ind
ex("beer").loc[meta.beer]
            assert len(group) == len(x)
            np.testing.assert_array_equal(group.fold, fold_ids)
            BASE.close(group.observed, y, "Fixed forest OOF labels")
            rows.append({"scope": "per_seed", "repeat": repeat, "method": meth
od,
                         **score(group.observed, group.prediction)})
            for fold in range(1, 6):
                test = fold_ids == fold
                fold_rows.append({"repeat": repeat, "fold": fold, "method": me
thod,
                                  **score(y.loc[test], group.prediction.to_num
py()[test])})
                if method == "mean":
```

```
                    BASE.close(group.prediction.to_numpy()[test], y.loc[~test]
.mean(), "Fixed study fold mean")
    for method in oof.method.unique():
        group = oof[oof.method.eq(method)]
        rows.append({"scope": "pooled_repeated_oof", "repeat": 0, "method": me
thod,
                     **score(group.observed, group.prediction)})
    metrics = pd.read_csv(folder / "metrics.csv")
    BASE.same_table(metrics, pd.DataFrame(rows), ["scope", "repeat", "method"]
, columns, "Fixed forest OOF metrics")
    BASE.same_table(pd.read_csv(folder / "metrics_by_fold.csv"), pd.DataFrame(
fold_rows),
                    ["repeat", "fold", "method"], columns, "Fixed forest fold
metrics")
    artifact = joblib.load(folder / "transfer_stale_model.joblib")
    ensemble = joblib.load(folder / "bootstrap_ensemble.joblib")
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    excluded = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    for saved in [artifact, ensemble]:
        np.testing.assert_array_equal(saved["train_global_indices"], train)
        np.testing.assert_array_equal(saved["excluded_global_indices"], exclud
ed)
        assert saved["features"] == x.columns.tolist() and saved["parameter_tu
ning"] is False
    inner = pd.read_csv(folder / "transfer_inner_oof.csv")
    np.testing.assert_array_equal(inner.beer, meta.beer.iloc[train])
    BASE.close(inner.observed, y.iloc[train], "Fixed transfer inner observed")
    inner_scores = score(inner.observed, inner.fixed_inner_oof_prediction)
    mean = np.empty(len(train))
    for tr, te in KFold(3, shuffle=True, random_state=manifest["transfer_cv_se
ed"]).split(train):
        mean[te] = y.iloc[train[tr]].mean()
    BASE.close(inner.mean_inner_oof_prediction, mean, "Fixed transfer fold mea
ns")
    qualified = bool(inner_scores["prediction_variance_ratio"] >= .05
                     and inner_scores["rmse"] < score(y.iloc[train], mean)["rm
se"])
    assert qualified == artifact["qualified_for_proxy"] == ensemble["qualified
_for_proxy"]
    indices = np.asarray(ensemble["bootstrap_indices"])
    assert indices.shape == (60, len(train)) and not np.isin(indices, excluded
).any()
    assert np.isin(indices, train).all()
    assert ensemble["selection_model_indices"] == list(range(40))
    assert ensemble["audit_model_indices"] == list(range(40, 60))
    assert artifact["pipeline"].named_steps["model"].n_estimators == 300
    all_models = [(artifact["pipeline"], train)] + list(zip(ensemble["models"]
, indices))
    for i, (model, training_indices) in enumerate(all_models):
        imputer = model.named_steps["imputer"]
        BASE.close(imputer.statistics_, np.nanmedian(x.iloc[training_indices],
 axis=0), "Fixed model source-excluded medians")
        np.testing.assert_array_equal(imputer.indicator_.features_, np.flatnon
zero(x.iloc[training_indices].isna().any(axis=0)))
        tree = model.named_steps["model"]
        assert tree.min_samples_leaf == 3 and tree.max_features == .7
        assert tree.n_estimators == (300 if i == 0 else 120)
    with np.load(folder / "bootstrap_indices.npz") as saved:
        np.testing.assert_array_equal(saved["indices"], indices)
        np.testing.assert_array_equal(saved["bootstrap_seeds"], ensemble["boot
strap_seeds"])
    for i, seed in enumerate(ensemble["bootstrap_seeds"]):
```

```
        expected_seed = manifest["selection_bootstrap_seed"] + i if i < 40 els
e manifest["audit_bootstrap_seed"] + i - 40
        assert seed == expected_seed
        np.testing.assert_array_equal(indices[i], np.random.default_rng(seed).
choice(train, len(train), replace=True))
    heldout = pd.read_csv(folder / "pils_style_holdout_predictions.csv")
    BASE.close(heldout.prediction, np.asarray(artifact["pipeline"].predict(x.i
loc[excluded])).reshape(-1), "Fixed source holdout")
    holdout = pd.read_csv(folder / "pils_style_holdout_metrics.csv").set_index
("model")
    for name, column in [("fixed_single_extra_trees", "prediction"), ("non_pil
s_mean", "mean_baseline_prediction"),
                         ("old_multioutput_transfer_proxy", "old_multioutput_p
rediction")]:
        BASE.close(holdout.loc[name, columns], list(score(heldout.observed, he
ldout[column]).values()), "Fixed holdout metrics")
    context.update({"fixed_stale": artifact, "fixed_ensemble": ensemble,
                    "optimized_train": train, "optimized_sources": excluded})
    pooled = metrics[metrics.scope.eq("pooled_repeated_oof")].set_index("metho
d")
    cluster = BASE.read_json(folder / "paired_cluster_bootstrap.json")
    errors = oof.assign(error_squared=(oof.prediction - oof.observed) ** 2)
    per_beer = errors.pivot_table(index="beer", columns="method", values="erro
r_squared", aggfunc="mean").sort_index()
    fixed_errors = per_beer.fixed_single_extra_trees.to_numpy()
    old_errors = per_beer.old_multioutput_extra_trees.to_numpy()
    draws = np.random.default_rng(cluster["seed"]).integers(0, len(per_beer),
(cluster["repeats"], len(per_beer)))
    fixed_rmse = np.sqrt(fixed_errors[draws].mean(axis=1))
    old_rmse = np.sqrt(old_errors[draws].mean(axis=1))
    differences, reductions = fixed_rmse - old_rmse, 1 - fixed_rmse / old_rmse
    BASE.close(cluster["rmse_difference_percentile95"], np.quantile(difference
s, [.025, .975]), "Beer-cluster RMSE difference interval")
    BASE.close(cluster["relative_rmse_reduction_percentile95"], np.quantile(re
ductions, [.025, .975]), "Beer-cluster relative change interval")
    BASE.close(cluster["bootstrap_fraction_rmse_difference_below_zero"], np.me
an(differences < 0), "Beer-cluster difference fraction")
    BASE.close(cluster["point_rmse_difference"], np.sqrt(fixed_errors.mean())
- np.sqrt(old_errors.mean()), "Beer-cluster point difference")
    return {"extra_internal_seeds": manifest["outer_seeds"], "parameter_tuning
": False,
            "fixed_single_oof_rmse": float(pooled.loc["fixed_single_extra_tree
s", "rmse"]),
            "same_split_old_multioutput_rmse": float(pooled.loc["old_multioutp
ut_extra_trees", "rmse"]),
            "same_split_mean_rmse": float(pooled.loc["mean", "rmse"]),
            "transfer_qualified": qualified, "bootstrap_shape": list(indices.s
hape),
            "beer_cluster_bootstrap_repeats": cluster["repeats"],
            "rmse_difference_interval": cluster["rmse_difference_percentile95"
],
            "pils_holdout_rmse": float(holdout.loc["fixed_single_extra_trees",
 "rmse"]),
            "pils_holdout_mean_rmse": float(holdout.loc["non_pils_mean", "rmse
"])}


def check_transfer(context):
    folder = OUT / "transfer"
    meta, x = context["meta"], context["x"]
    train, sources = context["optimized_train"], context["optimized_sources"]
    summary = BASE.read_json(folder / "summary.json")
```

```
    scenarios = BASE.read_json(folder / "threshold_scenarios.json")
    thresholds = pd.read_excel(data_dir() / "8.xlsx", sheet_name="Sensory thre
sholds").set_index("field_name_R")
    assert len(scenarios) == 10
    expected_ids = {f"{statistic}_x{factor:.1f}" for statistic in ["median", "
mean"] for factor in [.8, .9, 1, 1.1, 1.2]}
    assert {scenario["scenario"] for scenario in scenarios} == expected_ids
    for scenario in scenarios:
        for field in BASE.DEFECT_FIELDS:
            raw = thresholds.at[field, "threshold_" + scenario["statistic"]]
            actual = scenario["thresholds"][field]
            if pd.isna(raw):
                assert actual is None and field == "X.E..2.nonenal"
            else:
                BASE.close(actual, raw * scenario["factor"], "Threshold stress
 scenario")
    assert scenarios == summary["threshold_scenarios"]
    geometry = joblib.load(SOLUTION / "outputs/q3/transfer/transfer_copula.job
lib")
    reference = geometry["copula"]
    np.testing.assert_array_equal(geometry["training_rows"], train)
    generator_artifact = joblib.load(folder / "transfer_generator.joblib")
    np.testing.assert_array_equal(generator_artifact["training_rows"], train)
    np.testing.assert_array_equal(generator_artifact["source_rows"], sources)
    generator = generator_artifact["generator"]
    BASE.close(generator.fitted_candidates_["legacy_copula"].median_, np.nanme
dian(x.iloc[train], axis=0), "Source-excluded new generator medians")
    old_draws = pd.read_csv(folder / "old_base_draws.csv")
    new_draws = pd.read_csv(folder / "optimized_base_draws.csv")
    assert old_draws.columns.tolist() == new_draws.columns.tolist() == x.colum
ns.tolist()
    BASE.close(old_draws, reference.sample("Tripel", len(old_draws), 20261023
+ 301), "Frozen old generator base draws")
    BASE.close(new_draws, generator.sample("Tripel", len(new_draws), 20261023
+ 301), "Source-excluded new generator base draws")
    assert bool(np.array_equal(old_draws.to_numpy(), new_draws.to_numpy())) ==
 summary["base_draws_equal"]
    report = pd.read_csv(folder / "transfer_summary.csv")
    diagnostics = pd.read_csv(folder / "candidate_diagnostics.csv")
    spectra = pd.read_csv(folder / "transferred_spectra.csv").set_index("trans
fer_id")
    paired = pd.read_csv(folder / "stale_paired_deltas.csv")
    sensitivity = pd.read_csv(folder / "threshold_sensitivity.csv")
    profiles = pd.read_csv(folder / "sensory_before_after.csv")
    policies = pd.read_csv(folder / "policy_summary.csv")
    ensemble = context["fixed_ensemble"]
    old_ensemble = joblib.load(SOLUTION / "outputs/q3/sensory/stale_bootstrap.
joblib")
    profile_model = joblib.load(SOLUTION / "outputs/q3/sensory/transfer_proxy.
joblib")
    target = x.loc[meta.tasting_category_fine.eq("Tripel")]
    tz = reference.transform(target)
    dimension = x.shape[1]
    neighbors = cdist(tz, tz) / np.sqrt(dimension)
    np.fill_diagonal(neighbors, np.inf)
    support_limit = np.quantile(neighbors.min(axis=1), .95)
    BASE.close(support_limit, summary["support_nn_q95"], "Unchanged support li
mit")
    assert summary["target_improvement_minimum"] == .1 and summary["latent_rms
_change_minimum"] == .05
    assert summary["selection_models"] == 40 and summary["audit_models"] == 20
    medians = x.iloc[train].median()
```

```
    minimum, maximum = x.iloc[train].min().to_numpy(), x.iloc[train].max().to_
numpy()
    target_median = target.median().to_numpy()
    p_selected = report[report.candidate_index.notna()]
    assert set(p_selected.transfer_id) == set(spectra.index) and spectra.index
.is_unique
    selected_predictions = np.vstack([model.predict(spectra[x.columns]) for mo
del in ensemble["models"]])
    old_predictions = np.vstack([model.predict(spectra[x.columns]) for model i
n old_ensemble["models"]])
    selected_profiles = profile_model["pipeline"].predict(spectra[x.columns])
    max_quantile_error, argmin_checks, scenario_checks = 0.0, 0, 0
    for source_index in sources:
        beer = int(meta.beer.iloc[source_index])
        raw_source = x.iloc[[source_index]]
        source = raw_source.fillna(medians)
        caps = {}
        for field in BASE.DEFECT_FIELDS:
            levels = [scenario["thresholds"][field] for scenario in scenarios
if scenario["thresholds"][field] is not None]
            value = float(raw_source[field].iloc[0])
            caps[field] = max(value, min(levels)) if levels else value
            if levels:
                BASE.close(caps[field], min(max(value, level) for level in lev
els), "Robust minimum-of-scenario cap")
        arrays, families, gammas, draws = [], [], [], []
        for family, base in [("old_copula", old_draws), ("optimized", new_draw
s)]:
            for gamma in [.25, .5, .75, 1.]:
                arrays.append((1-gamma) * source.to_numpy()[0] + gamma * base.
to_numpy())
                families.extend([family] * len(base)); gammas.extend([gamma] *
 len(base)); draws.extend(range(len(base)))
        for gamma in [.25, .5, .75, 1.]:
            arrays.append(((1-gamma) * source.to_numpy()[0] + gamma * target_m
edian)[None])
            families.append("shared_target_median"); gammas.append(gamma); dra
ws.append(-1)
        values = pd.DataFrame(np.vstack(arrays), columns=x.columns)
        for field, cap in caps.items():
            values[field] = values[field].clip(lower=0, upper=cap)
        diagnostic = diagnostics[diagnostics.source_beer.eq(beer)].sort_values
("candidate_index")
        assert len(diagnostic) == len(values)
        np.testing.assert_array_equal(diagnostic.candidate_index, np.arange(le
n(values)))
        assert diagnostic.family.tolist() == families
        BASE.close(diagnostic.gamma, gammas, "Reconstructed interpolation frac
tions")
        np.testing.assert_array_equal(diagnostic.draw, draws)
        z, sz = reference.transform(values), reference.transform(source)
        distance, before = reference.distance(values, "Tripel"), float(referen
ce.distance(source, "Tripel")[0])
        nn = cdist(z, tz).min(axis=1) / np.sqrt(dimension)
        change = np.linalg.norm(z - sz, axis=1) / np.sqrt(dimension)
        improvement = 1 - distance / max(before, 1e-8)
        support = (nn <= support_limit + TOL) & (values.to_numpy() >= minimum-
TOL).all(axis=1) & (values.to_numpy() <= maximum+TOL).all(axis=1)
        chemical = BASE.chemical_flags(values, caps)
        source_pred = np.array([float(np.asarray(model.predict(source)).reshap
e(-1)[0]) for model in ensemble["models"]])
        delta = np.column_stack([np.asarray(model.predict(values)).reshape(-1)
```

```
-source_pred[b] for b, model in enumerate(ensemble["models"][:40])])
        q95 = np.quantile(delta, .95, axis=1)
        nonzero = np.any(np.abs(delta) > 1e-8, axis=1)
        feasible = support & chemical & (change >= .05) & (improvement >= .1)
& (q95 <= TOL) & nonzero
        BASE.close(diagnostic[["target_distance", "target_improvement", "targe
t_nn_rms", "change_latent_rms", "selection_q95"]],
                   np.column_stack([distance, improvement, nn, change, q95]),
"Independently rebuilt candidate geometry and screening quantiles")
        np.testing.assert_array_equal(diagnostic.selection_feasible, feasible)
        np.testing.assert_array_equal(diagnostic.support_ok, support)
        np.testing.assert_array_equal(diagnostic.all_thresholds_chemical_ok, c
hemical)
        np.testing.assert_array_equal(diagnostic.nonzero_paired_signal, nonzer
o)
        center_scale = max(float(np.linalg.norm(sz[0] - tz.mean(axis=0)) / np.
sqrt(dimension)), 1e-8)
        masks = {"old_generator": np.isin(families, ["old_copula", "shared_tar
get_median"]),
                 "optimized_generator": np.isin(families, ["optimized", "share
d_target_median"]),
                 "combined_pool": np.ones(len(values), bool)}
        old_source_pred = np.array([float(np.asarray(model.predict(source)).re
shape(-1)[0]) for model in old_ensemble["models"]])
        for _, row in report[report.source_beer.eq(beer)].iterrows():
            mask = masks[row.pool]
            allowed = feasible & mask
            assert row.n_candidates == mask.sum() and row.n_selection_feasible
 == allowed.sum()
            variation = np.std(delta[mask].mean(axis=1))
            zero_fraction = np.mean(np.all(np.abs(delta[mask]) <= 1e-8, axis=1
))
            BASE.close([row.candidate_mean_delta_sd, row.candidate_zero_paired
_fraction], [variation, zero_fraction], "Proxy responsiveness diagnostics")
            if not allowed.any():
                assert pd.isna(row.candidate_index) and row.status == "no_cand
idate_found"
                continue
            objective = distance / max(before, 1e-8) + row["lambda"] * change
/ center_scale
            chosen = int(np.flatnonzero(allowed)[np.argmin(objective[allowed])
])
            assert chosen == int(row.candidate_index), "Candidate differs from
 fixed selection-only argmin"
            argmin_checks += 1
            final = spectra.loc[[row.transfer_id], x.columns]
            BASE.close(final, values.iloc[[chosen]], "Selected spectrum recons
tructed from base draws")
            saved_position = spectra.index.get_loc(row.transfer_id)
            all_delta = selected_predictions[:, saved_position]-source_pred
            old_delta = old_predictions[:, saved_position]-old_source_pred
            quantities = [np.quantile(all_delta[:40], .95), np.quantile(all_de
lta[40:], .95),
                          np.quantile(old_delta[:30], .95), np.quantile(old_de
lta[30:], .95)]
            actual = [row.selection_q95, row.audit_q95, row.old_selection_q95,
 row.old_audit_q95]
            BASE.close(actual, quantities, "Selected and frozen-architecture a
udit quantiles")
            max_quantile_error = max(max_quantile_error, float(np.max(np.abs(n
p.asarray(actual)-quantities))))
            informative = bool(variation > 1e-6 and nonzero[chosen])
```

```
            qualified = bool(context["fixed_stale"]["qualified_for_proxy"])
            passed = bool(qualified and informative and quantities[1] <= TOL)
            old_consensus = bool(quantities[2] <= TOL and quantities[3] <= TOL
)
            assert passed == row.all_model_checks_passed and old_consensus ==
row.old_proxy_consensus
            assert bool(passed and old_consensus) == row.cross_proxy_checks_pa
ssed
            expected_status = "proxy_not_qualified" if not qualified else "pro
xy_uninformative" if not informative else "model_checks_passed" if quantities[
1] <= TOL else "resampling_audit_failed"
            assert row.status == expected_status
            for label, differences in [("selection", all_delta[:40]), ("audit"
, all_delta[40:]),
                                       ("old_selection", old_delta[:30]), ("ol
d_audit", old_delta[30:])]:
                recorded = paired[paired.transfer_id.eq(row.transfer_id) & pai
red.ensemble.eq(label)].sort_values("model_index")
                np.testing.assert_array_equal(recorded.model_index, np.arange(
len(differences)))
                BASE.close(recorded.paired_delta, differences, "Per-model scre
ening/audit paired differences")
            check_rows = sensitivity[sensitivity.transfer_id.eq(row.transfer_i
d)]
            assert len(check_rows) == len(scenarios) * len(BASE.DEFECT_FIELDS)
            for check in check_rows.itertuples(index=False):
                scenario = next(item for item in scenarios if item["scenario"]
 == check.scenario)
                threshold = scenario["thresholds"][check.feature]
                original, transferred = float(raw_source[check.feature].iloc[0
]), float(final[check.feature].iloc[0])
                cap = max(original, threshold) if threshold is not None else o
riginal
                BASE.close([check.source, check.transferred, check.upper_bound
, check.robust_upper_bound],
                           [original, transferred, cap, caps[check.feature]],
"All-scenario concentration audit")
                assert bool(0 <= transferred <= cap + TOL) == check.passed
                scenario_checks += 1
            source_profile = profile_model["pipeline"].predict(source)[0]
            after_profile = selected_profiles[saved_position].copy()
            position = context["y"].columns.get_loc("stale_hops")
            source_profile[position] = float(np.asarray(context["fixed_stale"]
["pipeline"].predict(source)).reshape(-1)[0])
            after_profile[position] = float(np.asarray(context["fixed_stale"][
"pipeline"].predict(final)).reshape(-1)[0])
            for phase, profile in [("source", source_profile), ("transferred",
 after_profile)]:
                recorded = profiles[profiles.transfer_id.eq(row.transfer_id) &
 profiles.phase.eq(phase)]
                assert len(recorded) == 1
                BASE.close(recorded[context["y"].columns], profile[None], "Mix
ed-model sensory profile")
        print(f"Verified robust candidates: source {beer}", flush=True)
    expected_policies = []
    for (pool, weight), group in report.groupby(["pool", "lambda"]):
        expected_policies.append({"pool": pool, "lambda": weight, "sources": l
en(group),
                                  "selected": int(group.candidate_index.notna()
.sum()),
                                  "model_checks_passed": int(group.all_model_ch
ecks_passed.sum()),
```

```
                                    "cross_proxy_checks_passed": int(group.cross_
proxy_checks_passed.sum()),
                                    "audit_failed": int(group.status.eq("resampli
ng_audit_failed").sum()),
                                    "no_candidate": int(group.status.eq("no_candi
date_found").sum())})
    BASE.same_table(policies, pd.DataFrame(expected_policies), ["pool", "lambd
a"],
                    ["sources", "selected", "model_checks_passed", "cross_prox
y_checks_passed", "audit_failed", "no_candidate"], "Robust policy summary")
    default = report[report.is_default_policy]
    assert default.pool.eq(summary["default_pool"]).all() and default["lambda"
].eq(summary["default_lambda"]).all()
    counts = {"sources": len(default), "selected": int(default.candidate_index
.notna().sum()),
              "model_checks_passed_all_thresholds": int(default.all_model_chec
ks_passed.sum()),
              "cross_proxy_checks_passed_all_thresholds": int(default.cross_pr
oxy_checks_passed.sum()),
              "audit_failed": int(default.status.eq("resampling_audit_failed")
.sum()),
              "no_candidate": int(default.status.eq("no_candidate_found").sum(
())}
    assert counts == summary["default_policy"]
    archived = pd.read_csv(folder / "archived_threshold_recheck.csv")
    old_spectra = pd.read_csv(SOLUTION / "outputs/q3/transfer/transferred_spec
tra.csv").set_index("transfer_id")
    for row in archived.itertuples(index=False):
        source = x.loc[meta.beer.eq(row.source_beer)]
        selected = old_spectra.loc[[row.transfer_id], x.columns]
        scenario = next(item for item in scenarios if item["scenario"] == row.
scenario)
        caps = {field: max(float(source[field].iloc[0]), level) if level is no
t None else float(source[field].iloc[0])
                for field, level in scenario["thresholds"].items()}
        assert bool(BASE.chemical_flags(selected, caps)[0]) == row.chemical_pa
ssed
    original_passed = archived[archived.old_model_checks_passed].groupby("sour
ce_beer").chemical_passed.all()
    assert int(original_passed.sum()) == summary["archived_baseline"]["model_c
hecks_passed_all_thresholds_same_spectra"]
    return {"scenario_count": len(scenarios), "sources": len(sources), "recons
tructed_candidates": len(diagnostics),
            "fixed_selection_argmin_checks": argmin_checks, "concentration_sce
nario_checks": scenario_checks,
            "maximum_paired_quantile_error": max_quantile_error,
            "base_draws_equal": summary["base_draws_equal"], "default_policy":
 counts}


def check_report(context):
    generated = context["optimized_generated"]
    meta, x, y = context["meta"], context["x"], context["y"]
    profiles = pd.read_csv(OUT / "generated_sensory_profiles.csv")
    assert len(profiles) == len(generated) == 1200 and profiles.sample_id.is_u
nique
    assert set(profiles.sample_id) == set(generated.sample_id)
    old = joblib.load(SOLUTION / "outputs/q3/sensory/sensory_model.joblib")
    expected = old["pipeline"].predict(generated[x.columns])
    expected[:, y.columns.get_loc("stale_hops")] = np.asarray(
        context["fixed_stale"]["pipeline"].predict(generated[x.columns])).resh
ape(-1)
```

```
    aligned = profiles.set_index("sample_id").loc[generated.sample_id]
    assert aligned.target_style.tolist() == generated.target_style.tolist()
    BASE.close(aligned[y.columns], expected, "Optimized generated 44+1 sensory profiles")
    summary_rows = []
    for style in BASE.GENERATION_STYLES:
        positions = generated.target_style.eq(style).to_numpy()
        for j, target in enumerate(y):
            values = expected[positions, j]
            summary_rows.append({"style": style, "target": target,
                                 "predicted_mean": values.mean(), "predicted_p05": np.quantile(values, .05),
                                 "predicted_p95": np.quantile(values, .95),
                                 "real_observed_mean": y.loc[meta.tasting_category_fine.eq(style), target].mean()})
    sensory_summary = pd.read_csv(OUT / "generated_sensory_summary.csv")
    BASE.same_table(sensory_summary, pd.DataFrame(summary_rows), ["style", "target"],
                    ["predicted_mean", "predicted_p05", "predicted_p95", "real_observed_mean"],
                    "Optimized generated sensory summary")
    assert sensory_summary.scale.eq("attachment_4_standardized").all()
    assert sensory_summary.interval_meaning.eq("generated_spectrum_spread_not_confidence_interval").all()
    folder = OUT / "transfer"
    report = pd.read_csv(folder / "transfer_summary.csv")
    default = report[report.is_default_policy]
    current = pd.read_csv(folder / "threshold_sensitivity.csv")
    archived = pd.read_csv(folder / "archived_threshold_recheck.csv")
    expected_counts = []
    for scenario in BASE.read_json(folder / "threshold_scenarios.json"):
        name = scenario["scenario"]
        old_rows = archived[archived.scenario.eq(name)]
        passing = current[current.scenario.eq(name)].groupby("transfer_id").passed.all()
        chemical = default.transfer_id.map(passing).fillna(False)
        expected_counts.append({"scenario": name, "statistic": scenario["statistic"], "factor": scenario["factor"],
                                "old_model_checks_and_chemical": int((old_rows.old_model_checks_passed & old_rows.chemical_passed).sum()),
                                "new_chemical_only": int(chemical.sum()),
                                "new_model_checks_and_chemical": int((chemical & default.all_model_checks_passed).sum()),
                                "cross_proxy_checks_and_chemical": int((chemical & default.cross_proxy_checks_passed).sum())})
    BASE.same_table(pd.read_csv(folder / "threshold_pass_counts.csv"), pd.DataFrame(expected_counts), ["scenario"],
                    ["factor", "old_model_checks_and_chemical", "new_chemical_only", "new_model_checks_and_chemical", "cross_proxy_checks_and_chemical"],
                    "All-scenario pass-count report")
    results = BASE.read_json(OUT / "results_summary.json")
    cv = pd.read_csv(OUT / "generation/cv_summary.csv")
    gains = {}
    for style in BASE.GENERATION_STYLES:
        rows = cv[cv["style"].eq(style)].set_index("method")
        gains[style] = float(1 - rows.loc["nested_selected", "energy_pca5_mean"] / rows.loc["legacy_copula", "energy_pca5_mean"])
        BASE.close(results["generation_energy_reduction_vs_matched_legacy"][style], gains[style], "Generation report gains")
    fixed = BASE.read_json(OUT / "stale_fixed/summary.json")
    transfer = BASE.read_json(folder / "summary.json")
    assert results["default_transfer"] == transfer["default_policy"]
```

```
    assert results["base_draws_equal"] == transfer["base_draws_equal"]
    assert results["source_style_prediction_improved"] == fixed["pils_holdout_improves_old"]
    BASE.close(results["fixed_stale_rmse_reduction_vs_matched_old"], fixed["rmse_reduction_vs_old_multioutput"], "Fixed-proxy report change")
    BASE.close(results["paired_rmse_difference_interval"], fixed["paired_cluster_bootstrap"]["rmse_difference_percentile95"], "Reported paired uncertainty interval")
    text = (SOLUTION / "docs/q3_optimization_results.md").read_text(encoding="utf-8")
    assert "尚未证实稳定的预测提升" in text
    assert f"**{transfer['default_policy']['model_checks_passed_all_thresholds']}/11**" in text
    assert f"**{transfer['default_policy']['cross_proxy_checks_passed_all_thresholds']}/11**" in text
    for style in ["Kriek", "Lambic"]:
        assert f"{100*gains[style]:.1f}%" in text
    figures = ["generation_and_prediction", "threshold_stability", "sensory_fingerprint_comparison"]
    for name in figures:
        for suffix in ["png", "svg"]:
            path = OUT / "figures" / f"{name}.{suffix}"
            assert path.is_file() and path.stat().st_size > 100
    return {"generated_sensory_rows": len(profiles), "sensory_targets": len(y.columns),
            "profile_model": "44 original full-data outputs plus source-excluded fixed stale target",
            "scenario_count_rows": len(expected_counts), "summary_values_recomputed": True,
            "figures_with_png_and_svg": len(figures), "results_report_exists": True}


def main():
    start = perf_counter()
    result = {"status": "running", "checks": [],
              "scope": "Frozen baseline integrity, repeated internal validation and robust candidate model checks"}
    active = "preserved_baseline_before"
    try:
        result["checks"].append({"name": active, "details": check_baseline()})
        active = "raw_sources_and_hybrid_contract"
        provenance = BASE.check_hashes()
        context, contract = BASE.load_contract()
        result["checks"].append({"name": active, "details": {"sources": provenance, "contract": contract}})
        for active, operation in [("optimized_stale_nested_validation", check_stale),
                                  ("optimized_generation_nested_validation", check_generation),
                                  ("fixed_single_target_followup", check_fixed_stale),
                                  ("robust_threshold_transfer", check_transfer),
                                  ("report_profiles_and_threshold_counts", check_report)]:
            details = operation(context)
            result["checks"].append({"name": active, "details": details})
            print(f"Verified: {active}", flush=True)
        active = "preserved_baseline_after"
        result["checks"].append({"name": active, "details": check_baseline()})
        result["status"] = "passed"
```

```
        result["limitations"] = [
            "Repeated and nested validation reuse the same real samples; new seeds are not fresh independent data.",
            "Bootstrap audit shares real training data and does not provide calibrated post-search coverage.",
            "Numerical and chemical checks do not establish actual sensory improvement or brewing feasibility.",
        ]
    except Exception as error:
        result.update({"status": "failed", "failed_check": active,
                       "error": f"{type(error).__name__}: {error}"})
        raise
    finally:
        result["elapsed_seconds"] = perf_counter() - start
        (OUT / "verification.json").write_text(json.dumps(result, ensure_ascii=False, indent=2,
                                                          allow_nan=False) + "\n", encoding="utf-8", newline="\n")
        print(json.dumps(result, ensure_ascii=False, indent=2, allow_nan=False), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/16_q3_stale_domain.py

SHA-256: 65bb6832fc558142c609129009b595681fd6a074a94f327b579cac0e85c92122

```
"""Non-Pils leave-one-style-out selection and repeatedly viewed Pils diagnosis."""
from __future__ import annotations

import json
import platform
import warnings
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
import sklearn
from scipy.stats import ConstantInputWarning
from scipy.spatial.distance import cdist
from sklearn.model_selection import LeaveOneGroupOut
from threadpoolctl import threadpool_limits

from common import SOLUTION, data_dir
from q3_data import load_q3_data
from q3_stale_optimized import predict_1d, scores as regression_scores
from q3_stale_domain import (
    AUDIT_BOOTSTRAP_SEED, BIAS_PENALTY, FINAL_SEED, LOSO_SEED,
    SELECTION_BOOTSTRAP_SEED, VARIANCE_RATIO_MIN, domain_candidate_specs,
    make_domain_pipeline, training_fit_params,
)

OUT = SOLUTION / "outputs" / "q3_domain" / "stale"
TARGET = "stale_hops"


def scores(y, pred):
    # A few tiny styles have constant labels: correlation is undefined, not 0.
    with warnings.catch_warnings():
        warnings.simplefilter("ignore", ConstantInputWarning)
        result = regression_scores(y, pred)
    if result["spearman"] is not None and not np.isfinite(result["spearman"]):
        result["spearman"] = None
    return result


def write_json(path, value):
    path.write_text(json.dumps(value, ensure_ascii=False, indent=2, allow_nan=False), encoding="utf-8", newline="\n")


def predict_target(model, x, spec, target_position):
    if spec["family"] == "old_multioutput":
        return np.asarray(model.predict(x))[:, target_position]
    return predict_1d(model, x)


def write_local_neighborhood_diagnostics(final_model, models, indices, train_indices,
                                         source_indices, meta, x):
    """Feature-only bootstrap neighbourhood checks, never used for selection."""
    xs = x.iloc[source_indices]
    final_regressor = final_model.named_steps["model"]
```

```
    k = final_regressor.n_neighbors
    final_distances = cdist(final_model[:-1].transform(xs), final_regressor.x_
)
    final_neighbors = [set(train_indices[np.argpartition(row, k-1)[:k]]) for r
ow in final_distances]
    rows = []
    for b, (model, index) in enumerate(zip(models, indices)):
        regressor = model.named_steps["model"]
        distances = cdist(model[:-1].transform(xs), regressor.x_)
        prediction = predict_1d(model, xs)
        for j, (source_index, row) in enumerate(zip(source_indices, distances)
):
            near = np.argpartition(row, k-1)[:k]
            neighbors = set(index[near])
            weights = regressor.sample_weight_[near] / np.maximum(row[near], 1
e-12)
            # Repeated resample positions are not independent source beers.
            # Keep the original position-level Kish count and also aggregate
            # all weights belonging to the same original beer before Kish.
            _, beer_inverse = np.unique(index[near], return_inverse=True)
            weights_by_beer = np.bincount(beer_inverse, weights=weights)
            effective_positions = float(weights.sum()**2/np.sum(weights**2))
            effective_beers = float(weights_by_beer.sum()**2/np.sum(weights_by
_beer**2))
            if effective_beers > len(neighbors)+1e-10:
                raise AssertionError("Beer-level effective count exceeds uniqu
e neighbours")
            rows.append({"beer": int(meta.iloc[source_index].beer), "model_ind
ex": b,
                "role": "selection" if b < 40 else "audit", "prediction": pred
iction[j],
                "nearest_unique_beers": len(neighbors),
                "neighbor_jaccard_vs_final": len(neighbors & final_neighbors[j
])/len(neighbors | final_neighbors[j]),
                "effective_resampled_position_count": effective_positions,
                "effective_unique_beer_count": effective_beers,
                "imputer_indicator_count": len(model.named_steps["imputer"].in
dicator_.features_)})
    frame = pd.DataFrame(rows)
    frame.to_csv(OUT / "neighborhood_bootstrap_diagnostics.csv", index=False,
lineterminator="\n")
    frame.groupby("beer").agg(
        bootstrap_prediction_sd=("prediction", "std"),
        median_neighbor_jaccard=("neighbor_jaccard_vs_final", "median"),
        mean_unique_neighbors=("nearest_unique_beers", "mean"),
        median_effective_resampled_position_count=("effective_resampled_positi
on_count", "median"),
        median_effective_unique_beer_count=("effective_unique_beer_count", "me
dian"),
    ).to_csv(OUT / "neighborhood_bootstrap_summary.csv", lineterminator="\n")


def main():
    started = perf_counter()
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y45, manifest = load_q3_data()
    y, target_position = y45[TARGET], y45.columns.get_loc(TARGET)
    source_indices = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"
))
    train_indices = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"
))
    assert len(source_indices) == 11 and len(train_indices) == 239
```

```
    xtr, ytr = x.iloc[train_indices], y.iloc[train_indices]
    groups = meta.iloc[train_indices].tasting_category_fine.to_numpy()
    features = x.columns.tolist()
    calibrated = manifest.loc[manifest.representation.eq("calibrated"), "featu
re"].tolist()
    threshold_metadata = pd.read_excel(data_dir() / "8.xlsx", sheet_name="Sens
ory thresholds")
    aging_set = set(threshold_metadata.loc[threshold_metadata.aging.notna(), "
field_name_R"])
    aging = [feature for feature in features if feature in aging_set]
    specs = domain_candidate_specs()
    spec_map = {spec["name"]: spec for spec in specs}
    run_manifest = {
        "candidate_specs": specs, "target": TARGET, "features": features, "agi
ng_features": aging,
        "population": "239 non-Pils samples", "heldout_groups": sorted(np.uniq
ue(groups).tolist()),
        "validation": "complete leave-one-style-out; 21 folds; every preproces
sing operation fitted per training fold",
        "selection_rule": "minimum macro(style RMSE) + 0.25*macro(abs(style me
an prediction error)) among selectable nonconstant candidates",
        "bias_penalty": BIAS_PENALTY, "variance_ratio_min": VARIANCE_RATIO_MIN
,
        "qualification_rule": "LOSO prediction variance ratio >=0.05 and macro
 RMSE < better of global/style-balanced mean baselines",
        "fallback": "if every selectable candidate fails nonconstant gate, ret
ain minimum score but mark unqualified",
        "loso_seed": LOSO_SEED, "final_seed": FINAL_SEED,
        "selection_bootstrap_seed": SELECTION_BOOTSTRAP_SEED, "audit_bootstrap
_seed": AUDIT_BOOTSTRAP_SEED,
        "pils_labels_used_in_training_selection_or_intercept": False,
        "pils_status": "previously repeatedly viewed diagnostic set; not a new
 test set",
        "forbidden_prediction_features": ["style", "identity", "other observed
 sensory targets", "attachment 7 comments"],
    }
    # Freeze all candidates/rules before starting the new grouped evaluation.
    write_json(OUT / "run_manifest.json", run_manifest)
    pd.DataFrame({"feature": aging}).to_csv(OUT / "predeclared_aging_features.
csv", index=False, lineterminator="\n")
    predictions = {spec["name"]: np.full(len(train_indices), np.nan) for spec
in specs}
    fold_ids = np.zeros(len(train_indices), dtype=int)
    rows_by_style, fold_audit = [], []
    for fold, (train_local, test_local) in enumerate(LeaveOneGroupOut().split(
xtr, ytr, groups), 1):
        heldout_style = str(groups[test_local[0]])
        train_global, test_global = train_indices[train_local], train_indices[
test_local]
        assert not set(train_global) & set(source_indices)
        assert not set(groups[train_local]) & {heldout_style}
        fold_seed = LOSO_SEED + fold
        for spec in specs:
            name = spec["name"]
            if spec["family"] == "ensemble":
                values = np.mean([predictions[member["name"]][test_local] for
member in spec["members"]], axis=0)
            else:
                model = make_domain_pipeline(spec, features, calibrated, aging
, fold_seed)
                target = y45.iloc[train_global] if spec["family"] == "old_mult
ioutput" else y.iloc[train_global]
```

```
                model.fit(x.iloc[train_global], target,
                          **training_fit_params(spec, meta.iloc[train_global].
tasting_category_fine))
                values = predict_target(model, x.iloc[test_global], spec, targ
et_position)
            predictions[name][test_local] = values
            rows_by_style.append({"method": name, "heldout_style": heldout_sty
le,
                                  "fold": fold, "n": len(test_local),
                                  **scores(y.iloc[test_global], values),
                                  "bias": float(np.mean(values-y.iloc[test_glo
bal].to_numpy()))})
        fold_ids[test_local] = fold
        fold_audit.extend({"fold": fold, "heldout_style": heldout_style, "role
": role,
                           "global_index": int(index), "beer": int(meta.iloc[i
ndex].beer)}
                          for role, indices in [("train", train_global), ("tes
t", test_global)] for index in indices)
        pd.DataFrame(rows_by_style).to_csv(OUT / "loso_metrics_by_style.csv",
index=False, lineterminator="\n")
        print(f"Stale domain LOSO {fold}/21: {heldout_style} ({len(test_local)
} samples)", flush=True)
    loso_by_style = pd.DataFrame(rows_by_style)
    audit = pd.DataFrame(fold_audit)
    audit.to_csv(OUT / "loso_split_audit.csv", index=False, lineterminator="\n
")
    overall_rows, prediction_rows = [], []
    for spec in specs:
        name, pred = spec["name"], predictions[spec["name"]]
        assert np.isfinite(pred).all()
        per_style = loso_by_style[loso_by_style.method.eq(name)]
        metric = scores(ytr, pred)
        macro_rmse = float(per_style.rmse.mean())
        macro_abs_bias = float(per_style.bias.abs().mean())
        within_pred_ss = within_truth_ss = 0.0
        for style in np.unique(groups):
            mask = groups == style
            within_pred_ss += float(np.sum((pred[mask]-pred[mask].mean())**2))
            within_truth_ss += float(np.sum((ytr.to_numpy()[mask]-ytr.to_numpy
()[mask].mean())**2))
        overall_rows.append({"method": name, "selectable": spec["selectable"],
            "balanced": spec["balanced"], "family": spec["family"], "styles":
len(per_style),
            "macro_style_rmse": macro_rmse, "macro_style_mae": float(per_style
.mae.mean()),
            "macro_style_abs_bias": macro_abs_bias, "macro_style_bias": float(
per_style.bias.mean()),
            "selection_score": macro_rmse+BIAS_PENALTY*macro_abs_bias,
            "nonconstant_qualified": metric["prediction_variance_ratio"] >= VA
RIANCE_RATIO_MIN,
            "within_style_prediction_variance_ratio": within_pred_ss/within_tr
uth_ss,
            **metric})
        prediction_rows.append(pd.concat([meta.iloc[train_indices].reset_index
(drop=True),
            pd.DataFrame({"global_index": train_indices, "method": name, "obse
rved": ytr.to_numpy(),
                          "prediction": pred, "heldout_style": groups, "fold":
 fold_ids})], axis=1))
    overall = pd.DataFrame(overall_rows)
    mean_floor = float(overall.loc[overall.method.isin(["mean_global", "mean_s
```

```
tyle_balanced"]), "macro_style_rmse"].min())
    overall["improves_best_mean_macro_rmse"] = overall.macro_style_rmse < mean_floor
    overall["qualified_for_proxy"] = overall.selectable & overall.nonconstant_qualified & overall.improves_best_mean_macro_rmse
    eligible = overall[overall.selectable & overall.nonconstant_qualified]
    fallback_used = eligible.empty
    if fallback_used:
        eligible = overall[overall.selectable]
    selected_row = eligible.sort_values(["selection_score", "method"]).iloc[0]
    selected_method = str(selected_row.method)
    selected_config = spec_map[selected_method]
    qualified = bool(selected_row.qualified_for_proxy)
    loso_predictions = pd.concat(prediction_rows, ignore_index=True)
    loso_predictions.to_csv(OUT / "loso_predictions.csv", index=False, lineterminator="\n")
    overall.to_csv(OUT / "loso_metrics_overall.csv", index=False, lineterminator="\n")
    selection_result = {"selected_method": selected_method, "config": selected_config,
        "selected_loso_metrics": selected_row.to_dict(), "qualified_for_proxy": qualified,
        "fallback_used": fallback_used, "best_mean_macro_rmse": mean_floor,
        "selection_complete_before_pils_diagnostic": True,
        "qualification_scope": "training-only LOSO diagnostic; not an unbiased estimate after selection, not causal validation"}
    write_json(OUT / "selection_result.json", selection_result)
    print(f"Stale domain selected without Pils labels: {selected_method}, qualified={qualified}", flush=True)

    # Fit all fixed candidates only after the selection decision is frozen.
    # All Pils labels are used solely for the diagnostic tables below.
    all_fitted = {}
    for spec in specs:
        model = make_domain_pipeline(spec, features, calibrated, aging, FINAL_SEED)
        target = y45.iloc[train_indices] if spec["family"] == "old_multioutput" else ytr
        model.fit(xtr, target, **training_fit_params(spec, groups))
        all_fitted[spec["name"]] = model
    common_metadata = {"features": features, "target": TARGET,
        "target_scale": "attachment_4_standardized", "config": selected_config,
        "selected_config": selected_config, "selected_method": selected_method,
        "qualified_for_proxy": qualified, "qualification_scope": selection_result["qualification_scope"],
        "inner_oof_variance_ratio": float(selected_row.prediction_variance_ratio),
        "inner_oof_rmse": float(selected_row.rmse),
        "loso_macro_style_rmse": float(selected_row.macro_style_rmse),
        "loso_macro_style_abs_bias": float(selected_row.macro_style_abs_bias),
        "loso_selection_score": float(selected_row.selection_score),
        "train_global_indices": train_indices, "excluded_global_indices": source_indices,
        "excluded_style": "Pils/Lager", "selection_protocol": run_manifest["selection_rule"],
        "pils_diagnostic_used_for_selection": False}
    final_model = all_fitted[selected_method]
    joblib.dump({"pipeline": final_model, **common_metadata}, OUT / "transfer_stale_model.joblib", compress=3)

```

```
    diagnostic_rows, diagnostic_metrics = [], []
    for spec in specs:
        name = spec["name"]
        values = predict_target(all_fitted[name], x.iloc[source_indices], spec
, target_position)
        diagnostic_rows.append(pd.concat([meta.iloc[source_indices].reset_inde
x(drop=True),
            pd.DataFrame({"global_index": source_indices, "method": name,
                          "observed": y.iloc[source_indices].to_numpy(), "pred
iction": values,
                          "selected_without_pils_labels": name == selected_met
hod})], axis=1))
        diagnostic_metrics.append({"method": name, "selected_without_pils_labe
ls": name == selected_method,
                                   "n": len(source_indices), **scores(y.iloc[s
ource_indices], values)})
    pd.concat(diagnostic_rows, ignore_index=True).to_csv(OUT / "pils_diagnosti
c_predictions.csv", index=False, lineterminator="\n")
    pd.DataFrame(diagnostic_metrics).to_csv(OUT / "pils_diagnostic_metrics.csv
", index=False, lineterminator="\n")

    models, indices, bootstrap_seeds, estimator_seeds = [], [], [], []
    for b in range(60):
        seed = SELECTION_BOOTSTRAP_SEED+b if b < 40 else AUDIT_BOOTSTRAP_SEED+
b-40
        index = np.random.default_rng(seed).choice(train_indices, size=len(tra
in_indices), replace=True)
        estimator_seed = seed+10000
        model = make_domain_pipeline(selected_config, features, calibrated, ag
ing, estimator_seed)
        model.fit(x.iloc[index], y.iloc[index],
                  **training_fit_params(selected_config, meta.iloc[index].tast
ing_category_fine))
        models.append(model)
        indices.append(index)
        bootstrap_seeds.append(seed)
        estimator_seeds.append(estimator_seed)
        if (b+1) % 10 == 0:
            print(f"Stale domain bootstrap {b+1}/60", flush=True)
    ensemble = {"models": models, "bootstrap_indices": indices, **common_metad
ata,
        "selection_model_indices": list(range(40)), "audit_model_indices": lis
t(range(40, 60)),
        "bootstrap_seeds": bootstrap_seeds, "estimator_seeds": estimator_seeds
,
        "pairing": "same_model_candidate_minus_source", "paired_quantile": 0.9
5,
        "hyperparameter_uncertainty_included": False,
        "resampling": "iid rows from 239 non-Pils; style-balanced weights re-e
stimated per draw where used",
        "audit_protocol": "first 40 screening; final 20 once-only audit; never
 reselect after audit",
        "interpretation": "fixed-configuration model-proxy bootstrap; not a ca
librated confidence interval"}
    joblib.dump(ensemble, OUT / "bootstrap_ensemble.joblib", compress=3)
    np.savez_compressed(OUT / "bootstrap_indices.npz", indices=np.asarray(indi
ces),
                        bootstrap_seeds=np.asarray(bootstrap_seeds), estimator
_seeds=np.asarray(estimator_seeds))
    assert len(np.unique(groups)) == 21
    assert len(loso_predictions) == len(train_indices)*len(specs)
    assert np.asarray(indices).shape == (60, 239)
```

```
    assert all(not set(index) & set(source_indices) for index in indices)
    assert len(set(bootstrap_seeds)) == 60
    assert np.isfinite(predict_1d(final_model, x)).all()
    if selected_config["family"] == "local":
        write_local_neighborhood_diagnostics(final_model, models, indices, tra
in_indices,
                                             source_indices, meta, x)
    selected_pils = next(row for row in diagnostic_metrics if row["method"] ==
 selected_method)
    summary = {
        "target": TARGET, "samples": len(x), "training_samples": len(train_ind
ices),
        "excluded_pils_sources": len(source_indices), "features": len(features
), "aging_features": len(aging),
        "loso_styles": len(np.unique(groups)), "candidate_count": len(specs),
        "mean_baseline_method": "mean_global",
        "style_balanced_mean_baseline_method": "mean_style_balanced",
        "old_multioutput_baseline_method": "old_multioutput_tree",
        "old_single_tree_baseline_method": "fixed_single_tree",
        **selection_result, "selected_pils_diagnostic_metrics": selected_pils,
        "all_pils_diagnostic_metrics": diagnostic_metrics,
        "pils_status": "previously repeatedly viewed diagnostic set; not a new
 test set",
        "pils_used_for_training_selection_or_intercept": False,
        "bootstrap": {"models": 60, "selection": 40, "audit": 20,
                      "indices_shape": [60, 239], "fixed_selected_configuratio
n": True,
                      "style_balanced_weights_refitted": bool(selected_config[
"balanced"]),
                      "algorithm_selection_uncertainty_included": False},
        "limitations": [
            "Complete LOSO uses only the 239 non-Pils samples; style labels de
termine groups and training weights, never prediction covariates.",
            "LOSO macro metrics treat the 21 observed styles equally; styles a
re observational groupings, not independent randomized domains.",
            "The selected score is the minimum among fixed candidate compariso
ns and is optimistic after selection; no outer grouped evaluation of the selec
tor is claimed.",
            "Pils labels have been repeatedly inspected in prior work; current
 Pils metrics are diagnostics, not a fresh test or basis for selection/interce
pt correction.",
            "All candidate Pils results are retained and never change the prev
iously frozen selected method.",
            "The variance gate is not a guarantee of response to each candidat
e chemical change.",
            "Row bootstrap conditions on the observed style pool and fixed cho
sen configuration; it omits algorithm-selection uncertainty and new-domain unc
ertainty.",
            "Screening and audit model draws share the same data; audit quanti
les are neither independent experiments nor calibrated confidence bounds.",
            "Chemical-only prediction may miss oxidation, storage and process
causes; passing model constraints does not establish actual stale-hops taste."
,
            "Targets retain the supplied standardized scale; original 0-6 sens
ory scores cannot be recovered.",
        ],
        "verification": {"source_exclusion": True, "loso_styles": 21, "loso_pr
ediction_rows": len(loso_predictions),
                         "bootstrap_indices_shape": [60, 239], "bootstrap_seed
s_unique": True,
                         "prediction_finite": True},
        "versions": {"python": platform.python_version(), "numpy": np.__versio
```

```
n__,
                      "pandas": pd.__version__, "sklearn": sklearn.__version__}
,
        "elapsed_seconds": perf_counter()-started,
    }
    write_json(OUT / "summary.json", summary)
    print(overall[["method", "macro_style_rmse", "macro_style_abs_bias", "sele
ction_score",
                     "prediction_variance_ratio", "qualified_for_proxy"]].to_str
ing(index=False), flush=True)
    print("Pils selected diagnostic:", json.dumps(selected_pils, ensure_ascii=
False), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/17_q3_transfer_domain.py

SHA-256: 037118a4c4ef024736fd03c754110118fa8c67f0035d6c907e4dfcf6ef21b642

```
"""Joint committee screening with fixed candidate budgets and fresh audit draws."""
from __future__ import annotations

import json
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from threadpoolctl import threadpool_limits

from common import SOLUTION
from q3_data import load_q3_data, read_defect_thresholds
from q3_stale_optimized import predict_1d, raw_tree_pipeline

OUT = SOLUTION / "outputs/q3_domain/transfer"
OLD = SOLUTION / "outputs/q3"
PREVIOUS = SOLUTION / "outputs/q3_optimized"
DOMAIN = SOLUTION / "outputs/q3_domain/stale"
ADDITIONAL_DRAW_SEED = 20271223
FRESH_AUDIT_SEED = 20280123
GAMMAS = [.25, .5, .75, 1.0]
POOLS = ["matched_2004", "expanded_6004"]
POLICIES = ["single_geometry", "joint_geometry", "joint_margin"]
DEFAULT_POOL, DEFAULT_POLICY = "matched_2004", "joint_margin"
WEIGHT, TOL = .2, 1e-10


def write_json(path, value):
    path.write_text(json.dumps(value, ensure_ascii=False, indent=2, allow_nan=False), encoding="utf-8", newline="\n")


def paired(models, frame, source):
    return np.column_stack([predict_1d(model, frame) - predict_1d(model, source)[0]
                            for model in models])


def chemical_ok(frame, source, scenario):
    good = np.ones(len(frame), dtype=bool)
    for field, threshold in scenario["thresholds"].items():
        observed = float(source[field].iloc[0])
        cap = max(observed, threshold) if threshold is not None else observed
        values = frame[field].to_numpy(float)
        good &= np.isfinite(values) & (values >= 0) & (values <= cap + TOL)
    return good


def build_candidates(source, draws, target_median, caps):
    blocks, descriptions = [], []
    for gamma in GAMMAS:
        block = (1-gamma) * source.to_numpy()[0] + gamma * draws.to_numpy()
        blocks.append(block)
        descriptions.extend({"gamma": gamma, "draw": j, "matched_budget": j < 500}
                            for j in range(len(draws)))
```

```
    for gamma in GAMMAS:
        blocks.append(((1-gamma)*source.to_numpy()[0]+gamma*target_median)[None])
        descriptions.append({"gamma": gamma, "draw": -1, "matched_budget": True})
    values = pd.DataFrame(np.vstack(blocks), columns=source.columns)
    for field, cap in caps.items():
        values[field] = values[field].clip(lower=0, upper=cap)
    return values, pd.DataFrame(descriptions)


def policy_counts(part):
    return {"sources": len(part), "selected": int(part.candidate_index.notna().sum()),
            "new_model_checks_passed": int(part.all_model_checks_passed.sum()),
            "historical_cross_proxy_passed": int(part.cross_proxy_checks_passed.sum()),
            "fresh_cross_proxy_passed": int(part.fresh_cross_proxy_checks_passed.sum()),
            "all_committees_passed": int(part.all_committees_passed.sum()),
            "no_candidate": int(part.status.eq("no_candidate_found").sum())}


def main(output_directory=OUT, proxy_directory=DOMAIN, experiment="domain_loso",
         fresh_domain_audit_seed=None, fresh_original_audit_seed=FRESH_AUDIT_SEED):
    started = perf_counter()
    OUT, DOMAIN = output_directory, proxy_directory
    FRESH_AUDIT_SEED = fresh_original_audit_seed
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y, _ = load_q3_data()
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    sources = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    target_rows = np.flatnonzero(meta.tasting_category_fine.eq("Tripel"))
    features = x.columns.tolist()
    defects = read_defect_thresholds()
    scenarios = json.loads((PREVIOUS / "transfer/threshold_scenarios.json").read_text(encoding="utf-8"))
    # This protocol is persisted before committee predictions or audit fitting.
    manifest = {"experiment":experiment,"proxy_directory":DOMAIN.relative_to(SOLUTION).as_posix(),
        "default_pool": DEFAULT_POOL, "default_policy": DEFAULT_POLICY,
        "pools": {"matched_2004": 2004, "expanded_6004": 6004}, "policies": POLICIES,
        "selection": "40 current-proxy models; first 30 frozen original models; paired Q95 <= 0",
        "joint_margin_order": "minimize max(domain selection Q95, original selection Q95), then geometry objective",
        "geometry_objective": "target_distance/source_distance + .2*change_rms/source_center_rms",
        "domain_audit": "last 20 current-proxy models, selected spectra only",
        "fresh_domain_audit_seed":fresh_domain_audit_seed,
        "historical_diagnostic": "last 10 original models, adaptively reused across previous experiments",
        "fresh_audit": "20 fresh-seed draws of original 120-tree single-target protocol, selected spectra only",
        "fresh_audit_seed": FRESH_AUDIT_SEED, "additional_draw_seed": ADDITIONAL_DRAW_SEED,
        "gammas": GAMMAS, "lambda": WEIGHT, "minimum_target_improvement": .10,
```

```
        "minimum_change_rms": .05, "threshold_scenarios": scenarios,
        "audit_reselection": False, "default_selected_from_audit": False,
        "qualification_required": True,
        "limitations": ["All audits reuse the same 239 observed training beers.",
                        "Bootstrap quantiles do not have calibrated post-search or causal coverage.",
                        "A safety-margin objective can require larger chemical changes."]}
    write_json(OUT / "run_manifest.json", manifest)
    geometry = joblib.load(OLD / "transfer/transfer_copula.joblib")
    np.testing.assert_array_equal(geometry["training_rows"], train)
    reference = geometry["copula"]
    previous_draws = pd.read_csv(PREVIOUS / "transfer/optimized_base_draws.csv")
    draws = pd.concat([previous_draws, reference.sample("Tripel", 1000, seed=ADDITIONAL_DRAW_SEED)], ignore_index=True)
    draws.to_csv(OUT / "base_draws.csv", index=False, lineterminator="\n")
    target_z = reference.transform(x.iloc[target_rows])
    dimension = x.shape[1]
    pairwise = cdist(target_z, target_z)/np.sqrt(dimension)
    np.fill_diagonal(pairwise, np.inf)
    support_limit = float(np.quantile(pairwise.min(axis=1), .95))
    target_center = target_z.mean(axis=0)
    medians = x.iloc[train].median()
    minimum, maximum = x.iloc[train].min().to_numpy(), x.iloc[train].max().to_numpy()
    target_median = x.iloc[target_rows].median().to_numpy()
    domain_model = joblib.load(DOMAIN / "transfer_stale_model.joblib")
    domain_ensemble = joblib.load(DOMAIN / "bootstrap_ensemble.joblib")
    if fresh_domain_audit_seed is not None:
        # Follow-up experiments keep the frozen 40 screening models, but do
        # not reuse their already observed audit predictions as fresh evidence.
        assert domain_model["selected_config"]["family"]=="extra_trees"
        replacement, replacement_indices, replacement_seeds = [], [], []
        for b in range(20):
            seed=fresh_domain_audit_seed+b
            index=np.random.default_rng(seed).choice(train,size=len(train),replace=True)
            replacement.append(raw_tree_pipeline(seed+10000,n_estimators=120).fit(x.iloc[index],y.stale_hops.iloc[index]))
            replacement_indices.append(index)
            replacement_seeds.append(seed)
        domain_ensemble={**domain_ensemble,
            "models":domain_ensemble["models"][:40]+replacement,
            "bootstrap_indices":list(domain_ensemble["bootstrap_indices"][:40])+replacement_indices,
            "bootstrap_seeds":list(domain_ensemble["bootstrap_seeds"][:40])+replacement_seeds,
            "estimator_seeds":list(domain_ensemble["estimator_seeds"][:40])+[s+10000 for s in replacement_seeds],
            "audit_protocol":"frozen 40 screening models; 20 new-seed audit models for a declared exploratory follow-up"}
        joblib.dump(domain_ensemble,OUT/"screening_and_audit.joblib",compress=3)
    original = joblib.load(OLD / "sensory/stale_bootstrap.joblib")
    old_center = joblib.load(OLD / "sensory/transfer_proxy.joblib")
    for artifact in [domain_model, domain_ensemble, original]:
        assert artifact["features"] == features
        np.testing.assert_array_equal(artifact["train_global_indices"], train)
    for index in domain_ensemble["bootstrap_indices"]:
```

```
        assert not np.isin(index, sources).any()
    new_select, new_audit = domain_ensemble["models"][:40], domain_ensemble["m
odels"][40:]
    old_select, old_historical = original["models"][:30], original["models"][3
0:]
    assert len(new_select) == 40 and len(new_audit) == 20
    qualified = bool(domain_model["qualified_for_proxy"])
    fresh_models, fresh_indices = [], []
    for b in range(20):
        seed = FRESH_AUDIT_SEED+b
        index = np.random.default_rng(seed).choice(train, size=len(train), rep
lace=True)
        fresh_models.append(raw_tree_pipeline(seed+10000, n_estimators=120).fi
t(x.iloc[index], y.stale_hops.iloc[index]))
        fresh_indices.append(index)
    joblib.dump({"models": fresh_models, "bootstrap_indices": fresh_indices,
                 "bootstrap_seeds": list(range(FRESH_AUDIT_SEED, FRESH_AUDIT_S
EED+20)),
                 "features": features, "train_global_indices": train,
                 "excluded_global_indices": sources, "target": "stale_hops",
                 "protocol": "original single-target ExtraTrees 120/minleaf3/m
axfeatures.7"},
                OUT / "fresh_original_protocol_audit.joblib", compress=3)
    summaries, diagnostics, spectra, deltas, thresholds, previous_checks = [],
 [], [], [], [], []
    previous_summary = pd.read_csv(PREVIOUS / "transfer/transfer_summary.csv")
    previous_summary = previous_summary[previous_summary.is_default_policy].se
t_index("source_beer")
    previous_spectra = pd.read_csv(PREVIOUS / "transfer/transferred_spectra.cs
v").set_index("transfer_id")
    stale_position = y.columns.get_loc("stale_hops")
    for count, index in enumerate(sources, 1):
        beer = int(meta.beer.iloc[index])
        raw_source = x.iloc[[index]]
        assert all(np.isfinite(raw_source[rule["feature"]].iloc[0]) and raw_so
urce[rule["feature"]].iloc[0]>=0
                   for rule in defects.values())
        source = raw_source.fillna(medians)
        caps = {}
        for rule in defects.values():
            field = rule["feature"]
            finite = [scenario["thresholds"][field] for scenario in scenarios
if scenario["thresholds"][field] is not None]
            caps[field] = max(float(raw_source[field].iloc[0]), min(finite)) i
f finite else float(raw_source[field].iloc[0])
        values, descriptions = build_candidates(source, draws, target_median,
caps)
        latent, source_z = reference.transform(values), reference.transform(so
urce)
        distance = reference.distance(values, "Tripel")
        before = float(reference.distance(source, "Tripel")[0])
        nn = cdist(latent, target_z).min(axis=1)/np.sqrt(dimension)
        change = np.linalg.norm(latent-source_z, axis=1)/np.sqrt(dimension)
        center_scale = max(float(np.linalg.norm(source_z[0]-target_center)/np.
sqrt(dimension)), 1e-8)
        improvement = 1-distance/max(before, 1e-8)
        support = (nn <= support_limit+TOL) & ((values.to_numpy()>=minimum-TOL
)&(values.to_numpy()<=maximum+TOL)).all(axis=1)
        chemical = np.column_stack([chemical_ok(values, raw_source, s) for s i
n scenarios]).all(axis=1)
        unique, inverse = np.unique(values.to_numpy(), axis=0, return_inverse=
True)
```

```
        unique_frame = pd.DataFrame(unique, columns=features)
        new_delta = paired(new_select, unique_frame, source)[inverse]
        old_delta = paired(old_select, unique_frame, source)[inverse]
        new_q95, old_q95 = np.quantile(new_delta, .95, axis=1), np.quantile(ol
d_delta, .95, axis=1)
        worst = np.maximum(new_q95, old_q95)
        new_signal = np.any(np.abs(new_delta)>1e-8, axis=1)
        old_signal = np.any(np.abs(old_delta)>1e-8, axis=1)
        base_ok = support & chemical & (improvement>=.1) & (change>=.05)
        single_ok = base_ok & (new_q95<=TOL) & new_signal
        joint_ok = single_ok & (old_q95<=TOL) & old_signal
        objective = distance/max(before, 1e-8)+WEIGHT*change/center_scale
        diagnostics.append(pd.concat([pd.DataFrame({"source_beer":beer, "candi
date_index":np.arange(len(values)),
            "target_distance":distance,"target_improvement":improvement,"targe
t_nn_rms":nn,
            "change_latent_rms":change,"support_ok":support,"all_thresholds_ch
emical_ok":chemical,
            "selection_new_q95":new_q95,"selection_old_q95":old_q95,"worst_sel
ection_q95":worst,
            "new_signal":new_signal,"old_signal":old_signal,"single_feasible":
single_ok,
            "joint_feasible":joint_ok,"geometry_objective":objective}), descri
ptions],axis=1))
        before_stale = float(predict_1d(domain_model["pipeline"], source)[0])
        before_old = float(old_center["pipeline"].predict(source)[0,stale_posi
tion])
        audit_cache = {}
        for pool in POOLS:
            pool_mask = descriptions.matched_budget.to_numpy() if pool=="match
ed_2004" else np.ones(len(values),bool)
            new_variation = float(np.std(new_delta[pool_mask].mean(axis=1)))
            old_variation = float(np.std(old_delta[pool_mask].mean(axis=1)))
            for policy in POLICIES:
                eligible = (single_ok if policy=="single_geometry" else joint_
ok) & pool_mask
                ids = np.flatnonzero(eligible)
                transfer_id = f"beer_{beer}_{pool}_{policy}"
                common = {"transfer_id":transfer_id,"source_beer":beer,"pool":
pool,"policy":policy,
                    "is_default_policy":pool==DEFAULT_POOL and policy==DEFAULT
_POLICY,"n_candidates":int(pool_mask.sum()),
                    "n_selection_feasible":len(ids),"target_distance_before":b
efore,"support_nn_limit":support_limit,
                    "proxy_qualified":qualified,"new_candidate_delta_sd":new_v
ariation,"old_candidate_delta_sd":old_variation,
                    "all_model_checks_passed":False,"cross_proxy_checks_passed
":False,
                    "fresh_cross_proxy_checks_passed":False,"all_committees_pa
ssed":False}
                if not len(ids):
                    summaries.append({**common,"candidate_index":np.nan,"statu
s":"no_candidate_found"})
                    continue
                chosen = int(ids[np.lexsort((objective[ids],worst[ids]))[0]])
if policy=="joint_margin" else int(ids[np.argmin(objective[ids])])
                selected = values.iloc[[chosen]]
                key = selected.to_numpy().tobytes()
                if key not in audit_cache:
                    audit_cache[key] = {"new_audit":paired(new_audit,selected,
source)[0],
                        "old_historical":paired(old_historical,selected,source
```

```
)[0],
                        "fresh_original_audit":paired(fresh_models,selected,source)[0],
                        "stale_after":float(predict_1d(domain_model["pipeline"],selected)[0]),
                        "old_center_after":float(old_center["pipeline"].predict(selected)[0,stale_position])}
                cached = audit_cache[key]
                audit_q95 = {group:float(np.quantile(cached[group],.95)) for group in ["new_audit","old_historical","fresh_original_audit"]}
                informative = new_variation>1e-6 and bool(new_signal[chosen])
                old_informative = old_variation>1e-6 and bool(old_signal[chosen])
                new_pass = bool(qualified and informative and audit_q95["new_audit"]<=TOL)
                cross = bool(new_pass and old_informative and old_q95[chosen]<=TOL and audit_q95["old_historical"]<=TOL)
                fresh_cross = bool(new_pass and old_informative and old_q95[chosen]<=TOL
                                   and audit_q95["fresh_original_audit"]<=TOL)
                all_committees = bool(cross and fresh_cross)
                status = ("proxy_not_qualified" if not qualified else "proxy_uninformative" if not informative
                          else "new_audit_failed" if not new_pass else "fresh_original_audit_failed" if not fresh_cross
                          else "all_checks_passed" if all_committees else "fresh_checks_passed_historical_disagrees")
                summaries.append({**common,"candidate_index":chosen,"status":status,"objective":float(objective[chosen]),
                    "target_distance_after":float(distance[chosen]),"target_improvement":float(improvement[chosen]),
                    "target_nn_after":float(nn[chosen]),"change_latent_rms":float(change[chosen]),
                    "selection_new_q95":float(new_q95[chosen]),"selection_old_q95":float(old_q95[chosen]),
                    "worst_selection_q95":float(worst[chosen]),"new_audit_q95":audit_q95["new_audit"],
                    "old_historical_audit_q95":audit_q95["old_historical"],"fresh_original_audit_q95":audit_q95["fresh_original_audit"],
                    "all_thresholds_chemical_ok":True,"all_model_checks_passed":new_pass,
                    "cross_proxy_checks_passed":cross,"fresh_cross_proxy_checks_passed":fresh_cross,
                    "all_committees_passed":all_committees,
                    "stale_before":before_stale,"stale_after":cached["stale_after"],
                    "old_center_before":before_old,"old_center_after":cached["old_center_after"]})
                spectra.append({"transfer_id":transfer_id,"source_beer":beer,"pool":pool,"policy":policy,**selected.iloc[0].to_dict()})
                groups = {"new_selection":new_delta[chosen],"old_selection":old_delta[chosen],
                          **{group:cached[group] for group in audit_q95}}
                for group, delta in groups.items():
                    deltas.extend({"transfer_id":transfer_id,"ensemble":group,"model_index":k,"paired_delta":float(value)}
                                  for k,value in enumerate(delta))
                for scenario in scenarios:
                    for label,rule in defects.items():
                        field=rule["feature"]
                        threshold=scenario["thresholds"][field]
                        observed=float(raw_source[field].iloc[0])
```

```
                        cap=max(observed,threshold) if threshold is not None e
lse observed
                        value=float(selected[field].iloc[0])
                        thresholds.append({"transfer_id":transfer_id,"source_b
eer":beer,"pool":pool,"policy":policy,
                            "scenario":scenario["scenario"],"defect":label,"fe
ature":field,"unit":rule["unit"],
                            "threshold":threshold,"source":observed,"transferr
ed":value,"upper_bound":cap,"passed":value<=cap+TOL})
        # Fixed previous selections are evaluated only after this round's choi
ces.
        previous_row=previous_summary.loc[beer]
        if pd.notna(previous_row.candidate_index):
            frame=previous_spectra.loc[[previous_row.transfer_id],features]
            previous_z=reference.transform(frame)
            previous_nn=float(cdist(previous_z,target_z).min()/np.sqrt(dimensi
on))
            previous_change=float(np.linalg.norm(previous_z-source_z)/np.sqrt(
dimension))
            previous_improvement=1-float(reference.distance(frame,"Tripel")[0]
)/max(before,1e-8)
            geometry_ok=bool(previous_nn<=support_limit+TOL and previous_chang
e>=.05 and previous_improvement>=.1
                             and ((frame.to_numpy()>=minimum-TOL)&(frame.to_nu
mpy()<=maximum+TOL)).all())
            new_previous_delta=paired(new_select,frame,source)
            old_previous_delta=paired(old_select,frame,source)
            nq=float(np.quantile(new_previous_delta,.95))
            oq=float(np.quantile(old_previous_delta,.95))
            na=float(np.quantile(paired(new_audit,frame,source),.95))
            oh=float(np.quantile(paired(old_historical,frame,source),.95))
            fa=float(np.quantile(paired(fresh_models,frame,source),.95))
            chem=all(chemical_ok(frame,raw_source,s)[0] for s in scenarios)
            matched=descriptions.matched_budget.to_numpy()
            new_ok=bool(qualified and chem and geometry_ok and nq<=TOL and na<
=TOL
                        and np.any(np.abs(new_previous_delta)>1e-8) and np.std
(new_delta[matched].mean(axis=1))>1e-6)
            old_screen_ok=bool(oq<=TOL and np.any(np.abs(old_previous_delta)>1
e-8)
                               and np.std(old_delta[matched].mean(axis=1))>1e-
6)
            old_ok=bool(old_screen_ok and oh<=TOL)
            previous_checks.append({"source_beer":beer,"previous_transfer_id":
previous_row.transfer_id,
                "all_thresholds_chemical_ok":chem,"geometry_ok":geometry_ok,"s
election_new_q95":nq,"selection_old_q95":oq,
                "new_audit_q95":na,"old_historical_audit_q95":oh,"fresh_origin
al_audit_q95":fa,
                "all_model_checks_passed":new_ok,"cross_proxy_checks_passed":n
ew_ok and old_ok,
                "fresh_cross_proxy_checks_passed":new_ok and old_screen_ok and
 fa<=TOL,
                "all_committees_passed":new_ok and old_ok and fa<=TOL,
                "previous_target_improvement":float(previous_row.target_improv
ement)})
        print(f"Domain transfer {count}/11 beer={beer}: single={single_ok.sum(
)}, joint={joint_ok.sum()}",flush=True)
    result=pd.DataFrame(summaries)
    result.to_csv(OUT/"transfer_summary.csv",index=False, lineterminator="\n")
    pd.concat(diagnostics,ignore_index=True).to_csv(OUT/"candidate_diagnostics
.csv",index=False, lineterminator="\n")
```

```
    pd.DataFrame(spectra).to_csv(OUT/"transferred_spectra.csv",index=False, lineterminator="\n")
    pd.DataFrame(deltas).to_csv(OUT/"stale_paired_deltas.csv",index=False, lineterminator="\n")
    pd.DataFrame(thresholds).to_csv(OUT/"threshold_sensitivity.csv",index=False, lineterminator="\n")
    previous_frame=pd.DataFrame(previous_checks)
    previous_frame.to_csv(OUT/"previous_same_spectra_recheck.csv",index=False, lineterminator="\n")
    policies=[{"pool":pool,"policy":policy,**policy_counts(part)} for (pool,policy),part in result.groupby(["pool","policy"])]
    pd.DataFrame(policies).to_csv(OUT/"policy_summary.csv",index=False, lineterminator="\n")
    default=result[result.is_default_policy]
    summary={"experiment":experiment,"protocol":manifest,"training_n":len(train),"sources":len(sources),"features":len(features),
        "support_nn_limit":support_limit,"proxy_qualified":qualified,"selected_domain_config":domain_model.get("selected_config",domain_model.get("config")),
        "default_policy":policy_counts(default),"policies":policies,
        "previous_original_rules":json.loads((PREVIOUS/"transfer/summary.json").read_text(encoding="utf-8"))["default_policy"],
        "previous_same_spectra_current_rules":{"sources":len(previous_frame),
            "new_model_checks_passed":int(previous_frame.all_model_checks_passed.sum()),
            "historical_cross_proxy_passed":int(previous_frame.cross_proxy_checks_passed.sum()),
            "fresh_cross_proxy_passed":int(previous_frame.fresh_cross_proxy_checks_passed.sum()),
            "all_committees_passed":int(previous_frame.all_committees_passed.sum())},
        "original_committee_protocol":"single-target 120-tree ExtraTrees; central original predictor alone was 45-output",
        "elapsed_seconds":perf_counter()-started}
    write_json(OUT/"summary.json",summary)
    print(json.dumps(summary["default_policy"],ensure_ascii=False,indent=2),flush=True)


if __name__=="__main__":
    with threadpool_limits(limits=1):
        main()
```

src/18_q3_domain_report.py

SHA-256: 60ba9b79a52af7cdd74e0dfe12175209d329267cc011bc8792afa969d8927712

```
"""Build the domain-transfer report from saved prediction and audit evidence."
""
from __future__ import annotations

import hashlib
import json
from pathlib import Path
import textwrap

import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt
from matplotlib.lines import Line2D
import numpy as np
import pandas as pd

from common import SOLUTION


OUT = SOLUTION / "outputs/q3_domain"
STALE = OUT / "stale"
TRANSFER = OUT / "transfer"
PREVIOUS = SOLUTION / "outputs/q3_optimized"
TABLES = OUT / "report_tables"
FIGURES = OUT / "figures"
SOURCES = []
COLORS = {"current": "#277DA8", "previous": "#8C959E",
          "historical": "#BD8733", "fresh": "#667C42", "text": "#30383F"}
CHECKS = {"new": "all_model_checks_passed", "historical": "cross_proxy_checks_
passed",
          "fresh": "fresh_cross_proxy_checks_passed", "all": "all_committees_p
assed"}


def record_source(path, rows=None):
    SOURCES.append({"path": path.relative_to(SOLUTION).as_posix(), "rows": row
s,
                    "sha256": hashlib.sha256(path.read_bytes()).hexdigest()})


def read_csv(path):
    frame = pd.read_csv(path)
    record_source(path, len(frame))
    return frame


def read_json(path):
    value = json.loads(path.read_text(encoding="utf-8"))
    record_source(path)
    return value


def boolean(series):
    if pd.api.types.is_bool_dtype(series.dtype):
        return series.fillna(False)
    converted = series.map({True: True, False: False, 1: True, 0: False,
                            "True": True, "False": False, "true": True, "false
": False})
    if (converted.isna() & series.notna()).any():
```

```
        raise ValueError(f"Unexpected boolean values: {series.unique()}")
    return converted.fillna(False).astype(bool)


def normalize_checks(frame):
    result = frame.copy()
    for column in [*CHECKS.values(), "is_default_policy", "all_thresholds_chemical_ok"]:
        if column in result:
            result[column] = boolean(result[column])
    if "all_committees_passed" not in result and all(c in result for c in
            ["cross_proxy_checks_passed", "fresh_cross_proxy_checks_passed"]):
        result["all_committees_passed"] = result.cross_proxy_checks_passed & result.fresh_cross_proxy_checks_passed
    return result


def method_name(method):
    aliases = {"mean": "Training mean", "non_pils_mean": "Training mean", "mean_global": "Training mean",
               "mean_style_balanced": "Style-balanced mean", "old_multioutput_tree": "Old 45-output tree",
               "fixed_single_tree": "Dedicated 300-tree",
               "mean_baseline": "Training mean", "old_multioutput_extra_trees": "Old 45-output tree",
               "old_multioutput": "Old 45-output tree", "fixed_single_extra_trees": "Dedicated 300-tree",
               "old_single_tree": "Dedicated 300-tree"}
    return aliases.get(str(method), str(method).replace("_", " "))


def prediction_tables(overall, by_style, pils_metrics, pils_predictions, stale_summary):
    selected = stale_summary["selected_method"]
    if selected not in set(overall.method) or selected not in set(pils_metrics.method):
        raise ValueError("Selected method is absent from prediction evidence")
    merged = overall.merge(pils_metrics[["method", "rmse", "mae", "r2"]].rename(
        columns={"rmse": "pils_rmse", "mae": "pils_mae", "r2": "pils_r2"}), on="method", validate="one_to_one")
    merged["is_selected"] = merged.method.eq(selected)
    merged.to_csv(TABLES / "prediction_method_comparison.csv", index=False, lineterminator="\n")
    selected_predictions = pils_predictions.loc[pils_predictions.method.eq(selected)].copy()
    if not selected_predictions.beer.is_unique:
        raise ValueError("Expected one saved Pils diagnostic prediction per selected-method beer")
    paired = selected_predictions[["beer", "observed", "prediction"]].rename(
        columns={"prediction": "domain_prediction"})
    baseline_ids = {"matched_single_tree": stale_summary["old_single_tree_baseline_method"],
                    "old_multioutput": stale_summary["old_multioutput_baseline_method"],
                    "training_mean": stale_summary["mean_baseline_method"]}
    for label, method in baseline_ids.items():
        part = pils_predictions.loc[pils_predictions.method.eq(method), ["beer", "observed", "prediction"]]
        paired = paired.merge(part.rename(columns={"observed": "check_observed",
                                "prediction": label + "_prediction"}), on="beer"
```

```
, validate="one_to_one")
        if len(paired) != len(selected_predictions) or not np.allclose(paired.observed, paired.check_observed):
            raise ValueError("Matched diagnostic predictions cover different populations or targets")
        paired = paired.drop(columns="check_observed")
    for label, field in [("matched_single_tree", "matched_single_tree_prediction"),
                         ("old_multioutput", "old_multioutput_prediction"),
                         ("training_mean", "training_mean_prediction"),
                         ("domain_selected", "domain_prediction")]:
        paired[f"{label}_residual"] = paired[field] - paired.observed
        squared = paired[f"{label}_residual"] ** 2
        paired[f"{label}_sse_share"] = squared / squared.sum()
    paired.sort_values("beer").to_csv(TABLES / "pils_source_error_influence.csv", index=False, lineterminator="\n")
    style_table = by_style.loc[by_style.method.eq(selected)].copy()
    style_table.to_csv(TABLES / "selected_loso_by_style.csv", index=False, lineterminator="\n")
    return merged, paired, selected


def transfer_tables(transfers, thresholds, previous, scenarios, experiment):
    rows = []
    for (pool, policy), group in transfers.groupby(["pool", "policy"], sort=False):
        if not group.source_beer.is_unique:
            raise ValueError("Duplicate source within transfer policy")
        selected = group.candidate_index.notna()
        rows.append({"pool": pool, "policy": policy, "sources": len(group),
            "selected": int(selected.sum()), **{f"{key}_passed": int(group[field].sum())
                                                for key, field in CHECKS.items()},
            "median_target_improvement_selected": float(group.loc[selected, "target_improvement"].median()),
            "median_change_rms_selected": float(group.loc[selected, "change_latent_rms"].median()),
            "median_target_improvement_fresh_pass": float(group.loc[group[CHECKS["fresh"]], "target_improvement"].median())})
    policies = pd.DataFrame(rows)
    policies.to_csv(TABLES / f"{experiment}_policy_comparison.csv", index=False, lineterminator="\n")
    default = transfers.loc[transfers.is_default_policy].sort_values("source_beer")
    if not default.source_beer.is_unique:
        raise ValueError("Default policy must contain one row per source")
    if set(default.source_beer) != set(previous.source_beer):
        raise ValueError("Current and rechecked historical spectra cover different sources")
    current_chemical = thresholds.groupby(["transfer_id", "scenario"]).passed.all()
    scenario_rows = []
    for scenario in scenarios:
        name = scenario["scenario"]
        mask = np.array([bool(current_chemical.get((t, name), False)) for t in default.transfer_id])
        scenario_rows.append({"scenario": name, "statistic": scenario.get("statistic"),
            "factor": scenario.get("factor"), "sources": len(default),
            "chemical_only": int(mask.sum()),
            **{f"{key}_passed": int(np.sum(mask & default[field].to_numpy(bool
```

```
    )))
144                 for key, field in CHECKS.items()}})
145     scenario_table = pd.DataFrame(scenario_rows)
146     scenario_table.to_csv(TABLES / f"{experiment}_default_threshold_pass_count
    s.csv", index=False, lineterminator="\n")
147     source = default.merge(previous.rename(columns={field: "previous_" + field
     for field in CHECKS.values()}),
148                            on="source_beer", suffixes=("", "_previous"), valid
    ate="one_to_one")
149     source.to_csv(TABLES / f"{experiment}_default_source_comparison.csv", inde
    x=False, lineterminator="\n")
150     return policies, default, scenario_table, source
151
152
153 def configure_figures():
154     plt.rcParams.update({"font.family": "DejaVu Sans", "font.size": 10,
155         "axes.spines.top": False, "axes.spines.right": False,
156         "axes.labelcolor": COLORS["text"], "text.color": COLORS["text"],
157         "figure.facecolor": "white", "savefig.facecolor": "white",
158         "svg.fonttype": "none"})
159
160
161 def save_figure(fig, name):
162     fig.savefig(FIGURES / f"{name}.png", dpi=300)
163     fig.savefig(FIGURES / f"{name}.svg")
164     plt.close(fig)
165
166
167 def prediction_figure(comparison, selected, n_styles, n_pils):
168     positions = np.arange(len(comparison))
169     labels = [textwrap.fill(method_name(m), 30) + (" *" if m == selected else
    "") for m in comparison.method]
170     colors = [COLORS["current"] if m == selected else COLORS["previous"] for m
     in comparison.method]
171     fig, axes = plt.subplots(1, 2, figsize=(12.8, max(7.0, len(comparison) * .
    45)), sharey=True)
172     for axis, field, title in [(axes[0], "macro_style_rmse", f"Selection evide
    nce: LOSO macro RMSE ({n_styles} styles)"),
173                                (axes[1], "pils_rmse", f"Repeatedly viewed Pil
    s diagnostic RMSE (n={n_pils})")]:
174         values = comparison[field].to_numpy(float)
175         axis.barh(positions, values, height=.6, color=colors)
176         axis.set_xlim(0, float(values.max()) * 1.19)
177         for y, value in zip(positions, values):
178             axis.text(value + values.max() * .015, y, f"{value:.3f}", va="cent
    er", fontsize=9)
179         axis.set_title(title, loc="left", fontsize=11, pad=15)
180         axis.set_xlabel("Stale hops RMSE (attachment-standardized units)")
181         axis.grid(axis="x", color="#E5E8EC", linewidth=.7)
182         axis.set_axisbelow(True)
183     axes[0].set_yticks(positions, labels, fontsize=9)
184     axes[0].invert_yaxis()
185     fig.text(.24, .025, "* Selected by non-Pils LOSO score, not by the Pils co
    lumn.\n"
186              "Candidate LOSO scores were used for selection; they are not unbi
    ased post-selection test estimates.",
187              fontsize=9, color="#525C65")
188     fig.subplots_adjust(left=.24, right=.98, top=.9, bottom=.14, wspace=.23)
189     save_figure(fig, "prediction_domain_validation")
190
191
192 def transfer_figure(experiments):
```

```
    rows, matrix_rows, matrix_labels = [], [], []
    for name, evidence in experiments.items():
        for kind, part in [("Previous spectra\nrechecked", evidence["previous"]),
                           ("Fixed default", evidence["default"])]:
            rows.append({"label": f"{evidence['label']}\n{kind}", "sources": len(part),
                         **{f"{key}_passed": int(part[field].sum()) for key, field in CHECKS.items()}})
        for field, label in [("chemical_only", "chemical"), ("fresh_passed", "fresh checks")]:
            matrix_rows.append(evidence["scenario_table"][field].to_numpy())
            matrix_labels.append(evidence["label"] + ": " + label)
    table = pd.DataFrame(rows)
    n = int(table.sources.max())
    fig, axes = plt.subplots(1, 2, figsize=(14.6, 6.2), gridspec_kw={"width_ratios": [1.0, 1.45]})
    y = np.arange(len(table))
    specs = [(-.27, "new", "Primary committee checks", COLORS["current"]),
             (-.09, "historical", "+ original / historical", COLORS["historical"]),
             (.09, "fresh", "+ original / fresh", COLORS["fresh"]),
             (.27, "all", "Historical and fresh intersection", COLORS["text"])]
    for offset, key, label, color in specs:
        values = table[f"{key}_passed"]
        axes[0].barh(y + offset, values, .16, label=label, color=color)
        for yy, value, denominator in zip(y + offset, values, table.sources):
            axes[0].text(value + .08, yy, f"{value}/{denominator}", va="center", fontsize=8)
    axes[0].set_yticks(y, table.label, fontsize=9)
    axes[0].invert_yaxis()
    axes[0].set_xlim(0, n + 1.3)
    axes[0].set_xlabel("Sources passing the stated checks")
    axes[0].set_title("Each default and its matched historical recheck", loc="left", fontsize=11, pad=14)
    axes[0].grid(axis="x", color="#E5E8EC", linewidth=.7)
    axes[0].set_axisbelow(True)
    axes[0].legend(frameon=False, fontsize=8, loc="upper left", bbox_to_anchor=(0, -.12), ncol=2)
    matrix = np.asarray(matrix_rows)
    scenario_table = next(iter(experiments.values()))["scenario_table"]
    axes[1].imshow(matrix, vmin=0, vmax=n, cmap="Blues", aspect="auto")
    axes[1].set_yticks(np.arange(len(matrix)), matrix_labels, fontsize=9)
    scenario_labels = [f"{r.statistic}\nx{r.factor:g}" if pd.notna(r.factor) else r.scenario
                       for r in scenario_table.itertuples()]
    axes[1].set_xticks(np.arange(len(scenario_table)), scenario_labels, fontsize=8)
    for (row, column), value in np.ndenumerate(matrix):
        axes[1].text(column, row, f"{value}/{n}", ha="center", va="center", fontsize=8,
                     color="white" if value > n * .6 else COLORS["text"])
    axes[1].set_title("Fixed spectra across the saved threshold scenarios", loc="left", fontsize=11, pad=14)
    axes[1].spines[["left", "bottom"]].set_visible(False)
    axes[1].tick_params(length=0)
    fig.text(.16, .025, "Domain and follow-up use different primary committees; each historical recheck uses its own matching audit draws.\n"
             "Fresh checks do not require the reused historical 10 models. All groups still share the same observed training population.",
             fontsize=9, color="#525C65")
```

```
    fig.subplots_adjust(left=.16, right=.99, top=.89, bottom=.25, wspace=.56)
    save_figure(fig, "transfer_policy_and_thresholds")


def target_figure(experiments, archived):
    frame = archived[["source_beer", "target_improvement", "change_latent_rms"]].rename(
        columns={"target_improvement": "previous_target_improvement", "change_latent_rms": "previous_change_rms"})
    specifications = [("domain", "Domain default", experiments["domain"]["default"], COLORS["current"], "D", -.06),
                      ("consensus", "Consensus matched default", experiments["consensus"]["default"], COLORS["fresh"], "s", .07)]
    consensus = experiments["consensus"]
    expanded_pool = max(consensus["manifest"]["pools"], key=consensus["manifest"]["pools"].get)
    expanded = consensus["transfers"].loc[consensus["transfers"].pool.eq(expanded_pool)
                & consensus["transfers"].policy.eq(consensus["manifest"]["default_policy"])]
    specifications.append(("expanded", f"Consensus expanded ({consensus['manifest']['pools'][expanded_pool]})",
                           expanded, COLORS["historical"], "^", .2))
    for name, label, part, color, marker, offset in specifications:
        keep = part[["source_beer", "target_improvement", "change_latent_rms", "fresh_cross_proxy_checks_passed"]]
        frame = frame.merge(keep.rename(columns={c: f"{name}_{c}" for c in keep if c != "source_beer"}),
                            on="source_beer", validate="one_to_one")
    frame = frame.sort_values("source_beer")
    frame.to_csv(TABLES / "all_default_target_comparison.csv", index=False, lineterminator="\n")
    fig, axes = plt.subplots(1, 2, figsize=(14.5, 7.0), sharey=True)
    positions = np.arange(len(frame))
    for ax, field, label, scale in [(axes[0], "target_improvement", "Reduction in target-style distance (%)", 100),
                                    (axes[1], "change_latent_rms", "Chemical change (Gaussian-space RMS)", 1)]:
        previous_field = "previous_target_improvement" if field == "target_improvement" else "previous_change_rms"
        ax.scatter(frame[previous_field] * scale, positions - .2, s=35,
                   color=COLORS["previous"], marker="o", zorder=2)
        for name, _, part, color, marker, offset in specifications:
            for position, (_, row) in zip(positions, frame.iterrows()):
                value = row[f"{name}_{field}"]
                if pd.isna(value):
                    continue
                passed = bool(row[f"{name}_fresh_cross_proxy_checks_passed"])
                ax.scatter(value * scale, position + offset, s=45, marker=marker,
                           facecolor=color if passed else "white", edgecolor=color, linewidth=1.15, zorder=3)
        ax.set_xlabel(label)
        ax.grid(axis="x", color="#E5E8EC", linewidth=.7)
        ax.set_axisbelow(True)
    axes[0].set_yticks(positions, [str(int(v)) for v in frame.source_beer])
    axes[0].invert_yaxis()
    axes[0].set_ylabel("Pils/Lager source beer")
    axes[0].set_xlim(0, 103)
    axes[0].axvline(10, color="#747E87", linewidth=1, linestyle="--")
    axes[0].set_title("Target-style proximity", loc="left", fontsize=12, pad=15)
```

```
    axes[1].set_xlim(left=0)
    axes[1].set_title("Amount of chemical change", loc="left", fontsize=12, pad=15)
    handles = [Line2D([], [], color=COLORS["previous"], marker="o", linestyle="None", label="Historical fixed spectra (reference)"),
               *[Line2D([], [], color=color, marker=marker, linestyle="None", label=label)
                 for _, label, _, color, marker, _ in specifications],
               Line2D([], [], color=COLORS["text"], marker="o", linestyle="None", label="Filled: respective fresh checks pass"),
               Line2D([], [], color=COLORS["text"], marker="o", markerfacecolor="white", linestyle="None", label="Open: at least one fresh check fails")]
    fig.legend(handles=handles, frameon=False, fontsize=9, loc="lower center", bbox_to_anchor=(.52, .085), ncol=3)
    fig.text(.09, .025, "Same source beers and frozen geometry. Missing markers mean no candidate; all missing cases stay in the 11-source denominator.\n"
             "Expanded search is a separate budget. Fresh audit draws differ between domain and consensus experiments.",
             fontsize=9, color="#525C65")
    fig.subplots_adjust(left=.09, right=.98, top=.9, bottom=.25, wspace=.23)
    save_figure(fig, "target_distance_and_consistency")


def write_report(comparison, influence, selected, by_style, stale_summary, stale_manifest,
                 experiments, neighborhood):
    selected_row = comparison.set_index("method").loc[selected]
    matched_tree = comparison.set_index("method").loc[stale_summary["old_single_tree_baseline_method"]]
    matched_multi = comparison.set_index("method").loc[stale_summary["old_multioutput_baseline_method"]]
    matched_mean = comparison.set_index("method").loc[stale_summary["mean_baseline_method"]]
    domain, consensus = experiments["domain"], experiments["consensus"]
    n_sources, n_styles = len(domain["default"]), by_style.heldout_style.nunique()
    n_train = int(stale_summary["training_samples"])
    selected_pils = float(selected_row.pils_rmse)
    prediction_failed = selected_pils >= min(matched_tree.pils_rmse, matched_multi.pils_rmse, matched_mean.pils_rmse)
    heading = "Pils预测未改善，联合筛查只有有限收益" if prediction_failed else "Pils诊断与联合筛查的探索性比较"
    d_default, c_default = domain["default"], consensus["default"]
    c_previous = consensus["previous"]
    expanded_pool = max(consensus["manifest"]["pools"], key=consensus["manifest"]["pools"].get)
    expanded_budget = consensus["manifest"]["pools"][expanded_pool]
    matched_budget = consensus["manifest"]["pools"][consensus["manifest"]["default_pool"]]
    expanded = consensus["transfers"].loc[consensus["transfers"].pool.eq(expanded_pool)
                  & consensus["transfers"].policy.eq(consensus["manifest"]["default_policy"])]
    fresh_d = int(d_default.fresh_cross_proxy_checks_passed.sum())
    fresh_c = int(c_default.fresh_cross_proxy_checks_passed.sum())
    fresh_c_previous = int(c_previous.fresh_cross_proxy_checks_passed.sum())
    fresh_expanded = int(expanded.fresh_cross_proxy_checks_passed.sum())
    influence_row = influence.loc[influence.matched_single_tree_sse_share.idxmax()]
    original_rules = domain["summary"]["previous_original_rules"]
    lines = [f"# 第三问：{heading}", "",
        f"在 {n_train} 款非 Pils 啤酒的 {n_styles} 风格留一验证中，保存的主模型为 `{s
```

```
elected}`。"
        f"其宏 RMSE 为 **{selected_row.macro_style_rmse:.4f}**，较优均值基线为 "
        f"**{stale_summary['best_mean_macro_rmse']:.4f}**；但 Pils 的诊断 RMSE 为 "
        f"**{selected_pils:.4f}**，同轮旧多输出结构重训为 **{matched_multi.pils_rmse:.4f}**，"
        f"固定专用树为 **{matched_tree.pils_rmse:.4f}**。**没有实现 Pils 跨风格预测改善。**", "",
        f"局部域模型的固定默认迁移仅选出 **{d_default.candidate_index.notna().sum()}/{n_sources}** 款，"
        f"其中 **{fresh_d}/{n_sources}** 通过 fresh 一致检查。随后沿旧固定树协议做联合筛查消融："
        f"同 **{matched_budget}** 候选预算默认策略通过 **{fresh_c}/{n_sources}**，历史固定谱在"
        f"同一追加实验规则下重检通过 **{fresh_c_previous}/{n_sources}**；"
        f"预算扩为 **{expanded_budget}** 后为 **{fresh_expanded}/{n_sources}**。"
        "追加实验由前一轮失败触发，属于探索性策略比较，没有据此替换默认或证明预测精度提高。", "",
        "## 风格留出分数与Pils诊断", "",
        f"完整 LOSO 每次排除一种非 Pils 风格，在 {n_styles} 折分别拟合预处理和预测器。"
        "选择量为风格宏 RMSE 加上预声明的风格绝对偏差惩罚；风格宏平均给每种风格相同权重，"
        "与按啤酒数量加权的 pooled RMSE 不同。",
        f"本轮惩罚系数为 {stale_manifest['bias_penalty']:g}，选中方法的宏绝对偏差为 "
        f"{selected_row.macro_style_abs_bias:.4f}，选择分数为 {selected_row.selection_score:.4f}，"
        f"样本加权 LOSO RMSE 为 {selected_row.rmse:.4f}。", "",
        "LOSO 得分参与了方法选择，最低分存在选择乐观；未另设外层来检验整个选择器。"
        "Pils 标签此前已反复查看，本轮明确视为诊断集。配置选择在保存 LOSO 结果后完成，"
        "没有把 Pils 列中最低误差的配置替换为主方法，也没有按 Pils 标签校正截距。", "",
        "|方法|LOSO宏RMSE|宏绝对偏差|选择分数|Pils诊断RMSE|主方法|",
        "|---|---:|---:|---:|---:|---|"]
    for _, row in comparison.iterrows():
        lines.append(f"|`{row['method']}`|{row.macro_style_rmse:.4f}|{row.macro_style_abs_bias:.4f}|"
                     f"{row.selection_score:.4f}|{row.pils_rmse:.4f}|{'是' if row.is_selected else ''}|")
    lines.extend(["", "![跨风格预测比较](../outputs/q3_domain/figures/prediction_domain_validation.png)", "",
        f"图1：全部 {len(comparison)} 个预声明配置的非 Pils 风格宏 RMSE 与全 {n_sources} 款 Pils 诊断 RMSE。"
        "蓝色只标记按 LOSO 规则选中的配置，未构造独立置信区间。", "",
        f"同轮固定专用树的 Pils 平方误差中，**{influence_row.matched_single_tree_sse_share:.1%}** 来自 beer "
        f"**{int(influence_row.beer)}**，其真实值为 {influence_row.observed:.4f}。"
        f"主局部模型对同一源预测 {influence_row.domain_prediction:.4f}，该源贡献主模型平方误差的 "
        f"**{influence_row.domain_selected_sse_share:.1%}**。所有主指标保留全部源，"
        "没有删除影响最大的样本或以该源单独调整方法。", "",
        f"局部模型的 bootstrap 邻域诊断中，每次名义上的 {stale_summary['config']['n_neighbors']} 个近邻"
        f"平均仅含 {neighborhood.nearest_unique_beers.mean():.2f} 款不同啤酒；"
        f"相对全量拟合邻域的 Jaccard 中位数为 {neighborhood.neighbor_jaccard_vs_final.median():.2f}。"
        "有放回抽样同时改变邻居、重复权重和拟合空间，说明训练内方差门槛不足以保证迁移配对差稳定。"
        "域模型因此保留为失败探索，不据其训练分数替代原有预测基准。", "",
        "## 两项迁移实验与检查口径", "",
        "第一项使用 LOSO 选出的局部域模型；第二项在看到其候选覆盖不足后，沿此前固定专用树协议追加联合筛查消融。"
        "追加实验重新固定默认策略和审计种子，仍然复用同一批源和训练总体，不能视为独立确认实
```

```
验。", "",
367         "每项实验都保存三种策略与两种预算：`single_geometry` 只用主筛选委员会并按几何目标排序；"
368         "`joint_geometry` 加原筛选委员会约束，仍按几何目标排序；`joint_margin` 优先最小化两组筛选 Q95 "
369         "的较差值，再按几何目标排序。默认都是保存协议中的 matched 预算和 joint_margin；"
370         "扩池结果单列，未依据审计通过数重选默认。", "",
371         "检查定义如下：", "",
372         "- **主代理**：主筛选委员会与该实验的主审计检查通过。",
373         "- **历史一致**：再要求原筛选委员会及已在先前实验中使用的原后10模型通过。",
374         "- **fresh一致（主口径）**：主代理加原筛选委员会、fresh原协议20模型；**不要求历史10模型通过**。",
375         "- **全部交集**：历史一致和fresh一致同时成立。", "",
376         "原中心预测器是45输出模型，但原40个bootstrap模型本身是单目标120树协议。"
377         "追加实验的两组新审计也沿单目标120树协议，只是种子不同，不能称为独立架构验证。"
378         "所有组共享同一真实训练总体；historical与fresh采用并列定义，非逐层包含。", "",
379         "|实验|预算|策略|源数|选出|主代理|历史一致|fresh一致|全部交集|选出谱改善中位数|选出谱改动RMS中位数|",
380         "|---|---|---|---:|---:|---:|---:|---:|---:|---:|---:|"])
381     for name, evidence in experiments.items():
382         for row in evidence["policies"].itertuples():
383             lines.append(f"|{evidence['label_zh']}|{row.pool}|{row.policy}|{row.sources}|{row.selected}|"
384                 f"{row.new_passed}|{row.historical_passed}|{row.fresh_passed}|{row.all_passed}|"
385                 f"{row.median_target_improvement_selected:.1%}|{row.median_change_rms_selected:.3f}|")
386     lines.extend(["", "改善与改动中位数只在各行选出谱中计算；选出数量不同，不可忽略分母直接比较。"
387         "未找到候选的源计为未通过，保留在全部源分母。", "",
388         f"历史报告在原规则下为 {original_rules['model_checks_passed_all_thresholds']}/{n_sources} 主代理通过、"
389         f"{original_rules['cross_proxy_checks_passed_all_thresholds']}/{n_sources} 新旧一致通过。"
390         "这些旧口径不含本轮主代理和fresh审计，不能和本轮数字直接计算提升。"
391         "每项实验都对同一历史固定谱按该实验相同模型和规则重新计算：", "",
392         "|重检所用实验|历史固定谱主代理|历史一致|fresh一致|全部交集|", "|---|---:|---:|---:|---:|"])
393     for evidence in experiments.values():
394         previous = evidence["previous"]
395         lines.append(f"|{evidence['label_zh']}|{previous.all_model_checks_passed.sum()}/{len(previous)}|"
396                      f"{previous.cross_proxy_checks_passed.sum()}/{len(previous)}|"
397                      f"{previous.fresh_cross_proxy_checks_passed.sum()}/{len(previous)}|"
398                      f"{previous.all_committees_passed.sum()}/{len(previous)}|")
399     lines.extend(["", "![策略及阈值比较](../outputs/q3_domain/figures/transfer_policy_and_thresholds.png)", "",
400         "图2：每项固定默认策略及其历史固定谱重检；右侧为默认固定谱跨全部阈值情景的化学保护及fresh一致通过数。"
401         "两项实验的主代理和审计抽样不同，跨实验数字是探索性对照；同项重检才使用完全匹配规则。", "",
402         "## 阈值情景、风格接近与改动代价", "",
403         "化学投影同时保护保存的中位数/均值及各乘数情景；每项缺陷超阈程度均不得增加。"
404         "trans-2-nonenal 无附件阈值时采用浓度不得增加。所有情景检查同一个已选谱，没有逐情景重新挑候选。"
405         "下表化学保护计数也要求已选出谱，未选出的源没有可检查迁移谱，计为未通过而非伪造浓度。", "",
406         "|阈值情景|域默认化学保护|域默认fresh|固定树默认化学保护|固定树默认fresh|",
407         "|---|---:|---:|---:|---:|"])
```

```
    ds, cs = domain["scenario_table"].set_index("scenario"), consensus["scenario_table"].set_index("scenario")
    for scenario in domain["scenario_table"].scenario:
        dr, cr = ds.loc[scenario], cs.loc[scenario]
        lines.append(f"|{scenario}|{dr.chemical_only}/{dr.sources}|{dr.fresh_passed}/{dr.sources}|"
                     f"{cr.chemical_only}/{cr.sources}|{cr.fresh_passed}/{cr.sources}|")
    lines.extend(["", "![目标距离与改动代价](../outputs/q3_domain/figures/target_distance_and_consistency.png)", "",
        "图3：全部源的历史固定谱、域模型默认、固定树matched默认及同策略expanded谱。左为冻结旧几何下的目标距离改善，"
        "右为同一高斯空间的改动RMS；历史灰点只作几何参考。其他实心点通过各自fresh检查，空心点失败，"
        "缺点表示无候选。expanded使用更多搜索预算，未替换matched默认。", "",
        f"追加实验 expanded joint_margin 的 {fresh_expanded}/{n_sources} fresh通过伴随目标接近度代价。"
        f"历史固定谱的目标改善中位数为 {consensus['previous'].previous_target_improvement.median():.1%}，"
        f"expanded选出谱为 {expanded.target_improvement.median():.1%}；改动RMS的对应差别与全部策略见上表。"
        "边际安全余量与几何最优并不一致，不能只用较高通过数量概括结果。", "",
        "|expanded joint_margin源|状态|目标改善|改动RMS|较差筛选Q95|主audit Q95|fresh原协议Q95|fresh通过|",
        "|---|---|---:|---:|---:|---:|---:|---|"])
    def number(value):
        return f"{value:+.4f}" if pd.notna(value) else "-"
    for row in expanded.sort_values("source_beer").itertuples():
        improvement = f"{row.target_improvement:.1%}" if pd.notna(row.target_improvement) else "-"
        change = f"{row.change_latent_rms:.3f}" if pd.notna(row.change_latent_rms) else "-"
        lines.append(f"|{row.source_beer}|{row.status}|{improvement}|{change}|"
            f"{number(row.worst_selection_q95)}|{number(row.new_audit_q95)}|{number(row.fresh_original_audit_q95)}|"
            f"{'是' if row.fresh_cross_proxy_checks_passed else '否'}|")
    passing = expanded.loc[expanded.fresh_cross_proxy_checks_passed]
    if len(passing):
        thin = passing.loc[passing.worst_selection_q95.idxmax()]
        lines.extend(["", f"通过谱中最接近筛选边界的是源 {int(thin.source_beer)}，"
            f"较差筛选Q95为 {thin.worst_selection_q95:+.4f}。这类临界结果应保留连续数值，"
            "不把微小负值解释为具有品评置信保证。"])
    lines.extend(["", "## 范围与复现", "",
        "本轮仍未证明跨风格Stale hops准确预测改善。LOSO模型选择、候选搜索及多次追加实验复用现有数据，"
        "fresh只指新重采样模型，未带来新的独立啤酒或真实品评。固定结构bootstrap也未包含算法选择、"
        "测量误差和生成谱分布偏移；配对差Q95不是覆盖率校准的置信上界。", "",
        "所有感官值保持附件标准化量表，未恢复0–6分。当前输出是化学目标谱和模型内筛查，"
        "需要新增真实风格样本及迁移后的理化、品评实验，才能判断真实Stale hops是否不增加。", "",
        "- LOSO与Pils诊断：`../outputs/q3_domain/stale/`。",
        "- 域模型迁移失败探索：`../outputs/q3_domain/transfer/`。",
        "- 固定树联合筛查追加实验：`../outputs/q3_domain/consensus/`。",
        "- 本报告计算表：`../outputs/q3_domain/report_tables/`。",
        "- 三张图的PNG/SVG：`../outputs/q3_domain/figures/`。",
        "- 输入逐文件哈希与行数：`../outputs/q3_domain/report_source_manifest.json`。", "",
        "```bash", ".venv/bin/python solution_a/src/18_q3_domain_report.py", "```", ""])
```

```
    (SOLUTION / "docs/q3_domain_results.md").write_text("\n".join(lines), encoding="utf-8", newline="\n")
    result = {"selected_method": selected, "non_pils_training_n": n_train, "loso_styles": n_styles,
        "pils_diagnostic_n": n_sources, "selected_loso_macro_rmse": float(selected_row.macro_style_rmse),
        "selected_pils_diagnostic_rmse": selected_pils, "matched_fixed_tree_pils_rmse": float(matched_tree.pils_rmse),
        "matched_old_multioutput_pils_rmse": float(matched_multi.pils_rmse), "pils_prediction_improved": not prediction_failed,
        "experiments": {name: {"default_pool": evidence["manifest"]["default_pool"],
            "default_policy": evidence["manifest"]["default_policy"],
            "default": {"sources": len(evidence["default"]), "selected": int(evidence["default"].candidate_index.notna().sum()),
                        **{key: int(evidence["default"][field].sum()) for key, field in CHECKS.items()}},
            "previous_same_spectra": {"sources": len(evidence["previous"]),
                        **{key: int(evidence["previous"][field].sum()) for key, field in CHECKS.items()}}}
            for name, evidence in experiments.items()},
        "consensus_expanded_same_policy": {"budget": expanded_budget, "sources": len(expanded),
            "selected": int(expanded.candidate_index.notna().sum()), "fresh": fresh_expanded,
            "all": int(expanded.all_committees_passed.sum()),
            "median_target_improvement_selected": float(expanded.target_improvement.median()),
            "median_change_rms_selected": float(expanded.change_latent_rms.median())},
        "threshold_scenarios": len(ds), "scientific_figure_count": 3,
        "scope": "Failed Pils prediction exploration and limited consensus-search gains, no sensory guarantee"}
    (OUT / "report_summary.json").write_text(json.dumps(result, ensure_ascii=False, indent=2), encoding="utf-8", newline="\n")
    return result


def main():
    TABLES.mkdir(parents=True, exist_ok=True)
    FIGURES.mkdir(parents=True, exist_ok=True)
    stale_summary = read_json(STALE / "summary.json")
    stale_manifest = read_json(STALE / "run_manifest.json")
    overall = read_csv(STALE / "loso_metrics_overall.csv")
    by_style = read_csv(STALE / "loso_metrics_by_style.csv")
    pils_metrics = read_csv(STALE / "pils_diagnostic_metrics.csv")
    pils_predictions = read_csv(STALE / "pils_diagnostic_predictions.csv")
    neighborhood = read_csv(STALE / "neighborhood_bootstrap_diagnostics.csv")
    comparison, influence, selected = prediction_tables(overall, by_style, pils_metrics, pils_predictions, stale_summary)
    experiments = {}
    for name, directory, label, label_zh in [("domain", TRANSFER, "Domain", "局部域模型"),
            ("consensus", OUT / "consensus", "Consensus follow-up", "固定树追加实验")]:
        summary = read_json(directory / "summary.json")
        manifest = read_json(directory / "run_manifest.json")
        transfers = normalize_checks(read_csv(directory / "transfer_summary.csv"))
        thresholds = read_csv(directory / "threshold_sensitivity.csv")
        thresholds["passed"] = boolean(thresholds.passed)
        previous = normalize_checks(read_csv(directory / "previous_same_spectr
```

```
a_recheck.csv"))
        policies, default, scenario_table, source = transfer_tables(transfers, thresholds, previous,
            manifest["threshold_scenarios"], name)
        experiments[name] = {"summary": summary, "manifest": manifest, "transfers": transfers,
            "policies": policies, "default": default, "scenario_table": scenario_table,
            "source": source, "previous": previous, "label": label, "label_zh": label_zh}
    if experiments["domain"]["scenario_table"].scenario.tolist() != experiments["consensus"]["scenario_table"].scenario.tolist():
        raise ValueError("Domain and follow-up threshold scenarios differ")
    archived = normalize_checks(read_csv(PREVIOUS / "transfer/transfer_summary.csv"))
    archived = archived.loc[archived.is_default_policy]
    configure_figures()
    prediction_figure(comparison, selected, by_style.heldout_style.nunique(), len(experiments["domain"]["default"]))
    transfer_figure(experiments)
    target_figure(experiments, archived)
    result = write_report(comparison, influence, selected, by_style, stale_summary, stale_manifest,
                          experiments, neighborhood)
    (OUT / "report_source_manifest.json").write_text(json.dumps(SOURCES, ensure_ascii=False, indent=2), encoding="utf-8", newline="\n")
    print(json.dumps(result, ensure_ascii=False, indent=2), flush=True)


if __name__ == "__main__":
    main()
```

src/19_q3_domain_verify.py

SHA-256: 47b27fb2c62595bf9fbf11563176d4af2e70047402846433426d14830b7aef92

```
"""Verify style-held-out prediction and predeclared committee search."""
from __future__ import annotations

import hashlib
import importlib
import json
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from scipy.stats import spearmanr
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from threadpoolctl import threadpool_limits

from common import SOLUTION

BASE = importlib.import_module("10_q3_verify")
PREVIOUS_VERIFY = importlib.import_module("15_q3_optimized_verify")
OUT = SOLUTION / "outputs/q3_domain"
TOL = 1e-10


def score(y, prediction):
    y, prediction = np.asarray(y, float), np.asarray(prediction, float)
    actual_var, predicted_var = np.var(y), np.var(prediction)
    actual_range = np.quantile(y, .95)-np.quantile(y, .05)
    predicted_range = np.quantile(prediction, .95)-np.quantile(prediction, .05)
    return {"mae": mean_absolute_error(y, prediction), "rmse": np.sqrt(mean_squared_error(y, prediction)),
            "r2": r2_score(y, prediction),
            "spearman": spearmanr(y, prediction).statistic if actual_var > 1e-20 and predicted_var > 1e-20 else np.nan,
            "prediction_variance": predicted_var, "target_variance": actual_var,
            "prediction_variance_ratio": predicted_var/actual_var if actual_var else np.nan,
            "prediction_std_ratio": np.sqrt(predicted_var/actual_var) if actual_var else np.nan,
            "prediction_range90": predicted_range, "target_range90": actual_range,
            "prediction_range90_ratio": predicted_range/actual_range if actual_range else np.nan,
            "mean_bias": np.mean(prediction-y)}


def check_frozen():
    details = []
    for folder, manifest_path in [(SOLUTION / "outputs/q3_optimized", OUT / "previous_hashes.json"),
                                  (SOLUTION / "outputs/q3", SOLUTION / "outputs/q3_optimized/baseline_hashes.json")]:
        manifest = BASE.read_json(manifest_path)
        paths = {path.relative_to(folder).as_posix() for path in folder.rglob("*") if path.is_file()}
        assert paths == {row["path"] for row in manifest["files"]}
        for row in manifest["files"]:
```

```
            raw = (folder/row["path"]).read_bytes()
            assert len(raw) == row["bytes"] and hashlib.sha256(raw).hexdigest(
) == row["sha256"], row["path"]
        details.append({"directory": folder.relative_to(SOLUTION).as_posix(),
"unchanged_files": len(paths)})
    return details


def style_weights(styles):
    labels = np.asarray(styles)
    unique, inverse, counts = np.unique(labels, return_inverse=True, return_co
unts=True)
    return len(labels)/(len(unique)*counts[inverse])


def check_local_training(model, training, target, styles, calibrated):
    if "chemical" in model.named_steps:
        PREVIOUS_VERIFY.check_pipeline_training(model, training, calibrated)
    elif "imputer" in model.named_steps:
        BASE.close(model.named_steps["imputer"].statistics_, np.nanmedian(trai
ning, axis=0), "Source-excluded raw medians")
    estimator = model.named_steps["model"]
    if hasattr(estimator, "models_"):
        for member in estimator.models_:
            check_local_training(member, training, target, styles, calibrated)
    if hasattr(estimator, "x_"):
        BASE.close(estimator.x_, model[:-1].transform(training), "Local predic
tor training coordinates")
        BASE.close(estimator.y_, target, "Local predictor training labels")
        BASE.close(estimator.sample_weight_, style_weights(styles), "Equal-sty
le local training weights")
    if hasattr(estimator, "target_mean_"):
        BASE.close(estimator.target_mean_, np.average(target, weights=style_we
ights(styles)), "Centered weighted target mean")


def check_domain(context):
    from q3_stale_domain import make_domain_pipeline, training_fit_params
    folder = OUT / "stale"
    meta, x, y45 = context["meta"], context["x"], context["y"]
    y = y45.stale_hops
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    sources = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    manifest = BASE.read_json(folder/"run_manifest.json")
    summary = BASE.read_json(folder/"summary.json")
    selection = BASE.read_json(folder/"selection_result.json")
    assert manifest["pils_labels_used_in_training_selection_or_intercept"] is
False
    assert manifest["features"] == x.columns.tolist()
    specs = {spec["name"]: spec for spec in manifest["candidate_specs"]}
    predictions = pd.read_csv(folder/"loso_predictions.csv")
    audit = pd.read_csv(folder/"loso_split_audit.csv")
    by_style = pd.read_csv(folder/"loso_metrics_by_style.csv")
    overall = pd.read_csv(folder/"loso_metrics_overall.csv").set_index("method
")
    assert len(predictions) == len(train)*len(specs)
    assert not predictions.duplicated(["method", "global_index"]).any()
    assert set(predictions.global_index) == set(train)
    assert set(predictions.method) == set(specs)
    groups = meta.tasting_category_fine.iloc[train]
    assert set(groups.unique()) == set(manifest["heldout_groups"])
    assert len(groups.unique()) == summary["loso_styles"]
```

```
    calculated_styles = []
    selected_spec = selection["config"]
    for fold, fold_rows in audit.groupby("fold"):
        heldout = fold_rows.heldout_style.unique()
        assert len(heldout) == 1
        style = heldout[0]
        expected_test = train[groups.to_numpy() == style]
        expected_train = train[groups.to_numpy() != style]
        assert set(fold_rows.loc[fold_rows.role.eq("test"), "global_index"]) ==
= set(expected_test)
        assert set(fold_rows.loc[fold_rows.role.eq("train"), "global_index"])
== set(expected_train)
        assert len(fold_rows) == len(train) and not fold_rows.global_index.dup
licated().any()
        assert fold_rows.beer.tolist() == fold_rows.global_index.map(meta.beer
).tolist()
        model = make_domain_pipeline(selected_spec, x.columns.tolist(), contex
t["calibrated_features"],
                                     manifest["aging_features"], manifest["los
o_seed"]+int(fold))
        model.fit(x.iloc[expected_train], y.iloc[expected_train],
                  **training_fit_params(selected_spec, meta.tasting_category_f
ine.iloc[expected_train]))
        selected_rows = predictions[predictions.method.eq(selection["selected_
method"])
                                    & predictions.fold.eq(fold)].set_index("gl
obal_index").loc[expected_test]
        BASE.close(selected_rows.prediction, np.asarray(model.predict(x.iloc[e
xpected_test])).reshape(-1),
                   "Selected LOSO prediction refitted without the held-out sty
le")
        for method in specs:
            rows = predictions[predictions.method.eq(method) & predictions.fol
d.eq(fold)].set_index("global_index").loc[expected_test]
            assert rows.heldout_style.eq(style).all()
            BASE.close(rows.observed, y.iloc[expected_test], "LOSO true labels
")
            calculated_styles.append({"method": method, "heldout_style": style
, "fold": fold,
                                      **score(rows.observed, rows.prediction),
                                      "bias": np.mean(rows.prediction.to_numpy
()-rows.observed.to_numpy())})
            if method == "mean_global":
                BASE.close(rows.prediction, y.iloc[expected_train].mean(), "LO
SO global training mean")
            if method == "mean_style_balanced":
                means = y.iloc[expected_train].groupby(meta.tasting_category_f
ine.iloc[expected_train]).mean()
                BASE.close(rows.prediction, means.mean(), "LOSO equal-style tr
aining mean")
    metric_names = list(score(y, y))
    BASE.same_table(by_style, pd.DataFrame(calculated_styles), ["method", "hel
dout_style", "fold"],
                    metric_names+["bias"], "LOSO per-style metrics")
    calculated = []
    for method, spec in specs.items():
        rows = predictions[predictions.method.eq(method)].set_index("global_in
dex").loc[train]
        styles = by_style[by_style.method.eq(method)]
        metrics = score(rows.observed, rows.prediction)
        within_prediction = within_truth = 0.
        for style in groups.unique():
```

```
            mask = groups.to_numpy() == style
            pred, truth = rows.prediction.to_numpy()[mask], rows.observed.to_n
umpy()[mask]
            within_prediction += np.sum((pred-pred.mean())**2)
            within_truth += np.sum((truth-truth.mean())**2)
        macro_rmse, macro_bias = styles.rmse.mean(), styles.bias.abs().mean()
        calculated.append({"method": method, **metrics,
                           "macro_style_rmse": macro_rmse, "macro_style_mae":
styles.mae.mean(),
                           "macro_style_abs_bias": macro_bias, "macro_style_bi
as": styles.bias.mean(),
                           "selection_score": macro_rmse+manifest["bias_penalt
y"]*macro_bias,
                           "within_style_prediction_variance_ratio": within_pr
ediction/within_truth})
        assert bool(metrics["prediction_variance_ratio"] >= manifest["variance
_ratio_min"]) == overall.at[method,"nonconstant_qualified"]
        assert spec["selectable"] == overall.at[method,"selectable"]
    BASE.same_table(overall.reset_index(), pd.DataFrame(calculated), ["method"
],
                    [key for key in calculated[0] if key != "method"], "LOSO m
acro and pooled metrics")
    best_mean = overall.loc[["mean_global", "mean_style_balanced"], "macro_sty
le_rmse"].min()
    eligible = overall[overall.selectable & overall.nonconstant_qualified]
    fallback = eligible.empty
    if fallback:
        eligible = overall[overall.selectable]
    winner = eligible.reset_index().sort_values(["selection_score", "method"])
.iloc[0]
    assert winner.method == selection["selected_method"] == summary["selected_
method"]
    assert fallback == selection["fallback_used"]
    qualified = bool(winner.nonconstant_qualified and winner.macro_style_rmse
< best_mean)
    assert qualified == selection["qualified_for_proxy"] == summary["qualified
_for_proxy"]
    artifact = joblib.load(folder/"transfer_stale_model.joblib")
    ensemble = joblib.load(folder/"bootstrap_ensemble.joblib")
    for saved in [artifact, ensemble]:
        np.testing.assert_array_equal(saved["train_global_indices"], train)
        np.testing.assert_array_equal(saved["excluded_global_indices"], source
s)
        assert saved["selected_config"] == selected_spec and saved["qualified_
for_proxy"] == qualified
        assert saved["pils_diagnostic_used_for_selection"] is False
    check_local_training(artifact["pipeline"], x.iloc[train], y.iloc[train], g
roups, context["calibrated_features"])
    indices = np.asarray(ensemble["bootstrap_indices"])
    assert indices.shape == (60,len(train)) and not np.isin(indices,sources).a
ny()
    assert ensemble["selection_model_indices"] == list(range(40)) and ensemble
["audit_model_indices"] == list(range(40,60))
    with np.load(folder/"bootstrap_indices.npz") as saved:
        np.testing.assert_array_equal(saved["indices"],indices)
        np.testing.assert_array_equal(saved["bootstrap_seeds"],ensemble["boots
trap_seeds"])
    for b,(model,index,seed) in enumerate(zip(ensemble["models"],indices,ensem
ble["bootstrap_seeds"])):
        expected_seed = manifest["selection_bootstrap_seed"]+b if b<40 else ma
nifest["audit_bootstrap_seed"]+b-40
        assert seed == expected_seed
```

```
        np.testing.assert_array_equal(index,np.random.default_rng(seed).choice(train,len(train),replace=True))
        check_local_training(model,x.iloc[index],y.iloc[index],meta.tasting_category_fine.iloc[index],context["calibrated_features"])
    diagnostic = pd.read_csv(folder/"pils_diagnostic_predictions.csv")
    diagnostic_metrics = pd.read_csv(folder/"pils_diagnostic_metrics.csv").set_index("method")
    assert set(diagnostic.method) == set(specs) and len(diagnostic)==len(sources)*len(specs)
    for method in specs:
        rows=diagnostic[diagnostic.method.eq(method)].set_index("global_index").loc[sources]
        BASE.close(rows.observed,y.iloc[sources],"Pils diagnostic labels")
        BASE.close(diagnostic_metrics.loc[method,metric_names],list(score(rows.observed,rows.prediction).values()),"Pils diagnostic metrics")
    rows=diagnostic[diagnostic.method.eq(selection["selected_method"])].set_index("global_index").loc[sources]
    BASE.close(rows.prediction,np.asarray(artifact["pipeline"].predict(x.iloc[sources])).reshape(-1),"Frozen selected Pils diagnostic")
    if selected_spec["family"]=="local":
        local_rows=[]
        final=artifact["pipeline"];final_estimator=final.named_steps["model"]
        k=final_estimator.n_neighbors
        final_distance=cdist(final[:-1].transform(x.iloc[sources]),final_estimator.x_)
        final_neighbors=[set(train[np.argpartition(distance,k-1)[:k]]) for distance in final_distance]
        for b,(model,index) in enumerate(zip(ensemble["models"],indices)):
            estimator=model.named_steps["model"]
            distances=cdist(model[:-1].transform(x.iloc[sources]),estimator.x_)
            predicted=np.asarray(model.predict(x.iloc[sources])).reshape(-1)
            for j,(source_index,distance) in enumerate(zip(sources,distances)):
                near=np.argpartition(distance,k-1)[:k]
                neighbors=set(index[near]);weights=estimator.sample_weight_[near]/np.maximum(distance[near],1e-12)
                _,inverse=np.unique(index[near],return_inverse=True)
                by_beer=np.bincount(inverse,weights=weights)
                unique_effective=by_beer.sum()**2/np.sum(by_beer**2)
                assert unique_effective<=len(neighbors)+1e-10
                local_rows.append({"beer":int(meta.beer.iloc[source_index]),"model_index":b,
                    "prediction":predicted[j],"nearest_unique_beers":len(neighbors),
                    "neighbor_jaccard_vs_final":len(neighbors&final_neighbors[j])/len(neighbors|final_neighbors[j]),
                    "effective_resampled_position_count":weights.sum()**2/np.sum(weights**2),
                    "effective_unique_beer_count":unique_effective,
                    "imputer_indicator_count":len(model.named_steps["imputer"].indicator_.features_)})
        expected_neighborhood=pd.DataFrame(local_rows)
        BASE.same_table(pd.read_csv(folder/"neighborhood_bootstrap_diagnostics.csv"),expected_neighborhood,
                        ["beer","model_index"],[column for column in expected_neighborhood if column not in {"beer","model_index"}],
                        "Bootstrap neighborhood and unique-beer influence diagnostics")
        expected_summary=expected_neighborhood.groupby("beer").agg(
            bootstrap_prediction_sd=("prediction","std"),median_neighbor_jaccard=("neighbor_jaccard_vs_final","median"),
```

```
            mean_unique_neighbors=("nearest_unique_beers","mean"),
            median_effective_resampled_position_count=("effective_resampled_position_count","median"),
            median_effective_unique_beer_count=("effective_unique_beer_count","median")).reset_index()
        BASE.same_table(pd.read_csv(folder/"neighborhood_bootstrap_summary.csv"),expected_summary,["beer"],
                        [column for column in expected_summary if column!="beer"],"Neighborhood diagnostic summaries")
    context.update({"domain_model":artifact,"domain_ensemble":ensemble,"train":train,"sources":sources})
    return {"non_source_rows":len(train),"heldout_styles":len(groups.unique()),"candidate_count":len(specs),
            "prediction_rows":len(predictions),"selected_method":selection["selected_method"],
            "selected_loso_predictions_refitted":len(groups.unique()),"qualified":qualified,
            "selected_macro_rmse":float(winner.macro_style_rmse),"best_mean_macro_rmse":float(best_mean),
            "selected_pils_diagnostic_rmse":float(diagnostic_metrics.at[selection["selected_method"],"rmse"]),
            "bootstrap_indices_shape":list(indices.shape),"pils_is_fresh_test":False}


def counts(frame):
    return {"sources":len(frame),"selected":int(frame.candidate_index.notna().sum()),
            "new_model_checks_passed":int(frame.all_model_checks_passed.sum()),
            "historical_cross_proxy_passed":int(frame.cross_proxy_checks_passed.sum()),
            "fresh_cross_proxy_passed":int(frame.fresh_cross_proxy_checks_passed.sum()),
            "all_committees_passed":int(frame.all_committees_passed.sum()),
            "no_candidate":int(frame.status.eq("no_candidate_found").sum())}


def check_transfer(context,experiment="transfer"):
    folder=OUT/experiment
    meta,x,y=context["meta"],context["x"],context["y"]
    train,sources=context["train"],context["sources"]
    manifest=BASE.read_json(folder/"run_manifest.json")
    summary=BASE.read_json(folder/"summary.json")
    proxy_folder=SOLUTION/manifest.get("proxy_directory","outputs/q3_domain/stale")
    current_model=joblib.load(proxy_folder/"transfer_stale_model.joblib")
    frozen_ensemble=joblib.load(proxy_folder/"bootstrap_ensemble.joblib")
    current_ensemble=joblib.load(folder/"screening_and_audit.joblib") if (folder/"screening_and_audit.joblib").exists() else frozen_ensemble
    for artifact in [current_model,current_ensemble]:
        np.testing.assert_array_equal(artifact["train_global_indices"],train)
        np.testing.assert_array_equal(artifact["excluded_global_indices"],sources)
    if manifest.get("fresh_domain_audit_seed") is not None:
        for b in range(40):
            np.testing.assert_array_equal(current_ensemble["bootstrap_indices"][b],frozen_ensemble["bootstrap_indices"][b])
            BASE.close(current_ensemble["models"][b].predict(x.iloc[train]),frozen_ensemble["models"][b].predict(x.iloc[train]),"Frozen follow-up screening models")
        for b in range(20):
```

```
            seed=manifest["fresh_domain_audit_seed"]+b
            index=current_ensemble["bootstrap_indices"][40+b]
            assert current_ensemble["bootstrap_seeds"][40+b]==seed
            np.testing.assert_array_equal(index,np.random.default_rng(seed).ch
oice(train,len(train),replace=True))
            tree=current_ensemble["models"][40+b].named_steps["model"]
            assert tree.n_outputs_==1 and tree.n_estimators==120 and tree.min_
samples_leaf==3 and tree.max_features==.7
            BASE.close(current_ensemble["models"][40+b].named_steps["imputer"]
.statistics_,np.nanmedian(x.iloc[index],axis=0),"Fresh current-protocol audit
medians")
    assert manifest["default_pool"]=="matched_2004" and manifest["default_poli
cy"]=="joint_margin"
    assert manifest["audit_reselection"] is False and manifest["default_select
ed_from_audit"] is False
    scenarios=manifest["threshold_scenarios"]
    assert scenarios==BASE.read_json(SOLUTION/"outputs/q3_optimized/transfer/t
hreshold_scenarios.json")
    geometry=joblib.load(SOLUTION/"outputs/q3/transfer/transfer_copula.joblib"
)
    reference=geometry["copula"]
    np.testing.assert_array_equal(geometry["training_rows"],train)
    draws=pd.read_csv(folder/"base_draws.csv")
    previous_draws=pd.read_csv(SOLUTION/"outputs/q3_optimized/transfer/optimiz
ed_base_draws.csv")
    BASE.close(draws.iloc[:500],previous_draws,"Preserved matched base draws")
    BASE.close(draws.iloc[500:],reference.sample("Tripel",1000,manifest["addit
ional_draw_seed"]),"Additional frozen-seed draws")
    assert len(draws)==1500 and draws.columns.tolist()==x.columns.tolist()
    original=joblib.load(SOLUTION/"outputs/q3/sensory/stale_bootstrap.joblib")
    old_center=joblib.load(SOLUTION/"outputs/q3/sensory/transfer_proxy.joblib"
)
    fresh=joblib.load(folder/"fresh_original_protocol_audit.joblib")
    for saved in [original,fresh]:
        np.testing.assert_array_equal(saved["train_global_indices"],train)
        assert saved["features"]==x.columns.tolist()
    assert old_center["pipeline"].named_steps["model"].n_outputs_==45
    assert len(fresh["models"])==20
    for saved in [original,fresh]:
        for model,index in zip(saved["models"],saved["bootstrap_indices"]):
            tree=model.named_steps["model"]
            assert tree.n_outputs_==1 and tree.n_estimators==120 and tree.min_
samples_leaf==3 and tree.max_features==.7
            assert not np.isin(index,sources).any()
            BASE.close(model.named_steps["imputer"].statistics_,np.nanmedian(x
.iloc[index],axis=0),"Original-protocol audit training medians")
    for b,(index,seed) in enumerate(zip(fresh["bootstrap_indices"],fresh["boot
strap_seeds"])):
        assert seed==manifest["fresh_audit_seed"]+b
        np.testing.assert_array_equal(index,np.random.default_rng(seed).choice
(train,len(train),replace=True))
    target=x.loc[meta.tasting_category_fine.eq("Tripel")]
    tz=reference.transform(target); dimension=x.shape[1]
    pairwise=cdist(tz,tz)/np.sqrt(dimension);np.fill_diagonal(pairwise,np.inf)
    support_limit=np.quantile(pairwise.min(axis=1),.95)
    BASE.close(support_limit,summary["support_nn_limit"],"Frozen full-dimensio
nal support")
    minimum,maximum=x.iloc[train].min().to_numpy(),x.iloc[train].max().to_nump
y()
    medians=x.iloc[train].median();target_median=target.median().to_numpy()
    report=pd.read_csv(folder/"transfer_summary.csv")
    diagnostics=pd.read_csv(folder/"candidate_diagnostics.csv")
```

```
    spectra=pd.read_csv(folder/"transferred_spectra.csv").set_index("transfer_id")
    deltas_csv=pd.read_csv(folder/"stale_paired_deltas.csv")
    thresholds=pd.read_csv(folder/"threshold_sensitivity.csv")
    previous_checks=pd.read_csv(folder/"previous_same_spectra_recheck.csv").set_index("source_beer")
    previous_summary=pd.read_csv(SOLUTION/"outputs/q3_optimized/transfer/transfer_summary.csv")
    previous_summary=previous_summary[previous_summary.is_default_policy].set_index("source_beer")
    previous_spectra=pd.read_csv(SOLUTION/"outputs/q3_optimized/transfer/transferred_spectra.csv").set_index("transfer_id")
    models=current_ensemble["models"]
    selected_predictions=np.vstack([np.asarray(model.predict(spectra[x.columns])).reshape(-1) for model in models])
    original_predictions=np.vstack([np.asarray(model.predict(spectra[x.columns])).reshape(-1) for model in original["models"]])
    fresh_predictions=np.vstack([np.asarray(model.predict(spectra[x.columns])).reshape(-1) for model in fresh["models"]])
    assert len(report)==len(sources)*len(manifest["pools"])*len(manifest["policies"])
    assert set(report[report.candidate_index.notna()].transfer_id)==set(spectra.index)
    selections=scenario_count=0; maximum_quantile_error=0.
    qualified=bool(current_model["qualified_for_proxy"])
    for source_index in sources:
        beer=int(meta.beer.iloc[source_index]);raw=x.iloc[[source_index]];source=raw.fillna(medians)
        caps={}
        for field in BASE.DEFECT_FIELDS:
            levels=[scenario["thresholds"][field] for scenario in scenarios if scenario["thresholds"][field] is not None]
            caps[field]=max(float(raw[field].iloc[0]),min(levels)) if levels else float(raw[field].iloc[0])
        arrays=[];gammas=[];draw_ids=[];matched=[]
        for gamma in manifest["gammas"]:
            arrays.append((1-gamma)*source.to_numpy()[0]+gamma*draws.to_numpy())
            gammas.extend([gamma]*len(draws));draw_ids.extend(range(len(draws)));matched.extend(np.arange(len(draws))<500)
        for gamma in manifest["gammas"]:
            arrays.append(((1-gamma)*source.to_numpy()[0]+gamma*target_median)[None])
            gammas.append(gamma);draw_ids.append(-1);matched.append(True)
        values=pd.DataFrame(np.vstack(arrays),columns=x.columns)
        for field,cap in caps.items(): values[field]=values[field].clip(lower=0,upper=cap)
        z,sz=reference.transform(values),reference.transform(source)
        distance=reference.distance(values,"Tripel");before=float(reference.distance(source,"Tripel")[0])
        nn=cdist(z,tz).min(axis=1)/np.sqrt(dimension)
        change=np.linalg.norm(z-sz,axis=1)/np.sqrt(dimension);improvement=1-distance/max(before,1e-8)
        objective=distance/max(before,1e-8)+manifest["lambda"]*change/max(float(np.linalg.norm(sz[0]-tz.mean(axis=0))/np.sqrt(dimension)),1e-8)
        support=(nn<=support_limit+TOL)&(values.to_numpy()>=minimum-TOL).all(axis=1)&(values.to_numpy()<=maximum+TOL).all(axis=1)
        chemical=BASE.chemical_flags(values,caps)
        source_new=np.array([float(np.asarray(model.predict(source)).reshape(-1)[0]) for model in models])
        source_old=np.array([float(np.asarray(model.predict(source)).reshape(-1)[0]) for model in original["models"]])
```

```
        source_fresh=np.array([float(np.asarray(model.predict(source)).reshape(-1)[0]) for model in fresh["models"]])
        unique,inverse=np.unique(values.to_numpy(),axis=0,return_inverse=True);unique=pd.DataFrame(unique,columns=x.columns)
        new_delta=np.column_stack([np.asarray(model.predict(unique)).reshape(-1)-source_new[b] for b,model in enumerate(models[:40])])[inverse]
        old_delta=np.column_stack([np.asarray(model.predict(unique)).reshape(-1)-source_old[b] for b,model in enumerate(original["models"][:30])])[inverse]
        nq,oq=np.quantile(new_delta,.95,axis=1),np.quantile(old_delta,.95,axis=1);worst=np.maximum(nq,oq)
        new_signal=np.any(np.abs(new_delta)>1e-8,axis=1);old_signal=np.any(np.abs(old_delta)>1e-8,axis=1)
        base_ok=support&chemical&(improvement>=.1)&(change>=.05)
        single=base_ok&(nq<=TOL)&new_signal;joint=single&(oq<=TOL)&old_signal
        diag=diagnostics[diagnostics.source_beer.eq(beer)].sort_values("candidate_index")
        assert len(diag)==len(values)==manifest["pools"]["expanded_6004"]
        np.testing.assert_array_equal(diag.candidate_index,np.arange(len(values)))
        np.testing.assert_array_equal(diag.draw,draw_ids);BASE.close(diag.gamma,gammas,"Interpolation gamma")
        np.testing.assert_array_equal(diag.matched_budget,matched)
        BASE.close(diag[["target_distance","target_improvement","target_nn_rms","change_latent_rms","selection_new_q95","selection_old_q95","worst_selection_q95","geometry_objective"]],
                   np.column_stack([distance,improvement,nn,change,nq,oq,worst,objective]),"Reconstructed screening-only candidate statistics")
        for column,expected in [("support_ok",support),("all_thresholds_chemical_ok",chemical),("new_signal",new_signal),
                                ("old_signal",old_signal),("single_feasible",single),("joint_feasible",joint)]:
            np.testing.assert_array_equal(diag[column],expected)
        for _,row in report[report.source_beer.eq(beer)].iterrows():
            mask=np.asarray(matched) if row.pool=="matched_2004" else np.ones(len(values),bool)
            eligible=(single if row.policy=="single_geometry" else joint)&mask;ids=np.flatnonzero(eligible)
            assert row.n_candidates==mask.sum() and row.n_selection_feasible==len(ids)
            nv,ov=np.std(new_delta[mask].mean(axis=1)),np.std(old_delta[mask].mean(axis=1))
            BASE.close([row.new_candidate_delta_sd,row.old_candidate_delta_sd],[nv,ov],"Per-pool proxy response")
            if not len(ids): assert pd.isna(row.candidate_index) and row.status=="no_candidate_found";continue
            chosen=int(ids[np.lexsort((objective[ids],worst[ids]))[0]]) if row.policy=="joint_margin" else int(ids[np.argmin(objective[ids])])
            assert chosen==int(row.candidate_index),"Audit entered candidate selection"
            selections+=1;final=spectra.loc[[row.transfer_id],x.columns];BASE.close(final,values.iloc[[chosen]],"Rebuilt selected spectrum")
            position=spectra.index.get_loc(row.transfer_id)
            nd=selected_predictions[:,position]-source_new;od=original_predictions[:,position]-source_old;fd=fresh_predictions[:,position]-source_fresh
            groups_delta={"new_selection":nd[:40],"old_selection":od[:30],"new_audit":nd[40:],"old_historical":od[30:],"fresh_original_audit":fd}
            actual=[row.selection_new_q95,row.selection_old_q95,row.new_audit_q95,row.old_historical_audit_q95,row.fresh_original_audit_q95]
            expected=[np.quantile(difference,.95) for difference in groups_delta.values()]
            BASE.close(actual,expected,"Selected paired screening and audit quantiles")
```

```
            maximum_quantile_error=max(maximum_quantile_error,float(np.max(np.abs(np.asarray(actual)-expected))))
            new_pass=bool(qualified and nv>1e-6 and new_signal[chosen] and expected[2]<=TOL)
            historical=bool(new_pass and ov>1e-6 and old_signal[chosen] and expected[1]<=TOL and expected[3]<=TOL)
            fresh_pass=bool(new_pass and ov>1e-6 and old_signal[chosen] and expected[1]<=TOL and expected[4]<=TOL)
            assert [new_pass,historical,fresh_pass,historical and fresh_pass]==[row.all_model_checks_passed,row.cross_proxy_checks_passed,row.fresh_cross_proxy_checks_passed,row.all_committees_passed]
            for label,difference in groups_delta.items():
                stored=deltas_csv[deltas_csv.transfer_id.eq(row.transfer_id)&deltas_csv.ensemble.eq(label)].sort_values("model_index")
                np.testing.assert_array_equal(stored.model_index,np.arange(len(difference)));BASE.close(stored.paired_delta,difference,"Per-model paired difference")
            checks=thresholds[thresholds.transfer_id.eq(row.transfer_id)]
            assert len(checks)==len(scenarios)*len(BASE.DEFECT_FIELDS)
            for check in checks.itertuples(index=False):
                scenario=next(s for s in scenarios if s["scenario"]==check.scenario);threshold=scenario["thresholds"][check.feature]
                observed=float(raw[check.feature].iloc[0]);cap=max(observed,threshold) if threshold is not None else observed
                value=float(final[check.feature].iloc[0]);BASE.close([check.source,check.transferred,check.upper_bound],[observed,value,cap],"Scenario concentration")
                assert bool(0<=value<=cap+TOL)==check.passed;scenario_count+=1
        previous=previous_spectra.loc[[previous_summary.at[beer,"transfer_id"]],x.columns]
        nd=np.array([float(np.asarray(model.predict(previous)).reshape(-1)[0])-source_new[b] for b,model in enumerate(models)])
        od=np.array([float(np.asarray(model.predict(previous)).reshape(-1)[0])-source_old[b] for b,model in enumerate(original["models"])])
        fd=np.array([float(np.asarray(model.predict(previous)).reshape(-1)[0])-source_fresh[b] for b,model in enumerate(fresh["models"])])
        pq=[np.quantile(nd[:40],.95),np.quantile(od[:30],.95),np.quantile(nd[40:],.95),np.quantile(od[30:],.95),np.quantile(fd,.95)]
        recorded=previous_checks.loc[beer]
        BASE.close(recorded[["selection_new_q95","selection_old_q95","new_audit_q95","old_historical_audit_q95","fresh_original_audit_q95"]],pq,"Previous frozen-spectrum current-rule quantiles")
        pz=reference.transform(previous);pi=1-float(reference.distance(previous,"Tripel")[0])/max(before,1e-8)
        pg=bool(pi>=.1 and np.linalg.norm(pz-sz)/np.sqrt(dimension)>=.05 and cdist(pz,tz).min()/np.sqrt(dimension)<=support_limit+TOL
                and (previous.to_numpy()>=minimum-TOL).all() and (previous.to_numpy()<=maximum+TOL).all())
        pc=bool(BASE.chemical_flags(previous,caps)[0]);assert pc==recorded.all_thresholds_chemical_ok and pg==recorded.geometry_ok
        matched_mask=np.asarray(matched)
        pn=bool(qualified and pg and pc and pq[0]<=TOL and pq[2]<=TOL and np.any(np.abs(nd[:40])>1e-8) and np.std(new_delta[matched_mask].mean(axis=1))>1e-6)
        po=bool(pq[1]<=TOL and np.any(np.abs(od[:30])>1e-8) and np.std(old_delta[matched_mask].mean(axis=1))>1e-6)
        assert [pn,pn and po and pq[3]<=TOL,pn and po and pq[4]<=TOL,pn and po and pq[3]<=TOL and pq[4]<=TOL]==list(recorded[["all_model_checks_passed","cross_proxy_checks_passed","fresh_cross_proxy_checks_passed","all_committees_passed"]])
        print(f"Verified domain candidates: source {beer}",flush=True)
    policies=[]
```

```
    for (pool,policy),group in report.groupby(["pool","policy"]):policies.append({"pool":pool,"policy":policy,**counts(group)})
    BASE.same_table(pd.read_csv(folder/"policy_summary.csv"),pd.DataFrame(policies),["pool","policy"],list(counts(report)),"Domain policy summaries")
    default=report[report.is_default_policy];assert default.pool.eq(manifest["default_pool"]).all() and default.policy.eq(manifest["default_policy"]).all()
    assert counts(default)==summary["default_policy"]
    for name,column in [("new_model_checks_passed","all_model_checks_passed"),("historical_cross_proxy_passed","cross_proxy_checks_passed"),
                        ("fresh_cross_proxy_passed","fresh_cross_proxy_checks_passed"),("all_committees_passed","all_committees_passed")]:
        assert int(previous_checks[column].sum())==summary["previous_same_spectra_current_rules"][name]
    context.setdefault("transfer_summaries",{})[experiment]=summary
    return {"experiment":experiment,"reconstructed_candidates":len(diagnostics),"selection_only_argmin_checks":selections,"scenario_concentration_checks":scenario_count,
            "maximum_paired_quantile_error":maximum_quantile_error,"default_policy":counts(default),
            "original_committee_outputs":1,"original_center_outputs":45,"fresh_original_protocol_models":20}


def check_reports(context):
    tables=OUT/"report_tables"
    provenance=BASE.read_json(OUT/"report_source_manifest.json")
    for source in provenance:
        path=SOLUTION/source["path"]
        assert hashlib.sha256(path.read_bytes()).hexdigest()==source["sha256"],source["path"]
        if source.get("rows") is not None:assert len(pd.read_csv(path))==source["rows"]
    overall=pd.read_csv(OUT/"stale/loso_metrics_overall.csv")
    pils=pd.read_csv(OUT/"stale/pils_diagnostic_metrics.csv")
    selected=context["domain_model"]["selected_method"]
    expected=overall.merge(pils[["method","rmse","mae","r2"]].rename(
        columns={"rmse":"pils_rmse","mae":"pils_mae","r2":"pils_r2"}),on="method",validate="one_to_one")
    comparison=pd.read_csv(tables/"prediction_method_comparison.csv")
    BASE.same_table(comparison,expected,["method"],["macro_style_rmse","pils_rmse","pils_mae","pils_r2"],"Report prediction comparison")
    assert comparison.is_selected.equals(comparison.method.eq(selected))
    by_style=pd.read_csv(OUT/"stale/loso_metrics_by_style.csv")
    BASE.same_table(pd.read_csv(tables/"selected_loso_by_style.csv"),by_style[by_style.method.eq(selected)],
                    ["heldout_style"],["rmse","mae","bias"],"Report selected LOSO styles")
    predictions=pd.read_csv(OUT/"stale/pils_diagnostic_predictions.csv")
    influence=pd.read_csv(tables/"pils_source_error_influence.csv").set_index("beer")
    assert set(influence.index)==set(context["meta"].beer.iloc[context["sources"]])
    method_map={"domain_prediction":selected,"matched_single_tree_prediction":"fixed_single_tree",
                "previous_single_tree_prediction":"fixed_single_tree","old_multioutput_prediction":"old_multioutput_tree",
                "training_mean_prediction":"mean_global"}
    for column,method in method_map.items():
        if column not in influence:continue
        rows=predictions[predictions.method.eq(method)].set_index("beer").loc[influence.index]
        BASE.close(influence[column],rows.prediction,"Report source prediction
```

```
 influence")
        BASE.close(influence.observed,rows.observed,"Report source observed va
lues")
    for column in influence:
        if column.endswith("_sse_share"):
            prefix=column.removesuffix("_sse_share")
            prediction_column="domain_prediction" if prefix=="domain_selected"
 else prefix+"_prediction"
            if prediction_column in influence:
                squared=(influence[prediction_column]-influence.observed)**2
                BASE.close(influence[column],squared/squared.sum(),"Report per
-source squared-error shares")
    check_names={"new":"all_model_checks_passed","historical":"cross_proxy_che
cks_passed",
                 "fresh":"fresh_cross_proxy_checks_passed","all":"all_committe
es_passed"}
    for experiment,folder_name in [("domain","transfer"),("consensus","consens
us")]:
        folder=OUT/folder_name
        transfer=pd.read_csv(folder/"transfer_summary.csv")
        manifest=BASE.read_json(folder/"run_manifest.json")
        previous=pd.read_csv(folder/"previous_same_spectra_recheck.csv")
        thresholds=pd.read_csv(folder/"threshold_sensitivity.csv")
        expected_policies=[]
        for (pool,policy),group in transfer.groupby(["pool","policy"]):
            valid=group.candidate_index.notna()
            expected_policies.append({"pool":pool,"policy":policy,"sources":le
n(group),"selected":int(valid.sum()),
                **{name+"_passed":int(group[column].sum()) for name,column in
check_names.items()},
                "median_target_improvement_selected":group.loc[valid,"target_i
mprovement"].median(),
                "median_change_rms_selected":group.loc[valid,"change_latent_rm
s"].median(),
                "median_target_improvement_fresh_pass":group.loc[group.fresh_c
ross_proxy_checks_passed,"target_improvement"].median()})
        expected_policies=pd.DataFrame(expected_policies)
        BASE.same_table(pd.read_csv(tables/f"{experiment}_policy_comparison.cs
v"),expected_policies,["pool","policy"],
                        [column for column in expected_policies if column not
in {"pool","policy"}],"Report policy counts and tradeoffs")
        default=transfer[transfer.is_default_policy]
        passed=thresholds.groupby(["transfer_id","scenario"]).passed.all()
        expected_scenarios=[]
        for scenario in manifest["threshold_scenarios"]:
            chemical=np.array([bool(passed.get((transfer_id,scenario["scenario
"]),False)) for transfer_id in default.transfer_id])
            expected_scenarios.append({"scenario":scenario["scenario"],"source
s":len(default),"chemical_only":int(chemical.sum()),
                                       **{name+"_passed":int((chemical&default[
column].to_numpy(bool)).sum()) for name,column in check_names.items()}})
        expected_scenarios=pd.DataFrame(expected_scenarios)
        BASE.same_table(pd.read_csv(tables/f"{experiment}_default_threshold_pa
ss_counts.csv"),expected_scenarios,["scenario"],
                        [column for column in expected_scenarios if column!="s
cenario"],"Report default threshold counts")
        source_comparison=pd.read_csv(tables/f"{experiment}_default_source_com
parison.csv").set_index("source_beer")
        BASE.close(source_comparison.loc[default.source_beer,"target_improveme
nt"],default.target_improvement,"Report default source geometry")
        for column in check_names.values():
            np.testing.assert_array_equal(source_comparison.loc[default.source
```

```
_beer,column],default[column])
498             np.testing.assert_array_equal(source_comparison.loc[previous.sourc
e_beer,"previous_"+column],previous[column])
499     target_comparison=pd.read_csv(tables/"all_default_target_comparison.csv").
set_index("source_beer")
500     for prefix,folder_name,pool in [("domain","transfer","matched_2004"),("con
sensus","consensus","matched_2004"),
501                                     ("expanded","consensus","expanded_6004")]:
502         rows=pd.read_csv(OUT/folder_name/"transfer_summary.csv")
503         rows=rows[rows.pool.eq(pool)&rows.policy.eq("joint_margin")]
504         BASE.close(target_comparison.loc[rows.source_beer,prefix+"_target_impr
ovement"],rows.target_improvement,"Report target comparison")
505         BASE.close(target_comparison.loc[rows.source_beer,prefix+"_change_late
nt_rms"],rows.change_latent_rms,"Report chemical-change comparison")
506     report_path=SOLUTION/"docs/q3_domain_results.md"
507     text=report_path.read_text(encoding="utf-8")
508     assert len(text)>100 and selected in text
509     assert f"{pils.set_index('method').at[selected,'rmse']:.4f}" in text
510     assert "不是" in text or "不能" in text
511     figures=["prediction_domain_validation","transfer_policy_and_thresholds","
target_distance_and_consistency"]
512     for name in figures:
513         for extension in ["png","svg"]:
514             path=OUT/"figures"/f"{name}.{extension}"
515             assert path.is_file() and path.stat().st_size>100
516     report_summary=BASE.read_json(OUT/"report_summary.json")
517     assert report_summary["selected_method"]==selected
518     BASE.close(report_summary["selected_pils_diagnostic_rmse"],pils.set_index(
"method").at[selected,"rmse"],"Report diagnostic summary")
519     comparison_by_method=comparison.set_index("method")
520     baseline_min=comparison_by_method.loc[["fixed_single_tree","old_multioutpu
t_tree","mean_global"],"pils_rmse"].min()
521     assert report_summary["pils_prediction_improved"]==bool(comparison_by_meth
od.at[selected,"pils_rmse"]<baseline_min)
522     for experiment,folder_name in [("domain","transfer"),("consensus","consens
us")]:
523         transfer=pd.read_csv(OUT/folder_name/"transfer_summary.csv")
524         default=transfer[transfer.is_default_policy]
525         previous=pd.read_csv(OUT/folder_name/"previous_same_spectra_recheck.cs
v")
526         expected_default={"sources":len(default),"selected":int(default.candid
ate_index.notna().sum()),
527                           **{name:int(default[column].sum()) for name,column i
n check_names.items()}}
528         expected_previous={"sources":len(previous),**{name:int(previous[column
].sum()) for name,column in check_names.items()}}
529         assert report_summary["experiments"][experiment]["default"]==expected_
default
530         assert report_summary["experiments"][experiment]["previous_same_spectr
a"]==expected_previous
531     consensus=pd.read_csv(OUT/"consensus/transfer_summary.csv")
532     expanded=consensus[consensus.pool.eq("expanded_6004")&consensus.policy.eq(
"joint_margin")]
533     expanded_summary=report_summary["consensus_expanded_same_policy"]
534     assert expanded_summary["budget"]==6004 and expanded_summary["sources"]==l
en(expanded)
535     assert expanded_summary["selected"]==expanded.candidate_index.notna().sum(
)
536     assert expanded_summary["fresh"]==expanded.fresh_cross_proxy_checks_passed
.sum()
537     BASE.close([expanded_summary["median_target_improvement_selected"],expande
d_summary["median_change_rms_selected"]],
```

```
                [expanded.target_improvement.median(),expanded.change_latent_rms.median()],"Report expanded-budget tradeoffs")
    return {"hashed_report_sources":len(provenance),"prediction_comparisons":len(comparison),
            "experiments_with_policy_and_scenario_tables":2,"source_diagnostics":len(influence),
            "figure_pairs":len(figures),"results_report_exists":True}


def main():
    start=perf_counter();result={"status":"running","checks":[]};active="frozen_previous_results_before"
    try:
        result["checks"].append({"name":active,"details":check_frozen()})
        context,contract=BASE.load_contract();provenance=BASE.check_hashes()
        result["checks"].append({"name":"original_inputs","details":{"contract":contract,"provenance":provenance}})
        for active,operation in [("non_source_loso_selection",check_domain),("predeclared_transfer_search",check_transfer),
                                 ("fixed_protocol_consensus_followup",lambda ctx:check_transfer(ctx,"consensus")),("final_artifacts",check_reports)]:
            details=operation(context);result["checks"].append({"name":active,"details":details});print(f"Verified: {active}",flush=True)
        active="frozen_previous_results_after";result["checks"].append({"name":active,"details":check_frozen()})
        result["status"]="passed";result["limitations"]=["Pils results are repeatedly viewed diagnostics, not fresh external tests.",
            "LOSO-selected scores are optimistic after candidate selection; bootstrap fixes the chosen configuration.",
            "Committee consistency and audit quantiles do not establish true taste or causal defect preservation."]
    except Exception as error:
        result.update({"status":"failed","failed_check":active,"error":f"{type(error).__name__}: {error}"});raise
    finally:
        result["elapsed_seconds"]=perf_counter()-start
        (OUT/"verification.json").write_text(json.dumps(result,ensure_ascii=False,indent=2,allow_nan=False)+"\n",encoding="utf-8", newline="\n")
        print(json.dumps(result,ensure_ascii=False,indent=2,allow_nan=False),flush=True)


if __name__=="__main__":
    with threadpool_limits(limits=1):main()
```

src/20_q3_transfer_consensus.py

SHA-256: dda1e13b939733bb8c569a3d452e8e36c3b170a98035caf726be04bdc6c31fcf

```
"""Fixed-tree consensus follow-up after unsuccessful LOSO domain transfer.

The domain experiment remains an unsuccessful recorded experiment. This
follow-up isolates joint screening at the previous fixed-tree protocol;
its defaults are fixed before any of its new audit draws are evaluated.
"""
from importlib import import_module

from threadpoolctl import threadpool_limits

from common import SOLUTION


if __name__=="__main__":
    transfer=import_module("17_q3_transfer_domain")
    with threadpool_limits(limits=1):
        transfer.main(output_directory=SOLUTION/"outputs/q3_domain/consensus",
            proxy_directory=SOLUTION/"outputs/q3_optimized/stale_fixed",
            experiment="fixed_tree_consensus_followup",
            fresh_domain_audit_seed=20290123,
            fresh_original_audit_seed=20291123)
```

src/21_q3_beer81_audit.py

SHA-256: 20907975c2045de3afabc81913c3e7a98d49be21194eb90a9147d7ac00ab5e3e

```
"""Trace beer 81 identity, chemistry, sensory evidence and prediction influence."""
from __future__ import annotations

import hashlib
import json
from pathlib import Path
import re

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from scipy.stats import spearmanr
from sklearn.impute import SimpleImputer
from sklearn.preprocessing import StandardScaler
from threadpoolctl import threadpool_limits

from common import KEYS, ROOT, SOLUTION, data_dir, resolve_recorded_path
from q3_data import load_q3_data
from q3_stale_optimized import FoldChemicalTransform


OUT = SOLUTION / "outputs/q3_refined/beer81"
TARGET_BEER = 81
SOURCE_FILES = []


def source(path):
    SOURCE_FILES.append({"path": path.relative_to(ROOT).as_posix(), "sha256": hashlib.sha256(path.read_bytes()).hexdigest()})
    return path


def percentile(values, value):
    finite = np.asarray(values, float)
    finite = finite[np.isfinite(finite)]
    return float((np.sum(finite < value) + .5 * np.sum(finite == value)) / len(finite))


def rounded_id_agrees(reference, printed):
    text = str(printed)
    if "e" not in text.lower():
        return str(reference) == text
    mantissa, exponent = re.split("[eE]", text)
    digits = len(mantissa.split(".")[1]) if "." in mantissa else 0
    resolution = 10.0 ** (int(exponent) - digits)
    return abs(float(reference) - float(text)) <= resolution / 2


def identity_audit(raw, sensory, comments, calibrated):
    frames = {"1.csv": raw, "4.csv": sensory, "7.csv": comments, "8.xlsx/calibrated": calibrated}
    reference = raw.loc[raw.beer.eq(TARGET_BEER)].iloc[0]
    rows = []
    for name, frame in frames.items():
        selected = frame.loc[frame.beer.eq(TARGET_BEER)]
        row = selected.iloc[0]
```

```
        rows.append({"source": name, "rows": len(frame), "beer_unique": frame.beer.is_unique,
                     "beer81_matches": len(selected), "style": row.tasting_category_fine,
                     "style_matches_1csv": row.tasting_category_fine == reference.tasting_category_fine,
                     "beer_id_text": str(row.beer_id), "exact_id_matches_1csv": str(row.beer_id) == str(reference.beer_id),
                     "id_matches_printed_precision": rounded_id_agrees(reference.beer_id, row.beer_id),
                     "beer_id_unique_count": frame.beer_id.nunique(),
                     "rows_after_exact_beer_join": len(raw[["beer"]].merge(frame, on="beer", validate="one_to_one"))})
    table = pd.DataFrame(rows)
    if not (table.beer_unique.all() and table.beer81_matches.eq(1).all()
            and table.style_matches_1csv.all() and table.id_matches_printed_precision.all()):
        raise AssertionError("Identity audit found an unresolved discrepancy")
    table.to_csv(OUT / "identity_join_audit.csv", index=False, lineterminator="\n")
    return table


def chemical_audit(meta, x, manifest, raw, calibrated, thresholds, train, target):
    chemistry = thresholds.drop_duplicates("field_name_R").set_index("field_name_R")
    rows = []
    other_pils = meta.tasting_category_fine.eq("Pils/Lager") & meta.beer.ne(TARGET_BEER)
    raw_row = raw.set_index("beer").loc[TARGET_BEER]
    cal_row = calibrated.set_index("beer").loc[TARGET_BEER]
    for entry in manifest.to_dict("records"):
        field, value = entry["feature"], float(x.iloc[target][entry["feature"]])
        tr = x.loc[train, field].dropna()
        peers = x.loc[other_pils, field].dropna()
        details = chemistry.loc[field] if field in chemistry.index else pd.Series(dtype=object)
        threshold = details.get("threshold_median", np.nan)
        rows.append({"feature": field, "representation": entry["representation"], "unit": entry["unit"],
                     "value": value, "original_1csv_value": raw_row[field],
                     "calibrated_value": cal_row.get(field, np.nan),
                     "nonpils_n_observed": len(tr), "nonpils_min": tr.min(), "nonpils_q01": tr.quantile(.01),
                     "nonpils_median": tr.median(), "nonpils_q99": tr.quantile(.99), "nonpils_max": tr.max(),
                     "nonpils_percentile": percentile(tr, value), "other_pils_percentile": percentile(peers, value),
                     "outside_nonpils_range": bool(value < tr.min() or value > tr.max()),
                     "at_nonpils_minimum": bool(value == tr.min()), "at_nonpils_maximum": bool(value == tr.max()),
                     "zero": value == 0, "aging": details.get("aging"), "origin": details.get("origin_paper"),
                     "chemical_name": details.get("chemical_name"), "off_flavors": details.get("off_flavors"),
                     "sensory_threshold_median": threshold,
                     "ratio_to_sensory_threshold": value / threshold if entry["representation"] == "calibrated"
                     and pd.notna(threshold) and threshold > 0 else np.nan})
```

```
    table = pd.DataFrame(rows)
    table.to_csv(OUT / "chemical_profile_beer81.csv", index=False, linetermina
tor="\n")
    relative = manifest.loc[manifest.representation.eq("relative"), "feature"]
.tolist()
    floor_rows = []
    for i in range(len(raw)):
        counts = raw.loc[i, relative].value_counts(dropna=True)
        floor_rows.append({"beer": int(meta.beer.iloc[i]), "style": meta.tasti
ng_category_fine.iloc[i],
            "most_repeated_relative_value": float(counts.index[0]), "most_repe
ated_relative_count": int(counts.iloc[0])})
    floor_table = pd.DataFrame(floor_rows)
    floor_table.to_csv(OUT / "relative_value_repeat_patterns.csv", index=False
, lineterminator="\n")
    numeric_fields = [c for c in raw if c not in KEYS]
    repeated = raw_row[numeric_fields].value_counts()
    repeated_rows = [{"value": float(v), "count": int(n),
        "features": ";".join(c for c in numeric_fields if raw_row[c] == v),
        "interpretation": "repeated supplied value; attachment does not identi
fy an analytical detection limit"}
        for v, n in repeated.items() if n > 1]
    pd.DataFrame(repeated_rows).to_csv(OUT / "beer81_repeated_original_values.
csv", index=False, lineterminator="\n")
    calibrated_fields = manifest.loc[manifest.representation.eq("calibrated"),
 "feature"].tolist()
    zero_fields = table.loc[table.zero, "feature"].tolist()
    profile = {"raw_numeric_missing": int(raw_row[numeric_fields].isna().sum()
),
        "hybrid_missing": int(x.iloc[target].isna().sum()),
        "calibrated_negative_count": int((pd.to_numeric(cal_row[calibrated_fie
lds]) < 0).sum()),
        "raw_negative_count": int((pd.to_numeric(raw_row[numeric_fields]) < 0)
.sum()),
        "hybrid_negative_relative_count": int((x.iloc[target][relative] < 0).s
um()),
        "hybrid_zero_count": len(zero_fields), "hybrid_zero_features": zero_fi
elds,
        "exact_hybrid_duplicate_other_rows": int(np.sum(np.all(np.isclose(x.to
_numpy(float), x.iloc[target].to_numpy(float),
            rtol=0, atol=0, equal_nan=True), axis=1)) - 1),
        "outside_nonpils_feature_ranges": int(table.outside_nonpils_range.sum(
)),
        "repeated_original_values": repeated_rows,
        "analytical_detection_limits_available": False,
        "detection_limit_note": "Sensory thresholds are perceptual thresholds,
 not analytical LOD/LOQ"}
    return table, floor_table, profile


def sensory_and_comments(meta, sensory, comments, train, target):
    sensory = sensory.set_index("beer").loc[meta.beer].reset_index()
    comments = comments.set_index("beer").loc[meta.beer].copy().reset_index()
    stale = sensory.stale_hops
    profiles, associations = [], []
    for field in [c for c in sensory if c not in KEYS]:
        value = float(sensory[field].iloc[target])
        correlation = spearmanr(sensory.loc[train, field], stale.loc[train]).s
tatistic
        profiles.append({"sensory": field, "value": value, "all_percentile": p
ercentile(sensory[field], value),
            "nonpils_percentile": percentile(sensory.loc[train, field], value)
```

```
,
            "nonpils_spearman_with_stale": float(correlation)})
        if field != "stale_hops":
            associations.append({"sensory": field, "nonpils_spearman_with_stal
e": float(correlation)})
    pd.DataFrame(profiles).to_csv(OUT / "sensory_profile_beer81.csv", index=Fa
lse, lineterminator="\n")
    pd.DataFrame(associations).to_csv(OUT / "sensory_covariation_nonpils.csv",
 index=False, lineterminator="\n")
    tail = meta.copy()
    tail["stale_hops"] = stale
    tail["descending_rank"] = stale.rank(method="min", ascending=False).astype
(int)
    tail["nonpils_training"] = train
    tail.sort_values("stale_hops", ascending=False).to_csv(OUT / "stale_target
_distribution.csv", index=False, lineterminator="\n")
    terms = []
    for field in [c for c in comments if c not in KEYS]:
        value = comments[field].iloc[target]
        relevant = any(field.endswith("_" + term) for term in
            ["stale", "cardboard", "papery", "metallic", "barnyard", "cheesy",
 "cabbage", "acetaldehyde"])
        terms.append({"term": field, "beer81_value": value,
            "all_percentile": percentile(comments[field], value) if pd.notna(v
alue) else np.nan,
            "nonpils_percentile": percentile(comments.loc[train, field], value
) if pd.notna(value) else np.nan,
            "predeclared_quality_term": relevant, "source": "7.csv numeric for
um descriptor table"})
    terms = pd.DataFrame(terms)
    terms.to_csv(OUT / "forum_all_terms_beer81.csv", index=False, lineterminat
or="\n")
    terms.loc[terms.predeclared_quality_term].to_csv(OUT / "forum_quality_term
_evidence.csv", index=False, lineterminator="\n")
    return pd.DataFrame(profiles), tail, terms


def distance_audit(meta, x, manifest, train, target, y):
    train_indices, pils = np.flatnonzero(train), np.flatnonzero(~train)
    calibrated = manifest.loc[manifest.representation.eq("calibrated"), "featu
re"].tolist()
    aging_table = pd.read_csv(source(SOLUTION / "outputs/q3_domain/stale/prede
clared_aging_features.csv"))
    aging = aging_table.feature.tolist()
    values = x.to_numpy(float).copy()
    for j, field in enumerate(x):
        if field in calibrated:
            positive = values[train_indices, j]
            positive = positive[np.isfinite(positive) & (positive > 0)]
            scale = float(np.median(positive)) if len(positive) else 1.0
            values[:, j] = np.log1p(values[:, j] / scale)
    imp = SimpleImputer(strategy="median", keep_empty_features=True).fit(value
s[train_indices])
    imputed = imp.transform(values)
    scaler = StandardScaler().fit(imputed[train_indices])
    standard = scaler.transform(imputed)
    aging_indices = [x.columns.get_loc(c) for c in aging]
    spaces = {"unclipped_log_scaled_226": standard, "unclipped_log_scaled_agin
g24": standard[:, aging_indices]}
    for label, subset in [("clipped_log_scaled_226", None), ("clipped_log_scal
ed_aging24", aging)]:
        transform = FoldChemicalTransform(x.columns.tolist(), calibrated, subs
```

```
et).fit(x.iloc[train_indices])
        v = transform.transform(x)
        imputer = SimpleImputer(strategy="median", keep_empty_features=True).f
it(v[train_indices])
        v = imputer.transform(v)
        fitted_scale = StandardScaler().fit(v[train_indices])
        spaces[label] = fitted_scale.transform(v)
    geometry = joblib.load(source(SOLUTION / "outputs/q3/transfer/transfer_cop
ula.joblib"))
    np.testing.assert_array_equal(geometry["training_rows"], train_indices)
    latent = geometry["copula"].transform(x)
    spaces["old_copula_226"] = latent
    spaces["old_copula_aging24"] = latent[:, aging_indices]
    local = joblib.load(source(SOLUTION / "outputs/q3_domain/stale/transfer_st
ale_model.joblib"))
    np.testing.assert_array_equal(local["train_global_indices"], train_indices
)
    spaces["frozen_domain_aging_pca8"] = local["pipeline"][:-1].transform(x)
    ood, neighbor_rows, reference_rows, all81, other_pils_rows = [], [], [], [
], []
    for name, space in spaces.items():
        d_train = cdist(space[train_indices], space[train_indices]) / np.sqrt(
space.shape[1])
        np.fill_diagonal(d_train, np.inf)
        loo = d_train.min(axis=1)
        reference_rows.extend({"space": name, "beer": int(meta.beer.iloc[i]),
"loo_nn_distance": float(d)}
                              for i, d in zip(train_indices, loo))
        d_query = cdist(space[pils], space[train_indices]) / np.sqrt(space.sha
pe[1])
        d_pils = cdist(space[pils], space[pils]) / np.sqrt(space.shape[1])
        np.fill_diagonal(d_pils, np.inf)
        target_position = int(np.flatnonzero(pils == target)[0])
        for rank, position in enumerate(np.argsort(d_pils[target_position]), s
tart=1):
            i = pils[position]
            if i == target:
                continue
            other_pils_rows.append({"space": name, "query_beer": TARGET_BEER,
"neighbor_rank": rank,
                "neighbor_beer": int(meta.beer.iloc[i]), "distance": float(d_p
ils[target_position, position]),
                "neighbor_stale": float(y.stale_hops.iloc[i])})
        for row, query in enumerate(pils):
            order = np.argsort(d_query[row])
            nearest = float(d_query[row, order[0]])
            ood.append({"space": name, "query_beer": int(meta.beer.iloc[query]
),
                "dimensions": space.shape[1], "nearest_nonpils_distance": near
est,
                "nonpils_loo_nn_percentile": float(np.mean(loo <= nearest)),
                "nearest_other_pils_distance": float(d_pils[row].min()),
                "training_loo_nn_q95": float(np.quantile(loo, .95))})
            for rank, position in enumerate(order, start=1):
                i = train_indices[position]
                record = {"space": name, "query_beer": int(meta.beer.iloc[quer
y]), "neighbor_rank": rank,
                    "neighbor_beer": int(meta.beer.iloc[i]), "neighbor_style":
 meta.tasting_category_fine.iloc[i],
                    "distance": float(d_query[row, position]), "neighbor_stale
": float(y.stale_hops.iloc[i])}
                if rank <= 25:
```

```
                    neighbor_rows.append(record)
                if query == target:
                    all81.append(record)
    ood, neighbors, reference, all81 = map(pd.DataFrame, [ood, neighbor_rows, reference_rows, all81])
    ood["nearest_nonpils_distance_rank_within_pils_desc"] = ood.groupby("space").nearest_nonpils_distance.rank(
        ascending=False, method="min").astype(int)
    ood.to_csv(OUT / "chemical_ood_all_pils.csv", index=False, lineterminator="\n")
    neighbors.to_csv(OUT / "nearest_training_neighbors.csv", index=False, lineterminator="\n")
    all81.to_csv(OUT / "beer81_all_training_neighbor_ranks.csv", index=False, lineterminator="\n")
    reference.to_csv(OUT / "training_loo_distance_reference.csv", index=False, lineterminator="\n")
    pd.DataFrame(other_pils_rows).to_csv(OUT / "beer81_other_pils_neighbors.csv", index=False, lineterminator="\n")
    neighbor_summaries = []
    for (name, query), group in neighbors.groupby(["space", "query_beer"]):
        for k in [5, 10, 25]:
            part = group.loc[group.neighbor_rank <= k]
            neighbor_summaries.append({"space": name, "query_beer": query, "k": k,
                "stale_min": part.neighbor_stale.min(), "stale_median": part.neighbor_stale.median(),
                "stale_mean": part.neighbor_stale.mean(), "stale_max": part.neighbor_stale.max(),
                "stale_at_least_beer81": int(part.neighbor_stale.ge(y.stale_hops.iloc[target]).sum())})
    pd.DataFrame(neighbor_summaries).to_csv(OUT / "neighbor_target_summaries.csv", index=False, lineterminator="\n")
    tail_ranks = all81.loc[all81.neighbor_stale.ge(y.stale_hops.iloc[target])]
    tail_ranks.to_csv(OUT / "high_stale_training_neighbor_ranks.csv", index=False, lineterminator="\n")
    return ood, all81, tail_ranks


def influence_audit(sensory):
    saved = pd.read_csv(source(SOLUTION / "outputs/q3_domain/stale/pils_diagnostic_predictions.csv"))
    saved["stage"] = "domain_same_seed_comparison"
    parts = [saved[["stage", "method", "beer", "observed", "prediction"]]]
    prior = pd.read_csv(source(SOLUTION / "outputs/q3_optimized/stale_fixed/pils_style_holdout_predictions.csv"))
    for method, field in [("fixed_single_tree", "prediction"), ("old_multioutput", "old_multioutput_prediction"),
                          ("mean", "mean_baseline_prediction")]:
        part = prior[["beer", "observed", field]].rename(columns={field: "prediction"})
        part["stage"], part["method"] = "previous_fixed_seed_comparison", method
        parts.append(part)
    frozen = pd.read_csv(source(SOLUTION / "outputs/q3/sensory/transfer_pils_heldout_predictions.csv"))
    frozen = frozen[["beer", "stale_hops"]].rename(columns={"stale_hops": "prediction"})
    frozen["observed"] = frozen.beer.map(sensory.set_index("beer").stale_hops)
    frozen["stage"], frozen["method"] = "original_frozen_proxy", "multioutput_center"
    parts.append(frozen)
    predictions = pd.concat(parts, ignore_index=True)
```

```
    predictions["residual"] = predictions.prediction - predictions.observed
    predictions["squared_error"] = predictions.residual ** 2
    predictions["sse_share"] = predictions.squared_error / predictions.groupby(["stage", "method"]).squared_error.transform("sum")
    predictions.to_csv(OUT / "all_saved_pils_prediction_errors.csv", index=False, lineterminator="\n")
    rows, deletion = [], []
    for (stage, method), group in predictions.groupby(["stage", "method"]):
        source81 = group.loc[group.beer.eq(TARGET_BEER)].iloc[0]
        full_rmse = float(np.sqrt(group.squared_error.mean()))
        rows.append({"stage": stage, "method": method, "n_sources": len(group), "full_rmse": full_rmse,
            "beer81_prediction": source81.prediction, "beer81_residual": source81.residual,
            "beer81_sse_share": source81.sse_share})
        for beer in group.beer:
            reduced = group.loc[group.beer.ne(beer)]
            deletion.append({"stage": stage, "method": method, "omitted_beer": beer,
                "full_n": len(group), "remaining_n": len(reduced), "full_rmse": full_rmse,
                "fixed_prediction_rmse_without_one_source": float(np.sqrt(reduced.squared_error.mean())),
                "interpretation": "influence only; same fixed predictions, no retraining, never substitutes the all-source metric"})
    influence = pd.DataFrame(rows)
    influence.to_csv(OUT / "beer81_sse_contribution.csv", index=False, lineterminator="\n")
    pd.DataFrame(deletion).to_csv(OUT / "leave_one_source_out_influence.csv", index=False, lineterminator="\n")
    return influence


def main():
    OUT.mkdir(parents=True, exist_ok=True)
    root = data_dir()
    raw, sensory, comments = [pd.read_csv(source(root / filename), dtype={"beer_id": str})
                              for filename in ["1.csv", "4.csv", "7.csv"]]
    source(root / "8.xlsx")
    calibrated = pd.read_excel(root / "8.xlsx", sheet_name="Calibrated chemical dataset", dtype={"beer_id": str})
    thresholds = pd.read_excel(root / "8.xlsx", sheet_name="Sensory thresholds")
    sensory_names = pd.read_excel(root / "8.xlsx", sheet_name="Sensory names")
    target_metadata = sensory_names.loc[sensory_names.R_name.isin(["stale_hops", "barnyard", "t2n", "dms"])]
    target_metadata.to_csv(OUT / "sensory_target_metadata.csv", index=False, lineterminator="\n")
    meta, x, y, manifest = load_q3_data()
    target = int(np.flatnonzero(meta.beer.eq(TARGET_BEER))[0])
    train = meta.tasting_category_fine.ne("Pils/Lager")
    identity = identity_audit(raw, sensory, comments, calibrated)
    chemicals, floors, profile = chemical_audit(meta, x, manifest, raw, calibrated, thresholds, train, target)
    sensation, tail, terms = sensory_and_comments(meta, sensory, comments, train, target)
    ood, neighbors, tail_ranks = distance_audit(meta, x, manifest, train, target, y)
    influence = influence_audit(sensory)
    local_neighbors = neighbors.loc[neighbors.space.eq("frozen_domain_aging_pca8") & neighbors.neighbor_rank.le(25)]
```

```
    key_terms = terms.loc[terms.term.isin(["aroma_stale", "taste_stale", "tast
e_cardboard", "taste_papery"])]
    high_tail = tail.loc[tail.nonpils_training & tail.stale_hops.ge(y.stale_ho
ps.iloc[target])]
    selected = json.loads((SOLUTION / "outputs/q3_domain/stale/summary.json").
read_text(encoding="utf-8"))["selected_method"]
    source(SOLUTION / "outputs/q3_domain/stale/summary.json")
    selected_influence = influence.loc[influence.stage.eq("domain_same_seed_co
mparison") & influence.method.eq(selected)].iloc[0]
    own_floor = floors.loc[floors.beer.eq(TARGET_BEER)].iloc[0]
    barnyard = sensation.loc[sensation.sensory.eq("barnyard")].iloc[0]
    summary = {"source_beer": TARGET_BEER, "exact_beer_join_passed": True,
        "barcode_consistent_at_supplied_precision": True, "barcode_exact_1csv_
8xlsx": True,
        "sample_profile": profile, "stale_observed": float(y.stale_hops.iloc[t
arget]),
        "stale_descending_rank_all250": int(tail.loc[tail.beer.eq(TARGET_BEER)
, "descending_rank"].iloc[0]),
        "nonpils_training_rows": int(train.sum()), "nonpils_stale_at_least_bee
r81": len(high_tail),
        "nonpils_high_tail_beers": high_tail.beer.tolist(),
        "frozen_local_top25_stale_min": float(local_neighbors.neighbor_stale.m
in()),
        "frozen_local_top25_stale_max": float(local_neighbors.neighbor_stale.m
ax()),
        "beer81_outside_local_top25_target_convex_hull": bool(y.stale_hops.ilo
c[target] > local_neighbors.neighbor_stale.max()),
        "selected_domain_model": selected, "selected_domain_beer81_prediction"
: float(selected_influence.beer81_prediction),
        "selected_domain_beer81_sse_share": float(selected_influence.beer81_ss
e_share),
        "relative_repeated_floor_count": int(own_floor.most_repeated_relative_
count),
        "relative_floor_count_all250_percentile": float(np.mean(floors.most_re
peated_relative_count <= own_floor.most_repeated_relative_count)),
        "stale_target_datatype": target_metadata.loc[target_metadata.R_name.eq
("stale_hops"), "DataType"].iloc[0],
        "barnyard_target_datatype": target_metadata.loc[target_metadata.R_name
.eq("barnyard"), "DataType"].iloc[0],
        "nonpils_stale_barnyard_spearman": float(barnyard.nonpils_spearman_wit
h_stale),
        "ood_beer81": ood.loc[ood.query_beer.eq(TARGET_BEER)].to_dict("records
"),
        "forum_quality_evidence": key_terms.to_dict("records"),
        "raw_forum_text_available": False, "analytical_lod_loq_available": Fal
se,
        "label_error_established": False,
        "interpretation": "Rare high sensory target lacks matching high-target
 chemical neighbours; identity and descriptor evidence do not establish a wron
g label. Chemical predictability remains unresolved."}
    (OUT / "summary.json").write_text(json.dumps(summary, ensure_ascii=False,
indent=2), encoding="utf-8", newline="\n")
    verification = {"identity_join_four_sources_passed": bool(identity.beer_un
ique.all()),
        "features": len(chemicals), "forum_fields": len(terms), "ood_query_spa
ce_rows": len(ood),
        "training_neighbor_rank_rows": len(neighbors),
        "other_pils_neighbor_rows": len(pd.read_csv(OUT / "beer81_other_pils_n
eighbors.csv")),
        "local_target_convex_hull_gap_verified": summary["beer81_outside_local
_top25_target_convex_hull"],
        "leave_one_source_out_only_fixed_prediction_influence": True,
```

```
        "source_hashes_unchanged_after_analysis": all(hashlib.sha256(resolve_recorded_path(row["path"]).read_bytes()).hexdigest()
                                                      == row["sha256"] for row in SOURCE_FILES)}
    assert verification["source_hashes_unchanged_after_analysis"]
    (OUT / "verification.json").write_text(json.dumps(verification, ensure_ascii=False, indent=2), encoding="utf-8", newline="\n")
    (OUT / "source_manifest.json").write_text(json.dumps(SOURCE_FILES, ensure_ascii=False, indent=2), encoding="utf-8", newline="\n")
    write_note(summary, chemicals, sensation, terms, tail_ranks, influence)
    print(json.dumps(summary, ensure_ascii=False, indent=2), flush=True)


def write_note(summary, chemicals, sensation, terms, tail_ranks, influence):
    lines = ["# Beer 81误差来源诊断", "",
        "beer81的高残差目前不能归因于标签错误。附件键连接、风格和可核验条码一致；"
        "无缺失、负校准值或重复化学行解释该误差。陈旧描述在论坛术语表中也处高位。"
        "直接观察到的困难是高stale尾部样本很少，且未落入现有化学近邻空间。", "",
        "## 连接与测量检查", "",
        "1.csv与8.xlsx校准表的完整条码为8715608222557，风格均Pils/Lager。4.csv与7.csv提供"
        "的8.71561E+12与其打印精度一致；它们是舍入后的身份信息，实际按唯一beer键连接，"
        "未采用舍入条码连接。", "",
        f"原231化学列缺失数为{summary['sample_profile']['raw_numeric_missing']}，226混合输入缺失数为"
        f"{summary['sample_profile']['hybrid_missing']}，负校准值为{summary['sample_profile']['calibrated_negative_count']}，"
        f"其他样本中的整行化学重复为{summary['sample_profile']['exact_hybrid_duplicate_other_rows']}。"
        "原始表示中的负值不能直接视为负浓度；混合输入的未校准相对字段仍保留其供应表示。", "",
        "原表有多个字段重复同一低值，完整清单见beer81_repeated_original_values.csv。"
        "附件未提供分析LOD/LOQ，不能把共同低值直接命名为检出限；8.xlsx给的是感官阈值，"
        "也不等于仪器检测上下限。经验最小值、最大值与0值仅作为观测支持诊断保存。", "",
        f"81有{summary['relative_repeated_floor_count']}个相对字段重复同一低值，重复数量仅处250款的"
        f"{summary['relative_floor_count_all250_percentile']:.1%}位置，并非该现象最严重的样本。", "",
        "## 化学异常与支持域", "",
        "所有尺度仅拟合239款非Pils：校准字段先按训练正数中位数做log1p尺度化，训练中位数补缺，"
        "再训练标准化；另比较训练1%/99%截断、冻结旧copula秩空间以及16实际冻结aging/PCA8空间。"
        "没有用11款源学习尺度或边界。", "",
        "|空间|81最近非Pils距离|相对训练留一NN距离百分位|81最近其他Pils距离|", "|---|---:|---:|---:|"]
    for row in summary["ood_beer81"]:
        lines.append(f"|{row['space']}|{row['nearest_nonpils_distance']:.4f}|{row['nonpils_loo_nn_percentile']:.1%}|"
                     f"{row['nearest_other_pils_distance']:.4f}|")
    lines.extend(["", "不同空间有不同含义：全化学谱显示一定风格偏移，但aging及其PCA空间接近训练邻域。"
        "参考距离只排除训练行自身，未逐行重拟合预处理；这些百分位只是相同训练表示下的描述性比较，"
        "不是交叉拟合或校准OOD概率，也不证明所有有效化学信息已被表示。", "",
        "校准字段中，训练百分位低于2.5%或高于97.5%的项目完整列在下表；这是多变量描述性筛查，非显著性检验。", "",
        "|字段|81校准值|单位|非Pils百分位|附件aging标记|", "|---|---:|---|---:|---|"])
    extreme = chemicals.loc[chemicals.representation.eq("calibrated") &
                            ((chemicals.nonpils_percentile < .025) | (chemicals.nonpils_percentile > .975))]
```

```
    for row in extreme.itertuples():
        lines.append(f"|{row.feature}|{row.value:.6g}|{row.unit}|{row.nonpils_percentile:.1%}|{row.aging if pd.notna(row.aging) else '无'}|")
    lines.extend(["", "SO2高百分位、部分酒花来源指标低百分位均未形成附件内已验证的stale机制。"
        "不能从这些异常单独推导储存条件、氧化时间或标签错误。所有226字段的值、训练边界、百分位、"
        "来源、aging与阈值信息保存在chemical_profile_beer81.csv。", "",
        "题目四种化学缺陷的核对如下。感官阈值与stale_hops不是同一目标，不可把某一化学项超阈直接当作其误差原因。", "",
        "|字段|81校准值|单位|非Pils百分位|附件感官阈值中位数|", "|---|---:|---|---:|---:|"])
    for row in chemicals.loc[chemicals.feature.isin(["DMS", "X2.3.butanedione", "X4VG", "X.E..2.nonenal"])].itertuples():
        threshold = f"{row.sensory_threshold_median:.6g}" if pd.notna(row.sensory_threshold_median) else "未提供"
        lines.append(f"|{row.feature}|{row.value:.6g}|{row.unit}|{row.nonpils_percentile:.1%}|{threshold}|")
    outside = chemicals.loc[chemicals.outside_nonpils_range]
    if len(outside):
        labels = "; ".join(f"{r.feature}={r.value:.6g}（训练范围{r.nonpils_min:.6g}至{r.nonpils_max:.6g}）"
                           for r in outside.itertuples())
        lines.extend(["", f"全226字段超出训练观测范围的完整清单为：{labels}。"
            "该字段仍是未校准相对表示，不能擅自换算成浓度或视为仪器越限。"])
    lines.extend(["",
        "## 尾部稀缺与邻域错位", "",
        f"81的stale={summary['stale_observed']:.6f}，在250款中第{summary['stale_descending_rank_all250']}高；"
        f"239款训练中仅{summary['nonpils_stale_at_least_beer81']}款不低于它。"
        f"16实际局部模型的最近25训练邻居stale最高只有{summary['frozen_local_top25_stale_max']:.6f}，"
        f"低于81实测值；其预测为{summary['selected_domain_beer81_prediction']:.6f}。"
        "局部加权均值受邻居目标凸包限制，因此现有邻域结构无法给出81的高标签。", "",
        "|高stale训练beer|风格|实测stale|aging/PCA8近邻排名|", "|---|---|---:|---:|"])
    for row in tail_ranks.loc[tail_ranks.space.eq("frozen_domain_aging_pca8")].sort_values("neighbor_rank").itertuples():
        lines.append(f"|{row.neighbor_beer}|{row.neighbor_style}|{row.neighbor_stale:.6f}|{row.neighbor_rank}|")
    lines.extend(["", "全226旧copula的最近邻同样多为低stale样本。完整近邻及其真实目标保存，而非只展示支持结论的邻居。"
        "这说明现有化学距离不足以组织该尾部目标，不能证明不存在其他可预测化学组合；"
        "当前附件也无法核验储存、包装、批次或品评个体差异。", "",
        "## 其他感官与论坛描述", "",
        "其他实测感官仅用于解释。所有50项值与239款非Pils中的stale相关均保存，"
        "它们不会作为源样本的chemical-only预测输入。论坛7.csv是数值描述符表，未提供原文、"
        "评论人数、时间或逐批次对应信息；字段数值不能解释为词出现次数。", "",
        f"8.xlsx明确stale_hops与barnyard均为numeric，不能把它们当作categorical父类继承值。"
        f"两者在239款非Pils中的Spearman相关为{summary['nonpils_stale_barnyard_spearman']:.4f}；"
        "这是很强的共同变化，但没有原始品评记录来区分共享感官因素或数据加工来源，不能据此判错。", "",
        "numeric说明数据类型，不代表恢复了0–6原始评分；本诊断始终保留4.csv供应的标准化表示。", "",
        "|论坛字段|81供应数值|250款百分位|", "|---|---:|---:|"])
    for row in terms.loc[terms.term.isin(["aroma_stale", "taste_stale", "taste_cardboard", "taste_papery", "aroma_papery"])].itertuples():
        lines.append(f"|{row.term}|{row.beer81_value:.4f}|{row.all_percentile:
```

```
.1%}|")
    lines.extend(["", "这些陈旧、纸板、纸张相关描述构成另一供应数据通道的相符证据，支持谨慎保留高stale标签；"
        "但其采样是否与品评完全独立、是否对应同一批次均不明，不能称为独立真值认证。", "",
        "论坛barnyard描述并不高，两个通道并非所有感官属性逐项相符；完整186项记录均已保存，"
        "没有仅保留支持高stale解释的字段。", "",
        "## 误差影响与可采取的解释", "",
        "|保存阶段|模型|全11源RMSE|81预测|81平方误差占比|", "|---|---|---:|---:|---:|"])
    preferred = influence.loc[(influence.stage.eq("original_frozen_proxy")) |
        (influence.stage.eq("domain_same_seed_comparison") & influence.method.isin(
            [summary["selected_domain_model"], "old_multioutput_tree", "fixed_single_tree", "mean_global"]))]
    for row in preferred.itertuples():
        lines.append(f"|{row.stage}|{row.method}|{row.full_rmse:.4f}|{row.beer81_prediction:.4f}|{row.beer81_sse_share:.1%}|")
    lines.extend(["", "leave_one_source_out_influence.csv只从已保存预测中临时去掉一个源计算影响，"
        "没有重训，也不构成新的交叉验证；任何去掉81后的误差都不能替代全11源主指标。", "",
        "目前可确认的是尾部样本稀缺、化学近邻与高stale错位，以及已有模型的强回归均值倾向。"
        "不能确认是测量、储存、批次、未观测成分、感官个体差异或标签问题所致。"
        "后续仅可在非Pils训练内验证尾部权重、共享感官表示及其他化学模型；论坛描述和81标签不得进入选型。", "",
        "```bash", ".venv/bin/python solution_a/src/21_q3_beer81_audit.py", "```", ""])
    (SOLUTION / "docs/q3_beer81_audit.md").write_text("\n".join(lines), encoding="utf-8", newline="\n")


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/22_q3_stale_refined.py

SHA-256: d9a9f67965d6270217dfb145ebbfd429c4928f349085cd266bb7b47aa19236ef

```
"""Grouped selection, auxiliary supervision and stability-first stale proxy."""
from __future__ import annotations

import json
import platform
import warnings
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
import sklearn
from scipy.spatial.distance import cdist
from scipy.stats import ConstantInputWarning
from sklearn.model_selection import GroupKFold, LeaveOneGroupOut
from threadpoolctl import threadpool_limits

from common import SOLUTION, data_dir
from q3_data import load_q3_data
from q3_stale_optimized import scores as previous_scores
from q3_stale_refined import (
    AUDIT_BOOTSTRAP_SEED, BIAS_PENALTY, FINAL_SEED, FixedChemicalTransform,
    NESTED_SEED, RefinedStaleModel, SELECTION_BOOTSTRAP_SEED,
    STABILITY_DRAWS, STABILITY_SEED, TARGET, VARIANCE_RATIO_MIN, refined_specs,
)

OUT = SOLUTION / "outputs" / "q3_refined" / "stale"


def write_json(path, value):
    path.write_text(json.dumps(value, ensure_ascii=False, indent=2, allow_nan=False), encoding="utf-8", newline="\n")


def scores(y, pred):
    with warnings.catch_warnings():
        warnings.simplefilter("ignore", ConstantInputWarning)
        result = previous_scores(y, pred)
    if result["spearman"] is not None and not np.isfinite(result["spearman"]):
        result["spearman"] = None
    return result


def model(spec, context, seed):
    return RefinedStaleModel(context["features"], context["calibrated"],
                             context["aging"], context["target_names"], spec, seed)


def uses_auxiliary(spec):
    return spec["family"] in ("aux", "aux_kernel") or (
        spec["family"] == "ensemble" and any(uses_auxiliary(member) for member in spec["members"]))


def save_candidate_models(fitted_candidates, specs, context, final_table,
                          decision, stability, train, source):
```

```
    """Keep every selectable candidate, including failed development paths."""
    destination = OUT/"candidate_models"
    destination.mkdir(parents=True, exist_ok=True)
    table = final_table.set_index("method")
    stability_table = stability.set_index("method")
    manifest_rows = []
    for spec in specs:
        if not spec["selectable"]:
            continue
        name = spec["name"]
        row = table.loc[name]
        candidate_stability = stability_table.loc[name].to_dict() if name in s
tability_table.index else None
        internal_qualification = None if candidate_stability is None else bool
(
            row.eligible_for_one_se and candidate_stability["pair_delta_signal
_rms"] > 1e-4
            and candidate_stability["response_noise_ratio"] <= 1)
        selected = name == decision["selected_method"]
        auxiliary = uses_auxiliary(spec)
        artifact = {"pipeline": fitted_candidates[name], "features": context["
features"],
            "target": TARGET, "target_scale": "attachment_4_standardized", "co
nfig": spec,
            "selected_config": spec, "train_global_indices": train, "excluded_
global_indices": source,
            "excluded_style": "Pils/Lager", "not_selected": not selected,
            "selection_status": "selected_reference_copy" if selected else "no
t_selected",
            "development_diagnostic_only": True, "selected_in_frozen_protocol"
: selected,
            "eligible_for_one_se": bool(row.eligible_for_one_se), "within_one_
se": bool(row.within_one_se),
            "loso_metrics": row.to_dict(), "candidate_stability": candidate_st
ability,
            "candidate_internal_qualification": internal_qualification,
            "qualified_for_proxy": bool(selected and decision["qualified_for_p
roxy"]),
            "qualification_scope": "candidate archive; unselected artifacts ar
e development diagnostics, not deployment models",
            "uses_auxiliary_supervision": auxiliary,
            "training_auxiliary_targets": [name for name in context["target_na
mes"] if name != TARGET] if auxiliary else [],
            "pils_status": "repeatedly viewed development diagnostic", "pils_u
sed_for_selection": False,
            "final_seed": FINAL_SEED}
        joblib.dump(artifact, destination/f"{name}.joblib", compress=3)
        manifest_rows.append({"method": name, "file": f"candidate_models/{name
}.joblib",
            "selected_in_frozen_protocol": selected, "eligible_for_one_se": bo
ol(row.eligible_for_one_se),
            "within_one_se": bool(row.within_one_se), "development_diagnostic_
only": True,
            "macro_style_rmse": float(row.macro_style_rmse), "pooled_rmse": fl
oat(row.rmse)})
    pd.DataFrame(manifest_rows).to_csv(OUT/"candidate_model_manifest.csv", ind
ex=False, lineterminator="\n")


def evaluate_loso(indices, specs, context, seed, scope):
    meta, x, y45 = context["meta"], context["x"], context["y45"]
    groups = meta.iloc[indices].tasting_category_fine.to_numpy()
```

```
    truth = y45.iloc[indices][TARGET].to_numpy()
    predictions = {spec["name"]: np.full(len(indices), np.nan) for spec in spe
cs}
    folds, thresholds = np.zeros(len(indices), dtype=int), np.full(len(indices
), np.nan)
    style_rows, audit_rows = [], []
    for fold, (tr, te) in enumerate(LeaveOneGroupOut().split(indices, truth, g
roups), 1):
        train_global, test_global = indices[tr], indices[te]
        style = str(groups[te[0]])
        assert not meta.iloc[train_global].tasting_category_fine.eq(style).any
()
        assert not meta.iloc[train_global].tasting_category_fine.eq("Pils/Lage
r").any()
        for spec in specs:
            if spec["family"] == "ensemble":
                values = np.mean([predictions[member["name"]][te] for member i
n spec["members"]], axis=0)
            else:
                fitted = model(spec, context, seed+fold).fit(x.iloc[train_glob
al], y45.iloc[train_global],
                    meta.iloc[train_global].tasting_category_fine)
                values = fitted.predict(x.iloc[test_global])
            predictions[spec["name"]][te] = values
            style_rows.append({"scope": scope, "method": spec["name"], "heldou
t_style": style,
                               "fold": fold, "n": len(te), **scores(truth[te],
 values),
                               "bias": float(np.mean(values-truth[te]))})
        folds[te] = fold
        thresholds[te] = np.quantile(y45.iloc[train_global][TARGET], .9)
        audit_rows.extend({"scope": scope, "fold": fold, "heldout_style": styl
e,
                           "role": role, "global_index": int(index)}
                          for role, sample in [("train", train_global), ("test
", test_global)] for index in sample)
    per_style = pd.DataFrame(style_rows)
    summaries, long_rows = [], []
    tail = truth >= thresholds
    for spec in specs:
        pred = predictions[spec["name"]]
        assert np.isfinite(pred).all()
        subset = per_style[per_style.method.eq(spec["name"])]
        losses = subset.rmse.to_numpy()+BIAS_PENALTY*subset.bias.abs().to_nump
y()
        metric = scores(truth, pred)
        summaries.append({"scope": scope, "method": spec["name"], "selectable"
: spec["selectable"],
            "priority": spec["priority"], "styles": len(subset),
            "macro_style_rmse": float(subset.rmse.mean()),
            "macro_style_abs_bias": float(subset.bias.abs().mean()),
            "selection_score": float(losses.mean()),
            "style_score_se": float(losses.std(ddof=1)/np.sqrt(len(losses))),
            "tail_n": int(tail.sum()), "tail_rmse": float(np.sqrt(np.mean((pre
d[tail]-truth[tail])**2))),
            **metric})
        long_rows.append(pd.concat([meta.iloc[indices].reset_index(drop=True),
 pd.DataFrame({
            "global_index": indices, "scope": scope, "method": spec["name"], "
observed": truth,
            "prediction": pred, "heldout_style": groups, "fold": folds,
            "tail_threshold_training_q90": thresholds, "is_tail_eval": tail})]
```

```
, axis=1))
    return pd.DataFrame(summaries), per_style, pd.concat(long_rows, ignore_index=True), pd.DataFrame(audit_rows)


def feature_pairs(indices, context):
    transform = FixedChemicalTransform(context["features"], context["calibrated"], context["aging"]).fit(context["x"].iloc[indices])
    z = transform.transform(context["x"].iloc[indices])
    distances = cdist(z, z)
    np.fill_diagonal(distances, np.inf)
    # Third-nearest distinct training row; the fixed rule never sees target y.
    nearest_local = np.argsort(distances, axis=1)[:, 2]
    return indices[nearest_local]


def stability_compare(indices, candidates, context, seed, scope):
    pairs = feature_pairs(indices, context)
    records, pair_rows = [], []
    for spec in candidates:
        delta = []
        for b in range(STABILITY_DRAWS):
            index = np.random.default_rng(seed+b).choice(indices, size=len(indices), replace=True)
            fitted = model(spec, context, seed+10000+b).fit(context["x"].iloc[index], context["y45"].iloc[index],
                context["meta"].iloc[index].tasting_category_fine)
            delta.append(fitted.predict(context["x"].iloc[indices])-fitted.predict(context["x"].iloc[pairs]))
        delta = np.asarray(delta)
        noise = float(np.sqrt(np.mean(np.var(delta, axis=0, ddof=1))))
        signal = float(np.sqrt(np.mean(delta.mean(axis=0)**2)))
        ratio = noise/max(signal, 1e-8)
        records.append({"scope": scope, "method": spec["name"], "stability_draws": STABILITY_DRAWS,
                        "pair_delta_noise_rms": noise, "pair_delta_signal_rms": signal,
                        "response_noise_ratio": ratio, "priority": spec["priority"]})
    pair_rows = [{"scope": scope, "global_index": int(index), "paired_global_index": int(pair)}
                 for index, pair in zip(indices, pairs)]
    return pd.DataFrame(records), pd.DataFrame(pair_rows)


def select_stable(indices, summary, specs, context, seed, scope):
    table = summary.copy()
    mean = table[table.method.eq("mean_global")].iloc[0]
    eligible = table.selectable & (table.prediction_variance_ratio >= VARIANCE_RATIO_MIN)
    eligible &= (table.macro_style_rmse < mean.macro_style_rmse) & (table.rmse < mean.rmse)
    table["eligible_for_one_se"] = eligible
    candidates = table[eligible]
    fallback = candidates.empty
    if fallback:
        best = table[table.selectable].sort_values(["selection_score", "method"]).iloc[0]
        one_se = table[table.method.eq(best.method)]
    else:
        best = candidates.sort_values(["selection_score", "method"]).iloc[0]
        one_se = candidates[candidates.selection_score <= best.selection_score
```

```
+best.style_score_se]
    table["within_one_se"] = table.method.isin(one_se.method)
    spec_map = {spec["name"]: spec for spec in specs}
    stability, pairs = stability_compare(indices, [spec_map[name] for name in
one_se.method], context, seed, scope)
    chosen = stability.sort_values(["response_noise_ratio", "priority", "metho
d"]).iloc[0]
    selected_method = str(chosen.method)
    chosen_metrics = table[table.method.eq(selected_method)].iloc[0]
    qualified = bool(not fallback and chosen.pair_delta_signal_rms > 1e-4 and
chosen.response_noise_ratio <= 1.0)
    decision = {"selected_method": selected_method, "config": spec_map[selecte
d_method],
        "qualified_for_proxy": qualified, "eligibility_fallback": bool(fallbac
k),
        "lowest_score_method": str(best.method), "lowest_selection_score": flo
at(best.selection_score),
        "one_se_width": float(best.style_score_se),
        "one_se_threshold": float(best.selection_score+best.style_score_se),
        "selected_loso_metrics": chosen_metrics.to_dict(), "selected_stability
": chosen.to_dict(),
        "qualification_scope": "training-only grouped selection and response s
tability; not Pils or causal validation"}
    return decision, table, stability, pairs


def main():
    started = perf_counter()
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y45, manifest = load_q3_data()
    features = x.columns.tolist()
    calibrated = manifest.loc[manifest.representation.eq("calibrated"), "featu
re"].tolist()
    source = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    thresholds = pd.read_excel(data_dir()/"8.xlsx", sheet_name="Sensory thresh
olds")
    aging_set = set(thresholds.loc[thresholds.aging.notna(), "field_name_R"])
    aging = [feature for feature in features if feature in aging_set]
    context = {"meta": meta, "x": x, "y45": y45, "features": features,
               "calibrated": calibrated, "aging": aging, "target_names": y45.c
olumns.tolist()}
    specs = refined_specs()
    write_json(OUT/"run_manifest.json", {
        "candidate_specs": specs, "features": features, "aging_features": agin
g,
        "training_indices": train.tolist(), "excluded_indices": source.tolist(
),
        "auxiliary_target_names": [name for name in y45 if name != TARGET],
        "auxiliary_representation": "weighted Ridge alpha100 to 44 standardize
d auxiliary outcomes; right singular directions rank4/8; stale excluded",
        "fixed_missing_representation": "always append all selected missing fl
ags at weight0.2; never variance-scale flags",
        "tail_training_weight": "multiply top20% training-only stale outcomes
by2, then normalize mean weight1",
        "score": "macro(style RMSE)+0.25*macro(abs(style mean error))",
        "one_se_eligibility": "selectable and OOF variance ratio>=0.05 and mac
ro/pooled RMSE<global mean baseline",
        "one_se_rule": "score<=best score+SE across held-out styles; choose lo
west response-noise/signal ratio from8 common row bootstraps; complexity prior
ity breaks exact ties",
        "qualification": "eligibility and response signal RMS>1e-4 and respons
```

```
e noise/signal<=1",
        "chemical_pair_rule": "third-nearest distinct non-Pils training row in
 fixed aging transform",
        "final_validation": "complete non-Pils21 LOSO", "nested_validation": "
4 outer shuffled GroupKFold; complete inner LOSO; selector stability computed
on outer training only",
        "stability_seed": STABILITY_SEED, "stability_draws": STABILITY_DRAWS,
        "nested_seed": NESTED_SEED, "final_seed": FINAL_SEED,
        "selection_bootstrap_seed": SELECTION_BOOTSTRAP_SEED, "audit_bootstrap
_seed": AUDIT_BOOTSTRAP_SEED,
        "pils_labels_used_for_selection_or_intercept": False,
        "pils_status": "repeatedly viewed development diagnostic, not a new te
st",
        "all_candidates_retained": True, "no_beer81_exclusion": True,
    })
    # The full grouped candidate comparison is fixed before reading Pils error
s.
    full, by_style, pred, audit = evaluate_loso(train, specs, context, FINAL_S
EED, "full_loso")
    full.to_csv(OUT/"loso_metrics_overall_raw.csv", index=False, lineterminato
r="\n")
    by_style.to_csv(OUT/"loso_metrics_by_style.csv", index=False, lineterminat
or="\n")
    pred.to_csv(OUT/"loso_predictions.csv", index=False, lineterminator="\n")
    audit.to_csv(OUT/"loso_split_audit.csv", index=False, lineterminator="\n")
    decision, final_table, stability, pairs = select_stable(train, full, specs
, context, STABILITY_SEED, "full_loso")
    final_table.to_csv(OUT/"loso_metrics_overall.csv", index=False, linetermin
ator="\n")
    stability.to_csv(OUT/"selection_stability.csv", index=False, lineterminato
r="\n")
    pairs.to_csv(OUT/"selection_chemical_pairs.csv", index=False, lineterminat
or="\n")
    write_json(OUT/"selection_result.json", decision)
    print("Refined full LOSO selected:", decision["selected_method"], "qualifi
ed", decision["qualified_for_proxy"], flush=True)

    # Evaluate the entire predeclared selector in an additional grouped layer.
    outer_rows, nested_choices, nested_inner_rows, nested_stability_rows = [],
 [], [], []
    nested_inner_audits, nested_outer_audits = [], []
    selector_specs = [spec for spec in specs if spec["family"] not in ("old_tr
ee", "single_tree")]
    groups = meta.iloc[train].tasting_category_fine.to_numpy()
    for fold, (tr, te) in enumerate(GroupKFold(4, shuffle=True, random_state=N
ESTED_SEED).split(train, groups=groups), 1):
        tr_global, te_global = train[tr], train[te]
        summary, _, _, inner_audit = evaluate_loso(tr_global, selector_specs,
context, NESTED_SEED+fold*1000, f"nested_{fold}")
        inner_audit["outer_fold"] = fold
        nested_inner_audits.append(inner_audit)
        nested_outer_audits.extend({"outer_fold":fold,"role":role,"global_inde
x":int(index),
            "style":str(meta.iloc[index].tasting_category_fine)}
            for role,sample in [("train",tr_global),("test",te_global)] for in
dex in sample)
        selected, inner_table, stab, _ = select_stable(tr_global, summary, sel
ector_specs, context,
                                                       STABILITY_SEED+fold*1000,
 f"nested_{fold}")
        inner_table["outer_fold"] = fold
        stab["outer_fold"] = fold
```

```
        nested_inner_rows.append(inner_table)
        nested_stability_rows.append(stab)
        nested_choices.append({"outer_fold": fold, "selected_method": selected["selected_method"],
                               "qualified_for_proxy": selected["qualified_for_proxy"],
                               "heldout_styles": ";".join(sorted(meta.iloc[te_global].tasting_category_fine.unique())),
                               "train_n": len(tr_global), "test_n": len(te_global)})
        for method_name in ("nested_stability_rule", "mean_global", "old_multioutput_tree", "fixed_single_tree"):
            spec = selected["config"] if method_name == "nested_stability_rule" else next(spec for spec in specs if spec["name"] == method_name)
            fitted = model(spec, context, NESTED_SEED+fold).fit(x.iloc[tr_global], y45.iloc[tr_global], meta.iloc[tr_global].tasting_category_fine)
            values = fitted.predict(x.iloc[te_global])
            outer_rows.append(pd.concat([meta.iloc[te_global].reset_index(drop=True), pd.DataFrame({
                "global_index": te_global, "outer_fold": fold, "method": method_name,
                "observed": y45.iloc[te_global][TARGET].to_numpy(), "prediction": values,
                "selected_method": selected["selected_method"] if method_name == "nested_stability_rule" else method_name,
                "tail_threshold_training_q90": np.quantile(y45.iloc[tr_global][TARGET], .9)})], axis=1))
        print(f"Refined nested group fold {fold}/4: {selected['selected_method']}", flush=True)
    nested = pd.concat(outer_rows, ignore_index=True)
    nested.to_csv(OUT/"nested_predictions.csv", index=False, lineterminator="\n")
    pd.DataFrame(nested_choices).to_csv(OUT/"nested_choices.csv", index=False, lineterminator="\n")
    pd.concat(nested_inner_rows, ignore_index=True).to_csv(OUT/"nested_inner_metrics.csv", index=False, lineterminator="\n")
    pd.concat(nested_stability_rows, ignore_index=True).to_csv(OUT/"nested_selection_stability.csv", index=False, lineterminator="\n")
    pd.concat(nested_inner_audits, ignore_index=True).to_csv(OUT/"nested_inner_split_audit.csv", index=False, lineterminator="\n")
    pd.DataFrame(nested_outer_audits).to_csv(OUT/"nested_outer_split_audit.csv", index=False, lineterminator="\n")
    nested_metrics, nested_style_rows = [], []
    for name, group in nested.groupby("method"):
        style_metrics = []
        for style, z in group.groupby("tasting_category_fine"):
            value = {"method": name, "heldout_style": style, "n": len(z), **scores(z.observed, z.prediction)}
            nested_style_rows.append(value)
            style_metrics.append(value)
        tail = group.observed >= group.tail_threshold_training_q90
        nested_metrics.append({"method": name, "macro_style_rmse": float(np.mean([z["rmse"] for z in style_metrics])),
            "macro_style_abs_bias": float(np.mean([abs(z["mean_bias"]) for z in style_metrics])),
            "tail_n": int(tail.sum()), "tail_rmse": float(np.sqrt(np.mean((group.loc[tail,"prediction"]-group.loc[tail,"observed"])**2))),
            **scores(group.observed, group.prediction)})
    pd.DataFrame(nested_metrics).to_csv(OUT/"nested_metrics.csv", index=False, lineterminator="\n")
    pd.DataFrame(nested_style_rows).to_csv(OUT/"nested_metrics_by_style.csv", index=False, lineterminator="\n")
```

```
311
312     selected_spec = decision["config"]
313     selected_metrics = decision["selected_loso_metrics"]
314     selected_uses_auxiliary = uses_auxiliary(selected_spec)
315     metadata = {"features": features, "target": TARGET, "target_scale": "attac
    hment_4_standardized",
316         "config": selected_spec, "selected_config": selected_spec, "selected_m
    ethod": decision["selected_method"],
317         "qualified_for_proxy": decision["qualified_for_proxy"], "qualification
    _scope": decision["qualification_scope"],
318         "inner_oof_variance_ratio": selected_metrics["prediction_variance_rati
    o"],
319         "inner_oof_rmse": selected_metrics["rmse"], "loso_macro_style_rmse": s
    elected_metrics["macro_style_rmse"],
320         "loso_macro_style_abs_bias": selected_metrics["macro_style_abs_bias"],
321         "train_global_indices": train, "excluded_global_indices": source, "exc
    luded_style": "Pils/Lager",
322         "uses_auxiliary_supervision": selected_uses_auxiliary,
323         "training_auxiliary_targets": [name for name in y45 if name != TARGET]
     if selected_uses_auxiliary else [],
324         "candidate_protocol_auxiliary_targets": [name for name in y45 if name
    != TARGET],
325         "prediction_inputs": "chemical features only", "pils_used_for_selectio
    n": False}
326     fitted_candidates = {spec["name"]: model(spec, context, FINAL_SEED).fit(x.
    iloc[train], y45.iloc[train], meta.iloc[train].tasting_category_fine) for spec
     in specs}
327     save_candidate_models(fitted_candidates, specs, context, final_table, deci
    sion, stability, train, source)
328     final = fitted_candidates[decision["selected_method"]]
329     joblib.dump({"pipeline": final, **metadata}, OUT/"transfer_stale_model.job
    lib", compress=3)
330     # Development diagnostics only: every model is already fixed above.
331     diagnostic_rows, diagnostic_metrics = [], []
332     for spec in specs:
333         values = fitted_candidates[spec["name"]].predict(x.iloc[source])
334         diagnostic_rows.append(pd.concat([meta.iloc[source].reset_index(drop=T
    rue), pd.DataFrame({
335             "global_index": source, "method": spec["name"], "observed": y45.il
    oc[source][TARGET].to_numpy(),
336             "prediction": values, "selected_without_pils_labels": spec["name"]
     == decision["selected_method"]})], axis=1))
337         diagnostic_metrics.append({"method": spec["name"], "selected_without_p
    ils_labels": spec["name"] == decision["selected_method"],
338                                    "n": len(source), **scores(y45.iloc[source]
    [TARGET], values)})
339     pd.concat(diagnostic_rows, ignore_index=True).to_csv(OUT/"pils_diagnostic_
    predictions.csv", index=False, lineterminator="\n")
340     pd.DataFrame(diagnostic_metrics).to_csv(OUT/"pils_diagnostic_metrics.csv",
     index=False, lineterminator="\n")
341
342     models, indices, seeds = [], [], []
343     for b in range(60):
344         seed = SELECTION_BOOTSTRAP_SEED+b if b < 40 else AUDIT_BOOTSTRAP_SEED+
    b-40
345         index = np.random.default_rng(seed).choice(train, size=len(train), rep
    lace=True)
346         fitted = model(selected_spec, context, seed+10000).fit(x.iloc[index],
    y45.iloc[index], meta.iloc[index].tasting_category_fine)
347         models.append(fitted)
348         indices.append(index)
349         seeds.append(seed)
```

```
    ensemble = {"models": models, "bootstrap_indices": indices, **metadata,
        "selection_model_indices": list(range(40)), "audit_model_indices": lis
t(range(40,60)),
        "bootstrap_seeds": seeds, "estimator_seeds": [seed+10000 for seed in s
eeds],
        "pairing": "same_model_candidate_minus_source", "paired_quantile": .95
,
        "hyperparameter_uncertainty_included": False,
        "audit_protocol": "40 selection;20 once-only audit;no reselection", "f
ixed_indicator_dimensions": True}
    joblib.dump(ensemble, OUT/"bootstrap_ensemble.joblib", compress=3)
    np.savez_compressed(OUT/"bootstrap_indices.npz", indices=np.asarray(indice
s), bootstrap_seeds=np.asarray(seeds))

    # Same chemical pairs compare stability with the prior local architecture.
    chemical_pairs = feature_pairs(train, context)
    comparisons = []
    for label, committee in [("refined_selected", models), ("domain_local_prev
ious", joblib.load(SOLUTION/"outputs/q3_domain/stale/bootstrap_ensemble.joblib
")["models"])]:
        delta = np.asarray([m.predict(x.iloc[train])-m.predict(x.iloc[chemical
_pairs]) for m in committee])
        noise = float(np.sqrt(np.mean(np.var(delta, axis=0, ddof=1))))
        signal = float(np.sqrt(np.mean(delta.mean(axis=0)**2)))
        comparisons.append({"method": label, "models": len(committee), "pair_d
elta_noise_rms": noise,
                            "pair_delta_signal_rms": signal, "response_noise_r
atio": noise/max(signal,1e-8),
                            "status": "descriptive fixed-pair architecture com
parison; not used for selection"})
    pd.DataFrame(comparisons).to_csv(OUT/"bootstrap_response_comparison.csv",
index=False, lineterminator="\n")
    assert np.asarray(indices).shape == (60,239)
    assert all(not set(index)&set(source) for index in indices)
    assert all(np.isfinite(m.predict(x)).all() for m in models)
    summary = {
        "selected_method": decision["selected_method"], "config": selected_spe
c,
        "qualified_for_proxy": decision["qualified_for_proxy"], "selection_res
ult": decision,
        "training_samples": len(train), "pils_sources": len(source), "loso_sty
les":21,"candidate_count":len(specs),
        "mean_baseline_method":"mean_global","old_multioutput_baseline_method"
:"old_multioutput_tree","old_single_tree_baseline_method":"fixed_single_tree",
        "selected_loso_metrics": selected_metrics, "nested_metrics":nested_met
rics,
        "all_pils_diagnostic_metrics":diagnostic_metrics,
        "selected_pils_diagnostic_metrics":next(row for row in diagnostic_metr
ics if row["method"]==decision["selected_method"]),
        "pils_status":"repeatedly viewed development diagnostic; never used to
 select or correct intercept",
        "bootstrap_response_comparison":comparisons,
        "bootstrap":{"models":60,"selection":40,"audit":20,"source_excluded":T
rue,"configuration_fixed":True},
        "limitations":[
            "Auxiliary sensory values are training outcomes only; neither stal
e nor any measured sensory value is an inference feature.",
            "Every auxiliary fit, fixed indicator transform, tail threshold, s
tyle weight and stability draw excludes its held-out group.",
            "Full LOSO is used to fit the final selection rule; selected score
s are optimistic. Four outer grouped folds assess that fixed rule internally."
,
```

```
            "The same dataset has guided prior exploration; grouped resampling is not new external validation and Pils diagnostics are repeatedly viewed.",
            "Tail weighting uses only training quantiles and never the beer81 outcome, but can increase average bias.",
            "The one-SE rule uses a descriptive across-style SE; observed styles are not independent randomized domains.",
            "Model response stability does not establish accuracy on synthetic interventions or genuine stale-hops taste.",
            "60 bootstrap models fix the chosen configuration and omit algorithm-selection and new-domain uncertainty.",
            "The 20 audit models cannot be used to reselect a proposal; model quantiles are not calibrated confidence limits.",
            "The provided standardized target is retained; no original 0-6 score is inferred."],
        "verification":{"source_exclusion":True,"bootstrap_indices_shape":[60,239],"all_model_predictions_finite":True},
        "versions":{"python":platform.python_version(),"numpy":np.__version__,"pandas":pd.__version__,"sklearn":sklearn.__version__},
        "elapsed_seconds":perf_counter()-started}
    write_json(OUT/"summary.json",summary)
    print(final_table[["method","macro_style_rmse","selection_score","prediction_variance_ratio","within_one_se"]].to_string(index=False),flush=True)
    print("Pils selected development diagnostic:",json.dumps(summary["selected_pils_diagnostic_metrics"],ensure_ascii=False),flush=True)
    print("Bootstrap response:",comparisons,flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

src/23_q3_transfer_balanced.py

SHA-256: 953bf8882498756a1dbcf8675f41144e55967be5d2475f35868fb31efa3a935d

```
"""Candidate contraction and predeclared proximity/committee trade-offs."""
from __future__ import annotations

from importlib import import_module
import json
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from threadpoolctl import threadpool_limits

from common import SOLUTION
from q3_data import load_q3_data, read_defect_thresholds
from q3_stale_optimized import predict_1d, raw_tree_pipeline

CORE = import_module("17_q3_transfer_domain")
OUT = SOLUTION / "outputs/q3_refined/transfer"
PRIOR = SOLUTION / "outputs/q3_domain"
ORIGINAL = SOLUTION / "outputs/q3"
OPTIMIZED = SOLUTION / "outputs/q3_optimized"
REFINED = SOLUTION / "outputs/q3_refined/stale"
POOLS = ("legacy_2004", "legacy_6004", "contracted_6004")
BOUNDS = {"absolute10":(.10,None), "absolute30":(.30,None),
          "absolute50":(.50,None), "absolute60":(.60,None),
          "retain80":(.10,.80), "retain100":(.10,1.0)}
RANKINGS = ("geometry", "margin")
CONTRACTIONS = (.2,.4,.6)
GAMMAS = (.25,.5,.75,1.0)
DEFAULT = {"arm":"refined", "pool":"contracted_6004", "bound":"retain80", "ranking":"margin"}
OLD_AUDIT_SEED = 202104123
FIXED_AUDIT_SEED = 202105123
TOL = 1e-10


def write_json(path, value):
    path.write_text(json.dumps(value,ensure_ascii=False,indent=2,allow_nan=False)+"\n",encoding="utf-8", newline="\n")


def target_draws(reference, legacy):
    base = reference.transform(legacy.iloc[:500])
    center = reference.style_center_["Tripel"]
    latent = np.vstack([center+c*(base-center) for c in CONTRACTIONS])
    return reference.inverse_transform(latent), latent


def candidate_values(source, legacy, contracted, median, caps):
    blocks, rows = [], []
    for family, draws in [("legacy",legacy),("contracted",contracted)]:
        for gamma in GAMMAS:
            blocks.append((1-gamma)*source.to_numpy()[0]+gamma*draws.to_numpy())
            rows.extend({"family":family,"gamma":gamma,"draw":j,
                         "contraction":CONTRACTIONS[j//500] if family=="contracted" else np.nan}
                        for j in range(len(draws)))
```

```
    for gamma in GAMMAS:
        blocks.append(((1-gamma)*source.to_numpy()[0]+gamma*median)[None])
        rows.append({"family":"median","gamma":gamma,"draw":-1,"contraction":np.nan})
    frame = pd.DataFrame(np.vstack(blocks),columns=source.columns)
    for field,cap in caps.items():
        frame[field] = frame[field].clip(lower=0,upper=cap)
    return frame,pd.DataFrame(rows)


def pool_masks(descriptions):
    median = descriptions.family.eq("median").to_numpy()
    legacy = descriptions.family.eq("legacy").to_numpy()
    return {"legacy_2004":median|(legacy&descriptions.draw.lt(500).to_numpy()),
            "legacy_6004":median|legacy,
            "contracted_6004":median|descriptions.family.eq("contracted").to_numpy()}


def fresh_trees(x, y, train, seed):
    models, indices = [], []
    for b in range(20):
        current = seed+b
        index = np.random.default_rng(current).choice(train,len(train),replace=True)
        models.append(raw_tree_pipeline(current+10000,n_estimators=120).fit(x.iloc[index],y.iloc[index]))
        indices.append(index)
    return {"models":models,"bootstrap_indices":indices,"bootstrap_seeds":list(range(seed,seed+20)),
            "train_global_indices":train,"features":x.columns.tolist(),
            "protocol":"single-target ExtraTrees 120/minleaf3/max_features.7"}


def counts(part):
    selected = part.candidate_index.notna()
    passing = part.fresh_consistency_passed
    return {"sources":len(part),"selected":int(selected.sum()),"new_passed":int(part.new_model_passed.sum()),
        "fresh_consistency_passed":int(passing.sum()),"historical_consistency_passed":int(part.historical_consistency_passed.sum()),
        "no_candidate":int((~selected).sum()),
        "median_improvement_selected":float(part.loc[selected,"target_improvement"].median()) if selected.any() else None,
        "median_improvement_passed":float(part.loc[passing,"target_improvement"].median()) if passing.any() else None,
        "median_retention_selected":float(part.loc[selected,"retained_anchor_gain"].median()) if selected.any() else None,
        "median_change_rms_selected":float(part.loc[selected,"change_latent_rms"].median()) if selected.any() else None}


def main():
    started = perf_counter()
    OUT.mkdir(parents=True,exist_ok=True)
    meta,x,y45,_ = load_q3_data()
    y = y45.stale_hops
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    sources = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    target = np.flatnonzero(meta.tasting_category_fine.eq("Tripel"))
    features = x.columns.tolist()
```

```
    defects = read_defect_thresholds()
    scenarios = json.loads((OPTIMIZED/"transfer/threshold_scenarios.json").rea
d_text(encoding="utf-8"))
    manifest = {"default":DEFAULT,"pools":dict(zip(POOLS,(2004,6004,6004))),
        "bounds":{key:{"absolute_minimum":value[0],"anchor_fraction":value[1]}
 for key,value in BOUNDS.items()},
        "rankings":RANKINGS,"contractions":CONTRACTIONS,"gammas":GAMMAS,
        "contracted_latents":"transform frozen legacy first500 chemical rows,
then mu+c*(z-mu); empirical inverse CDF",
        "anchor":"frozen q3_optimized default spectrum per source; same origin
al geometry",
        "retention_floor":"max(.10, anchor_fraction*anchor_gain)",
        "screens":"new40 and original30 paired Q95<=0; both current centers de
lta<=0; nonzero paired signals",
        "fresh_audit":"new20 and new-seed original single-target120tree20; no
reselection",
        "historical_audit":"original last10 reused diagnostic only, excluded f
rom primary fresh gate",
        "old_audit_seed":OLD_AUDIT_SEED,"fixed_audit_seed":FIXED_AUDIT_SEED,
        "threshold_scenarios":scenarios,"minimum_change_rms":.05,"geometry_lam
bda":.2,
        "default_chosen_from_audit":False,"audit_reselection":False,
        "interpretation":"finite empirical trade-off grid; not a global Pareto
 optimum or tasting validation"}
    write_json(OUT/"run_manifest.json",manifest)
    geometry = joblib.load(ORIGINAL/"transfer/transfer_copula.joblib")
    np.testing.assert_array_equal(geometry["training_rows"],train)
    reference = geometry["copula"]
    legacy = pd.read_csv(PRIOR/"consensus/base_draws.csv")
    contracted,contracted_latents = target_draws(reference,legacy)
    legacy.to_csv(OUT/"legacy_base_draws.csv",index=False, lineterminator="\n"
)
    contracted.to_csv(OUT/"contracted_base_draws.csv",index=False, linetermina
tor="\n")
    np.save(OUT/"contracted_latents.npy",contracted_latents)
    pd.DataFrame({"draw":np.arange(1500),"base_draw":np.tile(np.arange(500),3)
,
        "contraction":np.repeat(CONTRACTIONS,500)}).to_csv(OUT/"contracted_dra
w_metadata.csv",index=False, lineterminator="\n")
    tz = reference.transform(x.iloc[target])
    dim = x.shape[1]
    pairwise = cdist(tz,tz)/np.sqrt(dim)
    np.fill_diagonal(pairwise,np.inf)
    support_limit = float(np.quantile(pairwise.min(axis=1),.95))
    center = tz.mean(axis=0)
    medians = x.iloc[train].median()
    minimum,maximum = x.iloc[train].min().to_numpy(),x.iloc[train].max().to_nu
mpy()
    target_median = x.iloc[target].median().to_numpy()
    old = joblib.load(ORIGINAL/"sensory/stale_bootstrap.joblib")
    old_center = joblib.load(ORIGINAL/"sensory/transfer_proxy.joblib")
    refined_center = joblib.load(REFINED/"transfer_stale_model.joblib")
    refined_ensemble = joblib.load(REFINED/"bootstrap_ensemble.joblib")
    fixed_center = joblib.load(OPTIMIZED/"stale_fixed/transfer_stale_model.job
lib")
    fixed_ensemble = joblib.load(OPTIMIZED/"stale_fixed/bootstrap_ensemble.job
lib")
    old_audit = fresh_trees(x,y,train,OLD_AUDIT_SEED)
    fixed_audit = fresh_trees(x,y,train,FIXED_AUDIT_SEED)
    old_audit["excluded_global_indices"] = sources
    fixed_audit["excluded_global_indices"] = sources
    joblib.dump(old_audit,OUT/"fresh_original_audit.joblib",compress=3)
```

```
    joblib.dump(fixed_audit,OUT/"fresh_fixed_audit.joblib",compress=3)
    arms = {"refined":{"center":refined_center,"selection":refined_ensemble["models"][:40],
                       "audit":refined_ensemble["models"][40:]},
            "fixed":{"center":fixed_center,"selection":fixed_ensemble["models"][:40],"audit":fixed_audit["models"]}}
    for artifact in [old,old_center,refined_center,refined_ensemble,fixed_center,fixed_ensemble]:
        np.testing.assert_array_equal(artifact["train_global_indices"],train)
        assert artifact["features"]==features
    assert len(refined_ensemble["models"])==60
    anchor_summary = pd.read_csv(OPTIMIZED/"transfer/transfer_summary.csv")
    anchor_summary = anchor_summary[anchor_summary.is_default_policy].set_index("source_beer")
    anchor_spectra = pd.read_csv(OPTIMIZED/"transfer/transferred_spectra.csv").set_index("transfer_id")
    prior_summary = pd.read_csv(PRIOR/"consensus/transfer_summary.csv")
    prior_spectra = pd.read_csv(PRIOR/"consensus/transferred_spectra.csv").set_index("transfer_id")
    records,diags,geometry_rows,selected_rows,delta_rows,threshold_rows,rechecks,uniqueness = [],[],[],[],[],[],[],[]
    stale_position = y45.columns.get_loc("stale_hops")
    for number,index in enumerate(sources,1):
        beer = int(meta.beer.iloc[index])
        raw = x.iloc[[index]]
        source = raw.fillna(medians)
        assert all(np.isfinite(raw[r["feature"]].iloc[0]) and raw[r["feature"]].iloc[0]>=0 for r in defects.values())
        caps = {}
        for rule in defects.values():
            field = rule["feature"]
            values = [s["thresholds"][field] for s in scenarios if s["thresholds"][field] is not None]
            caps[field] = max(float(raw[field].iloc[0]),min(values)) if values else float(raw[field].iloc[0])
        candidates,descriptions = candidate_values(source,legacy,contracted,target_median,caps)
        masks = pool_masks(descriptions)
        unique,inverse = np.unique(candidates.to_numpy(),axis=0,return_inverse=True)
        unique_frame = pd.DataFrame(unique,columns=features)
        z,sz = reference.transform(candidates),reference.transform(source)
        distance = reference.distance(candidates,"Tripel")
        before = float(reference.distance(source,"Tripel")[0])
        improvement = 1-distance/max(before,1e-8)
        change = np.linalg.norm(z-sz,axis=1)/np.sqrt(dim)
        nn = cdist(z,tz).min(axis=1)/np.sqrt(dim)
        support = (nn<=support_limit+TOL)&((candidates.to_numpy()>=minimum-TOL)&(candidates.to_numpy()<=maximum+TOL)).all(axis=1)
        chemical = np.column_stack([CORE.chemical_ok(candidates,raw,s) for s in scenarios]).all(axis=1)
        geometric = support&chemical&(change>=.05)
        scale = max(float(np.linalg.norm(sz[0]-center)/np.sqrt(dim)),1e-8)
        objective = distance/max(before,1e-8)+.2*change/scale
        anchor_row = anchor_summary.loc[beer]
        anchor_frame = anchor_spectra.loc[[anchor_row.transfer_id],features]
        anchor_gain = 1-float(reference.distance(anchor_frame,"Tripel")[0])/max(before,1e-8)
        assert anchor_gain>0
        geometry_rows.append(pd.concat([pd.DataFrame({"source_beer":beer,"candidate_index":np.arange(len(candidates)),
            "target_distance":distance,"target_improvement":improvement,"chang
```

```
e_latent_rms":change,"target_nn_rms":nn,
198             "support_ok":support,"chemical_ok":chemical,"geometry_objective":o
bjective}),descriptions],axis=1))
199         for pool,mask in masks.items():
200             unique_n = len(np.unique(candidates.to_numpy()[mask],axis=0))
201             uniqueness.append({"source_beer":beer,"pool":pool,"nominal_candida
tes":int(mask.sum()),"unique_candidates":unique_n,
202                 "duplicate_fraction":1-unique_n/int(mask.sum()),"anchor_gain":
anchor_gain})
203         old_delta = CORE.paired(old["models"][:30],unique_frame,source)[invers
e]
204         old_q = np.quantile(old_delta,.95,axis=1)
205         old_signal = np.any(np.abs(old_delta)>1e-8,axis=1)
206         center_old_source = float(old_center["pipeline"].predict(source)[0,sta
le_position])
207         center_old_delta = old_center["pipeline"].predict(unique_frame)[:,stal
e_position][inverse]-center_old_source
208         for arm,models in arms.items():
209             current = models["center"]
210             qualified = bool(current["qualified_for_proxy"])
211             new_delta = CORE.paired(models["selection"],unique_frame,source)[i
nverse]
212             new_q = np.quantile(new_delta,.95,axis=1)
213             new_signal = np.any(np.abs(new_delta)>1e-8,axis=1)
214             center_new_source = float(predict_1d(current["pipeline"],source)[0
])
215             center_new_delta = predict_1d(current["pipeline"],unique_frame)[in
verse]-center_new_source
216             worst = np.maximum(new_q,old_q)
217             center_ok = (center_new_delta<=TOL)&(center_old_delta<=TOL)
218             joint = geometric&(new_q<=TOL)&(old_q<=TOL)&new_signal&old_signal&
center_ok
219             diags.append(pd.DataFrame({"source_beer":beer,"arm":arm,"candidate
_index":np.arange(len(candidates)),
220                 "new_selection_q95":new_q,"old_selection_q95":old_q,"worst_sel
ection_q95":worst,
221                 "center_new_delta":center_new_delta,"center_old_delta":center_
old_delta,
222                 "new_signal":new_signal,"old_signal":old_signal,"joint_feasibl
e":joint}))
223             cache = {}
224             def assess(frame):
225                 key=frame.to_numpy().tobytes()
226                 if key not in cache:
227                     cache[key]={"new_audit":CORE.paired(models["audit"],frame,
source)[0],
228                         "old_fresh_audit":CORE.paired(old_audit["models"],fram
e,source)[0],
229                         "old_historical":CORE.paired(old["models"][30:],frame,
source)[0]}
230                 return cache[key]
231             for pool,mask in masks.items():
232                 new_variation=float(np.std(new_delta[mask].mean(axis=1)))
233                 old_variation=float(np.std(old_delta[mask].mean(axis=1)))
234                 informative=new_variation>1e-6 and old_variation>1e-6
235                 for bound,(absolute,retention) in BOUNDS.items():
236                     floor=max(absolute,retention*anchor_gain) if retention is
not None else absolute
237                     ids=np.flatnonzero(joint&mask&(improvement>=floor))
238                     for ranking in RANKINGS:
239                         uid=f"{arm}_beer{beer}_{pool}_{bound}_{ranking}"
240                         common={"transfer_id":uid,"source_beer":beer,"arm":arm
```

```
,"pool":pool,"bound":bound,"ranking":ranking,
                            "is_default_policy":arm==DEFAULT["arm"] and pool==DEFAULT["pool"] and bound==DEFAULT["bound"] and ranking==DEFAULT["ranking"],
                            "is_arm_default":pool==DEFAULT["pool"] and bound==DEFAULT["bound"] and ranking==DEFAULT["ranking"],
                            "anchor_gain":anchor_gain,"required_gain":floor,"qualified":qualified,"informative":informative,
                            "candidate_count":int(mask.sum()),"feasible_count":len(ids),"new_delta_sd":new_variation,"old_delta_sd":old_variation,
                            "candidate_index":np.nan,"new_model_passed":False,"fresh_consistency_passed":False,"historical_consistency_passed":False}
                        if not len(ids):
                            records.append({**common,"status":"no_candidate"});continue
                        chosen=int(ids[np.lexsort((objective[ids],worst[ids]))[0]]) if ranking=="margin" else int(ids[np.argmin(objective[ids])])
                        frame=candidates.iloc[[chosen]]
                        audited=assess(frame)
                        aq={name:float(np.quantile(delta,.95)) for name,delta in audited.items()}
                        new_pass=bool(qualified and informative and aq["new_audit"]<=TOL)
                        fresh_pass=bool(new_pass and aq["old_fresh_audit"]<=TOL)
                        history_pass=bool(new_pass and aq["old_historical"]<=TOL)
                        status="unqualified" if not qualified else "uninformative" if not informative else "new_audit_failed" if not new_pass else "old_fresh_audit_failed" if not fresh_pass else "passed"
                        records.append({**common,"candidate_index":chosen,"status":status,"target_distance_before":before,
                            "target_distance_after":float(distance[chosen]),"target_improvement":float(improvement[chosen]),
                            "retained_anchor_gain":float(improvement[chosen]/anchor_gain),"change_latent_rms":float(change[chosen]),
                            "target_nn_rms":float(nn[chosen]),"support_nn_limit":support_limit,"geometry_objective":float(objective[chosen]),
                            "new_selection_q95":float(new_q[chosen]),"old_selection_q95":float(old_q[chosen]),"worst_selection_q95":float(worst[chosen]),
                            "center_new_delta":float(center_new_delta[chosen]),"center_old_delta":float(center_old_delta[chosen]),
                            "new_audit_q95":aq["new_audit"],"old_fresh_audit_q95":aq["old_fresh_audit"],"old_historical_q95":aq["old_historical"],
                            "new_model_passed":new_pass,"fresh_consistency_passed":fresh_pass,"historical_consistency_passed":history_pass})
                        selected_rows.append({"transfer_id":uid,**frame.iloc[0].to_dict()})
                        for name,delta in {"new_selection":new_delta[chosen],"old_selection":old_delta[chosen],**audited}.items():
                            delta_rows.extend({"transfer_id":uid,"ensemble":name,"model_index":j,"delta":float(value)} for j,value in enumerate(delta))
                        for scenario in scenarios:
                            for label,rule in defects.items():
                                field=rule["feature"];threshold=scenario["thresholds"][field]
                                source_value=float(raw[field].iloc[0]);after=float(frame[field].iloc[0])
                                cap=max(source_value,threshold) if threshold is not None else source_value
                                threshold_rows.append({"transfer_id":uid,"scenario":scenario["scenario"],"defect":label,"feature":field,
                                    "source":source_value,"transferred":after,
```

```
    "cap":cap,"passed":after<=cap+TOL})
            references=[("original_anchor",anchor_frame)]
            for pool in ("matched_2004","expanded_6004"):
                prior_row=prior_summary[prior_summary.source_beer.eq(beer)&pri
or_summary.pool.eq(pool)&prior_summary.policy.eq("joint_margin")].iloc[0]
                if pd.notna(prior_row.candidate_index):
                    references.append((f"prior_{pool}",prior_spectra.loc[[prio
r_row.transfer_id],features]))
            for label,frame in references:
                pz=reference.transform(frame);gain=1-float(reference.distance(
frame,"Tripel")[0])/max(before,1e-8)
                shift=float(np.linalg.norm(pz-sz)/np.sqrt(dim))
                support_ok=bool(cdist(pz,tz).min()/np.sqrt(dim)<=support_limit
+TOL and
                    ((frame.to_numpy()>=minimum-TOL)&(frame.to_numpy()<=maximu
m+TOL)).all())
                chemical_ok=bool(all(CORE.chemical_ok(frame,raw,s)[0] for s in
 scenarios))
                nd=CORE.paired(models["selection"],frame,source)[0];od=CORE.pa
ired(old["models"][:30],frame,source)[0]
                nq,oq=float(np.quantile(nd,.95)),float(np.quantile(od,.95))
                cdn=float(predict_1d(current["pipeline"],frame)[0]-center_new_
source)
                cdo=float(old_center["pipeline"].predict(frame)[0,stale_positi
on]-center_old_source)
                assessed=assess(frame);aq={key:float(np.quantile(value,.95)) f
or key,value in assessed.items()}
                evaluation_mask=masks[DEFAULT["pool"]]
                base_pass=bool(qualified and np.std(new_delta[evaluation_mask]
.mean(axis=1))>1e-6
                    and np.std(old_delta[evaluation_mask].mean(axis=1))>1e-6
                    and support_ok and chemical_ok and shift>=.05 and nq<=TOL
and oq<=TOL and cdn<=TOL and cdo<=TOL
                    and np.any(np.abs(nd)>1e-8) and np.any(np.abs(od)>1e-8))
                for bound,(absolute,retention) in BOUNDS.items():
                    floor=max(absolute,retention*anchor_gain) if retention is
not None else absolute
                    passed=bool(base_pass and gain>=floor and aq["new_audit"]<
=TOL and aq["old_fresh_audit"]<=TOL)
                    rechecks.append({"source_beer":beer,"arm":arm,"reference":
label,"evaluation_pool":DEFAULT["pool"],"bound":bound,"required_gain":floor,
                        "target_improvement":gain,"retained_anchor_gain":gain/
anchor_gain,"change_latent_rms":shift,
                        "support_ok":support_ok,"chemical_ok":chemical_ok,"new
_selection_q95":nq,"old_selection_q95":oq,
                        "center_new_delta":cdn,"center_old_delta":cdo,"new_aud
it_q95":aq["new_audit"],
                        "old_fresh_audit_q95":aq["old_fresh_audit"],"fresh_con
sistency_passed":passed})
            print(f"Balanced transfer source {number}/11 beer={beer}, arm={arm
}, joint={joint.sum()}",flush=True)
    result=pd.DataFrame(records)
    result.to_csv(OUT/"transfer_summary.csv",index=False, lineterminator="\n")
    pd.concat(geometry_rows,ignore_index=True).to_csv(OUT/"candidate_geometry.
csv.gz",index=False,compression="gzip", lineterminator="\n")
    pd.concat(diags,ignore_index=True).to_csv(OUT/"candidate_model_checks.csv.
gz",index=False,compression="gzip", lineterminator="\n")
    pd.DataFrame(selected_rows).to_csv(OUT/"selected_spectra.csv",index=False,
 lineterminator="\n")
    pd.DataFrame(delta_rows).to_csv(OUT/"paired_deltas.csv",index=False, linet
erminator="\n")
    pd.DataFrame(threshold_rows).to_csv(OUT/"threshold_checks.csv",index=False
```

```
, lineterminator="\n")
    pd.DataFrame(rechecks).to_csv(OUT/"fixed_spectra_rechecks.csv",index=False
, lineterminator="\n")
    pd.DataFrame(uniqueness).to_csv(OUT/"pool_uniqueness.csv",index=False, lin
eterminator="\n")
    frontier=[{"arm":arm,"pool":pool,"bound":bound,"ranking":ranking,**counts(
part)}
        for (arm,pool,bound,ranking),part in result.groupby(["arm","pool","bou
nd","ranking"])]
    pd.DataFrame(frontier).to_csv(OUT/"frontier.csv",index=False, lineterminat
or="\n")
    arm_defaults={arm:counts(result[result.arm.eq(arm)&result.is_arm_default])
 for arm in arms}
    summary={"default":DEFAULT,"default_results":counts(result[result.is_defau
lt_policy]),"arm_defaults":arm_defaults,
        "model_qualified":{arm:bool(models["center"]["qualified_for_proxy"]) f
or arm,models in arms.items()},
        "nominal_candidates_per_source":12004,"sources":len(sources),"training
_n":len(train),"support_limit":support_limit,
        "contracted_targets_unique":len(np.unique(contracted.to_numpy(),axis=0
)),"contracted_targets_nominal":len(contracted),
        "frontier_rows":len(frontier),"policies":len(result),"selected":len(se
lected_rows),"threshold_rows":len(threshold_rows),
        "elapsed_seconds":perf_counter()-started}
    write_json(OUT/"summary.json",summary)
    print(json.dumps(summary,ensure_ascii=False,indent=2),flush=True)


if __name__=="__main__":
    with threadpool_limits(limits=1):main()
```

src/24_q3_refinement_report.py

SHA-256: ddcd0c5097ddbfa230a6544cdc717bfa08eec80d964cb1a59fc4999162c3f87e

```
"""Report beer81 diagnosis, grouped prediction, and finite transfer trade-offs."""
import hashlib
import json

import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd

from common import SOLUTION

OUT=SOLUTION/"outputs/q3_refined"
SOURCES=[]
COLORS={"legacy_2004":"#929AA3","legacy_6004":"#B98632","contracted_6004":"#267DA7"}


def read(path):
    raw=path.read_bytes()
    value=json.loads(raw) if path.suffix==".json" else pd.read_csv(path)
    SOURCES.append({"path":path.relative_to(SOLUTION).as_posix(),"sha256":hashlib.sha256(raw).hexdigest(),
                    "rows":len(value) if isinstance(value,pd.DataFrame) else None})
    return value


def number(value, percent=False):
    return "-" if pd.isna(value) else (f"{value:.1%}" if percent else f"{value:.4f}")


def save(fig,name):
    fig.savefig(OUT/f"figures/{name}.png",dpi=300,bbox_inches="tight")
    fig.savefig(OUT/f"figures/{name}.svg",bbox_inches="tight")
    plt.close(fig)


def main():
    (OUT/"figures").mkdir(parents=True,exist_ok=True)
    (OUT/"report_tables").mkdir(parents=True,exist_ok=True)
    audit=read(OUT/"beer81/summary.json")
    prediction=read(OUT/"stale/summary.json")
    loso=read(OUT/"stale/loso_metrics_overall.csv")
    pils=read(OUT/"stale/pils_diagnostic_metrics.csv")
    pils_rows=read(OUT/"stale/pils_diagnostic_predictions.csv")
    nested=read(OUT/"stale/nested_metrics.csv")
    response=read(OUT/"stale/bootstrap_response_comparison.csv")
    transfer=read(OUT/"transfer/summary.json")
    manifest=read(OUT/"transfer/run_manifest.json")
    frontier=read(OUT/"transfer/frontier.csv")
    outcomes=read(OUT/"transfer/transfer_summary.csv")
    references=read(OUT/"transfer/fixed_spectra_rechecks.csv")
    unique=read(OUT/"transfer/pool_uniqueness.csv")
    comparison=loso.merge(pils[["method","rmse","mean_bias"]].rename(columns={"rmse":"pils_rmse","mean_bias":"pils_bias"}),on="method",validate="one_to_one")
```

```
    comparison.to_csv(OUT/"report_tables/prediction_comparison.csv",index=Fals
e, lineterminator="\n")
    selected=prediction["selected_method"]
    selected_row=comparison.set_index("method").loc[selected]
    tail=comparison.set_index("method").loc["tail_ridge_aging100"]
    tail_r2=float(pils.set_index("method").loc["tail_ridge_aging100","r2"])
    old=comparison.set_index("method").loc["old_multioutput_tree"]
    nested_values=nested.set_index("method")
    selected81=float(pils_rows.loc[pils_rows.method.eq(selected)&pils_rows.bee
r.eq(81),"prediction"].iloc[0])
    tail81=float(pils_rows.loc[pils_rows.method.eq("tail_ridge_aging100")&pils
_rows.beer.eq(81),"prediction"].iloc[0])
    retained=outcomes[outcomes.bound.eq("retain80")]
    retained.to_csv(OUT/"report_tables/retain80_all_policies.csv",index=False,
 lineterminator="\n")
    ref_counts=references.groupby(["arm","reference","bound"],as_index=False).
agg(
        available=("source_beer","size"),passed=("fresh_consistency_passed","s
um"),
        median_gain=("target_improvement","median"))
    ref_counts["sources_denominator"]=11
    ref_counts.to_csv(OUT/"report_tables/reference_counts.csv",index=False, li
neterminator="\n")
    plt.rcParams.update({"font.family":"DejaVu Sans","font.size":10,"axes.spin
es.top":False,"axes.spines.right":False,"svg.fonttype":"none"})
    fig,axes=plt.subplots(1,2,figsize=(12,5.4),gridspec_kw={"width_ratios":[1.
1,1]})
    for row in comparison.itertuples():
        color="#267DA7" if row.method==selected else "#B98632" if row.method==
"tail_ridge_aging100" else "#929AA3"
        axes[0].scatter(row.macro_style_rmse,row.pils_rmse,color=color,s=50)
    for method,label,offset in [(selected,"Selected stable ridge",(10,8)),("ta
il_ridge_aging100","Tail ridge (not eligible)",(-125,12)),("old_multioutput_tr
ee","45-output reference",(8,-12))]:
        row=comparison.set_index("method").loc[method]
        axes[0].annotate(label,(row.macro_style_rmse,row.pils_rmse),xytext=off
set,textcoords="offset points",fontsize=8,
                         arrowprops={"arrowstyle":"-","color":"#68717C","lw":.
6})
    axes[0].set(xlabel="Non-Pils LOSO macro RMSE (selection data)",ylabel="Pil
s RMSE (repeatedly viewed diagnostic)",title="Prediction trade-off; lower is b
etter",xlim=(.36,.422),ylim=(.509,.567))
    beer=pils_rows[pils_rows.beer.eq(81)].set_index("method")
    methods=["old_multioutput_tree",selected,"tail_ridge_aging100","aux4_tail_
ridge10"]
    values=beer.loc[methods,"prediction"].to_numpy()
    axes[1].barh(np.arange(4),values,color=["#929AA3","#267DA7","#B98632","#C5
AC79"])
    axes[1].set_yticks(np.arange(4),["45-output reference","Selected stable ri
dge","Tail ridge (not selected)","Auxiliary tail (not selected)"],fontsize=8)
    axes[1].axvline(audit["stale_observed"],color="#333D46",label="Observed be
er81",linestyle="--")
    axes[1].axvline(audit["frozen_local_top25_stale_max"],color="#929AA3",labe
l="Previous top25 maximum",linestyle=":")
    axes[1].set(xlabel="Standardized stale_hops",title="Beer81 underprediction
",xlim=(-.3,1.85))
    axes[1].legend(frameon=False,fontsize=8,loc="lower right")
    for ax in axes:ax.grid(alpha=.2);ax.set_axisbelow(True)
    fig.subplots_adjust(wspace=.75,bottom=.2)
    fig.text(.1,.025,"Pils labels did not select the main model. The tail conf
iguration improves this diagnostic point estimate\nbut fails training-only eli
gibility; no candidate is promoted using this diagnostic.",fontsize=9,color="#
```

```
5C6470")
    save(fig,"beer81_and_prediction")
    fig,axes=plt.subplots(1,2,figsize=(12.5,5.1),sharey=True)
    for ax,arm in zip(axes,["refined","fixed"]):
        part=frontier[frontier.arm.eq(arm)]
        for pool,color in COLORS.items():
            for ranking,marker in [("margin","o"),("geometry","s")]:
                rows=part[part.pool.eq(pool)&part.ranking.eq(ranking)&part.fresh_consistency_passed.gt(0)]
                ax.scatter(100*rows.median_improvement_passed,rows.fresh_consistency_passed,
                           marker=marker,facecolors=color if ranking=="margin" else "none",edgecolors=color,s=50,label=f"{pool} / {ranking}")
        point=part[part.pool.eq(manifest["default"]["pool"])&part.bound.eq("retain80")&part.ranking.eq("margin")].iloc[0]
        ax.scatter(100*point.median_improvement_passed,point.fresh_consistency_passed,marker="*",s=250,color="#27323C",zorder=5)
        ax.set(title=f"{arm}: fixed policy grid",xlabel="Median Tripel distance reduction among passing spectra (%)",ylim=(-.3,11.5),xlim=(0,100),yticks=range(0,12))
        ax.grid(alpha=.2)
    axes[0].set_ylabel("Sources passing fresh checks (out of 11)")
    handles,labels=axes[0].get_legend_handles_labels()
    fig.legend(handles,labels,loc="lower center",ncol=3,frameon=False,fontsize=8,bbox_to_anchor=(.5,.035))
    fig.subplots_adjust(bottom=.29,wspace=.15)
    fig.text(.12,.005,"Stars: predeclared contracted / retain80 / margin. No audit-driven default switch; finite observed grid, not a global Pareto proof.",fontsize=8,color="#5C6470")
    save(fig,"proximity_consistency_grid")
    lines=["# 第三问：beer 81误差诊断与迁移接近度保留","",
        "## 本轮结果","",
        f"beer 81身份连接正确，陈旧感目标为 **{audit['stale_observed']:.4f}**（全250款第{audit['stale_descending_rank_all250']}高）。"
        "论坛术语表也有较高的陈旧/纸板/纸质描述；没有证据据此改标签或删除该样本。",
        f"稳定性选型保留 `{selected}`，Pils诊断RMSE **{selected_row.pils_rmse:.4f}**，仍未优于本轮旧45输出对照 **{old.pils_rmse:.4f}**。"
        f"预声明尾部加权备选的Pils点误差为 **{tail.pils_rmse:.4f}**，但其非Pils留出误差变差，未获准替换主模型。",
        f"主预测模型迁移臂通过 **{transfer['arm_defaults']['refined']['fresh_consistency_passed']}/11**；"
        f"固定树方法对照的中央候选、retain80、margin通过 **{transfer['arm_defaults']['fixed']['fresh_consistency_passed']}/11**，"
        f"所选谱目标距离改善中位数 **{transfer['arm_defaults']['fixed']['median_improvement_selected']:.1%}**。"
        "两臂分别报告，没有依据审计把较高通过数的一臂改名为默认。","",
        "## beer 81为什么难预测","",
        f"1.csv与8.xlsx精确条码一致，4.csv/7.csv条码只是给定精度较低；始终以beer精确连接。"
        f"该行混合化学输入没有缺失或非法校准负值，只有{audit['sample_profile']['outside_nonpils_feature_ranges']}项略超非Pils训练范围。"
        "相对量中重复负值是附件给定表示，不能擅自当作浓度或检测下限。",
        f"旧局部模型的25近邻目标范围为 [{audit['frozen_local_top25_stale_min']:.4f}, {audit['frozen_local_top25_stale_max']:.4f}]，"
        f"实际值{audit['stale_observed']:.4f}超出该凸包，非负加权均值结构无法达到它。训练239款中仅"
        f"{audit['nonpils_stale_at_least_beer81']}款同等高尾，且均不在这25个近邻中。"
        "这说明高缺陷尾部稀疏、化学相似性与该感官目标不一致，不能证明所有化学模型都不可能预测。",
        f"新主模型对81预测 **{selected81:.4f}**，尾部加权备选为 **{tail81:.4f}**，仍明显低估。"
```

```
        "缺陷可能涉及未记录的储存、批次或品评差异，当前附件无法识别真实原因。7.csv是数值术语表而非原始评论；"
        "它仅用于语义佐证，未用作生成谱推理特征。所有Pils主指标保留11源。","",
        "## 预测的内部改善与外推代价","",
        "固定缺失指示维数、平滑岭回归、辅助感官训练监督及训练内尾部权重均为本轮预声明比较。"
        "辅助44感官只在训练阶段学习化学方向，推理只接受226维化学输入。"
        "主规则先应用完整风格留出精度与非退化门槛，再在一标准误差容忍带内按训练内响应稳定性选择。"
        "该容忍带是选择启发式，不是置信区间。",
        f"4外层分组、内层完整风格留出评价整个规则：pooled RMSE **{nested_values.loc['nested_stability_rule','rmse']:.4f}**，"
        f"同折旧45输出树 **{nested_values.loc['old_multioutput_tree','rmse']:.4f}**、固定单目标树 **{nested_values.loc['fixed_single_tree','rmse']:.4f}**。"
        "这是复用本批非Pils数据的嵌套内部点比较，不是新增外部测试。",
        "|配置|LOSO宏RMSE|LOSO pooled RMSE|Pils诊断RMSE|训练内准入|主方法|","|---|---:|---:|---:|---|---|"]
    for row in comparison.itertuples():
        lines.append(f"|{row.method}|{row.macro_style_rmse:.4f}|{row.rmse:.4f}|{row.pils_rmse:.4f}|{'是' if row.eligible_for_one_se else '否'}|{'是' if row.method==selected else ''}|")
    lines.extend(["",f"尾部备选的LOSO宏RMSE为{tail.macro_style_rmse:.4f}、pooled为{tail.rmse:.4f}，Pils R²仍为{tail_r2:.4f}，因此不能因Pils较小就后验换主方法。"
        "全部可选配置工件均保存于 `../outputs/q3_refined/stale/candidate_models/`，未选配置明确标作开发诊断。",
        "", "|60次bootstrap响应|噪声RMS|信号RMS|噪声/信号|","|---|---:|---:|---:|"])
    for row in response.itertuples():lines.append(f"|{row.method}|{row.pair_delta_noise_rms:.4f}|{row.pair_delta_signal_rms:.4f}|{row.response_noise_ratio:.4f}|")
    lines.extend(["","响应对由非Pils真实化学邻居固定产生；其中包含拟合内点，只是训练内稳定性诊断，不能证明迁移后的真实感官因果效应。",
        "","![81与预测误差](../outputs/q3_refined/figures/beer81_and_prediction.png)","",
        "## 同时保护一致性与Tripel接近幅度","",
        "新增中央候选把冻结500个目标谱经原高斯秩映射后，按0.2/0.4/0.6向Tripel中心收缩，再经经验逆CDF还原。"
        "它是搜索proposal，不当作更高质量生成模型的证据；每源投影后重新检查原完整226维几何、NN支持和十阈值保护。",
        f"1500个中央目标谱中有{transfer['contracted_targets_unique']}个唯一向量。逐源投影后去重数和重复率另存pool_uniqueness.csv；"
        "6004表示名义预算，不等于6004个独立新样本。",
        "retain80要求每源保留最早冻结默认谱至少80%的目标距离改善，并保持最少10%改善。"
        "另完整保存retain100及绝对10%/30%/50%/60%下限、两种排序、三个池的经验权衡网格。"
        "默认在审计前固定为refined/contracted_6004/retain80/margin，没有根据审计改选。",
        "筛选同时要求新旧委员会配对Q95不增加及两个中心预测不增加。旧中心确为45输出模型，但旧bootstrap仍是单目标120树；"
        "45输出中心只作单点一致检查，不声称已做该架构的bootstrap审计。新20与新种子旧协议20只审计已选谱，失败不重选。",
        "","|臂|候选池|retain80排序|选出/11|fresh通过/11|通过谱改善中位数|所选谱改善中位数|保留率中位数|",
        "|---|---|---|---:|---:|---:|---:|---:|"])
    for row in frontier[frontier.bound.eq("retain80")].itertuples():
        lines.append(f"|{row.arm}|{row.pool}|{row.ranking}|{row.selected}|{row.fresh_consistency_passed}|{number(row.median_improvement_passed,True)}|{number(row.median_improvement_selected,True)}|{number(row.median_retention_selected,True)}|")
    lines.extend(["", "同一臂、同一审计及下限才可直接比较。geometry是预声明几何优先对照，margin优先预测余量；"
        "两者的观察结果均保留，不按通过数宣布一个新默认。没有找到谱的源始终计入11分母。",
        "","|同本轮规则重检历史固定谱（retain80）|可用谱|fresh通过/11|原改善中位数|","|
```

```
---|---:|---:|---:|"])
    for row in ref_counts[ref_counts.bound.eq("retain80")].itertuples():
        lines.append(f"|{row.arm}/{row.reference}|{row.available}|{row.passed}|{row.median_gain:.1%}|")
    lines.extend(["", "上一轮保守谱的8/11和19.9%使用旧规则，不能直接当成本轮统计提升率；这里按新下限和同一新审计重检。",
        "","![接近度和一致性网格](../outputs/q3_refined/figures/proximity_consistency_grid.png)","",
        "完整72个网格点见 `../outputs/q3_refined/transfer/frontier.csv`，792条策略记录、选谱、逐情景浓度及配对差均保留。"
        "这是有限候选的经验权衡，不证明连续空间的全局Pareto最优，也没有真实品评覆盖率。","",
        "## 复现与边界","",
        "Pils/81目标已经多轮查看，属于开发诊断。尾部候选的点改善、嵌套内部改善和模型检查通过均不能替代新批次外测。"
        "全部目标仍为附件标准化尺度，未恢复原0–6分。",
        "诊断详见 `q3_beer81_audit.md`，预测方法见 `q3_stale_refined.md`，独立审查见 `q3_refinement_review.md`。",
        "","```bash",".venv/bin/python solution_a/run_q3_refined.py","```",""])
    (SOLUTION/"docs/q3_refinement_results.md").write_text("\n".join(lines),encoding="utf-8", newline="\n")
    summary={"selected_method":selected,"selected_pils_rmse":float(selected_row.pils_rmse),
        "tail_candidate_pils_rmse":float(tail.pils_rmse),"tail_candidate_eligible":bool(tail.eligible_for_one_se),
        "matched_old_pils_rmse":float(old.pils_rmse),"beer81_observed":audit["stale_observed"],"beer81_selected_prediction":selected81,
        "nested_rule_rmse":float(nested_values.loc["nested_stability_rule","rmse"]),
        "default_results":transfer["default_results"],"arm_defaults":transfer["arm_defaults"],
        "candidate_rows":len(comparison),"frontier_rows":len(frontier),"source_denominator":11,"figure_pairs":2}
    (OUT/"report_summary.json").write_text(json.dumps(summary,ensure_ascii=False,indent=2)+"\n",encoding="utf-8", newline="\n")
    (OUT/"report_sources.json").write_text(json.dumps(SOURCES,ensure_ascii=False,indent=2)+"\n",encoding="utf-8", newline="\n")
    print(json.dumps(summary,ensure_ascii=False,indent=2),flush=True)


if __name__=="__main__":main()
```

src/25_q3_refined_verify.py

SHA-256: 7db48f83f62efdf7ed8240cbff3404c1788d88a3f18a578b64f1a4b3fd1f9491

```
"""Recompute source diagnosis, grouped proxy selection and balanced transfer."""
from __future__ import annotations

import hashlib
import importlib
import json
from decimal import Decimal
from pathlib import Path
from time import perf_counter

import joblib
import numpy as np
import pandas as pd
from scipy.spatial.distance import cdist
from sklearn.impute import SimpleImputer
from sklearn.linear_model import Ridge
from sklearn.model_selection import GroupKFold
from sklearn.preprocessing import StandardScaler
from threadpoolctl import threadpool_limits

from common import SOLUTION, data_dir, resolve_recorded_path

BASE = importlib.import_module("10_q3_verify")
DOMAIN = importlib.import_module("19_q3_domain_verify")
OUT = SOLUTION / "outputs/q3_refined"
TOL = 1e-10


def check_frozen():
    details = DOMAIN.check_frozen()
    folder = SOLUTION / "outputs/q3_domain"
    manifest = BASE.read_json(OUT / "previous_hashes.json")
    actual = {p.relative_to(folder).as_posix() for p in folder.rglob("*") if p.is_file()}
    assert actual == {r["path"] for r in manifest["files"]}
    for row in manifest["files"]:
        raw = (folder / row["path"]).read_bytes()
        assert len(raw) == row["bytes"] and hashlib.sha256(raw).hexdigest() == row["sha256"], row["path"]
    details.append({"directory": "outputs/q3_domain", "unchanged_files": len(actual)})
    return details


def check_beer81(context):
    from q3_stale_optimized import FoldChemicalTransform
    folder = OUT / "beer81"
    meta, x, y45 = context["meta"], context["x"], context["y"]
    y = y45.stale_hops
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    sources = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    index = np.flatnonzero(meta.beer.eq(81)).item()
    summary = BASE.read_json(folder / "summary.json")
    for row in BASE.read_json(folder / "source_manifest.json"):
        assert hashlib.sha256(resolve_recorded_path(row["path"]).read_bytes()).hexdigest() == row["sha256"]
    identity = pd.read_csv(folder / "identity_join_audit.csv")
    assert len(identity) == 4 and identity.beer81_matches.eq(1).all()
```

```
    assert identity.beer_unique.all() and identity.style_matches_1csv.all() an
d identity.id_matches_printed_precision.all()
    assert identity.rows_after_exact_beer_join.eq(250).all()
    originals = {f:pd.read_csv(data_dir()/f,dtype={"beer_id":str}) for f in ["
1.csv","4.csv","7.csv"]}
    originals["8.xlsx/calibrated"] = pd.read_excel(data_dir()/"8.xlsx",sheet_n
ame="Calibrated chemical dataset",dtype={"beer_id":str})
    reference_id = Decimal(originals["1.csv"].set_index("beer").at[81,"beer_id
"])
    for name, frame in originals.items():
        assert frame.beer.is_unique and set(frame.beer)==set(meta.beer)
        row = frame.set_index("beer").loc[81]
        assert row.tasting_category_fine=="Pils/Lager"
        printed = Decimal(row.beer_id)
        resolution = Decimal(10)**printed.as_tuple().exponent
        assert abs(reference_id-printed)<=resolution/2
        actual = identity.set_index("source").loc[name]
        assert actual.beer_id_unique_count==frame.beer_id.nunique()
        assert bool(actual.exact_id_matches_1csv)==(reference_id==printed)
    names = pd.read_excel(data_dir()/"8.xlsx", sheet_name="Sensory names")
    saved_names = pd.read_csv(folder/"sensory_target_metadata.csv")
    assert set(saved_names.R_name) == {"stale_hops", "barnyard", "t2n", "dms"}
    assert names.set_index("R_name").loc[["stale_hops", "barnyard"], "DataType
"].eq("numeric").all()
    profile = pd.read_csv(folder/"chemical_profile_beer81.csv").set_index("fea
ture").loc[x.columns]
    BASE.close(profile.value, x.iloc[index], "Beer81 hybrid measurements")
    BASE.close(profile[["nonpils_min","nonpils_q01","nonpils_median","nonpils_
q99","nonpils_max"]],
               np.column_stack([x.iloc[train].min(),x.iloc[train].quantile(.01
),x.iloc[train].median(),x.iloc[train].quantile(.99),x.iloc[train].max()]))
    outside = (x.iloc[index] < x.iloc[train].min())|(x.iloc[index] > x.iloc[tr
ain].max())
    np.testing.assert_array_equal(profile.outside_nonpils_range,outside)
    assert summary["sample_profile"]["outside_nonpils_feature_ranges"]==outsid
e.sum()
    assert not x.iloc[index].isna().any() and x.iloc[index][context["calibrate
d_features"]].ge(0).all()
    assert summary["label_error_established"] is False and summary["analytical
_lod_loq_available"] is False
    BASE.close(summary["stale_observed"], y.iloc[index])
    assert summary["stale_descending_rank_all250"] == int(y.rank(ascending=Fal
se, method="min").iloc[index])
    high = train[y.iloc[train].to_numpy() >= y.iloc[index]]
    assert summary["nonpils_stale_at_least_beer81"] == len(high)
    assert set(summary["nonpils_high_tail_beers"]) == set(meta.beer.iloc[high]
)
    raw = x.to_numpy(float).copy()
    for j, field in enumerate(x):
        if field in context["calibrated_features"]:
            positive = raw[train, j]
            positive = positive[np.isfinite(positive) & (positive > 0)]
            raw[:, j] = np.log1p(raw[:, j] / (np.median(positive) if len(posit
ive) else 1.))
    imp = SimpleImputer(strategy="median", keep_empty_features=True).fit(raw[t
rain])
    filled = imp.transform(raw)
    standard = StandardScaler().fit(filled[train]).transform(filled)
    aging = BASE.read_json(OUT/"stale/run_manifest.json")["aging_features"]
    positions = [x.columns.get_loc(c) for c in aging]
    spaces = {"unclipped_log_scaled_226": standard, "unclipped_log_scaled_agin
g24": standard[:, positions]}
```

```
    for name, subset in [("clipped_log_scaled_226", None), ("clipped_log_scaled_aging24", aging)]:
        z = FoldChemicalTransform(x.columns.tolist(), context["calibrated_features"], subset).fit(x.iloc[train]).transform(x)
        imputer = SimpleImputer(strategy="median", keep_empty_features=True).fit(z[train])
        z = imputer.transform(z)
        spaces[name] = StandardScaler().fit(z[train]).transform(z)
    reference = joblib.load(SOLUTION/"outputs/q3/transfer/transfer_copula.joblib")["copula"]
    spaces["old_copula_226"] = reference.transform(x)
    spaces["old_copula_aging24"] = spaces["old_copula_226"][:, positions]
    local = joblib.load(SOLUTION/"outputs/q3_domain/stale/transfer_stale_model.joblib")["pipeline"]
    spaces["frozen_domain_aging_pca8"] = local[:-1].transform(x)
    saved = pd.read_csv(folder/"chemical_ood_all_pils.csv").set_index(["space", "query_beer"])
    neighbors = pd.read_csv(folder/"nearest_training_neighbors.csv")
    full81 = pd.read_csv(folder/"beer81_all_training_neighbor_ranks.csv")
    assert len(saved) == 7*len(sources) and len(neighbors) == 7*len(sources)*25 and len(full81) == 7*len(train)
    for name, z in spaces.items():
        training_d = cdist(z[train], z[train])/np.sqrt(z.shape[1])
        np.fill_diagonal(training_d, np.inf)
        loo = training_d.min(axis=1)
        query_d = cdist(z[sources], z[train])/np.sqrt(z.shape[1])
        for query, distances in zip(sources, query_d):
            beer = int(meta.beer.iloc[query]); row = saved.loc[(name, beer)]
            BASE.close(row[["nearest_nonpils_distance", "nonpils_loo_nn_percentile", "training_loo_nn_q95"]],
                       [distances.min(), np.mean(loo <= distances.min()), np.quantile(loo, .95)])
            order = np.argsort(distances)
            part = neighbors[neighbors.space.eq(name)&neighbors.query_beer.eq(beer)].sort_values("neighbor_rank")
            np.testing.assert_array_equal(part.neighbor_beer, meta.beer.iloc[train[order[:25]]])
            BASE.close(part.distance, distances[order[:25]])
            BASE.close(part.neighbor_stale, y.iloc[train[order[:25]]])
            if beer == 81:
                part = full81[full81.space.eq(name)].sort_values("neighbor_rank")
                np.testing.assert_array_equal(part.neighbor_beer, meta.beer.iloc[train[order]])
                BASE.close(part.distance, distances[order])
    local25 = neighbors[neighbors.space.eq("frozen_domain_aging_pca8")&neighbors.query_beer.eq(81)]
    assert summary["beer81_outside_local_top25_target_convex_hull"] == bool(y.iloc[index] > local25.neighbor_stale.max())
    errors = pd.read_csv(folder/"all_saved_pils_prediction_errors.csv")
    influence = pd.read_csv(folder/"beer81_sse_contribution.csv").set_index(["stage", "method"])
    deletion = pd.read_csv(folder/"leave_one_source_out_influence.csv").set_index(["stage", "method", "omitted_beer"])
    for keys, part in errors.groupby(["stage", "method"]):
        assert len(part) == len(sources) and set(part.beer) == set(meta.beer.iloc[sources])
        BASE.close(part.observed, part.beer.map(pd.Series(y.to_numpy(), index=meta.beer)))
        residual = part.prediction.to_numpy()-part.observed.to_numpy()
        BASE.close(part.residual, residual); BASE.close(part.squared_error, residual**2)
```

```
        BASE.close(part.sse_share, residual**2/np.sum(residual**2))
        r81 = part[part.beer.eq(81)].iloc[0]
        BASE.close(influence.loc[keys, ["full_rmse", "beer81_residual", "beer81_sse_share"]],
                   [np.sqrt(np.mean(residual**2)), r81.residual, r81.sse_share])
        for row in part.itertuples():
            BASE.close(deletion.loc[(*keys, row.beer), "fixed_prediction_rmse_without_one_source"],
                       np.sqrt(part.loc[part.beer.ne(row.beer), "squared_error"].mean()))
    forum = pd.read_csv(data_dir()/"7.csv").set_index("beer")
    terms = pd.read_csv(folder/"forum_all_terms_beer81.csv")
    assert len(terms) == 186
    for row in terms.itertuples():
        BASE.close(row.beer81_value, forum.at[81, row.term])
        values = forum[row.term].to_numpy(float)
        values = values[np.isfinite(values)]
        value = forum.at[81, row.term]
        BASE.close(row.all_percentile, (np.sum(values < value)+.5*np.sum(values==value))/len(values) if pd.notna(value) else np.nan)
    return {"source": 81, "chemical_features": len(profile), "ood_spaces": len(spaces),
            "retained_sources": len(sources), "stale_rank": summary["stale_descending_rank_all250"],
            "high_tail_training": len(high), "label_error_established": False,
            "fixed_prediction_influence_groups": len(influence)}


def check_fixed_transform(transform, training, calibrated):
    selected = transform.selected_features_
    values = training[selected].to_numpy(float).copy()
    missing = np.isnan(values)
    scales = np.ones(len(selected))
    for j, field in enumerate(selected):
        if field in calibrated:
            positive = values[np.isfinite(values[:, j])&(values[:, j] > 0), j]
            scales[j] = np.median(positive) if len(positive) else 1.
            values[:, j] = np.log1p(values[:, j]/scales[j])
    bounds = np.nanquantile(values, [.01, .99], axis=0)
    values = np.clip(values, *bounds)
    medians = np.nan_to_num(np.nanmedian(values, axis=0), nan=0.)
    filled = np.where(np.isnan(values), medians, values)
    means, std = filled.mean(axis=0), filled.std(axis=0)
    std[std < 1e-12] = 1.
    for actual, expected in [(transform.positive_scales_, scales), (transform.bounds_, bounds),
                             (transform.medians_, medians), (transform.means_, means), (transform.scales_, std)]:
        BASE.close(actual, expected, "Fold-local fixed-width chemical transform")
    assert transform.indicator_weight == .2 and transform.n_output_features_ == 2*len(selected)
    result = np.column_stack([(filled-means)/std, .2*missing])
    BASE.close(transform.transform(training), result, "Fixed unscaled missing flags")
    return result


def check_model_training(model, training, y45, styles, calibrated):
    assert model.n_features_in_ == 226 and model.n_outputs_ == 1
    if hasattr(model, "members_"):
```

```
        for member in model.members_:
            check_model_training(member, training, y45, styles, calibrated)
        return
    if hasattr(model, "chemical_"):
        z = check_fixed_transform(model.chemical_, training, calibrated)
        target = y45.stale_hops.to_numpy()
        BASE.close(model.tail_training_threshold_, np.quantile(target, .8))
        if hasattr(model, "auxiliary_target_indices_"):
            assert model.auxiliary_target_names_ == [c for c in y45 if c != "s
tale_hops"]
            assert len(model.auxiliary_target_indices_) == 44 and model.target
_position_ not in model.auxiliary_target_indices_
            w = DOMAIN.style_weights(styles)
            aux = y45[model.auxiliary_target_names_].to_numpy()
            BASE.close(model.auxiliary_mean_, np.average(aux, axis=0, weights=
w))
        if model.config["family"] == "ridge":
            weights = DOMAIN.style_weights(styles)
            if model.config.get("tail", False):
                weights *= np.where(target >= np.quantile(target, .8), 2., 1.)
                weights *= len(weights)/weights.sum()
            fitted = Ridge(alpha=model.config["alpha"], solver="svd").fit(z, t
arget, sample_weight=weights)
            BASE.close(model.model_.coef_, fitted.coef_, "Training-only weight
ed ridge coefficients")
            BASE.close(model.model_.intercept_, fitted.intercept_)


def select_from_tables(table, stability):
    baseline = table[table.method.eq("mean_global")].iloc[0]
    eligible = table.selectable & (table.prediction_variance_ratio >= .05)
    eligible &= (table.macro_style_rmse < baseline.macro_style_rmse)&(table.rm
se < baseline.rmse)
    np.testing.assert_array_equal(eligible, table.eligible_for_one_se)
    candidates = table[eligible]
    fallback = candidates.empty
    best = (table[table.selectable] if fallback else candidates).sort_values([
"selection_score", "method"]).iloc[0]
    one_se = [best.method] if fallback else candidates.loc[candidates.selectio
n_score <= best.selection_score+best.style_score_se, "method"].tolist()
    assert set(table.loc[table.within_one_se, "method"]) == set(one_se) == set
(stability.method)
    selected = stability.sort_values(["response_noise_ratio", "priority", "met
hod"]).iloc[0]
    qualified = bool(not fallback and selected.pair_delta_signal_rms > 1e-4 an
d selected.response_noise_ratio <= 1.)
    return selected.method, qualified, best


def check_stale(context):
    from q3_stale_refined import RefinedStaleModel, FixedChemicalTransform, re
fined_specs
    folder = OUT/"stale"
    meta, x, y45 = context["meta"], context["x"], context["y"]
    y = y45.stale_hops
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    sources = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    manifest, decision, summary = [BASE.read_json(folder/f) for f in ("run_man
ifest.json", "selection_result.json", "summary.json")]
    specs = {s["name"]: s for s in manifest["candidate_specs"]}
    assert list(specs.values()) == refined_specs() and len(specs) == 12
    assert manifest["pils_labels_used_for_selection_or_intercept"] is False an
```

```
d manifest["no_beer81_exclusion"]
    assert manifest["features"] == x.columns.tolist()
    assert manifest["auxiliary_target_names"] == [c for c in y45 if c != "stal
e_hops"]
    np.testing.assert_array_equal(manifest["training_indices"], train)
    np.testing.assert_array_equal(manifest["excluded_indices"], sources)
    def fit(spec, rows, seed):
        return RefinedStaleModel(x.columns.tolist(), context["calibrated_featu
res"], manifest["aging_features"],
                                 y45.columns.tolist(), spec, seed).fit(x.iloc[
rows], y45.iloc[rows], meta.tasting_category_fine.iloc[rows])
    predictions = pd.read_csv(folder/"loso_predictions.csv")
    audit = pd.read_csv(folder/"loso_split_audit.csv")
    by_style = pd.read_csv(folder/"loso_metrics_by_style.csv")
    overall = pd.read_csv(folder/"loso_metrics_overall.csv")
    assert len(predictions) == len(train)*len(specs) and not predictions.dupli
cated(["method", "global_index"]).any()
    calculated_styles = []
    for fold, part in audit.groupby("fold"):
        heldout = part.heldout_style.unique().item()
        te = train[meta.tasting_category_fine.iloc[train].eq(heldout)]
        tr = train[~meta.tasting_category_fine.iloc[train].eq(heldout)]
        assert set(part.loc[part.role.eq("train"), "global_index"]) == set(tr)
        assert set(part.loc[part.role.eq("test"), "global_index"]) == set(te)
        assert len(part) == len(train) and not part.global_index.duplicated().
any()
        fitted = fit(decision["config"], tr, manifest["final_seed"]+int(fold))
        check_model_training(fitted, x.iloc[tr], y45.iloc[tr], meta.tasting_ca
tegory_fine.iloc[tr], context["calibrated_features"])
        for method in specs:
            rows = predictions[predictions.method.eq(method)&predictions.fold.
eq(fold)].set_index("global_index").loc[te]
            assert rows.heldout_style.eq(heldout).all()
            BASE.close(rows.observed, y.iloc[te])
            BASE.close(rows.tail_threshold_training_q90, np.quantile(y.iloc[tr
], .9))
            np.testing.assert_array_equal(rows.is_tail_eval, rows.observed >=
rows.tail_threshold_training_q90)
            if method == decision["selected_method"]:
                BASE.close(rows.prediction, fitted.predict(x.iloc[te]), "Selec
ted LOSO refit excluding held-out style")
            if method == "mean_global": BASE.close(rows.prediction, y.iloc[tr]
.mean())
            calculated_styles.append({"method": method, "heldout_style": heldo
ut, "fold": fold,
                                      **DOMAIN.score(rows.observed, rows.predi
ction), "bias": (rows.prediction-rows.observed).mean()})
    metrics = list(DOMAIN.score(y, y))
    BASE.same_table(by_style, pd.DataFrame(calculated_styles), ["method", "hel
dout_style", "fold"], metrics+["bias"], "LOSO style statistics")
    calculated = []
    for method in specs:
        rows = predictions[predictions.method.eq(method)].set_index("global_in
dex").loc[train]
        bs = by_style[by_style.method.eq(method)]
        losses = bs.rmse+.25*bs.bias.abs()
        tail = rows.is_tail_eval
        calculated.append({"method": method, **DOMAIN.score(rows.observed, row
s.prediction),
                           "macro_style_rmse": bs.rmse.mean(), "macro_style_ab
s_bias": bs.bias.abs().mean(),
                           "selection_score": losses.mean(), "style_score_se":
```

```
 losses.std(ddof=1)/np.sqrt(len(losses)),
                            "tail_n": tail.sum(), "tail_rmse": np.sqrt(np.mean(
(rows.loc[tail, "prediction"]-rows.loc[tail, "observed"])**2))})
    BASE.same_table(overall, pd.DataFrame(calculated), ["method"], list(calcul
ated[0])[1:], "LOSO pooled and selection statistics")
    stability = pd.read_csv(folder/"selection_stability.csv")
    selected, qualified, best = select_from_tables(overall, stability)
    assert selected == decision["selected_method"] == summary["selected_method
"] and qualified == decision["qualified_for_proxy"]
    BASE.close([decision["lowest_selection_score"], decision["one_se_width"],
decision["one_se_threshold"]],
               [best.selection_score, best.style_score_se, best.selection_scor
e+best.style_score_se])
    pairs_transform = FixedChemicalTransform(x.columns.tolist(), context["cali
brated_features"], manifest["aging_features"]).fit(x.iloc[train])
    z = check_fixed_transform(pairs_transform, x.iloc[train], context["calibra
ted_features"])
    d = cdist(z, z); np.fill_diagonal(d, np.inf)
    pairs = train[np.argsort(d, axis=1)[:, 2]]
    pair_table = pd.read_csv(folder/"selection_chemical_pairs.csv").set_index(
"global_index").loc[train]
    np.testing.assert_array_equal(pair_table.paired_global_index, pairs)
    for row in stability.itertuples():
        delta = []
        for b in range(manifest["stability_draws"]):
            seed = manifest["stability_seed"]+b
            resample = np.random.default_rng(seed).choice(train, len(train), r
eplace=True)
            fitted = fit(specs[row.method], resample, seed+10000)
            delta.append(fitted.predict(x.iloc[train])-fitted.predict(x.iloc[p
airs]))
        delta = np.asarray(delta)
        noise, signal = np.sqrt(np.mean(np.var(delta, axis=0, ddof=1))), np.sq
rt(np.mean(delta.mean(axis=0)**2))
        BASE.close([row.pair_delta_noise_rms, row.pair_delta_signal_rms, row.r
esponse_noise_ratio], [noise, signal, noise/max(signal, 1e-8)])
    artifact = joblib.load(folder/"transfer_stale_model.joblib")
    ensemble = joblib.load(folder/"bootstrap_ensemble.joblib")
    for saved in [artifact, ensemble]:
        np.testing.assert_array_equal(saved["train_global_indices"], train)
        np.testing.assert_array_equal(saved["excluded_global_indices"], source
s)
        assert saved["pils_used_for_selection"] is False and saved["selected_c
onfig"] == specs[selected]
        assert saved["qualified_for_proxy"] == qualified and saved["features"]
 == x.columns.tolist()
    check_model_training(artifact["pipeline"], x.iloc[train], y45.iloc[train],
 meta.tasting_category_fine.iloc[train], context["calibrated_features"])
    indices = np.asarray(ensemble["bootstrap_indices"])
    assert indices.shape == (60, len(train)) and not np.isin(indices, sources)
.any()
    assert ensemble["selection_model_indices"] == list(range(40)) and ensemble
["audit_model_indices"] == list(range(40,60))
    with np.load(folder/"bootstrap_indices.npz") as saved:
        np.testing.assert_array_equal(saved["indices"], indices)
        np.testing.assert_array_equal(saved["bootstrap_seeds"], ensemble["boot
strap_seeds"])
    for b, (model, rows, seed) in enumerate(zip(ensemble["models"], indices, e
nsemble["bootstrap_seeds"])):
        assert seed == (manifest["selection_bootstrap_seed"]+b if b < 40 else
manifest["audit_bootstrap_seed"]+b-40)
        np.testing.assert_array_equal(rows, np.random.default_rng(seed).choice
```

```
    (train, len(train), replace=True))
325         assert model.seed == seed+10000
326         check_model_training(model, x.iloc[rows], y45.iloc[rows], meta.tasting
    _category_fine.iloc[rows], context["calibrated_features"])
327     archive = pd.read_csv(folder/"candidate_model_manifest.csv")
328     assert set(archive.method) == {name for name, spec in specs.items() if spe
    c["selectable"]}
329     for row in archive.itertuples():
330         saved = joblib.load(folder/row.file)
331         np.testing.assert_array_equal(saved["train_global_indices"], train)
332         assert saved["pils_used_for_selection"] is False and saved["selected_c
    onfig"] == specs[row.method]
333         check_model_training(saved["pipeline"], x.iloc[train], y45.iloc[train]
    , meta.tasting_category_fine.iloc[train], context["calibrated_features"])
334     diagnostic = pd.read_csv(folder/"pils_diagnostic_predictions.csv")
335     dm = pd.read_csv(folder/"pils_diagnostic_metrics.csv")
336     assert len(diagnostic) == len(specs)*len(sources)
337     for method, part in diagnostic.groupby("method"):
338         part = part.set_index("global_index").loc[sources]
339         BASE.close(part.observed, y.iloc[sources])
340         BASE.close(dm.set_index("method").loc[method, metrics], list(DOMAIN.sc
    ore(part.observed, part.prediction).values()))
341         if method == selected: BASE.close(part.prediction, artifact["pipeline"
    ].predict(x.iloc[sources]))
342         if specs[method]["selectable"]:
343             saved = joblib.load(folder/f"candidate_models/{method}.joblib")
344             BASE.close(part.prediction, saved["pipeline"].predict(x.iloc[sourc
    es]), "All archived candidate Pils diagnostics")
345             refitted = fit(specs[method], train, manifest["final_seed"])
346             BASE.close(saved["pipeline"].predict(x), refitted.predict(x), "Can
    didate refit on non-Pils training only")
347     comparisons = pd.read_csv(folder/"bootstrap_response_comparison.csv").set_
    index("method")
348     old_models = joblib.load(SOLUTION/"outputs/q3_domain/stale/bootstrap_ensem
    ble.joblib")["models"]
349     for label, models in [("refined_selected", ensemble["models"]), ("domain_l
    ocal_previous", old_models)]:
350         delta = np.asarray([m.predict(x.iloc[train])-m.predict(x.iloc[pairs])
    for m in models])
351         noise, signal = np.sqrt(np.mean(np.var(delta, axis=0, ddof=1))), np.sq
    rt(np.mean(delta.mean(axis=0)**2))
352         BASE.close(comparisons.loc[label, ["pair_delta_noise_rms", "pair_delta
    _signal_rms", "response_noise_ratio"]], [noise, signal, noise/max(signal, 1e-8
    )])
353     nested = pd.read_csv(folder/"nested_predictions.csv")
354     choices = pd.read_csv(folder/"nested_choices.csv").set_index("outer_fold")
355     outer_audit = pd.read_csv(folder/"nested_outer_split_audit.csv")
356     inner_audit = pd.read_csv(folder/"nested_inner_split_audit.csv")
357     inner_metrics = pd.read_csv(folder/"nested_inner_metrics.csv")
358     inner_stability = pd.read_csv(folder/"nested_selection_stability.csv")
359     assert len(nested) == len(train)*4 and not nested.duplicated(["method", "g
    lobal_index"]).any()
360     groups = meta.tasting_category_fine.iloc[train].to_numpy()
361     for fold, (tr, te) in enumerate(GroupKFold(4, shuffle=True, random_state=m
    anifest["nested_seed"]).split(train, groups=groups), 1):
362         tr, te = train[tr], train[te]
363         for role, rows in [("train", tr), ("test", te)]:
364             actual = outer_audit[outer_audit.outer_fold.eq(fold)&outer_audit.r
    ole.eq(role)]
365             np.testing.assert_array_equal(actual.global_index, rows)
366         assert not set(meta.tasting_category_fine.iloc[tr])&set(meta.tasting_c
    ategory_fine.iloc[te])
```

```
        for _, part in inner_audit[inner_audit.outer_fold.eq(fold)].groupby("fold"):
            style = part.heldout_style.unique().item()
            assert set(part.global_index) == set(tr)
            assert set(part.loc[part.role.eq("test"), "global_index"]) == set(tr[meta.tasting_category_fine.iloc[tr].eq(style)])
            assert not set(part.global_index)&set(te)
        method, ok, _ = select_from_tables(inner_metrics[inner_metrics.outer_fold.eq(fold)], inner_stability[inner_stability.outer_fold.eq(fold)])
        assert method == choices.at[fold, "selected_method"] and ok == choices.at[fold, "qualified_for_proxy"]
        rows = nested[nested.outer_fold.eq(fold)&nested.method.eq("nested_stability_rule")].set_index("global_index").loc[te]
        fitted = fit(specs[method], tr, manifest["nested_seed"]+fold)
        BASE.close(rows.prediction, fitted.predict(x.iloc[te]), "Outer grouped selected predictor")
        BASE.close(rows.observed, y.iloc[te]); BASE.close(rows.tail_threshold_training_q90, np.quantile(y.iloc[tr], .9))
    nm = pd.read_csv(folder/"nested_metrics.csv").set_index("method")
    for method, rows in nested.groupby("method"):
        BASE.close(nm.loc[method, metrics], list(DOMAIN.score(rows.observed, rows.prediction).values()))
    context.update(refined_artifact=artifact, refined_ensemble=ensemble)
    return {"candidate_models": len(specs), "archived_selectable_models": len(archive), "loso_styles": len(audit.fold.unique()),
            "loso_predictions": len(predictions), "nested_outer_folds": len(choices), "bootstrap_models": len(indices),
            "source_excluded": True, "selected_method": selected, "qualified_internal": qualified,
            "pils_rmse": float(dm.set_index("method").at[selected, "rmse"]),
            "pooled_loso_rmse": float(overall.set_index("method").at[selected, "rmse"]),
            "nested_selected_rmse": float(nm.at["nested_stability_rule", "rmse"])}


def paired(models, candidate, source):
    return np.column_stack([np.asarray(m.predict(candidate)).reshape(-1)-np.asarray(m.predict(source)).reshape(-1)[0] for m in models])


def check_transfer(context):
    from q3_data import read_defect_thresholds
    folder = OUT/"transfer"
    meta, x, y45 = context["meta"], context["x"], context["y"]
    features = x.columns.tolist(); dim = len(features)
    train = np.flatnonzero(~meta.tasting_category_fine.eq("Pils/Lager"))
    sources = np.flatnonzero(meta.tasting_category_fine.eq("Pils/Lager"))
    target = np.flatnonzero(meta.tasting_category_fine.eq("Tripel"))
    manifest, summary = [BASE.read_json(folder/f) for f in ("run_manifest.json", "summary.json")]
    default = {"arm":"refined", "pool":"contracted_6004", "bound":"retain80", "ranking":"margin"}
    assert manifest["default"] == summary["default"] == default
    assert manifest["default_chosen_from_audit"] is False and manifest["audit_reselection"] is False
    bounds = {"absolute10":(.1,None), "absolute30":(.3,None), "absolute50":(.5,None),
              "absolute60":(.6,None), "retain80":(.1,.8), "retain100":(.1,1.)}
    assert manifest["bounds"] == {k:{"absolute_minimum":v[0],"anchor_fraction":v[1]} for k,v in bounds.items()}
    assert manifest["pools"] == {"legacy_2004":2004,"legacy_6004":6004,"contra
```

```
cted_6004":6004}
    geometry = joblib.load(SOLUTION/"outputs/q3/transfer/transfer_copula.jobli
b")
    np.testing.assert_array_equal(geometry["training_rows"], train)
    reference = geometry["copula"]
    tz = reference.transform(x.iloc[target]); center = tz.mean(axis=0)
    d = cdist(tz,tz)/np.sqrt(dim); np.fill_diagonal(d,np.inf)
    limit = np.quantile(d.min(axis=1),.95)
    BASE.close(summary["support_limit"],limit)
    legacy = pd.read_csv(folder/"legacy_base_draws.csv")
    BASE.close(legacy,pd.read_csv(SOLUTION/"outputs/q3_domain/consensus/base_d
raws.csv"))
    assert legacy.shape == (1500,226)
    base = reference.transform(legacy.iloc[:500])
    expected_latent = np.vstack([reference.style_center_["Tripel"]+c*(base-ref
erence.style_center_["Tripel"]) for c in [.2,.4,.6]])
    BASE.close(np.load(folder/"contracted_latents.npy"),expected_latent)
    contracted = pd.read_csv(folder/"contracted_base_draws.csv")
    BASE.close(contracted,reference.inverse_transform(expected_latent),"Contra
cted latent inverse")
    drawmeta = pd.read_csv(folder/"contracted_draw_metadata.csv")
    BASE.close(drawmeta, np.column_stack([np.arange(1500),np.tile(np.arange(50
0),3),np.repeat([.2,.4,.6],500)]))
    assert summary["contracted_targets_unique"] == len(np.unique(contracted,ax
is=0))
    scenarios = BASE.read_json(SOLUTION/"outputs/q3_optimized/transfer/thresho
ld_scenarios.json")
    assert manifest["threshold_scenarios"] == scenarios and len(scenarios) ==
10
    rules = read_defect_thresholds()
    original = joblib.load(SOLUTION/"outputs/q3/sensory/stale_bootstrap.joblib
")
    center_old = joblib.load(SOLUTION/"outputs/q3/sensory/transfer_proxy.jobli
b")["pipeline"]
    fixed = joblib.load(SOLUTION/"outputs/q3_optimized/stale_fixed/transfer_st
ale_model.joblib")
    fixed_ensemble = joblib.load(SOLUTION/"outputs/q3_optimized/stale_fixed/bo
otstrap_ensemble.joblib")
    fresh = {}
    for label,filename,seed in [("old","fresh_original_audit.joblib",202104123
),("fixed","fresh_fixed_audit.joblib",202105123)]:
        saved = joblib.load(folder/filename)
        np.testing.assert_array_equal(saved["train_global_indices"],train)
        np.testing.assert_array_equal(saved["excluded_global_indices"],sources
)
        assert saved["features"] == features and len(saved["models"]) == 20
        for b,(model,rows,current) in enumerate(zip(saved["models"],saved["boo
tstrap_indices"],saved["bootstrap_seeds"])):
            assert current == seed+b
            np.testing.assert_array_equal(rows,np.random.default_rng(current).
choice(train,len(train),replace=True))
            BASE.close(model.named_steps["imputer"].statistics_,x.iloc[rows].m
edian())
            tree = model.named_steps["model"]
            assert tree.n_outputs_ == 1 and tree.n_estimators == 120 and tree.
min_samples_leaf == 3 and tree.max_features == .7
            assert tree.random_state == current+10000
        fresh[label] = saved["models"]
    assert center_old.named_steps["model"].n_outputs_ == 45
    assert all(m.named_steps["model"].n_outputs_ == 1 for m in original["model
s"])
    arms = {"refined":(context["refined_artifact"],context["refined_ensemble"]
```

```
["models"][:40],context["refined_ensemble"]["models"][40:]),
            "fixed":(fixed,fixed_ensemble["models"][:40],fresh["fixed"])}
    result = pd.read_csv(folder/"transfer_summary.csv")
    geom = pd.read_csv(folder/"candidate_geometry.csv.gz")
    model_checks = pd.read_csv(folder/"candidate_model_checks.csv.gz")
    spectra = pd.read_csv(folder/"selected_spectra.csv").set_index("transfer_i
d")
    deltas = pd.read_csv(folder/"paired_deltas.csv")
    thresholds = pd.read_csv(folder/"threshold_checks.csv")
    rechecks = pd.read_csv(folder/"fixed_spectra_rechecks.csv")
    assert rechecks.evaluation_pool.eq(default["pool"]).all()
    uniqueness = pd.read_csv(folder/"pool_uniqueness.csv").set_index(["source_
beer","pool"])
    anchors = pd.read_csv(SOLUTION/"outputs/q3_optimized/transfer/transfer_sum
mary.csv")
    anchors = anchors[anchors.is_default_policy].set_index("source_beer")
    anchor_spectra = pd.read_csv(SOLUTION/"outputs/q3_optimized/transfer/trans
ferred_spectra.csv").set_index("transfer_id")
    prior = pd.read_csv(SOLUTION/"outputs/q3_domain/consensus/transfer_summary
.csv")
    prior_spectra = pd.read_csv(SOLUTION/"outputs/q3_domain/consensus/transfer
red_spectra.csv").set_index("transfer_id")
    assert len(result) == len(arms)*3*6*2*len(sources) and not result.transfer
_id.duplicated().any()
    assert len(geom) == 12004*len(sources) and len(model_checks) == len(arms)*
len(geom)
    expected_deltas, expected_thresholds, expected_rechecks = [],[],[]
    medians = x.iloc[train].median(); target_median = x.iloc[target].median().
to_numpy()
    minimum,maximum = x.iloc[train].min().to_numpy(),x.iloc[train].max().to_nu
mpy()
    stale_position = y45.columns.get_loc("stale_hops")
    for index in sources:
        beer = int(meta.beer.iloc[index]); raw = x.iloc[[index]]; source = raw
.fillna(medians)
        descriptions,blocks = [],[]
        for family,draws in [("legacy",legacy),("contracted",contracted)]:
            for gamma in [.25,.5,.75,1.]:
                blocks.append((1-gamma)*source.to_numpy()[0]+gamma*draws.to_nu
mpy())
                descriptions.extend((family,gamma,j) for j in range(len(draws)
))
        for gamma in [.25,.5,.75,1.]:
            blocks.append(((1-gamma)*source.to_numpy()[0]+gamma*target_median)
[None])
            descriptions.append(("median",gamma,-1))
        candidates = pd.DataFrame(np.vstack(blocks),columns=features)
        desc = pd.DataFrame(descriptions,columns=["family","gamma","draw"])
        chemical = np.ones(len(candidates),bool)
        for rule in rules.values():
            field = rule["feature"]; c0 = raw[field].iloc[0]
            assert np.isfinite(c0) and c0 >= 0
            finite_t = [s["thresholds"][field] for s in scenarios if s["thresh
olds"][field] is not None]
            cap = max(c0,min(finite_t)) if finite_t else c0
            candidates[field] = candidates[field].clip(lower=0,upper=cap)
            for scenario in scenarios:
                threshold = scenario["thresholds"][field]
                chemical &= candidates[field].to_numpy() <= (max(c0,threshold)
 if threshold is not None else c0)+TOL
        assert np.isfinite(candidates.to_numpy()).all() and candidates[context
["calibrated_features"]].ge(0).all().all()
```

```
        masks = {"legacy_2004":desc.family.eq("median")|(desc.family.eq("legac
y")&desc.draw.lt(500)),
                 "legacy_6004":desc.family.isin(["legacy","median"]),"contract
ed_6004":desc.family.isin(["contracted","median"])}
        z,sz = reference.transform(candidates),reference.transform(source)
        distance = reference.distance(candidates,"Tripel"); before = reference
.distance(source,"Tripel")[0]
        improvement = 1-distance/max(before,1e-8)
        change = np.linalg.norm(z-sz,axis=1)/np.sqrt(dim)
        nn = cdist(z,tz).min(axis=1)/np.sqrt(dim)
        support = (nn<=limit+TOL)&((candidates.to_numpy()>=minimum-TOL)&(candi
dates.to_numpy()<=maximum+TOL)).all(axis=1)
        objective = distance/max(before,1e-8)+.2*change/max(np.linalg.norm(sz[
0]-center)/np.sqrt(dim),1e-8)
        geometric = support&chemical&(change>=.05)
        actual_geom = geom[geom.source_beer.eq(beer)].sort_values("candidate_i
ndex")
        BASE.close(actual_geom[["target_distance","target_improvement","change
_latent_rms","target_nn_rms","support_ok","chemical_ok","geometry_objective"]]
,
                   np.column_stack([distance,improvement,change,nn,support,che
mical,objective]),"All post-projection fixed geometry")
        assert actual_geom.family.tolist() == desc.family.tolist()
        BASE.close(actual_geom[["gamma","draw"]],desc[["gamma","draw"]])
        anchor_frame = anchor_spectra.loc[[anchors.at[beer,"transfer_id"]],fea
tures]
        anchor_gain = 1-reference.distance(anchor_frame,"Tripel")[0]/max(befor
e,1e-8)
        unique,inverse = np.unique(candidates.to_numpy(),axis=0,return_inverse
=True)
        unique = pd.DataFrame(unique,columns=features)
        old_delta = paired(original["models"][:30],unique,source)[inverse]
        old_q = np.quantile(old_delta,.95,axis=1); old_signal = np.any(np.abs(
old_delta)>1e-8,axis=1)
        old_center_source = center_old.predict(source)[0,stale_position]
        old_center_delta = center_old.predict(unique)[:,stale_position][invers
e]-old_center_source
        for pool,mask in masks.items():
            actual_unique = len(np.unique(candidates.to_numpy()[mask],axis=0))
; nominal = int(mask.sum())
            BASE.close(uniqueness.loc[(beer,pool),["nominal_candidates","uniqu
e_candidates","duplicate_fraction","anchor_gain"]],
                       [nominal,actual_unique,1-actual_unique/nominal,anchor_g
ain])
        for arm,(artifact,selection,audit) in arms.items():
            new_delta = paired(selection,unique,source)[inverse]
            new_q = np.quantile(new_delta,.95,axis=1); new_signal = np.any(np.
abs(new_delta)>1e-8,axis=1)
            current = artifact["pipeline"]
            center_source = np.asarray(current.predict(source)).reshape(-1)[0]
            center_delta = np.asarray(current.predict(unique)).reshape(-1)[inv
erse]-center_source
            worst = np.maximum(new_q,old_q)
            joint = geometric&(new_q<=TOL)&(old_q<=TOL)&new_signal&old_signal&
(center_delta<=TOL)&(old_center_delta<=TOL)
            checks = model_checks[model_checks.source_beer.eq(beer)&model_chec
ks.arm.eq(arm)].sort_values("candidate_index")
            BASE.close(checks[["new_selection_q95","old_selection_q95","worst_
selection_q95","center_new_delta","center_old_delta","new_signal","old_signal"
,"joint_feasible"]],
                       np.column_stack([new_q,old_q,worst,center_delta,old_cen
ter_delta,new_signal,old_signal,joint]),"Complete selection diagnostics withou
```

```
t audit")
            qualified = artifact["qualified_for_proxy"]
            rows = result[result.source_beer.eq(beer)&result.arm.eq(arm)]
            cache = {}
            def audit_frame(frame):
                key = frame.to_numpy().tobytes()
                if key not in cache:
                    cache[key] = {"new_audit":paired(audit,frame,source)[0],"o
ld_fresh_audit":paired(fresh["old"],frame,source)[0],
                                  "old_historical":paired(original["models"][3
0:],frame,source)[0]}
                return cache[key]
            for row in rows.itertuples():
                absolute,retention = bounds[row.bound]
                floor = max(absolute,retention*anchor_gain) if retention is no
t None else absolute
                mask = masks[row.pool].to_numpy()
                nsd,osd = np.std(new_delta[mask].mean(axis=1)),np.std(old_delt
a[mask].mean(axis=1))
                informative = bool(nsd>1e-6 and osd>1e-6)
                ids = np.flatnonzero(joint&mask&(improvement>=floor))
                BASE.close([row.anchor_gain,row.required_gain,row.candidate_co
unt,row.feasible_count,row.new_delta_sd,row.old_delta_sd],
                           [anchor_gain,floor,mask.sum(),len(ids),nsd,osd])
                assert row.qualified == qualified and row.informative == infor
mative
                arm_default = row.pool==default["pool"] and row.bound==default
["bound"] and row.ranking==default["ranking"]
                assert row.is_arm_default == arm_default and row.is_default_po
licy == (arm==default["arm"] and arm_default)
                if not len(ids):
                    assert pd.isna(row.candidate_index) and row.status=="no_ca
ndidate" and not row.fresh_consistency_passed
                    continue
                chosen = ids[np.lexsort((objective[ids],worst[ids]))[0]] if ro
w.ranking=="margin" else ids[np.argmin(objective[ids])]
                assert int(row.candidate_index)==chosen, "Frozen eligible argm
in cannot use audit predictions"
                frame = candidates.iloc[[chosen]]
                BASE.close(spectra.loc[row.transfer_id,features],frame.iloc[0]
,"Selected spectrum reconstruction")
                assessed = audit_frame(frame); aq = {k:np.quantile(v,.95) for
k,v in assessed.items()}
                newpass = bool(qualified and informative and aq["new_audit"]<=
TOL)
                freshpass = bool(newpass and aq["old_fresh_audit"]<=TOL)
                historypass = bool(newpass and aq["old_historical"]<=TOL)
                status = "unqualified" if not qualified else "uninformative" i
f not informative else "new_audit_failed" if not newpass else "old_fresh_audit
_failed" if not freshpass else "passed"
                assert row.status==status and row.new_model_passed==newpass an
d row.fresh_consistency_passed==freshpass and row.historical_consistency_passe
d==historypass
                BASE.close([row.target_distance_before,row.target_distance_aft
er,row.target_improvement,row.retained_anchor_gain,row.change_latent_rms,
                            row.target_nn_rms,row.support_nn_limit,row.geometr
y_objective,row.new_selection_q95,row.old_selection_q95,row.worst_selection_q9
5,
                            row.center_new_delta,row.center_old_delta,row.new_
audit_q95,row.old_fresh_audit_q95,row.old_historical_q95],
                           [before,distance[chosen],improvement[chosen],improv
ement[chosen]/anchor_gain,change[chosen],nn[chosen],limit,objective[chosen],
```

```
                                new_q[chosen],old_q[chosen],worst[chosen],center_delta[chosen],old_center_delta[chosen],aq["new_audit"],aq["old_fresh_audit"],aq["old_historical"]])
                for label,delta in {"new_selection":new_delta[chosen],"old_selection":old_delta[chosen],**assessed}.items():
                    expected_deltas.extend({"transfer_id":row.transfer_id,"ensemble":label,"model_index":i,"delta":value} for i,value in enumerate(delta))
                for scenario in scenarios:
                    for label,rule in rules.items():
                        field = rule["feature"]; threshold = scenario["thresholds"][field]; c0 = raw[field].iloc[0]
                        cap = max(c0,threshold) if threshold is not None else c0
                        expected_thresholds.append({"transfer_id":row.transfer_id,"scenario":scenario["scenario"],"defect":label,
                                "source":c0,"transferred":frame[field].iloc[0],"cap":cap,"passed":frame[field].iloc[0]<=cap+TOL})
            references = [("original_anchor",anchor_frame)]
            for pool in ("matched_2004","expanded_6004"):
                pr = prior[prior.source_beer.eq(beer)&prior.pool.eq(pool)&prior.policy.eq("joint_margin")].iloc[0]
                if pd.notna(pr.candidate_index): references.append((f"prior_{pool}",prior_spectra.loc[[pr.transfer_id],features]))
            evaluation = masks[default["pool"]].to_numpy()
            informative = np.std(new_delta[evaluation].mean(axis=1))>1e-6 and np.std(old_delta[evaluation].mean(axis=1))>1e-6
            for label,frame in references:
                pz = reference.transform(frame); gain = 1-reference.distance(frame,"Tripel")[0]/max(before,1e-8)
                shift = np.linalg.norm(pz-sz)/np.sqrt(dim)
                supported = bool(cdist(pz,tz).min()/np.sqrt(dim)<=limit+TOL and ((frame.to_numpy()>=minimum-TOL)&(frame.to_numpy()<=maximum+TOL)).all())
                chem = all(frame[r["feature"]].iloc[0] <= (max(raw[r["feature"]].iloc[0],s["thresholds"][r["feature"]]) if s["thresholds"][r["feature"]] is not None else raw[r["feature"]].iloc[0])+TOL for s in scenarios for r in rules.values())
                nd,od = paired(selection,frame,source)[0],paired(original["models"][:30],frame,source)[0]
                nq,oq = np.quantile(nd,.95),np.quantile(od,.95)
                cdn = np.asarray(current.predict(frame)).reshape(-1)[0]-center_source
                cdo = center_old.predict(frame)[0,stale_position]-old_center_source
                assessed = audit_frame(frame); aq = {k:np.quantile(v,.95) for k,v in assessed.items()}
                basepass = bool(qualified and informative and supported and chem and shift>=.05 and nq<=TOL and oq<=TOL and cdn<=TOL and cdo<=TOL and np.any(np.abs(nd)>1e-8) and np.any(np.abs(od)>1e-8))
                for bound,(absolute,retention) in bounds.items():
                    floor = max(absolute,retention*anchor_gain) if retention is not None else absolute
                    expected_rechecks.append({"source_beer":beer,"arm":arm,"reference":label,"bound":bound,"required_gain":floor,
                        "target_improvement":gain,"retained_anchor_gain":gain/anchor_gain,"change_latent_rms":shift,"support_ok":supported,"chemical_ok":chem,
                        "new_selection_q95":nq,"old_selection_q95":oq,"center_new_delta":cdn,"center_old_delta":cdo,"new_audit_q95":aq["new_audit"],
                        "old_fresh_audit_q95":aq["old_fresh_audit"],"fresh_consistency_passed":bool(basepass and gain>=floor and aq["new_audit"]<=TOL and aq["old_fresh_audit"]<=TOL)})
        print(f"Verified transfer source beer={beer}",flush=True)
```

```
    BASE.same_table(deltas,pd.DataFrame(expected_deltas),["transfer_id","ensemble","model_index"],["delta"],"Every selected paired model delta")
    BASE.same_table(thresholds,pd.DataFrame(expected_thresholds),["transfer_id","scenario","defect"],["source","transferred","cap","passed"],"All selected threshold scenarios")
    keys = ["source_beer","arm","reference","bound"]
    BASE.same_table(rechecks,pd.DataFrame(expected_rechecks),keys,[k for k in expected_rechecks[0] if k not in keys],"Same-rule frozen-spectrum rechecks")
    assert len(spectra)==result.candidate_index.notna().sum()==summary["selected"]
    assert len(thresholds)==len(spectra)*len(scenarios)*len(rules)==summary["threshold_rows"]
    frontier = pd.read_csv(folder/"frontier.csv")
    expected_frontier = []
    def counts(part):
        selected = part.candidate_index.notna(); passing = part.fresh_consistency_passed
        return {"sources":len(part),"selected":selected.sum(),"new_passed":part.new_model_passed.sum(),"fresh_consistency_passed":passing.sum(),
            "historical_consistency_passed":part.historical_consistency_passed.sum(),"no_candidate":(~selected).sum(),
            "median_improvement_selected":part.loc[selected,"target_improvement"].median(),"median_improvement_passed":part.loc[passing,"target_improvement"].median(),
            "median_retention_selected":part.loc[selected,"retained_anchor_gain"].median(),"median_change_rms_selected":part.loc[selected,"change_latent_rms"].median()}
    for (arm,pool,bound,ranking),part in result.groupby(["arm","pool","bound","ranking"]):
        expected_frontier.append({"arm":arm,"pool":pool,"bound":bound,"ranking":ranking,**counts(part)})
    BASE.same_table(frontier,pd.DataFrame(expected_frontier),["arm","pool","bound","ranking"],list(counts(result)),"Complete trade-off frontier")
    assert len(frontier)==summary["frontier_rows"]==72 and len(result)==summary["policies"]
    for key,value in counts(result[result.is_default_policy]).items():
        BASE.close(summary["default_results"][key],value)
    for arm in arms:
        for key,value in counts(result[result.arm.eq(arm)&result.is_arm_default]).items(): BASE.close(summary["arm_defaults"][arm][key],value)
    return {"candidate_geometry_rows":len(geom),"candidate_screening_rows":len(model_checks),"policies":len(result),
            "selected_spectra":len(spectra),"threshold_checks":len(thresholds),"frontier_rows":len(frontier),
            "same_rule_rechecks":len(rechecks),"default":default,"default_counts":summary["default_results"],
            "fixed_control_counts":summary["arm_defaults"]["fixed"],"all_argmins_reconstructed_without_audit":True}


def check_reports(context):
    import xml.etree.ElementTree as ET
    from PIL import Image
    report = SOLUTION/"docs/q3_refinement_results.md"
    assert report.is_file() and report.stat().st_size > 500
    text = report.read_text(encoding="utf-8")
    provenance = BASE.read_json(OUT/"report_sources.json")
    assert len(provenance)==13 and len({r["path"] for r in provenance})==len(provenance)
    for row in provenance:
        path = SOLUTION/row["path"]
        assert hashlib.sha256(path.read_bytes()).hexdigest()==row["sha256"],ro
```

```
w["path"]
        if row["rows"] is not None: assert len(pd.read_csv(path))==row["rows"]
    comparison = pd.read_csv(OUT/"report_tables/prediction_comparison.csv")
    loso = pd.read_csv(OUT/"stale/loso_metrics_overall.csv")
    pils = pd.read_csv(OUT/"stale/pils_diagnostic_metrics.csv")
    expected = loso.merge(pils[["method","rmse","mean_bias"]].rename(columns={
"rmse":"pils_rmse","mean_bias":"pils_bias"}),on="method",validate="one_to_one"
)
    columns = expected.select_dtypes(include=[np.number,bool]).columns.tolist(
)
    BASE.same_table(comparison,expected,["method"],columns,"Report prediction
table")
    transfer = pd.read_csv(OUT/"transfer/transfer_summary.csv")
    retained = pd.read_csv(OUT/"report_tables/retain80_all_policies.csv")
    expected = transfer[transfer.bound.eq("retain80")]
    columns = expected.select_dtypes(include=[np.number,bool]).columns.tolist(
)
    BASE.same_table(retained,expected,["transfer_id"],columns,"Report retained
-gain policy table")
    rechecks = pd.read_csv(OUT/"transfer/fixed_spectra_rechecks.csv")
    expected = rechecks.groupby(["arm","reference","bound"],as_index=False).ag
g(available=("source_beer","size"),passed=("fresh_consistency_passed","sum"),m
edian_gain=("target_improvement","median"))
    expected["sources_denominator"]=len(context["meta"][context["meta"].tastin
g_category_fine.eq("Pils/Lager")])
    BASE.same_table(pd.read_csv(OUT/"report_tables/reference_counts.csv"),expe
cted,["arm","reference","bound"],
                    ["available","passed","median_gain","sources_denominator"]
,"Report same-rule historical comparison")
    summary = BASE.read_json(OUT/"report_summary.json")
    selection = BASE.read_json(OUT/"stale/selection_result.json")
    ts = BASE.read_json(OUT/"transfer/summary.json")
    audit = BASE.read_json(OUT/"beer81/summary.json")
    nested = pd.read_csv(OUT/"stale/nested_metrics.csv").set_index("method")
    metric = pils.set_index("method")
    assert summary["selected_method"]==selection["selected_method"]
    for key,value in {"selected_pils_rmse":metric.at[selection["selected_metho
d"],"rmse"],
                      "tail_candidate_pils_rmse":metric.at["tail_ridge_aging10
0","rmse"],
                      "matched_old_pils_rmse":metric.at["old_multioutput_tree"
,"rmse"],
                      "nested_rule_rmse":nested.at["nested_stability_rule","rm
se"],
                      "beer81_observed":audit["stale_observed"]}.items():
        BASE.close(summary[key],value)
        assert f"{value:.4f}" in text, f"Reported number missing: {key}"
    prediction = pd.read_csv(OUT/"stale/pils_diagnostic_predictions.csv")
    selected81 = prediction[prediction.method.eq(selection["selected_method"])
&prediction.beer.eq(81)].prediction.item()
    BASE.close(summary["beer81_selected_prediction"],selected81)
    assert summary["arm_defaults"]==ts["arm_defaults"] and summary["default_re
sults"]==ts["default_results"]
    assert summary["tail_candidate_eligible"]==bool(loso.set_index("method").a
t["tail_ridge_aging100","eligible_for_one_se"])
    assert summary["candidate_rows"]==len(loso) and summary["frontier_rows"]==
len(pd.read_csv(OUT/"transfer/frontier.csv"))
    for row in comparison.itertuples():
        assert f"|{row.method}|{row.macro_style_rmse:.4f}|{row.rmse:.4f}|{row.
pils_rmse:.4f}|" in text
    frontier = pd.read_csv(OUT/"transfer/frontier.csv")
    for row in frontier[frontier.bound.eq("retain80")].itertuples():
```

```
        assert f"|{row.arm}|{row.pool}|{row.ranking}|{row.selected}|{row.fresh_consistency_passed}|" in text
    figures=[]
    for name in ["beer81_and_prediction","proximity_consistency_grid"]:
        png,svg = OUT/f"figures/{name}.png",OUT/f"figures/{name}.svg"
        with Image.open(png) as im:
            im.verify()
        with Image.open(png) as im:
            assert im.width>=1000 and im.height>=600
        root = ET.parse(svg).getroot()
        assert root.tag.endswith("svg") and len(list(root.iter()))>50
        assert f"figures/{name}.png" in text
        figures.append(name)
    assert summary["figure_pairs"]==len(figures) and summary["source_denominator"]==len(transfer[transfer.is_default_policy])
    return {"report":report.relative_to(SOLUTION).as_posix(),"source_hashes":len(provenance),"candidate_rows":len(comparison),
            "retention_policy_rows":len(retained),"reference_rows":len(expected),"figure_pairs":len(figures),
            "report_tables_and_text_reconciled":True}


def main(output_path=None):
    started = perf_counter()
    checks = {}
    checks["raw_sources"] = BASE.check_hashes()
    checks["frozen_history"] = check_frozen()
    context,checks["data_contract"] = BASE.load_contract()
    checks["beer81"] = check_beer81(context)
    checks["stale_prediction"] = check_stale(context)
    checks["balanced_transfer"] = check_transfer(context)
    checks["final_artifacts"] = check_reports(context)
    assert check_frozen() == checks["frozen_history"]
    result = {"status":"PASS","checks":checks,"elapsed_seconds":perf_counter()-started,
              "scope":"Saved-data provenance, training-only internal validation, model-response constraints and predeclared finite candidate search; no external sensory validation."}
    if output_path is not None:
        output_path = Path(output_path)
        output_path.parent.mkdir(parents=True, exist_ok=True)
        output_path.write_text(json.dumps(result,ensure_ascii=False,indent=2,allow_nan=False)+"\n",encoding="utf-8", newline="\n")
    print(json.dumps(result,ensure_ascii=False,indent=2),flush=True)


if __name__ == "__main__":
    import argparse
    parser = argparse.ArgumentParser(description=__doc__)
    parser.add_argument("--output", type=Path, help="Optional report path; existing results are read-only by default.")
    args = parser.parse_args()
    with threadpool_limits(limits=1): main(args.output)
```

src/common.py

SHA-256: b1b8ef459cfe3b9461efa0310ebe49e9593b655d8e58d2a02f32e7138fc5fa0f

```
"""Shared data contract for the A-track modelling experiments."""
from pathlib import Path

import numpy as np
import pandas as pd
from sklearn.base import BaseEstimator, TransformerMixin

ROOT = Path(__file__).resolve().parents[2]
SOLUTION = ROOT / "solution_a"
SEED = 20261023
KEYS = ["beer", "beer_id", "tasting_category_fine"]
EXCLUDED_TARGETS = ["alcohol", "aftertaste", "body", "co2", "overall"]


class QuantileClipper(TransformerMixin, BaseEstimator):
    """Learn clipping bounds on the training fold; preserve missing entries.""
"

    def __init__(self, lower=0.01, upper=0.99):
        self.lower = lower
        self.upper = upper

    def fit(self, x, y=None):
        values = np.asarray(x, dtype=float)
        self.n_features_in_ = values.shape[1]
        self.bounds_ = np.nanquantile(values, [self.lower, self.upper], axis=0
)
        return self

    def transform(self, x):
        values = np.asarray(x, dtype=float)
        if values.shape[1] != self.n_features_in_:
            raise ValueError("Feature count differs from training")
        return np.clip(values, self.bounds_[0], self.bounds_[1])


def data_dir():
    candidates = list(ROOT.glob("*/2026*赛道A*/附件"))
    if len(candidates) != 1:
        raise ValueError(f"Expected one A-track attachment directory; got {can
didates}")
    return candidates[0]


def resolve_recorded_path(value):
    """Resolve repository-relative provenance and the original machine's paths
."""
    recorded = str(value).replace("\\", "/")
    if recorded.startswith("solution_a/"):
        return ROOT / recorded
    if "/solution_a/" in recorded:
        return SOLUTION / recorded.split("/solution_a/", 1)[1]
    if "/附件/" in recorded:
        return data_dir() / recorded.rsplit("/", 1)[1]
    direct = Path(recorded)
    return direct if direct.is_absolute() else ROOT / direct


def load_xy():
```

```
    """Join by exact beer number, never by the rounded barcodes in 4.csv."""
    chem = pd.read_csv(data_dir() / "1.csv", dtype={"beer_id": str})
    sensory = pd.read_csv(data_dir() / "4.csv", dtype={"beer_id": str})
    for frame in (chem, sensory):
        if frame["beer"].isna().any() or not frame["beer"].is_unique:
            raise ValueError("beer must be a complete, unique sample key")
    if set(chem.beer) != set(sensory.beer):
        raise ValueError("Chemical and sensory populations differ")
    sensory = sensory.set_index("beer").loc[chem.beer].reset_index()
    if not chem.tasting_category_fine.equals(sensory.tasting_category_fine):
        raise ValueError("Styles disagree after joining by beer")
    features = [c for c in chem if c not in KEYS]
    targets = [c for c in sensory if c not in KEYS + EXCLUDED_TARGETS]
    x = chem[features].apply(pd.to_numeric, errors="raise")
    y = sensory[targets].apply(pd.to_numeric, errors="raise")
    if y.isna().any().any():
        raise ValueError("Missing labels need target-specific training, not im
putation")
    return chem[KEYS], x, y
```

src/platform_selfcheck.py

SHA-256: 35df4e836b8fb2d968dca1e679f27f3e1ebb97dd5bb9a93b70a1fd0a4b1c702b

```
"""Check portable paths, source hashes and frozen-history tamper detection."""
import hashlib
import importlib
import io
import json
import os
from pathlib import Path, PurePosixPath, PureWindowsPath
import sys
import tempfile
import unittest
from unittest.mock import patch

from common import SOLUTION, resolve_recorded_path
import common

sys.path.insert(0, str(SOLUTION))
OPTIMIZED = importlib.import_module("run_q3_optimized")
REFINED = importlib.import_module("run_q3_refined")
RUNNER = importlib.import_module("run_all")


class PlatformChecks(unittest.TestCase):
    def test_working_directory_cannot_shadow_project_sources(self):
        with tempfile.TemporaryDirectory(prefix="mathorcup-paths-") as tempora
ry:
            project, shadow = Path(temporary) / "project", Path(temporary) / "
shadow"
            for folder, data in [(project, b"project source"), (shadow, b"unre
lated source")]:
                (folder / "solution_a").mkdir(parents=True)
                (folder / "solution_a/example.txt").write_bytes(data)
            previous = Path.cwd()
            try:
                os.chdir(shadow)
                with patch.object(common, "ROOT", project), patch.object(commo
n, "SOLUTION", project / "solution_a"):
                    expected = project / "solution_a/example.txt"
                    self.assertEqual(resolve_recorded_path("solution_a/example
.txt"), expected)
                    self.assertEqual(resolve_recorded_path("/Users/old/repo/so
lution_a/example.txt"), expected)
            finally:
                os.chdir(previous)

    def test_rebuild_refuses_existing_results(self):
        with tempfile.TemporaryDirectory(prefix="mathorcup-runner-") as tempor
ary:
            root = Path(temporary)
            (root / "outputs").mkdir()
            saved = root / "outputs/saved.txt"
            saved.write_bytes(b"preserve this result")
            with patch.object(RUNNER, "HERE", root), patch.object(RUNNER, "run
") as execute:
                with patch.object(sys, "argv", ["run_all.py", "--rebuild"]), p
atch.object(sys, "stderr", io.StringIO()):
                    with self.assertRaises(SystemExit) as error:
                        RUNNER.main()
                self.assertEqual(error.exception.code, 2)
                execute.assert_not_called()
```

```
            self.assertEqual(saved.read_bytes(), b"preserve this result")

    def test_clean_rebuild_orders_every_phase(self):
        with tempfile.TemporaryDirectory(prefix="mathorcup-runner-") as tempor
ary:
            with patch.object(RUNNER, "HERE", Path(temporary)), patch.object(R
UNNER, "run") as execute:
                with patch.object(sys, "argv", ["run_all.py", "--rebuild"]):
                    RUNNER.main()
                phases = [call.args[0] for call in execute.call_args_list]
            self.assertEqual(phases, ["01_audit.py", "02_q1_baseline.py", "02b
_q1_robust.py",
                                      "03_q2_network.py", "04_stage_summary.py
", "05_verify_outputs.py",
                                      "run_q3.py", "run_q3_optimized.py", "run
_q3_domain.py", "run_q3_refined.py", "run_supplement.py"])

    def test_rebuild_refuses_existing_supplement(self):
        with tempfile.TemporaryDirectory(prefix="mathorcup-supplement-") as te
mporary:
            root = Path(temporary)
            saved = root / "supplement/results/sentinel.csv"
            saved.parent.mkdir(parents=True)
            saved.write_bytes(b"preserve supplementary results")
            with patch.object(RUNNER, "HERE", root), patch.object(RUNNER, "run
") as execute:
                with patch.object(sys, "argv", ["run_all.py", "--rebuild"]), p
atch.object(sys, "stderr", io.StringIO()):
                    with self.assertRaises(SystemExit):
                        RUNNER.main()
                execute.assert_not_called()
            self.assertEqual(saved.read_bytes(), b"preserve supplementary resu
lts")

    def test_portable_relative_paths(self):
        self.assertEqual(PureWindowsPath(r"stale\summary.json").as_posix(),
                         PurePosixPath("stale/summary.json").as_posix())

    def test_all_three_frozen_histories(self):
        snapshots = [SOLUTION / "outputs" / name for name in
                     ["q3_optimized/baseline_hashes.json", "q3_domain/previous
_hashes.json",
                      "q3_refined/previous_hashes.json"]]
        before = [path.read_bytes() for path in snapshots]
        REFINED.preserve_refined()
        self.assertEqual(before, [path.read_bytes() for path in snapshots])

    def test_recorded_sources_resolve_and_match(self):
        manifest = SOLUTION / "outputs/q3_refined/beer81/source_manifest.json"
        for row in json.loads(manifest.read_text(encoding="utf-8")):
            path = resolve_recorded_path(row["path"])
            self.assertTrue(path.is_file(), row["path"])
            self.assertEqual(hashlib.sha256(path.read_bytes()).hexdigest(), ro
w["sha256"])

    def test_changed_file_is_rejected(self):
        with tempfile.TemporaryDirectory(prefix="mathorcup-freeze-") as tempor
ary:
            root = Path(temporary)
            baseline, snapshot = root / "q3", root / "snapshot.json"
            target = baseline / "stale/summary.json"
            target.parent.mkdir(parents=True)
```

```
            target.write_text('{"label":"检验"}\n', encoding="utf-8", newline="\n")
            raw = target.read_bytes()
            record = {"files": [{"path": "stale/summary.json", "bytes": len(raw),
                                 "sha256": hashlib.sha256(raw).hexdigest()}]}
            (baseline / "verification.json").write_text("{}\n", encoding="utf-8", newline="\n")
            raw_verification = (baseline / "verification.json").read_bytes()
            record["files"].append({"path": "verification.json", "bytes": len(raw_verification),
                                    "sha256": hashlib.sha256(raw_verification).hexdigest()})
            snapshot.write_text(json.dumps(record), encoding="utf-8", newline="\n")
            with patch.object(OPTIMIZED, "BASELINE", baseline), patch.object(OPTIMIZED, "SNAPSHOT", snapshot):
                OPTIMIZED.preserve_baseline()
                target.write_bytes(raw + b" ")
                with self.assertRaisesRegex(RuntimeError, "frozen baseline has changed"):
                    OPTIMIZED.preserve_baseline()


if __name__ == "__main__":
    unittest.main(verbosity=2)
```

src/q3_copula.py

SHA-256: 1d5e21ca13654b7724a87f7590615cfc809a3061a8970c0e81475993c7763b73

```
"""Small-sample style conditional Gaussian copula in the mixed Q3 feature spac
e."""
import numpy as np
import pandas as pd
from scipy.linalg import solve_triangular
from scipy.special import ndtr, ndtri
from sklearn.covariance import LedoitWolf


class ConditionalGaussianCopula:
    """Empirical margins, shrunken style means, and positive definite covarian
ces.

    ``fit`` learns *all* preprocessing from its input rows. Missing entries ar
e
    replaced by training medians. The inverse empirical CDF returns observed
    column values, so zeros and ties have explicit probability intervals rathe
r
    than being replaced by interpolated concentrations. Their generated
    frequencies need not equal empirical frequencies after conditioning and
    the latent Gaussian approximation. Sampling creates new
    combinations, not necessarily new individual measurement values.

    ``sample(None, ...)`` is the unconditional copula comparison. ``distance``
    is sqrt(Mahalanobis squared / number of features); its fitted training
    reference must be used to interpret it, not a chi-square calibration.
    """

    def __init__(self, mean_strength=5.0, cov_strength=20.0):
        if mean_strength < 0 or cov_strength < 0:
            raise ValueError("Shrinkage strengths must be nonnegative")
        self.mean_strength = float(mean_strength)
        self.cov_strength = float(cov_strength)

    def _array(self, x):
        if isinstance(x, pd.DataFrame):
            missing = set(self.columns_) - set(x.columns)
            extra = set(x.columns) - set(self.columns_)
            if missing or extra:
                raise ValueError(f"Feature mismatch: missing={missing}, extra=
{extra}")
            values = x.loc[:, self.columns_].to_numpy(dtype=float)
        else:
            values = np.asarray(x, dtype=float)
        if values.ndim != 2 or values.shape[1] != len(self.columns_):
            raise ValueError("Expected a matrix with the fitted feature count"
)
        if np.isinf(values).any():
            raise ValueError("Infinite chemical measurements are unsupported")
        return values

    def impute(self, x):
        values = self._array(x)
        return np.where(np.isnan(values), self.median_, values)

    @staticmethod
    def _regularized_covariance(z, assume_centered=False):
        if len(z) > 1:
            covariance = LedoitWolf(assume_centered=assume_centered).fit(z).co
```

```
variance_
        else:
            covariance = np.eye(z.shape[1])
        # A tiny explicit ridge also handles completely constant columns.
        ridge = 1e-6 * max(float(np.trace(covariance) / len(covariance)), 1.0)
        return (covariance + covariance.T) / 2 + ridge * np.eye(z.shape[1])

    def fit(self, x, styles):
        if not isinstance(x, pd.DataFrame) or not x.columns.is_unique:
            raise ValueError("fit requires a DataFrame with unique feature nam
es")
        self.columns_ = x.columns.tolist()
        values = self._array(x)
        labels = np.asarray(styles, dtype=str)
        if labels.ndim != 1 or len(labels) != len(values) or len(values) < 2:
            raise ValueError("One style per row and at least two training rows
 required")
        if np.isnan(values).all(axis=0).any():
            raise ValueError("A feature is completely missing in this training
 fold")
        self.median_ = np.nanmedian(values, axis=0)
        values = np.where(np.isnan(values), self.median_, values)
        self.n_features_in_ = values.shape[1]
        self.n_samples_ = len(values)
        self.empirical_values_ = []
        self.empirical_midprob_ = []
        self.empirical_cumprob_ = []
        for column in values.T:
            unique, counts = np.unique(column, return_counts=True)
            cumulative = counts.cumsum() / len(column)
            midpoint = (counts.cumsum() - counts / 2) / len(column)
            self.empirical_values_.append(unique)
            self.empirical_midprob_.append(midpoint)
            self.empirical_cumprob_.append(cumulative)
        z = self.transform(x)
        self.global_center_ = z.mean(axis=0)
        self.global_cov_ = self._regularized_covariance(z)
        self.global_cholesky_ = np.linalg.cholesky(self.global_cov_)
        self.style_counts_ = {s: int(np.sum(labels == s)) for s in np.unique(l
abels)}
        raw_centers = {s: z[labels == s].mean(axis=0) for s in self.style_coun
ts_}
        residuals = np.vstack([z[labels == s] - raw_centers[s]
                               for s in self.style_counts_])
        self.pooled_within_cov_ = self._regularized_covariance(
            residuals, assume_centered=True)
        self.style_center_ = {}
        self.style_cov_ = {}
        self.style_cholesky_ = {}
        self.fit_diagnostics_ = []
        for style, count in self.style_counts_.items():
            a = count / (count + self.mean_strength)
            b = count / (count + self.cov_strength)
            center = a * raw_centers[style] + (1 - a) * self.global_center_
            local_cov = self._regularized_covariance(z[labels == style])
            covariance = b * local_cov + (1 - b) * self.pooled_within_cov_
            self.style_center_[style] = center
            self.style_cov_[style] = covariance
            self.style_cholesky_[style] = np.linalg.cholesky(covariance)
            self.fit_diagnostics_.append({
                "style": style, "n": count, "mean_local_weight": a,
                "cov_local_weight": b,
```

```
                "minimum_cov_eigenvalue": float(np.linalg.eigvalsh(covariance)
[0]),
            })
        return self

    def transform(self, x):
        values = self.impute(x)
        z = np.empty_like(values)
        # Mid-CDF is exact at observed ties. Linear interpolation is used only
        # to score intermediate inputs (e.g. projected migration candidates).
        tail = 0.5 / self.n_samples_
        for j in range(values.shape[1]):
            probability = np.interp(values[:, j], self.empirical_values_[j],
                                    self.empirical_midprob_[j])
            z[:, j] = ndtri(np.clip(probability, tail, 1 - tail))
        return z

    def inverse_transform(self, z):
        latent = np.asarray(z, dtype=float)
        if latent.ndim != 2 or latent.shape[1] != self.n_features_in_:
            raise ValueError("Latent feature count differs from training")
        probabilities = ndtr(latent)
        values = np.empty_like(latent)
        for j in range(latent.shape[1]):
            indices = np.searchsorted(self.empirical_cumprob_[j],
                                      probabilities[:, j], side="left")
            indices = np.minimum(indices, len(self.empirical_values_[j]) - 1)
            values[:, j] = self.empirical_values_[j][indices]
        return pd.DataFrame(values, columns=self.columns_)

    def sample(self, style, n=300, seed=20261023):
        if n < 1:
            raise ValueError("At least one sample is required")
        center = self.global_center_ if style is None else self.style_center_[
style]
        chol = self.global_cholesky_ if style is None else self.style_cholesky
_[style]
        z = np.random.default_rng(seed).normal(size=(n, self.n_features_in_))
        return self.inverse_transform(center + z @ chol.T)

    def distance(self, x, style=None):
        center = self.global_center_ if style is None else self.style_center_[
style]
        chol = self.global_cholesky_ if style is None else self.style_cholesky
_[style]
        residual = (self.transform(x) - center).T
        whitened = solve_triangular(chol, residual, lower=True, check_finite=F
alse)
        return np.sqrt(np.mean(whitened ** 2, axis=0))
```

src/q3_data.py

SHA-256: 00f645b5502651a2f4f57998c9286d38ef35ac8e6320c99455afd3a6a300a7f7

```
"""Explicit hybrid chemical representation shared by the question-3 models.

This module reads attachments without modifying them or fitting preprocessing.
"""
from __future__ import annotations

import numpy as np
import pandas as pd

from common import KEYS, data_dir, load_xy

DERIVED_FEATURES = (
    "kcalperc", "esters_sum", "aroma_hops_sum", "acids_sum", "sulfur_sum"
)
DEFECT_FEATURES = ("DMS", "X2.3.butanedione", "X4VG", "X.E..2.nonenal")
DEFECT_FIELD_MAP = {
    "DMS": "DMS",
    "Diacetyl": "X2.3.butanedione",
    "4VG": "X4VG",
    "trans_2_nonenal": "X.E..2.nonenal",
}


def read_defect_thresholds() -> dict:
    """Read exact field matches and threshold units from attachment 8.

    Missing thresholds are Python None, deliberately not inferred or imported
    from external sources. Values are in the calibrated representation only.
    """
    table = pd.read_excel(data_dir() / "8.xlsx", sheet_name="Sensory threshold
s")
    if table["field_name_R"].duplicated().any():
        raise ValueError("Ambiguous sensory-threshold field names")
    table = table.set_index("field_name_R")
    result = {}
    for label, feature in DEFECT_FIELD_MAP.items():
        row = table.loc[feature]
        result[label] = {
            "feature": feature,
            "chemical_name": str(row["chemical_name"]),
            "unit": str(row["unit"]) if pd.notna(row["unit"]) else None,
            "threshold_median": float(row["threshold_median"])
            if pd.notna(row["threshold_median"]) else None,
            "threshold_mean": float(row["threshold_mean"])
            if pd.notna(row["threshold_mean"]) else None,
            "threshold_source": "8.xlsx / Sensory thresholds / exact field_nam
e_R",
        }
    return result


# Exported immutable-by-convention attachment metadata for downstream scripts.
DEFECTS = read_defect_thresholds()


def load_q3_data() -> tuple[pd.DataFrame, pd.DataFrame, pd.DataFrame, pd.DataF
rame]:
    """Return identity metadata, 226 raw hybrid features, 45 targets, manifest
.
```

```
56
57      Rows and features preserve load_xy()/1.csv order. The 69 overlapping,
58      non-derived calibrated indicators replace their 1.csv representations by
59      exact beer key. The remaining 157 variables keep their supplied 1.csv
60      representations. Calibrated negatives become missing; relative negatives
61      are retained because their transformation/zero point is not identified.
62      No imputation, standardization or fitted data transformation occurs here.
63      """
64      meta, original, y = load_xy()
65      workbook = data_dir() / "8.xlsx"
66      calibrated = pd.read_excel(workbook, sheet_name="Calibrated chemical datas
    et")
67      thresholds = pd.read_excel(workbook, sheet_name="Sensory thresholds")
68      if calibrated["beer"].isna().any() or not calibrated["beer"].is_unique:
69          raise ValueError("Calibrated beer keys must be complete and unique")
70      if set(calibrated["beer"]) != set(meta["beer"]):
71          raise ValueError("Original and calibrated sample populations differ")
72      calibrated = calibrated.set_index("beer").loc[meta["beer"]].reset_index()
73      if not calibrated["tasting_category_fine"].equals(meta["tasting_category_f
    ine"]):
74          raise ValueError("Calibrated styles disagree after exact beer join")
75      if thresholds["field_name_R"].duplicated().any():
76          raise ValueError("Unit metadata must have unique exact field names")
77      unit_map = thresholds.set_index("field_name_R")["unit"].to_dict()
78      features = [feature for feature in original if feature not in DERIVED_FEAT
    URES]
79      calibrated_features = [feature for feature in calibrated if feature not in
     KEYS
80                             and feature not in DERIVED_FEATURES]
81      if not set(calibrated_features).issubset(features):
82          raise ValueError("Calibrated indicators are absent from 1.csv")
83      if len(features) != 226 or len(calibrated_features) != 69:
84          raise ValueError("Attachment shape differs from verified 226/69 contra
    ct")
85      x = original.loc[:, features].copy()
86      records = []
87      for position, feature in enumerate(features):
88          is_calibrated = feature in calibrated_features
89          values = pd.to_numeric(calibrated[feature] if is_calibrated
90                                 else original[feature], errors="raise").copy()
91          original_missing = int(values.isna().sum())
92          if np.isinf(values.to_numpy(dtype=float)).any():
93              raise ValueError(f"Infinite attachment feature: {feature}")
94          negative = values.lt(0) if is_calibrated else pd.Series(False, index=v
    alues.index)
95          values.loc[negative] = np.nan
96          x.loc[:, feature] = values.to_numpy()
97          raw_unit = unit_map.get(feature)
98          unit_available = is_calibrated and pd.notna(raw_unit)
99          records.append({
100             "position": position,
101             "feature": feature,
102             "representation": "calibrated" if is_calibrated else "relative",
103             "unit": str(raw_unit) if unit_available else
104                     ("not_provided_in_attachment" if is_calibrated
105                      else "supplied_relative_or_transformed_units"),
106             "unit_source": "8.xlsx / Sensory thresholds / exact field_name_R"
107                            if unit_available else "unidentified",
108             "source": "8.xlsx / Calibrated chemical dataset" if is_calibrated
    else "1.csv",
109             "original_missing_count": original_missing,
110             "original_1csv_missing_count": int(original[feature].isna().sum())
```

```
,
            "negative_invalid_count": int(negative.sum()),
            "final_missing_count": int(values.isna().sum()),
            "zero_count": int(values.eq(0).sum()),
            "negative_policy": "replace_with_NaN" if is_calibrated else "retai
n_supplied_representation",
            "is_defect_concentration": feature in DEFECT_FEATURES,
        })
    manifest = pd.DataFrame(records)
    if x.shape != (250, 226) or y.shape != (250, 45):
        raise ValueError("Unexpected question-3 input or target dimensions")
    if manifest["representation"].value_counts().to_dict() != {"relative": 157
, "calibrated": 69}:
        raise AssertionError("Hybrid representation count mismatch")
    return meta.loc[:, KEYS].copy(), x, y.copy(), manifest
```

src/q3_generator_optimized.py

SHA-256: 3d7f1004577298d5ecdd2ad9b7e0bbd2f299d863eff699fc45c047d279785156

```
"""Nested selection of small-sample generators with style-specific margins."""
import numpy as np
import pandas as pd
from scipy.special import ndtr, ndtri
from scipy.spatial.distance import cdist
from sklearn.covariance import LedoitWolf
from sklearn.decomposition import PCA
from sklearn.model_selection import StratifiedKFold

from q3_copula import ConditionalGaussianCopula


EVALUATION_STYLES = ("Tripel", "Kriek", "Lambic", "Pils/Lager")
CANDIDATE_METHODS = ("style_margin_copula", "style_smoothed_mixture", "legacy_copula")
MIN_INNER_NN_RATIO = 0.35
MAX_INNER_MATCH_FRACTION = 0.95
SMOOTHING_NOISE = 0.45


def empirical_tables(values):
    unique_values, midpoints, cumulative = [], [], []
    for column in values.T:
        unique, counts = np.unique(column, return_counts=True)
        unique_values.append(unique)
        midpoints.append((counts.cumsum() - counts / 2) / len(column))
        cumulative.append(counts.cumsum() / len(column))
    return unique_values, midpoints, cumulative


def normal_scores(values, tables):
    z = np.empty_like(values, dtype=float)
    for j, (unique, midpoints) in enumerate(zip(tables[0], tables[1])):
        z[:, j] = ndtri(np.interp(values[:, j], unique, midpoints))
    return z


def regularized_correlation(z):
    if len(z) < 2 or np.max(np.abs(z)) < 1e-12:
        return np.eye(z.shape[1])
    covariance = LedoitWolf().fit(z).covariance_
    covariance += 1e-6 * np.eye(z.shape[1])
    scale = np.sqrt(np.diag(covariance))
    correlation = covariance / scale[:, None] / scale[None, :]
    return (correlation + correlation.T) / 2


class StyleMarginCopula:
    """Use per-style inverse empirical margins and shrunken dependence.

    ``mode='copula'`` uses a zero-mean, unit-marginal Gaussian whose covariance
    mixes local and shared style-rank correlations. ``mode='smoothed'`` draws
    an empirical style row in normal-score space and adds correlated noise
    with fixed standard deviation 0.45. It smooths empirical combinations,
    rather than choosing an almost-zero perturbation to avoid exact copies.

    Zeros have probability intervals in the inverse CDF. Gaussian mode has
    standard-normal latent margins, so empirical zero rates are preserved in
```

```
    expectation; smoothed mode need not reproduce them exactly.
    """

    def __init__(self, mode="copula", cov_strength=10.0, noise=SMOOTHING_NOISE
):
        if mode not in ("copula", "smoothed"):
            raise ValueError("Unknown style-margin generation mode")
        self.mode = mode
        self.cov_strength = float(cov_strength)
        self.noise = float(noise)

    def fit(self, x, styles):
        self.columns_ = x.columns.tolist()
        values = x.to_numpy(dtype=float)
        labels = np.asarray(styles, dtype=str)
        self.global_median_ = np.nanmedian(values, axis=0)
        if np.isnan(self.global_median_).any() or np.isinf(values).any():
            raise ValueError("A feature is entirely missing or infinite")
        self.tables_, self.style_scores_, self.style_median_ = {}, {}, {}
        self.style_counts_ = {}
        for style in np.unique(labels):
            local = values[labels == style]
            median = np.array([np.median(c[np.isfinite(c)]) if np.isfinite(c).
any()
                               else self.global_median_[j] for j, c in enumera
te(local.T)])
            local = np.where(np.isnan(local), median, local)
            self.style_median_[style] = median
            self.tables_[style] = empirical_tables(local)
            self.style_scores_[style] = normal_scores(local, self.tables_[styl
e])
            self.style_counts_[style] = len(local)
        pooled = np.vstack(list(self.style_scores_.values()))
        self.shared_correlation_ = regularized_correlation(pooled)
        self.style_correlation_, self.style_cholesky_ = {}, {}
        for style, scores in self.style_scores_.items():
            weight = len(scores) / (len(scores) + self.cov_strength)
            correlation = (weight * regularized_correlation(scores)
                           + (1 - weight) * self.shared_correlation_)
            self.style_correlation_[style] = correlation
            self.style_cholesky_[style] = np.linalg.cholesky(correlation)
        return self

    def sample(self, style, n=300, seed=20261123):
        if n < 1:
            raise ValueError("At least one sample is required")
        rng = np.random.default_rng(seed)
        z = rng.normal(size=(n, len(self.columns_))) @ self.style_cholesky_[st
yle].T
        if self.mode == "smoothed":
            centers = self.style_scores_[style]
            indices = rng.integers(0, len(centers), size=n)
            z = centers[indices] + self.noise * z
        probability = ndtr(z)
        values = np.empty_like(z)
        unique, _, cumulative = self.tables_[style]
        for j in range(values.shape[1]):
            indices = np.searchsorted(cumulative[j], probability[:, j], side="
left")
            values[:, j] = unique[j][np.minimum(indices, len(unique[j]) - 1)]
        return pd.DataFrame(values, columns=self.columns_)

```

```

def fit_candidates(x, labels):
    legacy = ConditionalGaussianCopula(5.0, 20.0).fit(x, labels)
    copula = StyleMarginCopula(mode="copula").fit(x, labels)
    # Both families have identical fitted margins and covariance; reuse fitted
    # arrays and change only the declared sampling kernel.
    mixture = StyleMarginCopula(mode="smoothed")
    mixture.__dict__.update(copula.__dict__)
    mixture.mode = "smoothed"
    return {"style_margin_copula": copula, "style_smoothed_mixture": mixture,
            "legacy_copula": legacy}


def selection_metrics(reference_model, pca, pc_scale, style_train, heldout, ge
nerated):
    train_z = reference_model.transform(style_train)
    real_z = reference_model.transform(heldout)
    fake_z = reference_model.transform(generated)
    real_pc, fake_pc = pca.transform(real_z) / pc_scale, pca.transform(fake_z)
 / pc_scale
    energy = float(2 * cdist(real_pc, fake_pc).mean()
                   - cdist(real_pc, real_pc).mean() - cdist(fake_pc, fake_pc).
mean())
    distances = cdist(fake_z, train_z) / np.sqrt(train_z.shape[1])
    nn = distances.min(axis=1)
    real_nn = cdist(real_z, train_z).min(axis=1) / np.sqrt(train_z.shape[1])
    nearest = distances.argmin(axis=1)
    fake = reference_model.impute(generated)
    training = reference_model.impute(style_train)[nearest]
    equal_fraction = np.isclose(fake, training, rtol=1e-10, atol=1e-12).mean(a
xis=1)
    observed = style_train.to_numpy(dtype=float)
    copied_observed = (np.isclose(fake[:, None, :], observed[None, :, :],
                                  rtol=1e-10, atol=1e-12)
                       | np.isnan(observed)[None, :, :]).all(axis=2).any(axis=
1)
    return {"energy_pca5": energy,
            "nn_ratio": float(np.median(nn) / max(np.median(real_nn), 1e-12)),
            "copy_rate": float(np.mean(nn < 1e-12)),
            "observed_training_copy_rate": float(copied_observed.mean()),
            "nearest_equal_feature_fraction": float(np.median(equal_fraction))
}


class OptimizedStyleGenerator:
    """Choose one of three fixed generators using training-only inner folds.

    Inner validation uses two folds stratified across every training style.
    The generator for each of the four evaluation styles minimizes inner
    five-dimensional energy distance, subject to no exact copies, NN ratio
    >= 0.35, and median matching fraction <= 0.95 in every inner fold.
    Other styles default to the legacy generator. Bootstrap is evaluated as a
    benchmark but is excluded from selection because it is a copying model.
    """

    def __init__(self, selection_seed=20261123, inner_n_generated=300):
        self.selection_seed = int(selection_seed)
        self.inner_n_generated = int(inner_n_generated)

    def fit(self, x, styles):
        self.columns_ = x.columns.tolist()
        labels = pd.Series(np.asarray(styles, dtype=str), index=x.index)
```

```
        if labels.value_counts().min() < 2:
            raise ValueError("Inner stratified two-fold requires two rows per training style")
        selected_styles = [style for style in EVALUATION_STYLES if style in set(labels)]
        records = []
        splitter = StratifiedKFold(n_splits=2, shuffle=True, random_state=self.selection_seed)
        for fold, (train, validation) in enumerate(splitter.split(x, labels), start=1):
            inner_train = x.iloc[train]
            inner_labels = labels.iloc[train]
            fitted = fit_candidates(inner_train, inner_labels)
            reference = fitted["legacy_copula"]
            train_z = reference.transform(inner_train)
            pca = PCA(n_components=min(5, len(train_z) - 1), svd_solver="full").fit(train_z)
            pc_scale = np.maximum(np.sqrt(pca.explained_variance_), 1e-8)
            for style_index, style in enumerate(selected_styles):
                training_style = inner_train.loc[inner_labels == style]
                heldout = x.iloc[validation].loc[labels.iloc[validation] == style]
                for method, candidate in fitted.items():
                    seed = self.selection_seed + fold * 1000 + style_index * 10
                    generated = candidate.sample(style, self.inner_n_generated, seed)
                    metrics = selection_metrics(reference, pca, pc_scale, training_style, heldout, generated)
                    eligible = (metrics["copy_rate"] == 0
                                and metrics["observed_training_copy_rate"] == 0
                                and metrics["nn_ratio"] >= MIN_INNER_NN_RATIO
                                and metrics["nearest_equal_feature_fraction"] <= MAX_INNER_MATCH_FRACTION)
                    records.append({"inner_fold": fold, "style": style, "method": method,
                                    "seed": seed, "train_n_style": len(training_style),
                                    "validation_n_style": len(heldout), "eligible": eligible, **metrics})
        self.inner_scores_ = pd.DataFrame(records)
        self.selected_methods_ = {style: "legacy_copula" for style in labels.unique()}
        self.selection_table_ = []
        for style in selected_styles:
            subset = self.inner_scores_.loc[self.inner_scores_["style"] == style]
            grouped = subset.groupby("method").agg(energy_pca5=("energy_pca5", "mean"),
                eligible=("eligible", "all"), worst_nn_ratio=("nn_ratio", "min"),
                largest_matching_fraction=("nearest_equal_feature_fraction", "max"))
            accepted = grouped.loc[grouped.eligible]
            if len(accepted):
                selected = accepted.energy_pca5.idxmin()
                status = "selected_by_training_only_inner_energy_with_novelty_gates"
            else:
                selected = "legacy_copula"
                status = "no_candidate_passed_inner_gates_legacy_fallback_requ
```

```
ires_diagnostics"
            self.selected_methods_[style] = selected
            for method, row in grouped.iterrows():
                self.selection_table_.append({"style": style, "method": method
,
                    "selected": method == selected, "selection_status": status
, **row.to_dict()})
        self.fitted_candidates_ = fit_candidates(x, labels)
        return self

    def sample(self, style, n=300, seed=20261123):
        if style is None:
            return self.fitted_candidates_["legacy_copula"].sample(None, n, se
ed)
        return self.fitted_candidates_[self.selected_methods_[style]].sample(s
tyle, n, seed)
```

src/q3_stale_domain.py

SHA-256: 6d0be013ea3249f3ff95cd212e7011414796569d32eebd6fbdf26b412830e1c9

```
"""Style-held-out stale-hops candidates with chemical-only prediction inputs."
""
from __future__ import annotations

import numpy as np
from scipy.spatial.distance import cdist
from sklearn.base import BaseEstimator, RegressorMixin
from sklearn.decomposition import PCA
from sklearn.dummy import DummyRegressor
from sklearn.ensemble import ExtraTreesRegressor
from sklearn.impute import SimpleImputer
from sklearn.kernel_ridge import KernelRidge
from sklearn.linear_model import Ridge
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import StandardScaler
from sklearn.svm import SVR

from q3_stale_optimized import FoldChemicalTransform

BIAS_PENALTY = 0.25
VARIANCE_RATIO_MIN = 0.05
LOSO_SEED = 20270123
FINAL_SEED = 20271123
SELECTION_BOOTSTRAP_SEED = 20272123
AUDIT_BOOTSTRAP_SEED = 20273123


def style_balanced_weights(styles):
    """Each observed training style receives equal total regression weight."""
    values = np.asarray(styles)
    _, inverse, counts = np.unique(values, return_inverse=True, return_counts=
True)
    return len(values) / (len(counts) * counts[inverse])


class CenteredKernelRidge(RegressorMixin, BaseEstimator):
    """RBF ridge with a training-only weighted target mean for far points."""
    def __init__(self, alpha=1.0, gamma_factor=0.1):
        self.alpha = alpha
        self.gamma_factor = gamma_factor

    def fit(self, x, y, sample_weight=None):
        values = np.asarray(x, dtype=float)
        target = np.asarray(y, dtype=float).reshape(-1)
        self.target_mean_ = float(np.average(target, weights=sample_weight))
        self.n_features_in_ = values.shape[1]
        self.model_ = KernelRidge(alpha=self.alpha, kernel="rbf",
                                  gamma=self.gamma_factor / self.n_features_in
_)
        self.model_.fit(values, target - self.target_mean_, sample_weight=samp
le_weight)
        return self

    def predict(self, x):
        return self.target_mean_ + self.model_.predict(np.asarray(x, dtype=flo
at))


class StyleWeightedLocalMean(RegressorMixin, BaseEstimator):
```

```
    """Local chemical neighbours, inverse distance times training-style weight."""
    def __init__(self, n_neighbors=25):
        self.n_neighbors = n_neighbors

    def fit(self, x, y, sample_weight=None):
        self.x_ = np.asarray(x, dtype=float)
        self.y_ = np.asarray(y, dtype=float).reshape(-1)
        self.sample_weight_ = np.ones(len(self.y_)) if sample_weight is None else np.asarray(sample_weight)
        self.n_features_in_ = self.x_.shape[1]
        return self

    def predict(self, x):
        values = np.asarray(x, dtype=float)
        result = np.empty(len(values))
        k = min(self.n_neighbors, len(self.y_))
        for start in range(0, len(values), 2048):
            distances = cdist(values[start:start+2048], self.x_)
            for local, row in enumerate(distances):
                exact = row <= 1e-12
                if exact.any():
                    result[start + local] = np.average(self.y_[exact], weights=self.sample_weight_[exact])
                else:
                    indices = np.argpartition(row, k-1)[:k]
                    weights = self.sample_weight_[indices] / np.maximum(row[indices], 1e-12)
                    result[start + local] = np.average(self.y_[indices], weights=weights)
        return result


class EqualDomainEnsemble(RegressorMixin, BaseEstimator):
    """A fixed equal-weight average; no stacking or fitted mixture weights."""
    def __init__(self, features, calibrated_features, aging_features, member_specs, seed):
        self.features = features
        self.calibrated_features = calibrated_features
        self.aging_features = aging_features
        self.member_specs = member_specs
        self.seed = seed

    def fit(self, x, y, sample_weight=None):
        self.models_ = []
        for spec in self.member_specs:
            model = make_domain_pipeline(spec, self.features, self.calibrated_features,
                                         self.aging_features, self.seed)
            params = {"model__sample_weight": sample_weight} if sample_weight is not None else {}
            model.fit(x, y, **params)
            self.models_.append(model)
        self.n_features_in_ = len(self.features)
        return self

    def predict(self, x):
        return np.mean([np.asarray(model.predict(x)).reshape(-1) for model in self.models_], axis=0)


def domain_candidate_specs():
```

```
    """Freeze 14 comparisons before any new LOSO or Pils diagnostic results."""
    specs = [
        {"name": "mean_global", "family": "mean", "balanced": False, "selectable": False},
        {"name": "mean_style_balanced", "family": "mean", "balanced": True, "selectable": False},
        {"name": "old_multioutput_tree", "family": "old_multioutput", "balanced": False, "selectable": False},
        {"name": "fixed_single_tree", "family": "tree", "balanced": False, "selectable": True},
        {"name": "style_balanced_tree", "family": "tree", "balanced": True, "selectable": True},
        {"name": "ridge_all_balanced_100", "family": "ridge", "feature_set": "all226", "alpha": 100.0, "balanced": True, "selectable": True},
        {"name": "ridge_all_balanced_1000", "family": "ridge", "feature_set": "all226", "alpha": 1000.0, "balanced": True, "selectable": True},
        {"name": "ridge_aging_balanced_10", "family": "ridge", "feature_set": "aging", "alpha": 10.0, "balanced": True, "selectable": True},
        {"name": "ridge_aging_balanced_100", "family": "ridge", "feature_set": "aging", "alpha": 100.0, "balanced": True, "selectable": True},
        {"name": "krr_aging_balanced_g01", "family": "krr", "feature_set": "aging", "alpha": 1.0, "gamma_factor": 0.1, "balanced": True, "selectable": True},
        {"name": "krr_aging_balanced_g1", "family": "krr", "feature_set": "aging", "alpha": 1.0, "gamma_factor": 1.0, "balanced": True, "selectable": True},
        {"name": "svr_aging_balanced_C1", "family": "svr", "feature_set": "aging", "C": 1.0, "epsilon": 0.05, "balanced": True, "selectable": True},
        {"name": "local_aging_pca8_k25", "family": "local", "feature_set": "aging", "n_components": 8, "n_neighbors": 25, "balanced": True, "selectable": True},
    ]
    ensemble_names = ["style_balanced_tree", "ridge_aging_balanced_100", "krr_aging_balanced_g01"]
    specs.append({"name": "ensemble_equal3", "family": "ensemble", "balanced": True,
                  "selectable": True, "weights": [1/3, 1/3, 1/3],
                  "members": [dict(spec) for spec in specs if spec["name"] in ensemble_names]})
    return specs


def make_domain_pipeline(spec, features, calibrated, aging, seed):
    family = spec["family"]
    if family == "ensemble":
        return Pipeline([("model", EqualDomainEnsemble(features, calibrated, aging, spec["members"], seed))])
    imputer = SimpleImputer(strategy="median", add_indicator=True, keep_empty_features=True)
    if family in ("tree", "mean", "old_multioutput"):
        regressor = DummyRegressor(strategy="mean") if family == "mean" else ExtraTreesRegressor(
            n_estimators=300, min_samples_leaf=3, max_features=0.7, random_state=seed, n_jobs=1)
        return Pipeline([("imputer", imputer), ("model", regressor)])
    selected = aging if spec["feature_set"] == "aging" else None
    steps = [("chemical", FoldChemicalTransform(features, calibrated, selected)),
             ("imputer", imputer), ("scale", StandardScaler())]
    if family == "ridge":
        regressor = Ridge(alpha=spec["alpha"], solver="svd")
    elif family == "krr":
```

```
        regressor = CenteredKernelRidge(alpha=spec["alpha"], gamma_factor=spec["gamma_factor"])
    elif family == "svr":
        regressor = SVR(kernel="rbf", C=spec["C"], epsilon=spec["epsilon"], gamma="scale")
    elif family == "local":
        steps.append(("pca", PCA(n_components=spec["n_components"], svd_solver="full")))
        regressor = StyleWeightedLocalMean(n_neighbors=spec["n_neighbors"])
    else:
        raise ValueError(f"Unknown domain candidate: {family}")
    return Pipeline([*steps, ("model", regressor)])


def training_fit_params(spec, styles):
    return {"model__sample_weight": style_balanced_weights(styles)} if spec["balanced"] else {}
```

src/q3_stale_optimized.py

SHA-256: 1720024ac5855f1b905de115a751cbdcfc9f97e06249091e27c24549bd34dc4a

```
"""Fold-local chemical preprocessing and single-target stale-hops models."""
from __future__ import annotations

import numpy as np
from scipy.stats import spearmanr
from sklearn.base import BaseEstimator, TransformerMixin
from sklearn.cross_decomposition import PLSRegression
from sklearn.ensemble import ExtraTreesRegressor, GradientBoostingRegressor, RandomForestRegressor
from sklearn.impute import SimpleImputer
from sklearn.linear_model import ElasticNet, Ridge
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.model_selection import KFold
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import StandardScaler
from sklearn.svm import SVR

VARIANCE_RATIO_MIN = 0.05
OUTER_SEEDS = (20261123, 20262123)
TRANSFER_CV_SEED = 20263123
SELECTION_BOOTSTRAP_SEED = 20264123
AUDIT_BOOTSTRAP_SEED = 20265123


class FoldChemicalTransform(TransformerMixin, BaseEstimator):
    """Select predeclared chemical fields, log calibrated values, then clip.

    Positive-median scaling, 1%/99% clipping bounds and all downstream
    imputation/scaling are learned anew in each training subset. Relative
    representations are not exponentiated or treated as concentrations.
    """

    def __init__(self, features, calibrated_features, selected_features=None):
        self.features = features
        self.calibrated_features = calibrated_features
        self.selected_features = selected_features

    def _values(self, x):
        raw = x.loc[:, self.features].to_numpy(dtype=float) if hasattr(x, "loc") else np.asarray(x, dtype=float)
        if raw.ndim != 2 or raw.shape[1] != len(self.features):
            raise ValueError("Expected the declared 226-feature hybrid representation")
        return raw[:, self.positions_].copy()

    def _log(self, values):
        for position in self.calibrated_positions_:
            column = values[:, position]
            if np.any(column[np.isfinite(column)] < 0):
                raise ValueError("Calibrated concentrations/indicators must be nonnegative")
            values[:, position] = np.log1p(column / self.positive_scales_[position])
        return values

    def fit(self, x, y=None):
        selected = self.features if self.selected_features is None else self.selected_features
        self.positions_ = np.asarray([self.features.index(feature) for feature
```

```
 in selected])
        self.selected_features_ = list(selected)
        self.calibrated_positions_ = [i for i, feature in enumerate(selected)
                                      if feature in self.calibrated_features]
        values = self._values(x)
        self.positive_scales_ = np.ones(values.shape[1])
        for position in self.calibrated_positions_:
            positive = values[:, position][np.isfinite(values[:, position]) &
(values[:, position] > 0)]
            self.positive_scales_[position] = float(np.median(positive)) if le
n(positive) else 1.0
        values = self._log(values)
        self.bounds_ = np.nanquantile(values, [0.01, 0.99], axis=0)
        self.n_features_in_ = len(self.features)
        return self

    def transform(self, x):
        return np.clip(self._log(self._values(x)), self.bounds_[0], self.bound
s_[1])


def candidate_specs() -> list[dict]:
    """Small grid declared before inspecting any new outer-fold outcomes."""
    specs = []
    def add(family, label, **params):
        specs.append({"name": f"{family}_{label}", "family": family,
                      "feature_set": "all226", "params": params})
    for alpha in (10.0, 100.0, 1000.0):
        add("ridge", f"alpha{alpha:g}", alpha=alpha)
    for alpha in (0.01, 0.1):
        add("elastic_net", f"alpha{alpha:g}", alpha=alpha, l1_ratio=0.5)
    for n_components in (3, 8):
        add("pls", f"n{n_components}", n_components=n_components)
    for c in (0.3, 1.0, 3.0):
        add("svr", f"C{c:g}", C=c, epsilon=0.05, gamma="scale")
    for leaf in (3, 8):
        add("extra_trees", f"leaf{leaf}", n_estimators=160,
            min_samples_leaf=leaf, max_features=0.7)
        add("random_forest", f"leaf{leaf}", n_estimators=160,
            min_samples_leaf=leaf, max_features=0.7)
    for loss in ("squared_error", "huber"):
        add("gradient_boosting", loss, loss=loss, n_estimators=150,
            learning_rate=0.03, max_depth=2, min_samples_leaf=5)
    specs.append({"name": "ridge_aging_alpha10", "family": "ridge", "feature_s
et": "aging",
                  "params": {"alpha": 10.0}})
    specs.append({"name": "svr_aging_C1", "family": "svr", "feature_set": "agi
ng",
                  "params": {"C": 1.0, "epsilon": 0.05, "gamma": "scale"}})
    return specs


def make_pipeline(spec, features, calibrated_features, aging_features, seed):
    selected = aging_features if spec["feature_set"] == "aging" else None
    family, params = spec["family"], dict(spec["params"])
    if family == "ridge":
        estimator = Ridge(solver="svd", **params)
    elif family == "elastic_net":
        estimator = ElasticNet(max_iter=20000, tol=1e-5, random_state=seed, **
params)
    elif family == "pls":
        estimator = PLSRegression(scale=False, max_iter=1000, **params)
```

```
    elif family == "svr":
        estimator = SVR(**params)
    elif family == "extra_trees":
        estimator = ExtraTreesRegressor(random_state=seed, n_jobs=1, **params)
    elif family == "random_forest":
        estimator = RandomForestRegressor(random_state=seed, n_jobs=1, **param
s)
    elif family == "gradient_boosting":
        estimator = GradientBoostingRegressor(random_state=seed, **params)
    else:
        raise ValueError(f"Unsupported family: {family}")
    return Pipeline([
        ("chemical", FoldChemicalTransform(features, calibrated_features, sele
cted)),
        ("imputer", SimpleImputer(strategy="median", add_indicator=True, keep_
empty_features=True)),
        ("scale", StandardScaler()),
        ("model", estimator),
    ])


def raw_tree_pipeline(seed, n_estimators=300):
    return Pipeline([
        ("imputer", SimpleImputer(strategy="median", add_indicator=True, keep_
empty_features=True)),
        ("model", ExtraTreesRegressor(n_estimators=n_estimators, min_samples_l
eaf=3,
                                      max_features=0.7, random_state=seed, n_j
obs=1)),
    ])


def predict_1d(model, x):
    return np.asarray(model.predict(x), dtype=float).reshape(-1)


def scores(y, pred):
    truth, prediction = np.asarray(y, dtype=float).reshape(-1), np.asarray(pre
d, dtype=float).reshape(-1)
    truth_var, pred_var = float(np.var(truth)), float(np.var(prediction))
    correlation = float(spearmanr(truth, prediction).statistic) if pred_var >
1e-20 else None
    target_range = float(np.quantile(truth, .95) - np.quantile(truth, .05))
    prediction_range = float(np.quantile(prediction, .95) - np.quantile(predic
tion, .05))
    return {"mae": float(mean_absolute_error(truth, prediction)),
            "rmse": float(np.sqrt(mean_squared_error(truth, prediction))),
            "r2": float(r2_score(truth, prediction)), "spearman": correlation,
            "prediction_variance": pred_var, "target_variance": truth_var,
            "prediction_variance_ratio": pred_var / truth_var if truth_var > 0
 else None,
            "prediction_std_ratio": float(np.sqrt(pred_var / truth_var)) if tr
uth_var > 0 else None,
            "prediction_range90": prediction_range, "target_range90": target_r
ange,
            "prediction_range90_ratio": prediction_range / target_range if tar
get_range > 0 else None,
            "mean_bias": float(np.mean(prediction - truth))}


def inner_compare(x, y, specs, features, calibrated, aging, seed):
    """Training-only OOF comparison, with a prespecified nonconstant gate."""
```

```
    rows, predictions = [], {}
    splits = list(KFold(3, shuffle=True, random_state=seed).split(x))
    for spec in specs:
        pred = np.full(len(x), np.nan)
        for fold, (train, test) in enumerate(splits, 1):
            model = make_pipeline(spec, features, calibrated, aging, seed + fo
ld)
            model.fit(x.iloc[train], y.iloc[train])
            pred[test] = predict_1d(model, x.iloc[test])
        if not np.isfinite(pred).all():
            raise AssertionError(f"Nonfinite inner predictions: {spec['name']}
")
        metrics = scores(y, pred)
        rows.append({"candidate": spec["name"], "family": spec["family"],
                     "feature_set": spec["feature_set"], **metrics,
                     "nonconstant_qualified": metrics["prediction_variance_rat
io"] >= VARIANCE_RATIO_MIN})
        predictions[spec["name"]] = pred
    return rows, predictions


def choose_candidate(rows, family=None):
    choices = [row for row in rows if family is None or row["family"] == famil
y]
    eligible = [row for row in choices if row["nonconstant_qualified"]]
    # A failed gate never disappears: callers persist nonconstant_qualified.
    return min(eligible or choices, key=lambda row: (row["rmse"], row["candida
te"]))
```

src/q3_stale_refined.py

SHA-256: 11730edf74f74a438072a3ad3bc9e3218fbbf0fe1a9a602a2b936e37eec4b076

```
"""Smooth chemical-only stale prediction with training-only auxiliary targets.
"""
from __future__ import annotations

import numpy as np
from sklearn.base import BaseEstimator, RegressorMixin, TransformerMixin
from sklearn.ensemble import ExtraTreesRegressor
from sklearn.impute import SimpleImputer
from sklearn.kernel_ridge import KernelRidge
from sklearn.linear_model import Ridge

TARGET = "stale_hops"
BIAS_PENALTY = 0.25
VARIANCE_RATIO_MIN = 0.05
STABILITY_DRAWS = 8
STABILITY_SEED = 20280123
NESTED_SEED = 20281123
FINAL_SEED = 20282123
SELECTION_BOOTSTRAP_SEED = 20283123
AUDIT_BOOTSTRAP_SEED = 20284123


def style_weights(styles):
    _, inverse, counts = np.unique(np.asarray(styles), return_inverse=True, re
turn_counts=True)
    return len(inverse)/(len(counts)*counts[inverse])


class FixedChemicalTransform(TransformerMixin, BaseEstimator):
    """Fold-local log/clip/median/scale plus a fixed-width missing block.

    Missing indicators are always present and weighted by 0.2; unlike rare
    Bernoulli scaling, a single missing value cannot make a huge new axis.
    """
    def __init__(self, features, calibrated_features, selected_features=None,
                 indicator_weight=0.2):
        self.features = features
        self.calibrated_features = calibrated_features
        self.selected_features = selected_features
        self.indicator_weight = indicator_weight

    def _raw(self, x):
        values = x.loc[:, self.features].to_numpy(dtype=float) if hasattr(x, "
loc") else np.asarray(x, dtype=float)
        if values.shape[1] != len(self.features):
            raise ValueError("Expected declared hybrid feature order")
        return values[:, self.positions_].copy()

    def _log(self, values):
        for j in self.calibrated_positions_:
            if np.any(values[np.isfinite(values[:, j]), j] < 0):
                raise ValueError("Negative calibrated input")
            values[:, j] = np.log1p(values[:, j]/self.positive_scales_[j])
        return values

    def fit(self, x, y=None):
        selected = self.features if self.selected_features is None else self.s
elected_features
        self.selected_features_ = list(selected)
```

```
        self.positions_ = np.asarray([self.features.index(feature) for feature
 in selected])
        self.calibrated_positions_ = [j for j, feature in enumerate(selected)
                                      if feature in self.calibrated_features]
        values = self._raw(x)
        self.positive_scales_ = np.ones(values.shape[1])
        for j in self.calibrated_positions_:
            positive = values[np.isfinite(values[:, j]) & (values[:, j] > 0),
j]
            self.positive_scales_[j] = np.median(positive) if len(positive) el
se 1.0
        values = self._log(values)
        self.bounds_ = np.nanquantile(values, [.01, .99], axis=0)
        values = np.clip(values, self.bounds_[0], self.bounds_[1])
        self.medians_ = np.nanmedian(values, axis=0)
        self.medians_ = np.nan_to_num(self.medians_, nan=0.0)
        filled = np.where(np.isnan(values), self.medians_, values)
        self.means_ = filled.mean(axis=0)
        self.scales_ = filled.std(axis=0)
        self.scales_[self.scales_ < 1e-12] = 1.0
        self.n_features_in_ = len(self.features)
        self.n_output_features_ = 2*len(selected)
        return self

    def transform(self, x):
        values = self._raw(x)
        missing = np.isnan(values)
        values = np.clip(self._log(values), self.bounds_[0], self.bounds_[1])
        filled = np.where(np.isnan(values), self.medians_, values)
        return np.column_stack([(filled-self.means_)/self.scales_,
                                self.indicator_weight*missing.astype(float)])


def refined_specs():
    specs = [
        {"name": "mean_global", "family": "mean", "selectable": False, "priori
ty": 99},
        {"name": "old_multioutput_tree", "family": "old_tree", "selectable": F
alse, "priority": 99},
        {"name": "fixed_single_tree", "family": "single_tree", "selectable": F
alse, "priority": 99},
        {"name": "stable_ridge_aging100", "family": "ridge", "features": "agin
g", "alpha": 100.0, "priority": 1, "selectable": True},
        {"name": "stable_ridge_all1000", "family": "ridge", "features": "all22
6", "alpha": 1000.0, "priority": 2, "selectable": True},
        {"name": "tail_ridge_aging100", "family": "ridge", "features": "aging"
, "alpha": 100.0, "tail": True, "priority": 3, "selectable": True},
        {"name": "aux4_ridge10", "family": "aux", "features": "all226", "rank"
: 4, "alpha": 10.0, "priority": 4, "selectable": True},
        {"name": "aux8_ridge10", "family": "aux", "features": "all226", "rank"
: 8, "alpha": 10.0, "priority": 5, "selectable": True},
        {"name": "aux4_tail_ridge10", "family": "aux", "features": "all226", "
rank": 4, "alpha": 10.0, "tail": True, "priority": 6, "selectable": True},
        {"name": "aux4_smooth_kernel", "family": "aux_kernel", "features": "al
l226", "rank": 4, "alpha": 1.0, "gamma_factor": .25, "priority": 7, "selectabl
e": True},
        {"name": "style_center_within_ridge", "family": "within", "features":
"all226", "center_alpha": 1000.0, "within_alpha": 100.0, "style_shrinkage": 5.
0, "priority": 8, "selectable": True},
    ]
    members = ["stable_ridge_all1000", "aux4_ridge10", "tail_ridge_aging100"]
    specs.append({"name": "equal3_supervised_ensemble", "family": "ensemble",
```

```
    "priority": 9,
                     "selectable": True, "members": [dict(spec) for spec in specs
     if spec["name"] in members],
                     "weights": [1/3, 1/3, 1/3]})
    return specs


class RefinedStaleModel(RegressorMixin, BaseEstimator):
    """All sensory values are training targets; inference uses chemistry only.
    """
    def __init__(self, features, calibrated_features, aging_features, target_n
    ames,
                 config, seed):
        self.features = features
        self.calibrated_features = calibrated_features
        self.aging_features = aging_features
        self.target_names = target_names
        self.config = config
        self.seed = seed

    def fit(self, x, y, styles):
        all_targets = y.loc[:, self.target_names].to_numpy(dtype=float) if has
    attr(y, "loc") else np.asarray(y, dtype=float)
        if all_targets.ndim != 2 or all_targets.shape[1] != len(self.target_na
    mes):
            raise ValueError("Training requires the declared sensory target ma
    trix")
        self.target_position_ = self.target_names.index(TARGET)
        target = all_targets[:, self.target_position_]
        self.n_features_in_ = len(self.features)
        self.n_outputs_ = 1
        family = self.config["family"]
        if family == "mean":
            self.target_mean_ = float(target.mean())
            return self
        if family in ("old_tree", "single_tree"):
            self.imputer_ = SimpleImputer(strategy="median", add_indicator=Tru
    e,
                                          keep_empty_features=True).fit(x)
            self.model_ = ExtraTreesRegressor(n_estimators=300, min_samples_le
    af=3,
                max_features=.7, random_state=self.seed, n_jobs=1)
            self.model_.fit(self.imputer_.transform(x), all_targets if family
    == "old_tree" else target)
            return self
        if family == "ensemble":
            self.members_ = [RefinedStaleModel(self.features, self.calibrated_
    features,
                self.aging_features, self.target_names, member, self.seed).fit
    (x, y, styles)
                for member in self.config["members"]]
            return self
        selected = self.aging_features if self.config["features"] == "aging" e
    lse None
        self.chemical_ = FixedChemicalTransform(self.features, self.calibrated
    _features, selected).fit(x)
        z = self.chemical_.transform(x)
        base_weights = style_weights(styles)
        weights = base_weights.copy()
        self.tail_training_threshold_ = float(np.quantile(target, .8))
        if self.config.get("tail", False):
            weights *= np.where(target >= self.tail_training_threshold_, 2.0,
```

```
1.0)
            weights *= len(weights)/weights.sum()
        if family == "within":
            center = np.empty(len(target))
            values = np.asarray(styles)
            global_mean = np.average(target, weights=base_weights)
            for style in np.unique(values):
                mask = values == style
                shrinkage = mask.sum()/(mask.sum()+self.config["style_shrinkag
e"])
                center[mask] = global_mean+shrinkage*(target[mask].mean()-glob
al_mean)
            self.center_ = Ridge(alpha=self.config["center_alpha"], solver="sv
d").fit(z, center, sample_weight=base_weights)
            self.within_ = Ridge(alpha=self.config["within_alpha"], solver="sv
d").fit(z, target-center, sample_weight=base_weights)
            return self
        if family in ("aux", "aux_kernel"):
            # Stale is explicitly excluded from auxiliary supervision.
            self.auxiliary_target_indices_ = [j for j in range(len(self.target
_names)) if j != self.target_position_]
            self.auxiliary_target_names_ = [self.target_names[j] for j in self
.auxiliary_target_indices_]
            if TARGET in self.auxiliary_target_names_:
                raise AssertionError("Primary target cannot supervise its auxi
liary directions")
            auxiliary = all_targets[:, self.auxiliary_target_indices_]
            self.auxiliary_mean_ = np.average(auxiliary, axis=0, weights=base_
weights)
            self.auxiliary_scale_ = np.sqrt(np.average((auxiliary-self.auxilia
ry_mean_)**2, axis=0, weights=base_weights))
            self.auxiliary_scale_[self.auxiliary_scale_ < 1e-12] = 1.0
            standardized_auxiliary = (auxiliary-self.auxiliary_mean_)/self.aux
iliary_scale_
            self.auxiliary_ridge_ = Ridge(alpha=100.0, solver="svd").fit(z, st
andardized_auxiliary, sample_weight=base_weights)
            _, self.auxiliary_singular_values_, vt = np.linalg.svd(self.auxili
ary_ridge_.coef_, full_matrices=False)
            self.directions_ = vt[:self.config["rank"]].T
            latent = z@self.directions_
            self.latent_mean_ = np.average(latent, axis=0, weights=base_weight
s)
            self.latent_scale_ = np.sqrt(np.average((latent-self.latent_mean_)
**2, axis=0, weights=base_weights))
            self.latent_scale_[self.latent_scale_ < 1e-12] = 1.0
            z = (latent-self.latent_mean_)/self.latent_scale_
        if family == "aux_kernel":
            self.target_mean_ = float(np.average(target, weights=weights))
            self.model_ = KernelRidge(alpha=self.config["alpha"], kernel="rbf"
,
                                      gamma=self.config["gamma_factor"]/z.shape
[1])
            self.model_.fit(z, target-self.target_mean_, sample_weight=weights
)
        else:
            self.model_ = Ridge(alpha=self.config["alpha"], solver="svd").fit(
z, target, sample_weight=weights)
        return self

    def predict(self, x):
        family = self.config["family"]
        if family == "mean":
```

```
            return np.full(len(x), self.target_mean_)
        if family in ("old_tree", "single_tree"):
            prediction = self.model_.predict(self.imputer_.transform(x))
            return prediction[:, self.target_position_] if family == "old_tree
" else prediction
        if family == "ensemble":
            return np.mean([member.predict(x) for member in self.members_], ax
is=0)
        z = self.chemical_.transform(x)
        if family == "within":
            return self.center_.predict(z)+self.within_.predict(z)
        if family in ("aux", "aux_kernel"):
            z = (z@self.directions_-self.latent_mean_)/self.latent_scale_
        prediction = self.model_.predict(z)
        return prediction+self.target_mean_ if family == "aux_kernel" else pre
diction
```

supplement/q1_additional_checks.py

SHA-256: fef1d87fbcf839edc7270cf9fbcb25ed71fe5d27328e7c652d780b648cac4c93

```
"""Supplement the exploratory comparison with balanced groups and a NaN probe.

The shuffled group split had markedly unequal sample counts. This balanced
split was added after noticing that issue; both sets of results are retained.
"""
import json

import numpy as np
import pandas as pd
import sklearn
from sklearn.ensemble import ExtraTreesRegressor, GradientBoostingRegressor, HistGradientBoostingRegressor
from sklearn.model_selection import GroupKFold
from threadpoolctl import threadpool_limits

import q1_comparison as c


def main():
    x_small = np.array([[1., 2.], [2., np.nan], [np.nan, 4.], [4., 5.],
                        [5., 6.], [6., 7.], [7., 8.], [8., 9.]])
    y_small = np.arange(1., 9.)
    checks = {}
    for model in [GradientBoostingRegressor(n_estimators=3, random_state=1),
                  HistGradientBoostingRegressor(max_iter=3, min_samples_leaf=2,
                                                early_stopping=False, random_state=1),
                  ExtraTreesRegressor(n_estimators=3, random_state=1)]:
        name = type(model).__name__
        try:
            model.fit(x_small, y_small)
            pred = model.predict(np.array([[np.nan, 3.], [3., np.nan]]))
            checks[name] = {"fit_success": True, "predict_nan_success": bool(np.isfinite(pred).all()),
                            "predictions": pred.tolist()}
        except Exception as error:
            checks[name] = {"fit_success": False, "exception_type": type(error).__name__,
                            "message": str(error)}
    (c.OUT / "nan_support_check.json").write_text(json.dumps(
        {"sklearn": sklearn.__version__, "sample_n": 8, "checks": checks},
        ensure_ascii=False, indent=2), encoding="utf-8")
    meta, x, y = c.load_xy()
    rows, per_target = [], []
    predictions = {name: np.full(y.shape, np.nan) for name in ["mean", "extra_trees"]}
    fold_ids = np.zeros(len(x), dtype=int)
    for fold, (train, test) in enumerate(GroupKFold(3, shuffle=False).split(
            x, groups=meta.tasting_category_fine), 1):
        fold_ids[test] = fold
        assert not set(meta.iloc[train].tasting_category_fine) & set(meta.iloc[test].tasting_category_fine)
        for name in predictions:
            model = c.estimator(name, c.SEED + fold).fit(x.iloc[train], y.iloc[train])
            pred = model.predict(x.iloc[test])
            predictions[name][test] = pred
            rows.append({"protocol": "unseen_style_balanced_3fold", "model": n
```

```
ame, "fold": fold,
                           "train_n": len(train), "test_n": len(test), **c.score
s(y.iloc[test], pred)})
    overall = []
    for name, pred in predictions.items():
        overall.append({"protocol": "unseen_style_balanced_3fold", "model": na
me, **c.scores(y, pred)})
        for j, target in enumerate(y.columns):
            per_target.append({"model": name, "target": target, **c.scores(y.i
loc[:, j], pred[:, j])})
        pd.concat([meta, pd.DataFrame({"fold": fold_ids}), pd.DataFrame(pred,
columns=y.columns)], axis=1).to_csv(
            c.OUT / f"oof_unseen_style_balanced_3fold_{name}.csv", index=False
, lineterminator="\n")
    for name, values in [("by_fold", rows), ("overall", overall), ("by_target"
, per_target)]:
        pd.DataFrame(values).to_csv(c.OUT / f"balanced_group_metrics_{name}.cs
v", index=False, lineterminator="\n")
    print(pd.DataFrame(overall).to_string(index=False))


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

supplement/q1_comparison.py

SHA-256: 02febdf363a347d68891531d88abcfa1396db9679155d55238a3b650ba091ec3

```
"""Exploratory Q1 checks prompted by the supplied suggestions.

This script writes the supplementary Q1 comparisons. It does not
replace the frozen experiment, choose a model for submission, or recover
original 0-6 sensory labels. Parameters are fixed before this script is run.
"""
import hashlib
import json
import platform
import sys
import time
from pathlib import Path

HERE = Path(__file__).resolve().parent
SOLUTION = HERE.parent
sys.path.insert(0, str(SOLUTION / "src"))

import numpy as np
import pandas as pd
import sklearn
from sklearn.dummy import DummyRegressor
from sklearn.ensemble import ExtraTreesRegressor, GradientBoostingRegressor, HistGradientBoostingRegressor
from sklearn.impute import SimpleImputer
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.model_selection import GroupKFold, KFold
from sklearn.multioutput import MultiOutputRegressor
from sklearn.pipeline import Pipeline
from threadpoolctl import threadpool_limits

from common import data_dir, load_xy

SEED = 20261024
OUT = HERE / "results/q1"


def scores(actual, predicted):
    return {"mae": float(mean_absolute_error(actual, predicted)),
            "rmse": float(np.sqrt(mean_squared_error(actual, predicted))),
            "macro_r2": float(r2_score(actual, predicted, multioutput="uniform_average"))}


def estimator(name, seed):
    if name == "mean":
        return DummyRegressor(strategy="mean")
    if name == "extra_trees":
        model = ExtraTreesRegressor(n_estimators=300, min_samples_leaf=3,
                                    max_features=.7, random_state=seed, n_jobs=1)
    elif name == "gbr_per_target":
        model = MultiOutputRegressor(GradientBoostingRegressor(
            n_estimators=100, learning_rate=.05, max_depth=2, min_samples_leaf=5,
            loss="squared_error", random_state=seed), n_jobs=1)
    elif name == "hgb_per_target":
        model = MultiOutputRegressor(HistGradientBoostingRegressor(
            max_iter=100, learning_rate=.05, max_leaf_nodes=7, min_samples_leaf=10,
```

```
            l2_regularization=1., early_stopping=False, random_state=seed), n_
jobs=1)
    else:
        raise ValueError(name)
    return Pipeline([("imputer", SimpleImputer(strategy="median", add_indicato
r=True,
                                               keep_empty_features=True)), ("
model", model)])


def main():
    OUT.mkdir(parents=True, exist_ok=True)
    meta, x, y = load_xy()
    y_np = y.to_numpy()
    random_splits = list(KFold(3, shuffle=True, random_state=SEED).split(x))
    group_splits = list(GroupKFold(3, shuffle=True, random_state=SEED).split(
        x, groups=meta.tasting_category_fine))
    summary_rows, fold_rows, target_rows, masks = [], [], [], []
    started = time.perf_counter()
    for protocol, splits, names in [
        ("random_3fold", random_splits, ["mean", "extra_trees", "gbr_per_targe
t", "hgb_per_target"]),
        ("unseen_style_3fold", group_splits, ["mean", "extra_trees"]),
    ]:
        fold_ids = np.zeros(len(x), dtype=int)
        predictions = {name: np.full(y.shape, np.nan) for name in names}
        stressed = {rate: np.full((20, *y.shape), np.nan) for rate in (.1, .2)
} if protocol == "random_3fold" else {}
        timings = {name: 0. for name in names}
        for fold, (train, test) in enumerate(splits, 1):
            fold_ids[test] = fold
            if protocol == "unseen_style_3fold":
                assert not set(meta.iloc[train].tasting_category_fine) & set(m
eta.iloc[test].tasting_category_fine)
            for name in names:
                start = time.perf_counter()
                model = estimator(name, SEED + fold)
                model.fit(x.iloc[train], y.iloc[train])
                pred = model.predict(x.iloc[test])
                timings[name] += time.perf_counter() - start
                predictions[name][test] = pred
                if name != "mean":
                    np.testing.assert_allclose(model.named_steps["imputer"].st
atistics_,
                                               np.nanmedian(x.iloc[train], axi
s=0))
                fold_rows.append({"protocol": protocol, "model": name, "fold":
 fold,
                                  "train_n": len(train), "test_n": len(test),
                                  "test_styles": "|".join(sorted(meta.iloc[tes
t].tasting_category_fine.unique())),
                                  **scores(y.iloc[test], pred)})
                if protocol == "random_3fold" and name == "extra_trees":
                    for repeat in range(20):
                        uniforms = np.random.default_rng(SEED + 10000 + 100 *
repeat + fold).random((len(test), x.shape[1]))
                        for rate in (.1, .2):
                            mask = (uniforms < rate) & x.iloc[test].notna().to
_numpy()
                            stressed[rate][repeat, test] = model.predict(x.ilo
c[test].mask(mask))
                            masks.append({"repeat": repeat + 1, "fold": fold,
```

```
    "rate": rate,
                                            "additional_hidden": int(mask.sum())
    })
                print(f"{protocol} fold {fold}/3 {name}: RMSE={scores(y.iloc[t
    est], pred)['rmse']:.6f}", flush=True)
        for name, pred in predictions.items():
            assert np.isfinite(pred).all()
            summary_rows.append({"protocol": protocol, "model": name,
                                 "fit_and_predict_seconds": timings[name], **s
    cores(y, pred)})
            for j, target in enumerate(y.columns):
                target_rows.append({"protocol": protocol, "model": name,
                                    "target": target, **scores(y_np[:, j], pre
    d[:, j])})
            pd.concat([meta, pd.DataFrame({"fold": fold_ids}), pd.DataFrame(pr
    ed, columns=y.columns)], axis=1).to_csv(
                OUT / f"oof_{protocol}_{name}.csv", index=False, lineterminato
    r="\n")
        pd.concat([meta, pd.DataFrame({"fold": fold_ids})], axis=1).to_csv(
            OUT / f"fold_assignment_{protocol}.csv", index=False, lineterminat
    or="\n")
        if stressed:
            np.savez_compressed(OUT / "test_mask_predictions.npz",
                                rate10=stressed[.1], rate20=stressed[.2])
        for rate, values in stressed.items():
            for repeat in range(20):
                summary_rows.append({"protocol": "random_3fold_test_mask", "mo
    del": "extra_trees",
                                     "rate": rate, "repeat": repeat + 1, **sco
    res(y, values[repeat])})
    for filename, rows in [("metrics_overall.csv", summary_rows), ("metrics_by
    _fold.csv", fold_rows),
                           ("metrics_by_target.csv", target_rows), ("mask_coun
    ts.csv", masks)]:
        pd.DataFrame(rows).to_csv(OUT / filename, index=False, lineterminator=
    "\n")
    manifest = {"purpose": "Supplementary post-hoc comparison; primary experim
    ent retained", "seed": SEED,
                "samples": len(x), "features": x.shape[1], "targets": list(y.c
    olumns),
                "target_scale": "Attachment 4 standardized continuous scale, n
    ot original 0-6 scores",
                "total_seconds": time.perf_counter() - started,
                "protocols": {"random_3fold": "Same 3 shuffled folds and train
    ing-only imputation for all four models",
                              "unseen_style_3fold": "Whole fine styles exclude
    d from training; Mean and ExtraTrees only",
                              "stress": "20 test-mask draws per 10%/20% rate;
    masks are paired and nested; models remain unchanged"},
                "models": {name: repr(estimator(name, SEED + 1)) for name in [
    "mean", "extra_trees", "gbr_per_target", "hgb_per_target"]},
                "input_sha256": {filename: hashlib.sha256((data_dir()/filename
    ).read_bytes()).hexdigest() for filename in ["1.csv", "4.csv"]},
                "versions": {"python": platform.python_version(), "numpy": np.
    __version__,
                             "pandas": pd.__version__, "sklearn": sklearn.__ve
    rsion__},
                "limitations": ["Same 250 beers as development; a new split is
     not an independent data set.",
                                "One fixed parameter set per model; not a tune
    d-family superiority claim.",
                                "45-output ExtraTrees shares splits; boosting
```

```
    models fit each target separately.",
141                                 "Random and style-group protocols answer diffe
    rent deployment questions.",
142                                 "MCAR test masking does not model detection li
    mits, training-set missingness, or instrument failures.",
143                                 "Attachment creators' precomputed global trans
    formations cannot be undone."]}
144     (OUT / "manifest.json").write_text(json.dumps(manifest, ensure_ascii=False
    , indent=2), encoding="utf-8")
145     print(pd.DataFrame(summary_rows).head(6).to_string(index=False), flush=Tru
    e)
146     print(f"Completed in {manifest['total_seconds']:.2f} seconds", flush=True)
147
148
149 if __name__ == "__main__":
150     with threadpool_limits(limits=1):
151         main()
```

supplement/q1_indicator_ablation.py

SHA-256: 12410d3c8990ba0d2d7993b903f3498c52f5b045f7c966022b07a93e3e8a1308

```
"""Paired Q1 missing-indicator ablation; frozen primary results are read only.

Run this file to reproduce the comparison. Pass --verify-only to independently
recompute saved metrics, folds, masks, preprocessing and input hashes, without
fitting models or changing files. The sole configured model difference is
SimpleImputer.add_indicator. No parameter is selected from these results.
"""
import hashlib
import json
from pathlib import Path
import platform
import sys
import time

sys.dont_write_bytecode = True
HERE = Path(__file__).resolve().parent
ROOT = HERE.parent
REPO = ROOT.parent
sys.path.insert(0, str(ROOT / "src"))

import numpy as np
import pandas as pd
import sklearn
from sklearn.ensemble import ExtraTreesRegressor
from sklearn.impute import SimpleImputer
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.model_selection import KFold
from sklearn.pipeline import Pipeline
from threadpoolctl import threadpool_limits

from common import SEED, data_dir, load_xy

OUT = HERE / "results/q1_indicator_ablation"
ARMS = {"with_indicator": True, "without_indicator": False}
RATES = {"original": 0.0, "mask10": 0.1, "mask20": 0.2}
TREE_PARAMETERS = {"n_estimators": 300, "min_samples_leaf": 3,
                   "max_features": 0.7, "n_jobs": 1}


def sha256(path):
    return hashlib.sha256(path.read_bytes()).hexdigest()


def scores(actual, predicted):
    return {"mae": float(mean_absolute_error(actual, predicted)),
            "rmse": float(np.sqrt(mean_squared_error(actual, predicted))),
            "macro_r2": float(r2_score(actual, predicted, multioutput="uniform
_average"))}


def cohorts(x):
    missing = x.isna().any(axis=1).to_numpy()
    assert int(missing.sum()) == 63 and int((~missing).sum()) == 187
    return {"all": np.ones(len(x), dtype=bool), "original_missing": missing,
            "original_complete": ~missing}


def csv(name, rows):
    pd.DataFrame(rows).to_csv(OUT / name, index=False, lineterminator="\n")
```

```

def json_file(name, record):
    (OUT / name).write_text(json.dumps(record, ensure_ascii=False, indent=2) + "\n",
                            encoding="utf-8", newline="\n")


def baseline_comparison(predictions, meta, y, fold_ids):
    rows = []
    for scenario in RATES:
        suffix = "" if scenario == "original" else "_" + scenario
        frozen = pd.read_csv(ROOT / f"outputs/q1/oof_extra_trees{suffix}.csv")
        assert frozen.beer.tolist() == meta.beer.tolist()
        np.testing.assert_array_equal(frozen.fold, fold_ids)
        old = frozen[y.columns].to_numpy()
        current = predictions[("with_indicator", scenario)]
        difference = np.abs(current - old)
        rows.append({"scenario": scenario, "frozen_rmse": scores(y, old)["rmse"],
                     "refit_rmse": scores(y, current)["rmse"],
                     "max_abs_prediction_difference": float(difference.max()),
                     "mean_abs_prediction_difference": float(difference.mean()),
                     "same_predictions_at_1e_10": bool(np.allclose(current, old, rtol=0, atol=1e-10))})
    return rows


def main():
    started = time.perf_counter()
    OUT.mkdir(parents=True, exist_ok=True)
    protected = [p for folder in [data_dir(), ROOT / "outputs"]
                 for p in sorted(folder.rglob("*")) if p.is_file()]
    protected += [ROOT / "src/common.py", ROOT / "src/02_q1_baseline.py"]
    hashes = {p.relative_to(REPO).as_posix(): sha256(p) for p in protected}
    meta, x, y = load_xy()
    groups = cohorts(x)
    actual = y.to_numpy()
    predictions = {(arm, scenario): np.full(y.shape, np.nan)
                   for arm in ARMS for scenario in RATES}
    fold_ids = np.zeros(len(x), dtype=int)
    masks = {scenario: np.zeros(x.shape, dtype=bool) for scenario in ["mask10", "mask20"]}
    preprocessing, mask_rows = [], []
    for fold, (train, test) in enumerate(KFold(5, shuffle=True, random_state=SEED).split(x), 1):
        fold_ids[test] = fold
        xtr, xte = x.iloc[train], x.iloc[test]
        uniforms = np.random.default_rng(SEED + 100 + fold).random(xte.shape)
        inputs = {"original": xte}
        for scenario in ["mask10", "mask20"]:
            mask = (uniforms < RATES[scenario]) & xte.notna().to_numpy()
            masks[scenario][test] = mask
            inputs[scenario] = xte.mask(mask)
            mask_rows.append({"fold": fold, "scenario": scenario, "rate": RATES[scenario],
                              "additional_hidden": int(mask.sum()),
                              "original_observed": int(xte.notna().sum().sum())})
        for arm, indicator in ARMS.items():
            fitted = Pipeline([
```

```
                ("imputer", SimpleImputer(strategy="median", add_indicator=ind
icator,
                                          keep_empty_features=True)),
                ("model", ExtraTreesRegressor(random_state=SEED + fold, **TREE
_PARAMETERS))])
            fitted.fit(xtr, y.iloc[train])
            imputer, tree = fitted.named_steps["imputer"], fitted.named_steps[
"model"]
            np.testing.assert_allclose(imputer.statistics_, xtr.median().to_nu
mpy())
            preprocessing.append({"fold": fold, "arm": arm, "train_n": len(tra
in),
                                  "test_n": len(test), "median_statistics": im
puter.statistics_.tolist(),
                                  "indicator_indices": imputer.indicator_.feat
ures_.tolist() if indicator else [],
                                  "n_model_features": tree.n_features_in_,
                                  "n_candidate_features_per_split": tree.estim
ators_[0].max_features_})
            for scenario, test_input in inputs.items():
                predictions[(arm, scenario)][test] = fitted.predict(test_input
)
        print(f"Indicator ablation fold {fold}/5 completed", flush=True)
    assert all(np.isfinite(p).all() for p in predictions.values())
    assignment = meta.assign(fold=fold_ids, original_missing=groups["original_
missing"],
                             original_missing_count=x.isna().sum(axis=1))
    assignment.to_csv(OUT / "fold_assignments.csv", index=False, lineterminato
r="\n")
    np.savez_compressed(OUT / "test_masks.npz", **masks)
    json_file("preprocessing.json", preprocessing)
    csv("mask_counts.csv", mask_rows)
    metric_rows, fold_rows, paired_rows, error_rows = [], [], [], []
    for (arm, scenario), predicted in predictions.items():
        pd.concat([assignment, pd.DataFrame(predicted, columns=y.columns)], ax
is=1).to_csv(
            OUT / f"oof_{arm}_{scenario}.csv", index=False, lineterminator="\n
")
        for group, selected in groups.items():
            metric_rows.append({"arm": arm, "scenario": scenario, "rate": RATE
S[scenario],
                                "cohort": group, "n": int(selected.sum()),
                                **scores(actual[selected], predicted[selected]
)})
            for fold in range(1, 6):
                subset = selected & (fold_ids == fold)
                fold_rows.append({"arm": arm, "scenario": scenario, "cohort":
group,
                                  "fold": fold, "n": int(subset.sum()),
                                  **scores(actual[subset], predicted[subset])}
)
    for scenario in RATES:
        with_pred, without_pred = [predictions[(arm, scenario)] for arm in ARM
S]
        square = [np.mean((pred - actual) ** 2, axis=1) for pred in [with_pred
, without_pred]]
        absolute = [np.mean(np.abs(pred - actual), axis=1) for pred in [with_p
red, without_pred]]
        for i in range(len(x)):
            error_rows.append({"beer": int(meta.beer.iloc[i]), "fold": int(fol
d_ids[i]),
                               "scenario": scenario, "original_missing": bool(
```

```
    groups["original_missing"][i]),
154                                 "mse_with_indicator": float(square[0][i]),
155                                 "mse_without_indicator": float(square[1][i]),
156                                 "delta_mse": float(square[0][i] - square[1][i])
    ,
157                                 "mae_with_indicator": float(absolute[0][i]),
158                                 "mae_without_indicator": float(absolute[1][i])}
    )
159         for group, selected in groups.items():
160             a, b = [scores(actual[selected], pred[selected]) for pred in [with
    _pred, without_pred]]
161             paired_rows.append({"scenario": scenario, "cohort": group, "n": in
    t(selected.sum()),
162                                 **{f"{metric}_with_indicator": value for metri
    c, value in a.items()},
163                                 **{f"{metric}_without_indicator": value for me
    tric, value in b.items()},
164                                 **{f"delta_{metric}": a[metric] - b[metric] fo
    r metric in a},
165                                 "mean_paired_delta_mse": float((square[0] - sq
    uare[1])[selected].mean()),
166                                 "beers_with_lower_mse_using_indicator": int((s
    quare[0][selected] < square[1][selected]).sum())})
167     csv("metrics.csv", metric_rows)
168     csv("metrics_by_fold.csv", fold_rows)
169     csv("paired_metrics.csv", paired_rows)
170     csv("paired_errors.csv", error_rows)
171     comparison = baseline_comparison(predictions, meta, y, fold_ids)
172     csv("baseline_consistency.csv", comparison)
173     assert hashes == {p.relative_to(REPO).as_posix(): sha256(p) for p in prote
    cted}
174     json_file("manifest.json", {
175         "purpose": "Post-hoc paired missing-indicator ablation; primary model
    and results retained",
176         "seed": SEED, "model_seed": "SEED + outer fold (1 through 5)",
177         "n": len(x), "features": list(x.columns), "targets": list(y.columns),
178         "cohorts": {name: int(rows.sum()) for name, rows in groups.items()},
179         "sole_configured_difference": "SimpleImputer.add_indicator True versus
     False",
180         "preprocessing": "training-fold median, keep_empty_features=True, no X
    /Y scaling",
181         "tree_parameters": TREE_PARAMETERS, "folds": "five shuffled folds, 200
     train / 50 test",
182         "mask_logic": "default_rng(SEED + 100 + fold); observed test cells onl
    y; same uniforms for both rates and arms",
183         "mask_repeats": 1, "cohort_definition": "raw original missingness, fix
    ed before test masking",
184         "target_scale": "Attachment 4 standardized continuous values; not orig
    inal 0-6 scores",
185         "paired_difference_direction": "with indicator minus without indicator
    ; negative error delta favors indicator",
186         "baseline_consistency": comparison, "input_sha256": hashes,
187         "script_sha256": sha256(Path(__file__)), "frozen_inputs_unchanged": Tr
    ue,
188         "versions": {"python": platform.python_version(), "numpy": np.__versio
    n__,
189                      "pandas": pd.__version__, "sklearn": sklearn.__version__}
    ,
190         "elapsed_seconds": time.perf_counter() - started,
191         "limitations": [
192             "One fixed split seed and one mask draw per rate; not independent
    external validation or a confidence interval.",
```

```
            "Natural-missing versus complete cohorts differ in more than missingness; their contrast is not causal.",
            "Adding indicators changes effective feature dimension and the integer candidate count implied by max_features=0.7; it can change random tree paths even for complete rows.",
            "Indicators cover only columns missing in the training fold, not every newly hidden test column.",
            "Refitted floating-point tree outputs are compared explicitly to frozen outputs; exact identity is not assumed.",
            "MCAR-style test masking does not represent detection-limit censoring, training missingness or instrument failure.",
            "No hyperparameter or target-wise model selection is performed; existing original-0-6 limitations remain."]})
    report = verify_saved()
    json_file("verification.json", report)
    print(pd.DataFrame(paired_rows).to_string(index=False), flush=True)
    print(json.dumps(report, ensure_ascii=False), flush=True)


def numpy_scores(actual, predicted):
    """Metric recomputation independent of the sklearn functions used above."""
    squared = (actual - predicted) ** 2
    numerator = squared.sum(axis=0)
    denominator = ((actual - actual.mean(axis=0)) ** 2).sum(axis=0)
    ratios = np.divide(numerator, denominator, out=np.zeros_like(numerator), where=denominator != 0)
    r2 = np.where(denominator != 0, 1 - ratios, np.where(numerator == 0, 1., 0.))
    return {"mae": float(np.abs(actual - predicted).mean()),
            "rmse": float(np.sqrt(squared.mean())), "macro_r2": float(r2.mean())}


def verify_saved():
    meta, x, y = load_xy()
    actual, groups = y.to_numpy(), cohorts(x)
    manifest = json.loads((OUT / "manifest.json").read_text())
    assert manifest["script_sha256"] == sha256(Path(__file__))
    assert all(sha256(REPO / path) == value for path, value in manifest["input_sha256"].items())
    saved = pd.read_csv(OUT / "fold_assignments.csv")
    assert saved.beer.tolist() == meta.beer.tolist()
    np.testing.assert_array_equal(saved.original_missing, groups["original_missing"])
    np.testing.assert_array_equal(saved.original_missing_count, x.isna().sum(axis=1))
    stored_masks = np.load(OUT / "test_masks.npz")
    preprocess = json.loads((OUT / "preprocessing.json").read_text())
    counts = pd.read_csv(OUT / "mask_counts.csv")
    for fold, (train, test) in enumerate(KFold(5, shuffle=True, random_state=SEED).split(x), 1):
        assert saved.fold.iloc[test].eq(fold).all()
        uniforms = np.random.default_rng(SEED + 100 + fold).random((len(test), x.shape[1]))
        for scenario in ["mask10", "mask20"]:
            expected = (uniforms < RATES[scenario]) & x.iloc[test].notna().to_numpy()
            np.testing.assert_array_equal(stored_masks[scenario][test], expected)
            row = counts.loc[counts.fold.eq(fold) & counts.scenario.eq(scenario)].iloc[0]
```

```
            assert row.additional_hidden == int(expected.sum())
            assert row.original_observed == int(x.iloc[test].notna().sum().sum
())
        for arm, indicator in ARMS.items():
            item = next(r for r in preprocess if r["fold"] == fold and r["arm"
] == arm)
            np.testing.assert_allclose(item["median_statistics"], np.nanmedian
(x.iloc[train], axis=0))
            indices = np.flatnonzero(x.iloc[train].isna().any(axis=0)).tolist(
) if indicator else []
            assert item["indicator_indices"] == indices
            assert item["n_model_features"] == x.shape[1] + len(indices)
            assert item["n_candidate_features_per_split"] == int(.7 * item["n_
model_features"])
    assert not (stored_masks["mask10"] & ~stored_masks["mask20"]).any()
    metric = pd.read_csv(OUT / "metrics.csv")
    by_fold = pd.read_csv(OUT / "metrics_by_fold.csv")
    pair_metric = pd.read_csv(OUT / "paired_metrics.csv")
    pair_error = pd.read_csv(OUT / "paired_errors.csv")
    predictions = {}
    for arm in ARMS:
        for scenario in RATES:
            frame = pd.read_csv(OUT / f"oof_{arm}_{scenario}.csv")
            assert frame.beer.tolist() == meta.beer.tolist()
            np.testing.assert_array_equal(frame.fold, saved.fold)
            np.testing.assert_array_equal(frame.original_missing, groups["orig
inal_missing"])
            predicted = frame[y.columns].to_numpy()
            assert predicted.shape == actual.shape and np.isfinite(predicted).
all()
            predictions[(arm, scenario)] = predicted
            for group, selected in groups.items():
                row = metric.loc[metric.arm.eq(arm) & metric.scenario.eq(scena
rio) & metric.cohort.eq(group)].iloc[0]
                assert row.n == int(selected.sum())
                for key, value in numpy_scores(actual[selected], predicted[sel
ected]).items():
                    np.testing.assert_allclose(row[key], value, rtol=1e-10, at
ol=1e-12)
                for fold in range(1, 6):
                    subset = selected & saved.fold.eq(fold).to_numpy()
                    row = by_fold.loc[by_fold.arm.eq(arm) & by_fold.scenario.e
q(scenario)
                                      & by_fold.cohort.eq(group) & by_fold.fol
d.eq(fold)].iloc[0]
                    assert row.n == int(subset.sum())
                    for key, value in numpy_scores(actual[subset], predicted[s
ubset]).items():
                        np.testing.assert_allclose(row[key], value, rtol=1e-10
, atol=1e-12)
    for scenario in RATES:
        a, b = [predictions[(arm, scenario)] for arm in ARMS]
        delta = ((a - actual) ** 2 - (b - actual) ** 2).mean(axis=1)
        rows = pair_error.loc[pair_error.scenario.eq(scenario)]
        assert rows.beer.tolist() == meta.beer.tolist()
        np.testing.assert_allclose(rows.delta_mse, delta, rtol=1e-10, atol=1e-
12)
        for group, selected in groups.items():
            row = pair_metric.loc[pair_metric.scenario.eq(scenario) & pair_met
ric.cohort.eq(group)].iloc[0]
            sa, sb = [numpy_scores(actual[selected], pred[selected]) for pred
in [a, b]]
```

```
            for key in sa:
                for field, value in [(f"{key}_with_indicator", sa[key]),
                                     (f"{key}_without_indicator", sb[key]),
                                     (f"delta_{key}", sa[key] - sb[key])]:
                    np.testing.assert_allclose(row[field], value, rtol=1e-10, atol=1e-12)
            np.testing.assert_allclose(row.mean_paired_delta_mse, delta[selected].mean(), rtol=1e-10, atol=1e-12)
            assert row.beers_with_lower_mse_using_indicator == int((delta[selected] < 0).sum())
    comparison = baseline_comparison(predictions, meta, y, saved.fold.to_numpy())
    pd.testing.assert_frame_equal(pd.DataFrame(comparison),
                                  pd.DataFrame(manifest["baseline_consistency"]),
                                  check_exact=False, rtol=1e-10, atol=1e-12)
    return {"status": "PASS", "oof_tables": len(predictions), "metric_rows": len(metric),
            "fold_metric_rows": len(by_fold), "paired_metric_rows": len(pair_metric),
            "paired_beer_scenarios": len(pair_error), "folds": 5, "test_mask_scenarios": 2,
            "protected_files_unchanged": len(manifest["input_sha256"]),
            "baseline_consistency": comparison,
            "scope": "Read-only recomputation of saved numerical results and data contracts; no second model fit."}


if __name__ == "__main__":
    if sys.argv[1:] == ["--verify-only"]:
        print(json.dumps(verify_saved(), ensure_ascii=False, indent=2))
    else:
        assert not sys.argv[1:], "Only --verify-only is supported"
        with threadpool_limits(limits=1):
            main()
```

supplement/q2_permutation.py

SHA-256: 603de849964bae027c68f5bd6735070bb2dfc742fb5586e6f20b0301a9373a77

```
"""Held-out permutation dependence for all 45 sensory targets.

The original five splits and tree parameters are retained. Permutations act
on validation inputs only, including each feature's missing indicator.
Correlated modules are learned separately from each training fold.
"""
import hashlib
import importlib.util
import json
from pathlib import Path
import sys
import time

import numpy as np
import pandas as pd
from sklearn.model_selection import KFold
from threadpoolctl import threadpool_limits

HERE = Path(__file__).resolve().parent
ROOT = HERE.parent
sys.path.insert(0, str(ROOT / "src"))
from common import SEED, data_dir, load_xy

OUT = HERE / "results/q2_permutation"
REPEATS = 5


def load_module(name, filename):
    spec = importlib.util.spec_from_file_location(name, ROOT / "src" / filenam
e)
    module = importlib.util.module_from_spec(spec)
    spec.loader.exec_module(module)
    return module


def components(training):
    correlation = training.corr(method="spearman").fillna(0).to_numpy()
    adjacency = np.abs(correlation) >= .7
    remaining = set(range(training.shape[1]))
    groups = []
    while remaining:
        current = [min(remaining)]
        remaining.remove(current[0])
        group = []
        while current:
            j = current.pop()
            group.append(j)
            neighbors = sorted(remaining.intersection(np.flatnonzero(adjacency
[j])))
            remaining.difference_update(neighbors)
            current.extend(neighbors)
        groups.append(sorted(group))
    assert sorted(j for group in groups for j in group) == list(range(training
.shape[1]))
    return groups


def predict_permutations(tree, base, groups, columns, permutation, truth, base
line):
```

```
    result = np.empty((len(groups), truth.shape[1]))
    for start in range(0, len(groups), 32):
        batch = groups[start:start + 32]
        stacked = np.tile(base, (len(batch), 1))
        n = len(base)
        for k, group in enumerate(batch):
            selected = [col for j in group for col in columns[j]]
            stacked[k*n:(k+1)*n, selected] = base[np.ix_(permutation, selected)]
        prediction = tree.predict(stacked).reshape(len(batch), n, truth.shape[1])
        result[start:start + len(batch)] = ((prediction - truth) ** 2).mean(axis=1) - baseline
    return result


def main():
    started = time.perf_counter()
    OUT.mkdir(parents=True, exist_ok=True)
    q1 = load_module("q1_permutation_baseline", "02_q1_baseline.py")
    q2 = load_module("q2_permutation_candidates", "03_q2_network.py")
    meta, x, y = load_xy()
    features, targets = list(x), list(y)
    candidates = [j for j, feature in enumerate(features) if feature not in q2.EXCLUDE_X]
    assert len(candidates) == 218
    y_values = y.to_numpy()
    delta = np.empty((5, REPEATS, len(features), len(targets)))
    oof = np.full(y.shape, np.nan)
    fold_ids = np.zeros(len(x), dtype=int)
    fold_sizes = []
    module_rows, membership = [], []
    check_features = ["ethyl_acetate", "X4VG", "ethanol..v.v."]
    check_predictions = np.empty((5, REPEATS, len(check_features), 50, len(targets)))
    check_rows = []
    original = pd.read_csv(ROOT / "outputs/q1/oof_extra_trees.csv")
    assert original.beer.tolist() == meta.beer.tolist()
    for fold, (train, test) in enumerate(KFold(5, shuffle=True, random_state=SEED).split(x)):
        fold_ids[test] = fold + 1
        fold_sizes.append(len(test))
        assert original.iloc[test].fold.eq(fold + 1).all()
        model = q1.tree_pipeline(SEED + fold + 1).fit(x.iloc[train], y.iloc[train])
        imputer, tree = model.named_steps["imputer"], model.named_steps["model"]
        np.testing.assert_allclose(imputer.statistics_, np.nanmedian(x.iloc[train], axis=0))
        base = imputer.transform(x.iloc[test])
        oof[test] = tree.predict(base)
        truth = y_values[test]
        baseline = ((truth - oof[test]) ** 2).mean(axis=0)
        columns = [[j] for j in range(len(features))]
        for k, j in enumerate(imputer.indicator_.features_):
            columns[j].append(len(features) + k)
        groups = components(x.iloc[train])
        group_delta = np.empty((REPEATS, len(groups), len(targets)))
        for g, group in enumerate(groups):
            membership.append({"fold": fold + 1, "module": g + 1, "size": len(group),
                               "members": " | ".join(features[j] for j in grou
```

```
    p)})
108         for repeat in range(REPEATS):
109             permutation = np.random.default_rng(SEED + 50000 + 100*fold + repe
    at).permutation(len(test))
110             delta[fold, repeat] = predict_permutations(
111                 tree, base, [[j] for j in range(len(features))], columns, perm
    utation, truth, baseline)
112             group_delta[repeat] = predict_permutations(
113                 tree, base, groups, columns, permutation, truth, baseline)
114             for k, feature in enumerate(check_features):
115                 j = features.index(feature)
116                 raw = x.iloc[test].copy()
117                 raw.loc[:, feature] = x.iloc[test].iloc[permutation][feature].
    to_numpy()
118                 predicted = model.predict(raw)
119                 check_predictions[fold, repeat, k] = predicted
120                 independent = ((predicted - truth) ** 2).mean(axis=0) - baseli
    ne
121                 np.testing.assert_allclose(independent, delta[fold, repeat, j]
    , rtol=1e-10, atol=1e-12)
122         for g, group in enumerate(groups):
123             for k, target in enumerate(targets):
124                 module_rows.append({"fold": fold + 1, "module": g + 1, "size":
     len(group),
125                                     "target": target, "delta_mse": group_delta
    [:, g, k].mean(),
126                                     "repeat_sd": group_delta[:, g, k].std(ddof
    =1)})
127         check_rows.append(test)
128         print(f"Permutation fold {fold + 1}/5: {len(groups)} training modules;
     held-out rows={len(test)}", flush=True)
129     assert np.isfinite(delta).all() and np.isfinite(oof).all()
130     by_fold = delta.mean(axis=1)
131     mean = np.average(by_fold, axis=0, weights=fold_sizes)
132     sd = by_fold.std(axis=0, ddof=1)
133     positive = (by_fold > 0).sum(axis=0)
134     overall, fold_rows, top_rows, comparisons = [], [], [], []
135     original_top = pd.read_csv(ROOT / "outputs/q2/top3_compounds.csv")
136     for k, target in enumerate(targets):
137         ordered = sorted(candidates, key=lambda j: (-mean[j, k], j))
138         ranks = {j: rank for rank, j in enumerate(ordered, 1)}
139         chosen = ordered[:3]
140         existing = original_top.loc[original_top.sensory_target.eq(target)].so
    rt_values("rank").compound.tolist()
141         chosen_names = [features[j] for j in chosen]
142         common = set(chosen_names) & set(existing)
143         comparisons.append({"sensory_target": target, "spearman_top3": " | ".j
    oin(existing),
144                             "permutation_top3": " | ".join(chosen_names), "ove
    rlap": len(common),
145                             "jaccard": len(common) / len(set(chosen_names) | s
    et(existing)),
146                             "all_three_positive_mean": bool((mean[chosen, k] >
     0).all())})
147         for j, feature in enumerate(features):
148             row = {"sensory_target": target, "feature": feature, "chemical_can
    didate": j in ranks,
149                    "candidate_rank": ranks.get(j), "delta_mse": mean[j, k],
150                    "fold_sd": sd[j, k], "positive_folds": int(positive[j, k])}
151             overall.append(row)
152             if j in chosen:
153                 top_rows.append(row)
```

```
            for fold in range(5):
                fold_rows.append({"fold": fold + 1, "sensory_target": target, "feature": feature,
                                  "delta_mse": by_fold[fold, j, k],
                                  "repeat_sd": delta[fold, :, j, k].std(ddof=1)})
    for name, rows in [("importance", overall), ("importance_by_fold", fold_rows),
                       ("top3", top_rows), ("top3_comparison", comparisons),
                       ("module_importance_by_fold", module_rows), ("module_membership", membership)]:
        pd.DataFrame(rows).to_csv(OUT / f"{name}.csv", index=False, lineterminator="\n", float_format="%.12g")
    pd.concat([meta, pd.DataFrame({"fold": fold_ids}), pd.DataFrame(oof, columns=targets)], axis=1).to_csv(
        OUT / "oof.csv", index=False, lineterminator="\n")
    np.savez_compressed(OUT / "permutation_draws.npz", delta_mse=delta,
                        fold_ids=fold_ids, features=np.array(features), targets=np.array(targets),
                        check_predictions=check_predictions, check_features=np.array(check_features),
                        check_test_rows=np.array(check_rows))
    summary = {"scope": "Supplementary post-hoc model-dependence analysis; not causal effects or a new test dataset.",
               "seed": SEED, "folds": 5, "repeats": REPEATS, "features": len(features), "targets": len(targets),
               "chemical_candidates": len(candidates), "rmse": q1.scores(y_values, oof)["rmse"],
               "frozen_oof_max_abs_difference": float(np.max(np.abs(oof-original[targets].to_numpy()))),
               "frozen_oof_rmse": q1.scores(y_values, original[targets].to_numpy())["rmse"],
               "modules_per_fold": [sum(r["fold"] == f for r in membership) for f in range(1, 6)],
               "mean_jaccard_with_spearman": float(np.mean([r["jaccard"] for r in comparisons])),
               "targets_with_no_top3_overlap": sum(r["overlap"] == 0 for r in comparisons),
               "targets_with_all_positive_top3_means": sum(r["all_three_positive_mean"] for r in comparisons),
               "input_sha256": {name: hashlib.sha256((data_dir()/name).read_bytes()).hexdigest() for name in ["1.csv", "4.csv"]},
               "elapsed_seconds": time.perf_counter() - started,
               "limitations": ["Same development beers; follow-up designed after viewing the main results.",
                               "Correlated and derived inputs can substitute for each other; individual permutation may break chemical consistency.",
                               "Training-fold correlation modules differ across folds and are reported separately, not pooled as identical objects.",
                               "Positive folds and fold SD describe stability, not independent significance tests or causal contributions."]}
    (OUT / "summary.json").write_text(json.dumps(summary, ensure_ascii=False, indent=2) + "\n", encoding="utf-8")
    print(json.dumps(summary, ensure_ascii=False, indent=2), flush=True)


if __name__ == "__main__":
    with threadpool_limits(limits=1):
        main()
```

supplement/q2_stratified_bootstrap.py

SHA-256: af7ab7e04241b297b306c35215c15472b1ba69330ff096afb2d19fc8d65b5c50

```
"""Exploratory Q2 bootstrap with the observed style counts held fixed.

Writes supplementary results in results/q2_stratified. Existing Q2 rankings and frozen outputs remain
the reference. Run with the solution's requirements-lock.txt environment.
"""
from __future__ import annotations

import hashlib
import importlib.metadata
import importlib.util
import json
from pathlib import Path
import platform
import time

import numpy as np
import pandas as pd


HERE = Path(__file__).resolve().parent
SOLUTION = HERE.parent
OUT = HERE / "results/q2_stratified"
REPOSITORY = SOLUTION.parent
SEED = 20261023
BOOTSTRAPS = 200


def sha256(path):
    return hashlib.sha256(path.read_bytes()).hexdigest()


def csv(frame, name):
    frame.to_csv(OUT / name, index=False, encoding="utf-8-sig",
                 float_format="%.10g", lineterminator="\n")


def set_score(a, b):
    a, b = set(a), set(b)
    return len(a & b) / len(a | b)


def main():
    OUT.mkdir(parents=True, exist_ok=True)
    started = time.perf_counter()
    helper_path = SOLUTION / "src/03_q2_network.py"
    spec = importlib.util.spec_from_file_location("q2_existing_helper", helper_path)
    helper = importlib.util.module_from_spec(spec)
    spec.loader.exec_module(helper)
    files = [helper_path, helper.DATA / "1.csv", helper.DATA / "4.csv",
             SOLUTION / "outputs/q2/all_candidate_stability.csv",
             SOLUTION / "outputs/q2/top3_compounds.csv",
             SOLUTION / "outputs/q2/summary.json"]
    before_hashes = {p.relative_to(REPOSITORY).as_posix(): sha256(p) for p in files}
    chemical = pd.read_csv(helper.DATA / "1.csv")
    sensory = pd.read_csv(helper.DATA / "4.csv")
    candidates = [c for c in chemical.columns[3:] if c not in helper.EXCLUDE_X
```

```
]
    targets = [c for c in sensory.columns[3:] if c not in helper.EXCLUDE_Y]
    merged = chemical.merge(sensory[["beer", *targets]], on="beer",
                            validate="one_to_one", how="inner")
    assert merged.shape[0] == 250 and len(candidates) == 218 and len(targets)
== 45
    x = merged[candidates].to_numpy(float)
    y = merged[targets].to_numpy(float)
    rho = helper.cross_correlation(x, y, "spearman")
    initial_top = helper.top3(rho)
    original = pd.read_csv(SOLUTION / "outputs/q2/all_candidate_stability.csv"
)
    original_top = pd.read_csv(SOLUTION / "outputs/q2/top3_compounds.csv")
    for t, target in enumerate(targets):
        expected = original_top[original_top.sensory_target.eq(target)].sort_v
alues("rank")
        assert expected.compound.tolist() == [candidates[j] for j in initial_t
op[:, t]]
        for j in range(len(candidates)):
            existing = original[(original.sensory_target == target)
                                & (original.compound == candidates[j])]
            assert len(existing) == 1
            assert abs(float(existing.spearman_rho.iloc[0]) - rho[j, t]) < 1e-
9

    labels = merged.tasting_category_fine.astype(str).to_numpy()
    # First appearance order is explicit, rather than relying on groupby sorti
ng.
    styles = list(pd.unique(labels))
    style_indices = [np.flatnonzero(labels == style) for style in styles]
    style_sizes = [len(indices) for indices in style_indices]
    counts = np.zeros((len(candidates), len(targets)), dtype=np.int64)
    sampled_indices = np.empty((BOOTSTRAPS, len(merged)), dtype=np.int16)
    winners = np.empty((BOOTSTRAPS, 3, len(targets)), dtype=np.int16)
    rng = np.random.default_rng(SEED)
    for b in range(BOOTSTRAPS):
        rows = np.concatenate([rng.choice(indices, size=len(indices), replace=
True)
                               for indices in style_indices])
        assert all(int(np.sum(labels[rows] == style)) == size
                   for style, size in zip(styles, style_sizes))
        selected = helper.top3(helper.cross_correlation(x[rows], y[rows], "spe
arman"))
        counts[selected, np.arange(len(targets))] += 1
        sampled_indices[b] = rows
        winners[b] = selected
    assert np.all(counts.sum(axis=0) == 3 * BOOTSTRAPS)
    frequency = counts / BOOTSTRAPS
    extra = []
    for t, target in enumerate(targets):
        for j, candidate in enumerate(candidates):
            extra.append({"sensory_target": target, "compound": candidate,
                          "stratified_top3_count": int(counts[j, t]),
                          "stratified_top3_frequency": float(frequency[j, t])}
)
    comparison = original.merge(pd.DataFrame(extra), on=["sensory_target", "co
mpound"],
                                validate="one_to_one")
    comparison["frequency_difference_stratified_minus_global"] = (
        comparison.stratified_top3_frequency - comparison.bootstrap_top3_frequ
ency)
    csv(comparison, "all_candidates_comparison.csv")
```

```
    top = comparison[comparison["rank"].le(3)].copy()
    csv(top, "original_top3_comparison.csv")
    set_rows = []
    for t, target in enumerate(targets):
        base_set = [candidates[j] for j in initial_top[:, t]]
        global_freq = original[original.sensory_target.eq(target)].set_index("
compound")
        global_order = global_freq.reindex(candidates).bootstrap_top3_frequenc
y.to_numpy()
        global_set = [candidates[j] for j in np.argsort(-global_order, kind="s
table")[:3]]
        stratified_set = [candidates[j] for j in np.argsort(-frequency[:, t],
kind="stable")[:3]]
        per_draw = [helper.jaccard(initial_top[:, t], winners[b, :, t])
                    for b in range(BOOTSTRAPS)]
        set_rows.append({
            "sensory_target": target,
            "original_full_sample_spearman_top3": " | ".join(base_set),
            "global_frequency_ranked_top3": " | ".join(global_set),
            "stratified_frequency_ranked_top3": " | ".join(stratified_set),
            "jaccard_original_vs_stratified_frequency": set_score(base_set, st
ratified_set),
            "jaccard_global_frequency_vs_stratified_frequency": set_score(glob
al_set, stratified_set),
            "original_full_sample_set_changed": False,
            "frequency_ranked_set_changed_global_vs_stratified": set(global_se
t) != set(stratified_set),
            "stratified_draw_mean_jaccard_with_original": float(np.mean(per_dr
aw)),
            "stratified_draw_exact_original_top3_fraction": float(np.mean(np.a
rray(per_draw) == 1)),
            "original_top3_stratified_frequency_ge_0p8": int(np.sum(frequency[
initial_top[:, t], t] >= .8)),
        })
    sets = pd.DataFrame(set_rows)
    csv(sets, "target_set_comparison.csv")
    cases = comparison[((comparison.sensory_target == "X4vg") & (comparison.co
mpound == "X4VG"))
                       | ((comparison.sensory_target == "F_esters_ethac") & (c
omparison.compound == "ethyl_acetate"))
                       | ((comparison.sensory_target == "F_malt_all") & (compa
rison.compound == "ethanol..v.v."))].copy()
    assert len(cases) == 3
    csv(cases, "case_studies.csv")
    np.savez_compressed(OUT / "draw_indices_and_selections.npz", row_indices=s
ampled_indices,
                        selected_feature_indices=winners,
                        candidate_order=np.asarray(candidates), target_order=n
p.asarray(targets),
                        beer_order=merged.beer.to_numpy(), style_order=np.asar
ray(styles))
    after_hashes = {p.relative_to(REPOSITORY).as_posix(): sha256(p) for p in f
iles}
    assert before_hashes == after_hashes, "An input or frozen Q2 file changed
during the run."
    summary = {
        "scope": "Exploratory follow-up after the original Q2 results were exa
mined; no original ranking or frozen result changed.",
        "seed": SEED, "bootstraps": BOOTSTRAPS,
        "resampling": "Independently resample each style with replacement, ret
aining its observed count; concatenate styles in their first-appearance order.
",
```

```
        "n_beers": 250, "n_candidate_compounds": 218, "n_targets": 45,
        "style_counts": dict(zip(styles, style_sizes)),
        "n_styles": len(styles), "minimum_style_n": min(style_sizes),
        "singleton_styles": [style for style, size in zip(styles, style_sizes)
 if size == 1],
        "same_helper": "solution_a/src/03_q2_network.py::cross_correlation, to
p3, jaccard",
        "original_full_sample_top3_exactly_matched": True,
        "original_full_sample_ranking_changed": False,
        "original_top3_positions": len(top),
        "original_top3_global_frequency_ge_0p8": int(top.bootstrap_top3_freque
ncy.ge(.8).sum()),
        "original_top3_stratified_frequency_ge_0p8": int(top.stratified_top3_f
requency.ge(.8).sum()),
        "all_candidates_stratified_frequency_ge_0p8": int(comparison.stratifie
d_top3_frequency.ge(.8).sum()),
        "original_top3_mean_frequency_global": float(top.bootstrap_top3_freque
ncy.mean()),
        "original_top3_mean_frequency_stratified": float(top.stratified_top3_f
requency.mean()),
        "original_top3_median_frequency_stratified": float(top.stratified_top3
_frequency.median()),
        "original_top3_mean_abs_frequency_change": float(top.frequency_differe
nce_stratified_minus_global.abs().mean()),
        "original_top3_max_abs_frequency_change": float(top.frequency_differen
ce_stratified_minus_global.abs().max()),
        "frequency_ranked_top3_sets_changed": int(sets.frequency_ranked_set_ch
anged_global_vs_stratified.sum()),
        "frequency_ranked_top3_mean_jaccard_global_vs_stratified": float(sets.
jaccard_global_frequency_vs_stratified_frequency.mean()),
        "targets_whose_stratified_frequency_ranked_set_differs_from_original":
 int(sets.jaccard_original_vs_stratified_frequency.lt(1).sum()),
        "original_vs_stratified_frequency_ranked_mean_jaccard": float(sets.jac
card_original_vs_stratified_frequency.mean()),
        "stratified_draw_mean_jaccard_with_original": float(sets.stratified_dr
aw_mean_jaccard_with_original.mean()),
        "max_single_frequency_monte_carlo_standard_error": float(np.sqrt(.25 /
 BOOTSTRAPS)),
        "frequency_set_definition": "Top three ranked by bootstrap inclusion f
requency, input-column-order tie break. This sensitivity summary is not a repl
acement for the original full-sample Spearman Top-3.",
        "cases": cases[["sensory_target", "compound", "rank", "spearman_rho",
"bootstrap_top3_frequency", "stratified_top3_frequency", "frequency_difference
_stratified_minus_global", "within_style_spearman_rho"]].to_dict("records"),
        "input_sha256_before": before_hashes, "input_sha256_after": after_hash
es,
        "inputs_and_frozen_q2_unchanged": before_hashes == after_hashes,
        "python": platform.python_version(),
        "package_versions": {p: importlib.metadata.version(p) for p in ["numpy
", "pandas", "scipy", "scikit-learn"]},
        "elapsed_seconds": time.perf_counter() - started,
        "limitations": [
            "Preserving the observed style mixture does not remove between-sty
le confounding.",
            "The real sample count remains 250; bootstrap draws are not new be
ers.",
            "Rare styles carry little information about within-style uncertain
ty; a singleton style would always resample its sole row and cannot estimate w
ithin-style variation. There are no singleton styles in these data (minimum n=
3).",
            "The identical seed does not make these draws paired with the old
global-row bootstrap, because their sampling algorithms differ.",
```

```
            "Differences of a few percentage points are subject to Monte Carlo variation, and no significance claim is made for a frequency difference.",
            "No causal inference, false-discovery guarantee, or held-out predictive validation is provided by this experiment.",
        ],
    }
    (OUT / "summary.json").write_text(json.dumps(summary, ensure_ascii=False, indent=2) + "\n", encoding="utf-8", newline="\n")
    print(json.dumps({k: v for k, v in summary.items() if k not in ["input_sha256_before", "input_sha256_after", "style_counts"]}, ensure_ascii=False, indent=2))


if __name__ == "__main__":
    main()
```

supplement/reference_tables.py

SHA-256: a0191d5003e8d8ba7ea448132b51bd9154b7b6b3e5181d35612f23c02240f5a8

```
"""Summarize saved evidence for the reference review without fitting models.

Run: python solution_a/supplement/reference_tables.py
Read from a paper builder: load_reference_tables(solution_root)
"""
from __future__ import annotations

from hashlib import sha256
import json
from pathlib import Path

import numpy as np
import pandas as pd


SOLUTION = Path(__file__).resolve().parents[1]
DESTINATION = SOLUTION / "supplement/results/reference_tables"
TOLERANCE = 1e-10
POLICY = {"arm": "fixed", "pool": "contracted_6004", "bound": "retain80", "ranking": "margin"}
DEFECT_ORDER = ["DMS", "Diacetyl", "4VG", "trans_2_nonenal"]
# Identity checked before this revision. These are provenance, not live inputs.
REVIEW_BASELINE = {
    "scope": "Pre-revision 353-page delivery checked on 2026-10-25; current submission hashes may change.",
    "pdf_pages": 353,
    "pdf_sha256": "03287ed5830de2d60d91cf1c2cd27223a16324e67c101cafe4167bc91fbdcdd1",
    "archive_sha256": "5545c955b303d4b362df54e7173ef436240f0bf21564ce8c2305c553f4fc3a75",
    "comparison_report_sha256": "d1e76bcb19b713dd8adcbd0dba3fae48142714128e434554b0627360f5b1fbc3",
    "packaged_report_matched_working_report": True,
    "packaged_transfer_matched_saved_transfer": True,
}
TABLE_NAMES = [
    "transfer_defect_concentrations", "transfer_defect_activity_summary",
    "beer96_chemical", "beer96_committees", "ethyl_acetate_module_by_fold",
    "ethyl_acetate_F_esters_ethac_by_fold", "rebuild_grid_field_counts",
    "rebuild_changed_policies", "rebuild_changed_frontier",
]


def digest(path):
    value = sha256()
    with path.open("rb") as handle:
        for chunk in iter(lambda: handle.read(1024 * 1024), b""):
            value.update(chunk)
    return value.hexdigest()


def newline_digest(path):
    return sha256(path.read_bytes().replace(b"\r\n", b"\n")).hexdigest()


def resolve_input(root, relative):
    """Resolve workspace or lean-archive saved-result locations."""
    direct = root / relative
```

```
    if direct.is_file():
        return direct
    if relative.startswith("outputs/"):
        return root.parent / "paper_results" / relative.removeprefix("outputs/
")
    if relative.startswith("review/verification/"):
        return root.parent / "verification" / relative.removeprefix("review/ve
rification/")
    if relative.startswith("supplement/results/"):
        return root.parent / "supplement_results" / relative.removeprefix("sup
plement/results/")
    return direct


def equal_value(left, right):
    if pd.isna(left) and pd.isna(right):
        return True
    if isinstance(left, (float, np.floating)) and isinstance(right, (float, in
t, np.floating)):
        return bool(np.isclose(left, right, rtol=0, atol=TOLERANCE))
    return bool(left == right)


def load_reference_tables(solution_root=SOLUTION):
    """Return named saved DataFrames plus summary; this read interface writes
nothing."""
    root = Path(solution_root)
    folder = resolve_input(root, "supplement/results/reference_tables/summary.
json").parent
    tables = {name: pd.read_csv(folder / f"{name}.csv") for name in TABLE_NAME
S}
    tables["summary"] = json.loads((folder / "summary.json").read_text(encodin
g="utf-8"))
    return tables


def build_reference_tables(solution_root=SOLUTION):
    root = Path(solution_root).resolve()
    output = root / "supplement/results/reference_tables"
    tracked = {}

    def source(relative):
        path = resolve_input(root, relative)
        tracked[relative] = {"path": relative, "bytes": path.stat().st_size, "
sha256": digest(path),
                             "newline_normalized_sha256": newline_digest(path)
}
        return path

    def csv(relative):
        return pd.read_csv(source(relative))

    def js(relative):
        return json.loads(source(relative).read_text(encoding="utf-8"))

    transfer = csv("outputs/q3_refined/transfer/transfer_summary.csv")
    selected = transfer.copy()
    for field, value in POLICY.items():
        selected = selected[selected[field].eq(value)]
    assert len(selected) == 11 and selected.source_beer.is_unique
    assert selected.candidate_index.notna().all()
    assert selected.fresh_consistency_passed.sum() == 10
```

```
    assert selected.loc[~selected.fresh_consistency_passed, "source_beer"].tol
ist() == [96]
    scenarios = js("outputs/q3_optimized/transfer/threshold_scenarios.json")
    metadata = js("outputs/q3/sensory/defect_thresholds.json")
    threshold = csv("outputs/q3_refined/transfer/threshold_checks.csv")
    threshold = threshold[threshold.transfer_id.isin(selected.transfer_id)].co
py()
    assert len(scenarios) == 10 and len(threshold) == 11 * 4 * 10
    for _, group in threshold.groupby(["transfer_id", "defect"]):
        assert group.scenario.nunique() == 10
        assert group.source.nunique() == group.transferred.nunique() == group.
feature.nunique() == 1
    concentration = threshold.groupby(["transfer_id", "defect", "feature"], as
_index=False).agg(
        source=("source", "first"), transferred=("transferred", "first"),
        cap=("cap", "min"), scenario_count=("scenario", "nunique"), passed=("p
assed", "all"))
    concentration = concentration.merge(selected[["transfer_id", "source_beer"
]],
                                        on="transfer_id", validate="many_to_
one")
    concentration["unit"] = concentration.defect.map(lambda name: metadata[nam
e]["unit"])
    concentration["unit_display"] = concentration.unit.replace({"ug/L": "µg/L"}
)
    concentration["delta"] = concentration.transferred - concentration.source
    concentration["slack"] = concentration.cap - concentration.transferred
    concentration["at_upper"] = np.isclose(concentration.transferred, concentr
ation.cap,
                                           rtol=0, atol=TOLERANCE)
    concentration["at_zero"] = np.isclose(concentration.transferred, 0, rtol=0
, atol=TOLERANCE)
    assert concentration.passed.all() and (concentration.slack >= -TOLERANCE).
all()
    assert (concentration.transferred >= -TOLERANCE).all()
    for row in concentration.itertuples():
        values = [s["thresholds"][row.feature] for s in scenarios if s["thresh
olds"][row.feature] is not None]
        expected = max(row.source, min(values)) if values else row.source
        assert np.isclose(row.cap, expected, rtol=0, atol=TOLERANCE)
    source_order = {beer: number for number, beer in enumerate(selected.source
_beer)}
    concentration = concentration.sort_values(
        ["source_beer", "defect"], key=lambda column: column.map(
            source_order if column.name == "source_beer" else {name: i for i,
name in enumerate(DEFECT_ORDER)}))
    concentration = concentration[["source_beer", "transfer_id", "defect", "fe
ature", "unit", "unit_display",
                                   "source", "transferred", "delta", "cap", "s
lack", "scenario_count",
                                   "passed", "at_upper", "at_zero"]].reset_ind
ex(drop=True)
    activity = concentration.groupby("defect").agg(
        sources=("source_beer", "size"), all_scenarios_passed=("passed", "sum"
),
        at_upper_count=("at_upper", "sum"), at_zero_count=("at_zero", "sum"),
        minimum_slack=("slack", "min"), maximum_slack=("slack", "max")).reinde
x(DEFECT_ORDER).reset_index()
    upper_counts = activity.set_index("defect").at_upper_count.to_dict()
    zero_counts = activity.set_index("defect").at_zero_count.to_dict()
    assert upper_counts == {"DMS": 11, "Diacetyl": 7, "4VG": 0, "trans_2_nonen
al": 10}
```

```
    assert zero_counts["4VG"] == 11
    chemical96 = concentration[concentration.source_beer.eq(96)].reset_index(drop=True)
    beer96 = selected[selected.source_beer.eq(96)].iloc[0]
    deltas = csv("outputs/q3_refined/transfer/paired_deltas.csv")
    deltas = deltas[deltas.transfer_id.eq(beer96.transfer_id)]
    stages = [
        ("new_selection", "current_selection", 40, True, "new_selection_q95"),
        ("old_selection", "old_selection", 30, True, "old_selection_q95"),
        ("new_audit", "current_fresh_audit", 20, True, "new_audit_q95"),
        ("old_fresh_audit", "old_fresh_audit", 20, True, "old_fresh_audit_q95"),
        ("old_historical", "old_historical_diagnostic", 10, False, "old_historical_q95"),
    ]
    committees = []
    for ensemble, stage, count, gate, field in stages:
        group = deltas[deltas.ensemble.eq(ensemble)].sort_values("model_index")
        assert len(group) == count and group.model_index.is_unique
        q95 = float(group.delta.quantile(0.95))
        assert np.isclose(q95, beer96[field], rtol=0, atol=TOLERANCE)
        committees.append({"source_beer": 96, "transfer_id": beer96.transfer_id, "stage": stage,
                           "ensemble": ensemble, "model_count": count,
                           "positive_count": int(group.delta.gt(0).sum()), "q95": q95,
                           "median_delta": float(group.delta.median()), "minimum_delta": float(group.delta.min()),
                           "maximum_delta": float(group.delta.max()), "q95_passed": q95 <= TOLERANCE,
                           "used_in_primary_gate": gate})
    for field, stage in [("center_new_delta", "current_center"), ("center_old_delta", "old_center")]:
        value = float(beer96[field])
        committees.append({"source_beer": 96, "transfer_id": beer96.transfer_id, "stage": stage,
                           "ensemble": "center_point", "model_count": 1, "positive_count": int(value > 0),
                           "q95": value, "median_delta": value, "minimum_delta": value,
                           "maximum_delta": value, "q95_passed": value <= TOLERANCE,
                           "used_in_primary_gate": True})
    committees = pd.DataFrame(committees)
    fresh96 = committees[committees.stage.eq("current_fresh_audit")].iloc[0]
    assert fresh96.positive_count == 2 and fresh96.q95 > 0
    assert int(beer96.feasible_count) == 13 and beer96.status == "new_audit_failed"

    membership = csv("supplement/results/q2_permutation/module_membership.csv")
    module_metrics = csv("supplement/results/q2_permutation/module_importance_by_fold.csv")
    individual = csv("supplement/results/q2_permutation/importance_by_fold.csv")
    membership["tokens"] = membership.members.map(lambda text: text.split(" | "))
    member = membership[membership.tokens.map(lambda tokens: "ethyl_acetate" in tokens)].copy()
    assert member.fold.tolist() == [1, 2, 3, 4, 5]
    assert member["size"].tolist() == [11, 12, 9, 11, 27]
```

```
    assert all(len(row.tokens) == row.size and row.tokens.count("ethyl_acetate
") == 1
                for row in member.itertuples())
    member["members_json"] = member.tokens.map(lambda value: json.dumps(value,
 ensure_ascii=False))
    member = member.rename(columns={"members": "memberlist"}).drop(columns="to
kens")
    module_metrics = module_metrics.rename(columns={"delta_mse": "module_delta
_mse",
                                                    "repeat_sd": "module_repea
t_sd"})
    module = member.merge(module_metrics.drop(columns="size"), on=["fold", "mo
dule"], validate="one_to_many")
    single = individual[individual.feature.eq("ethyl_acetate")].rename(
        columns={"sensory_target": "target", "delta_mse": "individual_delta_ms
e",
                 "repeat_sd": "individual_repeat_sd"}).drop(columns="feature")
    module = module.merge(single, on=["fold", "target"], validate="one_to_one"
)
    module = module[["fold", "module", "size", "target", "memberlist", "member
s_json",
                     "module_delta_mse", "individual_delta_mse", "module_repea
t_sd", "individual_repeat_sd"]]
    module = module.sort_values(["target", "fold"]).reset_index(drop=True)
    module_case = module[module.target.eq("F_esters_ethac")].reset_index(drop=
True)
    assert len(module) == 225 and len(module_case) == 5

    # The report was byte-matched to the reviewed 353-page delivery. Do not ma
ke
    # later PDF/ZIP regeneration a prerequisite for these numerical summaries.
    comparison_path = source("review/verification/rebuilt_numeric_comparison.j
son")
    comparison_bytes = comparison_path.read_bytes()
    comparison = json.loads(comparison_bytes)
    assert sha256(comparison_bytes.replace(b"\r\n", b"\n")).hexdigest() == REV
IEW_BASELINE["comparison_report_sha256"]
    evidence = comparison["q3_transfer_full_grid"]
    changes = evidence["changed_policies"]
    fields = ["candidate_index", "status", "new_model_passed", "fresh_consiste
ncy_passed", "historical_consistency_passed"]
    assert len({record["transfer_id"] for record in changes}) == len(changes)
    recounted = {field: sum(not equal_value(record["original"][field], record[
"rebuilt"][field])
                            for record in changes) for field in fields}
    assert all(recounted[field] == evidence["changed_policy_fields"][field] fo
r field in fields)
    assert recounted == {"candidate_index": 16, "status": 7, "new_model_passed
": 5,
                         "fresh_consistency_passed": 4, "historical_consistenc
y_passed": 5}
    assert len(changes) == evidence["changed_policies_count"] == 16
    assert evidence["policies"] == 792 and evidence["frontier_rows"] == 72
    frontier_changes = evidence["frontier_count_changed_rows"]
    assert len(frontier_changes) == 9
    for record in frontier_changes:
        assert set(record["original"]) == set(record["rebuilt"])
        assert any(record["original"][field] != record["rebuilt"][field] for f
ield in record["original"])
    for headline in comparison["q3_transfer_headlines"].values():
        assert all(abs(value) <= TOLERANCE for value in headline["difference"]
.values())
```

```
    assert all(comparison["q3_transfer_selected_candidates_and_statuses_match"].values())
    field_counts = pd.DataFrame([{"field": field, "changed_rows": count, "total_rows": 792}
                                 for field, count in recounted.items()])
    changed_policies = pd.json_normalize(changes, sep="_")
    changed_frontier = pd.json_normalize(frontier_changes, sep="_")
    summary = {
        "status": "PASS", "scope": "Saved-data summaries only; no fitting or new reconstruction run.",
        "policy": POLICY, "sources": 11, "concentration_rows": 44, "chemical_scenarios": 10,
        "chemical_all_passed": True, "upper_counts": upper_counts, "zero_counts": zero_counts,
        "interpretation": "Touching a bound is descriptive; it does not identify a binding causal bottleneck or a KKT multiplier.",
        "beer96": {"candidate_count": int(beer96.candidate_count), "feasible_count": 13,
                   "chemical_all_passed": True, "status": beer96.status,
                   "current_fresh_q95": float(fresh96.q95), "current_fresh_positive_count": 2,
                   "old_fresh_q95": float(beer96.old_fresh_audit_q95)},
        "ethyl_acetate_module": {"feature": "ethyl_acetate", "token_match": "exact pipe-delimited member token",
                                 "fold_sizes": member["size"].tolist(), "all_target_rows": 225,
                                 "case_target": "F_esters_ethac", "case_rows": 5,
                                 "scope": "Q1 231-variable fold graphs; not a Q3 226-variable soft constraint or causal importance."},
        "reconstruction": {"evidence_scope": "Recount of detailed saved historical reconstruction evidence packaged in the current verified delivery.",
                           "new_rebuild_performed": False, "raw_rebuilt_folder_available": (root.parent / comparison["rebuilt_outputs"]).exists(),
                           "historical_original_equals_current_outputs_required": False,
                           "historical_scope": "The report original/rebuilt pair is recounted internally; current transfer CSVs independently supply the chemistry and beer96 tables.",
                           "comparison_report": "review/verification/rebuilt_numeric_comparison.json",
                           "review_baseline_provenance": REVIEW_BASELINE,
                           "policies": 792, "changed_policies": 16, "changed_fields": recounted,
                           "frontier_rows": 72, "changed_frontier_count_rows": 9,
                           "principal_transfer_headlines": "PASS", "principal_transfer_rows": comparison["q3_transfer_comparison_rows"],
                           "full_grid_exact_reproduction": comparison["exact_full_grid_reproduction"]},
        "positive_count_definition": "Number of saved paired deltas strictly greater than zero; Q95 pass tolerance is 1e-10.",
    }
    tables = dict(zip(TABLE_NAMES, [concentration, activity, chemical96, committees, module, module_case,
                                    field_counts, changed_policies, changed_frontier]))
    output.mkdir(parents=True, exist_ok=True)
    for name, frame in tables.items():
        frame.to_csv(output / f"{name}.csv", index=False, float_format="%.17g")
    (output / "summary.json").write_text(json.dumps(summary, ensure_ascii=Fals
```

```
    e, indent=2, allow_nan=False) + "\n", encoding="utf-8")
267     for relative, record in tracked.items():
268         assert digest(resolve_input(root, relative)) == record["sha256"], f"In
    put changed during summary: {relative}"
269     manifest = {"script": {"path": "supplement/reference_tables.py", "sha256":
     digest(Path(__file__))},
270                 "inputs": list(tracked.values()), "outputs": [], "no_model_fit
    ting": True,
271                 "text_hash_rule": "Exact bytes, or CRLF/LF-only equivalence ve
    rified by newline_normalized_sha256.",
272                 "read_interface": "from supplement.reference_tables import loa
    d_reference_tables; tables = load_reference_tables(solution_root)"}
273     for path in sorted(output.iterdir()):
274         if path.name == "input_hash_manifest.json":
275             continue
276         manifest["outputs"].append({"path": path.relative_to(root).as_posix(),
     "bytes": path.stat().st_size,
277                                     "sha256": digest(path), "newline_normalize
    d_sha256": newline_digest(path)})
278     (output / "input_hash_manifest.json").write_text(json.dumps(manifest, ensu
    re_ascii=False, indent=2) + "\n", encoding="utf-8")
279     return summary
280
281
282 def verify_reference_tables(solution_root=SOLUTION):
283     """Verify saved summaries and their numerical inputs; no PDF/ZIP dependenc
    y."""
284     root = Path(solution_root).resolve()
285     output = resolve_input(root, "supplement/results/reference_tables/summary.
    json").parent
286     manifest = json.loads((output / "input_hash_manifest.json").read_text(enco
    ding="utf-8"))
287     assert digest(Path(__file__)) == manifest["script"]["sha256"]
288     assert all(not item["path"].startswith("submission/") for item in manifest
    ["inputs"])
289     for item in manifest["inputs"]:
290         path = resolve_input(root, item["path"])
291         exact = path.stat().st_size == item["bytes"] and digest(path) == item[
    "sha256"]
292         assert exact or newline_digest(path) == item["newline_normalized_sha25
    6"], item["path"]
293     for item in manifest["outputs"]:
294         path = resolve_input(root, item["path"])
295         exact = path.stat().st_size == item["bytes"] and digest(path) == item[
    "sha256"]
296         assert exact or newline_digest(path) == item["newline_normalized_sha25
    6"], item["path"]
297     tables = load_reference_tables(root)
298     concentration = tables["transfer_defect_concentrations"]
299     assert len(concentration) == 44 and concentration.source_beer.nunique() ==
     11
300     assert concentration.passed.all() and concentration.scenario_count.eq(10).
    all()
301     assert concentration.groupby("defect").at_upper.sum().to_dict() == {
302         "4VG": 0, "DMS": 11, "Diacetyl": 7, "trans_2_nonenal": 10}
303     assert concentration[concentration.defect.eq("4VG")].at_zero.all()
304     current_audit = tables["beer96_committees"].query("stage == 'current_fresh
    _audit'").iloc[0]
305     assert current_audit.model_count == 20 and current_audit.positive_count ==
     2
306     assert np.isclose(current_audit.q95, 0.0210027907557986, rtol=0, atol=TOLE
    RANCE)
```

```
    case = tables["ethyl_acetate_F_esters_ethac_by_fold"]
    assert case.fold.tolist() == [1, 2, 3, 4, 5] and case["size"].tolist() == [11, 12, 9, 11, 27]
    assert all(json.loads(row.members_json).count("ethyl_acetate") == 1 for row in case.itertuples())
    counts = tables["rebuild_grid_field_counts"].set_index("field").changed_rows.to_dict()
    assert counts["candidate_index"] == 16 and counts["status"] == 7 and counts["fresh_consistency_passed"] == 4
    assert len(tables["rebuild_changed_frontier"]) == 9
    return {"status": "PASS", "numerical_inputs_checked": len(manifest["inputs"]),
            "outputs_checked": len(manifest["outputs"]), "concentration_rows": 44,
            "committee_rows": 7, "module_case_rows": 5, "new_model_fitting": False,
            "current_submission_files_required": False}


if __name__ == "__main__":
    import argparse

    parser = argparse.ArgumentParser(description=__doc__)
    parser.add_argument("--verify-only", action="store_true", help="Read and verify saved summaries without writing")
    if parser.parse_args().verify_only:
        result = verify_reference_tables()
    else:
        result = build_reference_tables()
        result = {"status": result["status"], "output": str(DESTINATION),
                  "rows": result["concentration_rows"], "module_case_rows": 5,
                  "grid_changed_policies": result["reconstruction"]["changed_policies"]}
    print(json.dumps(result, ensure_ascii=False))
```

supplement/verify_supplement.py

SHA-256: e98d1d0bb8c6a7332fec3de0902432f9cbb07ca256e9b76e0ee908e9fa73c715

```
"""Read-only numerical checks for the supplementary analyses."""
import hashlib
import importlib.util
import json
from pathlib import Path
import sys

import numpy as np
import pandas as pd
from scipy.sparse.csgraph import connected_components
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.model_selection import KFold

HERE = Path(__file__).resolve().parent
ROOT = HERE.parent
sys.path.insert(0, str(ROOT / "src"))
from common import SEED, data_dir, load_xy


def module(filename):
    spec = importlib.util.spec_from_file_location("supplement_check_" + filena
me, ROOT / "src" / filename)
    result = importlib.util.module_from_spec(spec)
    spec.loader.exec_module(result)
    return result


def close(a, b):
    np.testing.assert_allclose(a, b, rtol=1e-8, atol=1e-10)


def scores(actual, predicted):
    return dict(mae=mean_absolute_error(actual, predicted),
                rmse=np.sqrt(mean_squared_error(actual, predicted)),
                macro_r2=r2_score(actual, predicted, multioutput="uniform_aver
age"))


def input_hash_matches(path, expected):
    raw = path.read_bytes()
    if hashlib.sha256(raw).hexdigest() == expected:
        return True
    if path.suffix not in {".csv", ".json"}:
        return False
    lf = raw.replace(b"\r\n", b"\n")
    return expected in {hashlib.sha256(lf).hexdigest(),
                        hashlib.sha256(lf.replace(b"\n", b"\r\n")).hexdigest()
}


def main():
    meta, x, y = load_xy()
    targets = list(y)
    checks = []
    q1 = HERE / "results/q1"
    metrics = pd.read_csv(q1 / "metrics_overall.csv")
    balanced = pd.read_csv(q1 / "balanced_group_metrics_overall.csv")
    tested = 0
    for path in q1.glob("oof_*.csv"):
```

```
        frame = pd.read_csv(path)
        assert frame.beer.tolist() == meta.beer.tolist()
        predicted = frame[targets].to_numpy()
        assert np.isfinite(predicted).all()
        name = path.stem.removeprefix("oof_")
        if "balanced" in name:
            model = "extra_trees" if name.endswith("extra_trees") else "mean"
            row = balanced.loc[balanced.model.eq(model)].iloc[0]
        else:
            protocol = "unseen_style_3fold" if name.startswith("unseen_style") else "random_3fold"
            model = name.removeprefix(protocol + "_")
            row = metrics.loc[metrics.protocol.eq(protocol) & metrics.model.eq(model)].iloc[0]
        for key, value in scores(y, predicted).items():
            close(row[key], value)
        for fold in sorted(frame.fold.unique()):
            test = frame.fold.eq(fold).to_numpy()
            if "unseen_style" in name:
                assert not set(meta.loc[test, "tasting_category_fine"]) & set(meta.loc[~test, "tasting_category_fine"])
            if model == "mean":
                close(predicted[test], np.tile(y.loc[~test].mean().to_numpy(), (test.sum(), 1)))
        tested += 1
    assert tested == 8
    draws = np.load(q1 / "test_mask_predictions.npz")
    for rate, field in [(.1, "rate10"), (.2, "rate20")]:
        assert draws[field].shape == (20, 250, 45)
        for repeat, predicted in enumerate(draws[field], 1):
            row = metrics.loc[metrics.protocol.eq("random_3fold_test_mask") & metrics.rate.eq(rate)
                              & metrics["repeat"].eq(repeat)].iloc[0]
            for key, value in scores(y, predicted).items():
                close(row[key], value)
    checks.append({"name": "q1_oof_metrics_and_group_exclusion", "oof_tables": tested, "mask_draws": 40})

    q2 = HERE / "results/q2_stratified"
    helper = module("03_q2_network.py")
    saved = np.load(q2 / "draw_indices_and_selections.npz")
    chemical = pd.read_csv(data_dir() / "1.csv")
    sensory = pd.read_csv(data_dir() / "4.csv")
    merged = chemical.merge(sensory[["beer", *targets]], on="beer", validate="one_to_one")
    candidates = saved["candidate_order"].tolist()
    candidate_targets = saved["target_order"].tolist()
    xx, yy = merged[candidates].to_numpy(), merged[candidate_targets].to_numpy()
    assert saved["beer_order"].tolist() == merged.beer.tolist()
    labels = merged.tasting_category_fine.to_numpy()
    counts = np.zeros((218, 45), dtype=int)
    for rows, winners in zip(saved["row_indices"], saved["selected_feature_indices"]):
        assert pd.Series(labels[rows]).value_counts().to_dict() == pd.Series(labels).value_counts().to_dict()
        counts[winners, np.arange(45)] += 1
    for i in [0, 99, 199]:
        rows = saved["row_indices"][i]
        np.testing.assert_array_equal(helper.top3(helper.cross_correlation(xx[rows], yy[rows], "spearman")),
                                      saved["selected_feature_indices"][i])
```

```
    table = pd.read_csv(q2 / "all_candidates_comparison.csv")
    for k, target in enumerate(candidate_targets):
        subset = table.loc[table.sensory_target.eq(target)].set_index("compoun
d").loc[candidates]
        close(subset.stratified_top3_count, counts[:, k])
        close(subset.stratified_top3_frequency, counts[:, k] / 200)
    checks.append({"name": "q2_stratified_draws_and_frequencies", "draws": 200
, "candidate_target_pairs": 9810})

    perm = HERE / "results/q2_permutation"
    arrays = np.load(perm / "permutation_draws.npz")
    delta = arrays["delta_mse"]
    assert delta.shape == (5, 5, 231, 45) and np.isfinite(delta).all()
    frame = pd.read_csv(perm / "oof.csv")
    assert frame.beer.tolist() == meta.beer.tolist()
    importance = pd.read_csv(perm / "importance.csv")
    fold_means = delta.mean(axis=1)
    for k, target in enumerate(targets):
        part = importance.loc[importance.sensory_target.eq(target)].set_index(
"feature").loc[x.columns]
        close(part.delta_mse, fold_means[:, :, k].mean(axis=0))
        close(part.fold_sd, fold_means[:, :, k].std(axis=0, ddof=1))
        close(part.positive_folds, (fold_means[:, :, k] > 0).sum(axis=0))
    membership = pd.read_csv(perm / "module_membership.csv")
    for fold, (train, test) in enumerate(KFold(5, shuffle=True, random_state=S
EED).split(x)):
        np.testing.assert_array_equal(arrays["check_test_rows"][fold], test)
        assert frame.iloc[test].fold.eq(fold + 1).all()
        truth = y.iloc[test].to_numpy()
        baseline = ((truth - frame.iloc[test][targets].to_numpy()) ** 2).mean(
axis=0)
        for k, feature in enumerate(arrays["check_features"]):
            j = list(x).index(feature)
            independent = ((arrays["check_predictions"][fold, :, k] - truth) *
* 2).mean(axis=1) - baseline
            close(independent, delta[fold, :, j])
        corr = x.iloc[train].corr(method="spearman").fillna(0).to_numpy()
        _, labels = connected_components(np.abs(corr) >= .7, directed=False)
        independent_groups = {frozenset(x.columns[labels == label]) for label
in set(labels)}
        recorded_groups = {frozenset(r.split(" | ")) for r in membership.loc[m
embership.fold.eq(fold+1), "members"]}
        assert independent_groups == recorded_groups
    top = pd.read_csv(perm / "top3.csv")
    for target in targets:
        eligible = importance.loc[importance.sensory_target.eq(target) & impor
tance.chemical_candidate].copy()
        order = {feature: i for i, feature in enumerate(x.columns)}
        eligible["order"] = eligible.feature.map(order)
        expected = eligible.sort_values(["delta_mse", "order"], ascending=[Fal
se, True]).head(3).feature.tolist()
        actual = top.loc[top.sensory_target.eq(target)].sort_values("candidate
_rank").feature.tolist()
        assert actual == expected
    checks.append({"name": "held_out_permutation_metrics_and_training_modules"
, "feature_target_pairs": 10395,
                   "folds": 5, "repeats": 5, "independent_raw_feature_checks":
 75})
    for source in [q1 / "manifest.json", q2 / "summary.json", perm / "summary.
json"]:
        record = json.loads(source.read_text(encoding="utf-8"))
        hashes = record.get("input_sha256", record.get("input_sha256_before",
```

```
{}))
        for name, expected in hashes.items():
            path = ROOT.parent / name if "/" in name else data_dir() / name
            assert input_hash_matches(path, expected), name
    from q1_indicator_ablation import verify_saved
    from reference_tables import verify_reference_tables
    checks.append({"name": "paired_missing_indicator_ablation", **verify_saved()})
    checks.append({"name": "saved_reference_tables", **verify_reference_tables()})
    report = {"status": "PASS", "checks": checks,
              "scope": "Saved supplementary calculations, fold separation and source integrity; no causal or independent-population validation."}
    (HERE / "verification.json").write_text(json.dumps(report, ensure_ascii=False, indent=2) + "\n", encoding="utf-8")
    print(json.dumps(report, ensure_ascii=False, indent=2))


if __name__ == "__main__":
    main()
```