

NAME

get_type – get type object

SYNOPSIS

```

#include <ShoreApp.h>

// Return the OID of T's persistent type object
// Return the OID of T's persistent type object
// Return the OID of T's persistent type object
shrc      Ref<T>::get_type(LOID &type_loid) const;

// The combination of the macro TYPE_OBJECT
// and the method isa() lets you cast references:
//
// returns a Ref<T>
// if "any" points to a T or subclass of T;
// otherwise they return a null ref:
//
// pardon the pseudo-code ...
const Ref<T> TYPE_OBJECT(T).isa(const Ref<U> &any);

{
    Ref<any>      aref;
    Ref<I>        iref;

    iref = TYPE_OBJECT(I).isa(a);
}

```

DESCRIPTION

The first form of **get_type** returns the logical oid of the object's type object. If the ref is nil, *LOID::null* is returned.

The CPP macro **TYPE_OBJECT(T)** yields a reference to the compiled-in C++ type object for T. Uses of **TYPE_OBJECT** will not compile if the SDL language binding for T is not included at compile time.

The second form of **get_type** returns a pointer to the given object's C++ type object, even if the SDL language binding for T is not included at compile time. In that case, the C++ type object is constructed from the type's persistent object. A null pointer is returned if the reference is not to a Shore object.

Get_type obtains a SH-mode (share-mode) lock on the object.

The method **isa** returns typed references:

```
iref = TYPE_OBJECT(T).isa(a);
```

If *any* points to a T or subclass of T, *any* is cast to a *Ref<T>* and returned. If not, a null reference is returned.

VERSION

This manual page applies to Version 1.1 of the Shore software.

SPONSORSHIP

The Shore project is sponsored by the Advanced Research Project Agency, ARPA order number 018 (formerly 8230), monitored by the U.S. Army Research Laboratory under contract DAAB07-91-C-Q518.

COPYRIGHT

Copyright © 1994, 1995, 1996, 1997, Computer Sciences Department, University of WisconsinMadison.
All Rights Reserved.

SEE ALSO

ref(cxxlb), stat(oc), ostat(cxxlb).