



TDM (TEST DATA MANAGEMENT) UPGRADE PROCEDURE TO V8.1

This document describes the following:

- How to upgrade TDM onto the present version: **V8.1**.
- How to re-implement the modified product's features.

Notes:

- This document does not cover the Fabric server topology changes, such as additions of nodes, data centers, changes of replication factors or consistency level.
- The TDM upgrade procedure should be performed on testing environments prior to applying it on your production deployment.
- Perform a sanity test upon completion of the upgrade procedure, such as running a few TDM tasks and conducting other checks per the sanity procedure defined in your project.

SOFTWARE UPGRADE PROCEDURE

1. TDM 8.1 Installation - Prerequisites

- Upgrade Fabric to Fabric 7.2 and above for TDM 8.1.

2. Related Documents

- [FABRIC UPGRADE PROCEDURE TO V7.2.0](#)
- [Note that Step 1 of Fabric Upgrade Procedure document is irrelevant for a TDM project, since the TDM project does not contain the iidFinder process.](#)

For more information about TDM V8.1 installation, please read the TDM Installation article in the [TDM Configuration](#).

3. Import the Updated TDM V8.1 Library

Step 1 – Back Up and Update the TDM Project Before the Import


- Run an export of the Fabric project in order to create a backup of the project before starting the upgrade. Verify that you have backups for the following objects:
 - CustomLogicFlow.actor
 - TDMSeqList.actor
 - TDMSeqSrc2TrgMapping.actor
 - FilterOutTargetTables.actor
 - TDMTargetTablesNames.actor
- Delete the following from your project:




TDM UPGRADE PROCEDURE

- TDM Library's Java files under the Shared Objects except the Shared Globals.

See the screenshot below:



- TDM Library's Shared Broadway flows in the TDM subfolder:




- TDM Library's Shared Templates (in the Shared Objects).



TDM UPGRADE PROCEDURE

- TDM Library's Web Services:



- TDM LU
- TDM_LIBRARY LU

Step 2 - Import the TDM Library to the Project

Open the TDM Fabric project in Fabric Studio and custom import the following objects of the updated TDM 8.1 Library into the Fabric project:

- **Web Services:** import all the Web Services' files.



TDM UPGRADE PROCEDURE

- **Shared Java files:** import all Java files in the Shared Objects.
- **Shared Globals:**
 - Import the shared Globals file from the TDM Library.
 - Import and override the shared Globals from the backed-up project to merge the project's setting and Globals into the shared Globals.
 - New shared Globals have been added. Edit them if needed:

Global name	Description	Default value	Additional information
TDM_DELETE_TABLES_PREFIX	TDM added an automatic generation of the target LU table to support the deletion of an entity by a TDM task. This Global defines the prefix for the generated target LU tables.	_TAR	Delete entities implementation
TDM_BATCH_LIMIT	Limit the number of entities to be populated into the TDM execution tables for a task execution. By default, the number of entities for a task execution is unlimited (-1)	-1	Task execution process
TDM_SEQ_REPORT	When set to true (the default value), the task execution populates the TDM_SEQ_MAPPING table and generates the Replace Sequence Summary Report tab in the task execution report. This Global can be set to false to avoid the population of TDM_SEQ_MAPPING and the generation of the Replace Sequence Summary Report for a better performance.	true	TDM Flows Implementation
TDM_POPULATE_JMX_STATS	Set this Global to true to enable the execution of populationJMX population flow on TASK_EXECUTION TDM LU table.	false	TDM statistics handling
SEQ_CACHE_INTREFACE	Starting from Fabric V7.2, SQLite and PostgreSQL are also supported as Fabric operational DBs in addition	DB_CASSANDRA	Fabric operational database



TDM UPGRADE PROCEDURE

Global name	Description	Default value	Additional information
	to Cassandra. If you use the TDM PG DB as the operational (system) DB, update this Global accordingly and set it to TDM.		

- **Shared Broadway Flows and Actors:**

- Import the shared Broadway flows and Actors from the TDM Library.
- After the import, edit the following Actors:
 - **TDMSeqList:**
 - Custom import the backed-up object from the export file, created for the project before the upgrade.
 - Note that starting from TDM 8.1 the CACHE_DB_NAME field is removed from the tdmSeqList, since the caching DB is taken from the SEQ_CACHE_INTREFACE Global. The old CACHE_DB_NAME will no longer be checked when generating sequence Actors. Instead, verify that the SEQ_CACHE_INTREFACE Global is set properly.

Click [here](#) for more information about the sequence implementation.

Click [here](#) for more information about Fabric operational DB.

- **TDMSeqSrc2TrgMapping:**
 - Custom import the backed-up object.
- **TDMFilterOutTargetTables:**
 - Custom import the backed-up object from the export file, created for the project before the upgrade.
- **CustomLogicFlows:**
 - Custom import the backed-up object from the export file, created for the project before the upgrade.

- **Shared Templates:** import the shared templates from the TDM Library.
- **TDM_LIBRARY LU:**
 - Import the TDM_LIBRARY LU from the TDM Library.
- **TDM LU:**
 - Import the TDM LU. Use the TDM LU export file (it contains only the TDM LU).



TDM UPGRADE PROCEDURE

- Note that you must use the *Import All* option to import the TDM portal code under the web subdirectory. The custom import method does not import the TDM portal code as the web subfolder is not supported by the desktop studio (it is supported only by the web studio).
- **TDM_Reference LU:**
 - Import the TDM_Reference LU from the TDM Library.

Step 3 – Update the LUs

- Copy and override FABRIC_TDM_ROOT LU and LU_PARAMS tables from the TDM_LIBRARY LU into each LU. This is needed due to the following changes:
 - FABRIC_TDM_ROOT table – the population flow has been updated to get the root entity id for each LUI, set it into a session key level, and populate it into task_execution_entities and <LU Name>_params TDM DB tables.
 - LU_PARAMS – both, table's structure and table's population, have been changed. Note that adding the LU parameters to the LU_PARAMS table is no longer required.

Step 4 – Deploy:

- Redeploy the Web Services to Fabric.
- Redeploy the TDM LU to Fabric:
Verify that the **BUILD_TDMDB** shared Global is set to **false** before deploying the TDM LU, otherwise the TDMDB will be created in the deploy flow.
- Redeploy the LUs to Fabric.
- Redeploy the TDM_Reference to Fabric.

4. Run the Upgrade Flow

The upgrade flow needs to run in order to upgrade the following:

- TDM database.
- Convert the TDM translations into MTables

TDM UPGRADE FLOW EXECUTION

- Take the following steps **before** running the upgrade script:
 - Back up the TDM DB. You can use the pgAdmin and create a backup file on the TDMDB.
 - Deploy all LUs including the TDM LU to Fabric debug server.
 - Stop all TDM jobs on Fabric debug and execution servers in order to avoid locking the TDM DB tables by the parallel execution of the upgrade script and the TDM jobs. Use the Web Admin to stop the TDM jobs:



TDM UPGRADE PROCEDURE

Type	Name	UID	Status	Creation Time	Start Time	End Time
USER_JOB	TDM.tdmExecuteTask	tdmExecuteTask	SCHEDULED	2023-09-18 08:34:48	2023-09-18 08:34:50	2023-09-18 08:34:50
USER_JOB	TDM.TDMDB_CleanUp	TDMDB_CleanUp	SCHEDULED	2023-09-18 08:34:48	2023-09-18 08:34:50	2023-09-18 08:34:52
USER_JOB	TDM.fnCheckMigrateAndUpdateTDMDB	checkMigrateAndUpdateTDMDB	SCHEDULED	2023-09-18 08:34:48	2023-09-18 08:34:50	2023-09-18 08:34:50
Start	TDM.tdmTaskScheduler	tdmTaskScheduler	SCHEDULED	2023-09-18 08:34:48	2023-09-18 08:34:50	2023-09-18 08:34:50
Restart						
Stop						

- Verify that the imported **TDMDBUpgradeScripts** Actor has an entry to upgrade the TDM to 8.1: Verify that the script_name is populated with update_tdmdb_from_v8.0_to_v8.1.sql and that the flow_name is populated with Upgrade80_to_81.
- Run the **RunTDMDBUpgradeScripts** flow. Populate the current version and the target version input parameters. Set the target version parameter to 8.1. For example:
CURRENT_TDM_VERSION = 8.0.
TARGET_TDM_VERSION = 8.1.
- Note that you can run the **RunTDMDBUpgradeScripts** flow from Fabric console using the following command:

Broadway TDM.RunTDMDBUpgradeScripts CURRENT_TDM_VERSION='8.0',
TARGET_TDM_VERSION='8.1';

TDM DB UPGRADE

- The **RunTDMDBUpgradeScripts** flow runs update_tdmdb_from_v8.0_to_v8.1.sql script. This script adds new fields to the TDM DB tables and populates the new fields in task_execution_entities and <LU Name>_params tables.

LU PARAMETERS TABLE UPGRADE

- Previous TDM versions created a materialized view in the TDM DB on each combination of BE and source environment, enabling a selection of entities based on parameters. From TDM 8.1 onwards, each LU parameters table (naming convention: <LU name>_params) contains the following fields, connecting the entity id to its root entity:
 - root_lu_name
 - root_iid

These fields are also added to the task_Execution_entities tables.

- The upgrade script **updates the <LU name>_params tables based on the task_execution_entities table**. Note that if the related task_execution_entities record has previously been cleaned by the TDM clean-up process, the upgrade job deletes the related <LU name>_params record as well.
- **Rerun the Extract tasks after the TDM upgrade to repopulate the missing <LU name>_params records if the cleaned task executions' parameters are needed.**



TDM UPGRADE PROCEDURE

- The materialized views are no longer needed. Still, to be on the safe side, **the upgrade script does not drop the materialized views from the TDM DB**. You can drop them after running the TDM 8.1 successfully for a while.

CONVERT THE TDM TRANSLATIONS INTO MTABLES

- TDM replaces the previous TDM translations with MTables to support the TDM development on both Fabric Studios - Desktop-Studio and Web-Studio.
- The **RunTDMDBUpgradeScripts** flow runs the **Upgrade80_to_81** flow, which invokes the **convertLuTranslations** inner flow in order to convert old TDM translations to the new equivalent TDM MTables. Each execution of the upgrade flow deletes and re-populates the related MTables.

TDM UPGRADE – POST EXECUTION ACTIVITIES

- Deploy the Reference to Fabric (debug and execution servers): the MTables are populated with the translation data.
- Deploy all the LUs to Fabric. Verify that the TDM jobs are up and running.

5. Optional - Data Generation Implementation – PII Fields

- The implementation guidelines for the previous TDM version recommended to use the LU population's Masking Actors for the synthetic data generation as well. However, this approach was less effective when defining a PII field as an external input parameter for the data generation task.
- There are 2 alternatives for existing data generation flows:
 - Keep the existing implementation using the Masking actors. In order to enable the Masking Actors on data generation tasks, you must check the Mask Sensitive Data checkbox of the Synthetic environment window in the TDM portal.
 - Edit the data generation flows: use the random data generation Actors or the new TDM 8.1 Actor: GenerateConsistent.
- Note: TDM 8.1 supports an integration with Fabric catalog for data generation and the TDM 8.1 templates create new data generation flows with Fabric catalog Actors. However, the existing data generation flows can still work. It is not mandatory to edit them.

[Click here for guidelines on data generation implementation.](#)

6. TDM Portal – Re-saving Tasks with Parameters Selection Method

- TDM changes the way the tasks with Parameters selection method are saved in the TDM DB. Therefore, it is required to open and re-save TDM tasks with Parameters selection method after upgrading the TDM to 8.1 and before executing the TDM tasks.



7. Optional - Change Fabric Storage to a Storage that does not Support a TTL

- TDM enables creating tasks with a retention period (TTL) on the task's entities in order to save these entities in Fabric only for a limited period of time. However, if the Fabric storage does not support a TTL for the LUIs (such as PG DB), the TDM needs to limit the TDM task's retention period options to either 'Do not Delete' or 'Do not Retain'.
- Run the following steps to limit the TDM retention period:
 - I. Update the `tdm_general_parameters` TDM DB to limit the TDM task's retention period options to either 'Do not Delete' or 'Do not Retain'.

View the Update statements in

https://support.k2view.com/Academy/articles/TDM/tdm_configuration/02_tdmdb_general_parameters.html

II. Open the TDM portal, then open the TDM tasks and update them with a retention period other than 'Do not Delete' or 'Do not Retain'.