

---

# Contents

---

<b>Contents</b>	<b>i</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Security amplification theorems . . . . .	1
1.2 Organization of the thesis . . . . .	1
<b>2 Preliminaries</b>	<b>3</b>
2.1 Notation . . . . .	3
2.2 Pairwise independent family of hash functions . . . . .	4
2.3 Oracle Algorithms . . . . .	5
<b>3 Weakly verifiable cryptographic primitives</b>	<b>7</b>
3.1 Weakly verifiable puzzles . . . . .	7
3.2 Examples . . . . .	8
3.2.1 Message authentication codes . . . . .	8
3.2.2 Public key encryption . . . . .	8
3.2.3 Bit commitments . . . . .	8
3.2.4 CAPTACHs . . . . .	8
3.3 Preview results . . . . .	8
3.3.1 Results of R.Canetti, S.Halevi, and M.Steiner . . . . .	8
3.3.2 Results of Y.Dodis, R.Impagliazzo, R.Jaiswal, V.Kabanets	8
3.3.3 Results of T.Holenstein and G.Scheonebeck . . . . .	8
3.4 Limitations of security amplification . . . . .	8
<b>4 Security amplification for dynamic weakly verifiable puzzles</b>	<b>9</b>
4.1 Main theorem . . . . .	9
4.2 Intuition . . . . .	9
4.3 Domain partitioning . . . . .	9
4.4 Amplification proof for partitioned domain . . . . .	9
4.5 Putting it together . . . . .	9

## CONTENTS

---

4.6	Discussion . . . . .	9
4.6.1	Intuition . . . . .	11
4.7	The main result . . . . .	12
<b>A</b>	<b>Appendix</b>	<b>31</b>
A.1	Basic inequalities . . . . .	31
	<b>Bibliography</b>	<b>33</b>

## Chapter 1

---

# Introduction

---

### 1.1 Security amplification theorems

Introduction to security amplification theorems and hardness implication statements. Example of classical results. Problems captured by weakly verifiable puzzles. Contribution of this thesis.

### 1.2 Organization of the thesis

Overview of the content of the succeeding chapters.



## Chapter 2

---

# Preliminaries

---

In this section we set up notation and terminology used in the thesis.

### 2.1 Notation

**(Algorithms, Bitstrings and Circuits)** We define a circuit as a directed acyclic graph with input vertices and vertices implementing logical functions *and*, *or*, and *not*. We denote circuits using capital letters from the Greek and English alphabet. For a circuit  $C$  we write  $Size(C)$  to denote total number of vertices of  $C$ . We define a *family of probabilistic circuits*  $\{C_n\}$  as a family of circuits taking as part of the input a random bitstring. A circuit  $C_n \in \{C_n\}$  is called a probabilistic circuit. We define a *two phase circuit*  $C := (C_1, C_2)$  as a circuit where in the first phase a circuit  $C_1$  is used and in the second phase a circuit  $C_2$ . It is well known [AB09] that a probabilistic polynomial time algorithm can be represented as a circuit of polynomial size. Additionally it can be computed in polynomial time and logarithmic space. Therefore, whenever we state a theorem about circuits we can also apply it to polynomial time algorithms.

We write  $poly(\alpha_1, \dots, \alpha_n)$  to denote a polynomial on variables  $\alpha_1, \dots, \alpha_n$ . For an algorithm  $A$  we write  $Time(A)$  to denote the number of steps it takes to execute  $A$ . We often write the randomness used by a probabilistic algorithm explicitly as a bitstring provided as an auxiliary input.

We write  $\{0, 1\}^n$  to denote a set of all bitstring of length  $n$ , and  $\{0, 1\}^*$  for a set of bitstrings that length is arbitrary. We note that for probabilistic algorithms and circuits the length of an arbitrary bitstring provided as an input is naturally bounded by running time of an algorithm or number of input vertices of a circuit.

**(Probabilities and distributions)** For a finite set  $\mathcal{R}$  we write  $r \xleftarrow{\$} \mathcal{R}$  to denote that  $r \in \mathcal{R}$  is chosen from  $\mathcal{R}$  uniformly at random. For  $\delta \in \mathbb{R} : 0 \leq \delta \leq$

1 we write  $\mu_\delta$  to denote the Bernoulli distribution where outcome 1 occurs with probability  $\delta$  and 0 with probability  $1 - \delta$ . Moreover, we use  $\mu_\delta^k$  to denote the probability distribution over  $k$ -tuples where each element of a  $k$ -tuple is drawn independently according to  $\mu_\delta$ . Finally, let  $u \leftarrow \mu_\delta^k$  denote that a  $k$ -tuple  $u$  is chosen according to  $\mu_\delta^k$ .

Let  $(\Omega, \mathcal{F}, \Pr)$  be a probability space and  $n \in \mathbb{N}$ . We say that an event  $E_n \in \mathcal{F}$  happens *almost surely* or with *high probability* if  $\Pr[E_n] \geq 1 - 2^{-n} \text{poly}(n)$ .

**(Interactive protocols)** We are often interested in situations where two probabilistic algorithms interact with each other according to some protocol. A protocol execution between two probabilistic algorithms  $A$  and  $B$  is denoted by  $\langle A, B \rangle$ . We limit ourselves to the cases where  $A$  and  $B$  interact by means of messages that can be represented as bitstrings. The output of  $A$  in a protocol execution is denoted by  $\langle A, B \rangle_A$  and of  $B$  by  $\langle A, B \rangle_B$ . A sequence of all messages sent by  $A$  and  $B$  in the protocol execution is called a communication transcript and is denoted by  $\langle A, B \rangle_{\text{trans}}$ .

## 2.2 Pairwise independent family of hash functions

**Definition 2.1 (Polynomial time sampleable function) *TODO*:**

**Definition 2.2 (Pairwise independent family of efficient hash functions)**

Let  $\mathcal{D}$  and  $\mathcal{R}$  be finite sets and  $\mathcal{H}$  be a family of functions mapping values from  $\mathcal{D}$  to values in  $\mathcal{R}$ . We say that  $\mathcal{H}$  is an *efficient family of pairwise independent hash functions* if  $\mathcal{H}$  has the following properties.

**(Pairwise independent)** For  $\forall x \neq y \in \mathcal{D}$  and  $\forall \alpha, \beta \in \mathcal{R}$ , it holds

$$\Pr_{\text{hash} \leftarrow \mathcal{H}}[\text{hash}(x) = \alpha \mid \text{hash}(y) = \beta] = \frac{1}{|\mathcal{R}|}.$$

**(Polynomial time sampleable)** For every  $\text{hash} \in \mathcal{H}$  the function  $\text{hash}$  is sampleable in time  $\text{poly}(\log |\mathcal{D}|, \log |\mathcal{R}|)$ .

**(Efficiently computable)** For every  $\text{hash} \in \mathcal{H}$  there exists an algorithm running in time  $\text{poly}(\log |\mathcal{D}|, \log |\mathcal{R}|)$  which on input  $x \in \mathcal{D}$  outputs  $y \in \mathcal{R}$  such that  $y = \text{hash}(x)$ .

We note that the pairwise independence property is equivalent to

$$\Pr_{\text{hash} \leftarrow \mathcal{H}}[\text{hash}(x) = \alpha \wedge \text{hash}(y) = \beta] = \frac{1}{|\mathcal{R}|^2}.$$

It is well known [CW77] that there exists a family of hash functions meeting the above criteria.

## 2.3 Oracle Algorithms

Explain the motivation to model our problem using algorithms with oracle access. Clarify the case when an algorithm is run with different oracles, or the oracle calls are simulated and answered by the algorithm. Description how the oracle calls are counted.





## Chapter 3

---

# Weakly verifiable cryptographic primitives

---

In this chapter we introduce the notion of weakly verifiable puzzles. In section 3.1 we provide a formal definitions that is followed by a series of cryptographic primitives that are captured by this notion. Finally, in Section 3.3 we give an overview of the earlier research in this area that is primarily covered in [CHS04], [DIJK09], and [HS10].

### 3.1 Weakly verifiable puzzles

**Definition 3.1 (Dynamic weakly verifiable puzzle.)** *A dynamic weakly verifiable puzzle (DWVP) is defined by a family of probabilistic circuits  $\{P_n\}$ . A circuit belonging to  $\{P_n\}$  is called a problem poser. A solver  $C := (C_1, C_2)$  for  $P_n$  is a probabilistic two phase circuit. We write  $P_n(\pi)$  to denote the execution of  $P_n$  with the randomness fixed to  $\pi \in \{0, 1\}^n$ , and  $(C_1, C_2)(\rho)$  to denote the execution of both  $C_1$  and  $C_2$  with the randomness fixed to  $\rho \in \{0, 1\}^*$ .*

*In the first phase, the problem poser  $P_n(\pi)$  and the solver  $C_1(\rho)$  interact. As the result of the interaction  $P_n(\pi)$  outputs a verification circuit  $\Gamma_V$  and a hint circuit  $\Gamma_H$ . The circuit  $C_1(\rho)$  produces no output. The circuit  $\Gamma_V$  takes as input  $q \in Q$ , an answer  $y \in \{0, 1\}^*$ , and outputs a bit. We say that an answer  $(q, y)$  is a correct solution if and only if  $\Gamma_V(q, y) = 1$ . The circuit  $\Gamma_H$  on input  $q \in Q$  outputs a hint such that  $\Gamma_V(q, \Gamma_H(q)) = 1$ .*

*In the second phase,  $C_2$  takes as input  $x := \langle P_n(\pi), C_1(\rho) \rangle_{trans}$ , and has oracle access to  $\Gamma_V$  and  $\Gamma_H$ . The execution of  $C_2$  with the input  $x$  and the randomness fixed to  $\rho$  is denoted by  $C_2(x, \rho)$ . The queries of  $C_2$  to  $\Gamma_V$  and  $\Gamma_H$  are called verification queries and hint queries respectively. The circuit  $C_2$  succeeds if*

*and only if it makes a verification query  $(q, y)$  such that  $\Gamma_V(q, y) = 1$ , and it has not previously asked for a hint query on  $q$ .*

## **3.2 Examples**

### **3.2.1 Message authentication codes**

### **3.2.2 Public key encryption**

### **3.2.3 Bit commitments**

### **3.2.4 CAPTACHs**

## **3.3 Previews results**

### **3.3.1 Results of R.Canetti, S.Halevi, and M.Steiner**

### **3.3.2 Results of Y.Dodis, R.Impagliazzo, R.Jaiswal, V.Kabanets**

### **3.3.3 Results of T.Holenstein and G.Scheonebeck**

## **3.4 Limitations of security amplification**

## Chapter 4

---

# Security amplification for dynamic weakly verifiable puzzles

---

In this chapter we show that it is possible to amplify security of dynamic weakly verifiable puzzles. In section 4.1 we state the theorem, which is next proved in three steps. First, in Section 4.3, we show how to use to partition the domain on which hint and verification queries are asked, next we give a prove of security amplification under the simplifying assumption that there is no collisions of hint and verification queries. Finally, in Section 4.5 we combine both former steps which yields the desirable result.

### 4.1 Main theorem

### 4.2 Intuition

### 4.3 Domain partitioning

### 4.4 Amplification proof for partitioned domain

### 4.5 Putting it together

### 4.6 Discussion

**Definition 4.1 ( $k$ -wise direct-product of DWVPs.)** Let  $g : \{0,1\}^k \rightarrow \{0,1\}$  be a monotone function and  $P_n^{(1)}$  a problem poser as in Definition 3.1. The  $k$ -wise direct product of  $P_n^{(1)}$  is a DWVP defined by a circuit  $P_{kn}^{(g)}$ . We write  $P_{kn}^{(g)}(\pi^{(k)})$  to denote the execution of  $P_{kn}^{(g)}$  with the randomness fixed to  $\pi^{(k)} := (\pi_1, \dots, \pi_k)$  where for each  $1 \leq i \leq n : \pi_i \in \{0,1\}^n$ . Let  $(C_1, C_2)(\rho)$  be

a solver for  $P_{kn}^{(g)}$  as in Definition 3.1. In the first phase, the algorithm  $C_1(\rho)$  sequentially interacts in  $k$  rounds with  $P_{kn}^{(g)}(\pi^{(k)})$ . In the  $i$ -th round  $C_1(\rho)$  interacts with  $P_n^{(1)}(\pi_i)$ , and as the result  $P_n^{(1)}(\pi_i)$  generates circuits  $\Gamma_V^i, \Gamma_H^i$ . Finally, after  $k$  rounds  $P_{kn}^{(g)}(\pi^{(k)})$  outputs a verification circuit

$$\Gamma_V^{(g)}(q, y_1, \dots, y_k) := g(\Gamma_V^1(q, y_1), \dots, \Gamma_V^k(q, y_k))$$

and a hint circuit

$$\Gamma_H^{(k)}(q) := (\Gamma_H^1(q), \dots, \Gamma_H^k(q)).$$

If it is clear from the context, we omit the subscript  $n$  and write  $P(\pi)$  instead of  $P_n(\pi)$  where  $\pi \in \{0, 1\}^n$ .

A verification query  $(q, y)$  of a solver  $C$  for which a hint query on this  $q$  has been asked before cannot be a verification query for which  $C$  succeeds. Therefore, without loss of generality, we make the assumption that  $C$  does not ask verification queries on  $q$  for which a hint query has been asked before. Furthermore, we assume that once  $C$  asked a verification query that succeeds, it does not ask any further hint or verification queries.

**Experiment**  $\text{Success}^{P,C}(\pi, \rho)$

**Oracle:** A problem poser  $P$ , a solver  $C = (C_1, C_2)$  for  $P$ .

**Input:** Bitstrings  $\pi \in \{0, 1\}^n$ ,  $\rho \in \{0, 1\}^*$ .

**Output:** A bit  $b \in \{0, 1\}$ .

```

run  $\langle P(\pi), C_1(\rho) \rangle$ 
       $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$ 
       $x := \langle P(\pi), C_1(\rho) \rangle_{\text{trans}}$ 

run  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$ 
      if  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$  asks a verification query  $(q, y)$  s.t.  $\Gamma_V(q, y) = 1$  then
        return 1
return 0
    
```

We define the *success probability* of  $C$  in solving a puzzle defined by  $P$  as

$$\Pr_{\pi, \rho}[\text{Success}^{P,C}(\pi, \rho) = 1]. \quad (4.1)$$

Furthermore, we say that  $C$  *succeeds* for  $\pi, \rho$  if  $\text{Success}^{P,C}(\pi, \rho) = 1$ .

**Theorem 4.2 (Security amplification for dynamic weakly verifiable puzzles.)**

Let  $P_n^{(1)}$  be a fixed problem poser as in Definition 3.1 and  $P_{kn}^{(g)}$  a problem poser for the  $k$ -wise direct product of  $P_n^{(1)}$ . Additionally, let  $C$  be a problem solver for  $P_{kn}^{(g)}$  asking at most  $h$  hint queries and  $v$  verification queries. There exists a probabilistic algorithm  $Gen$  with oracle access to a solver circuit  $C$ , a monotone function  $g : \{0, 1\}^k \rightarrow \{0, 1\}$  and problem posers  $P_n^{(1)}$ ,  $P_{kn}^{(g)}$ . Furthermore,  $Gen$  takes as input parameters  $\varepsilon$ ,  $\delta$ ,  $n$ ,  $k$ ,  $h$ ,  $v$ , and outputs a solver circuit  $D$  for  $P_n^{(1)}$  such that the following holds:

If  $C$  is such that

$$\Pr_{\substack{\pi^{(k)} \in \{0,1\}^{kn} \\ \rho \in \{0,1\}^*}} \left[ \text{Success}^{P_{kn}^{(g)}, C}(\pi^{(k)}, \rho) = 1 \right] \geq 16(h + v) \left( \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon \right)$$

then  $D$  is a two phase probabilistic circuit and satisfies almost surely

$$\Pr_{\substack{\pi \in \{0,1\}^n \\ \rho \in \{0,1\}^*}} \left[ \text{Success}^{P_n^{(1)}, D}(\pi, \rho) = 1 \right] \geq \delta + \frac{\varepsilon}{6k}.$$

Additionally,  $D$  requires oracle access to  $g$ ,  $P_n^{(1)}$ ,  $C$ , hint and verification circuits and asks at most  $\frac{6k}{\varepsilon} \log\left(\frac{6k}{\varepsilon}\right) h$  hint queries and one verification query. Finally,  $\text{Time}(Gen) = \text{poly}(k, \frac{1}{\varepsilon}, n, v, h)$  with oracle access to  $C$ .

**4.6.1 Intuition**

The idea of the algorithm  $Gen$  is to output a circuit  $D$  that solves the input puzzle often. We know that  $C$  has high success probability in solving the  $k$ -wise direct product of  $P^{(1)}$ . The algorithm  $Gen$  tries to find a puzzle such that when  $C$  runs with this puzzle fixed on the first position and disregards whether this puzzle is correctly solved then the assumptions of Theorem 4.2 are true for the  $(k - 1)$ -wise direct product. If it was possible to find such a puzzle, then  $Gen$  could recurse and solve a smaller problem. In the optimistic case we can reach  $k = 1$ , which means that we found a good circuit for solving a single puzzle by just fixing the initial puzzles of  $C$ .

Otherwise, when the first position is disregarded then the success probability of  $C$  is not substantially better. This is remarkable, as we know that  $C$  performs good for the  $k$ -wise direct product. It means that the first position is important, in the sense that  $C$  solves the puzzle on that position unusually often. Therefore, it is reasonable to construct the circuit  $D$  using  $C$  by placing the input puzzle of  $D$  on that position, and then finding remaining  $k - 1$  puzzles. The  $(k - 1)$  remaining puzzles are generated by the circuit  $D$ , hence it is possible to check whether they are correctly solved by the circuit  $C$ . We know that circuit  $C$  has good success probability, and the puzzle on the first position is important. Therefore, if we are able to find a  $(k - 1)$  puzzles such

that the fact whether the  $k$ -wise direct product is correctly solved depends on whether the puzzle on the first position is correctly solved then we can assume that  $C$  is often correct on this first position.

There are some problems with this approach, first we have to ensure that we can make a decision when the algorithm  $Gen$  should recurse and when not correctly with high probability. Then, we have to show that it is possible to find a puzzles such that  $C$  is often correct on the first position. Finally, we also have to be sure that we do not ask a hint query, on the final verification query to the oracle. To satisfy the last requirement we split the set  $Q$ .

## 4.7 The main result

Let  $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$ , the idea is to partition  $Q$  such that the set of preimages of 0 for  $hash$  contains  $q \in Q$  on which  $C$  is not allowed to ask hint queries, and the first successful verification query  $(q, y)$  of  $C$  is such that  $hash(q) = 0$ . Therefore, if  $C$  makes a verification query  $(q, y)$  such that  $hash(q) = 0$ , then we know that no hint query is ever asked on this  $q$ .

We denote the  $i$ -th query of  $C$  by  $q_i$  if it is a hint query, and by  $(q_i, y_i)$  if it is a verification query. We define the following experiment *CanonicalSuccess* in which the set  $Q$  is partitioned using a function  $hash$ . We say that a solver circuit *succeeds* in the experiment *CanonicalSuccess* if it asks a successful verification query  $(q_j, y_j)$  such that  $hash(q_j) = 0$ , and no hint query  $q_i$  is asked before  $(q_j, y_j)$  such that  $hash(q_i) = 0$ .

**Experiment**  $CanonicalSuccess^{P,C,hash}(\pi, \rho)$

**Oracle:** A problem poser  $P$ , a solver circuit  $C = (C_1, C_2)$  for  $P$ ,  
a function  $hash : Q \rightarrow \{0, \dots, 2(h + v) - 1\}$ .

**Input:** Bitstrings  $\pi \in \{0, 1\}^n$ ,  $\rho \in \{0, 1\}^*$ .

**Output:** A bit  $b \in \{0, 1\}$ .

```

run  $\langle P(\pi), C_1(\rho) \rangle$ 
       $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$ 
       $x := \langle P(\pi), C_1(\rho) \rangle_{trans}$ 

run  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$ 
      if  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$  does not succeed for any verification query then
        return 0
      Let  $(q_j, y_j)$  be the first verification query such that  $\Gamma_V(q_j, y_j) = 1$ .

if  $(\forall i < j : hash(q_i) \neq 0)$  and  $(hash(q_j) = 0)$  then
```

<pre> <b>return</b> 1 <b>else</b> <b>return</b> 0 </pre>
--

We define the *canonical success probability* of a solver circuit  $C$  for  $P$  with respect to a function  $hash$  as

$$\Pr_{\pi, \rho}[CanonicalSuccess^{P, C, hash}(\pi, \rho) = 1]. \quad (4.2)$$

For fixed  $hash$  and  $P$  a *canonical success* of  $C$  for bistrings  $\pi, \rho$  is a situation where  $CanonicalSuccess^{P, C, hash}(\pi, \rho) = 1$ .

We show that if a solver circuit  $C$  for  $P$  often succeeds in the experiment *Success*, then there exists a function  $hash$  such that  $C$  also often succeeds in the experiment *CanonicalSuccess*.

**Lemma 4.3** (*Success probability in solving DWVP with respect to a function hash.*) For fixed  $P_n$  let  $C$  be a solver for  $P_n$  with success probability at least  $\gamma$ , asking at most  $h$  hint queries and  $v$  verification queries. Let  $\mathcal{H}$  be an efficient family of pairwise independent hash functions  $Q \rightarrow \{0, 1, \dots, 2(h+v)-1\}$ . There exists a probabilistic algorithm *FindHash* that takes as input parameters  $\gamma, n, h, v$ , and has oracle access to  $C$  and  $P_n$ . Furthermore, *FindHash* runs in time  $\text{poly}(h, v, \frac{1}{\gamma}, n)$ , and with high probability outputs a function  $hash \in \mathcal{H}$  such that the canonical success probability of  $C$  with respect to  $hash$  is at least  $\frac{\gamma}{16(h+v)}$ .

**Proof (4.3).** We fix a problem poser  $P$  and a solver  $C$  for  $P$  in the whole proof of Lemma 4.3. For  $k, l \in \{1, \dots, (h+v)\}$  and  $\alpha, \beta \in \{0, 1, \dots, 2(h+v)-1\}$  by the pairwise independence property, we have

$$\begin{aligned} \forall q_k \neq q_l \in Q : \Pr_{hash \leftarrow \mathcal{H}}[hash(q_k) = \alpha \mid hash(q_l) = \beta] &= \Pr_{hash \leftarrow \mathcal{H}}[hash(q_k) = \alpha] \\ &= \frac{1}{2(h+v)}. \end{aligned} \quad (4.3)$$

We write  $\mathcal{P}_{Success}$  to denote a set containing all  $(\pi, \rho)$  for which  $Success^{P, C}(\pi, \rho) = 1$ . Let us fix  $(\pi^*, \rho^*) \in \mathcal{P}_{Success}$ . We are interested in the probability over a choice of function  $hash$  of the event  $CanonicalSuccess^{P, C, hash}(\pi^*, \rho^*) = 1$ . Let

$(q_j, y_j)$  denote the first query such that  $\Gamma_V(q_j, y_j) = 1$ . We have

$$\begin{aligned}
 & \Pr_{hash \leftarrow \mathcal{H}} \left[ \text{CanonicalSuccess}^{P,C,hash}(\pi^*, \rho^*) = 1 \right] \\
 &= \Pr_{hash \leftarrow \mathcal{H}} [hash(q_j) = 0 \wedge (\forall i < j : hash(q_i) \neq 0)] \\
 &= \Pr_{hash \leftarrow \mathcal{H}} [\forall i < j : hash(q_i) \neq 0 \mid hash(q_j) = 0] \Pr_{hash \leftarrow \mathcal{H}} [hash(q_j) = 0] \\
 &\stackrel{(4.3)}{=} \frac{1}{2(h+v)} \left( 1 - \Pr_{hash \leftarrow \mathcal{H}} [\exists i < j : hash(q_i) = 0 \mid hash(q_j) = 0] \right) \\
 &\stackrel{(*)}{\geq} \frac{1}{2(h+v)} \left( 1 - \sum_{i < j} \Pr_{hash \leftarrow \mathcal{H}} [hash(q_i) = 0 \mid hash(q_j) = 0] \right) \\
 &\stackrel{(4.3)}{=} \frac{1}{2(h+v)} \left( 1 - \sum_{i < j} \Pr_{hash \leftarrow \mathcal{H}} [hash(q_i) = 0] \right) \\
 &\stackrel{(4.3)}{\geq} \frac{1}{4(h+v)}, \tag{4.4}
 \end{aligned}$$

where in  $(*)$  we used the union bound. Let us denote the set of those  $(\pi, \rho)$  for which  $\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1$  by  $\mathcal{P}_{\text{Canonical}}$ . If for  $\pi, \rho$  the circuit  $C$  succeeds canonically, then for the same  $\pi, \rho$  we also have  $\text{Success}^{P,C}(\pi, \rho) = 1$ . Hence,  $\mathcal{P}_{\text{Canonical}} \subseteq \mathcal{P}_{\text{Success}}$ , and we conclude

$$\begin{aligned}
 & \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[ \text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \right] \\
 &= \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[ \text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}} \right] \Pr_{\pi, \rho} [(\pi, \rho) \in \mathcal{P}_{\text{Success}}] \\
 &\quad + \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[ \text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \mid (\pi, \rho) \notin \mathcal{P}_{\text{Success}} \right] \Pr_{\pi, \rho} [(\pi, \rho) \notin \mathcal{P}_{\text{Success}}] \\
 &= \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[ \text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}} \right] \Pr_{\pi, \rho} [(\pi, \rho) \in \mathcal{P}_{\text{Success}}] \\
 &\geq \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[ \text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}} \right] \cdot \gamma \\
 &= \mathbb{E}_{(\pi, \rho) \in \mathcal{P}_{\text{Success}}} \left[ \Pr_{hash \leftarrow \mathcal{H}} [\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1] \right] \cdot \gamma \\
 &\stackrel{(4.4)}{\geq} \frac{\gamma}{4(h+v)}. \tag{4.5}
 \end{aligned}$$



---

**Algorithm** FindHash<sup>*P,C*</sup>( $\gamma, n, h, v$ )

---

**Oracle:** A problem poser  $P$ , a solver circuit  $C$  for  $P$ .

**Input:** Parameters  $\gamma, n$ . The number of hint queries  $h$  and of verification queries  $v$ .

**Output:** A function  $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$ .

---

```

for  $i := 1$  to  $32n(h + v)^2/\gamma^2$  do:
   $hash \leftarrow \mathcal{H}$ 
   $count := 0$ 
  for  $j := 1$  to  $32n(h + v)^2/\gamma^2$  do:
     $\pi \leftarrow \{0, 1\}^n$ 
     $\rho \leftarrow \{0, 1\}^*$ 
    if  $CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1$  then
       $count := count + 1$ 
  if  $count \geq \frac{\gamma}{12(h+v)} \frac{32(h+v)^2}{\gamma^2} n$  then
    return  $hash$ 
return  $\perp$ 

```

---

We show that FindHash chooses  $hash \in \mathcal{H}$  such that the canonical success probability of  $C$  with respect to  $hash$  is at least  $\frac{\gamma}{16(h+v)}$  almost surely. Let  $\mathcal{H}_{Good}$  denote a family of functions  $hash \in \mathcal{H}$  for which

$$\Pr_{\pi, \rho} \left[ CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \right] \geq \frac{\gamma}{8(h+v)}, \quad (4.6)$$

and  $\mathcal{H}_{Bad}$  be a family of functions  $hash \in \mathcal{H}$  such that

$$\Pr_{\pi, \rho} \left[ CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \right] \leq \frac{\gamma}{16(h+v)}. \quad (4.7)$$

Let  $N$  denote the number of iterations of the inner loop of FindHash. We consider a single iteration of the outer loop of FindHash in which  $hash$  is fixed. We define independent, identically distributed, binary random variables  $X_1, \dots, X_N$  such that

$$X_i = \begin{cases} 1 & \text{if in the } i\text{-th iteration of the inner loop } count \text{ is increased} \\ 0 & \text{otherwise.} \end{cases}$$

We now turn to the case when  $hash \in \mathcal{H}_{Bad}$  and show that it is unlikely that  $hash$  is returned by FindHash. From (4.7) it follows that  $\mathbb{E}_{\pi, \rho}[X_i] \leq \frac{\gamma}{16(h+v)}$ . Therefore, for any fixed  $hash \in \mathcal{H}_{Bad}$  using the Chernoff bound we get

$$\begin{aligned} \Pr_{\pi, \rho} \left[ \frac{1}{N} \sum_{i=1}^N X_i \geq \frac{\gamma}{12(h+v)} \right] &\leq \Pr_{\pi, \rho} \left[ \frac{1}{N} \sum_{i=1}^N X_i \geq \left(1 + \frac{1}{3}\right) \mathbb{E}[X_i] \right] \\ &\leq e^{-\frac{\gamma}{16(h+v)} N/27} \leq e^{-\frac{2}{27} \frac{(h+v)}{\gamma} n} \stackrel{(*)}{\leq} e^{-\frac{2}{27} n}, \end{aligned}$$

where in (\*) we used the trivial facts that  $h+v \geq 1$  and  $\gamma \leq 1$ . The probability that  $hash \in \mathcal{H}_{Good}$ , when picked, is not returned amounts

$$\begin{aligned} \Pr_{\pi, \rho} \left[ \frac{1}{N} \sum_{i=1}^N X_i \leq \frac{\gamma}{12(h+v)} \right] &\leq \Pr_{\pi, \rho} \left[ \frac{1}{N} \sum_{i=1}^N X_i \leq \left(1 - \frac{1}{3}\right) \mathbb{E}[X_i] \right] \\ &\leq e^{-\frac{\gamma}{8(h+v)} N/18} \leq e^{-\frac{2}{9} \frac{(h+v)}{\gamma} n} \stackrel{(*)}{\leq} e^{-\frac{2}{9} n}, \end{aligned}$$

where we once more used the Chernoff bound. We now show that the probability of picking  $hash \in \mathcal{H}_{Good}$  is at least  $\frac{\gamma}{8(h+v)}$ . To obtain a contradiction suppose that

$$\Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] < \frac{\gamma}{8(h+v)}. \quad (4.8)$$

From this it follows that we can bound probability of canonical success as follows

$$\begin{aligned} &\Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1] \\ &= \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \in \mathcal{H}_{Good}] \Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] \\ &\quad + \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \notin \mathcal{H}_{Good}] \Pr_{hash \leftarrow \mathcal{H}} [hash \notin \mathcal{H}_{Good}] \\ &\leq \Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] + \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \notin \mathcal{H}_{Good}] \\ &\stackrel{(4.6)}{<} \stackrel{(4.8)}{<} \frac{\gamma}{8(h+v)} + \frac{\gamma}{8(h+v)} = \frac{\gamma}{4(h+v)}, \end{aligned}$$

which contradicts (4.5). Therefore, we conclude that the probability of choosing a  $hash \in \mathcal{H}_{Good}$  amounts at least  $\frac{\gamma}{8(h+v)}$ .

We show that FindHash picks in one of its iteration  $hash \in \mathcal{H}_{Good}$  almost surely. Let  $K$  be the number of iterations of the outer loop of FindHash and  $Y_i$  be a random variable for the event that in the  $i$ -th iteration of the outer loop  $hash \notin \mathcal{H}_{Good}$  is picked. We use  $\Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] \geq \frac{\gamma}{8(h+v)}$  and  $K \leq \frac{32(h+v)^2}{\gamma^2} n$ , and conclude

$$\begin{aligned} \Pr_{hash \leftarrow \mathcal{H}} \left[ \bigcap_{1 \leq i \leq K} Y_i \right] &\leq \left( 1 - \frac{\gamma}{8(h+v)} \right)^{\frac{32(h+v)^2}{\gamma^2} n} \leq e^{-\frac{\gamma}{8(h+v)} \frac{32(h+v)^2}{\gamma^2} n} \\ &\leq e^{-\frac{4(h+v)}{\gamma} n} \leq e^{-n}. \end{aligned}$$

It is clear that running time of FindHash is  $\text{poly}(n, h, v, \gamma)$  with oracle access. This finishes the proof of Lemma 4.3.  $\square$

Let  $C = (C_1, C_2)$  be a solver circuit for a dynamic weakly verifiable puzzle as in definition 3.1. We write  $C_2^{(\cdot, \cdot)}$  to emphasize that  $C_2$  does not obtain direct access to hint and verification circuits. Instead, whenever  $C_2$  ask hint or verification queries, then it is answered explicitly as in the following code excerpt of the circuit  $\tilde{C}_2$ .

**Circuit**  $\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)$

**Oracle:** A hint circuit  $\Gamma_H$ , a circuit  $C_2$ ,  
a function  $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$ .

**Input:** Bitstrings  $x \in \{0, 1\}^*$ ,  $\rho \in \{0, 1\}^*$ .

**Output:** A pair  $(q, y)$ .

```

run  $C_2^{(\cdot, \cdot)}(x, \rho)$ 
  if  $C_2^{(\cdot, \cdot)}(x, \rho)$  asks a hint query on  $q$  then
    if  $hash(q) = 0$  then
      return  $\perp$ 
    else
      answer the query of  $C_2^{(\cdot, \cdot)}(x, \rho)$  using  $\Gamma_H(q)$ 

  if  $C_2^{(\cdot, \cdot)}(x, \rho)$  asks a verification query  $(q, y)$  then
    if  $hash(q) = 0$  then
      return  $(q, y)$ 
    else
      answer the verification query of  $C_2^{(\cdot, \cdot)}(x, \rho)$  with 0

return  $\perp$ 

```

Given  $C = (C_1, C_2)$  we define the circuit  $\tilde{C} = (C_1, \tilde{C}_2)$ . Every hint query  $q$  asked by  $\tilde{C}$  is such that  $hash(q) \neq 0$ . Furthermore,  $\tilde{C}$  asks no verification queries. Instead, it returns  $(q, y)$  such that  $hash(q) = 0$  or  $\perp$ .

For fixed  $\pi$ ,  $\rho$ , and  $hash$  we say that the circuit  $\tilde{C}$  *succeeds* if for  $x := \langle P(\pi), C_1(\rho) \rangle_{trans}$ ,  $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$ , we have

$$\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)) = 1.$$

**Lemma 4.4** *For fixed  $P$ ,  $C$ , and  $hash$  the following statement is true*

$$\Pr_{\pi, \rho}[CanonicalSuccess^{P, C, hash}(\pi, \rho) = 1] \leq \Pr_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}}[\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)) = 1]$$

**Proof.** If for fixed  $\pi$ ,  $\rho$ , and  $hash$  the circuit  $C$  succeeds canonically, then for the same  $\pi$ ,  $\rho$ , and  $hash$  also  $\tilde{C}$  succeeds. Using this observation, we conclude that

$$\begin{aligned}
 & \Pr_{\pi, \rho} \left[ CanonicalSuccess^{P, C, hash}(\pi, \rho) = 1 \right] \\
 & \leq \mathbb{E}_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}} [\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)) = 1] \\
 & = \Pr_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}} [\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)) = 1] \quad \square
 \end{aligned}$$

**Lemma 4.5 (Security amplification for dynamic weakly verifiable puzzles with respect to hash.)** Let  $g : \{0, 1\}^k \rightarrow \{0, 1\}$  be a monotone function and  $P_n^{(1)}$  a fixed problem poser as in Definition 3.1 and  $\tilde{C} := (C_1, \tilde{C}_2)$  a circuit with oracle access to a function  $hash : Q \rightarrow \{0, 1, \dots, 2(h + v - 1)\}$  and a solver circuit  $C := (C_1, C_2)$  for  $P_{kn}^{(g)}$  which asks at most  $h$  hint queries and  $v$  verification queries. There exists an algorithm  $Gen$  that takes as input parameters  $\varepsilon$ ,  $\delta$ ,  $n$ ,  $k$ , has oracle access to  $P_n^{(1)}$ ,  $\tilde{C}$ ,  $hash$ ,  $g$ , and outputs a circuit  $D := (D_1, D_2)$  such that the following holds:  
If  $\tilde{C}$  is such that

$$\Pr_{\substack{\pi^{(k)} \in \{0, 1\}^{kn}, \rho \in \{0, 1\}^* \\ x := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{trans} \\ (\Gamma_H^{(k)}, \Gamma_V^{(g)}) := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{P^{(g)}}}} [\Gamma_V^{(g)}(\tilde{C}_2^{\Gamma_H^{(k)}, C_2, hash}(x, \rho)) = 1] \geq \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon,$$

then  $D$  satisfies almost surely

$$\Pr_{\substack{\pi \in \{0, 1\}^n, \rho \in \{0, 1\}^* \\ x := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{trans} \\ (\Gamma_H, \Gamma_V) := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{P^{(1)}}}} [\Gamma_V(D_2^{P^{(1)}, \tilde{C}, hash, g, \Gamma_H}(x, \rho)) = 1] \geq \delta + \frac{\varepsilon}{6k}.$$

Furthermore,  $D$  asks at most  $\frac{6k}{\varepsilon} \log\left(\frac{6k}{\varepsilon}\right) h$  hint queries and no verification queries. Finally,  $Time(Gen) = poly(k, \frac{1}{\varepsilon}, n)$  with oracle access to  $\tilde{C}$ .

Before we give the proof of Lemma 4.5 we define additional algorithms. First, we are interested in the probability that for  $u \leftarrow \mu_\delta^k$  and a bit  $b$  we have  $g(b, u_2, \dots, u_k) = 1$ . The estimate of this probability is calculated by `EstimateFunctionProbability`.

---

**Algorithm** EstimateFunctionProbability<sup>g</sup>(b, k, ε, δ, n)

---

**Oracle:** A function  $g : \{0, 1\}^k \rightarrow \{0, 1\}$ .

**Input:** A bit  $b \in \{0, 1\}$ , parameters  $k, \varepsilon, \delta, n$ .

**Output:** An estimate  $\tilde{g}_b$  of  $\Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1]$ .

---

**for**  $i := 1$  **to**  $N := \frac{64k^2}{\varepsilon^2}n$  **do:**
 $u \leftarrow \mu_\delta^k$ 
 $g_i := g(b, u_2, \dots, u_k)$ 
**return**  $\frac{1}{N} \sum_{i=1}^N g_i$ 


---

**Lemma 4.6** *The algorithm EstimateFunctionProbability<sup>g</sup>(b, k, ε, δ, n) outputs an estimate  $\tilde{g}_b$  such that  $|\tilde{g}_b - \Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1]| \leq \frac{\varepsilon}{8k}$  almost surely.*

**Proof.** We fix the notation as in the algorithm EstimateFunctionProbability. Let us define independent, identically distributed binary random variables  $K_1, K_2, \dots, K_N$  such that for each  $1 \leq i \leq N$  the random variable  $K_i$  takes value  $g_i$ . We use the Chernoff bound to obtain

$$\begin{aligned} \Pr \left[ \left| \tilde{g}_b - \Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1] \right| \geq \frac{\varepsilon}{8k} \right] \\ = \Pr \left[ \left| \left( \frac{1}{N} \sum_{i=1}^N K_i \right) - \mathbb{E}_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k)] \right| \geq \frac{\varepsilon}{8k} \right] \leq 2 \cdot e^{-n/3}. \square \end{aligned}$$

The algorithm EvaluatePuzzles<sup>P<sup>(1)</sup>,  $\tilde{C}$ , hash</sup>( $\pi^{(k)}, \rho, n, k$ ) evaluates which of the  $k$  puzzles of the  $k$ -wise direct product defined by  $P^{(g)}$  are solved successfully by  $\tilde{C}(\rho) := (C_1, \tilde{C}_2)(\rho)$ . To decide whether the  $i$ -th puzzle of the  $k$ -wise direct product is solved successfully we need to gain access to the verification circuit for the puzzle generated in the  $i$ -th round of the interaction between  $P^{(g)}$  and  $\tilde{C}$ . Therefore, the algorithm EvaluatePuzzles runs  $k$  times  $P^{(1)}$  to simulate the interaction with  $C_1(\rho)$  each time with a fresh random bitstring  $\pi_i \in \{0, 1\}^n$  where  $1 \leq i \leq k$ .

Let us introduce some additional notation. We denote by  $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle^i$  the execution of the  $i$ -th round of the sequential interaction. We use  $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{P^{(1)}}^i$  to denote the output of  $P^{(1)}(\pi_i)$  in the  $i$ -th round. Finally, we write  $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{trans}^i$  to denote the transcript of communication in the  $i$ -th round. We note that the  $i$ -th round of the interaction between  $P^{(1)}$  and  $C_1$  is well defined only if all previous rounds have been executed before.

To make the notation easier in the code excerpts of circuits  $C_2$ ,  $D_2$  and EvaluatePuzzles we omit superscripts of some oracles. Exemplary, we write  $\tilde{C}_2^{\Gamma_H^{(k)}, hash}$  instead of  $\tilde{C}_2^{\Gamma_H^{(k)}, C, hash}$  where the superscript of the oracle circuit  $C$

#### 4. SECURITY AMPLIFICATION FOR DYNAMIC WEAKLY VERIFIABLE PUZZLES

is omitted. We make sure that it is clear from the context which oracles are used.

**Algorithm** EvaluatePuzzles $^{P^{(1)}, \tilde{C}, hash}(\pi^{(k)}, \rho, n, k)$

**Oracle:** A problem poser  $P^{(1)}$ , a solver circuit  $\tilde{C} = (C_1, \tilde{C}_2)$  for  $P^{(g)}$ ,  
a function  $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$ .

**Input:** Bitstrings  $\pi^{(k)} \in \{0, 1\}^{kn}$ ,  $\rho \in \{0, 1\}^*$ , parameters  $n, k$ .

**Output:** A tuple  $(c_1, \dots, c_k) \in \{0, 1\}^k$ .

---

**for**  $i := 1$  **to**  $k$  **do:** *//simulate k rounds of interaction*  
 $(\Gamma_V^i, \Gamma_H^i) := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{P^{(1)}}^i$   
 $x_i := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{trans}^i$   
 $x := (x_1, \dots, x_k)$   
 $\Gamma_H^{(k)} := (\Gamma_H^1, \dots, \Gamma_H^k)$   
 $(q, y_1, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, hash}(x, \rho)$   
**if**  $(q, y_1, \dots, y_k) = \perp$  **then**  
    **return**  $(0, \dots, 0)$   
 $(c_1, \dots, c_k) := (\Gamma_V^1(q, y_1), \dots, \Gamma_V^k(q, y_k))$   
**return**  $(c_1, \dots, c_k)$

---

All puzzles used by EvaluatePuzzles are generated internally thus the algorithm has access to hint circuit, and can answer itself all queries of  $\tilde{C}_2$ .

We are interested in the success probability of  $\tilde{C}$  with the bitstring  $\pi_1$  fixed to  $\pi^*$  where the fact whether  $\tilde{C}$  succeeds in solving the first puzzle defined by  $P^{(1)}(\pi_1)$  is neglected, and instead a bit  $b$  is used. More formally, we define the surplus  $S_{\pi^*, b}$  as

$$S_{\pi^*, b} = \Pr_{\pi^{(k)}, \rho} [g(b, c_2, \dots, c_k) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_\delta^k} [g(b, u_2, \dots, u_k) = 1], \quad (4.9)$$

where  $(c_2, c_3, \dots, c_k)$  is obtained as in EvaluatePuzzles.

The algorithm EstimateSurplus returns an estimate  $\tilde{S}_{\pi^*, b}$  for  $S_{\pi^*, b}$ .

**Algorithm** EstimateSurplus $^{P^{(1)}, \tilde{C}, g, hash}(\pi^*, b, k, \varepsilon, \delta, n)$

**Oracle:** A problem poser  $P^{(1)}$ , a circuit  $\tilde{C}$  for  $P^{(g)}$ , functions  
 $g : \{0, 1\}^k \rightarrow \{0, 1\}$  and  $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$ .

**Input:** A bistring  $\pi^* \in \{0, 1\}^n$ , a bit  $b \in \{0, 1\}$ , parameters  $k, \varepsilon, \delta, n$ .

**Output:** An estimate  $\tilde{S}_{\pi^*, b}$  for  $S_{\pi^*, b}$ .

---

```

for  $i := 1$  to  $N := \frac{64k^2}{\varepsilon^2}n$  do:
     $(\pi_2, \dots, \pi_k) \xleftarrow{\$} \{0, 1\}^{(k-1)n}$ 
     $\rho \xleftarrow{\$} \{0, 1\}^*$ 
     $(c_1, \dots, c_k) := \text{EvaluatePuzzles}^{P^{(1)}, \tilde{C}, \text{hash}}((\pi^*, \pi_2, \dots, \pi_k), \rho, n, k)$ 
     $\tilde{s}_{\pi^*, b}^i := g(b, c_2, \dots, c_k)$ 
 $\tilde{g}_b := \text{EstimateFunctionProbability}^g(b, k, \varepsilon, \delta, n)$ 
return  $\left( \frac{1}{N} \sum_{i=1}^N \tilde{s}_{\pi^*, b}^i \right) - \tilde{g}_b$ 

```

---

**Lemma 4.7** *The estimate  $\tilde{S}_{\pi^*, b}$  returned by *EstimateSurplus* differs from  $S_{\pi^*, b}$  by at most  $\frac{\varepsilon}{4k}$  almost surely.*

**Proof.** We use the union bound and similar argument as in Lemma 4.6 which yields that  $\frac{1}{N} \sum_{i=1}^N \tilde{s}_{\pi^*, b}^i$  differs from  $\mathbb{E}[g(b, c_2, \dots, c_k)]$  by at most  $\frac{\varepsilon}{8k}$  almost surely. Together, with Lemma 4.6 we conclude that the surplus estimate returned by *EstimateSurplus* differs from  $S_{\pi^*, b}$  by at most  $\frac{\varepsilon}{4k}$  almost surely.  $\square$

We define the following solver circuit  $C' = (C'_1, C'_2)$  for the  $(k-1)$ -wise direct product of  $P^{(1)}$ .

---

**Circuit**  $C'_1{}^{\tilde{C}, P^{(1)}}(\rho)$

---

**Oracle:** A solver circuit  $\tilde{C} = (C_1, \tilde{C}_2)$  for  $P^{(g)}$ , a poser  $P^{(1)}$ .

**Input:** A bitstring  $\rho \in \{0, 1\}^*$ .

**Hard-coded:** A bitstring  $\pi^* \in \{0, 1\}^n$ .

---

Simulate  $\langle P^{(1)}(\pi^*), C_1(\rho) \rangle^1$

Use  $C_1(\rho)$  for the remaining  $k-1$  rounds of interaction.

---



---

**Circuit**  $\tilde{C}_2{}^{\Gamma_H^{(k-1)}, \tilde{C}, \text{hash}}(x^{(k-1)}, \rho)$

---

**Oracle:** A hint oracle  $\Gamma_H^{(k-1)} := (\Gamma_H^2, \dots, \Gamma_H^k)$ ,  
a solver circuit  $\tilde{C} = (C_1, \tilde{C}_2)$  for  $P^{(g)}$ ,  
a function  $\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h+v)-1\}$ .

**Input:** A transcript of  $k-1$  rounds of interaction

$x^{(k-1)} := (x_2, \dots, x_k) \in \{0, 1\}^*$ , a bitstring  $\rho \in \{0, 1\}^*$

**Hard-coded:** A bitstring  $\pi^* \in \{0, 1\}^n$

---

Simulate  $\langle P^{(1)}(\pi^*), C_1(\rho) \rangle^1$

$(\Gamma_H^*, \Gamma_V^*) := \langle P^{(1)}(\pi^*), C_1(\rho) \rangle_{P^{(1)}}^1$

$x^* := \langle P^{(1)}(\pi^*), C_1(\rho) \rangle_{\text{trans}}^1$

---

#### 4. SECURITY AMPLIFICATION FOR DYNAMIC WEAKLY VERIFIABLE PUZZLES

---

```

 $\Gamma_H^{(k)} := (\Gamma_H^*, \Gamma_H^2, \dots, \Gamma_H^k)$ 
 $x^{(k)} := (x^*, x_2, \dots, x_k)$ 
 $(q, y_1, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, hash}(x^{(k)}, \rho)$ 
return  $(q, y_2, \dots, y_k)$ 

```

---

We are ready to define the solver circuit  $D = (D_1, D_2)$  for  $P^{(1)}$  and the algorithm Gen.

---

**Circuit**  $D_1^{\tilde{C}}(r)$

---

**Oracle:** A solver circuit  $\tilde{C} = (C_1, \tilde{C}_2)$  for  $P^{(g)}$ .

**Input:** A pair  $r := (\rho, \sigma)$  where  $\rho \in \{0, 1\}^*$  and  $\sigma \in \{0, 1\}^*$ .

---

Interact with the problem poser  $\langle P^{(1)}, C_1(\rho) \rangle^1$ .

Let  $x^* := \langle P^{(1)}, C_1(\rho) \rangle_{trans}^1$ .

---



---

**Circuit**  $D_2^{P^{(1)}, \tilde{C}, hash, g, \Gamma_H}(x^*, r)$

---

**Oracle:** A poser  $P^{(1)}$ , a solver circuit  $\tilde{C} = (C_1, \tilde{C}_2)$  for  $P^{(g)}$ ,  
functions  $hash : Q \rightarrow \{0, 1, \dots, 2(h+v)-1\}$ ,  $g : \{0, 1\}^k \rightarrow \{0, 1\}$ ,  
a hint circuit  $\Gamma_H$  for  $P^{(1)}$ .

**Input:** A communication transcript  $x^* \in \{0, 1\}^*$ , a bitstring  $r := (\rho, \sigma)$   
where  $\rho \in \{0, 1\}^*$  and  $\sigma \in \{0, 1\}^*$

**Output:** A pair  $(q, y^*)$ .

---

**for** at most  $\frac{6k}{\epsilon} \log(\frac{6k}{\epsilon})$  iterations **do:**

$(\pi_2, \dots, \pi_k) \leftarrow$  read next  $(k-1) \cdot n$  bits from  $\sigma$

Use  $x^*$  to simulate the first round of interaction of  $C_1(\rho)$  with the problem poser  $P^{(1)}$

**for**  $i := 2$  **to**  $k$  **do:**

**run**  $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle^i$

$(\Gamma_V^i, \Gamma_H^i) := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{P^{(1)}}^i$

$x_i := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{trans}^i$

$\Gamma_H^{(k)}(q) := (\Gamma_H(q), \Gamma_H^2(q), \dots, \Gamma_H^k(q))$

$(q, y^*, y_2, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, hash}((x^*, x_2, \dots, x_k), \rho)$

$(c_2, \dots, c_k) := (\Gamma_V^2(q, y_2), \dots, \Gamma_V^k(q, y_k))$

**if**  $g(1, c_2, \dots, c_k) = 1$  **and**  $g(0, c_2, \dots, c_k) = 0$  **then**

**return**  $(q, y^*)$

**return**  $\perp$

---



---

**Algorithm**  $\text{Gen}^{P^{(1)}, \tilde{C}, g, \text{hash}}(\varepsilon, \delta, n, k)$ 


---

**Oracle:** A poser  $P^{(1)}$ , a solver circuit  $\tilde{C}$  for  $P^{(g)}$ , functions  $g : \{0, 1\}^k \rightarrow \{0, 1\}$ ,

$\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$ .

**Input:** Parameters  $\varepsilon, \delta, n, k$ .

**Output:** A circuit  $D$ .

---

**for**  $i := 1$  **to**  $\frac{6k}{\varepsilon}n$  **do:**

$\pi^* \xleftarrow{\$} \{0, 1\}^n$

$\tilde{S}_{\pi^*, 0} := \text{EstimateSurplus}^{P^{(1)}, \tilde{C}, g, \text{hash}}(\pi^*, 0, k, \varepsilon, \delta, n)$

$\tilde{S}_{\pi^*, 1} := \text{EstimateSurplus}^{P^{(1)}, \tilde{C}, g, \text{hash}}(\pi^*, 1, k, \varepsilon, \delta, n)$

**if**  $\exists b \in \{0, 1\} : \tilde{S}_{\pi^*, b} \geq (1 - \frac{3}{4k})\varepsilon$  **then**

Let  $C'_1$  have oracle access to  $\tilde{C}$ , and have hard-coded  $\pi^*$

Let  $\tilde{C}'_2$  have oracle access to  $\tilde{C}$ , and have hard-coded  $\pi^*$ .

$\tilde{C}' := (C'_1, \tilde{C}'_2)$

$g'(b_2, \dots, b_k) := g(b, b_2, \dots, b_k)$

**return**  $\text{Gen}^{P^{(1)}, \tilde{C}', g', \text{hash}}(\varepsilon, \delta, n, k - 1)$

*// all estimates are lower than  $(1 - \frac{3}{4k})\varepsilon$*

**return**  $D^{P^{(1)}, \tilde{C}, \text{hash}, g}$

---

**Proof (Lemma 4.5).** First let us consider the case where  $k = 1$ . The function  $g : \{0, 1\} \rightarrow \{0, 1\}$  is either the identity or a constant function. If  $g$  is the identity function, then the circuit  $D$  returned by  $\text{Gen}$  directly uses  $\tilde{C}$  to find a solution. From the assumptions of Lemma 4.5 it follows that  $\tilde{C}$  succeeds with probability at least  $\delta + \varepsilon$ . Hence,  $D$  trivially satisfies the statement of Lemma 4.5. In the latter case  $g$  is a constant function, and the statement is vacuously true.

For the general case, we consider two possibilities. Either  $\text{Gen}$  in one of the iterations finds an estimate  $\tilde{S}_{\pi^*, b} \geq (1 - \frac{3}{4k})\varepsilon$  or it fails and returns the circuit  $D$ .

In the former case we define a new monotone function  $g'(b_2, \dots, b_k) := g(b, b_2, \dots, b_k)$  and a new circuit  $\tilde{C}' = (C'_1, \tilde{C}'_2)$  with oracle access to  $\tilde{C} := (C_1, \tilde{C}_2)$ . By Lemma 4.7 it follows that  $S_{\pi^*, b} \geq \tilde{S}_{\pi^*, b} - \frac{\varepsilon}{4k} \geq (1 - \frac{1}{k})\varepsilon$  almost surely. Therefore, the circuit  $\tilde{C}'$  succeeds in solving the  $(k-1)$ -wise direct product of puzzles with probability at least  $\Pr_{u \leftarrow \mu_\delta^{(k-1)}}[g'(u_1, \dots, u_{k-1})] + (1 - \frac{1}{k})\varepsilon$ . In this case  $\tilde{C}'$  satisfies the conditions of Lemma 4.5 for the  $(k-1)$ -wise direct product of puzzles. Therefore, the recursive call to  $\text{Gen}$  with access to  $g'$  and  $\tilde{C}$  returns

a circuit  $D = (D_1, D_2)$  that with high probability satisfies

$$\Pr_{\pi, \rho} [\Gamma_V(D_2^{P^{(1)}, \tilde{C}, hash, g, \Gamma_H}(x, \rho)) = 1] \geq \delta + \left(1 - \frac{1}{k}\right) \frac{\varepsilon}{6(k-1)} = \delta + \frac{\varepsilon}{6k}. \quad (4.10)$$

$x := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{trans}$   
 $(\Gamma_H, \Gamma_V) := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{P^{(1)}}$

The only point remaining concerns the behavior of Gen when none of the estimates is greater than  $(1 - \frac{3}{4k})\varepsilon$ . Assume that...

**TODO : Give more intuition (and the correct one with references to the equations)**

Intuitively this means that  $\tilde{C}$  does not succeed on the remaining  $k-1$  puzzles with much higher probability than an algorithm that correctly solves each puzzle with probability  $\delta$ . However, from the assumptions of Lemma 4.5 we know that on all  $k$  puzzles the success probability of  $\tilde{C}$  is higher. Therefore, it is likely that the first puzzle is correctly solved unusually often. It remains to prove that this intuition is indeed correct.

We fix the notation used in the code excerpt of the circuit  $D_2$ . We consider a single iteration of the outer loop of  $D_2$ , in which values  $\pi_2, \dots, \pi_k$  are fixed. Additionally, we write  $\pi_1$  to denote the randomness of the problem poser and define  $c_1 := \Gamma_V(q, y_1)$ , where  $\Gamma_V$  is the verification circuit generated by  $P^{(1)}(\pi_1)$  in the first phase when interacting with  $D_1(r)$ . Finally, we introduce the additional notation  $\mathcal{G}_b := \{(b_1, b_2, \dots, b_k) : g(b, b_2, \dots, b_k) = 1\}$  and  $c = (c_1, c_2, \dots, c_k)$ . Using the new notation the following holds

$$\begin{aligned} \Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_b] &= \Pr_{u \leftarrow \mu_\delta^k} [g(b, u_2, \dots, u_k) = 1] \\ \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_b] &= \Pr_{\pi^{(k)}, \rho} [g(b, c_2, \dots, c_k) = 1]. \end{aligned} \quad (4.11)$$

We fix the randomness  $\pi_1$  of the problem poser  $P^{(1)}$  to  $\pi^*$  and use (4.9), (4.11) to obtain

$$\begin{aligned} &\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1] - \Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_0] \\ &= \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \mid \pi_1 = \pi^*] - \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_0 \mid \pi_1 = \pi^*] - (S_{\pi^*, 1} - S_{\pi^*, 0}) \end{aligned} \quad (4.12)$$

We know that the function  $g$  is monotone, hence it holds  $\mathcal{G}_0 \subseteq \mathcal{G}_1$ , and we write (4.12) as

$$\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0] = \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] - (S_{\pi^*, 1} - S_{\pi^*, 0}). \quad (4.13)$$

Still having  $\pi_1 = \pi^*$  fixed we multiply both sides of (4.13) by

$$\Pr_r [\Gamma_V(D_2(x^*, r)) = 1] / \Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0],$$

$x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}$   
 $(\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}$

which yields

$$\begin{aligned}
& \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] \\
&= \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \frac{1}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \\
&\quad - \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*, 1} - S_{\pi^*, 0}) \frac{1}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]}.
\end{aligned} \tag{4.14}$$

We analyze the first summand of (4.14). First, we have

$$\begin{aligned}
& \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] \\
&= \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1 \mid D_2(x^*, r) \neq \perp] \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}}} [D_2(x^*, r) \neq \perp] \\
&\stackrel{(*)}{=} \Pr_{\substack{\pi^{(k)}, \rho \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}}} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}}} [D_2(x^*, r) \neq \perp], \tag{4.15}
\end{aligned}$$

where in  $(*)$  we use the observation that the event  $D_2(x^*, r) \neq \perp$  happens if and only if the circuit  $D_2(x^*, r)$  finds  $\pi^{(k)}$  such that  $c \in \mathcal{G}_1 \setminus \mathcal{G}_0$ . Furthermore, conditioned on  $c \in \mathcal{G}_1 \setminus \mathcal{G}_0$  we have that  $\Gamma_V(D_2(x^*, r)) = 1$  occurs if and only if  $c_1 = 1$ . Inserting (4.15) to the numerator of the first summand of (4.14) yields

$$\begin{aligned}
& \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \\
&= \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}}} [D_2(x^*, r) \neq \perp] \Pr_{\pi^{(k)}, \rho} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*].
\end{aligned} \tag{4.16}$$

We consider the following two cases. If  $\Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \leq \frac{\varepsilon}{6k}$  then

$$\Pr_{\pi^{(k)}, \rho} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \leq \frac{\varepsilon}{6k}. \tag{4.17}$$

When  $\Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] > \frac{\varepsilon}{6k}$  the circuit  $D_2$  outputs  $\perp$  if and only if it fails in all  $\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})$  iterations to find  $\pi^{(k)}$  such that  $c \in \mathcal{G}_1 \setminus \mathcal{G}_0$  which

happens with probability

$$\Pr_r[D_2(x^*, r) = \perp] \leq (1 - \frac{\varepsilon}{6k})^{\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})} \leq \frac{\varepsilon}{6k}. \quad (4.18)$$

$x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}$

We conclude that in both cases by (4.17) and (4.18) we have

$$\begin{aligned} & \Pr_r[D_2(x^*, r) \neq \perp] \Pr_{\pi^{(k)}, \rho}[c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \\ & \geq \Pr_{\pi^{(k)}, \rho}[c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\ & = \Pr_{\pi^{(k)}, \rho}[c_1 = 1 \wedge c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\ & = \Pr_{\pi^{(k)}, \rho}[g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\ & \stackrel{(4.9)}{=} \Pr_{\pi^{(k)}, \rho}[g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_\delta^{(k)}}[u \in \mathcal{G}_0] - S_{\pi^*, 0} - \frac{\varepsilon}{6k}. \end{aligned} \quad (4.19)$$

$x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}$

We insert (4.19) to (4.14) and calculate the expected value of over  $\pi^*$  which yields

$$\begin{aligned} & \Pr_{\pi, r}[\Gamma_V(D_2(x, r)) = 1] \geq \mathbb{E}_{\pi^*} \left[ \frac{\Pr_{\pi^{(k)}, \rho}[g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_\delta^{(k)}}[u \in \mathcal{G}_0] - \frac{\varepsilon}{6k}}{\Pr_{u \leftarrow \mu_\delta^{(k)}}[u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \right] \\ & \quad - \mathbb{E}_{\pi^*} \left[ \left( \Pr_r[\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*, 1} - S_{\pi^*, 0}) + S_{\pi^*, 0} \right) \frac{1}{\Pr_{u \leftarrow \mu_\delta^{(k)}}[u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \right]. \end{aligned}$$

$x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}$   
 $(\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}$

(4.20)

We show that if Gen does not recurse, then the majority of estimates is low almost surely. Let us assume that

$$\Pr_\pi \left[ \left( S_{\pi, 0} \leq (1 - \frac{1}{2k})\varepsilon \right) \wedge \left( S_{\pi, 1} \leq (1 - \frac{1}{2k})\varepsilon \right) \right] < 1 - \frac{\varepsilon}{6k}, \quad (4.21)$$

then Gen recurses almost surely, because the probability that Gen does not find  $\tilde{S}_{\pi, b} \geq (1 - \frac{3}{4k})\varepsilon$  in all of the  $\frac{6k}{\varepsilon}n$  iterations is at most

$$\left( 1 - \frac{\varepsilon}{6k} \right)^{\frac{6k}{\varepsilon}n} \leq e^{-n}$$

almost surely, where we used Lemma 4.7. Therefore, under the assumption that Gen does not recurse with high probability it holds

$$\Pr_{\pi, \rho} \left[ \left( S_{\pi, 0} \leq (1 - \frac{1}{2k})\varepsilon \right) \wedge \left( S_{\pi, 1} \leq (1 - \frac{1}{2k})\varepsilon \right) \right] \geq 1 - \frac{\varepsilon}{6k}. \quad (4.22)$$

Let us define a set

$$\mathcal{W} = \left\{ \pi : \left( S_{\pi,0} \leq \left(1 - \frac{1}{2k}\right)\varepsilon \right) \wedge \left( S_{\pi,1} \leq \left(1 - \frac{1}{2k}\right)\varepsilon \right) \right\}, \quad (4.23)$$

and use  $\overline{\mathcal{W}}$  to denote the complement of  $\mathcal{W}$ . We bound the numerator of the second summand in (4.20)

$$\begin{aligned} & \mathbb{E}_{\pi^*} [S_{\pi^*,0} + \Pr_{\substack{x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}}} [\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*,1} - S_{\pi^*,0})] \\ &= \mathbb{E}_{\pi^*} \left[ S_{\pi^*,0} + \Pr_{\substack{x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}}} [\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*,1} - S_{\pi^*,0}) \mid \pi^* \in \overline{\mathcal{W}} \right] \Pr_{\pi^*}[\pi^* \in \overline{\mathcal{W}}] \\ &+ \mathbb{E}_{\pi^*} \left[ S_{\pi^*,0} + \Pr_{\substack{x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}}} [\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*,1} - S_{\pi^*,0}) \mid \pi^* \in \mathcal{W} \right] \Pr_{\pi^*}[\pi^* \in \mathcal{W}] \\ &\leq \frac{\varepsilon}{6k} + \mathbb{E}_{\pi^*} \left[ S_{\pi^*,0} + \Pr_{\substack{x := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}}} [\Gamma_V(D_2^{\tilde{C}}(x^*, r)) = 1] \left( \left(1 - \frac{1}{2k}\right)\varepsilon - S_{\pi^*,0} \right) \mid \pi^* \in \mathcal{W} \right] \Pr_{\pi^*}[\pi^* \in \mathcal{W}] \\ &\leq \frac{\varepsilon}{6k} + \left(1 - \frac{1}{2k}\right)\varepsilon = \left(1 - \frac{1}{3k}\right)\varepsilon. \end{aligned} \quad (4.24)$$

We observe that

$$\begin{aligned} \Pr_{u \leftarrow \mu_{\delta}^k} [g(u) = 1] &= \Pr[u \in \mathcal{G}_0 \vee (u \in \mathcal{G}_1 \setminus \mathcal{G}_0 \wedge u_1 = 1)] \\ &= \Pr[u \in \mathcal{G}_0] + \delta \Pr[u \in \mathcal{G}_1 \setminus \mathcal{G}_0]. \end{aligned} \quad (4.25)$$

Finally, we insert (4.24) into (4.20) which yields

$$\Pr_{\substack{x := \langle P^{(1)}(\pi), D_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi), D_1(\rho) \rangle_{P(1)}}} [\Gamma_V(D_2(x, \rho)) = 1] \geq \mathbb{E}_{\pi^*} \left[ \frac{\Pr_{\pi^{(k)}, \rho} [g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_0] - \left(1 - \frac{1}{6k}\right)\varepsilon}{\Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \right].$$

From the assumptions of Lemma 4.5 it follows that

$$\Pr_{\pi^{(k)}, \rho} [g(c) = 1] \geq \Pr_{u \leftarrow \mu_{\delta}^{(k)}} [g(u) = 1] + \varepsilon.$$

thus we get

$$\begin{aligned} \Pr_{\substack{x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P(1)}}} [\Gamma_V(D_2(x, \rho)) = 1] &\geq \frac{\Pr_{u \leftarrow \mu_{\delta}^k} [g(u) = 1] + \varepsilon - \Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_0] - \left(1 - \frac{1}{6k}\right)\varepsilon}{\Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \\ &\stackrel{(4.25)}{\geq} \frac{\varepsilon + \delta \Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0] - \left(1 - \frac{1}{6k}\right)\varepsilon}{\Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \geq \delta + \frac{\varepsilon}{6k} \end{aligned} \quad (4.26)$$

Clearly, the running time of Gen is  $\text{poly}(k, \frac{1}{\varepsilon}, n)$ .  $\square$

**Proof (Theorem 4.2).** We define the following circuits.

**Circuit**  $\widetilde{D}_2^{D, P^{(1)}, \text{hash}, g, \Gamma_V, \Gamma_H}(x, \rho)$

**Oracle:** A circuit  $D := (D_1, D_2)$  from Lemma 4.5, a problem poser  $P^{(1)}$ , functions  $\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h+v)-1\}$ ,  $g : \{0, 1\}^k \rightarrow \{0, 1\}$  a verification oracle  $\Gamma_V$ , a hint oracle  $\Gamma_H$ .

**Input:** Bitstrings  $x \in \{0, 1\}^*$ ,  $\rho \in \{0, 1\}^*$ .

$(q, y) := D_2^{P^{(1)}, \widetilde{C}, \text{hash}, g, \Gamma_H}(x, \rho)$

Make a verification query to  $\Gamma_V$  using  $(q, y)$

**Algorithm**  $\widetilde{\text{Gen}}^{P^{(1)}, g, C}(n, \varepsilon, \delta, k, h, v)$

**Oracle:** A problem poser  $P^{(1)}$ , a function  $g : \{0, 1\}^k \rightarrow \{0, 1\}$ , a solver circuit  $C$  for  $P^{(g)}$ .

**Input:** Parameters  $n, \varepsilon, \delta, k, h, v$ .

$\text{hash} := \text{FindHash}((h+v)\varepsilon, n, h, v)$

Let  $\widetilde{C} := (C_1, \widetilde{C}_2)$  be as in Lemma 4.4 with oracle access to  $C$ ,  $\text{hash}$ .

$D := \text{Gen}^{P^{(1)}, \widetilde{C}, g, \text{hash}}(\varepsilon, \delta, n, k)$

**return**  $\widetilde{D} := (D_1, \widetilde{D}_2)$

We show that Theorem 4.2 follows from Lemma 4.3 and Lemma 4.5. We fix  $P^{(1)}, g, P^{(g)}$ . Given a solver circuit  $C = (C_1, C_2)$ , asking  $h$  hint queries and  $v$  verification queries, such that

$$\Pr_{\pi^{(k)}, \rho} \left[ \text{Success}^{P^{(g)}, C}(\pi^{(k)}, \rho) = 1 \right] \geq 16(h+v) \left( \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon \right)$$

we satisfy conditions of Lemma 4.3. Therefore,  $\widetilde{\text{Gen}}$  can use the algorithm FindHash to find  $\text{hash}$  such that

$$\Pr_{\pi^{(k)}, \rho} \left[ \text{CanonicalSuccess}^{P^{(g)}, C, \text{hash}}(\pi^{(k)}, \rho) = 1 \right] \geq \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon$$

almost surely. By Lemma 4.4 we know that it is possible to build  $\tilde{C} = (C_1, \tilde{C}_2)$  such that

$$\Pr_{\substack{\pi^{(k)}, \rho \\ x := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{trans} \\ (\Gamma_V^{(g)}, \Gamma_H^{(k)}) := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{P^{(g)}}}} [\Gamma_V^{(g)}(\tilde{C}_2^{\Gamma_H^{(k)}, C_2, hash}(x, \rho)) = 1] \geq \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon.$$

Now, we use Gen to obtain a circuit  $D = (D_1, D_2)$ , which by Lemma 4.5 satisfies

$$\Pr_{\pi, \rho} [\Gamma_V(D_2^{P^{(1)}, \tilde{C}, hash, g, \Gamma_H}(x, \rho)) = 1] \geq (\delta + \frac{\varepsilon}{6k}) \quad (4.27)$$

$$\substack{x := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{trans} \\ (\Gamma_H, \Gamma_V) := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{P^{(1)}}}$$

almost surely. Finally,  $\widetilde{\text{Gen}}$  outputs  $\tilde{D} = (D_1, \tilde{D}_2)$  with oracle access to  $D$ ,  $P^{(1)}$ ,  $hash$ ,  $g$  such that with high probability it holds

$$\Pr_{\pi, \rho} [Success^{P^{(1)}, \tilde{D}}(\pi, \rho) = 1] \geq (\delta + \frac{\varepsilon}{6k}).$$

The running time of FindHash is  $poly(h, v, \frac{1}{\varepsilon}, n)$  with oracle calls and of Gen  $poly(k, \frac{1}{\varepsilon}, n)$  with oracle access. Thus, the overall running time of  $\widetilde{\text{Gen}}$  is  $poly(k, \frac{1}{\varepsilon}, h, v, n, t)$  with oracle access. Furthermore, the circuit  $\tilde{D}$  asks at most  $\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})h$  hint queries and one verification query. Finally, we have  $Size(\tilde{D}) \leq Size(C) \cdot \frac{6k}{\varepsilon}$ . This finishes the proof of Theorem 4.2.  $\square$





## Appendix A

---

# Appendix

---

### A.1 Basic inequalities

**Lemma A.1 (Chernoff Bounds)** *For independent, identically distributed Bernoulli random variables  $X_1, \dots, X_n$  with  $X := \sum_{i=1}^n X_i$  with  $\Pr[X_i = 1] = p_i$  and  $\Pr[X_i = 0] = 1 - p_i$  for all  $1 \leq i \leq n$ . we have the following inequalities for  $0 \leq \delta \leq 1$  and  $\mathbb{E}[X] = \sum_{i=1}^n p_i$ :*

$$\Pr[X \geq (1 + \delta)\mathbb{E}[X]] \leq e^{-\mathbb{E}[X]\delta^2/3} \quad (\text{A.1})$$

$$\Pr[X \leq (1 - \delta)\mathbb{E}[X]] \leq e^{-\mathbb{E}[X]\delta^2/2} \quad (\text{A.2})$$

$$\Pr[|X - \mathbb{E}[X]| \geq \delta\mathbb{E}[X]] \leq 2e^{-\mathbb{E}[X]\delta^2/3}. \quad (\text{A.3})$$



---

## Bibliography

---

- [AB09] Sanjeev Arora and Boaz Barak. *Computational Complexity: A Modern Approach*. Cambridge University Press, New York, NY, USA, 1st edition, 2009.
- [CHS04] Ran Canetti, Shai Halevi, and Michael Steiner. Hardness amplification of weakly verifiable puzzles. 2004.
- [CW77] J. Lawrence Carter and Mark N. Wegman. Universal classes of hash functions (extended abstract). In *Proceedings of the Ninth Annual ACM Symposium on Theory of Computing, STOC '77*, pages 106–112, New York, NY, USA, 1977. ACM.
- [DIJK09] Yevgeniy Dodis, Russell Impagliazzo, Ragesh Jaiswal, and Valentine Kabanets. Security amplification for interactive cryptographic primitives. In *Proceedings of the 6th Theory of Cryptography Conference on Theory of Cryptography, TCC '09*, pages 128–145, Berlin, Heidelberg, 2009. Springer-Verlag.
- [HS10] Thomas Holenstein and Grant Schoenebeck. General hardness amplification of predicates and puzzles. *CoRR*, abs/1002.3534, 2010.