
Contents

Contents	i
1 Introduction	1
1.1 Security Amplification Theorems	1
1.2 Weakly verifiable puzzles	1
1.3 Contribution of the Thesis	1
1.4 Organization of the Thesis	1
2 Preliminaries	3
2.1 Notation and Definitions	3
3 Weakly Verifiable Cryptographic Primitives	7
3.1 Dynamic Interactive Weakly Verifiable Puzzles	7
3.2 Examples	8
3.2.1 Message Authentication Codes	8
3.2.2 Public Key Signature Scheme	9
3.2.3 Bit Commitments	11
3.2.4 Automated Turing Tests	12
3.3 Previous results	13
3.3.1 Results of R.Canetti, S.Halevi, and M.Steiner	13
3.3.2 Results of Y.Dodis, R.Impagliazzo, R.Jaiswal, V.Kabanets	16
3.3.3 Results of T.Holenstein and G.Scheonebeck	16
3.4 Limitations of Security Amplification	16
4 Security amplification for dynamic weakly verifiable puzzles	17
4.1 Main theorem	17
4.1.1 The k -wise direct product of weakly verifiable puzzle	17
4.1.2 Intuition	19
4.1.3 Domain partitioning	20
4.1.4 Amplification proof for partitioned domain	25

CONTENTS

4.1.5	Putting it together	36
4.2	Discussion	37
A	Appendix	39
A.1	Basic Inequalities	39
	Bibliography	41

Chapter 1

Introduction

1.1 Security Amplification Theorems

Introduction to security amplification theorems and hardness implication statements. Example of classical results. Problems captured by weakly verifiable puzzles. Contribution of this thesis.

1.2 Weakly verifiable puzzles

1.3 Contribution of the Thesis

1.4 Organization of the Thesis

Overview of the content of the succeeding chapters.

Chapter 2

Preliminaries

In this chapter we set up notation and terminology used in the Thesis.

2.1 Notation and Definitions

(Algorithms, Bitstrings and Circuits) We define a *Boolean circuit* as a directed acyclic graph with input vertices and vertices implementing logical functions *and*, *or*, and *not*. We denote Boolean circuits using capital letters from the Greek or English alphabet. We define a *probabilistic circuit* as a Boolean circuit $C_{m,n} : \{0,1\}^m \times \{0,1\}^n \rightarrow \{0,1\}^*$. Additionally, we write $C_{m,n}(x;r)$ which should be understood as a probabilistic circuit taking as input $x \in \{0,1\}^m$ and auxiliary input $r \in \{0,1\}^n$. If a probabilistic circuit does not take any input, we abuse notation and write $C_n(r)$. Similarly, we use $\{C_n\}_{n \in \mathbb{N}}$ to denote a family of probabilist circuits that takes only auxiliary input. We make sure that it is clear from the context that probabilistic circuits with only auxiliary input are not confused with circuits that do not take auxiliary input. For a (probabilistic) circuit C we write $\text{Size}(C)$ to denote the total number of vertices of C . A *(probabilistic) polynomial size circuit* is a (probabilistic) circuit of size polynomial in the number of input vertices (including auxiliary input). We define a *two phase circuit* $C := (C_1, C_2)$ as a circuit where in the first phase a circuit C_1 is used and in the second phase a circuit C_2 . If C_1 and C_2 are probabilistic circuits we write $C(\delta) := (C_1, C_2)(\delta)$ to denote that in both phases C_1 and C_2 take as auxiliary input the same bitstring δ .

TODO: Does it hold for search problems and for algorithms with not a single bit of output.

It is well known [AB09] that a probabilistic polynomial time algorithm can be represented as a circuit of polynomial size. Moreover, it can be computed in polynomial time and logarithmic space. Therefore, whenever we state a

theorem about circuits it can be also generalized for the polynomial time algorithms.

We write $\text{poly}(\alpha_1, \dots, \alpha_n)$ to denote a polynomial on variables $\alpha_1, \dots, \alpha_n$. For an algorithm A we write $\text{Time}(A)$ to denote the number of steps it takes to execute A . We say that A runs in *polynomial time* if the number of steps required to evaluate A is bounded by $\text{poly}(|x|)$, where $|x|$ denotes the length of the input that A takes. Similarly, as for probabilistic circuits we write the randomness used by a probabilistic algorithm explicitly as a bitstring provided as an auxiliary input.

(Probabilities and distributions) For a finite set \mathcal{R} we write $r \xleftarrow{\$} \mathcal{R}$ to denote that r is chosen from \mathcal{R} uniformly at random. For $\delta \in \mathbb{R} : 0 \leq \delta \leq 1$ we write μ_δ to denote the Bernoulli distribution where outcome 1 occurs with probability δ and 0 with probability $1 - \delta$. Moreover, we use μ_δ^k to denote the probability distribution over k -tuples where each element of a k -tuple is drawn independently according to μ_δ . Finally, let $u \leftarrow \mu_\delta^k$ denote that a k -tuple u is chosen according to μ_δ^k .

Let $(\Omega_n, \mathcal{F}_n, \text{Pr})$ be a probability space and $n \in \mathbb{N}$. Let $E_n \in \mathcal{F}_n$ denote an event that probability depends on n . We say that E_n happens *almost surely* or with *high probability* if $\text{Pr}[E_n] \geq 1 - 2^{-n} \text{poly}(n)$.

(Functions) We call a function $f : \mathbb{N} \rightarrow \mathbb{R}$ *negligible* if for every polynomial $\text{poly}(n)$ there exists $n_0 \in \mathbb{N}$ such that for all $n \in \mathbb{N} : n > n_0$ the following holds

$$f(n) < \frac{1}{\text{poly}(n)}.$$

On the other hand, we say that a function $f : \mathbb{N} \rightarrow \mathbb{R}$ is *non-negligible* if there exists a polynomial $\text{poly}(n)$ such that for some $n_0 \in \mathbb{N}$ and for all $n \in \mathbb{N} : n > n_0$ we have

$$f(n) \geq \frac{1}{\text{poly}(n)}.$$

We say that a function f is *efficiently computable* if there exists a polynomial time algorithm computing f .

(Interactive protocols) We are often interested in situations where two probabilistic circuits interact with each other according to some protocol. We limit ourselves to the cases where circuits interact by means of messages representable by bitstrings. Let $\{A_n\}_{n \in \mathbb{N}}$ and $\{B_n\}_{n \in \mathbb{N}}$ be families of circuits such that $A_n : \{0, 1\}^* \rightarrow \{0, 1\}^*$ and $B_n : \{0, 1\}^* \rightarrow \{0, 1\}^*$. An *interactive protocol* is defined by a $\{A_n\}_{n \in \mathbb{N}}$ and $\{B_n\}_{n \in \mathbb{N}}$ where for random bitstrings $\rho_A \in \{0, 1\}^n$, $\rho_B \in \{0, 1\}^n$ in the first round $m_0 := A_n(\rho_A)$ and in the second round $m_1 := B_n(\rho_B, m_0)$. In general in the k -th round we have $m_k :=$

$A_n(\rho_A, m_1, m_2, \dots, m_{k-1})$ and in the $k+1$ -th round $B_n(\rho_B, m_1, m_2, \dots, m_{k-1}, m_k)$. A protocol execution between two probabilistic circuits A and B is denoted by $\langle A, B \rangle$. The output of A in a protocol execution is denoted by $\langle A, B \rangle_A$ and of B by $\langle A, B \rangle_B$. A sequence of all messages sent by A and B in the protocol execution is called a communication transcript and is denoted by $\langle A, B \rangle_{trans}$.

(Oracle algorithms) We use notions of *oracle circuits* following the standard definition included in the literature [Gol04]. If a circuit A gain oracle access to a circuit B , we write A^B . If additionally B gain oracle access to a circuit C we write A^{BC} . However, to simplify notation we often write A^B instead of A^{BC} . We make sure that it is clear from the context which oracle is accessed by B .

Definition 2.1 (Polynomial time sampleable distribution) *We say that a distribution is polynomial time sampleable if it can be approximated by an algorithm running in time $\text{poly}(\log |\mathcal{D}|, \log |cR|)$ up to an exponential factor.*

Definition 2.2 (Pairwise independent family of efficient hash functions) *Let \mathcal{D} and \mathcal{R} be finite sets and \mathcal{H} be a family of functions mapping values from \mathcal{D} to values in \mathcal{R} . We say that \mathcal{H} is a family of pairwise independent efficient hash functions if \mathcal{H} has the following properties.*

(Pairwise independent) *For $\forall x \neq y \in \mathcal{D}$ and $\forall \alpha, \beta \in \mathcal{R}$, it holds*

$$\Pr_{hash \leftarrow \mathcal{H}}[hash(x) = \alpha \mid hash(y) = \beta] = \frac{1}{|\mathcal{R}|}.$$

(Polynomial time sampleable) *For every $hash \in \mathcal{H}$ the function $hash$ is sampleable in time $\text{poly}(\log |\mathcal{D}|, \log |\mathcal{R}|)$.*

(Efficiently computable) *For every $hash \in \mathcal{H}$ there exists an algorithm running in time $\text{poly}(\log |\mathcal{D}|, \log |\mathcal{R}|)$ which on input $x \in \mathcal{D}$ outputs $y \in \mathcal{R}$ such that $y = hash(x)$.*

We note that the pairwise independence property is equivalent to

$$\Pr_{hash \leftarrow \mathcal{H}}[hash(x) = \alpha \wedge hash(y) = \beta] = \frac{1}{|\mathcal{R}|^2}.$$

It is well know [CW77] that there exists families of functions meeting the above criteria.

Chapter 3

Weakly Verifiable Cryptographic Primitives

This chapter gives an overview of dynamic interactive weakly verifiable puzzles. In Section 3.1 we define dynamic interactive weakly verifiable puzzles. Next, in Section 3.2, we describe a series of cryptographic primitives that are captured by the notion of dynamic interactive weakly verifiable puzzles. The Section 3.3 is devoted to the previous research concerning weakly verifiable puzzles.

3.1 Dynamic Interactive Weakly Verifiable Puzzles

We consider the following definition of *dynamic interactive weakly verifiable puzzles*.

Definition 3.1 (Dynamic Interactive Weakly Verifiable Puzzle.) A dynamic interactive weakly verifiable puzzle (DIWVP) is defined by a family of probabilistic circuits $\{P_n\}_{n \in \mathbb{N}}$. A circuit belonging to $\{P_n\}_{n \in \mathbb{N}}$ is called a problem poser. A solver $C_n := (C_1, C_2)$ for P_n is a probabilistic two phase circuit. We write $P_n(\pi)$ to denote the execution of P_n with the randomness fixed to $\pi \in \{0, 1\}^n$, and $C_n(\rho) := (C_1, C_2)(\rho)$ to denote the execution of both C_1 and C_2 with the randomness fixed to $\rho \in \{0, 1\}^*$.

In the first phase, the problem poser $P_n(\pi)$ and the solver $C_1(\rho)$ interact. As the result of the interaction $P_n(\pi)$ outputs a verification circuit Γ_V and a hint circuit Γ_H . The circuit $C_1(\rho)$ produces no output. The circuit Γ_V takes as input $q \in Q$, an answer $y \in \{0, 1\}^*$ and outputs a bit. We say that an answer (q, y) is a correct solution if and only if $\Gamma_V(q, y) = 1$. The circuit Γ_H on input $q \in Q$ outputs a hint such that $\Gamma_V(q, \Gamma_H(q)) = 1$.

In the second phase, C_2 takes as input $x := \langle P_n(\pi), C_1(\rho) \rangle_{\text{trans}}$, and has oracle access to Γ_V and Γ_H . The execution of C_2 with the input x and the randomness fixed to ρ is denoted by $C_2(x, \rho)$. The queries of C_2 to Γ_V and Γ_H are called

3. WEAKLY VERIFIABLE CRYPTOGRAPHIC PRIMITIVES

verification queries and hint queries respectively. We say that the circuit C_2 succeeds if and only if it makes a verification query (q, y) such that $\Gamma_V(q, y) = 1$, and it has not previously asked for a hint query on q .

If for a certain DIWVP the number of hint queries is greater than zero, we say that such a puzzle is *dynamic*. Conversely, if a problem poser is not allowed to ask any hint queries, then such a puzzle is called *non-dynamic*.

We say that DIWVP is *interactive* if in the first phase the number of messages exchanged between a problem poser and a problem solver is greater than one.

Definition 3.1 generalizes and combines previous approaches of *weakly verifiable puzzles* [CHS04], *dynamic weakly verifiable puzzles* [DIJK09] and *interactive weakly verifiable puzzles* [HS10].

TODO: This is not obvious as: a) algorithms are in BPP but they are search problems so no direct use of Cook-Levin b) this theorem is for deterministic algorithms

There is no loss of generality in assuming that a problem poser and a problem solver are defined by probabilistic circuits. Definition 3.1 embraces also a case where a problem poser and a problem solver are probabilistic polynomial time algorithms. We use the well know fact [Hol13b] that polynomial time algorithms can be transform into equivalent family of Boolean circuits of polynomial size.

3.2 Examples

In this section we give examples of cryptographic constructions that are dynamic weakly verifiable puzzles.

3.2.1 Message Authentication Codes

TODO: Runtime of problem poser and problem solver.

We consider the setting in which two parties a *sender* and a *receiver* communicate over an insecure channel. The messages of the sender may be read, modified, and replaced by a third party called an *adversary*. The receiver needs a way to ensure that received messages have been indeed sent by the sender and have not been modified by the adversary. The solution is to use *message authentication codes*.

Loosely speaking, the message authentication codes may be explained as follows. Let sender, receiver, and adversary be polynomial time algorithms, and

messages be represented as bitstrings. Furthermore, we assume that the sender and the receiver share a secret key to which an adversary has no access. The sender appends to every message a tag which is computed as a function of the key and the message. The receiver, using the key, has a way to check whether an appended tag is valid for a received message. The receiver accepts a message if the tag is valid, otherwise it rejects. We require that it is hard for the adversary to find a tag and a message that is accepted by the receiver with non-negligible probability. We give the following formal definition of *Message Authentication Codes* based on [Mau13] and [Gol04].

Definition 3.2 (Message Authentication Codes) *Let $\mathcal{M} \subseteq \{0,1\}^*$ be a set of messages, $\mathcal{K} \subseteq \{0,1\}^n$ a set of keys and $\mathcal{T} \subseteq \{0,1\}^*$ a set of tags where $n \in \mathbb{N}$. We define the message authentication code (MAC) as an efficiently computable function $\mathcal{M} \times \mathcal{K} \rightarrow \mathcal{T}$. Furthermore, we say that MAC is secure if it satisfies the following condition:*

Let $k \xleftarrow{\$} \mathcal{K}$ and $\Gamma_H : \mathcal{M} \rightarrow \mathcal{T}$ be a polynomial size circuit computing a tag for a message where a key is fixed to k . We say that MAC is secure if there is no probabilistic polynomial time algorithm with oracle access to Γ_H that with non-negligible probability outputs a message $m \in \mathcal{M}$, as well as a corresponding tag $t \in \mathcal{T}$ such that $f(m, k) = t$, and Γ_H has not been queried for a tag of message m .

We show how MAC is captured by the dynamic interactive weakly verifiable puzzles. For fixed n the sender corresponds to a problem poser, the adversary to a problem solver, and the k key is a bitstring $\pi \in \{0,1\}^n$ taken as auxiliary input by a problem poser. In the first phase, which is non interactive, the problem poser outputs a hint circuit $\Gamma_H : \mathcal{M} \rightarrow \mathcal{T}$ that given a message computes a tag and a verification circuit $\Gamma_V : \mathcal{M} \times \mathcal{T} \rightarrow \{0,1\}$ that on input $m \in \mathcal{M}$ and $t \in \mathcal{T}$ outputs one if and only if $f(m, k) = t$.

In the second phase the adversary takes no input (x^* is empty string), as the first phase was non-interactive, and is given oracle access to Γ_H and Γ_V . A task of finding by an adversary a valid tag $t' \in \mathcal{T}$ for a message $m' \in \mathcal{M}$ such that a hint for m' has not been asked before corresponds to asking a successful verification query by a problem poser to Γ_V .

3.2.2 Public Key Signature Scheme

First we give a definition of public key encryption scheme, and what it means for such a scheme to be secure. These definitions are based on [Gol04].

TODO: Length of public and private key

Definition 3.3 (Public key signature scheme) Let \mathcal{Q} be the set of messages. A public key signature scheme is defined by a triple of probabilistic polynomial time algorithms: G – the key generation algorithm, V – the verification algorithm, S – the signing algorithm, such that the following conditions are satisfied:

- $G(1^n)$ outputs a pair of bitstrings $k_{priv} \in \{0, 1\}^n$ and $k_{pub} \in \{0, 1\}^n$ where n is a security parameter. We call k_{priv} a private key and k_{pub} a public key.
- The signing algorithm S takes as input k_{priv} , $q \in \mathcal{Q}$ and outputs a signature $s \in S$.
- The verification algorithm takes as input k_{pub} , $q \in \mathcal{Q}$, and $s \in S$ and outputs a bit $b \in \{0, 1\}$.
- For every k_{priv} , k_{pub} output by G and every $q \in \mathcal{Q}$ it holds

$$\Pr[V(k_{pub}, q, S(k_{priv}, q))] = 1,$$

where the probability is over the random coins of V and S .

We say that $s \in S$ is a *valid signature* for $q \in \mathcal{Q}$ if and only if $V(k_{pub}, q, s) = 1$.

Definition 3.4 (Security of public key signature scheme with respect to a chosen message attack) Let an adversary be a probabilistic polynomial time algorithm that takes as input k_{pub} and has oracle access to S . We say that the adversary succeeds if it finds a signature $s \in S$ for a message $q \in \mathcal{Q}$ such that $V(k_{pub}, q, s) = 1$, and the oracle S has not been queried for a signature of q . The public key encryption scheme is secure if there is no polynomial time algorithm that succeeds with non negligible probability.

We show now that the public key signature schemes defined as above can be represented as a dynamic interactive weakly verifiable puzzle. In the first phase the problem poser uses algorithm $G(1^n)$ to obtain k_{pub} , k_{priv} and sends to the adversary the public key k_{pub} . The problem poser generates a hint circuit Γ_H and a verification circuit Γ_V . The hint circuit takes as input $q \in \mathcal{Q}$ and outputs a signature for q . The verification circuit takes as input $s \in S$ and $q \in \mathcal{Q}$ and checks whether $s \in S$ is a valid signature for $q \in \mathcal{Q}$. In the second phase the problem solver takes as input a transcript of message from the first round which consists of a single message k_{pub} . Additionally, it gain oracle access to Γ_V and Γ_H . It is clear that if the adversary asks a successful verification query (q, s) , then it also breaks the security of a public key signature scheme.

Public key signature schemes are types of puzzles that are dynamic but are not interactive as in the first phase only a single message is sent.

3.2.3 Bit Commitments

Let us consider the following *bit commitment protocol* that involves two parties a *sender* and a *receiver*. We suppose that the sender and the receiver are polynomial time probabilistic algorithms. The protocol consists of a *commit phase* and a *reveal phase*. In the commit phase the sender and the receiver interact, as the result the sender commits to a value $b \in \{0, 1\}$. In the reveal phase the sender opens the commitment by sending to the receiver (y, b') where $y \in \{0, 1\}^*$ and $b' \in \{0, 1\}$. We require that after the commit phase it is hard for the receiver to correctly guess b . Additionally, in the *reveal phase* it should be hard for the sender to persuade the receiver that it was committed to the value $\neg b$.

We base the following definition of *bit commitment protocol* on [Hol13a].

Definition 3.5 (Bit Commitment Protocol) For a security parameter $n \in \mathbb{N}$ a bit commitment protocol is defined by a pair (S_n, R_n) where $S_n = (S_1, S_2)$ is a two phase probabilistic circuit, and R_n is a probabilistic circuit. The circuit S_1 , used in the commit phase, takes as input a tuple (b, ρ_S) where $b \in \{0, 1\}$ is interpreted as a bit to which S_n commits and $\rho_S \in \{0, 1\}^n$ is the randomness used by the algorithm S_n . The receiver R_n takes only auxiliary input $\rho_R \in \{0, 1\}^n$ that is the randomness used by R_n . The protocol consists of two phases. In the commit phase circuits S_1, R_n engage in the protocol execution. As the result S_1 commits to b and generates a circuit $\Gamma_V : \{0, 1\} \times \{0, 1\}^* \rightarrow \{0, 1\}$. In the reveal phase the circuit S_2 returns (b', y) . For fixed $b \in \{0, 1\}$ and n we require the bit commit protocol to have the following properties:

(Correctness) For a fixed $b \in \{0, 1\}$ we have

$$\Pr_{\substack{\Gamma_V := \langle S_1, R \rangle_R \\ (b, y) := S_2(k_{pub}, \rho_S)}} [V(b, y) = 1] \geq 1 - \varepsilon(n),$$

where $\varepsilon(n)$ is a negligible function of n .

(Hiding)

TODO: Describe it using equations, define somehow the guess of R ?
Maybe as a last message in the first phase of communication

Probability over random coins of S_n and R_n that any polynomial size circuit can guess bit b correctly after the commit phase is at most $\frac{1}{2} + \varepsilon(n)$ where $\varepsilon(n)$ is a negligible function of n .

(Binding) For every polynomial size circuit S_n we have

$$\Pr_{\substack{\Gamma_V := \langle S_1, R \rangle_R \\ (b, y) := S_2(k_{pub}, \rho_S)}} [\Gamma_V(0, y_0) = 1 \wedge V(1, y_1) = 1] \leq \varepsilon(k),$$

where $\varepsilon(k)$ is a negligible function in k .

The bit commitment protocols can be generalized as dynamic interactive weakly verifiable puzzles for a case where the number of hint queries amounts to zero and the number of the verification queries is at most one. The sender corresponds to a problem solver, and the receiver is a problem poser. Additionally, we require the problem solver to ask a verification query only on $q := \neg b$ where b is a bit to which the problem solver is committed after the first phase. The first phase corresponds to the commit phase. In the reveal phase the problem poser tries to find a bitstring y such that $V(\neg b, y) = 1$.

3.2.4 Automated Turing Tests

The goal of *Automated Turing Tests* is to distinguish humans from computers which is frequently used to prevent computer programs from accessing resources for humans. An example is *CAPTCHA* defined first in [VABHL03]. Loosely speaking, CAPTCHA is a test that human can solve with probability close to 1, but it is hard to write a computer program that has a success probability comparable to the one achieved by humans. An example of CAPTCHA is an image depicting a distorted text. Most humans guess the text which is displayed on the image correctly, but it might be hard to write a program for which it would also be easy. We note that the definition of hardness has not been particularly well defined, and bases on opinions of the AI community that distinguish between hard and easy AI problems [VABHL03].

CAPTCHAs based on guessing the distorted text are weakly verifiable puzzles. In the first round the problem poser and problem solver engage in an interactive protocol, such that after the execution of the protocol the problem poser has a way to verify the solution. The problem poser in the second round takes as input a distorted image, and tries to guess the text that was used to generate it. The standard CAPTCHAs are non-dynamic, as the problem poser does not gain access to the hint oracle and asks only a single verification query.

Our definition captures also the above type of problems, additionally it is also applicable in the broader context for a different AI problems.

As it is not known how good the possible algorithm can be to recognize CAPTCHA it is likely that the gap between human performance and a performance of computer programs may be small. Therefore, it is of interest to find a way to amplify this gap. It turns out that it is indeed possible. The first result for non-dynamic puzzles was proved in [HS10]. The proof presented in Chapter 4 applies also to the dynamic context.

TODO: Give an optimization problem for gap amplification

3.3 Previous results

Different types of dynamic interactive weakly verifiable puzzles has been analyzed in a series of papers [CHS04], [DIJK09] and [HS10]. This section give the short overview of the techniques used in these works, but also is aimed to give more intuition and insight into a problem of hardness amplification of dynamic interactive weakly verifiable puzzles.

3.3.1 Results of R.Canetti, S.Halevi, and M.Steiner

The notion of *weakly verifiable puzzles* has been coined by R.Canetti, S.Halevi and M.Steiner in the paper *Hardness amplification of weakly verifiable puzzles* [CHS04]. In comparison to Definition 3.1, the puzzles considered in [CHS04] are non-dynamic and non-interactive. Moreover, the number of verification queries is limited to one. First we give a definition of weakly verifiable puzzles following the one contained in the paper of R.Canetti, S.Halevi and M.Steiner. We compare it to Definition 3.1. We state the main theorem as in [CHS04] and give the intuition behind the proof of this theorem. The main proof of this Thesis uses many ideas from the proof of R.Canetti, S.Halevi and M.Steiner.

Definition 3.6 (Weakly Verifiable Puzzles) *A weakly verifiable puzzle is defined by a pair of probabilistic polynomial time algorithms. A puzzle generating algorithm G , and an algorithm used for verifying solutions V to the puzzles generated by G . The puzzle-generation algorithm G takes as input a bitstring 1^k where k is a security parameter. Additionally, we denote the randomness used by G by $\rho \in \{0,1\}^*$. The algorithm G outputs a puzzle $p \in \{0,1\}^*$ and a check information $c \in \{0,1\}^*$. The verifier V is a deterministic polynomial time algorithm that takes as input p , c and an answer $a \in \{0,1\}^*$ and outputs a bit $b \in \{0,1\}$. A solver S for G is a polynomial time probabilistic algorithm that takes as input p and outputs a . We denote the randomness used by S as $\pi \in \{0,1\}^*$. The success probability of S is the probability that the answer a is accepted by the verification algorithm.*

$$\Pr_{\substack{\rho \in \{0,1\}^*, \pi \in \{0,1\}^* \\ (p,c) := G(1^k, \rho) \\ a := S(p, \pi)}} \left[V(p, a, c) = 1 \right].$$

Definition 3.7 (n -fold repetition of Weakly Verifiable Puzzles) *Let $n \in \mathbb{N}$, and a weakly verifiable puzzle P be fixed. We define n -fold repetition of P as a weakly verifiable puzzle where the puzzle generation algorithm $G^{(n)}$ takes as input 1^k and uses $G(1^k)$ to generate n independent instances of puzzles. The algorithm $G^{(n)}$ outputs tuples $p^{(n)} := (p_1, \dots, p_n) \in \{0,1\}^*$ and $c^{(n)} := (c_1, \dots, c_n) \in \{0,1\}^*$. Finally, the verification algorithm $V^{(n)}$ takes as input an answer (a_1, \dots, a_n) , $p^{(n)}$ and $c^{(n)}$ and outputs $b \in \{0,1\}$ such that $b = 1$ if and only if for all $1 \leq i \leq n$ we have $V(a_i, c_i, p_i) = 1$.*

We compare the above definition with Definition 3.1. First we note that clearly instead of the polynomial time, probabilistic algorithms we can use the language of polynomial size circuits, as any polynomial time algorithm can be translated into a circuit of polynomial size. Next, we see that in Definition 3.6 the algorithm are parameterized by a bitstring 1^k meaning that the length of random bitstring taken by G is bounded by $\text{poly}(k)$. Without loss of generality, for a fixed k , we can model the algorithm G as a polynomial size circuit that does not take as input the bitstring 1^k but instead just a randomness used by G . Thus, the security parameters from Definition 3.6 and Definition 3.1 are not equal as in Definition 3.1 the security parameter bounds the length of the random bitstring taken by the circuit that defines puzzles. Next, in Definition 3.6 a verification algorithm takes as input a, p, c . Again, without loss of generality we can assume that bitstrings p and c are hard-coded in the circuit Γ_V from Definition 3.1. Moreover, the n -fold repetition of Weakly Verifiable Puzzles is solved successfully if and only if all n puzzles are solved successfully. In this Thesis we are interested in more general situation when whether some repetition of puzzles is solved successfully is decided by some monotone function $g : \{0,1\}^n \rightarrow \{0,1\}$. In this way, a solver for some n wise repetition of puzzles has to solve successfully puzzles only on some coordinates. Clearly, without loss of generality we can assume that g is such that all coordinates have to be solved successfully which is the case considered in Definition 3.7. The main theorem proved in [CHS04] states that it is possible to turn a good solver for the n -fold repetition of Weakly Verifiable Puzzles to a good solver for a single Weakly Verifiable Puzzle.

Theorem 3.8 (Hardness amplification for Weakly Verifiable Puzzles)

For an efficiently computable functions $n : \mathbb{N} \rightarrow \mathbb{N}$ and $q : \mathbb{N} \rightarrow \mathbb{N}$ and $\delta \rightarrow (0,1)$ and a fixed problem poser P as in Definition 3.6. Additionally, let running times of a generation algorithm G be T_G and of the verification algorithm V be T_V . If $S^{(k)}$ is a solver for the product of $P^{(k)}$ that has success probability $\delta^{(n)}$ and running time T , then there exists a solver S for G with success probability $\delta(1 - \frac{1}{q})$ with the running time $O(\frac{nq^3}{\delta^{2n-1}}(T + nT_G + nT_V))$.

For a tuple $x^{(n)}$ and an element x_{n+1} we use $x^{(n)} \circ x_{n+1}$ to denote the concatenation of $x^{(n)}$ and x_{n+1} which results in $x^{(n+1)} := (x_1, \dots, x_n, x_{n+1})$.

The following algorithm is used in [CHS04] to prove Theorem [?]. It uses a solver A for a n -fold repetition of P that succeeds with probability at least $\delta^{(n)}$ to solve a single puzzle with probability at least $\delta(1 - \frac{1}{q})$.

TODO: what is q ? what is p describe parameters that you use KHS algo with.

Algorithm: $KHS\text{-}solver^{S,V,G}(p, n, k, q, \delta)$

Oracle: A solver S for $P^{(k)}$, verifier and generator V, G for P

Input: A bistring $p \in \{0, 1\}^*$, parameters n, k, q, δ .

$prefix := \emptyset$

for $i = 1$ **to** $n - 1$ **do**:

$p^* := \text{ExtendPrefix}(prefix, i)$

if $(p^* = \perp)$ **then return** $\text{OnlinePhase}(prefix, i, n, k, q)$

else $prefix := prefix \circ p^*$

$a^{(n)} := A(prefix \circ p)$

return a_n

Algorithm: $\text{OnlinePhase}(prefix, p, v, n, k, q, \delta)$

Oracle: A solver A for $P^{(n)}$, a verification algorithm V for P .

Input: A $(n - i)$ -tuple of puzzles $prefix$, a bitstring $p \in \{0, 1\}^*$, parameters v, n, k, q, δ .

Repeat $K_i := \frac{6q \ln(6q)}{\delta^{n-v+1}}$

$((p_{v+1}, \dots, p_n), (c_{v+1}, \dots, c_n)) := G^{(n-v)}(1^k)$

$a^{(n)} := A(prefix, p, p_{v+1}, \dots, p_n)$

if $\forall_{v+1 \leq i \leq n} V(p_i, c_i, a_i) = 1$ **then return** a_v

return \perp

Algorithm: $\text{ExtendPrefix}(prefix, i, n, k, q, \delta)$

Oracle: A generator algorithm G and a verification algorithm V for P .

Input: A $(n - i)$ -tuple of puzzles $prefix$, parameters i, n, k, q, δ .

Repeat $\left\lceil \frac{6q}{\delta^{n-v+1}} \ln\left(\frac{18qn}{\delta}\right) \right\rceil$ **times do**:

$(p^*, c^*) := G(1^k)$

$\bar{\mu}_i := \text{EstimateResSuccProb}^{V,G}(prefix \circ p^*, i)$

if $\bar{\mu}_i \geq \delta^{n-i}$ **then return** p^*

return \perp

Algorithm: $\text{EstimateResSuccProb}^{V,P}(prefix, i, n, k, q, \delta)$

Oracle: Verification algorithm V for P , Generation algorithm G for P

Input: A $(n - i)$ -tuple of puzzles $prefix$, parameters i, n, k, q, δ .

3. WEAKLY VERIFIABLE CRYPTOGRAPHIC PRIMITIVES

```
successes := 0
Repeat  $M_i := \frac{84q^2}{\delta^{n-i}} \ln(\frac{18qn \cdot N_i}{\delta})$  times
     $((p_{i+1}, \dots, p_n), (c_{i+1}, \dots, c_n)) := G^{(n-i)}(1^k)$ 
    if  $\forall 1 \leq i \leq n : V(p_i, c_i, a_i) = 1$  then successes := successes + 1
return successes/ $M_i$ 
```

TODO: Give the intuition for CHS proof, the matrix and the repetition

3.3.2 Results of Y.Dodis, R.Impagliazzo, R.Jaiswal, V.Kabanets

3.3.3 Results of T.Holenstein and G.Scheonebeck

3.4 Limitations of Security Amplification

Chapter 4

Security amplification for dynamic weakly verifiable puzzles

In this chapter we show that it is possible to amplify security of dynamic weakly verifiable puzzles. In section 4.1 we state the theorem, which is next proved in three steps. First, in Section 4.1.3, we show how to use to partition the domain on which hint and verification queries are asked, next we give a prove of security amplification under the simplifying assumption that there is no collisions of hint and verification queries. Finally, in Section 4.1.5 we combine both former steps which yields the desirable result.

4.1 Main theorem

We start by giving the definition of the k -wise direct product of weakly verifiable puzzles.

4.1.1 The k -wise direct product of weakly verifiable puzzle

Definition 4.1 (k -wise direct-product of DWVPs.) Let $g : \{0, 1\}^k \rightarrow \{0, 1\}$ be a monotone function and $P_n^{(1)}$ a problem poser as in Definition 3.1. The k -wise direct product of $P_n^{(1)}$ is a DWVP defined by a circuit $P_{kn}^{(g)}$. We write $P_{kn}^{(g)}(\pi^{(k)})$ to denote the execution of $P_{kn}^{(g)}$ with the randomness fixed to $\pi^{(k)} := (\pi_1, \dots, \pi_k)$ where for each $1 \leq i \leq k : \pi_i \in \{0, 1\}^n$. Let $(C_1, C_2)(\rho)$ be a solver for $P_{kn}^{(g)}$ as in Definition 3.1. In the first phase, the algorithm $C_1(\rho)$ sequentially interacts in k rounds with $P_{kn}^{(g)}(\pi^{(k)})$. In the i -th round $C_1(\rho)$ interacts with $P_n^{(1)}(\pi_i)$, and as the result $P_n^{(1)}(\pi_i)$ generates circuits Γ_V^i, Γ_H^i . Finally, after k rounds $P_{kn}^{(g)}(\pi^{(k)})$ outputs a verification circuit

$$\Gamma_V^{(g)}(q, y_1, \dots, y_k) := g(\Gamma_V^1(q, y_1), \dots, \Gamma_V^k(q, y_k))$$

and a hint circuit

$$\Gamma_H^{(k)}(q) := (\Gamma_H^1(q), \dots, \Gamma_H^k(q)).$$

If it is clear from the context, we omit the subscript n and write $P(\pi)$ instead of $P_n(\pi)$ where $\pi \in \{0, 1\}^n$.

A verification query (q, y) of a solver C for which a hint query on this q has been asked before cannot be a verification query for which C succeeds. Therefore, without loss of generality, we make the assumption that C does not ask verification queries on q for which a hint query has been asked before. Furthermore, we assume that once C asked a verification query that succeeds, it does not ask any further hint or verification queries.

Experiment $Success^{P,C}(\pi, \rho)$

Oracle: A problem poser P , a solver $C = (C_1, C_2)$ for P .

Input: Bitstrings $\pi \in \{0, 1\}^n$, $\rho \in \{0, 1\}^*$.

Output: A bit $b \in \{0, 1\}$.

```

run  $\langle P(\pi), C_1(\rho) \rangle$ 
       $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$ 
       $x := \langle P(\pi), C_1(\rho) \rangle_{trans}$ 

run  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$ 
      if  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$  asks a verification query  $(q, y)$  s.t.  $\Gamma_V(q, y) = 1$  then
        return 1
return 0
    
```

We define the *success probability* of C in solving a puzzle defined by P as

$$\Pr_{\pi, \rho}[Success^{P,C}(\pi, \rho) = 1]. \quad (4.1)$$

Furthermore, we say that C *succeeds* for π, ρ if $Success^{P,C}(\pi, \rho) = 1$.

Theorem 4.2 (Security amplification for dynamic weakly verifiable puzzles.)

Let $P_n^{(1)}$ be a fixed problem poser as in Definition 3.1 and $P_{kn}^{(g)}$ a problem poser for the k -wise direct product of $P_n^{(1)}$. Additionally, let C be a problem solver for $P_{kn}^{(g)}$ asking at most h hint queries and v verification queries. There exists a probabilistic algorithm Gen with oracle access to a solver circuit C , a monotone function $g : \{0, 1\}^k \rightarrow \{0, 1\}$ and problem posers $P_n^{(1)}, P_{kn}^{(g)}$. Furthermore, Gen takes as input parameters $\varepsilon, \delta, n, k, h, v$, and outputs a solver circuit D

for $P_n^{(1)}$ such that the following holds:
 If C is such that

$$\Pr_{\substack{\pi^{(k)} \in \{0,1\}^{kn} \\ \rho \in \{0,1\}^*}} \left[\text{Success}^{P_{kn}^{(g)}, C}(\pi^{(k)}, \rho) = 1 \right] \geq 16(h + v) \left(\Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon \right)$$

then D is a two phase probabilistic circuit and satisfies almost surely

$$\Pr_{\substack{\pi \in \{0,1\}^n \\ \rho \in \{0,1\}^*}} \left[\text{Success}^{P_n^{(1)}, D}(\pi, \rho) = 1 \right] \geq \delta + \frac{\varepsilon}{6k}.$$

Additionally, D requires oracle access to g , $P_n^{(1)}$, C , hint and verification circuits and asks at most $\frac{6k}{\varepsilon} \log \left(\frac{6k}{\varepsilon} \right) h$ hint queries and one verification query. Finally, $\text{Time}(\text{Gen}) = \text{poly}(k, \frac{1}{\varepsilon}, n, v, h)$ with oracle access to C .

4.1.2 Intuition

TODO: add intuition for hashing

The idea of the algorithm Gen is to output a circuit D that solves the input puzzle often. We know that C has high success probability in solving the k -wise direct product of $P^{(1)}$. The algorithm Gen tries to find a puzzle such that when C runs with this puzzle fixed on the first position and disregards whether this puzzle is correctly solved then the assumptions of Theorem 4.2 are true for the $(k - 1)$ -wise direct product. If it was possible to find such a puzzle, then Gen could recurse and solve a smaller problem. In the optimistic case we can reach $k = 1$, which means that we found a good circuit for solving a single puzzle by just fixing the initial puzzles of C .

Otherwise, when the first position is disregarded then the success probability of C is not substantially better. This is remarkable, as we know that C performs good for the k -wise direct product. It means that the first position is important, in the sense that C solves the puzzle on that position unusually often. Therefore, it is reasonable to construct the circuit D using C by placing the input puzzle of D on that position, and then finding remaining $k - 1$ puzzles. The $(k - 1)$ remaining puzzles are generated by the circuit D , hence it is possible to check whether they are correctly solved by the circuit C . We know that circuit C has good success probability, and the puzzle on the first position is important. Therefore, if we are able to find a $(k - 1)$ puzzles such that the fact whether the k -wise direct product is correctly solved depends on whether the puzzle on the first position is correctly solved then we can assume that C is often correct on this first position.

There are some problems with this approach, first we have to ensure that we can make a decision when the algorithm Gen should recurse and when not

correctly with high probability. Then, we have to show that it is possible to find a puzzles such that C is often correct on the first position. Finally, we also have to be sure that we do not ask a hint query, on the final verification query to the oracle. To satisfy the last requirement we split the set Q .

4.1.3 Domain partitioning

Let $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$, the idea is to partition Q such that the set of preimages of 0 for $hash$ contains $q \in Q$ on which C is not allowed to ask hint queries, and the first successful verification query (q, y) of C is such that $hash(q) = 0$. Therefore, if C makes a verification query (q, y) such that $hash(q) = 0$, then we know that no hint query is ever asked on this q .

We denote the i -th query of C by q_i if it is a hint query, and by (q_i, y_i) if it is a verification query. We define the following experiment *CanonicalSuccess* in which the set Q is partitioned using a function $hash$. We say that a solver circuit *succeeds* in the experiment *CanonicalSuccess* if it asks a successful verification query (q_j, y_j) such that $hash(q_j) = 0$, and no hint query q_i is asked before (q_j, y_j) such that $hash(q_i) = 0$.

Experiment $CanonicalSuccess^{P,C,hash}(\pi, \rho)$

Oracle: A problem poser P , a solver circuit $C = (C_1, C_2)$ for P ,
a function $hash : Q \rightarrow \{0, \dots, 2(h + v) - 1\}$.

Input: Bitstrings $\pi \in \{0, 1\}^n$, $\rho \in \{0, 1\}^*$.

Output: A bit $b \in \{0, 1\}$.

```

run  $\langle P(\pi), C_1(\rho) \rangle$ 
       $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$ 
       $x := \langle P(\pi), C_1(\rho) \rangle_{trans}$ 

run  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$ 
      if  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$  does not succeed for any verification query then
        return 0
      Let  $(q_j, y_j)$  be the first verification query such that  $\Gamma_V(q_j, y_j) = 1$ .

if  $(\forall i < j : hash(q_i) \neq 0)$  and  $(hash(q_j) = 0)$  then
  return 1
else
  return 0
    
```

We define the *canonical success probability* of a solver circuit C for P with

respect to a function *hash* as

$$\Pr_{\pi, \rho}[CanonicalSuccess^{P, C, hash}(\pi, \rho) = 1]. \quad (4.2)$$

For fixed *hash* and *P* a *canonical success* of *C* for bistrings π, ρ is a situation where $CanonicalSuccess^{P, C, hash}(\pi, \rho) = 1$.

We show that if a solver circuit *C* for *P* often succeeds in the experiment *Success*, then there exists a function *hash* such that *C* also often succeeds in the experiment *CanonicalSuccess*.

Lemma 4.3 (*Success probability in solving DWVP with respect to a function hash.*) *For fixed P_n let C be a solver for P_n with success probability at least γ , asking at most h hint queries and v verification queries. Let \mathcal{H} be an efficient family of pairwise independent hash functions $Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$. There exists a probabilistic algorithm *FindHash* that takes as input parameters γ, n, h, v , and has oracle access to C and P_n . Furthermore, *FindHash* runs in time $\text{poly}(h, v, \frac{1}{\gamma}, n)$, and with high probability outputs a function $hash \in \mathcal{H}$ such that the canonical success probability of C with respect to $hash$ is at least $\frac{\gamma}{16(h+v)}$.*

Proof (4.3). We fix a problem poser *P* and a solver *C* for *P* in the whole proof of Lemma 4.3. For $k, l \in \{1, \dots, (h+v)\}$ and $\alpha, \beta \in \{0, 1, \dots, 2(h+v)-1\}$ by the pairwise independence property, we have

$$\begin{aligned} \forall q_k \neq q_l \in Q : \Pr_{hash \leftarrow \mathcal{H}}[hash(q_k) = \alpha \mid hash(q_l) = \beta] &= \Pr_{hash \leftarrow \mathcal{H}}[hash(q_k) = \alpha] \\ &= \frac{1}{2(h+v)}. \end{aligned} \quad (4.3)$$

We write $\mathcal{P}_{Success}$ to denote a set containing all (π, ρ) for which $Success^{P, C}(\pi, \rho) = 1$. Let us fix $(\pi^*, \rho^*) \in \mathcal{P}_{Success}$. We are interested in the probability over a choice of function *hash* of the event $CanonicalSuccess^{P, C, hash}(\pi^*, \rho^*) = 1$. Let

(q_j, y_j) denote the first query such that $\Gamma_V(q_j, y_j) = 1$. We have

$$\begin{aligned}
 & \Pr_{hash \leftarrow \mathcal{H}} \left[\text{CanonicalSuccess}^{P,C,hash}(\pi^*, \rho^*) = 1 \right] \\
 &= \Pr_{hash \leftarrow \mathcal{H}} [hash(q_j) = 0 \wedge (\forall i < j : hash(q_i) \neq 0)] \\
 &= \Pr_{hash \leftarrow \mathcal{H}} [\forall i < j : hash(q_i) \neq 0 \mid hash(q_j) = 0] \Pr_{hash \leftarrow \mathcal{H}} [hash(q_j) = 0] \\
 &\stackrel{(4.3)}{=} \frac{1}{2(h+v)} \left(1 - \Pr_{hash \leftarrow \mathcal{H}} [\exists i < j : hash(q_i) = 0 \mid hash(q_j) = 0] \right) \\
 &\stackrel{(*)}{\geq} \frac{1}{2(h+v)} \left(1 - \sum_{i < j} \Pr_{hash \leftarrow \mathcal{H}} [hash(q_i) = 0 \mid hash(q_j) = 0] \right) \\
 &\stackrel{(4.3)}{=} \frac{1}{2(h+v)} \left(1 - \sum_{i < j} \Pr_{hash \leftarrow \mathcal{H}} [hash(q_i) = 0] \right) \\
 &\stackrel{(4.3)}{\geq} \frac{1}{4(h+v)}, \tag{4.4}
 \end{aligned}$$

where in $(*)$ we used the union bound. Let us denote the set of those (π, ρ) for which $\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1$ by $\mathcal{P}_{\text{Canonical}}$. If for π, ρ the circuit C succeeds canonically, then for the same π, ρ we also have $\text{Success}^{P,C}(\pi, \rho) = 1$. Hence, $\mathcal{P}_{\text{Canonical}} \subseteq \mathcal{P}_{\text{Success}}$, and we conclude

$$\begin{aligned}
 & \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \right] \\
 &= \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}} \right] \Pr_{\pi, \rho} [(\pi, \rho) \in \mathcal{P}_{\text{Success}}] \\
 &\quad + \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \mid (\pi, \rho) \notin \mathcal{P}_{\text{Success}} \right] \Pr_{\pi, \rho} [(\pi, \rho) \notin \mathcal{P}_{\text{Success}}] \\
 &= \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}} \right] \Pr_{\pi, \rho} [(\pi, \rho) \in \mathcal{P}_{\text{Success}}] \\
 &\geq \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} \left[\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}} \right] \cdot \gamma \\
 &= \mathbb{E}_{(\pi, \rho) \in \mathcal{P}_{\text{Success}}} \left[\Pr_{hash \leftarrow \mathcal{H}} [\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1] \right] \cdot \gamma \\
 &\stackrel{(4.4)}{\geq} \frac{\gamma}{4(h+v)}. \tag{4.5}
 \end{aligned}$$

Algorithm FindHash^{*P,C*}(γ, n, h, v)

Oracle: A problem poser P , a solver circuit C for P .

Input: Parameters γ, n . The number of hint queries h and of verification queries v .

Output: A function $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$.

```

for  $i := 1$  to  $32n(h + v)^2/\gamma^2$  do:
     $hash \leftarrow \mathcal{H}$ 
     $count := 0$ 
    for  $j := 1$  to  $32n(h + v)^2/\gamma^2$  do:
         $\pi \leftarrow \{0, 1\}^n$ 
         $\rho \leftarrow \{0, 1\}^*$ 
        if  $CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1$  then
             $count := count + 1$ 
    if  $count \geq \frac{\gamma}{12(h+v)} \frac{32(h+v)^2}{\gamma^2} n$  then
        return  $hash$ 
return  $\perp$ 

```

We show that FindHash chooses $hash \in \mathcal{H}$ such that the canonical success probability of C with respect to $hash$ is at least $\frac{\gamma}{16(h+v)}$ almost surely. Let \mathcal{H}_{Good} denote a family of functions $hash \in \mathcal{H}$ for which

$$\Pr_{\pi, \rho} \left[CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \right] \geq \frac{\gamma}{8(h+v)}, \quad (4.6)$$

and \mathcal{H}_{Bad} be a family of functions $hash \in \mathcal{H}$ such that

$$\Pr_{\pi, \rho} \left[CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \right] \leq \frac{\gamma}{16(h+v)}. \quad (4.7)$$

Let N denote the number of iterations of the inner loop of FindHash. We consider a single iteration of the outer loop of FindHash in which $hash$ is fixed. We define independent, identically distributed, binary random variables X_1, \dots, X_N such that

$$X_i = \begin{cases} 1 & \text{if in the } i\text{-th iteration of the inner loop } count \text{ is increased} \\ 0 & \text{otherwise.} \end{cases}$$

We now turn to the case when $hash \in \mathcal{H}_{Bad}$ and show that it is unlikely that $hash$ is returned by FindHash. From (4.7) it follows that $\mathbb{E}_{\pi, \rho}[X_i] \leq \frac{\gamma}{16(h+v)}$. Therefore, for any fixed $hash \in \mathcal{H}_{Bad}$ using the Chernoff bound we get

$$\begin{aligned} \Pr_{\pi, \rho} \left[\frac{1}{N} \sum_{i=1}^N X_i \geq \frac{\gamma}{12(h+v)} \right] &\leq \Pr_{\pi, \rho} \left[\frac{1}{N} \sum_{i=1}^N X_i \geq \left(1 + \frac{1}{3}\right) \mathbb{E}[X_i] \right] \\ &\leq e^{-\frac{\gamma}{16(h+v)} N/27} \leq e^{-\frac{2}{27} \frac{(h+v)}{\gamma} n} \stackrel{(*)}{\leq} e^{-\frac{2}{27} n}, \end{aligned}$$

where in (*) we used the trivial facts that $h+v \geq 1$ and $\gamma \leq 1$. The probability that $hash \in \mathcal{H}_{Good}$, when picked, is not returned amounts

$$\begin{aligned} \Pr_{\pi, \rho} \left[\frac{1}{N} \sum_{i=1}^N X_i \leq \frac{\gamma}{12(h+v)} \right] &\leq \Pr_{\pi, \rho} \left[\frac{1}{N} \sum_{i=1}^N X_i \leq \left(1 - \frac{1}{3}\right) \mathbb{E}[X_i] \right] \\ &\leq e^{-\frac{\gamma}{8(h+v)} N/18} \leq e^{-\frac{2}{9} \frac{(h+v)}{\gamma} n} \stackrel{(*)}{\leq} e^{-\frac{2}{9} n}, \end{aligned}$$

where we once more used the Chernoff bound. We now show that the probability of picking $hash \in \mathcal{H}_{Good}$ is at least $\frac{\gamma}{8(h+v)}$. To obtain a contradiction suppose that

$$\Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] < \frac{\gamma}{8(h+v)}. \quad (4.8)$$

From this it follows that we can bound probability of canonical success as follows

$$\begin{aligned} &\Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1] \\ &= \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \in \mathcal{H}_{Good}] \Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] \\ &\quad + \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \notin \mathcal{H}_{Good}] \Pr_{hash \leftarrow \mathcal{H}} [hash \notin \mathcal{H}_{Good}] \\ &\leq \Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] + \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \notin \mathcal{H}_{Good}] \\ &\stackrel{(4.6)}{<} \stackrel{(4.8)}{<} \frac{\gamma}{8(h+v)} + \frac{\gamma}{8(h+v)} = \frac{\gamma}{4(h+v)}, \end{aligned}$$

which contradicts (4.5). Therefore, we conclude that the probability of choosing a $hash \in \mathcal{H}_{Good}$ amounts at least $\frac{\gamma}{8(h+v)}$.

We show that FindHash picks in one of its iteration $hash \in \mathcal{H}_{Good}$ almost surely. Let K be the number of iterations of the outer loop of FindHash and Y_i be a random variable for the event that in the i -th iteration of the outer loop $hash \notin \mathcal{H}_{Good}$ is picked. We use $\Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] \geq \frac{\gamma}{8(h+v)}$ and $K \leq \frac{32(h+v)^2}{\gamma^2} n$, and conclude

$$\begin{aligned} \Pr_{hash \leftarrow \mathcal{H}} \left[\bigcap_{1 \leq i \leq K} Y_i \right] &\leq \left(1 - \frac{\gamma}{8(h+v)} \right)^{\frac{32(h+v)^2}{\gamma^2} n} \leq e^{-\frac{\gamma}{8(h+v)} \frac{32(h+v)^2}{\gamma^2} n} \\ &\leq e^{-\frac{4(h+v)}{\gamma} n} \leq e^{-n}. \end{aligned}$$

It is clear that running time of FindHash is $poly(n, h, v, \gamma)$ with oracle access. This finishes the proof of Lemma 4.3. \square

4.1.4 Amplification proof for partitioned domain

Let $C = (C_1, C_2)$ be a solver circuit for a dynamic weakly verifiable puzzle as in definition 3.1. We write $C_2^{(\cdot, \cdot)}$ to emphasize that C_2 does not obtain direct access to hint and verification circuits. Instead, whenever C_2 ask hint or verification queries, then it is answered explicitly as in the following code excerpt of the circuit \tilde{C}_2 .

Circuit $\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)$

Oracle: A hint circuit Γ_H , a circuit C_2 ,
a function $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$.

Input: Bitstrings $x \in \{0, 1\}^*$, $\rho \in \{0, 1\}^*$.

Output: A pair (q, y) .

```

run  $C_2^{(\cdot, \cdot)}(x, \rho)$ 
  if  $C_2^{(\cdot, \cdot)}(x, \rho)$  asks a hint query on  $q$  then
    if  $hash(q) = 0$  then
      return  $\perp$ 
    else
      answer the query of  $C_2^{(\cdot, \cdot)}(x, \rho)$  using  $\Gamma_H(q)$ 

  if  $C_2^{(\cdot, \cdot)}(x, \rho)$  asks a verification query  $(q, y)$  then
    if  $hash(q) = 0$  then
      return  $(q, y)$ 
    else
      answer the verification query of  $C_2^{(\cdot, \cdot)}(x, \rho)$  with 0

return  $\perp$ 

```

Given $C = (C_1, C_2)$ we define the circuit $\tilde{C} = (C_1, \tilde{C}_2)$. Every hint query q asked by \tilde{C} is such that $hash(q) \neq 0$. Furthermore, \tilde{C} asks no verification queries. Instead, it returns (q, y) such that $hash(q) = 0$ or \perp .

For fixed π , ρ , and $hash$ we say that the circuit \tilde{C} *succeeds* if for $x := \langle P(\pi), C_1(\rho) \rangle_{trans}$, $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$, we have

$$\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)) = 1.$$

Lemma 4.4 *For fixed P , C , and $hash$ the following statement is true*

$$\Pr_{\pi, \rho}[CanonicalSuccess^{P, C, hash}(\pi, \rho) = 1] \leq \Pr_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}}[\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)) = 1]$$

Proof. If for fixed π , ρ , and $hash$ the circuit C succeeds canonically, then for the same π , ρ , and $hash$ also \tilde{C} succeeds. Using this observation, we conclude that

$$\begin{aligned}
 \Pr_{\pi, \rho} \left[CanonicalSuccess^{P, C, hash}(\pi, \rho) = 1 \right] & \\
 & \leq \mathbb{E}_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}} [\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)) = 1] \\
 & = \Pr_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}} [\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)) = 1] \quad \square
 \end{aligned}$$

Lemma 4.5 (Security amplification for dynamic weakly verifiable puzzles with respect to hash.) Let $g : \{0, 1\}^k \rightarrow \{0, 1\}$ be a monotone function and $P_n^{(1)}$ a fixed problem poser as in Definition 3.1 and $\tilde{C} := (C_1, \tilde{C}_2)$ a circuit with oracle access to a function $hash : Q \rightarrow \{0, 1, \dots, 2(h + v - 1)\}$ and a solver circuit $C := (C_1, C_2)$ for $P_{kn}^{(g)}$ which asks at most h hint queries and v verification queries. There exists an algorithm Gen that takes as input parameters ε , δ , n , k , has oracle access to $P_n^{(1)}$, \tilde{C} , $hash$, g , and outputs a circuit $D := (D_1, D_2)$ such that the following holds:
If \tilde{C} is such that

$$\Pr_{\substack{\pi^{(k)} \in \{0, 1\}^{kn}, \rho \in \{0, 1\}^* \\ x := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{trans} \\ (\Gamma_H^{(k)}, \Gamma_V^{(g)}) := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{P^{(g)}}}} [\Gamma_V^{(g)}(\tilde{C}_2^{\Gamma_H^{(k)}, C_2, hash}(x, \rho)) = 1] \geq \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon,$$

then D satisfies almost surely

$$\Pr_{\substack{\pi \in \{0, 1\}^n, \rho \in \{0, 1\}^* \\ x := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{trans} \\ (\Gamma_H, \Gamma_V) := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{P^{(1)}}}} [\Gamma_V(D_2^{P^{(1)}, \tilde{C}, hash, g, \Gamma_H}(x, \rho)) = 1] \geq \delta + \frac{\varepsilon}{6k}.$$

Furthermore, D asks at most $\frac{6k}{\varepsilon} \log\left(\frac{6k}{\varepsilon}\right) h$ hint queries and no verification queries. Finally, $Time(Gen) = poly(k, \frac{1}{\varepsilon}, n)$ with oracle access to \tilde{C} .

Before we give the proof of Lemma 4.5 we define additional algorithms. First, we are interested in the probability that for $u \leftarrow \mu_\delta^k$ and a bit b we have $g(b, u_2, \dots, u_k) = 1$. The estimate of this probability is calculated by `EstimateFunctionProbability`.

Algorithm EstimateFunctionProbability^g(b, k, ε, δ, n)

Oracle: A function $g : \{0, 1\}^k \rightarrow \{0, 1\}$.

Input: A bit $b \in \{0, 1\}$, parameters $k, \varepsilon, \delta, n$.

Output: An estimate \tilde{g}_b of $\Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1]$.

for $i := 1$ **to** $N := \frac{64k^2}{\varepsilon^2}n$ **do:**
 $u \leftarrow \mu_\delta^k$
 $g_i := g(b, u_2, \dots, u_k)$
return $\frac{1}{N} \sum_{i=1}^N g_i$

Lemma 4.6 *The algorithm EstimateFunctionProbability^g(b, k, ε, δ, n) outputs an estimate \tilde{g}_b such that $|\tilde{g}_b - \Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1]| \leq \frac{\varepsilon}{8k}$ almost surely.*

Proof. We fix the notation as in the algorithm EstimateFunctionProbability. Let us define independent, identically distributed binary random variables K_1, K_2, \dots, K_N such that for each $1 \leq i \leq N$ the random variable K_i takes value g_i . We use the Chernoff bound to obtain

$$\begin{aligned} \Pr \left[\left| \tilde{g}_b - \Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1] \right| \geq \frac{\varepsilon}{8k} \right] \\ = \Pr \left[\left| \left(\frac{1}{N} \sum_{i=1}^N K_i \right) - \mathbb{E}_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k)] \right| \geq \frac{\varepsilon}{8k} \right] \leq 2 \cdot e^{-n/3}. \square \end{aligned}$$

The algorithm EvaluatePuzzles^{P⁽¹⁾, \tilde{C} , hash}($\pi^{(k)}, \rho, n, k$) evaluates which of the k puzzles of the k -wise direct product defined by $P^{(g)}$ are solved successfully by $\tilde{C}(\rho) := (C_1, \tilde{C}_2)(\rho)$. To decide whether the i -th puzzle of the k -wise direct product is solved successfully we need to gain access to the verification circuit for the puzzle generated in the i -th round of the interaction between $P^{(g)}$ and \tilde{C} . Therefore, the algorithm EvaluatePuzzles runs k times $P^{(1)}$ to simulate the interaction with $C_1(\rho)$ each time with a fresh random bitstring $\pi_i \in \{0, 1\}^n$ where $1 \leq i \leq k$.

Let us introduce some additional notation. We denote by $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle^i$ the execution of the i -th round of the sequential interaction. We use $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{P^{(1)}}^i$ to denote the output of $P^{(1)}(\pi_i)$ in the i -th round. Finally, we write $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{trans}^i$ to denote the transcript of communication in the i -th round. We note that the i -th round of the interaction between $P^{(1)}$ and C_1 is well defined only if all previous rounds have been executed before.

To make the notation easier in the code excerpts of circuits C_2 , D_2 and EvaluatePuzzles we omit superscripts of some oracles. Exemplary, we write $\tilde{C}_2^{\Gamma_H^{(k)}, hash}$ instead of $\tilde{C}_2^{\Gamma_H^{(k)}, C, hash}$ where the superscript of the oracle circuit C

4. SECURITY AMPLIFICATION FOR DYNAMIC WEAKLY VERIFIABLE PUZZLES

is omitted. We make sure that it is clear from the context which oracles are used.

Algorithm EvaluatePuzzles ^{$P^{(1)}, \tilde{C}, hash$} ($\pi^{(k)}, \rho, n, k$)

Oracle: A problem poser $P^{(1)}$, a solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$, a function $hash : Q \rightarrow \{0, 1, \dots, 2(h+v) - 1\}$.

Input: Bitstrings $\pi^{(k)} \in \{0, 1\}^{kn}$, $\rho \in \{0, 1\}^*$, parameters n, k .

Output: A tuple $(c_1, \dots, c_k) \in \{0, 1\}^k$.

for $i := 1$ **to** k **do:** //simulate k rounds of interaction
 $(\Gamma_V^i, \Gamma_H^i) := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{P^{(1)}}^i$
 $x_i := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{trans}^i$
 $x := (x_1, \dots, x_k)$
 $\Gamma_H^{(k)} := (\Gamma_H^1, \dots, \Gamma_H^k)$
 $(q, y_1, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, hash}(x, \rho)$
if $(q, y_1, \dots, y_k) = \perp$ **then**
 return $(0, \dots, 0)$
 $(c_1, \dots, c_k) := (\Gamma_V^1(q, y_1), \dots, \Gamma_V^k(q, y_k))$
return (c_1, \dots, c_k)

All puzzles used by EvaluatePuzzles are generated internally thus the algorithm has access to hint circuit, and can answer itself all queries of \tilde{C}_2 .

We are interested in the success probability of \tilde{C} with the bitstring π_1 fixed to π^* where the fact whether \tilde{C} succeeds in solving the first puzzle defined by $P^{(1)}(\pi_1)$ is neglected, and instead a bit b is used. More formally, we define the surplus $S_{\pi^*, b}$ as

$$S_{\pi^*, b} = \Pr_{\pi^{(k)}, \rho} [g(b, c_2, \dots, c_k) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_\delta^k} [g(b, u_2, \dots, u_k) = 1], \quad (4.9)$$

where (c_2, c_3, \dots, c_k) is obtained as in EvaluatePuzzles.

The algorithm EstimateSurplus returns an estimate $\tilde{S}_{\pi^*, b}$ for $S_{\pi^*, b}$.

Algorithm EstimateSurplus ^{$P^{(1)}, \tilde{C}, g, hash$} ($\pi^*, b, k, \varepsilon, \delta, n$)

Oracle: A problem poser $P^{(1)}$, a circuit \tilde{C} for $P^{(g)}$, functions $g : \{0, 1\}^k \rightarrow \{0, 1\}$ and $hash : Q \rightarrow \{0, 1, \dots, 2(h+v) - 1\}$.

Input: A bistring $\pi^* \in \{0, 1\}^n$, a bit $b \in \{0, 1\}$, parameters $k, \varepsilon, \delta, n$.

Output: An estimate $\tilde{S}_{\pi^*, b}$ for $S_{\pi^*, b}$.

```

for  $i := 1$  to  $N := \frac{64k^2}{\varepsilon^2}n$  do:
     $(\pi_2, \dots, \pi_k) \xleftarrow{\$} \{0, 1\}^{(k-1)n}$ 
     $\rho \xleftarrow{\$} \{0, 1\}^*$ 
     $(c_1, \dots, c_k) := \text{EvaluatePuzzles}^{P^{(1)}, \tilde{C}, \text{hash}}((\pi^*, \pi_2, \dots, \pi_k), \rho, n, k)$ 
     $\tilde{s}_{\pi^*, b}^i := g(b, c_2, \dots, c_k)$ 
 $\tilde{g}_b := \text{EstimateFunctionProbability}^g(b, k, \varepsilon, \delta, n)$ 
return  $\left( \frac{1}{N} \sum_{i=1}^N \tilde{s}_{\pi^*, b}^i \right) - \tilde{g}_b$ 

```

Lemma 4.7 *The estimate $\tilde{S}_{\pi^*, b}$ returned by *EstimateSurplus* differs from $S_{\pi^*, b}$ by at most $\frac{\varepsilon}{4k}$ almost surely.*

Proof. We use the union bound and similar argument as in Lemma 4.6 which yields that $\frac{1}{N} \sum_{i=1}^N \tilde{s}_{\pi^*, b}^i$ differs from $\mathbb{E}[g(b, c_2, \dots, c_k)]$ by at most $\frac{\varepsilon}{8k}$ almost surely. Together, with Lemma 4.6 we conclude that the surplus estimate returned by *EstimateSurplus* differs from $S_{\pi^*, b}$ by at most $\frac{\varepsilon}{4k}$ almost surely. \square

We define the following solver circuit $C' = (C'_1, C'_2)$ for the $(k-1)$ -wise direct product of $P^{(1)}$.

Circuit $C'_1{}^{\tilde{C}, P^{(1)}}(\rho)$

Oracle: A solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$, a poser $P^{(1)}$.

Input: A bitstring $\rho \in \{0, 1\}^*$.

Hard-coded: A bitstring $\pi^* \in \{0, 1\}^n$.

Simulate $\langle P^{(1)}(\pi^*), C_1(\rho) \rangle^1$

Use $C_1(\rho)$ for the remaining $k-1$ rounds of interaction.

Circuit $\tilde{C}_2{}^{\Gamma_H^{(k-1)}, \tilde{C}, \text{hash}}(x^{(k-1)}, \rho)$

Oracle: A hint oracle $\Gamma_H^{(k-1)} := (\Gamma_H^2, \dots, \Gamma_H^k)$,
a solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$,
a function $\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h+v)-1\}$.

Input: A transcript of $k-1$ rounds of interaction

$x^{(k-1)} := (x_2, \dots, x_k) \in \{0, 1\}^*$, a bitstring $\rho \in \{0, 1\}^*$

Hard-coded: A bitstring $\pi^* \in \{0, 1\}^n$

Simulate $\langle P^{(1)}(\pi^*), C_1(\rho) \rangle^1$

$(\Gamma_H^*, \Gamma_V^*) := \langle P^{(1)}(\pi^*), C_1(\rho) \rangle_{P^{(1)}}^1$

$x^* := \langle P^{(1)}(\pi^*), C_1(\rho) \rangle_{\text{trans}}^1$

4. SECURITY AMPLIFICATION FOR DYNAMIC WEAKLY VERIFIABLE PUZZLES

```

 $\Gamma_H^{(k)} := (\Gamma_H^*, \Gamma_H^2, \dots, \Gamma_H^k)$ 
 $x^{(k)} := (x^*, x_2, \dots, x_k)$ 
 $(q, y_1, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, hash}(x^{(k)}, \rho)$ 
return  $(q, y_2, \dots, y_k)$ 

```

We are ready to define the solver circuit $D = (D_1, D_2)$ for $P^{(1)}$ and the algorithm Gen.

Circuit $D_1^{\tilde{C}}(r)$

Oracle: A solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$.

Input: A pair $r := (\rho, \sigma)$ where $\rho \in \{0, 1\}^*$ and $\sigma \in \{0, 1\}^*$.

Interact with the problem poser $\langle P^{(1)}, C_1(\rho) \rangle^1$.

Let $x^* := \langle P^{(1)}, C_1(\rho) \rangle_{trans}^1$.

Circuit $D_2^{P^{(1)}, \tilde{C}, hash, g, \Gamma_H}(x^*, r)$

Oracle: A poser $P^{(1)}$, a solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$,
functions $hash : Q \rightarrow \{0, 1, \dots, 2(h+v)-1\}$, $g : \{0, 1\}^k \rightarrow \{0, 1\}$,
a hint circuit Γ_H for $P^{(1)}$.

Input: A communication transcript $x^* \in \{0, 1\}^*$, a bitstring $r := (\rho, \sigma)$
where $\rho \in \{0, 1\}^*$ and $\sigma \in \{0, 1\}^*$

Output: A pair (q, y^*) .

for at most $\frac{6k}{\epsilon} \log(\frac{6k}{\epsilon})$ iterations **do:**

$(\pi_2, \dots, \pi_k) \leftarrow$ read next $(k-1) \cdot n$ bits from σ

Use x^* to simulate the first round of interaction of $C_1(\rho)$ with the problem poser $P^{(1)}$

for $i := 2$ **to** k **do:**

run $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle^i$

$(\Gamma_V^i, \Gamma_H^i) := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{P^{(1)}}^i$

$x_i := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{trans}^i$

$\Gamma_H^{(k)}(q) := (\Gamma_H(q), \Gamma_H^2(q), \dots, \Gamma_H^k(q))$

$(q, y^*, y_2, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, hash}((x^*, x_2, \dots, x_k), \rho)$

$(c_2, \dots, c_k) := (\Gamma_V^2(q, y_2), \dots, \Gamma_V^k(q, y_k))$

if $g(1, c_2, \dots, c_k) = 1$ **and** $g(0, c_2, \dots, c_k) = 0$ **then**

return (q, y^*)

return \perp

Algorithm $\text{Gen}^{P^{(1)}, \tilde{C}, g, \text{hash}}(\varepsilon, \delta, n, k)$

Oracle: A poser $P^{(1)}$, a solver circuit \tilde{C} for $P^{(g)}$, functions $g : \{0, 1\}^k \rightarrow \{0, 1\}$,

$\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$.

Input: Parameters $\varepsilon, \delta, n, k$.

Output: A circuit D .

for $i := 1$ **to** $\frac{6k}{\varepsilon}n$ **do:**

$\pi^* \xleftarrow{\$} \{0, 1\}^n$

$\tilde{S}_{\pi^*, 0} := \text{EstimateSurplus}^{P^{(1)}, \tilde{C}, g, \text{hash}}(\pi^*, 0, k, \varepsilon, \delta, n)$

$\tilde{S}_{\pi^*, 1} := \text{EstimateSurplus}^{P^{(1)}, \tilde{C}, g, \text{hash}}(\pi^*, 1, k, \varepsilon, \delta, n)$

if $\exists b \in \{0, 1\} : \tilde{S}_{\pi^*, b} \geq (1 - \frac{3}{4k})\varepsilon$ **then**

Let C'_1 have oracle access to \tilde{C} , and have hard-coded π^*

Let \tilde{C}'_2 have oracle access to \tilde{C} , and have hard-coded π^* .

$\tilde{C}' := (C'_1, \tilde{C}'_2)$

$g'(b_2, \dots, b_k) := g(b, b_2, \dots, b_k)$

return $\text{Gen}^{P^{(1)}, \tilde{C}', g', \text{hash}}(\varepsilon, \delta, n, k - 1)$

// all estimates are lower than $(1 - \frac{3}{4k})\varepsilon$

return $D^{P^{(1)}, \tilde{C}, \text{hash}, g}$

Proof (Lemma 4.5). First let us consider the case where $k = 1$. The function $g : \{0, 1\} \rightarrow \{0, 1\}$ is either the identity or a constant function. If g is the identity function, then the circuit D returned by Gen directly uses \tilde{C} to find a solution. From the assumptions of Lemma 4.5 it follows that \tilde{C} succeeds with probability at least $\delta + \varepsilon$. Hence, D trivially satisfies the statement of Lemma 4.5. In the latter case g is a constant function, and the statement is vacuously true.

For the general case, we consider two possibilities. Either Gen in one of the iterations finds an estimate $\tilde{S}_{\pi^*, b} \geq (1 - \frac{3}{4k})\varepsilon$ or it fails and returns the circuit D .

In the former case we define a new monotone function $g'(b_2, \dots, b_k) := g(b, b_2, \dots, b_k)$ and a new circuit $\tilde{C}' = (C'_1, \tilde{C}'_2)$ with oracle access to $\tilde{C} := (C_1, \tilde{C}_2)$. By Lemma 4.7 it follows that $S_{\pi^*, b} \geq \tilde{S}_{\pi^*, b} - \frac{\varepsilon}{4k} \geq (1 - \frac{1}{k})\varepsilon$ almost surely. Therefore, the circuit \tilde{C}' succeeds in solving the $(k-1)$ -wise direct product of puzzles with probability at least $\Pr_{u \leftarrow \mu_\delta^{(k-1)}}[g'(u_1, \dots, u_{k-1})] + (1 - \frac{1}{k})\varepsilon$. In this case \tilde{C}' satisfies the conditions of Lemma 4.5 for the $(k-1)$ -wise direct product of puzzles. Therefore, the recursive call to Gen with access to g' and \tilde{C} returns

a circuit $D = (D_1, D_2)$ that with high probability satisfies

$$\Pr_{\pi, \rho}[\Gamma_V(D_2^{P^{(1)}, \tilde{C}, hash, g, \Gamma_H}(x, \rho)) = 1] \geq \delta + \left(1 - \frac{1}{k}\right) \frac{\varepsilon}{6(k-1)} = \delta + \frac{\varepsilon}{6k}. \quad (4.10)$$

$x := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{trans}$
 $(\Gamma_H, \Gamma_V) := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{P^{(1)}}$

The only point remaining concerns the behavior of Gen when none of the estimates is greater than $(1 - \frac{3}{4k})\varepsilon$. Assume that...

TODO : Give more intuition (and the correct one with references to the equations)

Intuitively this means that \tilde{C} does not succeed on the remaining $k-1$ puzzles with much higher probability than an algorithm that correctly solves each puzzle with probability δ . However, from the assumptions of Lemma 4.5 we know that on all k puzzles the success probability of \tilde{C} is higher. Therefore, it is likely that the first puzzle is correctly solved unusually often. It remains to prove that this intuition is indeed correct.

We fix the notation used in the code excerpt of the circuit D_2 . We consider a single iteration of the outer loop of D_2 , in which values π_2, \dots, π_k are fixed. Additionally, we write π_1 to denote the randomness of the problem poser and define $c_1 := \Gamma_V(q, y_1)$, where Γ_V is the verification circuit generated by $P^{(1)}(\pi_1)$ in the first phase when interacting with $D_1(r)$. Finally, we introduce the additional notation $\mathcal{G}_b := \{(b_1, b_2, \dots, b_k) : g(b, b_2, \dots, b_k) = 1\}$ and $c = (c_1, c_2, \dots, c_k)$. Using the new notation the following holds

$$\begin{aligned} \Pr_{u \leftarrow \mu_\delta^k}[u \in \mathcal{G}_b] &= \Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1] \\ \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_b] &= \Pr_{\pi^{(k)}, \rho}[g(b, c_2, \dots, c_k) = 1]. \end{aligned} \quad (4.11)$$

We fix the randomness π_1 of the problem poser $P^{(1)}$ to π^* and use (4.9), (4.11) to obtain

$$\begin{aligned} &\Pr_{u \leftarrow \mu_\delta^k}[u \in \mathcal{G}_1] - \Pr_{u \leftarrow \mu_\delta^k}[u \in \mathcal{G}_0] \\ &= \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_1 \mid \pi_1 = \pi^*] - \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_0 \mid \pi_1 = \pi^*] - (S_{\pi^*, 1} - S_{\pi^*, 0}) \end{aligned} \quad (4.12)$$

We know that the function g is monotone, hence it holds $\mathcal{G}_0 \subseteq \mathcal{G}_1$, and we write (4.12) as

$$\Pr_{u \leftarrow \mu_\delta^k}[u \in \mathcal{G}_1 \setminus \mathcal{G}_0] = \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] - (S_{\pi^*, 1} - S_{\pi^*, 0}). \quad (4.13)$$

Still having $\pi_1 = \pi^*$ fixed we multiply both sides of (4.13) by

$$\Pr_r[\Gamma_V(D_2(x^*, r)) = 1] / \Pr_{u \leftarrow \mu_\delta^k}[u \in \mathcal{G}_1 \setminus \mathcal{G}_0],$$

$x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}$
 $(\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}$

which yields

$$\begin{aligned}
 & \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] \\
 &= \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \frac{1}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \\
 &\quad - \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*, 1} - S_{\pi^*, 0}) \frac{1}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]}.
 \end{aligned} \tag{4.14}$$

We analyze the first summand of (4.14). First, we have

$$\begin{aligned}
 & \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] \\
 &= \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1 \mid D_2(x^*, r) \neq \perp] \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}}} [D_2(x^*, r) \neq \perp] \\
 &\stackrel{(*)}{=} \Pr_{\substack{\pi^{(k)}, \rho \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}}} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}}} [D_2(x^*, r) \neq \perp], \tag{4.15}
 \end{aligned}$$

where in $(*)$ we use the observation that the event $D_2(x^*, r) \neq \perp$ happens if and only if the circuit $D_2(x^*, r)$ finds $\pi^{(k)}$ such that $c \in \mathcal{G}_1 \setminus \mathcal{G}_0$. Furthermore, conditioned on $c \in \mathcal{G}_1 \setminus \mathcal{G}_0$ we have that $\Gamma_V(D_2(x^*, r)) = 1$ occurs if and only if $c_1 = 1$. Inserting (4.15) to the numerator of the first summand of (4.14) yields

$$\begin{aligned}
 & \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x^*, r)) = 1] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \\
 &= \Pr_{\substack{r \\ x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}}} [D_2(x^*, r) \neq \perp] \Pr_{\pi^{(k)}, \rho} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*].
 \end{aligned} \tag{4.16}$$

We consider the following two cases. If $\Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \leq \frac{\varepsilon}{6k}$ then

$$\Pr_{\pi^{(k)}, \rho} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \leq \frac{\varepsilon}{6k}. \tag{4.17}$$

When $\Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] > \frac{\varepsilon}{6k}$ the circuit D_2 outputs \perp if and only if it fails in all $\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})$ iterations to find $\pi^{(k)}$ such that $c \in \mathcal{G}_1 \setminus \mathcal{G}_0$ which

happens with probability

$$\Pr_r[D_2(x^*, r) = \perp] \leq (1 - \frac{\varepsilon}{6k})^{\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})} \leq \frac{\varepsilon}{6k}. \quad (4.18)$$

$x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}$

We conclude that in both cases by (4.17) and (4.18) we have

$$\begin{aligned} & \Pr_r[D_2(x^*, r) \neq \perp] \Pr_{\pi^{(k)}, \rho}[c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \\ & \geq \Pr_{\pi^{(k)}, \rho}[c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\ & = \Pr_{\pi^{(k)}, \rho}[c_1 = 1 \wedge c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\ & = \Pr_{\pi^{(k)}, \rho}[g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{\pi^{(k)}, \rho}[c \in \mathcal{G}_0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\ & \stackrel{(4.9)}{=} \Pr_{\pi^{(k)}, \rho}[g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_\delta^{(k)}}[u \in \mathcal{G}_0] - S_{\pi^*, 0} - \frac{\varepsilon}{6k}. \end{aligned} \quad (4.19)$$

$x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}$

We insert (4.19) to (4.14) and calculate the expected value of over π^* which yields

$$\begin{aligned} & \Pr_{\pi, r}[\Gamma_V(D_2(x, r)) = 1] \geq \mathbb{E}_{\pi^*} \left[\frac{\Pr_{\pi^{(k)}, \rho}[g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_\delta^{(k)}}[u \in \mathcal{G}_0] - \frac{\varepsilon}{6k}}{\Pr_{u \leftarrow \mu_\delta^{(k)}}[u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \right] \\ & \quad - \mathbb{E}_{\pi^*} \left[\left(\Pr_r[\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*, 1} - S_{\pi^*, 0}) + S_{\pi^*, 0} \right) \frac{1}{\Pr_{u \leftarrow \mu_\delta^{(k)}}[u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \right]. \end{aligned} \quad (4.20)$$

$x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans}$
 $(\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}$

We show that if Gen does not recurse, then the majority of estimates is low almost surely. Let us assume that

$$\Pr_\pi \left[\left(S_{\pi, 0} \leq (1 - \frac{1}{2k})\varepsilon \right) \wedge \left(S_{\pi, 1} \leq (1 - \frac{1}{2k})\varepsilon \right) \right] < 1 - \frac{\varepsilon}{6k}, \quad (4.21)$$

then Gen recurses almost surely, because the probability that Gen does not find $\tilde{S}_{\pi, b} \geq (1 - \frac{3}{4k})\varepsilon$ in all of the $\frac{6k}{\varepsilon}n$ iterations is at most

$$\left(1 - \frac{\varepsilon}{6k} \right)^{\frac{6k}{\varepsilon}n} \leq e^{-n}$$

almost surely, where we used Lemma 4.7. Therefore, under the assumption that Gen does not recurse with high probability it holds

$$\Pr_{\pi, \rho} \left[\left(S_{\pi, 0} \leq (1 - \frac{1}{2k})\varepsilon \right) \wedge \left(S_{\pi, 1} \leq (1 - \frac{1}{2k})\varepsilon \right) \right] \geq 1 - \frac{\varepsilon}{6k}. \quad (4.22)$$

Let us define a set

$$\mathcal{W} = \left\{ \pi : \left(S_{\pi,0} \leq \left(1 - \frac{1}{2k}\right)\varepsilon \right) \wedge \left(S_{\pi,1} \leq \left(1 - \frac{1}{2k}\right)\varepsilon \right) \right\}, \quad (4.23)$$

and use $\overline{\mathcal{W}}$ to denote the complement of \mathcal{W} . We bound the numerator of the second summand in (4.20)

$$\begin{aligned} & \mathbb{E}_{\pi^*} [S_{\pi^*,0} + \Pr_{\substack{x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}}} [\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*,1} - S_{\pi^*,0})] \\ &= \mathbb{E}_{\pi^*} \left[S_{\pi^*,0} + \Pr_{\substack{x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}}} [\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*,1} - S_{\pi^*,0}) \mid \pi^* \in \overline{\mathcal{W}} \right] \Pr_{\pi^*} [\pi^* \in \overline{\mathcal{W}}] \\ &+ \mathbb{E}_{\pi^*} \left[S_{\pi^*,0} + \Pr_{\substack{x^* := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}}} [\Gamma_V(D_2(x^*, r)) = 1] (S_{\pi^*,1} - S_{\pi^*,0}) \mid \pi^* \in \mathcal{W} \right] \Pr_{\pi^*} [\pi^* \in \mathcal{W}] \\ &\leq \frac{\varepsilon}{6k} + \mathbb{E}_{\pi^*} \left[S_{\pi^*,0} + \Pr_{\substack{x := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(r) \rangle_{P(1)}}} [\Gamma_V(D_2^{\tilde{C}}(x^*, r)) = 1] \left(\left(1 - \frac{1}{2k}\right)\varepsilon - S_{\pi^*,0} \right) \mid \pi^* \in \mathcal{W} \right] \Pr_{\pi^*} [\pi^* \in \mathcal{W}] \\ &\leq \frac{\varepsilon}{6k} + \left(1 - \frac{1}{2k}\right)\varepsilon = \left(1 - \frac{1}{3k}\right)\varepsilon. \end{aligned} \quad (4.24)$$

We observe that

$$\begin{aligned} \Pr_{u \leftarrow \mu_{\delta}^k} [g(u) = 1] &= \Pr[u \in \mathcal{G}_0 \vee (u \in \mathcal{G}_1 \setminus \mathcal{G}_0 \wedge u_1 = 1)] \\ &= \Pr[u \in \mathcal{G}_0] + \delta \Pr[u \in \mathcal{G}_1 \setminus \mathcal{G}_0]. \end{aligned} \quad (4.25)$$

Finally, we insert (4.24) into (4.20) which yields

$$\Pr_{\substack{x := \langle P^{(1)}(\pi), D_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi), D_1(\rho) \rangle_{P(1)}}} [\Gamma_V(D_2(x, \rho)) = 1] \geq \mathbb{E}_{\pi^*} \left[\frac{\Pr_{\pi^{(k)}, \rho} [g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_0] - \left(1 - \frac{1}{6k}\right)\varepsilon}{\Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \right].$$

From the assumptions of Lemma 4.5 it follows that

$$\Pr_{\pi^{(k)}, \rho} [g(c) = 1] \geq \Pr_{u \leftarrow \mu_{\delta}^{(k)}} [g(u) = 1] + \varepsilon.$$

thus we get

$$\begin{aligned} \Pr_{\substack{x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{trans} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P(1)}}} [\Gamma_V(D_2(x, \rho)) = 1] &\geq \frac{\Pr_{u \leftarrow \mu_{\delta}^k} [g(u) = 1] + \varepsilon - \Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_0] - \left(1 - \frac{1}{6k}\right)\varepsilon}{\Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \\ &\stackrel{(4.25)}{\geq} \frac{\varepsilon + \delta \Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0] - \left(1 - \frac{1}{6k}\right)\varepsilon}{\Pr_{u \leftarrow \mu_{\delta}^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \geq \delta + \frac{\varepsilon}{6k} \end{aligned} \quad (4.26)$$

Clearly, the running time of Gen is $\text{poly}(k, \frac{1}{\varepsilon}, n)$. \square

4.1.5 Putting it together

In the previous sections we have shown that it is possible to partition the domain Q such that if the number of hint and verification queries is small, then success probability of a solver for the k -wise direct product is still substantial. As shown in Lemma 4.5 we can build a circuit that returns a solution that is likely to be good. It remains to use these build blocks and prove Theorem 4.2.

Proof (of Theorem 4.2). Let $\widetilde{\text{Gen}}$ be the algorithm from Theorem 4.2, and $\widetilde{D} = (D_1, D_2)$ the corresponding solver circuit for P that is output by $\widetilde{\text{Gen}}$ as in Theorem 4.2. They are defined on the following code excerpts.

Circuit $\widetilde{D}_2^{D, P^{(1)}, \text{hash}, g, \Gamma_V, \Gamma_H}(x, \rho)$

Oracle: A circuit $D := (D_1, \widetilde{D}_2)$ from Lemma 4.5, a problem poser $P^{(1)}$, functions $\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h+v)-1\}$, $g : \{0, 1\}^k \rightarrow \{0, 1\}$ a verification oracle Γ_V , a hint oracle Γ_H .

Input: Bitstrings $x \in \{0, 1\}^*$, $\rho \in \{0, 1\}^*$.

$(q, y) := D_2^{P^{(1)}, \widetilde{C}, \text{hash}, g, \Gamma_H}(x, \rho)$
Ask verification query (q, y) to Γ_V .

Algorithm $\widetilde{\text{Gen}}^{P^{(1)}, g, C}(n, \varepsilon, \delta, k, h, v)$

Oracle: A problem poser $P^{(1)}$, a function $g : \{0, 1\}^k \rightarrow \{0, 1\}$, a solver circuit C for $P^{(g)}$.

Input: Parameters $n, \varepsilon, \delta, k, h, v$.

Return: A circuit $\widetilde{D} = (D_1, \widetilde{D}_2)$.

$\text{hash} := \text{FindHash}((h+v)\varepsilon, n, h, v)$

Let $\widetilde{C} := (C_1, \widetilde{C}_2)$ be as in Lemma 4.4 with oracle access to C , hash .

$D := \text{Gen}^{P^{(1)}, \widetilde{C}, g, \text{hash}}(\varepsilon, \delta, n, k)$

return $\widetilde{D} := (D_1, \widetilde{D}_2)$

We show that Theorem 4.2 follows from Lemma 4.3 and Lemma 4.5. We fix $P^{(1)}$, g , $P^{(g)}$ in the whole proof and consider a solver circuit $C = (C_1, C_2)$, asking at most h hint queries and v verification queries, such that

$$\Pr_{\pi^{(k)}, \rho} \left[\text{Success}^{P^{(g)}, C}(\pi^{(k)}, \rho) = 1 \right] \geq 16(h+v) \left(\Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon \right).$$

First, we note that C meets the requirements of Lemma 4.3. Thus, the algorithm $\widetilde{\text{Gen}}$ can call FindHash to obtain $hash$ such that with high probability it holds

$$\Pr_{\pi^{(k)}, \rho} \left[\text{CanonicalSuccess}^{P^{(g)}, C, hash}(\pi^{(k)}, \rho) = 1 \right] \geq \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon.$$

Applying Lemma 4.4 for C we obtain a circuit $\tilde{C} = (C_1, \tilde{C}_2)$ that satisfies

$$\Pr_{\pi^{(k)}, \rho} [\Gamma_V^{(g)}(\tilde{C}_2^{\Gamma_H^{(k)}, C_2, hash}(x, \rho)) = 1] \geq \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon.$$

$x := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{trans}$
 $(\Gamma_V^{(g)}, \Gamma_H^{(k)}) := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{P^{(g)}}$

Now, we use the algorithm Gen as in Lemma 4.5 that yields a circuit $D = (D_1, D_2)$ which with high probability satisfies

$$\Pr_{\pi, \rho} [\Gamma_V(D_2^{P^{(1)}, \tilde{C}, hash, g, \Gamma_H}(x, \rho)) = 1] \geq (\delta + \frac{\varepsilon}{6k}). \quad (4.27)$$

$x := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{trans}$
 $(\Gamma_H, \Gamma_V) := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{P^{(1)}}$

Finally, $\widetilde{\text{Gen}}$ outputs $\tilde{D} = (D_1, \tilde{D}_2)$ with oracle access to D , $P^{(1)}$, $hash$, g such that with high probability it holds

$$\Pr_{\pi, \rho} [\text{Success}^{P^{(1)}, \tilde{D}}(\pi, \rho) = 1] \geq (\delta + \frac{\varepsilon}{6k}).$$

The running time of FindHash is $\text{poly}(h, v, \frac{1}{\varepsilon}, n)$ with oracle calls and of Gen $\text{poly}(k, \frac{1}{\varepsilon}, n)$ with oracle access. Thus, the overall running time of $\widetilde{\text{Gen}}$ is $\text{poly}(k, \frac{1}{\varepsilon}, h, v, n, t)$ with oracle access. Furthermore, the circuit \tilde{D} asks at most $\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})h$ hint queries and one verification query. Finally, we have $\text{Size}(\tilde{D}) \leq \text{Size}(C) \cdot \frac{6k}{\varepsilon}$. This finishes the proof of Theorem 4.2. \square

4.2 Discussion

Appendix A

Appendix

A.1 Basic Inequalities

Lemma A.1 (Chernoff Bounds) *For independent, identically distributed Bernoulli random variables X_1, \dots, X_n with $X := \sum_{i=1}^n X_i$ with $\Pr[X_i = 1] = p_i$ and $\Pr[X_i = 0] = 1 - p_i$ for all $1 \leq i \leq n$. we have the following inequalities for $0 \leq \delta \leq 1$ and $\mathbb{E}[X] = \sum_{i=1}^n p_i$:*

$$\Pr[X \geq (1 + \delta)\mathbb{E}[X]] \leq e^{-\mathbb{E}[X]\delta^2/3} \quad (\text{A.1})$$

$$\Pr[X \leq (1 - \delta)\mathbb{E}[X]] \leq e^{-\mathbb{E}[X]\delta^2/2} \quad (\text{A.2})$$

$$\Pr[|X - \mathbb{E}[X]| \geq \delta\mathbb{E}[X]] \leq 2e^{-\mathbb{E}[X]\delta^2/3}. \quad (\text{A.3})$$

Bibliography

- [AB09] Sanjeev Arora and Boaz Barak. *Computational Complexity: A Modern Approach*. Cambridge University Press, New York, NY, USA, 1st edition, 2009.
- [CHS04] Ran Canetti, Shai Halevi, and Michael Steiner. Hardness amplification of weakly verifiable puzzles. 2004.
- [CW77] J. Lawrence Carter and Mark N. Wegman. Universal classes of hash functions (extended abstract). In *Proceedings of the Ninth Annual ACM Symposium on Theory of Computing*, STOC '77, pages 106–112, New York, NY, USA, 1977. ACM.
- [DIJK09] Yevgeniy Dodis, Russell Impagliazzo, Ragesh Jaiswal, and Valentine Kabanets. Security amplification for interactive cryptographic primitives. In *Proceedings of the 6th Theory of Cryptography Conference on Theory of Cryptography*, TCC '09, pages 128–145, Berlin, Heidelberg, 2009. Springer-Verlag.
- [Gol04] Oded Goldreich. *Foundations of Cryptography: Volume 2, Basic Applications*. Cambridge University Press, New York, NY, USA, 2004.
- [Hol13a] Thomas Holenstein. Lecture notes in complexity theoretic cryptography, Spring 2013.
- [Hol13b] Thomas Holenstein. Lecture notes in complexity theory, Spring 2013.
- [HS10] Thomas Holenstein and Grant Schoenebeck. General hardness amplification of predicates and puzzles. *CoRR*, abs/1002.3534, 2010.

BIBLIOGRAPHY

- [Mau13] Ueli Maurer. Lecture notes in cryptography, Spring 2013.
- [VABHL03] Luis Von Ahn, Manuel Blum, Nicholas J Hopper, and John Langford. Captcha: Using hard ai problems for security. In *Advances in Cryptology—EUROCRYPT 2003*, pages 294–311. Springer, 2003.