

We write μ_δ to denote the Bernoulli distribution, where outcome 1 occurs with probability δ and 0 with probability $1 - \delta$ where $0 \leq \delta \leq 1$. Moreover, we use μ_δ^k to denote a probability distribution over k -tuples, where each bit of a k -tuple is drawn independently according to μ_δ . Finally, let $u \leftarrow \mu_\delta^k$ denote that a k -tuple u is chosen according to μ_δ^k .

The protocol execution between two probabilistic algorithms A and B is denoted by $\langle A, B \rangle$. The output of A in such a protocol execution is denoted by $\langle A, B \rangle_A$ and of B by $\langle A, B \rangle_B$. Finally, let $\langle A, B \rangle_{trans}$ denote the transcript of communication between A and B .

We define a *two phase circuit* $C := (C_1, C_2)$ as a circuit where in the first phase a circuit C_1 is executed and in the second phase a circuit C_2 .

We say that an event happens *almost surely* or with *high probability* if it occurs with probability at least $1 - 2^{-n} \text{poly}(n)$.

Definition 1.1 (Dynamic weakly verifiable puzzle.) A *dynamic weakly verifiable puzzle* (DWVP) is defined by a family of probabilistic circuits $\{P_n\}$. A circuit belonging to $\{P_n\}$ is called a *problem poser*. A *problem solver* $C := (C_1, C_2)$ for P_n is a probabilistic two phase circuit. We write $P_n(\pi)$ to denote the execution of P_n with the randomness fixed to $\pi \in \{0, 1\}^n$, and $(C_1, C_2)(\rho)$ to denote the execution of both C_1 and C_2 with the randomness fixed to $\rho \in \{0, 1\}^*$.

In the first phase, the poser $P_n(\pi)$ and the solver $C_1(\rho)$ interact. As the result of the interaction $P_n(\pi)$ outputs a verification circuit Γ_V and a hint circuit Γ_H . The circuit $C_1(\rho)$ produces no output. The circuit Γ_V takes as input $q \in Q$, an answer $y \in \{0, 1\}^*$, and outputs a bit. We say that an answer (q, y) is a *correct solution* if and only if $\Gamma_V(q, y) = 1$. The circuit Γ_H on input $q \in Q$ outputs a hint such that $\Gamma_V(q, \Gamma_H(q)) = 1$.

In the second phase, C_2 takes as input $x := \langle P_n(\pi), C_1(\rho) \rangle_{trans}$, and has oracle access to Γ_V and Γ_H . The execution of C_2 with the input x and the randomness fixed to ρ is denoted by $C_2(x, \rho)$. The queries of C_2 to Γ_V and Γ_H are called *verification queries* and *hint queries* respectively. The circuit C_2 succeeds if and only if it makes a verification query (q, y) such that $\Gamma_V(q, y) = 1$, and it has not previously asked for a hint query on q .

Definition 1.2 (k -wise direct-product of DWVPs.) Let $g : \{0, 1\}^k \rightarrow \{0, 1\}$ be a monotone function and $P_n^{(1)}$ a problem poser as in Definition 1.1. The k -wise direct product of $P_n^{(1)}$ is a DWVP defined by a circuit $P_{kn}^{(g)}$. We write $P_{kn}^{(g)}(\pi^{(k)})$ to denote the execution of $P_{kn}^{(g)}$ with the randomness fixed to $\pi^{(k)} := (\pi_1, \dots, \pi_k)$ where for each $1 \leq i \leq n : \pi_i \in \{0, 1\}^n$. Let $(C_1, C_2)(\rho)$ be a solver for $P_{kn}^{(g)}$ as in Definition 1.1. In the first phase, the algorithm $C_1(\rho)$ sequentially interacts in k rounds with $P_{kn}^{(g)}(\pi^{(k)})$. In the i -th round $C_1(\rho)$ interacts with $P_n^{(1)}(\pi_i)$, and as the result $P_n^{(1)}(\pi_i)$ generates circuits Γ_V^i, Γ_H^i . Finally, after k rounds $P_{kn}^{(g)}(\pi^{(k)})$ outputs a verification circuit

$$\Gamma_V^{(g)}(q, y_1, \dots, y_k) := g(\Gamma_V^1(q, y_1), \dots, \Gamma_V^k(q, y_k))$$

and a hint circuit

$$\Gamma_H^{(k)}(q) := (\Gamma_H^1(q), \dots, \Gamma_H^k(q)).$$

If it is clear from a context, we omit the parameter n , and write $P(\pi)$ instead of $P_n(\pi)$ where $\pi \in \{0, 1\}^n$.

A verification query (q, y) of a solver C for which a hint query on this q has been asked before can not be a verification query that succeeds. Therefore, without loss of generality, we make the assumption that C does not ask verification queries on q for which a hint query has been asked before. Furthermore, we assume that once C asked a verification query that succeeds, it does not ask any further hint or verification queries.

Experiment $Success^{P,C}(\pi, \rho)$

Oracle: A problem poser P , a solver $C = (C_1, C_2)$ for P .

Input: Bitstrings $\pi \in \{0, 1\}^n$, $\rho \in \{0, 1\}^*$.

Output: A bit $b \in \{0, 1\}$.

```

run  $\langle P(\pi), C_1(\rho) \rangle$ 
       $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$ 
       $x := \langle P(\pi), C_1(\rho) \rangle_{trans}$ 

run  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$ 
      if  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$  asks a verification query  $(q, y)$  such that  $\Gamma_V(q, y) = 1$  then
        return 1
return 0

```

We define the *success probability* of C in solving a puzzle defined by P as

$$\Pr_{\pi, \rho}[Success^{P,C}(\pi, \rho) = 1]. \quad (0.0.1)$$

Furthermore, we say that C succeeds for π, ρ if $Success^{P,C}(\pi, \rho) = 1$.

Theorem 1.3 (Security amplification for a dynamic weakly verifiable puzzle.) *Let $P_n^{(1)}$ be a fixed problem poser as in Definition 1.1, and $P_{kn}^{(g)}$ a poser for the k -wise direct product of $P_n^{(1)}$. Furthermore, let C be a problem solver for $P_{kn}^{(g)}$ asking at most h hint queries and v verification queries. There exists a probabilistic algorithm Gen with oracle access to a solver circuit C , a monotone function $g : \{0, 1\}^k \rightarrow \{0, 1\}$ and problem posers $P_n^{(1)}, P_{kn}^{(g)}$. Additionally, Gen takes as input parameters $\varepsilon, \delta, n, k, h, v$ and outputs a solver circuit D for $P_n^{(1)}$ such that the following holds:*

If C is such that

$$\Pr_{\substack{\pi^{(k)} \in \{0,1\}^{kn} \\ \rho \in \{0,1\}^*}} \left[Success^{P_{kn}^{(g)}, C}(\pi^{(k)}, \rho) = 1 \right] \geq 16(h + v) \left(\Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon \right)$$

then D satisfies almost surely

$$\Pr_{\substack{\pi \in \{0,1\}^n \\ \rho \in \{0,1\}^*}} \left[Success^{P_n^{(1)}, D}(\pi, \rho) = 1 \right] \geq (\delta + \frac{\varepsilon}{6k}).$$

Additionally, D requires oracle access to $g, P_n^{(1)}, C$, and asks at most $\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})h$ hint queries and one verification query. Finally, $Size(D) \leq Size(C) \cdot \frac{6k}{\varepsilon}$ and $Time(Gen) = poly(k, \frac{1}{\varepsilon}, n, v, h)$.

Let $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$, the idea is to partition Q such that the set of preimages of 0 for $hash$ contains $q \in Q$ on which C is not allowed to ask hint queries, and the first successful verification query (q, y) of C is such that $hash(q) = 0$. Therefore, if C makes a verification query (q, y) such that $hash(q) = 0$, then we know that no hint query is ever asked on this q .

We denote the i -th query of C by q_i if it is a hint query, and by (q_i, y_i) if it is a verification query. We define now an experiment *CanonicalSuccess* in which we partition Q using a function $hash$. We say that a solver circuit *succeeds* in the experiment *CanonicalSuccess* if it asks a successful verification query (q_j, y_j) such that $hash(q_j) = 0$, and no hint query q_i is asked before (q_j, y_j) such that $hash(q_i) = 0$.

Experiment $\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho)$

Oracle: A problem poser P , a solver circuit $C = (C_1, C_2)$ for P ,
a function $\text{hash} : Q \rightarrow \{0, \dots, 2(h+v) - 1\}$.

Input: Bitstrings $\pi \in \{0, 1\}^n$, $\rho \in \{0, 1\}^*$.

Output: A bit $b \in \{0, 1\}$.

```

run  $\langle P(\pi), C_1(\rho) \rangle$ 
       $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$ 
       $x := \langle P(\pi), C_1(\rho) \rangle_{\text{trans}}$ 

run  $C_2^{\Gamma_V, \Gamma_H}(x, \rho)$ 
      if  $C_2$  does not succeed for any verification query then
        return 0
      Let  $(q_j, y_j)$  be the first verification query of  $C_2$  such that  $\Gamma_V(q_j, y_j) = 1$ .

if  $(\forall i < j : \text{hash}(q_i) \neq 0)$  and  $(\text{hash}(q_j) = 0)$  then
  return 1
else
  return 0

```

We define the *canonical success probability* of a solver C for P with respect to a function hash as

$$\Pr_{\pi, \rho}[\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1]. \quad (0.0.2)$$

For fixed hash and a problem poser P a *canonical success* of C for π, ρ is a situation where $\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1$.

Let \mathcal{H} be the family of pairwise independent functions $Q \rightarrow \{0, 1, \dots, 2(h+v) - 1\}$. We write $\text{hash} \leftarrow \mathcal{H}$ to denote that hash is chosen from \mathcal{H} uniformly at random. We show that if a solver circuit C for P often succeeds in the experiment *Success*, then there exists a function $\text{hash} \in \mathcal{H}$ such that C also often succeeds in the experiment *CanonicalSuccess*.¹

Lemma 1.4 (Success probability in solving DWVP with respect to a function hash.)
For fixed P let C be a solver for P with success probability at least γ , asking at most h hint queries and v verification queries. There exists a probabilistic algorithm *FindHash* that takes as input: parameters γ, n , the number of verification queries v and hint queries h , and has oracle access to C and P . Furthermore, *FindHash* runs in time $\text{poly}(h, v, \frac{1}{\gamma}, n)$, and with high probability outputs a function $\text{hash} \in \mathcal{H}$ such that the canonical success probability of C with respect to hash is at least $\frac{\gamma}{16(h+v)}$.

Proof. We fix a problem poser P and a solver C for P in the whole proof of Lemma 1.4. For all $k, l \in \{1, \dots, (h+v)\}$ and $\alpha, \beta \in \{0, 1, \dots, 2(h+v) - 1\}$ by the pairwise independence property of \mathcal{H} , we have

$$\forall q_k, q_l \in Q, q_k \neq q_l : \Pr_{\text{hash} \leftarrow \mathcal{H}}[\text{hash}(q_k) = \alpha \mid \text{hash}(q_l) = \beta] = \Pr_{\text{hash} \leftarrow \mathcal{H}}[\text{hash}(q_k) = \alpha] = \frac{1}{2(h+v)}. \quad (0.0.3)$$

Let $\mathcal{P}_{\text{Success}}$ be a set containing all (π, ρ) for which $\text{Success}^{P,C}(\pi, \rho) = 1$. We fix $(\pi^*, \rho^*) \in \mathcal{P}_{\text{Success}}$, and are interested in the probability over a choice of function hash of the event

¹It is possible to implement a random function hash efficiently by for example building its function table on the fly.

$\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi^*, \rho^*) = 1$. Let (q_j, y_j) denote the first query such that $\Gamma_V(q_j, y_j) = 1$. We have

$$\begin{aligned}
& \Pr_{\text{hash} \leftarrow \mathcal{H}} [\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi^*, \rho^*) = 1] \\
&= \Pr_{\text{hash} \leftarrow \mathcal{H}} [\text{hash}(q_j) = 0 \wedge (\forall i < j : \text{hash}(q_i) \neq 0)] \\
&= \Pr_{\text{hash} \leftarrow \mathcal{H}} [\forall i < j : \text{hash}(q_i) \neq 0 \mid \text{hash}(q_j) = 0] \Pr_{\text{hash} \leftarrow \mathcal{H}} [\text{hash}(q_j) = 0] \\
&\stackrel{(0.0.3)}{=} \frac{1}{2(h+v)} \left(1 - \Pr_{\text{hash} \leftarrow \mathcal{H}} [\exists i < j : \text{hash}(q_i) = 0 \mid \text{hash}(q_j) = 0] \right) \\
&\stackrel{(*)}{\geq} \frac{1}{2(h+v)} \left(1 - \sum_{i < j} \Pr_{\text{hash} \leftarrow \mathcal{H}} [\text{hash}(q_i) = 0 \mid \text{hash}(q_j) = 0] \right) \\
&\stackrel{(0.0.3)}{=} \frac{1}{2(h+v)} \left(1 - \sum_{i < j} \Pr_{\text{hash} \leftarrow \mathcal{H}} [\text{hash}(q_i) = 0] \right) \\
&\stackrel{(0.0.3)}{\geq} \frac{1}{4(h+v)}. \tag{0.0.4}
\end{aligned}$$

Where in $(*)$ we used the union bound. Let us denote the set of those (π, ρ) for which $\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1$ by $\mathcal{P}_{\text{Canonical}}$. If for π, ρ the circuit C succeeds canonically, then for the same π, ρ we also have $\text{Success}^{P,C}(\pi, \rho) = 1$. Hence, $\mathcal{P}_{\text{Canonical}} \subseteq \mathcal{P}_{\text{Success}}$, and we conclude

$$\begin{aligned}
& \Pr_{\substack{\text{hash} \leftarrow \mathcal{H} \\ \pi, \rho}} [\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1] \\
&= \Pr_{\substack{\text{hash} \leftarrow \mathcal{H} \\ \pi, \rho}} [\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}}] \Pr_{\pi, \rho} [(\pi, \rho) \in \mathcal{P}_{\text{Success}}] \\
&\quad + \Pr_{\substack{\text{hash} \leftarrow \mathcal{H} \\ \pi, \rho}} [\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1 \mid (\pi, \rho) \notin \mathcal{P}_{\text{Success}}] \Pr_{\pi, \rho} [(\pi, \rho) \notin \mathcal{P}_{\text{Success}}] \\
&= \Pr_{\substack{\text{hash} \leftarrow \mathcal{H} \\ \pi, \rho}} [\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}}] \Pr_{\pi, \rho} [(\pi, \rho) \in \mathcal{P}_{\text{Success}}] \\
&\geq \Pr_{\substack{\text{hash} \leftarrow \mathcal{H} \\ \pi, \rho}} [\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1 \mid (\pi, \rho) \in \mathcal{P}_{\text{Success}}] \cdot \gamma \\
&= \mathbb{E}_{(\pi, \rho) \in \mathcal{P}_{\text{Success}}} \left[\Pr_{\text{hash} \leftarrow \mathcal{H}} [\text{CanonicalSuccess}^{P,C,\text{hash}}(\pi, \rho) = 1] \right] \cdot \gamma \\
&\stackrel{(0.0.4)}{\geq} \frac{\gamma}{4(h+v)} \tag{0.0.5}
\end{aligned}$$

Algorithm FindHash(γ, n, h, v)

Oracle: A problem poser P , a solver circuit C for P .

Input: Parameters γ, n . The number of h hint and v verification queries.

Output: A function $\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h+v) - 1\}$.

for $i := 1$ **to** $32n(h+v)^2/\gamma^2$ **do:**

$\text{hash} \leftarrow \mathcal{H}$

$\text{count} := 0$

for $j := 1$ **to** $32n(h+v)^2/\gamma^2$ **do:**

```

     $\pi \xleftarrow{\$} \{0, 1\}^n$ 
     $\rho \xleftarrow{\$} \{0, 1\}^*$ 
    if  $\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1$  then
         $count := count + 1$ 
    if  $count \geq \frac{\gamma}{12(h+v)} \frac{32(h+v)^2}{\gamma^2} n$  then
        return  $hash$ 
return  $\perp$ 

```

We show that FindHash chooses $hash \in \mathcal{H}$ such that the canonical success probability of C with respect to $hash$ is at least $\frac{\gamma}{16(h+v)}$ almost surely. Let \mathcal{H}_{Good} denote a family of functions $hash \in \mathcal{H}$ for which

$$\Pr_{\pi, \rho} \left[\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \right] \geq \frac{\gamma}{8(h+v)}, \quad (0.0.6)$$

and \mathcal{H}_{Bad} be the family of functions $hash \in \mathcal{H}$ such that

$$\Pr_{\pi, \rho} \left[\text{CanonicalSuccess}^{P,C,hash}(\pi, \rho) = 1 \right] \leq \frac{\gamma}{16(h+v)}. \quad (0.0.7)$$

Let N denote the number of iterations of the inner loop of FindHash. For a fixed $hash$, we define independent, identically distributed binary random variables X_1, \dots, X_N such that

$$X_i = \begin{cases} 1 & \text{if in the } i\text{-th iteration of the inner loop } count \text{ is increased} \\ 0 & \text{otherwise.} \end{cases}$$

We show now that FindHash is unlikely to return $hash \in \mathcal{H}_{Bad}$. For $hash \in \mathcal{H}_{Bad}$ by (0.0.7) we have $\mathbb{E}_{\pi, \rho}[X_i] \leq \frac{\gamma}{16(h+v)}$. Therefore, for any fixed $hash \in \mathcal{H}_{Bad}$ using the Chernoff bound we get ²

$$\Pr_{\pi, \rho} \left[\frac{1}{N} \sum_{i=1}^N X_i \geq \frac{\gamma}{12(h+v)} \right] \leq \Pr_{\pi, \rho} \left[\frac{1}{N} \sum_{i=1}^N X_i \geq (1 + \frac{1}{3}) \mathbb{E}[X_i] \right] \leq e^{-\frac{\gamma}{16(h+v)} N/27} \leq e^{-\frac{2}{27} \frac{(h+v)}{\gamma} n} \leq e^{-\frac{2}{27} n}.$$

The probability that $hash \in \mathcal{H}_{Good}$, when picked, is not returned amounts

$$\Pr_{\pi, \rho} \left[\frac{1}{N} \sum_{i=1}^N X_i \leq \frac{\gamma}{12(h+v)} \right] \leq \Pr_{\pi, \rho} \left[\frac{1}{N} \sum_{i=1}^N X_i \leq (1 - \frac{1}{3}) \mathbb{E}[X_i] \right] \leq e^{-\frac{\gamma}{8(h+v)} N/18} = e^{-\frac{2}{9} \frac{(h+v)}{\gamma} n} \leq e^{-\frac{2}{9} n},$$

where we once more used the Chernoff bound. We show now that the probability of picking $hash \in \mathcal{H}_{Good}$ is at least $\frac{\gamma}{8(h+v)}$. We prove this statement by contradiction. Let us assume that

$$\Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] < \frac{\gamma}{8(h+v)}. \quad (0.0.8)$$

²For independent, identically distributed binary random variables $X = \sum_{i=1}^N X_i$ and $0 < \delta \leq 1$ we use the Chernoff bounds in the form $\Pr[X \geq (1 + \delta)\mathbb{E}[X]] \leq e^{-\mathbb{E}[X]\delta^2/3}$ and $\Pr[X \leq (1 - \delta)\mathbb{E}[X]] \leq e^{-\mathbb{E}[X]\delta^2/2}$.

We have

$$\begin{aligned}
& \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1] \\
&= \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \in \mathcal{H}_{Good}] \Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] \\
&\quad + \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \notin \mathcal{H}_{Good}] \Pr_{hash \leftarrow \mathcal{H}} [hash \notin \mathcal{H}_{Good}] \\
&\leq \Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] + \Pr_{\substack{hash \leftarrow \mathcal{H} \\ \pi, \rho}} [CanonicalSuccess^{P,C,hash}(\pi, \rho) = 1 \mid hash \notin \mathcal{H}_{Good}] \\
&\stackrel{(0.0.6)}{<} \stackrel{(0.0.8)}{<} \frac{\gamma}{8(h+v)} + \frac{\gamma}{8(h+v)} = \frac{\gamma}{4(h+v)},
\end{aligned}$$

but this contradicts (0.0.5). Therefore, we know that the probability of choosing a $hash \in \mathcal{H}_{Good}$ amounts at least $\frac{\gamma}{8(h+v)}$ where the probability is taken over a choice of $hash$.

We show that FindHash picks in one of its iteration $hash \in \mathcal{H}_{Good}$ almost surely. Let K be the number of iterations of the outer loop of FindHash and Y_i be a random variable for the event that in the i -th iteration of the outer loop $hash \notin \mathcal{H}_{Good}$ is picked. We conclude using

$\Pr_{hash \leftarrow \mathcal{H}} [hash \in \mathcal{H}_{Good}] \geq \frac{\gamma}{8(h+v)}$ and $K \leq \frac{32(h+v)^2}{\gamma^2} n$ that

$$\Pr_{hash \leftarrow \mathcal{H}} \left[\bigcap_{1 \leq i \leq K} Y_i \right] \leq \left(1 - \frac{\gamma}{8(h+v)} \right)^{\frac{32(h+v)^2}{\gamma^2} n} \leq e^{-\frac{\gamma}{8(h+v)} \frac{32(h+v)^2}{\gamma^2} n} \leq e^{-\frac{4(h+v)}{\gamma} n} \leq e^{-n}. \quad \square$$

If we want to answer hint and verification queries of C_2 by ourselves we write $C_2^{(\cdot, \cdot)}$ to stress that C_2 does not obtain direct access to hint and verification circuits.

Circuit $\tilde{C}_2^{\Gamma_H, C_2, hash}(x, \rho)$

Oracle: A hint circuit Γ_H , a circuit C_2 ,
a function $hash : Q \rightarrow \{0, 1, \dots, 2(h+v) - 1\}$.

Input: Bitstrings $x \in \{0, 1\}^*$, $\rho \in \{0, 1\}^*$.

Output: A pair (q, y) .

```

run  $C_2^{(\cdot, \cdot)}(x, \rho)$ 
  if  $C_2^{(\cdot, \cdot)}(x, \rho)$  asks a hint query on  $q$  then
    if  $hash(q) = 0$  then
      return  $\perp$ 
    else
      answer the query of  $C_2^{(\cdot, \cdot)}(x, \rho)$  using  $\Gamma_H(q)$ 

  if  $C_2^{(\cdot, \cdot)}(x, \rho)$  asks a verification query  $(q, y)$  then
    if  $hash(q) = 0$  then
      return  $(q, y)$ 
    else
      answer the verification query of  $C_2^{(\cdot, \cdot)}(x, \rho)$  with 0

return  $\perp$ 

```

Given $C = (C_1, C_2)$ we define a circuit $\tilde{C} = (C_1, \tilde{C}_2)$. Every hint query q asked by \tilde{C} is such that $hash(q) \neq 0$. Furthermore, \tilde{C} asks no verification queries, instead it returns \perp or (q, y) such that $hash(q) = 0$.

We say that for a fixed π , ρ , *hash* the circuit \tilde{C} *succeeds* if for $x := \langle P(\pi), C_1(\rho) \rangle_{\text{trans}}$, $(\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P$, we have

$$\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, \text{hash}}(x, \rho)) = 1.$$

Lemma 1.5 *For fixed P, C and *hash* the following statement is true*

$$\Pr_{\pi, \rho}[\text{CanonicalSuccess}^{P, C, \text{hash}}(\pi, \rho) = 1] \leq \Pr_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}}[\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, \text{hash}}(x, \rho)) = 1]$$

Proof. If for some fixed π , ρ and *hash* the circuit C succeeds canonically, then for the same π , ρ and *hash* also \tilde{C} succeeds. Using this observation, we conclude that

$$\begin{aligned} \Pr_{\pi, \rho}[\text{CanonicalSuccess}^{P, C, \text{hash}}(\pi, \rho) = 1] &= \mathbb{E}_{\pi, \rho}[\text{CanonicalSuccess}^{P, C, \text{hash}}(\pi, \rho) = 1] \\ &\leq \mathbb{E}_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}}[\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, \text{hash}}(x, \rho)) = 1] \\ &= \Pr_{\substack{\pi, \rho \\ x := \langle P(\pi), C_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P(\pi), C_1(\rho) \rangle_P}}[\Gamma_V(\tilde{C}_2^{\Gamma_H, C_2, \text{hash}}(x, \rho)) = 1] \quad \square \end{aligned}$$

Lemma 1.6 (Security amplification of a dynamic weakly verifiable puzzle with respect to hash.) *For fixed $P_n^{(1)}$ there exists an algorithm Gen that takes as input parameters ε, δ , n , k , has oracle access to $P_n^{(1)}$, $P_{kn}^{(g)}$, \tilde{C} , functions $\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h + v - 1)\}$, $g : \{0, 1\}^k \rightarrow \{0, 1\}$, and outputs a circuit $D := (D_1, D_2)$ such that the following holds: If $\tilde{C} := (C_1, \tilde{C}_2)$ has oracle access to *hash* and a solver circuit $C := (C_1, C_2)$ for $P_{kn}^{(g)}$, which asks at most h hint queries and v verification queries, is such that*

$$\Pr_{\substack{\pi^{(k)} \in \{0, 1\}^{kn}, \rho \in \{0, 1\}^* \\ x := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_H^{(k)}, \Gamma_V^{(g)}) := \langle P^{(g)}(\pi^{(k)}), C_1(\rho) \rangle_{P^{(g)}}}}[\Gamma_V^{(g)}(\tilde{C}_2^{\Gamma_H^{(k)}, C_2, \text{hash}}(x, \rho)) = 1] \geq \Pr_{u \leftarrow \mu_\delta^k}[g(u) = 1] + \varepsilon,$$

then D satisfies almost surely

$$\Pr_{\substack{\pi \in \{0, 1\}^n, \rho \in \{0, 1\}^* \\ x := \langle P^{(1)}(\pi), D_1^{\tilde{C}}(\rho) \rangle_{\text{trans}} \\ (\Gamma_H, \Gamma_V) := \langle P^{(1)}(\pi), D_1^{P^{(1)}, \tilde{C}}(\rho) \rangle_{P^{(1)}}}}[\Gamma_V(D_2^{P^{(1)}, P^{(g)}, \tilde{C}, \text{hash}, g, \Gamma_H}(x, \rho)) = 1] \geq (\delta + \frac{\varepsilon}{6k}).$$

*Furthermore, D has oracle access to a hint circuit, $P^{(1)}$, $P^{(g)}$, \tilde{C} , *hash*, g , and asks at most $\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})h$ hint queries and no verification queries. Finally, $\text{Size}(D) \leq \text{Size}(C) \frac{6k}{\varepsilon}$ and $\text{Time}(\text{Gen}) = \text{poly}(k, \frac{1}{\varepsilon}, n, v, h)$.*

Before proving Lemma 1.6 we define additional algorithms that are later used by Gen . First, we are interested in the probability that for $u \leftarrow \mu_\delta^k$ and a bit $b \in \{0, 1\}$ the function g with the first input bit set to b takes value 1. The estimate of this probability is calculated by the algorithm *EstimateFunctionProbability*.

Algorithm: EstimateFunctionProbability^g($b, k, \varepsilon, \delta, n$)

Oracle: A function $g : \{0, 1\}^k \rightarrow \{0, 1\}$.

Input: A bit $b \in \{0, 1\}$, parameters $k, \varepsilon, \delta, n$.

Output: An estimate \tilde{g} of $\Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1]$.

for $i := 1$ **to** $\frac{64^2}{\varepsilon^2}n$ **do**:
 $u \leftarrow \mu_\delta^k$
 $g_i := g(b, u_2, \dots, u_k)$
return $\frac{\varepsilon^2}{64^2 n} \sum_{i=1}^{\frac{64^2}{\varepsilon^2}n} g_i$

Lemma 1.7 *The algorithm **EstimateFunctionProbability^g**($b, k, \varepsilon, \delta$) outputs an estimate \tilde{g} of $\Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1]$ where $b \in \{0, 1\}$ such that $|\tilde{g} - \Pr_{u \leftarrow \mu_\delta^k}[g(b, u_2, \dots, u_k) = 1]| \leq \frac{\varepsilon}{8k}$ almost surely.*

Proof. We define independent, identically distributed binary random variables $K_1, K_2, \dots, K_{\frac{64k^2}{\varepsilon^2}n}$ such that for each $1 \leq i \leq \frac{64k^2}{\varepsilon^2}n$ the random variable K_i takes value g_i . We use the Chernoff bound to obtain ³

$$\Pr \left[\left| \left(\frac{\varepsilon^2}{64k^2 n} \sum_{i=1}^{\frac{64k^2}{\varepsilon^2}n} K_i \right) - \mathbb{E}[K_i] \right| \geq \frac{\varepsilon}{8k} \right] \leq 2 \cdot e^{-n/3}. \quad \square$$

The next algorithm **EvaluatePuzzles^{P⁽¹⁾, P^(g), \tilde{C} , hash}**($\pi^{(k)}, \rho, n, k$) evaluates which of k puzzles of the k -wise direct product defined by $P^{(g)}$ are solved successfully by $\tilde{C}(\rho) := (C_1, \tilde{C}_2)(\rho)$. To decide whether the i -th puzzle of the k -wise direct product is solved successfully we need to gain access to the verification oracle for the puzzle generated in the i -th round of the interaction between $P^{(g)}$ and \tilde{C} . Therefore, in the algorithm **EvaluatePuzzles**, we use $P^{(1)}$, and invoke it k times to simulate the interaction with $C_1(\rho)$. Let us introduce some additional notation. We denote by $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle^i$ the execution of the i -th round of the simulation, and by $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{P^{(1)}}^i$ the output of $P^{(1)}(\pi_i)$ in the i -th round. Furthermore, we write $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{trans}^i$ to denote a transcript of communication in the i -th round.

To make the notation easier in the code excerpts of circuits C_2 , D_2 and *EvaluatePuzzles* we omit some oracle signatures writing for example $\tilde{C}_2^{\Gamma_H^{(k)}, hash}$ instead of $\tilde{C}_2^{\Gamma_H^{(k)}, C, hash}$ where the access to oracle circuit C is omitted. We make sure that it is clear from a context which circuit C is used by \tilde{C}_2 .

Algorithm: EvaluatePuzzles^{P⁽¹⁾, \tilde{C} , hash}($\pi^{(k)}, \rho, n, k$)

Oracle: Problem posers $P^{(1)}$, a solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$,
a function $hash : Q \rightarrow \{0, 1, \dots, 2(h+v)-1\}$.

Input: Bitstrings $\pi^{(k)} \in \{0, 1\}^{kn}$, $\rho \in \{0, 1\}^*$, parameters n, k .

Output: A tuple $(c_1, \dots, c_k) \in \{0, 1\}^k$.

for $i := 1$ **to** k **do**: //simulate k rounds of interaction
 $(\Gamma_V^i, \Gamma_H^i) := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{P^{(1)}}^i$

³For independent Bernoulli distributed random variables X_1, \dots, X_n with $X := \sum_{i=1}^n X_i$ and $0 \leq \delta \leq 1$ we use the Chernoff bound in the form $\Pr[|X - \mathbb{E}[X]| \geq \delta \mathbb{E}[X]] \leq 2e^{-\mathbb{E}[X]\delta^2/3}$.


```


$$x_i := \langle P^{(1)}(\pi_i), C_1(\rho) \rangle_{\text{trans}}^i$$


$$x := (x_1, \dots, x_k)$$


$$\Gamma_H^{(k)} := (\Gamma_H^1, \dots, \Gamma_H^k)$$


$$(q, y_1, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, \text{hash}}(x, \rho)$$


$$(c_1, \dots, c_k) := (\Gamma_V^1(q, y_1), \dots, \Gamma_V^k(q, y_k))$$

return  $(c_1, \dots, c_k)$ 

```

All puzzles used by the algorithm `EvalutePuzzles` are generated internally. Thus, the algorithm can answer itself all queries of \tilde{C}_2 to the hint oracle.

We are interested in the success probability of \tilde{C} with the bitstring π_1 fixed to π^* when the fact whether \tilde{C} succeeds in solving the first puzzle defined by $P^{(1)}(\pi_1)$ is neglected, and instead a bit $b \in \{0, 1\}$ is used. More formally, we define the surplus $S_{\pi^*, b}$ as

$$S_{\pi^*, b} = \Pr_{\pi^{(k)}, \rho} [g(b, c_2, \dots, c_k) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_\delta^k} [g(b, u_2, \dots, u_k) = 1]. \quad (0.0.9)$$

The algorithm `EstimateSurplus` returns an estimate $\tilde{S}_{\pi^*, b}$ for $S_{\pi^*, b}$.

Algorithm `EstimateSurplus` ^{$P^{(1)}, P^{(g)}, \tilde{C}, g, \text{hash}$} ($\pi^*, b, k, \varepsilon, \delta, n$)

Oracle: Problem posers $P^{(1)}, P^{(g)}$, a circuit \tilde{C} , a function $g : \{0, 1\}^k \rightarrow \{0, 1\}$
a function $\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$.

Input: A bitstring $\pi^* \in \{0, 1\}^n$, a bit $b \in \{0, 1\}$, parameters $k, \varepsilon, \delta, n$.

Output: An estimate $\tilde{S}_{\pi^*, b}$ for $S_{\pi^*, b}$.

for $i := 1$ **to** $\frac{64k^2}{\varepsilon^2}n$ **do:**

$(\pi_2, \dots, \pi_k) \xleftarrow{\$} \{0, 1\}^{(k-1)n}$

$\rho \xleftarrow{\$} \{0, 1\}^*$

$(c_1, \dots, c_k) := \text{EvalutePuzzles}^{P^{(1)}, P^{(g)}, \tilde{C}, \text{hash}}((\pi^*, \pi_2, \dots, \pi_k), \rho)$

$\tilde{s}_{\pi^*, b}^i := g(b, c_2, \dots, c_k)$

$\tilde{g}_b := \text{EstimateFunctionProbability}^g(b, k, \varepsilon, \delta, n)$

return $\left(\frac{\varepsilon^2}{64k^2n} \sum_{i=1}^{\frac{64k^2}{\varepsilon^2}n} \tilde{s}_{\pi^*, b}^i \right) - \tilde{g}_b$

Lemma 1.8 *The estimate $\tilde{S}_{\pi^*, b}$ returned by `EstimateSurplus` differs from $S_{\pi^*, b}$ by at most $\frac{\varepsilon}{4k}$ almost surely.*

Proof. We use the union bound and similar argument as in Lemma 1.7 which yields that

$\frac{\varepsilon^2}{64k^2n} \sum_{i=1}^{\frac{64k^2}{\varepsilon^2}n} \tilde{s}_{\pi^*, b}^i$ differs from $\mathbb{E}[g(b, c_2, \dots, c_k)]$ by at most $\frac{\varepsilon}{8k}$ almost surely. Together, with Lemma 1.7 we conclude that the surplus estimate returned by `EstimateSurplus` differs from $S_{\pi^*, b}$ by at most $\frac{\varepsilon}{4k}$ almost surely. \square

We define now the following circuit $C' = (C'_1, C'_2)$, which is a solver for a $(k - 1)$ -wise direct product of $P^{(1)}$.

Circuit $C'_1{}^{\tilde{C}, P^{(1)}}(\rho)$

Oracle: A solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$, a poser $P^{(1)}$.

Input: A bitstring $\rho \in \{0, 1\}^*$

Hard-coded: A bitstring $\pi^* \in \{0, 1\}^n$

Simulate $\langle P^{(1)}(\pi^*), C_1(\rho) \rangle^1$

Use $C_1(\rho)$ for the remaining $k - 1$ rounds of interaction.

Circuit $\tilde{C}_2^{\Gamma_H^{(k-1)}, \tilde{C}, hash}(x^{(k-1)}, \rho)$

Oracle: A hint oracle $\Gamma_H^{(k-1)} := (\Gamma_H^2, \dots, \Gamma_H^k)$, a solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$,
a function $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$

Input: A tuple $x^{(k-1)} := (x_2, \dots, x_k) \in \{0, 1\}^*$, a bitstring $\rho \in \{0, 1\}^*$

Hard-coded: A bitstring $\pi^* \in \{0, 1\}^n$

Simulate $\langle P^{(1)}(\pi^*), C_1(\rho) \rangle^1$

$(\Gamma_H^*, \Gamma_V^*) := \langle P^{(1)}(\pi^*), C_1(\rho) \rangle_{P^{(1)}}^1$

$x^* := \langle P^{(1)}(\pi^*), C_1(\rho) \rangle_{trans}^1$

$\Gamma_H^{(k)} := (\Gamma_H^*, \Gamma_H^2, \dots, \Gamma_H^k)$

$x^{(k)} := (x^*, x_2, \dots, x_k)$

$(q, y_1, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, hash}(x^{(k)}, \rho)$

return (q, y_2, \dots, y_k)

We are ready to define the solver circuit $D = (D_1, D_2)$ for $P^{(1)}$ and the algorithm Gen.

Circuit $D_1^{\tilde{C}}(\rho)$

Oracle: A solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$ for $P^{(g)}$.

Input: A tuple $\rho := (\tau, \sigma)$ where $\rho \in \{0, 1\}^*$ and $\sigma \in \{0, 1\}^*$.

Run the first round of interaction with a problem poser $\langle P^{(1)}, C_1(\tau) \rangle^1$.

Let $x^* := \langle P^{(1)}, C_1(\rho) \rangle_{trans}^1$.

Circuit $D_2^{P^{(1)}, P^{(g)}, \tilde{C}, hash, g, \Gamma_H^*}(x^*, \rho)$

Oracle: A poser $P^{(1)}$, a solver circuit $\tilde{C} = (C_1, \tilde{C}_2)$,
functions $hash : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$, $g : \{0, 1\}^k \rightarrow \{0, 1\}$,
a hint circuit Γ_H^* for $P^{(1)}$.

Input: A communication transcript $x^* \in \{0, 1\}^*$, a bitstring $\rho := (\tau, \sigma)$
where $\tau \in \{0, 1\}^*$ and $\sigma \in \{0, 1\}^*$

Output: A tuple (q, y^*) .

for at most $\frac{6k}{\epsilon} \log(\frac{6k}{\epsilon})$ iterations **do:**

$(\pi_2, \dots, \pi_k) \leftarrow$ read next $(k - 1) \cdot n$ bits from σ

for $i := 2$ **to** k **do:**

run $\langle P^{(1)}(\pi_i), C_1(\rho) \rangle^i$

$(\Gamma_V^i, \Gamma_H^i) := \langle P^{(1)}(\pi_i), C_1(\tau) \rangle_{P^{(1)}}^i$

$x_i := \langle P^{(1)}(\pi_i), C_1(\tau) \rangle_{trans}^i$

$\Gamma_H^{(k)}(q) := (\Gamma_H^*(q), \Gamma_H^2(q), \dots, \Gamma_H^k(q))$

$(q, y^*, y_2, \dots, y_k) := \tilde{C}_2^{\Gamma_H^{(k)}, hash}((x^*, x_2, \dots, x_k), \tau)$

```

 $(c_2, \dots, c_k) := (\Gamma_V^2(q, y_2), \dots, \Gamma_V^k(q, y_k))$ 
if  $g(1, c_2, \dots, c_k) = 1$  and  $g(0, c_2, \dots, c_k) = 0$  then
    return  $(q, y^*)$ 
return  $\perp$ 

```

Algorithm $\text{Gen}^{P^{(1)}, P^{(g)}, \tilde{C}, g, \text{hash}}(\varepsilon, \delta, n, v, h, k)$

Oracle: Posers $P^{(1)}, P^{(g)}$, a solver circuit \tilde{C} for $P^{(g)}$, functions $g : \{0, 1\}^k \rightarrow \{0, 1\}$,
 $\text{hash} : Q \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$.

Input: Parameters $\varepsilon, \delta, n, k$, the number of verification v and hint h queries.

Output: A circuit D .

for $i := 1$ **to** $\frac{6k}{\varepsilon}n$ **do:**

$\pi^* \xleftarrow{\$} \{0, 1\}^n$

$\tilde{S}_{\pi^*, 0} := \text{EstimateSurplus}^{P^{(1)}, P^{(g)}, \tilde{C}, g, \text{hash}}(\pi^*, 0, k, \varepsilon, \delta, n)$

$\tilde{S}_{\pi^*, 1} := \text{EstimateSurplus}^{P^{(1)}, P^{(g)}, \tilde{C}, g, \text{hash}}(\pi^*, 1, k, \varepsilon, \delta, n)$

if $\exists b \in \{0, 1\} : \tilde{S}_{\pi^*, b} \geq (1 - \frac{3}{4k})\varepsilon$ **then**

Let C'_1 have oracle access to \tilde{C} , and have hard-coded π^*

Let \tilde{C}'_2 have oracle access to \tilde{C} , and have hard-coded π^* .

$\tilde{C}' := (C'_1, \tilde{C}'_2)$

$g'(b_2, \dots, b_k) := g(b, b_2, \dots, b_k)$

return $\text{Gen}^{P^{(1)}, P^{(g)}, \tilde{C}', g', \text{hash}}(\varepsilon, \delta, n, v, h, k - 1)$

// all estimates are lower than $(1 - \frac{3}{4k})\varepsilon$

return $D^{P^{(1)}, P^{(g)}, \tilde{C}, \text{hash}, g}$

Proof (Lemma 1.6). First let us consider the case where $k = 1$. The function $g : \{0, 1\} \rightarrow \{0, 1\}$ is either the identity or a constant function. If g is the identity function, then the circuit D returned by Gen directly uses \tilde{C} to find a solution. From the assumptions of Lemma 1.6 we know that \tilde{C} succeeds with probability at least $\delta + \varepsilon$. Hence, D trivially satisfies the statement of Lemma 1.6. If g is a constant function the statement is vacuously true.

The general case is more involved. We distinguish two possibilities. If Gen manages to find in one of the iterations π^* such that an estimate $\tilde{S}_{\pi^*, b} \geq (1 - \frac{3}{4k})\varepsilon$, then we define a new monotone function $g'(b_2, \dots, b_k) := g(b, b_2, \dots, b_k)$ and a circuit $\tilde{C}' = (C'_1, \tilde{C}'_2)$ with oracle access to $\tilde{C} := (C_1, \tilde{C}_2)$, where C'_1 first internally simulates the interaction between C_1 and $P^{(1)}(\pi^*)$, and then use C_1 to interact with $P^{(g')}$. The circuit \tilde{C}'_2 uses \tilde{C} to obtain a solution (q, y_1, \dots, y_k) for the k -wise direct product with π_1 fixed to π^* , and returns (q, y_2, \dots, y_k) . We know that one of the surplus estimates $\tilde{S}_{\pi^*, b}$ is greater or equal $1 - \frac{3}{4k}\varepsilon$, and using Lemma 1.8 we conclude that $S_{\pi^*, b} \geq \tilde{S}_{\pi^*, b} - \frac{\varepsilon}{4k} \geq \varepsilon - \frac{\varepsilon}{k}$ almost surely. Therefore, the circuit \tilde{C}' succeeds in solving the $(k - 1)$ -wise direct product of puzzles with probability at least $\Pr_{u \leftarrow \mu_\delta^{k-1}}[g'(u_1, \dots, u_{k-1})] + \varepsilon$.

We see that in this case \tilde{C}' satisfies the conditions of Lemma 1.6 for the $(k - 1)$ -wise direct product of puzzles, and we recurse using g' and \tilde{C}' .

If all estimates are less than $(1 - \frac{3}{4k})\varepsilon$, then intuitively C does not succeeds on the remaining $k - 1$ puzzles with much higher probability than an algorithm that correctly solves each puzzle with probability δ . However, from the assumptions of Lemma 1.6 we know that on all k puzzles the success probability of \tilde{C} is higher. Therefore, it is likely that the first puzzle is correctly solved unusual often. It remains to prove that this intuition is indeed correct. Let

$\mathcal{G}_b := \{b_1, b_2, \dots, b_k : g(b, b_2, \dots, b_k) = 1\}$ then we have

$$\begin{aligned}\Pr_{u \leftarrow \mu_\delta^k} [u \in G_b] &= \Pr_{u \leftarrow \mu_\delta^k} [g(b, u_2, \dots, u_k) = 1] \\ \Pr_{\pi^{(k)}, \rho} [c \in G_b] &= \Pr_{\pi^{(k)}, \rho} [g(b, c_2, \dots, c_k) = 1].\end{aligned}\quad (0.0.10)$$

We fix π^* and use (0.0.9), (0.0.10) to obtain

$$\Pr_{u \leftarrow \mu_\delta^k} [u \in G_1] - \Pr_{u \leftarrow \mu_\delta^k} [u \in G_0] = \Pr_{\pi^{(k)}, \rho} [c \in G_1 \mid \pi_1 = \pi^*] - \Pr_{\pi^{(k)}, \rho} [c \in G_0 \mid \pi_1 = \pi^*] - (S_{\pi^*, 1} - S_{\pi^*, 0}) \quad (0.0.11)$$

Since g is monotone, we have that $\mathcal{G}_0 \subseteq \mathcal{G}_1$, and can write (0.0.11) as

$$\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0] = \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] - (S_{\pi^*, 1} - S_{\pi^*, 0}). \quad (0.0.12)$$

Still fixing $\pi_1 = \pi^*$ we multiply both sides of (0.0.12) by

$$\begin{aligned}\Pr_{\rho} [\Gamma_V(D_2(x, \rho)) = 1] / \Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0] \\ x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}}\end{aligned}$$

which yields

$$\begin{aligned}\Pr_{\rho} [\Gamma_V(D_2(x, \rho)) = 1] \\ x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}} \\ = \Pr_{\rho} [\Gamma_V(D_2(x, \rho)) = 1] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi = \pi^*] \frac{1}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \\ x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}} \\ - \Pr_{\rho} [\Gamma_V(D_2(x, \rho)) = 1] (S_{\pi^*, 1} - S_{\pi^*, 0}) \frac{1}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \\ x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}}\end{aligned} \quad (0.0.13)$$

We make use of the facts that $\Gamma_V(D(x, \rho)) = 1$ implies that $c_1 = 1$ and $D_2(x, \rho) \neq \perp$, and that the event $D_2(x, \rho) \neq \perp$ implies $c \in \mathcal{G}_1 \setminus \mathcal{G}_0$, which let us write the numerator of the first summand of (0.0.13) as

$$\begin{aligned}\Pr_{\rho} [\Gamma_V(D_2(x, \rho)) = 1] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \\ x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}} \\ = \Pr_{\rho} [D_2(x, \rho) \neq \perp] \Pr_{\pi^{(k)}, \rho} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \\ x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}}\end{aligned} \quad (0.0.14)$$

Now we consider two cases: if $\Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \leq \frac{\varepsilon}{6k}$ then

$$\Pr_{\pi^{(k)}} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \leq \frac{\varepsilon}{6k}, \quad (0.0.15)$$

for $\Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] > \frac{\varepsilon}{6k}$ the circuit D_2 outputs \perp if and only if it fails in all $\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})$ iterations to find $\pi^{(k)}$ such that $g(1, c_2, \dots, c_k) = 1 \wedge g(0, c_2, \dots, c_k) = 0$ (i.e. in none of the iterations $c \in \mathcal{G}_1 \setminus \mathcal{G}_0$) which happens with probability

$$\Pr_{\rho} [D_2(x, \rho) = \perp] \leq (1 - \frac{\varepsilon}{6k})^{\frac{6k}{\varepsilon} \log(\frac{6k}{\varepsilon})} \leq \frac{\varepsilon}{6k}. \quad (0.0.16)$$

We conclude that in both cases:

$$\begin{aligned}
& \Pr_{x:=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}}} [D_2(x, \rho) \neq \perp] \Pr_{\pi^{(k)}, \rho} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] \\
& \geq \Pr_{\pi^{(k)}, \rho} [c_1 = 1 \mid c \in \mathcal{G}_1 \setminus \mathcal{G}_0, \pi_1 = \pi^*] \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_1 \setminus \mathcal{G}_0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\
& = \Pr_{\pi^{(k)}, \rho} [c_1 = 1 \wedge c \in \mathcal{G}_0 \setminus \mathcal{G}_1 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\
& = \Pr_{\pi^{(k)}, \rho} [g(c_1, c_2, \dots, c_k) = 1 \wedge g(0, c_2, \dots, c_k) = 0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\
& = \Pr_{\pi^{(k)}, \rho} [g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{\pi^{(k)}, \rho} [c \in \mathcal{G}_0 \mid \pi_1 = \pi^*] - \frac{\varepsilon}{6k} \\
& \stackrel{(0.0.9)}{=} \Pr_{\pi^{(k)}, \rho} [g(c_1, c_2, \dots, c_k) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_{\delta}^{(k)}} [u \in \mathcal{G}_0] - S_{\pi^*, 0} - \frac{\varepsilon}{6k}. \quad (0.0.17)
\end{aligned}$$

For the second summand of (0.0.13) we show that if we do not recurse, then the majority of the estimates is low almost surely. Let us assume that

$$\Pr_{\pi, \rho} \left[\left(S_{\pi, 0} \leq \left(1 - \frac{1}{2k}\right) \varepsilon \right) \wedge \left(S_{\pi, 1} \leq \left(1 - \frac{1}{2k}\right) \varepsilon \right) \right] < 1 - \frac{\varepsilon}{6k}, \quad (0.0.18)$$

then the algorithm recurses almost surely. Therefore, under the assumption that *Gen* does not recurse, we have with high probability

$$\Pr_{\pi, \rho} \left[\left(S_{\pi, 0} \leq \left(1 - \frac{1}{2k}\right) \varepsilon \right) \wedge \left(S_{\pi, 1} \leq \left(1 - \frac{1}{2k}\right) \varepsilon \right) \right] \geq 1 - \frac{\varepsilon}{6k}. \quad (0.0.19)$$

Let us define a set

$$\mathcal{W} = \left\{ \pi : \left(S_{\pi, 0} \leq \left(1 - \frac{1}{2k}\right) \varepsilon \right) \wedge \left(S_{\pi, 1} \leq \left(1 - \frac{1}{2k}\right) \varepsilon \right) \right\} \quad (0.0.20)$$

and use \mathcal{W}^c to denote the complement of \mathcal{W} . We bound the second summand in (0.0.13)

$$\begin{aligned}
& \mathbb{E}_{\pi^*} [S_{\pi^*, 0} + \Pr_{\substack{x:=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H):=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x, \rho)) = 1] (S_{\pi^*, 1} - S_{\pi^*, 0})] \\
& = \mathbb{E}_{\pi^* \in \mathcal{W}^c} [S_{\pi^*, 0} + \Pr_{\substack{x:=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H):=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x, \rho)) = 1] (S_{\pi^*, 1} - S_{\pi^*, 0})] \\
& \quad + \mathbb{E}_{\pi^* \in \mathcal{W}} [S_{\pi^*, 0} + \Pr_{\substack{x:=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H):=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x, \rho)) = 1] (S_{\pi^*, 1} - S_{\pi^*, 0})] \\
& \leq \frac{\varepsilon}{6k} + \mathbb{E}_{\pi^* \in \mathcal{W}^c} [S_{\pi^*, 0} + \Pr_{\substack{x:=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H):=\langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}}}} [\Gamma_V(D_2^{\tilde{C}}(x, \rho)) = 1] ((1 - \frac{1}{2k}) \varepsilon - S_{\pi^*, 0})] \\
& \leq \frac{\varepsilon}{6k} + 1 - \frac{\varepsilon}{2k} = 1 - \frac{\varepsilon}{3k}. \quad (0.0.21)
\end{aligned}$$

We observe that

$$\begin{aligned}
& \Pr_{u \leftarrow \mu_{\delta}^k} [g(u) = 1] = \Pr[u \in \mathcal{G}_0 \vee (u \in \mathcal{G}_1 \setminus \mathcal{G}_0 \wedge u_1 = 1)] \\
& = \Pr[u \in \mathcal{G}_0] + \Pr[u \in \mathcal{G}_1 \setminus \mathcal{G}_0] \Pr[u_1 = 1]. \quad (0.0.22)
\end{aligned}$$

Finally, we insert (0.0.17) and (0.0.21) into equation (0.0.13) and use (0.0.22) to obtain

$$\Pr_{\substack{\rho \\ x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x, \rho)) = 1] \geq \mathbb{E}_{\pi^*} \left[\frac{\Pr_{\pi^{(k)}, \rho} [g(c) = 1 \mid \pi_1 = \pi^*] - \Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_0] - (1 - \frac{1}{6k})\varepsilon}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \right].$$

From the assumptions of Lemma 1.6 we know that $\Pr_{\pi^{(k)}, \rho} [g(c) = 1] \geq \Pr_{u \leftarrow \mu_\delta^{(k)}} [g(u) = 1]$, thus we get

$$\begin{aligned} \Pr_{\substack{\rho \\ x := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{\text{trans}} \\ (\Gamma_V, \Gamma_H) := \langle P^{(1)}(\pi^*), D_1(\rho) \rangle_{P^{(1)}}}} [\Gamma_V(D_2(x, \rho)) = 1] &\geq \frac{\Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon + \Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_0] - (1 - \frac{1}{6k})\varepsilon}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \\ &\geq \frac{\varepsilon + \delta \Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0] - (1 - \frac{1}{6k})\varepsilon}{\Pr_{u \leftarrow \mu_\delta^k} [u \in \mathcal{G}_1 \setminus \mathcal{G}_0]} \geq \delta + \frac{\varepsilon}{6k} \end{aligned} \quad (0.0.23) \quad \square$$

Proof (Theorem 1.3). Let use first define following circuits.

Circuit $\tilde{D}_2^{D, P^{(1)}, P^{(g)}, \text{hash}, g, \Gamma_V}(x, \rho)$

Oracle: A circuit D , problem posers $P^{(1)}, P^{(g)}$,
function $\text{hash} : \mathcal{Q} \rightarrow \{0, 1, \dots, 2(h + v) - 1\}$, $g : \{0, 1\}^k \rightarrow \{0, 1\}$
a verification oracle Γ_V , a hint oracle Γ_H

Input: Bitstrings $x \in \{0, 1\}^*$, $\rho \in \{0, 1\}^*$

$(q, y) := D_2^{P^{(1)}, P^{(g)}, \tilde{C}, \text{hash}, g, \Gamma_H}(x, \rho)$

Make a verification query to Γ_V using (q, y)

Algorithm $\widetilde{\text{Gen}}^{P^{(1)}, P^{(g)}, g, C}(n, \varepsilon, \delta, k, h, v)$

Oracle: Problem posers $P^{(1)}, P^{(g)}$, a function $g : \{0, 1\}^k \rightarrow \{0, 1\}$,
a solver circuit C for $P^{(g)}$.

Input: Parameters $n, \varepsilon, \delta, k, h, v$.

$\text{hash} := \text{FindHash}((h + v)\varepsilon, n, h, v)$

Let $\tilde{C} = (C_1, \tilde{C}_2)$ be as in Lemma 1.5 with oracle access to C , hash .

$D := \text{Gen}^{P^{(1)}, P^{(g)}, \tilde{C}, \text{hash}, g}(\varepsilon, \delta, n, k)$

return $\tilde{D} := (D_1, \tilde{D}_2)$

We show that Theorem 1.3 follows from Lemma 1.4 and Lemma 1.6. We use the algorithm $\widetilde{\text{Gen}}$ to obtain a circuit $D := (D_1, D_2)$ and a function hash . Then, the circuit D uses \tilde{D} to find (q, y) . We will show that

$$\Pr_{\pi, \rho} \left[\text{Success}^{P^{(1)}, \tilde{D}}(\pi, \rho) = 1 \right] \geq \left(\delta + \frac{\varepsilon}{6k} \right).$$

For fixed $P^{(1)}$, g , $P^{(g)}$ given a solver circuit $C = (C_1, C_2)$ such that

$$\Pr_{\pi^{(k)}, \rho} \left[\text{Success}^{P^{(g)}, C}(\pi^{(k)}, \rho) = 1 \right] \geq 16(h + v) \left(\Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon \right)$$

we apply Lemma 1.4 to find a function *hash* such that

$$\Pr_{\pi^{(k)}, \rho} \left[\text{CanonicalSuccess}^{P^{(g)}, C, \text{hash}}(\pi^{(k)}, \rho) = 1 \right] \geq \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon.$$

By Lemma 1.5 we know that it is possible to create a circuit $\tilde{C} = (C_1, \tilde{C}_2)$ with oracle access to *hash* and C such that

$$\Pr_{\pi, \rho} \left[\Gamma_V^{(g)}(\tilde{C}_2^{\Gamma_H^{(k)}, C_2, \text{hash}}(x, \rho)) = 1 \right] \geq \Pr_{u \leftarrow \mu_\delta^k} [g(u) = 1] + \varepsilon.$$

$x := \langle P(\pi), C_1(\rho) \rangle_{trans}$
 $(\Gamma_V^{(g)}, \Gamma_H^{(k)}) := \langle P(\pi), C_1(\rho) \rangle_P$

Now, we apply Lemma 1.6 for the function *hash* and $\tilde{C} = (C_1, \tilde{C}_2)$ and obtain a circuit $D = (D_1, D_2)$ such that

$$\Pr_{\pi, \rho} \left[\Gamma_V(D_2(x, \rho)) = 1 \right] \geq (\delta + \frac{\varepsilon}{6k}). \quad (0.0.24)$$

$x := \langle P^{(1)}(\pi), D_1(\rho) \rangle_{trans}$
 $(\Gamma_H, \Gamma_V) := \langle P^{(1)}(\pi), D_1(\rho) \rangle_{P^{(1)}}$

□