SKS 45 Carbine

Tula / Izhevsk / Factory 26 / Zastava • Simonov 7.62x39mm Semi-Automatic Carbine (Soviet, Chinese Type 56, Yugo M59/66)

Manufacturer:	Tula / Izhevsk / Factory 26 / Zastava	**Category:**	Rifles & Carbines
Action Type:	Short-Stroke Gas Piston Tilting Bolt Semi-Auto	**Era / Service:**	Early Cold War (1945–1959+)
Calibers:	7.62x39mm Soviet	**Covered Models:**	Soviet SKS-45, Chinese Type 56, Yugoslavian M59/66 (Grenade Spigot), Romanian / East German SKS

KEY ARMORER TASKS & BENCH OPERATIONS

Core Procedures: Free-Floating Firing Pin Slam-Fire Check • Spring-Loaded Firing Pin Upgrade (Murray's) • Gas Tube Piston Cleanout • Yugo Gas Valve Leak Remediation • Trigger Group Disassembly

CRITICAL ARMORER TOLERANCES & SPECIFICATIONS

SPECIFICATION / CLEARANCE	ARMORER TOLERANCE & BENCH SPECIFICATION
SLAM FIRE WARNING	CRITICAL ARMORER DANGER: SKS firing pin is free-floating with triangular cross-section. If cosmolene or carbon gums the channel, the pin sticks forward, causing FULL AUTO SLAM FIRE when releasing bolt on a loaded round
SHAKE TEST	Shake stripped bolt back and forth; firing pin MUST rattle freely under own inertia like a metallic maraca. If it does not rattle, weapon is UNSAFE
YUGO GAS VALVE	Yugoslavian M59/66 features rotatable gas shutoff valve for grenade launcher; corroded valve creates gas leak leading to short stroking

IMMEDIATE ACTION & MALFUNCTION DIAGNOSTIC MATRIX

MALFUNCTION CONDITION	PROBABLE CAUSES	ARMORER BENCH REMEDY
Stoppage 1: Slam-Fire Runaway (Full-Auto Discharge on Bolt Release) **Dropping bolt onto loaded chamber causes weapon to immediately fire without touching trigger, or empty entire magazine**	• Dried cosmolene or hardened primer sealant gumming the triangular firing pin channel. • Bent firing pin wedged in protruding position.	**Immediate Action: DANGEROUS CONDITION. Keep muzzle downrange. Gunsmith Action: Push out firing pin retaining pin from bolt body. Extract firing pin. Soak channel in lacquer thinner. Install Murray's Gunsmithing spring-loaded firing pin conversion which prevents inertia strikes.**

CURATED BENCH VIDEO REFERENCES

PROCEDURE TITLE	INSTRUCTOR / CREATOR	TECHNICAL PROCEDURE SUMMARY
SKS 45 Complete Disassembly, Cosmoline Cleaning & Slam-Fire Fix	Iraqveteran8888 Bench	Complete teardown of the SKS rifle: removing the trigger group, stripping the bolt, cleaning the gas tube and piston, and fixing slam-fire hazards.