ARMORER'S BENCH TECHNICAL MANUAL

Savage Model 110 & Axis Series

Savage Arms • Barrel Nut Headspace System & AccuTrigger (.308 Win, 6.5 CM, .223, .30-06)

Manufacturer:	Savage Arms	**Category:**	Rifles & Carbines
Action Type:	Floating Bolt Head Push-Feed Bolt Action	**Era / Service:**	American Mass Precision Benchmark (1958–Present)
Calibers:	.308 Winchester, 6.5 Creedmoor, .30-06, .223 Remington, .300 Win Mag	**Covered Models:**	Model 110 Apex, Model 110 Tactical, 110 Ultralite, Savage Axis II, Model 10 / 12 Varmint

KEY ARMORER TASKS & BENCH OPERATIONS

Core Procedures: Barrel Lock Nut Headspacing (Go-Gauge & Savage Wrench) • Floating Bolt Head Interchangeability • AccuTrigger Return Spring Adjustment (1.5–4.5 lbs) • AccuStock Aluminum Rail Bedding • Bolt Lift Kit Installation

CRITICAL ARMORER TOLERANCES & SPECIFICATIONS

SPECIFICATION / CLEARANCE	ARMORER TOLERANCE & BENCH SPECIFICATION
BARREL NUT SYSTEM	Threaded barrel lock nut allows gunsmith to screw barrel into receiver against a GO-gauge and lock it at exact zero headspace with a spanner wrench (no lathe chamber reaming required)
FLOATING BOLT HEAD	Bolt head is pinned to body with slight lateral play, allowing bolt lugs to self-align 100% against receiver locking abutments
ACCUTRIGGER SAFETY	AccuRelease center blade prevents sear release if rifle is dropped or jarred
THREAD SIZES	Small shank (1.055" x 20 TPI) / Large shank (1.120" x 20 TPI on magnums and target actions)

IMMEDIATE ACTION & MALFUNCTION DIAGNOSTIC MATRIX

MALFUNCTION CONDITION	PROBABLE CAUSES	ARMORER BENCH REMEDY
Stoppage 1: AccuTrigger Locks Up (Rifle Cocked but Trigger Stiff) **Shooter pulls trigger blade from an angle, hear click, but gun does not fire; trigger is completely locked**	• User pulled outer trigger shoe without fully depressing the center AccuRelease blade. • AccuTrigger pull weight spring adjusted below minimum 1.5 lb threshold.	**Immediate Action: Lift bolt handle up and down to recock action, then pull straight back on center blade. Gunsmith Action: Use Savage trigger tool to increase spring tension 1/2 turn until sear stays engaged during aggressive bolt cycling.**

CURATED BENCH VIDEO REFERENCES

PROCEDURE TITLE	INSTRUCTOR / CREATOR	TECHNICAL PROCEDURE SUMMARY
Savage 110 Barrel Swap & Headspace Setting with Barrel Nut	Brownells Gunsmithing Bench	Full demonstration of using a barrel nut wrench, Clymer GO/NO-GO gauges, swapping bolt heads from .223 to .308, and tuning the AccuTrigger.