ARMORER'S BENCH TECHNICAL MANUAL

SIG Sauer P226 / P229 / P220 Classic Line

SIG Sauer • Navy SEALs Mk25, P226, P229, P220 (.45 ACP, 9mm, .40 S&W;)

Manufacturer:	SIG Sauer	**Category:**	Pistols
Action Type:	Double-Action / Single-Action (DA/SA) with Decocker	**Era / Service:**	Modern Tactical Benchmark (1975–Present)
Calibers:	9x19mm Parabellum, .40 S&W;, .45 ACP, .357 SIG	**Covered Models:**	P226 Standard / Mk25, P229 Compact, P220 (.45 ACP), P226 Legion, P226 SAS

KEY ARMORER TASKS & BENCH OPERATIONS

Core Procedures: Short Reset Trigger (SRT) Installation • Frame Rail Anodizing Lubrication Check • Decocking Lever Timing Inspection • Roll Pin vs Solid Spiral Pin Service • Mainspring Strut Reassembly

CRITICAL ARMORER TOLERANCES & SPECIFICATIONS

SPECIFICATION / CLEARANCE	ARMORER TOLERANCE & BENCH SPECIFICATION
OPERATING SYSTEM	Short recoil tilting barrel; full chamber hood lockup into slide ejection port
FRAME MATERIAL	Hardcoat anodized 7075-T6 aluminum alloy (stainless steel in Elite models)
DECOCKING LEVER	Smooth manual decocker safely lowers hammer into safety intercept notch without contacting firing pin
TRIGGER PULL DA	10.0 lbs standard / 8.5 lbs with tuned mainspring
TRIGGER PULL SA	4.4 lbs standard / 3.5 to 3.8 lbs with factory SRT (Short Reset Trigger) sear
BREECH BLOCK PIN	Solid spiral roll pin (modern milled slides) / inner & outer concentric roll pins (early stamped slides)
FRAME RAIL GREASE	MANDATORY GREASE: Aluminum frame rails must be lubricated with high-pressure grease to prevent galling

IMMEDIATE ACTION & MALFUNCTION DIAGNOSTIC MATRIX

MALFUNCTION CONDITION	PROBABLE CAUSES	ARMORER BENCH REMEDY
Stoppage 1: Slide Sluggish / Frame Rail Wear & Galling **Slide movement feels rough and sluggish; anodized black finish wearing down to bright shiny silver aluminum**	• Running aluminum frame dry or using thin oil instead of grease on high-friction rail channels. • Grit and sand impregnated in oil acting as lapping compound.	**Gunsmith Action: Clean rails thoroughly. Inspect anodizing under loupe. If anodizing is intact, switch protocol to high-lubricity grease (TW25B or Lucas Gun Grease). If gouged, stone high spots flat with ceramic file; do not cut into remaining anodize layer.**

CURATED BENCH VIDEO REFERENCES

PROCEDURE TITLE	INSTRUCTOR / CREATOR	TECHNICAL PROCEDURE SUMMARY
Sig Sauer P226 Complete Detail Disassembly & SRT Install	Sig Mechanics / Armorer Bench	Teardown of the classic Sig P-series frame: decocker lever spring, sear, safety lever, mainspring strut, and installing the Short Reset Trigger sear kit.