ARMORER'S BENCH TECHNICAL MANUAL

Tikka T3 & T3x Bolt Action Rifles

Tikka (Sako Finland) • Finnish Sub-MOA Precision Hunting & Target Rifles (6.5 CM, .308 Win, .223)

Manufacturer:	Tikka (Sako Finland)	**Category:**	Rifles & Carbines
Action Type:	70° Throw Push-Feed Precision Bolt Action	**Era / Service:**	Modern European Precision (2003–Present)
Calibers:	6.5 Creedmoor, .308 Winchester, .30-06, .223 Rem, .300 Win Mag	**Covered Models:**	T3x Lite, T3x CTR (Compact Tactical Rifle), T3x Superlite, T3x TAC A1 (Chassis)

KEY ARMORER TASKS & BENCH OPERATIONS

Core Procedures: Steel Recoil Lug Bedding Upgrade • Single-Stage Trigger Set Screw Tuning (2–4 lbs) • Bolt Shroud Replacement (Aluminum) • Metric Barrel Threading (M17x1) • Magazine Latch Adjustment

CRITICAL ARMORER TOLERANCES & SPECIFICATIONS

SPECIFICATION / CLEARANCE	ARMORER TOLERANCE & BENCH SPECIFICATION
SUB MOA GUARANTEE	Factory 1-MOA 3-shot or 5-shot accuracy guarantee using match factory ammunition
BOLT LIFT	Fast 70° bolt throw (providing generous clearance for large high-magnification ocular optics bells)
BARREL THREADS	Metric M17x1 or 5/8x24 thread pitch depending on export market
TRIGGER ADJUSTMENT	Single allen head screw inside magazine well adjusts trigger weight cleanly from 2.0 to 4.0 lbs without opening action
RECOIL LUG	Separate mortised recoil lug fits into receiver slot (T3x features steel lug; upgrade from early aluminum)

IMMEDIATE ACTION & MALFUNCTION DIAGNOSTIC MATRIX

MALFUNCTION CONDITION	PROBABLE CAUSES	ARMORER BENCH REMEDY
Stoppage 1: Accuracy Degradation / Wandering Zero on Heavy Caliber **Sub-MOA rifle begins shooting 2 to 3-inch groups after 200 rounds of heavy magnum recoil**	• Factory aluminum recoil lug indented or deformed by steel receiver recoil shoulder. • Action screws loose in polymer stock without metal pillars.	**Gunsmith Action: Disassemble stock. Discard soft aluminum recoil lug. Install precision-ground stainless steel or titanium recoil lug. Glass bed the action and recoil lug with Devcon 10110 aluminum epoxy; torque action screws to 45 in-lbs.**

CURATED BENCH VIDEO REFERENCES

PROCEDURE TITLE	INSTRUCTOR / CREATOR	TECHNICAL PROCEDURE SUMMARY
Tikka T3x Complete Disassembly, Trigger Tuning & Upgrades	Brownells Gunsmithing Bench	Teardown of the Tikka T3x: adjusting the trigger pull weight with an allen wrench, replacing the bolt shroud, and installing a steel recoil lug.