Winchester Model 1894

Winchester Repeating Arms / USRAC • The Premier American Deer Rifle (.30-30 Winchester & .32 Win Special)

Manufacturer:	Winchester Repeating Arms / USRAC	**Category:**	Rifles & Carbines
Action Type:	Lever-Action Tubular Magazine Repeating Rifle	**Era / Service:**	American Deer Hunting Legend (1894–Present)
Calibers:	.30-30 Winchester, .32 Win Special, .38-55 Winchester	**Covered Models:**	Model 94 Carbine (20"), Model 94 Trapper (16"), Model 94 Sporter (24"), Model 94 Big Bore (.375 Win)

KEY ARMORER TASKS & BENCH OPERATIONS

Core Procedures: Cartridge Stop & Carrier Timing • Vertical Locking Bolt Upward Slide Engagement • Loading Gate Spring Tension Adjustment • Link Pin & Finger Lever Stoning • Top-Eject vs Angle-Eject Disassembly

CRITICAL ARMORER TOLERANCES & SPECIFICATIONS

SPECIFICATION / CLEARANCE	ARMORER TOLERANCE & BENCH SPECIFICATION
LOCKING SYSTEM	Vertical sliding steel locking bolt rises up behind the breech bolt, completely supporting chamber pressure
CARTRIDGE STOP	Spring-loaded stop on bottom of carrier prevents second round from escaping tubular magazine into action
ANGLE EJECT CHANGE	1982 redesign altered ejection angle to 45° to allow low-profile scope mounting over bore center
AMMUNITION SAFETY	FLAT POINT OR SOFT POINT BULLETS ONLY: Pointed spitzer bullets in tubular magazines can detonate primer of round ahead under recoil

IMMEDIATE ACTION & MALFUNCTION DIAGNOSTIC MATRIX

MALFUNCTION CONDITION	PROBABLE CAUSES	ARMORER BENCH REMEDY
Stoppage 1: Double Feed from Magazine Tube (Round Under Carrier) **Opening lever releases one round onto carrier, but a second round slips halfway out of tube beneath carrier, jamming lever solid**	• Worn or chipped cartridge stop lug on front of carrier. • Loose carrier screw on left receiver wall. • Weak or broken carrier spring.	**Immediate Action: DO NOT force lever. Use brass probe to push protruding cartridge back into magazine tube while slightly lifting lever. Gunsmith Action: Remove carrier. Inspect cartridge stop shelf. Square worn face with needle file or install new carrier. Tighten carrier screw with blue Loctite.**

CURATED BENCH VIDEO REFERENCES

PROCEDURE TITLE	INSTRUCTOR / CREATOR	TECHNICAL PROCEDURE SUMMARY
Winchester Model 94 Complete Disassembly, Cleaning & Assembly	Mark Novak / Anvil Gunsmithing	Teardown of the Winchester 94 action: link pin, locking bolt, loading gate spring, hammer assembly, and timing the carrier.