ROBIN code review

Date: 2026-10-16
Code reviewed: `main` at `493f53f` (LooseLab/ROBIN, forked to gmc-norr/ROBIN); the independent review's findings were checked at `5be9e04`.
Scope: all of `src/robin` (91 Python files, about 82,000 lines), plus packaging, resources and CI config.
Prepared with: Claude Code (an AI-assisted review), plus a correction pass by Codex and an independent review by GPT 6.1 Sol. Treat each finding as a lead to check, not as a final verdict.
Updated: 2026-10-16. The independent review's 11 findings are merged in; each keeps its original number (IR-01 to IR-11) next to its new ID. The CNV-1, GUI-1 and SEC-1 fix sizes are corrected, the status lines are up to date, and the reproduction scripts are added.
Updated: 2026-10-30. SEC-9 is added. Fixes made in our fork are listed under "This fork and the original ROBIN", and each fixed finding has a **Status** line. Batch 2 (VAR-9, VAR-8, VAR-10) is fixed too.
Updated: 2026-10-30. Batch 3, step 3's quick wins, is fixed in our fork: GUI-1, REP-1, JOB-6, GUI-4, CNV-5, GUI-2, VAR-3 and VAR-7. JOB-6 is only partly fixed — the timeout constant and its configurability, not the two consequences that overlap JOB-7.
Updated: 2026-10-31. Two follow-ups from batch 3's own review are fixed in our fork: `robin add-panel` reads BED files wider than 6 columns (BED12 was saved garbled), and the variant panel's "Hide Results" keeps pointing at the file it showed.
Updated: 2026-10-31. Five findings from a review of the fix series (`reviews/2026-10-31-fix-series-review.md`) are fixed in our fork: stale CNV breakpoints after a flat run, an older LGA results file hiding a newer one, an LGA status timer that never stopped, SNV sites with no usable bases read as "None Detected", and `{file}` quoting inside `$(...)`. ClinVar sites no read covers now need review too, and that batch's own review led to two more fixes (a failed CNV detection, a "(legacy location)" caption). Six more bugs found along the way are fixed too; see the fork table.
Updated: 2026-10-31. Step 4 is fixed in our fork: CNV-1 (the control profile comes from the control's own counts, which also ends a 16-bit wrap found while fixing it), with CNV-3 (a batch's last BAM counted twice) in the same code.
Updated: 2026-11-01. Step 5, the methylation maths, is fixed in our fork except METH-7 (left for later): METH-1 to METH-6, METH-13 and METH-14, checked against `modkit pileup --combine-strands` on synthetic reads, and part of METH-12.
Updated: 2026-11-01. Step 6, target input and coverage, is fixed in our fork: TGT-1 to TGT-5, checked against samtools run once on all of a sample's reads (split into 1, 2 and 4 BAMs, in five ways of running, two workers at once among them). Per-base panel depth (D4) is noted as later work under "Suggested order of work".

This fork and the original ROBIN

This review is of the original ROBIN (LooseLab/ROBIN at `493f53f`). Our fork, gmc-norr/ROBIN, now has fixes that the original does not, so the two have diverged. **Every finding below is still open in the original ROBIN** unless LooseLab fixes it themselves. A finding fixed in our fork has a **Status** line.

Change in gmc-norr/ROBIN	Finding	Commits	What users notice
Skip modkit files with no panel sites	The "Error processing file ... ['Chromosome', 'Start']" log line (context under METH-9)	`d02add2`	That error no longer appears for those files
Traceback and safe diagnostics when a modkit file fails to merge	—	`5be9e04`	A longer log line, with no patient positions or values

Change in gmc-norr/ROBIN	Finding	Commits	What users notice
Ray dashboard off by default, and on 127.0.0.1 when turned on	SEC-1	`3623e93`	Turn it on with `--ray-dashboard`. `workflow_ray` takes `--ray-dashboard` instead of `--no-ray-dashboard`
Ray workers get their own empty NiceGUI storage folder	Found after this review	`3623e93`	The `storage-general.json.tmp` error is gone
GUI storage moves from `./.nicegui` to `~/.robin/nicegui`	Found after this review	`c51e65d`, `944dbee`	Everyone sees the disclaimer and logs in again once
MGMT runs R without a shell	SEC-8	`2d3577e`, `0873744`	Nothing
Watched file names reach command templates as data	SEC-9	`4f26cf0`, `75485ce`	Inside a nested `sh -c`, `eval` or `ssh` command, use `"$ROBIN_FILE"` instead of `{file}`
Exact pins: numpy 1.26.4, pandas 2.1.4, scikit-learn 1.8.0; Python 3.12 only	PKG-3, part of PKG-6	`43db1df`	Installs refuse Python 3.13 and later
Lightweight variant check uses only the sample's own BAM and BED, and records them	VAR-9	`b9ffef8`	A missing file fails with "... for this sample at "
The GUI hides lightweight variant results that don't record their BAM	VAR-9	`d0e1975`	Old results aren't shown; run the variant analysis again
Every BED interval of a gene is checked	VAR-10	`20ea771`	Variants in later exons now appear
A pathogenic variant counts only with 3 or more alternate reads	VAR-8	`aeb5339`, `e5527a3`	New status "Insufficient Evidence" (1–2 reads, an indel or multi-base change, or reads showing neither allele); fewer genes flagged
The classification panel follows the classifiers the run enabled	GUI-1	`50da100`	With a classifier disabled, the panel keeps updating instead of freezing on the first result
Random Forest is scored against its own confidence cut-offs	REP-1	`229247f`, `f50ad61`	The PDF no longer says "High" where the GUI says "Medium" for the same sample
The sample-completion idle timeout defaults to an hour, not 60 s	JOB-6 (partly)	`c4592a0`, `b23ef4f`	Samples are no longer finalised mid-run. Set `ROBIN_COMPLETION_TIMEOUT_SECONDS` to change it; a run that relied on 60 s now waits an hour
The CNV card reports an absent gain/loss count instead of the batch counter	GUI-4	`e677991`	"Gained: Not available" in place of "Gained: 37"
The end of a chromosome's signal is a terminator, not a breakpoint	CNV-5	`53165ed`	About 24 fewer regions in the master BED per run
Refresh timers survive a reconnect	GUI-2	`7ff93b1`	An open page keeps updating after a Wi-Fi blip or laptop sleep; a page that really closed is torn down up to 60 s later
A ClinVar refresh rebuilds the tabix index	VAR-3	`8a37a7a`	Pathogenic annotations no longer vanish after a ClinVar update

Change in gmc-norr/ROBIN	Finding	Commits	What users notice
`robin add-panel` keeps every region of a gene	VAR-7	`1c8e95f`	Later exons and tiles stay in the panel, so coverage and SNP calling see them
`robin add-panel` reads BED files wider than 6 columns, by their first 4	Found while fixing VAR-7	`5af0a47`	A BED12 panel is saved with its real regions. It used to be saved garbled, with "added successfully"; 7 or 8 columns failed
The variant panel's "Hide Results" offers the file it showed	VAR-9 follow-up	`754741d`	After "Hide", "View" opens the trusted file again, not a hard-coded path
A CNV run with no breakpoints replaces the last run's breakpoints	CNV-5 follow-up	`4032f8b`	After a flat run, old breakpoints leave the CNV plot and the master BED
The newest trusted variant results file is the one shown	VAR-9 follow-up	`f3f29cd`	A fresh negative is no longer hidden by an older positive in the other results location
The variant panel's status timer stops when a run ends	VAR-9 follow-up	`6acc03d`	An opened results view stays open instead of resetting every half second
An SNV site with no usable bases needs review	VAR-8 follow-up	`b26c410`	Such a gene reads "insufficient evidence", not "None Detected"
A ClinVar site no read covers needs review	VAR-8 follow-up	`65ab945`	Such a gene reads "insufficient evidence", and its summary counts `sites_without_reads`; a site just before a BED region is no longer picked
A failed CNV breakpoint detection keeps the last good breakpoints	CNV-5 follow-up	`2ca41c7`	A warning in the log instead of a silent "no breakpoints"
Fresh variant results are never captioned "(legacy location)"	VAR-9 follow-up	`0964752`	In a watch-folder setup, a result just produced no longer reads as old
The CNV plot's absolute view draws breakpoint lines	Found after this review	`80207bd`	Dashed breakpoint lines appear in the absolute view too
The per-gene variant path piles up its first site	Found after this review	`e60306a`	Nothing in ROBIN calls it; scripts using `analyze_genes` see every site
`${file}` in a command template is left to the shell	SEC-9 follow-up	`49a8a79`	A shell variable named `file` works in templates
Variant results record their UTC offset	VAR-9 follow-up	`7689900`	The newest result is picked correctly across a clock change
Variant results and CNV arrays are written whole or not at all	Found after this review	`fa77eb7`	No half-read files in the GUI; a failed write keeps the last good file
`robin add-panel` says "No gene names found in column 4"	Found after this review	`edb76bd`	A clear error instead of `'chrom'`
Results written whole keep the usual file permissions	Found after this review	`5749e5d`	Group members can still read results in a shared output folder
A failed pileup reads "pileup failed"; the gene details count unread sites	VAR-8 follow-up	`c71527b`, `3fe7ba5`	The panel says why a gene reads "insufficient evidence"

Change in gmc-norr/ROBIN	Finding	Commits	What users notice
`{file}` after `$` inside single quotes is the placeholder	SEC-9 follow-up	`e8af255`	`'${file}'` prints `$` and the path, as the shell would
`{file}` inside `$(...)` is quoted for that context	SEC-9 follow-up	`ab5151b`	Templates like `"$(dirname "{file}")/x.bai"` work on paths with spaces
The CNV control's profile comes from the control's own counts	CNV-1	`b682da0`, `6ab6928`, `a06c4a2`, `2681f8b`	Gains and losses no longer fade over a run, and a sample no longer inherits the previous sample's events. CNV results change for the same data; a contig the control lacks leaves `CNV3.npy`
The CNV control's profile no longer wraps at 16 bits	Found while fixing CNV-1	`6ab6928`	Early in a run (up to about 24,000 reads), the CNV plot is no longer off by several copies
A multi-BAM CNV batch counts each BAM once	CNV-3	`391e159`	The batch's last BAM no longer counts double for the rest of the run
Methylation counts are summed per CpG across batches and both strands	METH-1, METH-2, METH-4, METH-5	`c50365a`	Methylation values and classifier results change; NanoDX sees minus-strand reads. A sample's old parquet is converted on its next merge
matkit counts each call as modkit does	METH-3, METH-13, METH-14	`d304ded`, `b70d6a5`	Unsure calls leave coverage; implicit-mode Cs count as unmethylated; supplementary alignments no longer count; MGMT's input changes too
The CpG panel is read as 0-based, and its cache can't go stale	METH-6, METH-5, part of METH-12	`dfd909f`	The base before each CpG is no longer pulled in
A test against modkit pins step 5	Step 5	`dfe9f29`, `1c6c65f`, `5bcd583`	Nothing
Target coverage adds up exactly across BAMs	TGT-3	`d6c87ff`, `d752ce6`	"Global coverage" is mean depth (it was covered bases over genome length); target depths shift a little (length end − start; deletions don't count); covered bases per chromosome are exact, or "not available" in a folder written before
One locked step adds a batch to the totals	TGT-4	`d6c87ff`	Two workers at once no longer lose a batch's coverage
Every BAM's panel reads reach target.bam, and a second finalize keeps the first	TGT-1, found while fixing it	`d6c87ff`, `24ebbc8`	SNP calls and IGV see the reads the coverage counts. `target.bam` holds the records overlapping the panel (`samtools view -L`), no longer the off-panel pieces of panel reads
The panel always reaches target.bam's regions	TGT-2	`063398d`, `d6c87ff`	Panel reads are kept even when the master BED was written without the panel
Read counts count primary records	TGT-5	`7773e2f`	Mapped reads, bases and yield drop for split reads; the 50,000-read gate counts reads
A test against samtools pins step 6	Step 6	`7b31e53`, `dd802d4`, `ee2fdd8`	Nothing

Every change has a regression test in `tests/`. The details are in `CHANGELOG.md` under `[Unreleased]`. Add a row here each time a fix lands.

How this was done, and its limits

- **Reviewers.** Seven reviewers worked in parallel, one per area:

    - workflow and job handling
    - CLI, launcher and security
    - GUI screens
    - methylation and classifiers
    - CNV, fusion, target and SNP
    - PDF reports
    - packaging and design
- **Evidence.** Every finding was checked against the code, including whether anything actually calls it. Many were reproduced with small scripts on synthetic data, or by running the real ROBIN functions with Ray and NiceGUI stubbed out.
- **My own spot-checks.** I re-read about fifteen of the most serious findings myself; all of them held up. They are marked *(spot-checked)*.
- **Independent review.** GPT 6.1 Sol looked separately at:
    - sample identity
    - the lightweight variant check
    - target coverage and BAM accumulation
    - methylation read processing
    - the MGMT command
    - the CNV→master-BED handoff

  Each of its 11 findings has a test that runs the real ROBIN functions on small synthetic BAMs with pysam. I re-ran all 11 (11 of 11 reproduced) and read the code for five of them.
- **Not done:**
    - Nothing was run on real patient BAMs.
    - Ray, NiceGUI, torch and cnv_from_bam were not installed. pysam was used only for the independent review's tests.
    - The `nanoDX` and `hv_rapidCNS2` submodules were not checked out, so the R and NN code inside them was not reviewed.
- **Confidence labels:**
    - **Confirmed:** traced end to end, or reproduced.
    - **Plausible:** a strong reading of the code, but not fully traced (usually because it depends on timing or on Ray scheduling).

The reproduction scripts are in `2026-10-16-repro/`, with a table of which script shows which finding. The independent review's test suite is in `2026-10-16-repro/independent/`. They are scripts, not regression tests yet. A "Confirmed" label only becomes repeatable evidence once its script is turned into a test in `tests/`.

Read this first

The pipeline has a sound shape: a file watcher feeds a job graph, each sample keeps its state on disk, and the analyses are pluggable. The main problems are not crashes. **Most of the serious problems give wrong or stale results with no warning.** Four patterns cause most of them:

1. **The methylation numbers fed to the classifiers are biased.** The merge averages percentages without weighting by coverage. matkit counts failed calls in the denominator. NanoDX throws away minus-strand calls.
2. **State lives in places that go stale.** There are caches inside long-lived Ray workers, the CNV control reference gets modified by every patient, the GUI keeps per-page state on a shared object, and there is one

"waiting" slot per classifier for all samples.

3. **Errors are swallowed at every layer.** Failed jobs are counted as "completed", and error details are never sent to the GUI. This is why the "Error processing file" log line never showed up in the frontend.
4. **Inputs aren't tied to the right sample or batch.** A missing BAM falls back to another sample's BAM. Early BAMs never reach the SNP input. The master BED can drop the selected panel.

Only two tests exist (added after this review), and no CI runs them.

Fix first

#	ID	Problem	What goes wrong	Where	Size of fix
1	SEC-1 *(fixed in our fork)*	Ray dashboard open on all network interfaces, with no password	Anyone on the network can run code as the ROBIN user	`cli.py:1725-1731`, `2435-2449`	Small (two places)
2	SEC-8 *(fixed in our fork)*	MGMT runs the sample folder path through the shell	A crafted sample name runs commands; a space in a path breaks MGMT	`analysis/mgmt_analysis.py:836-838`	Small
3	VAR-9 *(fixed in our fork)*	A missing BAM for sample A falls back to sample B's BAM	Another patient's variant evidence is saved under this sample	`analysis/lightweight_gene_analysis.py:1562-1605`	Small
4	METH-1 *(fixed in our fork)*	Methylation % is averaged without weighting by coverage	Every classifier gets biased input, and adding depth doesn't make it better	`analysis/temp_utilities.py:285-391`	Small
5	CNV-1 *(fixed in our fork)*	CNV control reference is modified by every patient's reads	Real gains and losses fade over a run; false events appear in the next patient	`analysis/cnv_analysis.py:118-145`	Medium (build the control profile without patient reads)
6	JOB-1	One waiting slot per classifier type, shared by all samples	In multi-sample runs, a sample's final classification can silently never run	`workflow_ray.py:2462-2535`	Medium
7	GUI-1 *(fixed in our fork)*	Classification panel freezes if any classifier is disabled	GUI keeps showing the first result for the rest of the run	`gui/components/classification.py:1003-1021`	Small (two loops)
8	GUI-2 *(fixed in our fork)*	Refresh timers are switched off on any brief reconnect	An open page shows hours-old results, with no sign that they are stale	8 GUI components	Small
9	VAR-8 *(fixed in our fork)*, VAR-1, VAR-2, VAR-3 *(fixed in our fork)*	Variant summaries and ClinVar handling	Reference-only sites reported as pathogenic; IDH1 R132H-type alleles lost; "conflicting" shown as pathogenic; a stale index returns nothing	`lightweight_gene_analysis.py`, `snp_processing.py`, `clinvar_manager.py`, `reporting/sections/variants.py`	Small to medium
10	TGT-1, TGT-2 *(fixed in our fork)*	Early BAMs never reach the SNP input; the master BED can drop the panel	SNP calls and IGV miss reads that the coverage numbers include	`analysis/target_analysis.py`, `cnv_analysis.py`, `master_bed_generator.py`	Medium
11	JOB-6 *(partly fixed in our fork)*	60-second idle timeout (a test value) left in	A sample is marked Complete and finalised too early; SNP calls cover only part of the data	`gui_launcher.py:420`	One line
12	METH-3, METH-4 *(fixed in our fork)*	matkit counts failed calls in coverage; NanoDX drops minus-strand calls	Methylation pushed down; about half the reads never reach NanoDX	`utilities/matkit.py`, `nanodx_analysis.py`	Medium

#	ID	Problem	What goes wrong	Where	Size of fix
13	ERR-1	Failed jobs counted as "completed"; errors never sent to the GUI	Stale or empty results look current	`workflow_ray.py`, the handlers	Medium
14	JOB-2	Same BAM can be processed twice, for example after a restart	Coverage and counts doubled	`workflow_ray.py:4949-4977`	Medium
15	REP-1 *(fixed in our fork)*	PDF report uses the wrong Random Forest cut-offs	The PDF can say "High" where the GUI says "Medium"	`reporting/sections/classification.py:399`	One line

Before trusting more runs: compare ROBIN's merged parquet and classifier inputs with `modkit pileup --combine-strands` on one small real BAM. Make that comparison a regression test.

Upstream: SEC-1 (Ray dashboard), SEC-8 (MGMT shell command), SEC-9 (watched file names in command templates) and SEC-2 (MNP-Flex TLS) are security problems in upstream ROBIN. Report them to LooseLab privately, not in a public issue.

End-to-end data flow (for orientation)

1. `robin workflow` (`cli.py`) checks the model files, then starts `workflow_ray.run()` (the default) or `workflow_simple` (`--no-use-ray`), plus the NiceGUI app.
2. `RayFileWatcher` finds new BAMs. The `Coordinator` actor batches them per sample (`SampleJobBatcher`, `BATCH_CONFIG`) and dispatches Ray tasks. The job graph is `TRIGGERS`.
3. **preprocessing** (`bam_preprocessor`): reads the sample ID and read counts, and writes `master.csv`. It then fans out to bed_conversion, mgmt, cnv, target and fusion.
4. **bed_conversion**: `matkit.run_matkit` writes a per-BAM CpG parquet. `temp_utilities.merge_modkit_files` filters it to `parquet_filter.txt` and merges it into `<work>/<sample>/<sample>.parquet`.
5. **Classifiers**, triggered by bed_conversion:
   - Sturgeon (ONNX)
   - NanoDX and PanNanoDX (NN pickle)
   - Random forest (an R script in `hv_rapidCNS2`)

   Their input comes from `merge_bedmethyl.load_modkit_data`.
6. **Per-sample analyses:**
   - MGMT (methylartist)
   - CNV (`cnv_from_bam` against `HG01280_control_new.pkl`, with ruptures)
   - target coverage
   - fusion (`fusion_work`, clustering of supplementary reads)
7. target → `igv_bam` → `snp_analysis`, which the GUI triggers. It runs ClairS-TO in Docker (`:latest`), then SnpEff/SnpSift with ClinVar.
8. All state is CSV, parquet, pickle or npy files under `work_dir/<sample>/`. There is no database.
9. The GUI (`gui_launcher.GUILauncher`, `gui/components/*`) polls and unpickles those files. Optionally, MNP-Flex uploads to mnp-flex.org.
10. PDF reports (`reporting/report.create_pdf`) are built from the same sample folder.

1. Methylation numbers fed to the classifiers

> **METH-1** CRITICAL · **Confirmed (spot-checked)**: Cumulative `percent_modified` is a mean of means.

- **Where:** `analysis/temp_utilities.py:380-391`
- **What's wrong:** Each merge does `group_by(chrom, chromStart)`. It sums `valid_cov`, `n_mod` and `n_canonical` correctly, but sets `percent_modified = mean(...)` of the old aggregate and the new batch. So the newest batch always carries at least 50% of the weight. The summed counts sit in the same row but are never used.
- **Who reads it:** every classifier and MNP-Flex read only `percent_modified`. `merge_bedmethyl.collapse_minimal_bedmethyl` then takes the mean again, despite a comment there saying "weighted average".
- **Reproduced:**
  - 50 reads at 80%, then 1 read at 0%: stored 40.0%, true 78.4%.
  - Simulation of 500 CpGs at 80%, arriving at 20× depth one read per batch: NanoDX "methylated" calls (≥60%) fell to 81% of sites, against 99% with weighting.
- **Fix:** after summing, set `percent_modified = 100 * n_mod / valid_cov`.
- **Status:** fixed in our fork (`c50365a`): every write sums `n_mod` and `n_canonical` per CpG and sets `percent_modified = 100 * n_mod / valid_cov`. The case above now stores 78.43%. Checked against `modkit pileup` on synthetic reads (`dfe9f29`; result `5bcd583`). Still open in the original ROBIN.

> **METH-2** HIGH · **Confirmed**: The first write isn't aggregated, so random forest can see values over 100%.

- **Where:** `temp_utilities.py:285-333`
- **What's wrong:** When no cumulative parquet exists yet, the concatenated per-BAM rows are written as they are. A first batch can hold up to 20 BAMs, so there is one row per BAM per site.
- **What goes wrong downstream:**
  - The random forest path sums `score`, so the R script gets methylation of 200-300%.
  - Sturgeon counts the duplicate rows as separate sites.
- **Fix:** always run the same aggregation before writing (this is the same fix as METH-1).
- **Status:** fixed in our fork (`c50365a`): the first write goes through the same summing. Random forest's input is one row per CpG at the parquet's percent, never over 100 (`1c6c65f`). Still open in the original ROBIN.

> **METH-3** HIGH · **Confirmed**: matkit puts failed calls into `valid_cov`.

- **Where:** `utilities/matkit.py:1344, 1373-1385, 1132-1139`
- **What's wrong:** The total is incremented for every read before it is classified, so fails are counted. The result is `n_mod / (mod + canonical + fail)`; modkit leaves fails out of the denominator.
- **Example:** 6 modified, 2 canonical and 2 failed reads are stored as 60% instead of 75%. That moves the site across Sturgeon's 0.7 cut-off and onto NanoDX's 60% cut-off.
- **Plausible, secondary:** with combine_mods, the call uses max(P_m, P_h, P_C) rather than comparing P_m+P_h with P_C. This matters in brain tissue, which has high 5hmC.
- **Status:** fixed in our fork (`d304ded`): `valid_cov` is `n_mod + n_canonical` in the per-BAM parquet and in MGMT's BED. The "plausible, secondary" point is refuted: modkit 0.6.4's `--combine-mods` also takes the most likely class, so a read with 5mC 0.45 and 5hmC 0.45 is a failed call in both. Still open in the original ROBIN.

> **METH-4** HIGH · **Confirmed**: NanoDX and PanNanoDX drop every minus-strand CpG call.

- **Where:** `nanodx_analysis.py:342-349`, `utilities/merge_bedmethyl.py:490-501`

- **What's wrong:** matkit records the minus-strand call at C+1. The collapse step relabels the strand as "." but still groups on position, so the + and − rows of one CpG never merge. NanoDX's exact join on the 0-based C position then keeps only the + row.
- **Effect:**
  - About half the reads never reach NanoDX.
  - Sturgeon gets the two strand rows as equal votes, ignoring coverage: 3 reads at 100% count the same as 20 reads at 0%.
- **Fix:** shift − rows to position−1, then sum counts per CpG (the equivalent of `--combine-strands`).
- **Status:** fixed in our fork (`c50365a`): a minus-strand row moves onto its CpG's C and the two strands' counts are summed, as `--combine-strands` does. NanoDX/PanNanoDX, Sturgeon, random forest and MNP-Flex each get one row per CpG (`1c6c65f`). Still open in the original ROBIN.

METH-5 MEDIUM · **Confirmed**: Panel intersect plus inner join double-counts sites.

- **Where:** `temp_utilities.py:250-266`
- **What's wrong:** `parquet_filter.txt` has 976 pairs of overlapping intervals, including 90 exact duplicates. After the widening in METH-6 there are 8,238. PyRanges `intersect` returns one row per overlap, so the join duplicates the site.
- **Example:** in a CGCG, coverage is stored as 16 instead of 8.
- **Fix:** use a semi-join, and remove duplicates from the panel.
- **Status:** fixed in our fork (`dfd909f`, `c50365a`): exact duplicate panel rows are dropped, and rows are kept by a semi-join on the CpG's C, so each site counts once. Still open in the original ROBIN.

METH-6 MEDIUM · **Confirmed (spot-checked)**: `parquet_filter.txt` is already 0-based, so the v0.5 "1-based fix" is wrong.

- **Where:** `temp_utilities.py:159-179`, `docs/releases/v0.5.md:19`
- **Evidence:** cg13869341 is at `15864-15866` in this file, in the 0-based NanoDX BED and in the 0-based MNP-Flex BED. About 486k of its probes match the NanoDX file exactly.
- **What's wrong:** `Start - 1` widens every CpG to 3 bp, and the release note wrongly tells users their old parquets were wrong.
- **Also:** the first data row is `chr1 -1 0 cg22940546`, which has a negative start.
- **Fix:** read the file as plain 0-based BED, and correct the release note.
- **Status:** fixed in our fork (`dfd909f`): the file is read as listed (cg13869341, cg02984631 and cg14817997 read "CG" in hg38 at their starts), the 26 rows with a negative start are dropped, and `docs/releases/v0.5.md` carries a correction. 4,366 of the 900,614 rows are 1 bp long (3,091 "ch", 65 "rs" and 1,210 "cg" probes; of the 1 bp "cg" rows, 2 of 4 we checked sit one base off a CpG in hg38, and 12 others the final review checked sit on one); every row's start is treated as a CpG's C. A "ch" row is a non-CpG C, so CpG calls give it no data (`b70d6a5`). Still open in the original ROBIN.

METH-7 MEDIUM · **Confirmed**: Classifiers never see coverage, and random forest gets a constant `cov=10`.

- **Where:** `merge_bedmethyl.py:72-189, 751-797`, `random_forest_analysis.py:283-346`
- **What's wrong:** The loader keeps only 5 columns. The random forest input invents `valid_cov=10`. So a site with 1 read counts the same as a site with 50.

METH-8 MEDIUM · **Confirmed**: Classifier failures are reported as success.

- **Where:** `sturgeon_analysis.py:585-588`, `merge_bedmethyl.py:93-102`, `nanodx_analysis.py:186-190, 366-397`, `mgmt_analysis.py:842-848`
- **Per classifier:**

  - **Sturgeon:** catches and logs the error, and appends no row.
  - **NanoDX:** appends an empty row with `number_probes=0`, and writes patient data to `errordf.csv` in the worker's current directory.
  - **MGMT:** an R failure only logs a warning, and the step returns True.
- **Effect:** the GUI keeps showing the previous result as if it were the latest.

METH-9 LOW/MEDIUM · **Confirmed (mechanism)**: One BAM failing in a batch is skipped and its data deleted.

- **Where:** `temp_utilities.py:268-270`, `bed_conversion.py:252-262, 323-329`
- **What's wrong:** Per-file errors in the merge are logged and the loop goes on. All the per-BAM parquets are then deleted, including the failed one, and the job reports success.
- **Context:** this is the path behind the original "Error processing file ... ['Chromosome', 'Start']" message. That case is fixed on `main` (commit `d02add2`), and it lost no data. Commit `5be9e04` makes this log line include a traceback and safe diagnostics.

METH-10 LOW · **Confirmed**: The MGMT site table can show 0.43% as 43%.

- **Where:** `mgmt_analysis.py:336-347`; the GUI copy is at `gui/components/mgmt.py:226-235`
- **What's wrong:** It guesses "fraction or percent?" from whether any row is above 1. An unmethylated promoter at high depth fools the guess. The GUI copy has also drifted from the analysis copy.

METH-11 LOW · **Plausible**: The `bam_file_count` metadata undercounts.

- **Where:** `bed_conversion.py:300`, `temp_utilities.py:275`
- **What's wrong:** bed_conversion always passes `num_bam_files_seen=1`, and the count isn't updated when every file in a batch is skipped.

METH-12 LOW · **Plausible**: The panel filter cache is keyed by the panel file's basename only.

- **Where:** `temp_utilities.py:152`
- **What's wrong:** A different panel file with the same name reuses the old ranges. The cache pickle is also written non-atomically, outside the lock.
- **Status:** partly fixed in our fork (`dfd909f`): the cache's name carries a format version and the panel file's size and modification time, and it is written atomically, because every sample's old cache would otherwise have hidden METH-6's fix. Still open in the original ROBIN.

METH-13 HIGH · **Confirmed (reproduced; spot-checked)**: Implicit canonical calls in MM tags are ignored, which pushes methylation up. *(IR-05)*

- **Where:** `utilities/matkit.py:1287-1293, 1311-1333`
- **What's wrong:** matkit counts only the calls that `read.modified_bases` lists. In the MM tag's implicit mode (`.` or no marker), skipped C bases mean "unmodified", but matkit never counts them as canonical. A read with an empty implicit list (`C+m.;`) is skipped entirely.
- **Reproduced:** two reads cover `CGCG`, each with one confident modified call and one implicit canonical base. matkit stores 100% instead of 50% at each CpG.
- **Who it affects:** only BAMs that use implicit mode. In `?` mode, skipped bases are "unknown", and ignoring them is correct. To check which mode a BAM uses: `samtools view x.bam | head -1 | grep -o 'MM:Z:C+[a-z]*[.?]\?'`.
- **Fix:** follow the MM skip-mode rules when building each read's observations. Add test files for explicit, implicit and unknown modes, and compare with modkit.
- **Status:** fixed in our fork (`d304ded`, `b70d6a5`): in implicit mode, every CpG C the MM tag skips is an unmethylated call (CpG as the read reads it; the first fix counted every C, which the final review caught); a

record with MM but no ML is skipped, as modkit does; `?` mode is unchanged; an implicit group with no positions now counts every C instead of skipping the read. Still open in the original ROBIN.

> **METH-14** MEDIUM · **Confirmed (reproduced)**: Whether a low-quality read is filtered depends on where its alignments lie. *(IR-06)*

- **Where:** `utilities/matkit.py:1263-1284`
- **What's wrong:** A read is added to the "exclude" set only when its low-QS primary record is reached. Supplementary records that come earlier in coordinate order have already been counted, and are never removed.
- **Reproduced:** the same QS=5 read keeps one methylation site when its supplementary alignment comes first, and none when its primary comes first. Both BAMs are coordinate-sorted.
- **Fix:** decide whether a read passes the QS filter before counting any of its alignments.
- **Status:** fixed in our fork (`d304ded`): only primary alignments count, as in modkit (its `--allow-non-primary` is off by default), so a low-QS read is dropped whatever the order of its records. Supplementary alignments no longer count toward methylation. Still open in the original ROBIN.

Not a problem:

- The 5hmC+5mC merge is by design.
- MGMT's 1-based to 0-based site handling is correct.
- Parquet writes are atomic.
- The cumulative merge is bounded by the panel size, not by total reads.

---

2. CNV

> **CNV-1** CRITICAL · **Confirmed (spot-checked)**: The cached control reference is modified in place and absorbs every patient's reads.

- **Where:** `analysis/cnv_analysis.py:118-145, 1181-1217, 1491, 1535-1597`
- **What's wrong:** `get_cached_ref_cnv_dict` returns one module-global dict, and it is passed straight to `cnv_from_bam.iterate_bam_file(copy_numbers=...)`, which adds reads into it (checked against the upstream Rust source). So in a long-lived Ray worker, the "control" grows with every BAM of every sample.
- **Simulated effect:**
  - Within one patient, a 3-copy gain reads +1.04 after the first batch, +0.49 when the patient has as many reads as the control, and +0.28 at 2.5× the control. A partial-purity gain drops below the ±0.4 call threshold, so events like 1p/19q or +7/−10 can disappear as the run goes on.
  - Across patients, a normal patient processed after another one showed mirror-image false events.
- **Fix:** build the reference profile from the stored control counts only, by re-binning them to the sample's bin width in numpy. Never pass a dict that must stay clean to `iterate_bam_file`.
- **Not enough on its own:** a `copy.deepcopy` per call is only a stopgap. It stops patients polluting each other, but each call still adds the current BAM to the copy, so the reference still contains that BAM's reads.
- **Status:** fixed in our fork (`b682da0`, `6ab6928`, `a06c4a2`, `2681f8b`). The new `analysis/cnv_reference.py` re-bins the stored control counts to the sample's bin width with the library's own formula, in 64-bit; the direct runner and `cnv_subprocess.py` use it in place of their second `iterate_bam_file` pass, and the cached control is a read-only mapping that the library refuses as `copy_numbers`. While fixing it we found that `cnv_from_bam` 0.4.4 sums bin chunks as 16-bit numbers with no overflow check: on the public control (12.7 M reads), a sample with up to about 24,000 reads gets bins whose control sums pass 65,535; at 4,000 and 20,000 reads the control's profile came out off by up to 4 and 17 copies. The 64-bit re-binning ends that too. One deliberate difference from the library: its median chunks the genome end to end in hash-map order, so

a chunk can straddle two contigs; ours stays within each contig. Measured on the public control where nothing wraps, the two differ by up to 0.035 copies (at 25,000 sample reads; 0.015 at 50,000, 0.024 at 200,000). The sample's own profile still uses the library's median, so `CNV3.npy` can carry an offset of that size, an order of magnitude under the ±0.4 call threshold. A contig that only the sample has is no longer in `CNV3.npy`. Still open in the original ROBIN.

CNV-2 HIGH · **Plausible**: Per-sample CNV counts are cached per Ray worker and never invalidated.

- **Where:** `cnv_analysis.py:1137-1178, 1446-1484, 1245, 1620`, `workflow_ray.py:392-394, 2037-2068`
- **What's wrong:**
  - The cache only checks that the path matches.
  - CNV isn't serialised per sample.
  - The pickle is written non-atomically, and a load error silently resets the counts to `{}`.
  - The Coordinator's cache cleanup runs in the wrong process, so it does nothing.
- **Example:** batch 1 runs on worker A, batch 2 on worker B, and batch 3 on worker A again. Worker A uses its stale cache, so batch 2's reads are lost for good.
- **Fix:** always reload from disk under a per-sample lock, and write with tmp + `os.replace`.

CNV-3 MEDIUM · **Confirmed**: Multi-BAM CNV adds the batch's last BAM twice.

- **Where:** `cnv_analysis.py:1515-1597, 1620`
- **What's wrong:** The loop has already accumulated every BAM, and the "final aggregated" call then adds the last one again. The result is saved, so the double count is permanent.
- **Status:** fixed in our fork (`391e159`): the loop's last result is the final one. Not fixed, and true before too: in subprocess mode (off by default, `USE_CNV_SUBPROCESS = False`), each loop call reloads the sample's counts from disk, which the loop never rewrites, so a batch keeps only its last BAM. Still open in the original ROBIN.

CNV-4 MEDIUM · **Confirmed**: The sex labels don't match the thresholds.

- **Where:** `cnv_analysis.py:677-689`, `classification_config.py:164`, `cnv_classification.py:195`, `gui/components/cnv.py:751-760`, `reporting/sections/cnv.py:365-373`
- **What's wrong:**
  - The estimator emits "Male (query X/Y ...)", which the threshold code treats as female.
  - The report compares against "XX"/"XY", which are never produced.
- **Effect:** for such males, a chrX gain needs >0.75 instead of >0.3, and chrY isn't skipped.
- **Fix:** use one shared XX/XY/UNKNOWN enum.

CNV-5 LOW · **Confirmed (by reading)**: Every chromosome gets a fake breakpoint at its end.

- **Where:** `cnv_analysis.py:574-580, 714-730`
- **What's wrong:** ruptures always returns the series length as its last change point. That adds about 24 spurious regions to the master BED.
- **Fix:** use `result[:-1]`.
- **Status:** fixed in our fork (`53165ed`). `run_ruptures` drops the terminator where it is produced, so those regions leave the master BED and `breakpoints_count` falls by about 24 per run. A chromosome whose only change point is the series end now yields no region at all, and when every chromosome does, `cnv_data_array.npy` and `breakpoints_NNN.bed` were not written, so the previous run's breakpoints stayed in the GUI and the master BED. Since `4032f8b` both are written empty instead; a detection that *failed* writes neither and logs a warning, so the last good breakpoints stay (`2ca41c7`). Still open in the original ROBIN.

The CNV summary card and the report's CNV problems are covered in sections 6 and 7.

---

3. Variants, fusions, target coverage and SNP input

Variants and ClinVar

> **VAR-1** HIGH · **Confirmed**: ClinVar records at the same position overwrite each other.

- **Where:** `analysis/lightweight_gene_analysis.py:228-229, 560-612`
- **What's wrong:** The lookup is keyed by `(chrom, pos)`, so only the last ALT allele at a position is kept.
- **Reproduced:** with IDH1 R132H (C>T) followed by C>A in the file, a patient who carries R132H shows "no_support". BRAF V600 and KRAS G12-type sites have the same problem.
- **Fix:** key by `(chrom, pos, ref, alt)`.

> **VAR-2** HIGH · **Confirmed**: "Conflicting classifications of pathogenicity" counts as pathogenic.

- **Where:** `snp_processing.py:14-23, 132-136`, `lightweight_gene_analysis.py:260-265`, `reporting/sections/variants.py:61-75`
- **What's wrong:**
  - Substring matching on "pathogenic" also matches "Conflicting_..._of_pathogenicity". In the report, the CLNSIGCONF vote branch is therefore never reached, and it would crash if it were.
  - Also: `parse_vcf` groups with `dropna=True`, so records without ANN vanish from the table. In the test, 2 of 3 variants were shown.
- **Fix:** match exact CLNSIG tokens, use one shared helper, and `groupby(..., dropna=False)`.

> **VAR-3** HIGH · **Confirmed (reproduced with bcftools)**: A ClinVar refresh keeps the old tabix index.

- **Where:** `utils/clinvar_manager.py:130-131, 221, 300`
- **What's wrong:** After a new `clinvar.vcf.gz` is swapped in, `_ensure_tabix_index` returns early because the old `.tbi` exists. Region queries then return nothing with exit code 0, so pathogenic annotations silently disappear.
- **Fix:** always rebuild the index after replacing the file.
- **Status:** fixed in our fork (`8a37a7a`, `849e078`). `_ensure_tabix_index` takes a keyword-only `force`, and the two callers that have just written the `.gz` — `ensure_clinvar_files` and `update_clinvar_if_newer` — pass it, so the index is rebuilt with the file. A caller that did not touch the `.gz` keeps `force=False`, so a good index is not rebuilt on every start-up. A forced rebuild also deletes the old index before it starts, so a rebuild that fails cannot leave a stale index for the next start-up to accept as good — which would have brought this finding back behind an error from an earlier run. Still open in the original ROBIN.

> **VAR-4** HIGH · **Confirmed**: The report says "No pathogenic variants" when ClinVar annotation never ran.

- **Where:** `reporting/sections/variants.py:229-246, 306-335`, `target_analysis.py:3891-3940`
- **What's wrong:**
  - If the ClinVar DB is missing or SnpSift fails, plain snpEff output is copied to `snpsift_output.vcf`, and the report reads that as "annotated, none found".
  - The file is also truncated before each re-annotation.
- **Fix:** write atomically, store an annotation-status marker, and have the report say "ClinVar annotation unavailable".

> **VAR-5** MEDIUM · **Confirmed**: Failed ClairS-TO regions are skipped silently.

- **Where:** `target_analysis.py:3549-3704`
- **What's wrong:**

- A container that fails (including an OOM kill, exit 137) only logs a warning, and the merge reports "completed successfully for all regions".
- Failed containers are never removed.
- Docker and snpEff have no timeouts.

VAR-6 LOW · **Confirmed**: VCF→CSV uses the first variant as the header row.

- **Where:** `target_analysis.py:4143-4165`, `gui/components/coverage.py:3913-3933`
- **Effect:** the SNP/INDEL counts are one low, and a VCF with a single variant shows 0.

VAR-7 HIGH · **Confirmed**: `robin add-panel` keeps only the first region of each gene.

- **Where:** `cli.py:957`
- **What's wrong:** `drop_duplicates(subset=['gene'])` drops every later exon or tile of a gene. In the test, a panel with 3 EGFR rows and 2 TP53 rows became 2 rows. Coverage, SNP calling and fusion detection then ignore the dropped regions.
- **Status:** fixed in our fork (`1c8e95f`). The dedupe key is the whole region (`chrom`, `start`, `end`, `gene`), so every distinct region survives and an exactly repeated row still collapses. The second problem the reproduction script showed, under no finding ID — `read_csv` is given six column names, so an 8-column BED shifts every field and the function fails on `int('EGFR')` — is fixed too (`5af0a47`). It was worse than an error: a BED12 panel passed, printed "added successfully", and was saved as columns 7–10. The BED is now read line by line like the validator, keeping the first 4 columns. Still open in the original ROBIN.

VAR-8 HIGH · **Confirmed (reproduced)**: Reference-only samples are summarised as having pathogenic variants. *(IR-01)*

- **Where:** `analysis/lightweight_gene_analysis.py:904-933, 1451-1488`, `gui/components/coverage.py:5290-5310`
- **What's wrong:** Every covered ClinVar site in a region is counted as "found", even when its own evidence says `alternate_support=0, evidence_level="no_support"`. `export_json` then sets `pathogenic_status="present_with_good_coverage"` once coverage reaches 10 reads. The GUI's gene table and the HTML report (line 1233) show that status.
- **Reproduced:** 20 reads with only the reference C at a pathogenic C>T site. The pileup correctly shows zero alternate reads, but the summary reports one gene with pathogenic variants.
- **Fix:** keep "known site checked" separate from "variant supported". Base positive statuses and counts only on alternate-read evidence, and keep explicit "insufficient evidence" states.
- **Status:** fixed in our fork (`aeb5339`): a site counts with 3 or more alternate reads; 1–2 reads, an indel or multi-base change, or reads showing neither allele give "insufficient evidence" (`e5527a3`), and so does an SNV site with no usable bases, e.g. every read deleted there (`b26c410`), and a ClinVar site no read covers (`65ab945`), which used to drop out before export, so a gene whose only site had no reads vanished from the results. The unused HTML report (`generate_report`, no callers) still uses the old counting. Still open in the original ROBIN.

VAR-9 CRITICAL · **Confirmed (reproduced; spot-checked)**: A missing BAM for sample A falls back to sample B's BAM. *(IR-02)*

- **Where:** `analysis/lightweight_gene_analysis.py:1562-1605, 1665-1677, 1710-1730`; called from `gui/components/coverage.py:5882-5932, 6012-6069`
- **What's wrong:** If `<work>/A/igv/igv_ready.bam` is missing, the handler walks the whole work directory (`os.walk`) and takes the first `igv_ready.bam` it finds, from any sample. It then saves the result under A. The BED fallback searches the same way. The GUI enables the action based on A's `target.bam`, so this is reachable from the GUI.

- **Reproduced:** A has a reference-only BAM but no IGV BAM; B's IGV BAM has 20 alternate reads. A's results file contains B's 20 alternate reads.
- **Fix:** resolve the sample folder once and look only inside it. A missing input must give an explicit "not available" result. Record which BAM was used in the result.
- **Status:** fixed in our fork (`b9ffef8`, `d0e1975`). A missing input raises an error naming the expected path, which the GUI shows; results record `input_bam` and `input_bed`; older results files are not shown. When both result locations hold a trusted file, the newer one is shown (`f3f29cd`), and the panel's status timer stops when a run ends (`6acc03d`). Still open in the original ROBIN.

> **VAR-10** MEDIUM · **Confirmed (reproduced)**: Several BED intervals with the same name are reduced to the first one. *(IR-09)*

- **Where:** `analysis/lightweight_gene_analysis.py:656-671, 676-698`
- **What's wrong:** Regions are grouped by name, and one pileup is run over the first interval's coordinates, so variants in a gene's later exons are dropped. This happens even when the BED on disk keeps every interval (unlike VAR-7).
- **Reproduced:** two `TEST` intervals, each with a supported pathogenic site; only the first site is reported.
- **Fix:** key regions by coordinates, analyse each interval, then group results by gene name.
- **Status:** fixed in our fork (`20ea771`). Overlapping intervals are merged before the pileup. Still open in the original ROBIN.

Fusions

> **FUS-1** MEDIUM · **Confirmed (simulated)**: Master-BED SV breakpoints almost never reach the support threshold.

- **Where:** `fusion_work.py:1670-1672, 1775-1855`
- **What's wrong:** Reads are keyed by the midpoint of the whole alignment. The supplementary span is taken as `pos + query_length`, which is 1-based and covers the whole read. Supplementary records also pair with themselves.
- **Simulated:** 5 to 50 reads through one junction never put 3 or more reads in the same key, so zero breakpoints were written.

> **FUS-2** MEDIUM · **Confirmed**: The breakpoint BED is keyed to the CNV counter, so earlier breakpoints are dropped.

- **Where:** `fusion_work.py:3072-3090, 3879-3913, 4265-4272`, `master_bed_generator.py:85-115, 1073`
- **What's wrong:** Fusion reads `master_bed_breakpoints_{cnv_counter}.bed`, and the counter moves on almost every batch. So each new file holds only the new breakpoints, and earlier SV regions fall out of the dynamic targets.

> **FUS-3** MEDIUM · **Confirmed (deletion); Plausible (double append)**: Fusion accumulation has no lock and deletes staging files that failed to load.

- **Where:** `fusion_work.py:2175-2437`
- **What's wrong:** That BAM's fusion reads are lost. With `analysis_workers > 1`, supporting reads can be counted twice.

Target coverage, read counts and SNP input

> **TGT-1** **HIGH** · **Confirmed (reproduced; spot-checked)**: BAMs that arrive before the coverage threshold never reach the SNP input. *(IR-11)*

- **Where:** `analysis/target_analysis.py:1839, 1855-1890, 1999-2010`; batch entry at `2183-2223`; final merge at `2631-2658`
- **What's wrong:** Filtered batch BAMs are only made once some panel target passes `callthreshold`. Until then, coverage is still added up and the staged source BAM references are deleted. When a later batch passes the threshold, only that batch's BAMs are filtered, and the earlier ones are never revisited.
- **Reproduced:** three BAMs with one read each, where the third crosses the threshold. Coverage includes all three reads, but the batch BAM holds only the third. This needs only one worker, with no restart or timeout.
- **Fix:** filter and keep each BAM's panel reads when it arrives. Apply the threshold at calling time.
- **Status:** fixed in our fork (`d6c87ff`, `24ebbc8`): every BAM's records in the panel (plus the master BED's regions) go to a batch BAM when it arrives, with `samtools view -L`; the call threshold still decides when SNP calling may run. The final merge keeps what `target.bam` already holds, and its header lists the batch BAMs merged in, so a crash can't merge one twice. Found while fixing it: a second finalize deleted every new batch BAM unmerged. `target.bam` now holds the records overlapping the regions, not every record of a read whose primary overlaps. Still open in the original ROBIN.

> **TGT-2** **HIGH** · **Confirmed (reproduced)**: The CNV-generated master BED can replace the panel with breakpoint-only targets. *(IR-10)*

- **Where:** `analysis/cnv_analysis.py:1028-1039, 1730-1743`, `master_bed_generator.py:950-974, 1102-1129, 1187-1207`, `target_analysis.py:1860-1864`
- **What's wrong:** `cnv_handler` receives the panel, but the CNV save path looks it up only from fusion metadata. With fusion disabled, or before its metadata exists, it passes `target_panel=None`. The master BED is then written with CNV breakpoints but without the panel, and target extraction prefers it over the configured panel. A later call with the right panel reuses the incomplete file, because the file already exists for that counter.
- **Reproduced:** a `demo` panel on chr1 with breakpoints on chr2: the master BED holds only chr2, and a panel read filters to zero reads.
- **Fix:** pass the panel explicitly from the handler. Always include the configured panel in extraction targets, and include the panel's identity in the cache key.
- **Status:** fixed in our fork (`063398d`, `d6c87ff`): `cnv_handler` passes its panel down to the master BED, and target extraction always reads the panel plus the master BED's regions. The cache key is unchanged: with the panel always included, a master BED written without it no longer costs reads. Still open in the original ROBIN.

> **TGT-3** **MEDIUM** · **Confirmed (reproduced; spot-checked)**: "Global coverage" adds up breadth across BAMs instead of measuring depth. *(IR-03)*

- **Where:** `analysis/target_analysis.py:1146-1148, 1817-1819`, `gui/components/coverage.py:6654-6679`, `reporting/sections/coverage.py:70-85`
- **What's wrong:** `covbases` (positions covered at least once) is summed per BAM, then divided by the genome length. Breadth doesn't add up across files, so the number depends on how the reads are split into BAMs.
- **Reproduced:** 10 reads over one of two 100-base contigs, so the true depth is 5×. As one BAM it reports 0.5×; as two BAMs, 1.0×.
- **How much it matters:** small early in a run, when reads in one BAM rarely overlap. Larger where they do.
- **Fix:** add up aligned bases (or length-weighted `meandepth`) for depth, and track breadth separately.
- **Status:** fixed in our fork (`d6c87ff`, `d752ce6`): each BAM gives its aligned bases per contig and per target (`bedcov -j`: deletions don't count, as in `samtools coverage`), and covered bases come from a union of

covered stretches kept per sample. The GUI and the report show mean depth, and a target's length is end − start. Equal to samtools on all reads together, however they are split (`ee2fdd8`). A folder written before shows covered bases as not available. Known limit: the single "target coverage" number sums bases and lengths over panel rows, so where rows overlap (the AML panel has 270 overlapping rows, rCNS2 none) the overlap counts twice, as before; each target's own depth is exact. Still open in the original ROBIN.

TGT-4 MEDIUM · **Confirmed (reproduced)**: Two target accumulations at the same time overwrite each other's coverage. *(IR-04)*

- **Where:** `analysis/target_analysis.py:1792-1814, 1906-1934, 1999-2010`
- **What's wrong:** The lock is released between reading the old totals and writing the new ones. Two workers can read the same totals, and the second write replaces the first. Both report success and delete their staged files.
- **Reproduced:** two one-read BAMs in parallel give a total of 100 bases instead of 200. A single target worker avoids this.
- **Fix:** read, update and write the totals inside one locked step, and track which batches have been committed.
- **Status:** fixed in our fork (`d6c87ff`): one locked step reads the totals, adds the batch and writes every file atomically, and a staged BAM is claimed only once all its files exist. Two processes at once now give samtools' numbers. Committed batches aren't tracked: a batch whose worker dies after claiming it is lost, not counted twice (recovering it is left for later). Still open in the original ROBIN.

TGT-5 MEDIUM · **Confirmed (reproduced)**: Supplementary alignments are counted as extra reads. *(IR-07)*

- **Where:** `analysis/bam_preprocessor.py:352-386, 809-838`, `master_csv_manager.py:172-211`
- **What's wrong:** The "primary alignments only" check excludes secondary records but not supplementary ones. So read counts, yield and length summaries are inflated for split reads. The same counts feed the 50,000-read gate, so a BAM can be skipped as "too large" too early (traced in code, not reproduced).
- **Reproduced:** one 4-base read with one supplementary alignment is counted as 2 mapped reads and 8 bases.
- **Fix:** count reads and yield on primary records only, and keep a separate counter for supplementary alignments.
- **Status:** fixed in our fork (`7773e2f`): mapped and unmapped reads, bases, the pass/fail splits and yield count primary records only, and equal `samtools view -c -F 0x904` and `samtools stats`; `supplementary_reads` still counts the rest. The "has MGMT reads" flag also looks at primary records only. Still open in the original ROBIN.

---

4. Scheduling and job handling

JOB-1 CRITICAL · **Confirmed (spot-checked)**: One global waiting slot per classifier type.

- **Where:** `workflow_ray.py:998-1000, 2462-2535, 2807-2871`
- **What's wrong:** Classification is limited to one running job per type, plus one waiting job per type for all samples. If the slot is taken, a new request is dropped with no else branch.
- **Reproduced:** with samples A and B, Sturgeon ran for A twice and never for B.
- **Fix:** keep a "dirty" flag per (sample, type), and run dirty samples round-robin.

JOB-2 HIGH · **Confirmed**: The same BAM can be processed twice.

- **Where:** `workflow_ray.py:4949-4977, 4116, 4155-4160, 4510-4551`

- **What's wrong:** The start-up scan doesn't add files to the watcher's dedup set. `add_watch_path` starts watching before it scans. There is no per-file record across restarts (`SQLiteStateTracker` exists but has no callers). Methylation counts, CNV and `master.csv` totals all just add up.
- **Effect:** a restart with the same `--work-dir` counts everything twice.
- **Fix:** keep a persistent per-file ledger, and share one dedup set.

> **JOB-3** HIGH · **Confirmed**: A failed handler runs again without `work_dir`, `reference` or `target_panel`.

- **Where:** `workflow_ray.py:704-742`
- **What's wrong:** The `try` wraps the handler call itself, so any exception falls through to the legacy `py_handler(job)`. The handler then runs a second time, writes output next to the BAM (inside the MinKNOW folder), and the real error is replaced by "target_panel is required".
- **Fix:** bind the arguments first, then call the handler once.

> **JOB-4** HIGH · **Confirmed (flush and ordering); Plausible (partial files)**: The watcher delays or loses files.

- **Where:** `workflow_ray.py:4117-4193, 5020-5030`
- **What's wrong:**
  - The pending buffer only flushes when a new file arrives, and there is no timer, so the last file(s) of a run may never be analysed.
  - The flush at shutdown happens after the coordinator has stopped.
  - Submit errors are swallowed after the file has been marked processed.
  - There is no check that a file is complete, so a BAM copied in with `cp` or `scp` can be read truncated.

> **JOB-5** HIGH · **Confirmed**: Repeat SNP requests are silently skipped while the UI says "queued".

- **Where:** `workflow_ray.py:1730-1737, 2991-2997, 2363-2367`
- **What's wrong:** The dedup counter is never decremented (`mark_running` has no callers), so after the first `snp_analysis` for a sample, every rerun is dropped.

> **JOB-6** HIGH · **Constant confirmed (spot-checked); impact Plausible**: The 60-second idle timeout is a test value.

- **Where:** `gui_launcher.py:420, 927-934, 7406, 7424-7426`, `target_analysis.py:2604-2618`
- **What's wrong:**
  - The code still says `completion_timeout_seconds = 60  # Set to 3600 for production`.
  - A gap of 60 s or more between BAMs marks the sample Complete and finalises it. Later SNP runs then skip the merge and use the old `target.bam`.
  - After a restart, unmerged batch BAMs are deleted.
- **Status:** partly fixed in our fork (`c4592a0`, `b23ef4f`): only the first bullet. The default is 3600 s, and `ROBIN_COMPLETION_TIMEOUT_SECONDS` overrides it (unset, empty, non-integer or below 1 all mean 3600, because finalisation deletes unmerged batch BAMs). The second and third bullets describe what happens *when* the timeout fires, overlap JOB-7 and are not fixed: a later SNP run still skips the merge once a sample is finalised (`gui_launcher.py:7406, 7424-7426`), and unmerged batch BAMs are still deleted when `target.bam` already exists (`target_analysis.py:2604-2618`). Still open in the original ROBIN.

> **JOB-7** HIGH · **Double run Confirmed; corruption Plausible**: `target.bam` finalisation runs twice.

- **Where:** `gui_launcher.py:7422-7512`
- **What's wrong:** `finalization_succeeded` stays True after the Ray job is queued, so the GUI also runs the finalisation inline. The two copies delete each other's temp and batch files.
- **Fix:** run the inline finalisation only when the submit fails, and add a per-sample lock.

JOB-8 MEDIUM · **Confirmed**: Files submitted by the watcher have no `reference` in their metadata.

- **Where:** `workflow_ray.py:4155-4185` vs `3756-3771`
- **What's wrong:** Files found at start-up get the reference and target panel; files that arrive later don't. So mgmt, target, CNV and fusion behave differently depending on when a BAM appeared.

JOB-9 MEDIUM · **Confirmed (opt-in setting)**: A job timeout releases its pool slot twice.

- **Where:** `workflow_ray.py:3575-3599` vs `3527-3534`
- **What's wrong:** With `ROBIN_JOB_TIMEOUT_SECONDS` set, each timeout adds a phantom slot, so a pool limited to 1 job runs jobs at the same time.

JOB-10 MEDIUM · **Plausible**: Shutdown kills jobs mid-write and drops waiting jobs.

- **Where:** `workflow_ray.py:3281-3363, 5020-5054`
- **What's wrong:** A Ctrl-C during a CNV save leaves a truncated pickle, and the next start silently resets the CNV history.

JOB-11 MEDIUM · **Confirmed**: The default Ray path ignores several CLI options.

- **Where:** `cli.py:2419-2537`
- **What's wrong:** `--no-gui`, `--commands`, `--deduplicate-jobs`, `--queue-priority` and `--show-priorities` have no effect. For example, `--show-priorities` starts a full run, and `--no-gui` still opens the GUI.

JOB-12 LOW · **Plausible**: Race conditions when `analysis_workers > 1`.

- **What's wrong:** MGMT's `mgmt.bam` accumulation and file numbering have no lock, and neither does the panel filter cache pickle. The default of 1 worker avoids this.

JOB-13 LOW · **Confirmed (latent)**: All job types for a file share one context object.

- **Where:** `workflow_ray.py:2554, 2947-2964`
- **What's wrong:** `_batched_job` is overwritten by each type's batch. This is harmless today only because every type's batch holds the same files.

---

5. Errors that never reach the user

This is why "Error processing file" showed up in the backend log but never in the GUI.

ERR-1 HIGH · **Confirmed**: Errors are lost at five layers.

- **Where:** `workflow_ray.py:3515-3521, 801-809, 4733-4928, 755`
- **Layer by layer:**
  1. The merge swallows per-file errors and reports success (METH-9).
  2. Handlers record errors under `"<type>_analysis"`, but the Pool only checks the `job_type` key, and the `finally` block adds `{"status": "success"}`. So **for 8 of 13 job types, a failed job counts as completed**: it isn't in `failed_jobs.csv` or in the failed count.
  3. `_publish_gui` sends only counts. Nothing ever sends `ERROR_UPDATE`, even though the GUI has handlers for it.
  4. `send_gui_update` calls from inside Ray workers find no GUI in that process and are dropped. This includes BAM alignment warnings such as "unaligned BAM" or "<1% mapped".

5. The TypeProcessor path (preset `high`) has no error detection at all.

- **Fix:** treat any `add_error` during a job as a failure, return per-file failures from the merge, forward failures from the driver to the GUI, and route worker notifications through the Coordinator.

> **ERR-2** MEDIUM · **Confirmed**: Import failures are swallowed and reported with the wrong cause.

- **Where:** `analysis/__init__.py:15-97`, `cli.py:55-81`, `workflow_ray.py:124-200`, `nanodx_analysis.py:24-38`, `temp_utilities.py:30-34`
- **Example:** a Sturgeon API change makes every Sturgeon job fail with "No implementation available for job_type='sturgeon'", with no reason given.
- **Missing submodules:** an empty submodule folder isn't detected.
- **Fix:** import lazily per job type, and print every import error at start-up.

> **ERR-3** · **Confirmed**: The codebase has 1,325 broad `except Exception` or bare `except` blocks, and 404 of them do nothing but `pass` or `continue`.

---

6. GUI

> **GUI-1** CRITICAL · **Confirmed (spot-checked)**: The classification panel stops updating when any classifier is disabled.

- **Where:** `gui/components/classification.py:1003-1021`
- **What's wrong:** The loop goes over all four tools in `tool_to_file`, but `charts` only has entries for the enabled ones. So `charts['PanNanoDX']` raises KeyError on every tick after the first. The panel keeps showing the first result, while the summary card moves on.
- **Fix:** in both loops of `_refresh_classification` (lines 1003-1008 and 1019-1021), loop over `charts` instead of `tool_to_file`, or skip tools that aren't in `charts`. The third loop (1041-1047) is already guarded.
- **Status:** fixed in our fork (`50da100`). The mtime scan moved into a module-level `classification_files_to_refresh` keyed by the tools present in `charts`, and the update loop and the log line iterate `charts` too, so a run with a classifier disabled keeps refreshing. Still open in the original ROBIN.

> **GUI-2** CRITICAL · **Confirmed (against NiceGUI 3.6 source)**: A brief websocket drop permanently stops every refresh timer.

- **Where:** `summary.py:352`, `classification.py:1068`, `coverage.py:6917`, `mgmt.py:721`, `cnv.py:2467`, `fusion.py:3421`, `mnpflex.py:860`, `bed_coverage.py:456`
- **What's wrong:** Every component calls `timer.deactivate()` in `on_disconnect`, which in NiceGUI 3 also fires on reconnect, and nothing reactivates the timers.
- **Effect:** after a Wi-Fi blip, laptop sleep or proxy timeout, the page shows hours-old results.
- **Fix:** use `client.on_delete`.
- **Status:** fixed in our fork (`7ff93b1`). All nine call sites use `client.on_delete` — the eight above plus `gui_launcher.py:5130`, which has the identical defect and is not listed here. The six theme-sync unregisters in those callbacks were the same bug class and are fixed with them. The trade: a page that really was closed is torn down up to 60 s later, after ROBIN's `reconnect_timeout`. No test proves a timer survives a real reconnect; `tests/test_gui_timer_cleanup.py` is lint-shaped. Still open in the original ROBIN.

> **GUI-3** HIGH · **Confirmed (MGMT simulated)**: A second viewer of the same sample misses updates.

- **Where:** `mgmt.py:388-405`, `cnv.py:1989-2010`, `coverage.py:6497-6531`, `gui_launcher.py:491-499`

- **What's wrong:** The "last seen mtime" markers live on the one shared `GUILauncher`. The first browser to see a new file records it, and the others then think nothing changed.
- **Reproduced:** after a new batch, browser A showed "Methylated" and browser B still showed "Unmethylated".

GUI-4 HIGH · **Confirmed (spot-checked)**: The CNV summary card shows the batch counter as "Gained".

- **Where:** `summary.py:1245-1292`
- **What's wrong:** It reads `cnv_analysis_counter.txt` as the number of gains. After 37 batches the card says "Gained: 37, Lost: 0" for every sample. The other files it looks for are never written.
- **Status:** fixed in our fork (`e677991`). The counter file has left the candidate list, and `gained` / `lost` default to `None`, which the card renders as "Not available" — the idiom it already uses for genetic sex, bin width and variance. Because nothing in `src/` writes a per-sample gain/loss count, that is what every sample now shows; a real `cnv_results.csv` would still supply real counts. Still open in the original ROBIN.

GUI-5 HIGH · **Confirmed (by reading)**: Per-page state is shared by all browsers.

- **Where:** `gui_launcher.py:2396, 2732, 3155-3163, 7289-7317`
- **What's wrong:** The sample table, selection and filters are stored on the singleton.
- **Example:** user B opening `/live_data` clears user A's selection, so A's Export gives B's samples.

GUI-6 MEDIUM · **Confirmed (path); race Plausible**: The GUI rewrites analysis output files.

- **Where:** `summary.py:1612-1626` → `fusion.py:307-404`, `mgmt.py:594-603`
- **What's wrong:** Every 30 s, for each browser, it rewrites `fusion_summary.csv`, `fusion_results.csv` and `sv_count.txt` non-atomically, using its own counting method. MGMT also overwrites `{N}_mgmt.pkl`.
- **Fix:** make the GUI read-only over sample folders.

GUI-7 MEDIUM · **Confirmed**: The summary card and the coverage panel use different coverage thresholds.

- **Where:** `summary.py:1180-1187` vs `coverage.py:6681-6699`
- **Example:** at 12× the card says "Moderate" while the panel says "Low".

GUI-8 MEDIUM · **Confirmed**: The GUI fusion check uses a different minimum support.

- **What's wrong:** It re-validates with min_support=4, while the analysis and `fusion_summary.csv` use 3. So the summary and the fusion tab can disagree.

GUI-9 LOW · **Confirmed**: The MGMT card's CpG count says "Not available" or is wrong.

- **Where:** `summary.py:1338-1388`
- **What's wrong:** The helper is defined in one branch only, so the other branch hits a NameError.

GUI-10 LOW · **Confirmed**: The "global" theme and metrics timers die with the first client.

- **Where:** `theme.py:127-134, 437-443`
- **What's wrong:** They are bound to the first client. Also, other users' charts follow the first user's dark-mode setting.

---

7. PDF report

REP-1 HIGH · **Confirmed (spot-checked)**: Random Forest confidence uses the default cut-offs.

- **Where:** `reporting/sections/classification.py:399`
- **What's wrong:** It looks up `"random forest"`, but the key is `"random_forest"`, so the default 80/50 is used instead of 85/65. At 82%, the PDF says "High" and the GUI says "Medium".
- **Fix:** map display names to config keys, and raise an error on an unknown classifier.
- **Status:** fixed in our fork (`229247f`, `f50ad61`). `classification_config` gained `CLASSIFIER_DISPLAY_NAMES` and `config_key_for_classifier()`, which resolves a display name to its key and raises on an unknown one; the report's one call site goes through it, so 82% bands as "Medium" in both the PDF and the GUI. `get_confidence_status` itself stays permissive, because `summary.py` passes section anchors ("coverage", "cnv", "mgmt", "fusion") that need the default fallback. Still open in the original ROBIN.

REP-2 HIGH · **Confirmed**: CNV gene counts and plot selection use an old ±1 SD rule.

- **Where:** `reporting/sections/cnv.py:122-160, 580-620, 988-1005`
- **What's wrong:** The GUI switched to fixed thresholds; the report still uses the old rule.
- **Reproduced:** on a CNV-neutral genome, the report listed 20 "gained" and 17 "lost" genes and plotted all 23 chromosomes, while its own events table was empty.

REP-3 HIGH · **Confirmed**: The fusion table shows the weakest breakpoint cluster.

- **Where:** `reporting/sections/fusion.py:249-262`
- **What's wrong:** The last row wins, and the rows are sorted strongest first. For example, KIAA1549-BRAF shows a 4-read cluster in the PDF, while the CSV export shows 25 reads.

REP-4 HIGH · **Confirmed**: Gene pairs are split on "-", which breaks hyphenated genes.

- **Where:** `reporting/sections/fusion.py:53, 121-127, 254, 561`
- **What's wrong:** Names like `EGFR-AS1` and `H3-3A` get cut in two. For example, EGFR-SEPTIN14 becomes the network "EGFR,EGFR - AS1", and SEPTIN14 disappears.
- **Fix:** carry gene1 and gene2 as separate fields.

REP-5 HIGH · **Plausible**: Report plotting shares global matplotlib state with GUI threads.

- **Where:** `reporting/plotting.py:340-430`, `analysis/methylation_wrapper.py:13-25, 256-293`
- **What's wrong:** The report uses pyplot's global state in a NiceGUI worker thread, while the GUI's MGMT refresh monkeypatches `Figure.savefig` process-wide.
- **Effect:** a plot can be swallowed, or another figure (possibly another sample's) embedded.
- **Fix:** use the object-oriented `Figure` API, or run report generation in a subprocess.

REP-6 MEDIUM · **Confirmed**: Missing fusion data is reported as "No fusion networks identified".

- **Where:** `reporting/sections/fusion.py:133-197, 425-441, 640-645`
- **What's wrong:** "Not run", "unreadable" and "none found" all print the same negative result. The methods text also states different thresholds from the code (>50 vs >49, >200 bp vs >249 bp).

REP-7 MEDIUM · **Confirmed**: CNV plot y-limits hide focal amplifications.

- **Where:** `reporting/plotting.py:264-267, 297, 356-357, 420`

- **What's wrong:** The limit is mean + 2 SD. An EGFR amplification at about 30 copies falls off the axis (the limit is about 8.6).

> **REP-8** MEDIUM · **Confirmed**: At low CNV resolution, the section crashes after half the summary is built.

- **Where:** `reporting/sections/cnv.py:689-723, 805`
- **What's wrong:** `events` is unbound, so the summary shows the CNV heading with no events and no "resolution insufficient" note.

> **REP-9** MEDIUM · **Confirmed**: A coverage file being written can abort the whole report.

- **Where:** `reporting/sections/coverage.py:28-31, 55-113`, `report.py:59-67, 142-144`
- **What's wrong:** The coverage CSVs are read in the constructor, outside the per-section error handling.

> **REP-10** MEDIUM · **Plausible**: The report reads live, non-atomic files with no snapshot.

- **Where:** `reporting/sections/cnv.py:418-433, 492-496`, `reporting/sections/classification.py:339-413`
- **What's wrong:** CNV.npy, CNV_dict.npy and CNV2.npy can come from different iterations. A stale `PanNanoDX_scores.csv` from an earlier configuration can appear in the PDF but not in the GUI.

---

8. Security and privacy

> **SEC-1** CRITICAL · **Confirmed (spot-checked)**: The Ray dashboard and Jobs API listen on 0.0.0.0 by default, with no authentication.

- **Where:** `cli.py:2435-2449, 1725-1731, 2302-2306`, `workflow_ray.py:5161`
- **What's wrong:** Anyone on the network can POST a job to `http://<host>:8265/api/jobs/` and run shell commands as the ROBIN user, with access to all BAMs and reports. This is the ShadowRay / CVE-2023-48022 class of issue.
- **Fix:** default to `127.0.0.1` and make the dashboard opt-in.
- **Status:** fixed in our fork (`3623e93`). Still open in the original ROBIN.

> **SEC-2** HIGH · **Confirmed**: MNP-Flex TLS verification is hard-coded off.

- **Where:** `gui_launcher.py:7180, 7225-7231`, `gui/components/mnpflex.py:92-147, 829-855`, `utils/mnpflex_client_standalone.py:34`
- **What's wrong:**
  - The credentials (the `client_secret` defaults to `"SECRET"`) and the patient methylation BED are sent without certificate checks, and the downloaded classification is shown as a result.
  - The upload starts automatically, once per open tab.
  - On failure, patient data is left on the third-party server.

> **SEC-3** HIGH · **Confirmed (reproduced)**: Partial model downloads are kept and accepted.

- **Where:** `utils/model_updater.py:121-152, 290-306`, `utils/model_checker.py:181-187`
- **What's wrong:** Downloads stream straight to the final filename, and the start-up check only tests `size > 0`. The models are pickles, so a swapped file means code execution.
- **Fix:** download to `.part`, verify the SHA-256, rename, and re-verify at start-up.

SEC-4 MEDIUM · **Confirmed**: The GUI listens on 0.0.0.0 over plain HTTP.

- **Where:** `cli.py:2284-2289`, `gui_launcher.py:535-546, 1845-1863, 2122-2131`
- **What's wrong:**
  - `storage_secret="robin"` is a constant.
  - Logins aren't throttled, and the argon2 check runs on the event loop.
  - There is an open redirect via `redirect_to`.
  - The "local client" check trusts the Host header.

SEC-5 MEDIUM · **Mechanism Confirmed; exploit Plausible**: The auth middleware lets some routes through without checks.

- **Where:** `gui_launcher.py:549-553, 2113-2117`
- **What's wrong:**
  - `/_nicegui*` and `/api/v1/*` are exempt, and `ui.download` URLs are predictable.
  - `/api/download/{sample_id}/{filename}` accepts `..` (one level up).

SEC-6 MEDIUM · **Confirmed**: Patient identifiers can be decrypted from the date of birth alone.

- **Where:** `gui_launcher.py:98-131, 8788-8806, 4407-4431`, `reporting/report.py:193-204`
- **What's wrong:**
  - The key comes from PBKDF2(DOB, fixed salt). That is about 36,500 possible keys, which takes about 20 s on a 72-core server.
  - The sample ID is an unsalted MD5, and it is sent to MNP-Flex.
  - PDFs with plaintext identifiers are left in the sample folder.

SEC-7 MEDIUM · **Plausible**: About 30 sites load pickles from results folders.

- **Examples:** `gui/components/summary.py:1221`, `reporting/sections/cnv.py:433`, `fusion_work.py:2601`
- **What's wrong:** Opening a results folder, or building a PDF from one, received from someone else can run code.

SEC-8 HIGH · **Confirmed (reproduced; spot-checked)**: MGMT runs the sample folder path through the shell. *(IR-08)*

- **Where:** `analysis/mgmt_analysis.py:836-838`; called at lines 1081 and 1393. Sample IDs come from BAM read-group metadata (`bam_preprocessor.py:260-275`).
- **What's wrong:** The Rscript command is built as one f-string with `sample_dir` and other paths unquoted, and run with `subprocess.run(cmd, shell=True)`. A sample ID becomes part of that path with no shell-safe handling.
- **Reproduced:** a sample folder named with a harmless `$(touch …)` marker. Running the real MGMT command path creates the marker file, so the shell ran it. A space in any path also splits the arguments and breaks MGMT.
- **Fix:** pass an argument list with `shell=False`. Separately, validate sample IDs before using them in paths.
- **Status:** the shell call is fixed in our fork (`2d3577e`, `0873744`). Sample IDs are not validated yet. Still open in the original ROBIN.

SEC-9 MEDIUM · **Confirmed (tested)**: Watched file names are pasted into the operator's shell command. *(Found 2026-10-30, while planning the fix for SEC-8.)*

- **Where:** `watcher.py:116` (`FileChangeHandler._run_command`) and `workflow_simple.py:1756` (`command_handler`, used by `--commands`).

- **What's wrong:** Both do `template.replace("{file}", path)` and run the result with `shell=True`. The template is the operator's own command, so a shell is intended, but the file name comes from the watched folder. A file named `a;rm -rf ~.bam` runs `rm`.
- **Tested:** with the old code, file names containing `$(touch …)` created the marker file, in bare, `"{file}"` and `'… {file} …'` templates.
- **Fix:** keep the shell, but never paste the name into the command text. Turn `{file}` into a quoted `$ROBIN_FILE` reference and pass the path in the environment. Quoting the name with `shlex.quote` is not enough: inside a longer double-quoted string such as `"{file}.bai"` it can still run. Templates that start a second shell (`sh -c "… {file}"`, `ssh host "…"`) re-parse the name there; document that.
- **Status:** fixed in our fork (`4f26cf0`, `75485ce`). A quoted `{file}` inside `$(...)` is quoted for that inner context and stays one word (`ab5151b`). Still open in the original ROBIN.

---

9. Packaging, dependencies, tests

> **PKG-1** HIGH · **Confirmed**: Builds aren't reproducible.

- **Where:** `pyproject.toml:38-40, 48, 55`, `target_analysis.py:3274, 3581`
- **What's wrong:**
  - `sturgeon@…@testing` tracks a moving branch.
  - `methylartist` has no git ref at all.
  - torch, polars, pyranges and ray are unpinned, and there is no lockfile.
  - ClairS-TO is pulled as `:latest`.
  - The GUI's CrossNN version lookup uses a path that doesn't exist, so it always shows "unknown".
- **Effect:** a report can't say which classifier or caller code produced it.

> **PKG-2** MEDIUM · **Confirmed**: There are no tests and no CI for code on `main`.

- **What's wrong:**
  - pytest's `tests/` folder holds only the two tests added after this review (`tests/test_temp_utilities.py`).
  - CI only builds the docs, on Python 3.11.
  - The mypy and black configs still target Python 3.8.

> **PKG-3** MEDIUM · **Confirmed**: Python 3.13+ installs fail.

- **Where:** `pyproject.toml:21`
- **What's wrong:** `requires-python = ">=3.12"`, but numpy 1.26, pandas 2.1.4 and pyarrow 16.1 have wheels only up to 3.12, and sturgeon@testing requires ≤3.12.
- **Fix:** add `<3.13`.
- **Status:** fixed in our fork (`43db1df`). Still open in the original ROBIN.

> **PKG-4** MEDIUM · **Confirmed**: Unpinned polars and pyranges are already causing problems.

- **What's wrong:**
  - `pl.StringCache` gives a deprecation warning on polars 2.0 (`temp_utilities.py:283`).
  - `ncls` is imported but not declared (`fusion_work.py:43`).
  - PyRanges objects are pickled into the sample folders.

PKG-5 MEDIUM · **Confirmed**: Resource files and the gitignore need cleaning up.

- **What's wrong:**
  - About 113 MB of unused or duplicate resources ship in every wheel. Examples: a 45 MB gencode GFF, two 20.6 MB MNP-Flex BED variants, and `None_data.csv.gz`. Some are byte-identical copies.
  - `.gitignore` misses the v2 model files (340 MB).
  - `src/robin/analysis/Untitled` is tracked in git.

PKG-6 LOW · **Confirmed**: The dependency list and licence need tidying.

- **What's wrong:**
  - 10 dependencies are listed twice, about 13 are never imported, and 6 that are imported aren't declared.
  - `robin.yml` leaves numpy unpinned while pip pins `<2`.
  - The package is labelled MIT but bundles GPL-3.0 nanoDx. That one is a licence question to raise.
- **Status:** partly fixed in our fork (`43db1df`): `robin.yml` pins numpy, pandas and scikit-learn, and the duplicate scikit-learn line is gone. The other duplicates, the undeclared imports and the licence question are still open.

---

10. Architecture

- **ARCH-1: Two workflow engines that have drifted apart.**
  - `workflow_ray.py` (5.2k lines) and `workflow_simple.py` each define their own `Job`, `WorkflowContext`, batcher and watcher.
  - Their `BATCH_CONFIG` differs (CNV 20 vs 50).
  - Inside workflow_ray there are three dispatch paths, each with different error detection.
  - Per-sample state is spread over about 15 dicts.
  - JOB-2, JOB-8 and ERR-1(5) all come from this.
- **ARCH-2: God files and god functions.**
  - `gui_launcher.py` is 9.2k lines.
  - `add_coverage_section` is one 5,181-line function, `add_cnv_section` is 2,260 lines and `run_snp_analysis` is 1,233 lines.
  - `fusion_work.py` is 6.5k lines.
  - None of these can be unit-tested.
- **ARCH-3: The same logic is copied into the analysis, GUI and report, and the copies have drifted.** Examples: cytoband CNV calls, fusion clustering and validation, pathogenicity checks, confidence and coverage thresholds, MGMT site parsing. REP-1, REP-2, GUI-7, GUI-8 and METH-10 are the results.
- **ARCH-4: Lots of dead code that still gets edited.** Examples:
  - matkit's copy of `merge_modkit_files`
  - about 1,000 lines in `fusion_work`
  - about 980 lines under `if False:` in `coverage.py`
  - about 800 lines in `gui_launcher`
  - 7 of 9 functions in `reporting/plotting.py`
  - `reporting/utils.py`, which is shadowed by `reporting/utils/`
  - `SQLiteStateTracker`
  - `DISABLE_MEMORY_MANAGER = True`, which is hard-coded
  - five separate model-download implementations
- **ARCH-5: Layering runs the wrong way.**
  - The analysis code imports the GUI.

    - The workflow raises "GUI not available", so headless runs still need NiceGUI.
    - `import robin` loads torch, onnxruntime, sturgeon, pysam and the rest, for every CLI call and every Ray worker.
- **ARCH-6: File contracts are undocumented.**
    - Counter files are shared across modules (fusion and target use `cnv_analysis_counter.txt`, which is the cause of FUS-2).
    - Many writes are non-atomic, and pickles are used everywhere.
    - Coordinates, percent vs fraction, strand convention and which columns carry coverage are not written down anywhere.
- **ARCH-7: The GUI orchestrates the pipeline by polling files.** For example, a failed SNP job makes a bulk SNP queue wait up to 24 hours per sample.

---

11. Performance

ID	Problem	Measured / estimated	Where
PERF-1	Fusion GUI refresh runs an O(n^3) validation on the event loop every 30 s, and nothing reads the result	400 reads per gene pair took 21.5 s; 2,000 reads didn't finish in 10 min. The GUI freezes for all users	`gui/components/fusion.py:2736-2915, 1275-1487`
PERF-2	The MGMT timer runs methylartist inside the GUI process, on the event loop	Freezes on every MGMT batch	`gui/components/mgmt.py:550-603`
PERF-3	IGV code `time.sleep`-polls JavaScript calls that are never awaited	At least 5 s freeze on every details page load; status text is wrong	`gui/components/coverage.py:593-640, 744-1010`
PERF-4	The background scan holds a lock over all file I/O; a `ray.get(timeout=30)` runs inside an async handler	Multi-second GUI stalls with many samples	`gui_launcher.py:795-1092, 1384-1436`, `coverage.py:1639-1697`
PERF-5	The module-level `@ui.refreshable` rebuilds every client's summary	N^2 rebuilds: 5 tabs mean 75 rebuilds per 30 s	`gui/components/summary.py:64, 137, 241`
PERF-6	`stats()` waits behind busy pools	GUI stats freeze while a 30-60 min Clair3 job runs	`workflow_ray.py:3497-3498, 1309-1311, 3060-3066`
PERF-7	Each fusion batch rescans the whole-sample state and re-runs DBSCAN	O(N^2) over a run	`fusion_work.py:2675-2803, 4504-4559`
PERF-8	The per-BAM merge decodes binary columns row by row in Python, and round-trips through pandas and PyRanges	5.6 s of 11 s per 4M-row file; a vectorised `cast(pl.Utf8)` takes 0.04 s	`temp_utilities.py:223-266`, `matkit.py:992-1019`
PERF-9	BAMs are read many times (CNV 2-3×, target about 5×); ClinVar × regions is a pure-Python loop	CPU backlog at PromethION throughput	`cnv_analysis.py`, `target_analysis.py`, `lightweight_gene_analysis.py:560-612`
PERF-10	The report renders 24 per-chromosome figures at 300 dpi, then throws most away	Slow reports	`reporting/sections/cnv.py:988-1011`, `plotting.py`
PERF-11	MNP-Flex re-sends three base64 PNGs every 30 s	Constant traffic and flicker	`gui/components/mnpflex.py:722-765`

Suggested order of work

Make each step below its own change, with its own regression test. The scripts in `2026-10-16-repro/` are the starting point for those tests.

1. **Security first** *(done in our fork, with the version pins)*:
   - SEC-1: Ray dashboard on 127.0.0.1, and opt-in
   - SEC-8: MGMT command as an argument list, with no shell
   - SEC-9: pass watched file names to command templates as data
2. **Sample identity and truthful variant summaries, together** *(done in our fork)*:
   - VAR-9: only look inside the sample's own folder
   - VAR-8: count a variant only when reads support it
   - VAR-10: analyse every interval, not only the first per name
3. **Quick wins (each a few lines):** *(done in our fork; JOB-6 only in part)*
   - GUI-1: guard both loops in `_refresh_classification`
   - REP-1: the RF config key
   - JOB-6: change 60 to 3600, and make it configurable
   - GUI-4: stop reading the counter file
   - CNV-5: drop the last change point
   - GUI-2: use `on_delete`
   - VAR-3: force-rebuild the tabix index
   - VAR-7: keep all panel regions
4. **CNV-1:** build the control profile without patient reads (see CNV-1; a deepcopy alone is not enough). *(done in our fork, with CNV-3)*
5. **The methylation maths, as one change with a test against `modkit pileup --combine-strands`:** *(done in our fork, except METH-7)*
   - METH-1 and METH-2: aggregate always, and recompute % from counts
   - METH-5: semi-join, and dedupe the panel
   - METH-6: drop the `Start-1`
   - METH-3: matkit denominator
   - METH-4: combine strands
   - METH-7: pass coverage through
   - METH-13, METH-14: honour MM skip modes, and decide the QS filter per read before counting. Add MM-mode and primary/supplementary test files.
6. **Target input and coverage:** *(done in our fork)*
   - TGT-1: keep every BAM's panel reads when it arrives
   - TGT-2: pass the panel explicitly to the master BED
   - TGT-4: one locked read-update-write step
   - TGT-3: depth from aligned bases. Test that the same reads split into different BAMs give the same number.
   - TGT-5: count primary records only
7. **Make failures visible:**
   - ERR-1: failures counted, and forwarded to the GUI
   - METH-8: classifiers raise instead of logging
   - VAR-4, REP-6: "not available" instead of a negative result
8. **Scheduling state:**
   - JOB-1: per-sample dirty flags
   - JOB-2: a persistent file ledger
   - CNV-2: no worker caches, and atomic writes
   - JOB-3, JOB-4, JOB-5, JOB-7
9. **Security hardening:** SEC-2 to SEC-7.
10. **Pin and record versions** (PKG-1), **add CI with a test suite** (PKG-2), then start on the architecture items. Delete dead code first (ARCH-4), because it is cheap and stops fixes from landing in the wrong copy.

11. **Later, a feature rather than a fix:** per-base depth for the panel (a D4 file from `mosdepth`), to report the share of each gene's bases at ≥20× and to find low-coverage holes in panel genes. Today "above 30×/20×/10×" counts whole targets by their average depth.

Already done: the original "Error processing file … ['Chromosome', 'Start']" log noise is fixed on `main` (commit `d02add2`), with a test. Commit `5be9e04` adds a traceback and safe diagnostics to that log line, because one clinical server still logs it after the fix. Step 1 (SEC-1, SEC-8, SEC-9), the version pins, step 2 (VAR-9, VAR-8, VAR-10) and step 3's quick wins (GUI-1, REP-1, JOB-6, GUI-4, CNV-5, GUI-2, VAR-3, VAR-7) are done too; see "This fork and the original ROBIN". Of step 3, only JOB-6 is partial: the timeout constant and its configurability are done, the merge-skip and the batch-BAM deletion that follow from the timeout firing are not, and they overlap JOB-7. The follow-ups batch 3's own review asked for soon are done as well, and so are the five findings of the 2026-10-31 review of the fix series. Step 4 (CNV-1) is done, with CNV-3, which sits in the same loop. Step 5 (the methylation maths) is done except METH-7, with a test against modkit. Step 6 (target input and coverage, TGT-1 to TGT-5) is done, with a test against samtools.