

Index

‘Note: Page numbers followed by “f” indicate figures and “t” indicate tables’.

A

- access link, 404
 - hybrid ARQ, 408–409
- access stratum (AS), 56
- acknowledgment resource indicator (ARI), 158, 326–327
- acknowledgment resource offset (ARO), 326–327
- active antenna systems (AAS), 524–525
- additional maximum power reduction (A-MPR), 503–504, 506
- Adjacent channel interference ratio (ACIR), 511
- adjacent channel leakage ratio (ACLR), 508–510, 511f, 519–520, 523
- adjacent channel selectivity (ACS), 510–512, 511f, 515, 520–521, 524
- aggregated channel bandwidth, 492f
- aggregated transmission bandwidth configuration, 492f
- AIFS. *See* arbitration inter-frame space
- almost blank subframes, 355. *See also* reduced-power subframes
- “always-on” transmissions, 548
- antenna port, 81–82
- APT, 8
- arbitration inter-frame space (AIFS), 387
- ARIB, 7
- ATIS, 7

B

- backhaul link, 404, 407–419
 - hybrid ARQ, 409–410
 - reference signals, 415
- band categories, 498–499
- Bandwidth-reduced/low-complexity UE (BL UE), 437
- base-station class
 - base-station class, local area, 504
 - home, 505
 - medium range, 504
 - wide area, 504
- BCCH. *See* broadcast control channel
- BCH. *See* broadcast channel
- BL UE. *See* Bandwidth-reduced/low-complexity UE
- blocking, 515
 - narrowband, 515
- BM-SC. *See* broadcast multicast service center
- broadcast channel (BCH), 64, 290
- broadcast control channel (BCCH), 63

- broadcast multicast service center (BM-SC), 424
- buffer-status report, dual connectivity. *See* dual connectivity; buffer-status report

C

- C-MTC. *See* critical-MTC
- C-RNTI. *See* cell radio-network temporary identifier
- CA. *See* carrier aggregation
- CACLR. *See* cumulative ACLR requirement
- carrier aggregation (CA), 41–42, 89, 309
 - aggregation of FDD and TDD, 311
 - bandwidth class, 492–493
 - bandwidth combination sets, 493
 - channel spacing, 493
 - component carrier, 309
 - component carrier deactivation, 319–322
 - control region, 322
 - cross-carrier scheduling, 314–315
 - FDD, 312f
 - inter-band, 42–43, 310f, 491
 - intra-band, 42–43, 310f, 491
 - number of carriers, 309
 - primary cell (Pcell), 313–314
 - primary component carrier, 313–314
 - protocol structure, 312–313
 - RF aspects, 491–495
 - secondary cell (Scell), 313–314
 - secondary component carrier, 313–314
 - self-scheduling, 314
 - TDD, 310–311
 - timing, 315
- carrier raster. *See* frequency raster
- CCA. *See* clear-channel assessment
- CCCH. *See* common control channel
- CCE. *See* control-channel element
- CCSA, 7
- CE levels, 453–454
- CE mode. *See* coverage enhancement mode
- cell identity group, 286
- cell radio-network temporary identifier (C-RNTI), 73
- cell search, 285
- cell-specific reference signals (CRS), 103–107
- CEPT/ECC, 8
- channel rank, 122

channel-quality indicator (CQI), 269, 276
channel-state information (CSI), 33, 68, 210–212, 269–273
 aperiodic, 270–271
 for carrier aggregation, 328–329
 codebook. *See* PMI, codebook
 for eIMTA, 371
 interference estimation, 273–276
 periodic, 270, 273
 processes, 276, 337–345
 reporting class A, 279–281
 reporting class B, 279–283
CITEL, 8
clear-channel assessment (CCA), 395
closed subscribed group (CSG), 361–362
closed-loop precoding, 123–124
CN. *See* core network
code block, 95
code-block segmentation, 95
 uplink, 170
codebook-based precoding, 121–125
coexistence, 487
 LTE and TD-SCDMA, 88
common control channel (CCCH), 63
common search space, PDCCH, 150
common subframe allocation (CSA), 428
CoMP. *See* coordinated multi-point
COMP hypotheses, 335–345
component carrier, 41–42, 89
conducted requirements, 524–525
control region, 79–80, 130–131, 426
control-channel element (CCE), 141
 aggregation, 141–142
control-plane protocols, 72–74
coordinated beam-forming, 340
coordinated link adaptation, 336–340
coordinated multi-point (CoMP), 45–46, 335
coordinated power control, 340
coordinated scheduling, 340–341
core network (CN), 55
coverage enhancement mode (CE mode), 439
coverage enhancement modes, 439
CQI. *See* channel-quality indicator
CRI. *See* CSI-RS resource indicator
critical MTC, 433. *See also* Ultra-reliable and low-latency communication
CRS. *See* cell-specific reference signals
CSA. *See* common subframe allocation
CSG. *See* closed subscribed group
CSI, per beam report. *See* CSI reporting class B
CSI, per element report. *See* CSI reporting class A
CSI. *See* channel-state information
CSI interference measurement (CSI-IM), 275

CSI reference signals (CSI-RS), 104, 111–116
 configuration, 112, 114
CSI-IM. *See* CSI interference measurement
CSI-RS, zero-power. *See* zero-power CSI-RS
CSI-RS. *See* CSI reference signals
CSI-RS resource indicator (CRI), 269, 281–282
cubic metric, 31
cubic-metric-preserving precoder matrix, 191
cumulative ACLR requirement (CACLR), 512
cyclic prefix, 77
 extended, 77
 normal, 77

D

D2D. *See* device-to-device connectivity
D2D communication, 461. *See also* sidelink communication
D2D discovery, 461. *See also* sidelink discovery
DAI. *See* downlink assignment index
data rates, 5G, 528
data region, 79–80, 130–131
DC subcarrier, 79
DCCH. *See* dedicated control channel
DCI. *See* downlink control information
DCI format, 138–139
 blind decoding, 153t. *See also* search space
 carrier indicator, 156, 164
 downlink, 154t
 for eMTC, 444, 447
 precoding information, 157
 resource information, 156, 164–165
 sidelink, 475
 uplink, 165t
 uplink index, 166
dedicated control channel (DCCH), 63
dedicated traffic channel (DTCH), 63
demodulation reference signals (DM-RS), 103–104, 107–111
 for EPDCCH, 111
 uplink, 177
device-specific search space, PDCCH, 149–150
device-to-device communication, 50
device-to-device connectivity (D2D), 461
DFS. *See* dynamic frequency selection
DFT precoding, 171
DFT-spread OFDM (DFTS-OFDM), 31. *See also* DFT precoding
DFTS-OFDM. *See* DFT-spread OFDM
discontinuous reception (DRX), 266–267
 carrier aggregation, 319
 cycle, 307
discovery (in the context of sidelink). *See* sidelink discovery
discovery reference signal (DRS), 365
discovery signal occasion, 365

distributed MIMO, 565–566
distributed resource mapping, 100
distributed VRB, 101
DL-SCH. *See* downlink shared channel
DM-RS. *See* demodulation reference signals
DMTC. *See* DRS measurements timing configuration
downlink assignment index (DAI), 158
downlink channel mapping, 65f
downlink control information (DCI), 70
 for carrier aggregation, 322–325
downlink reference configuration, 368
downlink shared channel (DL-SCH), 64
DRS, for LAA. *See* LAA; DRS
DRS. *See* discovery reference signal
DRS measurements timing configuration (DMTC), 366
DRX. *See* discontinuous reception
DTCH. *See* dedicated traffic channel
dual connectivity, 48, 374–375
 architecture, 375–378
 buffer-status report, 381
 control-plane diversity, 374
 control-plane/user-plane separation, 373
 master cell group, 375
 master eNodeB, 374–375
 power control, 379–381
 power headroom, 381–382
 protocol architecture, 376–378
 scheduling, 381
 secondary cell group, 375
 secondary eNodeB, 374–375
 split bearer, 376–377
 timing, 378–379
 uplink-downlink separation, 374
 use-plane aggregation, 373
DwPTS, 85–86
dynamic frequency selection (DFS), 386, 390–391
dynamic point
 blanking, 340
 selection, 341–342
dynamic range requirement, 514
dynamic TDD. *See* eIMTA

E

ECCE. *See* enhanced control-channel element
eIMTA, CSI reporting. *See* CSI; for eIMTA
eIMTA, hybrid ARQ. *See* hybrid ARQ; for eIMTA
eIMTA, interference handling. *See* ICIC; for eIMTA
eIMTA, power control. *See* power control; eIMTA
eIMTA. *See* enhanced interference mitigation and traffic adaptation
EIS. *See* equivalent isotropic sensitivity
electromagnetic fields (EMF), regulations of, 23

eMBB. *See* enhanced mobile broadband
eMTC. *See* enhanced MTC
enhanced control-channel element (ECCE), 146
enhanced distributed channel access (EDCA). *See* Wi-Fi; EDCA
enhanced DRX, 454
enhanced interference mitigation and traffic adaptation (eIMTA), 48–49, 366–372, 557–559
enhanced mobile broadband (eMBB), 11–12, 531
enhanced MTC (eMTC), 436–437
 CE levels, 453–454
 coverage enhancement modes, 439
 downlink transmission, 441–446
 frequency hopping, 440–441, 445–446
 PBCH structure, 451
 PDSCH repetition, 442
 PUCCH repetition, 450
 PUSCH repetition, 447
 uplink power control, 450
enhanced physical downlink control channel (EPDCCH), 71, 144–149
 blind decoding, 151
 for carrier aggregation, 323–325
 processing, 145–146
enhanced resource-element group (REG), 146
eNodeB, 29, 57
EPC. *See* evolved packet core
EPDCCH. *See* enhanced physical downlink control channel
EPDCCH mapping
 distributed, 148
 localized, 147–148
EPDCCH set, 146
 distributed, 146
 localized, 146
EPS. *See* evolved packet system
equivalent isotropic sensitivity (EIS), 526
EREG. *See* enhanced resource-element group
error-vector magnitude (EVM), 506–507
ETSI, 7
EVM. *See* error-vector magnitude
evolved packet core (EPC), 29, 55
evolved packet system (EPS), 55
extended DRX, 454

F

FBMC. *See* filter-bank multi-carrier
FCC. *See* federal communications commission
FD-MIMO. *See* full-dimension MIMO
FDD. *See* frequency-division duplex; time-division duplex
FEC. *See* forward error correction
federal communications commission (FCC), 23
filter-bank multi-carrier (FBMC), 554

filtered OFDM, 555f

5G

data rates, 528

latency, 528

for reference signals. *See* quasi-colocation

forward compatibility (in the context of 5G), 548

forward error correction (FEC), 227

frame, 76–77

frame structure

type 1, 83

type 2, 84–85

type 3, 89, 395–396

frequency hopping (in the context of eMTC), 440–441, 445–446

frequency hopping, uplink, 173

frequency raster, 91, 523

frequency-division duplex (FDD), 36–37

frequency-domain partitioning (for range expansion), 351, 353–354

frequency-Switched Transmit Diversity (FSTD), 120–121

FSTD. *See* frequency-Switched Transmit Diversity

full duplex, 559–560

link level vs. cell level, 559–560

full-dimension MIMO (FD-MIMO), 279

G

guard period, 86–87

guard-band deployment (in the context of NB-IoT), 456

H

half-duplex FDD, 37

type A, 84, 264–266

type B, 84, 435

harmonized standards, 8

header compression, 61

heterogeneous deployments, 47, 347

heterogeneous deployments, release 8, 352

HetNet, 347. *See* Heterogeneous deployments

hierarchical cell structures, 350

high interference indicator (HII), 334

high-speed packet access (HSPA), 2–3

highly interfered subframes, 356

HII. *See* high interference indicator

home subscriber service (HSS), 56–57

HSFN. *See* Hyper-SFN

HSPA. *See* high-speed packet access

HSS. *See* home subscriber service

hybrid ARQ, 68–70, 227–241

acknowledgements, 207–210

acknowledgements, for carrier aggregation, 326–328

asynchronous, 232–233, 232f

for backhaul link. *See* backhaul link; hybrid ARQ

chase combining, 229–230

downlink, 233–234

for eIMTA, 370

incremental redundancy, 229–230

parity bits, 230–231

process, 69, 229

redundancy version, 229–231

with soft combining, 229–231

synchronous, 232–233, 232f

systematic bits, 230–231

timing, FDD, 237–238

timing, TDD, 238–241

uplink, 234–236

hybrid ARQ, for access link. *See* access link; hybrid ARQ

hybrid ARQ, for LAA. *See* LAA; hybrid ARQ

Hyper-SFN (HSFN), 454

I

ICIC. *See* inter-cell interference coordination

ICNIRP. *See* international commission on non-ionizing radiation protection

ICS. *See* in-channel selectivity

IMT. *See* International Mobile

Telecommunications

IMT-2000, 10

IMT-2020, 11–13, 530–538

key capabilities, 533

IMT-Advanced, 10

in-band emissions, 507

in-channel selectivity (ICS), 516

in-coverage (in the context of D2D), 463

group, 480

indicator, 482

inband deployment (in the context of NB-IoT), 456

inter-cell interference coordination (ICIC), 34,

334–335

ICIC, for eIMTA, 371–372

interlayer interference handling, 347

interleaving

QPP, 96–97

Turbo coding, 96–97

international commission on non-ionizing radiation protection (ICNIRP), 23

International Mobile Telecommunications

(IMT), 9

International Telecommunications Union

(ITU), 8

Internet of Things (IoT), 433

IoT. *See* Internet of Things

ITU. *See* International Telecommunications Union

ITU-R, 8–9

J

joint reception, 345
 joint transmission, 344

L

L1/L2 control signaling
 downlink, 130
 on PUCCH, 196
 on PUSCH, 213–216
 uplink, 195
 LAA, frame structure. *See* frame structure; type 3
 LAA. *See* license-assisted access
 latency, 5G, 528
 LBT. *See* listen-before-talk
 LDPC codes. *See* low-density parity check codes
 license-assisted access (LAA), 43–44, 384
 backoff procedure, 392–394
 contention window, 394
 DFS, 391
 DRS, 398–399
 hybrid ARQ, 399
 LBT, 391–395
 scheduling, 399
 transmission burst, 396–397
 listen-before-talk (LBT), 387, 390–395
 localized resource mapping, 100
 localized VRB, 101
 logical channels, 62–63
 low-density parity check codes (LDPC codes), 562
 low-power nodes, 347

M

MAC. *See* medium-access control
 machine-type communication (MTC), 11–12, 433
 mapping and quasi-colocation configuration, 343
 massive MTC, 433, 532
 Master Information Block (MIB), 289
 maximum power reduction (MPR), 491–492, 506
 MBMS. *See* multimedia broadcaste multicast services
 MBSFN. *See* multicast/broadcast single-frequency network
 MCCH. *See* multicast control channel
 MCE. *See* multi-cell/multicast coordination entity
 MCH. *See* multicast channel
 MCH scheduling information (MSI), 429
 MCH scheduling period (MSP), 428
 MCH subframe allocation (MSA), 429
 medium-access control (MAC), 62–70
 control elements, 66
 multiplexing, 65–66
 METIS project, 536–537
 MIB. *See* Master Information Block

MME. *See* mobility management entity
 mobility management entity (MME), 56
 modulation
 downlink, 99
 uplink, 171
 MPDCCH. *See* MTC physical downlink control channel
 MPR. *See* maximum power reduction
 MSA. *See* MCH subframe allocation
 MSI. *See* MCH scheduling information
 MSP. *See* MCH scheduling period
 MSR. *See* multi-standard radio
 MTC. *See* machine-type communication
 MTC physical downlink control channel (MPDCCH), 71, 441
 repetition, 443–444
 MTCH. *See* multicast traffic channel
 MU-MIMO. *See* Multi-user MIMO; multi-user MIMO
 multi-cell/multicast coordination entity (MCE), 424
 multi-layer deployments, 348
 multi-point coordination, 336–341
 uplink, 345
 multi-point reception. *See* joint reception
 multi-point transmission, 341–345
 multi-site connectivity (in the context of 5G), 565
 multi-standard radio (MSR), 497
 multi-user MIMO (MU-MIMO), 35, 128
 uplink, 193
 multicast channel (MCH), 64, 425–426
 multicast control channel (MCCH), 63, 425
 multicast traffic channel (MTCH), 63, 425
 multicast/broadcast single-frequency network (MBSFN), 38, 422
 area, 423–424
 notification indicator, 430–431
 reference signal, 427–428
 reference signals, 104
 region, 80, 426
 scheduling, 428–431
 multimedia broadcaste multicast services (MBMS), 38, 421
 architecture, 423–425
 service area, 421

N

narrow-band IoT (NB-IoT), 434, 455
 downlink transmission, 456
 guard-band deployment, 456
 inband deployment, 456
 stand-alone deployment, 456
 uplink transmission, 457
 narrowband (in the context of eMTC), 438
 indicator, 444–445, 447
 narrowband PBCH (NPBCH), 459
 narrowband PDCCH (NPDCCH), 456

narrowband PDSCH (NPDSCH), 456
 NAS. *See* non-access stratum
 NB-IoT. *See* narrow-band IoT
 network slicing, 538–539
 Next-Generation Mobile Networks (NGMN), 8, 536
 NGMN. *See* Next-Generation Mobile Networks
 noise figure, 513–514
 non-access stratum (NAS), 56
 non-codebook-based precoding, 125
 NPBCH. *See* narrowband PBCH
 NPDCCH. *See* narrowband PDCCH
 NPDSCH. *See* narrowband PDSCH

O

OCC. *See* orthogonal cover code
 OFDM. *See* orthogonal frequency-division multiplexing
 OI. *See* overload indicator
 open access, 361–362
 open-loop precoding, 124–125
 operating band unwanted emissions (UEM), 509
 operating band unwanted emissions, 499
 orthogonal cover code (OCC), 108
 uplink, 182
 orthogonal frequency-division multiplexing (OFDM), 31
 OSDD. *See* OTA sensitivity direction declarations
 OTA sensitivity direction declarations (OSDD), 526
 out-of-band (OOB) emissions, 494, 507–508
 out-of-coverage (in the context of D2D), 463
 group, 480
 over-the-air (OTA) test, 524
 overload indicator (OI), 334

P

P-RNTI. *See* paging RNTI
 P-SLSS. *See* primary sidelink synchronization signal
 packet data convergence protocol (PDCP), 61
 packet data network gateway (PDN gateway, P-GW), 56
 paging, 307
 paging channel (PCH), 64
 paging control channel (PCCH), 63
 paging cycle. *See* DRX cycle
 paging RNTI (P-RNTI), 307
 PBCH. *See* physical broadcast channel
 PC3 interface, 466–467
 PC5 interface, 58, 466–467
 PCCH. *See* paging control channel
 PCFICH. *See* physical control format indicator channel
 PCH. *See* paging channel
 PCRF. *See* policy and charging rules function
 PDCCH. *See* physical downlink control channel
 PDCP. *See* packet data convergence protocol

PDSCH. *See* physical downlink shared channel
 PDU. *See* protocol data unit
 PHICH. *See* physical hybrid-ARQ indicator channel
 PHY. *See* physical layer
 physical broadcast channel (PBCH), 70
 for eMTC, 451
 physical channel, 70
 physical control format indicator channel (PCFICH), 71,
 132–134
 for carrier aggregation, 322
 physical downlink control channel (PDCCH), 71,
 138–144
 blind decoding, 149
 for carrier aggregation, 323–325
 processing, 139
 physical downlink shared channel (PDSCH), 70
 mapping and quasi-colocation configuration, 343
 repetition (in the context of eMTC), 442
 physical hybrid-ARQ indicator channel (PHICH), 71,
 135–137
 for carrier aggregation, 322–323
 group, 135–136
 physical layer (PHY), 70–72
 cell identity, 105
 physical multicast channel (PMCH), 71
 physical random-access channel (PRACH), 71, 298
 physical resource Block (PRB), 101
 physical sidelink broadcast channel (PSBCH), 71, 467
 physical sidelink control channel (PSCCH), 71, 467
 period, 469
 resource pool, 470
 subframe pool, 470
 physical sidelink discovery channel (PSDCH), 71, 467
 resource pool, 478
 subframe pool, 478
 physical sidelink shared channel (PSSCH), 71, 467
 subframe pool, 473
 physical uplink control channel (PUCCH), 71
 format 1, 197–199
 format 2, 200–201
 format 3, 201–203
 format 4, 203–204
 format 5, 204–205
 repetition (in the context of eMTC), 450
 resource-block mapping, 205–206
 physical uplink shared channel (PUSCH), 71
 repetition (in the context of eMTC), 447
 physical-layer cell identity, 286
 pico node, 347
 PMCH. *See* physical multicast channel
 PMI. *See* precoder matrix indicator
 polar codes, 562

policy and charging rules function (PCRF), 56–57
 positioning reference signals, 104
 power control, 216–223
 for eMTA, 371
 for eMTC, 450
 of PUCCH, 158, 168, 219–221
 of PUSCH, 166, 168, 221–223
 of SRS, 223
 power control, for dual connectivity. *See* dual connectivity;
 power control
 power headroom, dual connectivity. *See* dual connectivity;
 power headroom
 power saving mode (PSM), 436
 power-headroom report, 259–260
 type 1, 260–261
 type 2, 260
 PRACH. *See* physical random-access channel
 PRB. *See* physical resource Block
 pre-configuration (in the context of sidelink connectivity), 466
 precoder matrix
 downlink, 122–123
 uplink, 191t–192t
 precoder matrix indicator (PMI), 269, 277
 codebook, 277–279
 precoding, 117
 closed loop, 123
 codebook-based, 121–122
 non-codebook-based, 125
 open loop, 124–125
 uplink, 189–190
 primary sidelink synchronization signal (P-SLSS), 481
 primary synchronization signal (PSS), 286
 ProSe. *See* Proximity Services
 ProSe function, 466–467
 protected subframe, 355
 pattern, 355
 protocol data unit (PDU), 60
 Proximity Services (ProSe), 461
 PSBCH. *See* physical sidelink broadcast channel
 PSCCH. *See* physical sidelink control channel
 PSDCH. *See* physical sidelink discovery channel
 PSM. *See* power saving mode
 PSS. *See* primary synchronization signal
 PSSCH. *See* physical sidelink shared channel
 PUCCH. *See* physical uplink control channel
 PUSCH. *See* physical uplink shared channel

Q

QCL. *See* quasi-co-location
 QPP-based interleaving, 96–97
 quasi-colocation (QCL), 82
 quasi-colocation (for reference signals), 116

R

R-PDCCH. *See* relay physical downlink control channel
 RACH. *See* random-access channel
 radiated requirements, 524, 526
 radio bearer, 58–59
 radio interface specifications (RSPC), 9–10
 radio interface technologies (RITs), 9–10
 radio resource control (RRC), 72
 radio-access network (RAN), 55
 radio-link control (RLC), 61–62, 241–247
 acknowledged mode, 243
 reordering, 244
 retransmissions, 243–244
 segmentation, 242–243
 status report, 244
 transparent mode, 243
 unacknowledged mode, 243
 RAN. *See* radio-access network
 RAN protocol architecture, 58–59
 random access, 296
 random-access, for eMTC, 453
 random-access channel (RACH), 64
 range expansion
 frequency-domain partitioning, 351, 353–354
 time-domain partitioning, 352, 354–358
 rank indicator (RI), 269, 276–277
 rank override, 124
 rate adaptation, 32
 receiver intermodulation, 516
 reception resource pool, 476
 reduced-power subframes, 355
 redundancy version (RV), 97–98
 reference sensitivity requirement, 513–514
 reference signal received power (RSRP), 366
 reference signal received quality (RSRQ), 366
 reference signals, 81
 cell specific, 103–104
 for CSI, 104, 111
 for demodulation, 103–104, 107, 177
 downlink, 103–104
 for MBSFN, 104
 for positioning, 104
 uplink, 123
 reference signals, UE specific. *See* demodulation reference
 signals
 reference symbols, 104
 REG. *See* resource-element group
 relative narrowband transmit power (RNTP), 335
 relay, 403
 amplify-and-forward, 403
 architecture, 405–406
 backhaul-access link timing, 415–419

relay (*Continued*)
 decode-and-forward, 403–404
 inband, 405
 outband, 405
 relay, search space. *See* R-PDCCH; blind decoding
 relay physical downlink control channel (R-PDCCH), 71, 410–414
 blind decoding, 413–414
 relaying, 47
 resource block, 78
 resource element, 78
 resource-block allocation
 downlink, 156, 159–161
 type 0, 159
 type 1, 159–160
 type 2, 160
 uplink, 167–168
 resource-block indicator, for eMTC, 444–445, 447
 resource-element group (REG), 133–134
 RF bandwidth, 498
 edges, 498
 RI. *See* rank indicator
 RITs. *See* radio interface technologies
 RLC. *See* radio-link control
 RNTP. *See* relative narrowband transmit power
 RRC. *See* radio resource control
 RRC_CONNECTED, 73
 RRC_IDLE, 74
 RSPC. *See* radio interface specifications
 RSRP. *See* reference signal received power
 RSRQ. *See* reference signal received quality
 RV. *See* redundancy version

S

S-GW. *See* serving gateway
 S-SLSS. *See* secondary sidelink synchronization signal
 S1 interface, 57
 SAE. *See* system architecture evolution
 SBCCH. *See* sidelink broadcast control channel
 SC-MCCH. *See* single-cell multicast control channel
 SC-MTCH. *See* single-cell multicast traffic channel
 SC-PTM. *See* single-cell point to multi-point; single-cell point to multipoint
 scalable OFDM, 551–552
 scheduling, MBSFN. *See* MBSFN; scheduling
 scheduling, 249–261
 assignment, 153–163
 buffer-status reports, 259–260
 channel-dependent, 32
 downlink, 254–255
 downlink timing, 261
 eTMA, 370

 grant, 163–168
 half-duplex FDD, 264–266
 max-C/I, 250–252
 proportional fair, 252
 request, 208–210, 212, 257–259
 round robin, 252
 semi-persistent, 263–264
 strategies, 250–254
 uplink, 255–261
 uplink priority handling, 256–257
 uplink timing, 262–263
 scheduling, dual connectivity. *See* dual connectivity;
 scheduling
 scheduling, for carrier aggregation. *See* carrier aggregation;
 scheduling
 scheduling, for LAA. *See* LAA; scheduling
 scheduling, power-headroom report. *See* power-headroom
 report
 SCI. *See* sidelink control information
 scrambling
 downlink, 98
 uplink, 170
 SDO. *See* standards developing organization
 SDU. *See* service data unit
 search space. *See also* blind decoding
 carrier aggregation, 324–325
 EPDCCH, 151
 secondary sidelink synchronization signal (S-SLSS), 481
 secondary synchronization signal (SSS), 286
 self-backhauling, 404
 SEM. *See* spectrum emissions mask
 service data unit (SDU), 60
 serving gateway (S-GW), 56
 SFBC. *See* space-frequency block coding
 SFN. *See* system frame number
 shared cell, 347, 358–361
 short inter-frame space (SIFS), 387
 SI. *See* system information message
 SI-RNTI. *See* system-information RNTI
 SIB. *See* system information block
 SIB 18, 466
 SIB 19, 466
 SIB1 bandwidth reduced (SIB1-BR), 452
 SIB1-BR. *See* SIB1 bandwidth reduced
 sidelink (SL), 461–462
 architecture, 466–467
 configuration, 466
 resource pool, 468
 synchronization, 464, 479–485
 sidelink broadcast channel (SL-BCH), 64, 467, 482
 sidelink broadcast control channel (SBCCH),
 63, 467

sidelink communication, 468–477
 mode 1, 469
 mode 2, 469
 sidelink connectivity
 in-coverage, 463
 out-of-coverage, 463
 sidelink connectivity, preconfiguration, 466
 sidelink control information (SCI), 70, 474–475
 sidelink discovery, 477–479
 type 1, 478
 type 2, 478
 sidelink discovery channel (SL-DCH), 64, 467
 sidelink identity (SLI), 480
 pairs, 480–481
 sidelink master information block (SL-MIB), 467, 482
 sidelink shared channel (SL-SCH), 64, 467
 sidelink synchronization signal (SLSS), 480
 subframe, 481
 sidelink traffic channel (STCH), 63, 467
 SIFS. *See* short inter-frame space
 signaling radio bearer (SRB), 73
 single-cell multicast control channel (SC-MCCH), 63
 single-cell multicast traffic channel (SC-MTCH), 63
 single-cell point to multi-point (SC-PTM), 38–39
 single-cell point to multipoint (SC-PTM), 431
 single-user MIMO (SU-MIMO), 127
 SL. *See* sidelink
 SL-BCH. *See* sidelink broadcast channel
 SL-DCH. *See* sidelink discovery channel
 SL-MIB. *See* sidelink master information block
 SL-SCH. *See* sidelink shared channel
 SLI. *See* sidelink identity
 slot, 76–77
 SLSS. *See* sidelink synchronization signal
 small-cell on/off, 48, 363–366
 sounding reference signal (SRS), 68, 185
 request, 158, 166
 space-frequency block coding (SFBC), 119
 spatial multiplexing, 35
 spatial orthogonal-resource transmit diversity, 194
 spectrum emissions mask (SEM), 508–509
 spurious emissions, 507–508, 512–513
 SRB. *See* signaling radio bearer
 SRS. *See* sounding reference signal
 SRS transmission
 aperiodic, 189
 periodic, 185
 SSS. *See* secondary synchronization signal
 stand-alone deployment (in the context of NB-IoT), 456
 standards developing organization (SDO), 7
 STCH. *See* sidelink traffic channel
 SU-MIMO. *See* Single-user MIMO; single-user MIMO

subframe, 76–77
 MBSFN, 80
 normal, 80
 special, 85
 symbol quadruplet, 133–134
 synchronization signal, 286
 primary, 286
 secondary, 286
 SyncRef UE, 480
 system architecture evolution (SAE), 29, 55
 system frame number (SFN), 77
 system information, 289
 for eMTC, 452
 system information block (SIB), 293–296
 system information message (SI), 294
 system-information RNTI (SI-RNTI), 293d

T

TAG. *See* timing-advance group
 third-generation partnership project (3GPP), 2
 3GPP. *See* third-generation partnership project
 time repetition pattern (TRP), 472–473
 table, 472–473
 time repetition pattern index (TRPI), 472–473
 time-division duplex (FDD), 36–37
 time-domain partitioning (for range expansion), 352, 354–358
 timing advance, 223–225
 for carrier aggregation, 330
 timing-advance group (TAG), 330
 tracking area, 307
 transmission
 modes, 117
 point, 331, 359
 rank, 122
 transmission opportunity (TXOP), 387
 transmission time interval (TTI), 63
 transmit diversity, 119
 PUCCH, 194
 transmitter intermodulation, 513
 transport
 blocks, 63
 channels, 63–64
 format, 63–64
 transport-block size, signaling of, 161–163
 transport-channel processing
 for BCH, 290
 for DL-SCH, 94
 for UL-SCH, 169
 transport-format selection, 63–64
 TRP. *See* time repetition pattern
 TRPI. *See* time repetition pattern index

TSDSI, 7
 TTA, 7
 TTC, 7
 TTI. *See* transmission time interval
 turbo interleaving, 96–97
 TXOP. *See* transmission opportunity

U

UCI. *See* uplink control information
 UE. *See* user equipment
 UE capabilities, 51–53
 UE category 0, 434
 UE-specific reference signals. *See* demodulation reference signals
 UEM. *See* operating band unwanted emissions
 UL-SCH. *See* uplink shared channel
 ultra-lean design, 549
 ultra-reliable and low-latency communications (URLLC), 4, 11–12, 531–532
 unlicensed spectrum, 383, 385–386
 unwanted emissions, 490
 uplink
 channel mapping, 65f
 CoMP, 345
 frequency hopping, 173
 joint reception, 345
 reference configuration, 367–368
 reference signals, 123
 uplink control information (UCI), 70
 for carrier aggregation, 325–330
 uplink multi-point
 coordination, 345
 reception, 345
 uplink shared channel (UL-SCH), 64
 transport channel processing, 169
 uplink time alignment. *See* timing advance

uplink-downlink configuration, 86f
 current, 367–369
 for eIMTA, 367
 UpPTS, 85–86
 URLLC. *See* ultra-reliable and low-latency communications
 user equipment (UE), 30
 Uu interface, 58

V

virtual resource block (VRB), 100
 uplink, 173
 VRB. *See* virtual resource block

W

WCDMA, 2, 23–27
 Wi-Fi
 backoff procedure, 387–388
 contention window, 387
 EDCA, 386–388
 overview, 386–389
 WLAN interworking, 49
 Working Party 5D (WP5D), 9
 world radio-communication conference (WRC), 8–9
 WP5D. *See* Working Party 5D
 WRC. *See* world radio-communication conference
 Windowed OFDM, 555f

X

X2 interface, 58

Z

Zadoff-Chu sequences, 179
 ZC sequences. *See* Zadoff-Chu sequences
 Zero-power CSI-RS, 115–116