Correction checks: the weights are exact and the program is unchanged with the new setting off

Check	Result	Verdict
Supplement alone, sum of corrected weights per run (expected 1)	0.9915–1.0103 (mean 1.0009)	pass
Normal hand-off of the new runs, sum of corrected weights	0.9954–1.0013	pass
Combined (rule B), sum of weights over both sets	0.9973	pass
Same-run combination (rule C), P(north of 30°S) at 00:11	0.02208 against normal alone 0.02197; paired z +1.09	pass
Run J seed 1, own population: sums of corrected weights	supplement 1.001, normal 0.998	pass
Supplement rows north of 34.5°S at 00:11 (prediction 0.92)	0.920 (34.5–29.5°S 0.424, 29.5–25.5°S 0.362, 25.5–21.0°S 0.135)	as designed
Unit tests (four new: exact alone, exact combined, rho, configuration)	36 + 41 passed on deskstar	pass
Gates B and C; regress-seed1	byte-identical to 15 Oct references; −97.51251428262529 equal	pass
Flag off: run J repro seed 1 at the new revision	byte-identical to run J (8 files)	pass
Flag on: run J waypoints seed 1	all 11 normal outputs byte-identical to run J	pass
Mean ln Z per mode, new runs against run J	within 0.1 nat for every mode	pass

Plain: The table shows the checks on the weight correction. The corrected weights add up to 1 within the random error. The two ways to combine the hand-offs agree with the normal hand-off. With the new setting off, the program gives the same bytes as run J. The source is the core filter: run J, early-flight family 'waypoints' (24 runs), and the northern supplement (16 new runs). The prior track starts from the 18:01 radar position and follows a random route through the 2014 waypoints. The 00:11 data are used; the 00:19 data are not. The one-engine physics and the fuel-flow factor are provisional. No search areas, ocean drift or end-of-flight data are applied. The 18:25:27 signal is not used. The other three early-flight families are not included.

Technical: Sums: sum over rows of weight x exp(log_correction), per run. Rule B: balance heuristic across replicates with r_hat (r_hat.csv). Rule C: same-replicate balance heuristic, normal row weight / (1 + rho), supplement row weight x rho / (1 + rho), rho from production-mis.npy / mis.npy; paired over the 16 runs. Byte identity: deskstar job b6389957 (identity-flagoff-repro.txt, identity-flagon-waypoints.txt); handoff.toml compared uncompressed. Core 00:11 hand-offs (filtering distribution at m0011, look-ahead correction exp(log_correction) applied): run J waypoints seeds 1-24 (tag run-j, 1244b7c; 100k rows per seed) and supplement seeds 1001-1016 (rev 3bf0801; particles per mode [TH, MH, TT, MT, LN] = [1.2, 1.3, 1.1, 2.2, 1.2]M vs run J [1.0, 0.5, 2.5, 0.5, 2.5]M; supplement hand-off 100k rows per seed, tilt r(lat) = 0.1 + 0.9 h/H over 00:11 latitude -34.5..-21.0). BFO sd 4.3177 Hz; kappa_x ~ N(1.0, 0.046) and one-engine s7 + s8 PROVISIONAL; 18:25:27 R600 held out. Search case: none; ocean models: none; end-of-flight 00:19 options: not applied. Combination rule B: balance heuristic with r_hat (r_hat.csv), n1 = 2,399,999, n2 = 1,600,003 rows.