

# Number Theory 2

## Binary Exponentiation

Many times , our answer is out of range of datatype int. To avoid this we use modulo operation to overcome this problem. Some of the properties of modulo operation are:

$$(a + b) \% m = (a \% m) + (b \% m)$$

$$(a * b) \% m = (a \% m) * (b \% m)$$

$$(a - b) \% m = (a \% m) - (b \% m)$$

$$(a/b) \% m = (a \% m) * (b^{-1} \% m)$$

## Iterative

We can write any decimal number into a binary number. Let us take an example

$$7^{45}$$

We can write,

$$45 = 1 \times 2^5 + 0 \times 2^4 + 1 \times 2^3 + 1 \times 2^2 + 0 \times 2^1 + 1 \times 2^0$$

$\Rightarrow 7^{45}$  can be calculated easily.

## Code

```
int pr(int a, int n)
{
    int ans=1;
    while(n)
    {
        if(n&1)
            ans = (ans*a)%MOD;
        a = (a*a)%MOD;

        n >>= 1;
    }
    return ans;
}
```

## Recursive

To calculate  $a^n$ , we recursively call on  $a^{n/2}$  and multiply them. Its base case is returning 1 when  $n = 0$ .

## Code

```
int power(int a, int n){
    if(n == 0)
        return 1;

    if(n == 1){
        return a;
    }

    if(n&1)
        return ((a*power(a,n/2)%MOD)*power(a,n/2))%MOD;

    return (power(a,n/2)*power(a,n/2))%MOD;
}
```

## Euler Totient Function

For a positive integer  $n$ , totient function is represented as  $\Phi(n)$ . It is defined as the number of integers  $m$  such that

$$1 \leq m < n$$
$$\gcd(m, n) = 1$$

In simple words number of numbers from 1 to  $n-1$  which are coprime with  $n$ . Its formula is given by

$$\Phi(n) = n * (1 - 1/p_1) * (1 - 1/p_2) * (1 - 1/p_3) \dots * (1 - 1/p_k)$$

where  $p_1, p_2, p_3, \dots, p_k$  are distinct prime factors of  $n$ .

Derivation

If  $A$  and  $B$  are coprime or  $\gcd(A, B) = 1$ , then

$$\Phi(A * B) = \Phi(A) * \Phi(B)$$

We can write

$$n = p_1^a * p_2^b * p_3^c \dots p_k^k$$
$$\Phi(n) = \Phi(p_1^a * p_2^b * p_3^c \dots p_k^k)$$

$$\text{Since } \gcd(p_1^a, p_2^b) = 1$$

$$\Phi(n) = \Phi(p_1^a) * \Phi(p_2^b) * \Phi(p_3^c) * \dots * \Phi(p_k^k)$$

Let us analyze  $\Phi(p^a)$

Numbers from 1 to  $p^a$  which are not coprime with  $p^a$  are  $p, 2p, 3p \dots p^a$ .

This is an AP with common difference  $p$  and first term  $p$ . Using the formula of  $n$ th term of AP, we get

$$p^a = p + (x-1)*p$$
$$x = p^{a-1}$$

Therefore, the number of numbers that are coprime with  $p^a$  are

$$p^a - p^{a-1}$$

$$p^a(1 - 1/p)$$

Substituting this in above equation of  $\Phi(n)$ , we get

$$\begin{aligned}\Phi(n) &= p_1^a(1-1/p_1) * p_2^b(1-1/p_2) * p_3^c(1-1/p_3) * \dots * p_k^k(1-1/p_k) \\ \Phi(n) &= p_1^a * p_2^b * p_3^c * p_k^k * (1-1/p_1) * (1-1/p_2) * (1-1/p_3) * \dots * (1-1/p_k) \\ \Phi(n) &= n * (1-1/p_1) * (1-1/p_2) * (1-1/p_3) * \dots * (1-1/p_k) \\ &\text{since } n = p_1^a * p_2^b * p_3^c * \dots * p_k^k\end{aligned}$$

Implementing totient function

1. Declare an array  $a[]$  of size  $n+1$ .
2. Initialize the array with  $a[i] = i$ .
3. Iterate from 2 to  $n$  and check if  $(a[i] == i)$ , if yes, that means it is a prime number because it is not touched by previous numbers during their iteration. Change it to  $a[i]-1$  and multiply all its multiples with  $(1 - 1/a[i])$ .
4. You have your array with totient values ready.

Code

```
// tot array is ready with tot values upto 10^6..
const int size = 1e6+2;
int tot[size];
void totient()
{
    for(int i=0; i<size; i++)
        tot[i] = i;

    for(int i=2; i<size; i++)
    {
        if(tot[i] == i)
        {
            tot[i] -= 1;
            for(int j=2*i; j<size; j+=i)
                tot[j] -= tot[j]/i;
        }
    }
}
```

## Segmented Sieve

When the value of  $n$  is very large but the  $r-l$  range is less than  $10^8$ , then we use segmented sieve in place of Sieve of Eratosthenes.

### Code

```
// segmented sieve implementation
vector<bool> segmentedSieve(int l, int r)
{
    vector<int> primes;
    int rootR = sqrtl(r);
    vector<bool> isprime(rootR+1, 1);
    isprime[0] = isprime[1] = 0;

    for(int i=2; i<rootR+1; i++)
    {
        if(isprime[i])
        {
            primes.pb(i);
            for(int j=i*i; j<=rootR; j+=i)
                isprime[j] = 0;
        }
    }

    vector<bool> requiredSieve(r-l+1, 1);
    for(int currPrime : primes)
    {
        for(int j=max(currPrime*currPrime, (l+currPrime-1)/currPrime *
currPrime); j<=r; j+=currPrime)
        {
            requiredSieve[j-l] = 0;
        }
    }
    if(l==1)
        requiredSieve[0] = 0;

    return requiredSieve;
}
```

APNI KAKSHA