draft-moura-dnsop-authoritative-recommendations-03

Giovane C. M. Moura^{1,2}, Wes Hardaker³, John Heidemann³, Marco Davids¹

DNSOP – IETF 104 Prague, CZ 2019-03-XX

¹SIDN Labs, ²TU Delft, ³USC/ISI

Draft History

- This is an Informational draft
- Today: first time presented at DNSOP
- Versions and mailing list discussion:
 - -03 (2019-03-11): (minor changes from -02)
 - -02 (2019-03-08): link list thread (no responses)
 - -01 (2018-12-20): link list thread (no responses)
 - -00 (2018-11-28): link list thread
- Github link:
 - https://github.com/gmmoura/ draft-moura-dnsop-authoritative-recommendations

Context

- 13 people that have had 5 research papers:
 - Draft authors + Ricardo de O Schmidt, Wouter B. de Vries, Moritz Müller, Lan Wei, Cristian Hesselman, Jan Harm Kuipers, Pieter-Tjerk de Boer and Aiko Pras.
- Relevant papers with recommendations backed by large-scale, Internet-wide measurements:
 - 4x ACM IMC
 - 1x PAM
- However, papers tend to be long, detailed they explain why
- Target group: large authoritative DNS ops, with global traffic

This draft:

```
papers = []
papers .append (Moura16b)
papers .append (Mueller17b)
papers .append (Schmidt17a)
papers .append (Vries17b)
papers .append (Moura18b)


for p in papers:
   recommendations = TLDR(p) #great filter :-)
   print (recommendations)
```

- Tangible, direct language to OPs folks on what to
- Reader referred to papers to know why

Recommendations in a nutshell


- R1: Use equaly strong IP anycast in every authoritative server to achieve even load distribution [1]
- R2: Routing Can Matter More Than Locations [2]
- R3: Collecting Detailed Anycast Catchment Maps Ahead of Actual Deployment Can Improve Engineering Designs [3]
- R4: When under stress, employ two strategies [4]
- R5: Consider longer time-to-live values whenever possible [5]
- R6: Shared Infrastructure Risks Collateral Damage During Attacks [4]

R1: Use equaly strong IP anycast in every authoritative server to achieve even load distribution



- Resolvers will query ALL authoritatives [1]
 - Ripe Atlas, .nl and the Roots data
- However, ATs nearby will get more queries

R1: Use equaly strong IP anycast in every authoritative server to achieve even load distribution



- For OPs: latency of all ATs matter
- Unicast, by definition, cannot deliver good global performance
- [1] recommends then use anycast in all NS records
 - equally strong (peering and capacity), and phase out unicast.
- This has been applied to .nl.

R2: Routing Can Matter More Than Locations

- When choosing an anycast DNS provider, people always ask "how many sites/instances" it has
- Assumption: more sites → lower latency
- [2] shows that this is not always true:
 - c-root: 8 locations.
 - k-root: 33 locations
 - 1-root: 144 locations
 - Their median RTT: 30–32 ms to 7.9k Atlas probes

R2: Routing Can Matter More Than Locations


- Why? BGP is agnostic to geographical distance
 - A California client may be answered by a site in NRT even though there is a site in SFO
- [2] thus recommends to consider routing and connectivity when engineering DNS anycast services
 - 12 sites is enough to provide good global latency
 - However, more sites may be helpful in case of DDoS [4]

R3: Collecting Detailed Anycast Catchment Maps Ahead of Actual Deployment Can Improve Engineering Designs


- Say you run an anycast service with n instances
- Say you want to add 1 more instance in LAX
- How will that affect traffic among your other locations?
 - Very hard to predict

R3: Collecting Detailed Anycast Catchment Maps Ahead of Actual Deployment Can Improve Engineering Designs


- Solution: anycast catchment maps ahead of deployment
- [3] present a tool (Verfploeter) that does that using ICMP
 - https://github.com/Woutifier/verfploeter
- Applied to b-root to predict query load on LAX:
 - Predicted: 81.6%Actual: 81.4%.
- Current deployments:
 - 1. Anycast testbed (http://anycast-testbed.nl)
 - 2. B-root
 - 3. Large unnamed operator




- BGP will map traffic to locations
- What to do? Depends on the attack
 - 1. Do nothing and let LAX become a degraded absorber
 - 2. Withdraw/prepend routes to shift traffic
- Best option depends on attack and NS specifics



- BGP will map traffic to locations
- What to do? Depends on the attack
 - 1. Do nothing and let LAX become a degraded absorber
 - 2. Withdraw/prepend routes to shift traffic
- Best option depends on attack and NS specifics



- BGP will map traffic to locations
- What to do? Depends on the attack
 - 1. Do nothing and let LAX become a degraded absorber
 - 2. Withdraw/prepend routes to shift traffic
- Best option depends on attack and NS specifics



- BGP will map traffic to locations
- What to do? Depends on the attack
 - 1. Do nothing and let LAX become a degraded absorber
 - 2. Withdraw/prepend routes to shift traffic
- Best option depends on attack and NS specifics

R5: Consider longer TTL values whenever possible

- TTLs set how long queries should remain in resolver's cache
 - Sort of "ephemeral replication"
- [5] also emulates DDoS attacks (50-100% packet loss)




Figure 1: TTL: 1h; 100% Packet loss after t = 10min

R5: Consider longer TTL values whenever possible

- Caching is a key component of resolver's resilience
- Retries as well to the point that resolvers may "hammer" authoritatives
- As such, [5] recommend longer TTLs whenever possible

R6: Shared Infrastructure Risks Collateral Damage During Attacks

- Be careful when contracting/engineering DNS services:
 - · co-location implies you shared (parts of the) infrastructure
- [4] found that when Root DNS was attacked, some .nl
 co-located sites were also down
- Dyn 2016 Attack shows the same
 - multiple zones partially reachable when NSes were attacked
- OPS: be aware of shared infrastructure risk

Questions?

- R1: Use equaly strong IP anycast in every authoritative server to achieve even load distribution [1]
- R2: Routing Can Matter More Than Locations [2]
- R3: Collecting Detailed Anycast Catchment Maps Ahead of Actual Deployment Can Improve Engineering Designs [3]
- R4: When under stress, employ two strategies [4]
- R5: Consider longer time-to-live values whenever possible [5]
- R6: Shared Infrastructure Risks Collateral Damage During Attacks [4]

Thanks reviewers of draft versions

https://github.com/gmmoura/draft-moura-dnsop-authoritative-recommendations

References I

- [1] M. Müller, G. C. M. Moura, R. de O. Schmidt, and J. Heidemann, "Recursives in the wild: Engineering authoritative DNS servers," in *Proceedings of the ACM Internet Measurement Conference*, London, UK, 2017, pp. 489–495. [Online]. Available: http://www.isi.edu/%7ejohnh/PAPERS/Mueller17b.html
- [2] R. d. O. Schmidt, J. Heidemann, and J. H. Kuipers, "Anycast latency: How many sites are enough?" in *Proceedings of the Passive and Active Measurement Workshop*. Sydney, Australia: Springer, Mar. 2017, p. to appear, awarded Best Paper. [Online]. Available: http://www.isi.edu/%7ejohnh/PAPERS/Schmidt17a.html

References II

- [3] W. B. de Vries, R. de O. Schmidt, W. Hardaker, J. Heidemann, P.-T. de Boer, and A. Pras, "Verfploeter: Broad and load-aware anycast mapping," in *Proceedings of the ACM Internet Measurement Conference*, London, UK, 2017. [Online]. Available: http://www.isi.edu/%7ejohnh/PAPERS/Vries17b.html
- [4] G. C. M. Moura, R. de O. Schmidt, J. Heidemann, W. B. de Vries, M. Müller, L. Wei, and C. Hesselman, "Anycast vs. DDoS: Evaluating the November 2015 root DNS event," Nov. 2016. [Online]. Available: https://www.isi.edu/%7ejohnh/PAPERS/Moura16b.html

References III

[5] G. C. M. Moura, J. Heidemann, M. Müller, R. de O. Schmidt, and M. Davids, "When the dike breaks: Dissecting DNS defenses during DDoS," in *Proceedings of the ACM Internet Measurement Conference*, Oct. 2018. [Online]. Available: https://www.isi.edu/%7ejohnh/PAPERS/Moura18b.html