

Nyoka Sound Library
alfa 1

Generated by Doxygen 1.8.3.1

Mon Oct 7 2013 13:07:18

Contents

1	File Index	1
1.1	File List	1
2	File Documentation	3
2.1	cosft.cpp File Reference	3
2.1.1	Function Documentation	3
2.1.1.1	complete_arr	3
2.1.1.2	cosft	4
2.1.1.3	get_array_lenght	4
2.2	fftwest.cpp File Reference	4
2.2.1	Function Documentation	4
2.2.1.1	fft_west	4
2.2.1.2	ifft_west	5
2.3	freqfilters.cpp File Reference	5
2.3.1	Macro Definition Documentation	5
2.3.1.1	PI	5
2.3.2	Function Documentation	5
2.3.2.1	bandpass	5
2.3.2.2	highpass	5
2.3.2.3	lowpass	5
2.4	noise.cpp File Reference	6
2.4.1	Function Documentation	6
2.4.1.1	whitenoise	6
2.5	ogg_vorbis.cpp File Reference	6
2.5.1	Macro Definition Documentation	7
2.5.1.1	READ	7
2.5.2	Function Documentation	7
2.5.2.1	decode	7
2.5.2.2	encoder	7
2.5.2.3	samples_number	8
2.5.2.4	samples_rate	8

2.5.2.5	total_time	8
2.6	pitch_filter.cpp File Reference	8
2.6.1	Macro Definition Documentation	9
2.6.1.1	PI	9
2.6.1.2	PITCH	9
2.6.1.3	UNPITCH	9
2.6.2	Function Documentation	9
2.6.2.1	pitch_filter	9
2.7	plot.cpp File Reference	9
2.7.1	Function Documentation	9
2.7.1.1	plot_freq	10
2.7.1.2	plot_time	10
2.8	sinft.cpp File Reference	10
2.8.1	Function Documentation	10
2.8.1.1	complete_arr	10
2.8.1.2	get_array_lenght	10
2.8.1.3	sinft	10

Index

10

Chapter 1

File Index

1.1 File List

Here is a list of all files with brief descriptions:

cosft.cpp	3
fftwest.cpp	4
freqfilters.cpp	5
noise.cpp	6
ogg_vorbis.cpp	6
pitch_filter.cpp	8
plot.cpp	9
sinft.cpp	10

Chapter 2

File Documentation

2.1 cosft.cpp File Reference

```
#include <stdlib.h>
#include <iostream>
#include <math.h>
#include <complex>
#include <fftwest.hh>
```

Functions

- int [get_array_lenght](#) (double *arr, const int size)
The function found the number power of two, highest and closest to the size of the array.
- void [complete_arr](#) (double *arr_in, double *arr_out, const int size)
This function fill an array power of two with other smaller or equal array and with zeros in extra spaces.
- void [cosft](#) (double *y, complex< double > *rbuffer, const int size)
Is the function in charge to realize the cosine transform the one that you can obtain with equation $f_j = \{k=0\}^{n-1} x_k [{}_{\{n\}} j (k+1\{2\})]$

2.1.1 Function Documentation

2.1.1.1 complete_arr (double * arr_in, double * arr_out, const int size)

This function fill an array power of two with other smaller or equal array and with zeros in extra spaces.

Parameters

:	"*arr_in" is a pointer towards the smallest array with which will fill the biggest array.
:	"*arr_out" is a pointer towards the biggest array where is goint to get out the smaller array one time that is complete with the zeros.
:	"size" is the size of the smaller array .

It is equivalent to the imaginary parts of a DFT of roughly twice the length, is a linear and invertible function

Parameters

:	"*arr_in" is a pointer towards the smallest array with which will fill the biggest array.
:	"*arr_out" is a pointer towards the biggest array where is goint to get out the smaller array one time that is complete with the zeros.
:	"size" is the size of the smaller array .

2.1.1.2 `cosft (double * y, complex< double > * rbuffer, const int size)`

:Is the function in charge to realize the cosine transform the one that you can obtain with equation $f_j = \{k=0\}^{n-1} x_k \{j (k+1)\{2\} \}$

: this funcion is variation of the fast fourier transform,this give the sum of cosine functions oscillating at different frequencies from lossy compression of audio and images

Parameters

:	"size" is the size of the array.
:	"*y" is a pointer towards an array that has to be of a size power of two.
:	"*rbuffer" is a pointer towards an array where is going to return the cosine transform into other array of complex numbers.

2.1.1.3 `get_array_lenght (double * arr, const int size)`

The function found the number power of two, highest and closest to the size of the array.

The function found the highest closest number to the size of the array.

Parameters

<i>size</i>	is the size of the array
-------------	--------------------------

Returns

number result: Is the number power of two closest and bigger than size .

Parameters

<i>size</i>	is the size of the array
-------------	--------------------------

Returns

number result: Is the number power of two closest and bigger than size .

2.2 `fftwest.cpp` File Reference

```
#include <stdlib.h>
#include <iostream>
#include <complex>
#include <fftw3.h>
```

Functions

- void `fft_west` (int *smpls_num*, double **buffer*, complex< double > **retbuffer*)
- void `ifft_west` (int *smpls_num*, complex< double > **buffer*, double **retbuffer*)

2.2.1 Function Documentation

2.2.1.1 void `fft_west` (int *smpls_num*, double * *buffer*, complex< double > * *retbuffer*)

2.2.1.2 void `ifft_west` (int *smpls_num*, complex< double > * *buffer*, double * *retbuffer*)

2.3 freqfilters.cpp File Reference

Macros

- #define `PI` 3.141592654

Functions

- void `lowpass` (int *smpls_num*, int *smpls_rate*, double **buffer*, double **lowbuff*, double *freq*)
The function attenuates only the highest frequencies to a determinated frequency in a wave.
- void `highpass` (int *smpls_num*, int *smpls_rate*, double **buffer*, double **highbuff*, double *freq*)
The function attenuates only the lowest frequencies to a determinated frequency in a wave.
- void `bandpass` (int *smpls_num*, int *smpls_rate*, double **buffer*, double **bandbuff*, double *lowfreq*, double *highfreq*)
The function in charge of attenuated frequencies outside of a given rack in a wave.

2.3.1 Macro Definition Documentation

2.3.1.1 #define `PI` 3.141592654

2.3.2 Function Documentation

2.3.2.1 `bandpass` (int *smpls_num*, int *smpls_rate*, double * *buffer*, double * *bandbuff*, double *lowfreq*, double *highfreq*)

The function in charge of attenuated frequencies outside of a given rack in a wave.

Parameters

<i>smpls_num</i>	is the number of total samples.
<i>smpls_rate</i>	is the number of samples per second.
* <i>buffer</i>	is a pointer towards the array whit the decoded song .
* <i>bandbuff</i>	is a pointer towards an array where is going to send the attenuated frequencies.
<i>lowfreq</i>	is the is the minimun unattenuated frequency.
<i>highfreq</i>	is the is the maximun unattenuated frequency.

2.3.2.2 `highpass` (int *smpls_num*, int *smpls_rate*, double * *buffer*, double * *highbuff*, double *freq*)

The function attenuates only the lowest frequencies to a determinated frequency in a wave.

Parameters

:	* <i>buffer</i> is a pointer towards the array whit the decoded song .
:	* <i>highbuff</i> is a pointer towards an array where is going to send the attenuated frequencies.
:	<i>freq</i> is the is the minimun unattenuated frequency.
:	<i>smpls_num</i> es el tamaño del array <i>buffer</i>
:	<i>smpls_rate</i> is the number of samples per second.

2.3.2.3 `lowpass` (int *smpls_num*, int *smpls_rate*, double * *buffer*, double * *lowbuff*, double *freq*)

The function attenuates only the highest frequencies to a determinated frequency in a wave.

Parameters

:	*buffer is a pointer towards the array whit the decoded song .
:	*lowbuff is a pointer towards an array where is going to send the attenuated frequencies.
:	freq is the is the maximun unattenuated frequency.
:	smpls_num is the number of total samples.
:	smpls_rate is the number of samples per second.

2.4 noise.cpp File Reference

```
#include <math.h>
#include <stdlib.h>
#include <time.h>
#include <iostream>
```

Functions

- void [whitenoise](#) (int smpls_num, double *buffer)

The function fill a pointer with aleatoriis random numbers which when they join the song they can be seen like noisy.

2.4.1 Function Documentation

2.4.1.1 whitenoise (int smpls_num, double * buffer)

The function fill a pointer with aleatoriis random numbers which when they join the song they can be seen like noisy.

Parameters

:	*buffer is a pointer towards an array where is going to return the ramdon numbers.
:	smpls_num is the number of total samples and is equal to size of buffer.

2.5 ogg_vorbis.cpp File Reference

```
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <time.h>
#include <iostream>
#include <vorbis/vorbisenc.h>
#include <vorbis/vorbisfile.h>
```

Macros

- #define [READ](#) 1000000

Functions

- int [samples_number](#) (const char *fname)

The function receives a pointer towards to the name of the archive thar has to be .ogg and return the number of tatal samples.

- double [total_time](#) (const char *fname)
The function receives a pointer towards to the name of the archive thar has to be .ogg and return the time of the song in seconds.
- double [samples_rate](#) (const char *fname)
The function receives a pointer towards to the name of the archive thar has to be .ogg and return the samples for second.
- long [decode](#) (const char *fname, double *buffer, int smpls_num)
The functiondecodes the song in a real array and send it to buffer this need the file are monochannel sound and be a .ogg.
- void [encoder](#) (const char *outfilename, double *inbuffer, int smpls_num, double smpls_rate)
The function is the inverce to decoder this convert a array in a file .ogg using pointers.

2.5.1 Macro Definition Documentation

2.5.1.1 #define READ 1000000

2.5.2 Function Documentation

2.5.2.1 decode (const char * fname, double * buffer, int smpls_num)

The functiondecodes the song in a real array and send it to buffer this need the file are monochannel sound and be a .ogg.

Parameters

:	*buffer is a pointer towards array where de decoder song are sent.
:	*fname is a pointer towards the fist letter to the archive song.
:	smpls_num is the number of total samples and is equal to size of buffer.

Returns

the number of samples read

2.5.2.2 encoder (const char * outfilename, double * inbuffer, int smpls_num, double smpls_rate)

The function is the inverce to decoder this convert a array in a file .ogg using pointers.

Parameters

:	*outfilename is pointer toward the first letter to file where send the array once encoder
:	*inbuffer is a pointer to the array whit the song decoder or the file you want to convert.
:	*fname is a pointer towards the fist letter to the archive song.
:	smpls_num is the number of total samples and is equal to size of buffer.
:	smpls_rate is the number of samples per second.

The function the function choose a centroid and does window as a bell of Hann,whit this one values all the points ariund the centroid and does the point if greatest amplitude pitch and the point of less aplitude unpitc,with this made groups around,start to calculate the news centroids using f2 and f3,repeat the proces until the centroids aren't moving or until 100 iterations, chages the size of the window exponentially dependin of the increment. is chosen the size of the window with more distance between the centroids

Parameters

:	*buffer is a pointer towards array where de decoder song is saves.
:	percent is percent od samples per second.

:	increment is the increment and is given exponentially.
:	smpls_num is the number of total samples and is equal to size of buffer.
:	smpls_rate is the number of samples per second.

2.5.2.3 samples_number (const char * fname)

The function receives a pointer towards to the name of the archive thar has to be .ogg and return the number of tatal samples.

Parameters

:*fname	is a pointer towards the fist letter to the archive song.
---------	---

Returns

The number of samples in total song.

2.5.2.4 samples_rate (const char * fname)

The function receives a pointer towards to the name of the archive thar has to be .ogg and return the samples for second.

Parameters

:*fname	is a pointer towards the fist letter to the archive song.
---------	---

Returns

The samples for second of the song.

2.5.2.5 total_time (const char * fname)

The function receives a pointer towards to the name of the archive thar has to be .ogg and return the time of the song in seconds.

Parameters

:*fname	is a pointer towards the fist letter to the archive song.
---------	---

Returns

The total time in seconds song.

2.6 pitch_filter.cpp File Reference

```
#include <stdlib.h>
#include <math.h>
#include <stdio.h>
#include <cmath>
#include <iostream>
```

Macros

- `#define PI 3.141592654`
- `#define PITCH 1`
- `#define UNPITCH 0`

Functions

- void `pitch_filter` (int `smpls_num`, int `smpls_rate`, double `*inbuffer`, double `percent`, double `increment`)
The function receives a pointer to real array and with their generates a graphyc respect to time.

2.6.1 Macro Definition Documentation

2.6.1.1 `#define PI 3.141592654`

2.6.1.2 `#define PITCH 1`

2.6.1.3 `#define UNPITCH 0`

2.6.2 Function Documentation

2.6.2.1 `pitch_filter` (int *smpls_num*, int *smpls_rate*, double * *inbuffer*, double *percent*, double *increment*)

The function receives a pointer to real array and with their generates a graphyc respect to time.

The function receives a pointer towards an array of complex numbers and with their generates a graphyc respect to the frequency.

Parameters

	:	<code>*buffer</code> is a pointer towards the array whit the decoded song .
	:	<code>smpls_read</code> is the number of samples read .
	:	<code>smpls_rate</code> is the number of samples per second.
<code>*buffer</code>	:	is a pointer towards the array whit the decoded song .
	:	<code>smpls_read</code> is the number of samples read .
	:	<code>smpls_rate</code> is the number of samples per second.

2.7 plot.cpp File Reference

```
#include <iostream>
#include <stdlib.h>
#include <fstream>
#include <complex>
```

Functions

- void `plot_time` (double `*buffer`, int `smpls_read`, double `smpls_rate`)
- void `plot_freq` (complex< double > `*buffer`, int `smpls_read`, double `smpls_rate`)

2.7.1 Function Documentation

2.7.1.1 void plot_freq (complex< double > * *buffer*, int *smpIs_read*, double *smpIs_rate*)

2.7.1.2 void plot_time (double * *buffer*, int *smpIs_read*, double *smpIs_rate*)

2.8 sinft.cpp File Reference

```
#include <stdlib.h>
#include <iostream>
#include <math.h>
#include <complex>
#include <fftwest.hh>
```

Functions

- int [get_array_lenght](#) (const int size)
- void [complete_arr](#) (double *arr_in, double *arr_out, const int size)
- void [sinft](#) (double *y, complex< double > *rbuffer, const int size)
: Is the function in charge to realize the sine transform the one that you can obtain with equatio $F_k = \{j=1\}^{\wedge}\{N-1\}f_j \sin(j k/N)$

2.8.1 Function Documentation

2.8.1.1 void complete_arr (double * *arr_in*, double * *arr_out*, const int *size*)

2.8.1.2 int get_array_lenght (const int *size*)

2.8.1.3 sinft (double * *y*, complex< double > * *rbuffer*, const int *size*)

: Is the function in charge to realize the sine transform the one that you can obtain with equatio $F_k = \{j=1\}^{\wedge}\{N-1\}f_j \sin(j k/N)$

:

Parameters

:	"size" is the size of the array.
:	"*y" is a pointer towards an array that has to be of a size power of two.
:	"*rbuffer" is a pointer towards an array where is going to return the cosine transform into other array of complex numbers.

Index

bandpass
 freqfilters.cpp, 5

complete_arr
 cosft.cpp, 3
 sinft.cpp, 10

cosft
 cosft.cpp, 4
cosft.cpp, 3
 complete_arr, 3
 cosft, 4
 get_array_lenght, 4

decode
 ogg_vorbis.cpp, 7

encoder
 ogg_vorbis.cpp, 7

fft_west
 fftwest.cpp, 4

fftwest.cpp, 4
 fft_west, 4
 ifft_west, 4

freqfilters.cpp, 5
 bandpass, 5
 highpass, 5
 lowpass, 5
 PI, 5

get_array_lenght
 cosft.cpp, 4
 sinft.cpp, 10

highpass
 freqfilters.cpp, 5

ifft_west
 fftwest.cpp, 4

lowpass
 freqfilters.cpp, 5

noise.cpp, 6
 whitenoise, 6

ogg_vorbis.cpp, 6
 decode, 7
 encoder, 7
 READ, 7
 samples_number, 8

samples_rate, 8
total_time, 8

PI
 freqfilters.cpp, 5
 pitch_filter.cpp, 9

PITCH
 pitch_filter.cpp, 9

pitch_filter
 pitch_filter.cpp, 9

pitch_filter.cpp, 8

PI, 9
PITCH, 9
pitch_filter, 9
UNPITCH, 9

plot.cpp, 9
 plot_freq, 9
 plot_time, 10

plot_freq
 plot.cpp, 9

plot_time
 plot.cpp, 10

READ
 ogg_vorbis.cpp, 7

samples_number
 ogg_vorbis.cpp, 8

samples_rate
 ogg_vorbis.cpp, 8

sinft
 sinft.cpp, 10

sinft.cpp, 10
 complete_arr, 10
 get_array_lenght, 10
 sinft, 10

total_time
 ogg_vorbis.cpp, 8

UNPITCH
 pitch_filter.cpp, 9

whitenoise
 noise.cpp, 6