

Web Services/API Document

for

Integration with Warehouse Operator System

Submitted to



**WAREHOUSE
RECEIPT SYSTEM
COUNCIL**

Prepared by



CSM Technologies Private Limited

Level - 6, OCAC Tower, Acharya Vihar,
Bhubaneswar - 751013, Odisha, India

+91 (0)674-6635 900 | info@csm.co.in | www.csm.co.in

Contents

Contents	1
1. INTRODUCTION	2
2. PURPOSE OF THIS DOCUMENT	2
3. HOW TO ACCESS THE API SERVICES	2
4. List Of OAuth APIS	3
4.1 API for: Get OAuth Token.....	3
4.2 API for: Use Access Token	4
5. List Of Master APIS	5
5.1 Master API for: Type of Depositor.....	5
5.2 Master API for: Type of Entity	7
5.3 Master API for: get Type of counties.....	8
5.4 Master API for: Get Sub-Counties by County ID.....	9
5.5 Master API for: Get Wards by Sub-County ID	10
5.6 Master API for: Get Nationality Master Data	12
5.7 Master API for: Get Government Issued ID Types	13
5.8 Master API for: Get Commodity Types.....	14
5.9 Master API for: Get Commodity Names.....	16
5.10 Master API for: Get Crop Year / Season	18
5.11 Master API for: Get Charge Headers	19
5.12 Master API for: Get Unit Types	21
6. LIST OF EXTERNAL SERVICES.....	22
6.1 API for: Save Depositor Details.....	22
6.2 API for: Get All Depositor Details	24
6.3 API for: Get Depositor Details by Email ID	26
6.4 API for: Get Issuance of warehouse Receipt	28
6.5 API for: Registration of Warehouse Receipt.....	30
6.6 API for: Get market-data	31
6.7 API for: Save Market Data	33
6.8 API for: Get Listing Price By receiptId.....	34
6.9 API for: Pledging of Warehouse Receipt	35
6.10 API for: Loan Sanction	37
6.11 API for: Transfer to New Depositor	38
6.12 API for: Retire Warehouse Receipt.....	40

1. INTRODUCTION

E-warehouse is a platform for managing warehouse operations, depositor registrations, loan sanctions, and auction processes. The APIs facilitate secure data transactions and ensure seamless integration with external systems.

2. PURPOSE OF THIS DOCUMENT

This This document serves as a reference guide for stakeholders to understand the API endpoints, their usage, and integration with the e-Warehouse system.

3. HOW TO ACCESS THE API SERVICES

- ❖ **Registration of Application & Whitelisting of IP Address**
- ❖ **Token-Based Authentication using OAuth2**
- ❖ **Secure Communication via HTTPS**

4. List Of OAuth APIS

4.1 API for: Get OAuth Token.

❖ Use Cases:

This API will be helpful to get the Token no. for authenticating the user. Stakeholder has to provide the specified User Name and Password to get the Token No. This token no will be valid for 30 minutes and expires automatically. This token no. to be passed in header in every APIs.

❖ Service Request Name and URL

URL	http://localhost:8888/oauth2/token
Method	POST

❖ Authentication Details

- Auth Type: Basic Auth
- Username: winnie gwada
- Password: winnie123

❖ Request Header

Header	Value
Authorization	*****
Cache-Control	no-cache
Postman-Token	<calculated when request is sent>
Content-Type	application/x-www-form-urlencoded
Content-Length	<calculated when request is sent>
Host	<calculated when request is sent>
User-Agent	PostmanRuntime/7.43.3
Accept	/
Accept-Encoding	gzip, deflate, br
Connection	keep-alive

❖ Request Body (Form-Data/ x-www-form-urlencoded)

Key	Value
grant_type	client_credentials

client_id	priyanka
client_secret	winnie_gwada
scope	winnie123

❖ **Sample Request (cURL Format):**

```
http://localhost:8888/api/
eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcml5YW5rYSIsImF1ZCI6ImByaXlhbmthliwibmJmljoxNzQzNDkwNzQ5LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwizXhwljoxNzQzNDk0MzQ5LCJpYXQiOiJlE3NDM0OTA3NDksImp0aSI6IjU5MTkyZjRjLWI5OGUtNDJkOC1hYWU0LWFjZmMxODgxNDA2MCI9.gAf-rFXylM2uJc4O-GFtazSSyZZEDHGFaLw_isNxy-_Ut_hau8MK7-6nguH5muVPm1OPU1LkKQwFQSBXghxyxrT4N-SklVEpAG4o_3N9Ro8sZ7hs8atyEM_38FxTD6Eb42tFfYcpM2-_j572mj__ibKPTy5SrnlTXchK2TSwc_61IQSxESfyQsfD_i3iazE-sFDS3czrJ0RsKnDpHir_FAESfutn_Y7eoPUTfJgH1SivtnR4PD7PgKvklfMr31w2MdGSPimKxpHQLtTHglu_TIElcfQexx7EP9Y0wO41UcQE1t7WBpn6WqEoEyu_2dpC1lBB6KOWliP7oT-r8Tox9w
```

❖ **Sample Response Template:**

```
{
  "access_token": "
eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcml5YW5rYSIsImF1ZCI6ImByaXlhbmthliwibmJmljoxNzQzNDkwNzQ5LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwizXhwljoxNzQzNDk0MzQ5LCJpYXQiOiJlE3NDM0OTA3NDksImp0aSI6IjU5MTkyZjRjLWI5OGUtNDJkOC1hYWU0LWFjZmMxODgxNDA2MCI9.gAf-rFXylM2uJc4O-GFtazSSyZZEDHGFaLw_isNxy-_Ut_hau8MK7-6nguH5muVPm1OPU1LkKQwFQSBXghxyxrT4N-SklVEpAG4o_3N9Ro8sZ7hs8atyEM_38FxTD6Eb42tFfYcpM2-_j572mj__ibKPTy5SrnlTXchK2TSwc_61IQSxESfyQsfD_i3iazE-sFDS3czrJ0RsKnDpHir_FAESfutn_Y7eoPUTfJgH1SivtnR4PD7PgKvklfMr31w2MdGSPimKxpHQLtTHglu_TIElcfQexx7EP9Y0wO41UcQE1t7WBpn6WqEoEyu_2dpC1lBB6KOWliP7oT-r8Tox9w",
  "token_type": "bearer",
  "expires_in": 3600,
  "scope": "read write"
}
```

4.2 API for: Use Access Token

❖ **Use Cases**

Pass the token in the Authorization header for API calls.

❖ **Service Request Name and URL**

URL	http://localhost:8888/api/protected
Method	GET

❖ **Header**

Token

eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmIjoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwiaXhwaWJjoxNzQzNTAzNTE4LCJpYXQiOiJlZ3NDMD0OTk5MTgsImp0aSI6ImVIZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWw3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkj390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOlBNXpq3dRjkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0rA

❖ **Response Description**

```
{
  "message": "This is a protected resource accessed using OAuth2 token!"
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5. List Of Master APIs

5.1 Master API for: Type of Depositor

❖ **Use Cases**

This API is used to save the master data for depositors, whether they are entities or

individuals. This information is required to register depositors and map warehouse receipts and other transactions accurately within the eWRS platform.

❖ **Service Request Name and URL**

URL	http://localhost:8888/api/master-data/getDepositorType
Method	GET

❖ **Header**

Token

eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WjYyZWZkIiwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwiaXZhbWljoxNzQzNTAzNTE4LCJpYXQiOiE3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAAlaWVPBJP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Response Description**

```
[
  {
    " depositorTypeId": "1",
    " depositorType": "Entity"
  },
  {
    " depositorTypeId": "2",
    " depositorType": "Individual"
  }
]
```

Error Responses

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.2 Master API for: Type of Entity

❖ Use Cases

This API is used to save the master data for depositors, whether they are entities or individuals. This information is required to register depositors and map warehouse receipts and other transactions accurately within the eWRS platform.

❖ Service Request Name and URL

URL	http://localhost:8888/api/master-data/getType-of-entity
Method	GET

❖ Header

Token

```
eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJ3NDM0OTk5MTgsImp0aSI6ImVIZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWwzNGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-zNlvTnkgomsIfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8IHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra
```

❖ Response Description

```
[
  {
    "typeOfEntityId": "1",
    "typeOfEntityName": "Cooperative"
  },
]
```



```
{
  "typeOfEntityId": "2",
  "typeOfEntityName": "Partnership"
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.3 Master API for: get Type of counties**❖ Use Cases**

Retrieves the list of all available counties in the system. This data is used to populate the county dropdown in forms like depositor registration.

❖ Service Request Name and URL

URL	http://localhost:8888/api/master-data/counties
Method	GET

❖ Header**Token**

eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmIjoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo0ODg4IiwiaXhwaWJjoxNzQzNTAzNTE4LCJpYXQiOiJlE3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjth4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VViso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Response Description**

```
[
  {
    "countyId": "CNT001",
    "countyName": "Nairobi"
  },
  {
    "countyId": "CNT002",
    "countyName": "Mombasa"
  }
]
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.4 Master API for: Get Sub-Counties by County ID❖ **Use Cases**

Retrieves sub-counties based on the selected county. This allows dynamic filtering of sub-counties related to a specific county.

❖ **Service Request Name and URL**

URL	http://localhost:8888/api/master-data/subcounties/{countyId}
Method	GET

❖ **Header****Token**

eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbmthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WjYyZWZkIiwid3JpdGUiXSswiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlNDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNG

JlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ39
0w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-
lgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-
zNlvTnkgomsIfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-
PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-
m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-
Ee0Ra

❖ **Response Description**

```
[
  {
    "subCountyId": "1",
    "subCountyName": "Westlands"
  },
  {
    "subCountyId": "2",
    "subCountyName": "Langata"
  }
]
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.5 Master API for: Get Wards by Sub-County ID

❖ **Use Cases**

Retrieves wards based on the selected sub-county. This helps in narrowing down to specific local administrative areas.

❖ **Service Request Name and URL**

URL	http://localhost:8888/api/master-data /wards/{subCountyId}
Method	GET

❖ **Header****Token**

eyJhbGciOiJIUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmIjoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlE3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8IHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Response Description**

```
[
  {
    "wardId": "WRD001",
    "wardName": "Kileleshwa"
  },
  {
    "wardId": "WRD002",
    "wardName": "Karen"
  }
]
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.6 Master API for: Get Nationality Master Data

❖ Use Cases

Retrieves wards based on the selected sub-county. This helps in narrowing down to specific local administrative areas.

❖ Service Request Name and URL

URL	http://localhost:8888/api/master-data/nationality
Method	GET

❖ Header

Token

eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwljoxNzQzNTAzNTE4LCJpYXQiOiE3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy00ZDFjLWWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ Response Description

```
{
  "status": 200,
  "message": "Success",
  "result": [
    {
      "nationalityId": "N001",
      "nationalityName": "Kenyan"
    }
  ],
}
```

```
{
  "nationalityId": "N002",
  "nationalityName": "Ugandan"
},
{
  "nationalityId": "N003",
  "nationalityName": "Tanzanian"
}
]
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.7 Master API for: Get Government Issued ID Types**❖ Use Cases**

Retrieves the list of valid Government-issued ID types that can be used during user or entity registration (e.g., National ID, Passport, Alien ID).

❖ Service Request Name and URL

URL	http://localhost:8888/api/master-data/govt-id-types
Method	GET

❖ Header**Token**

eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWZkIiwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlNDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAIAWVPBJP97XO-

zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-
PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-
m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-
EeORa

❖ *Response Description*

```
{
  "status": 200,
  "message": "Success",
  "result": [
    {
      "govtIdTypeId": "1",
      "govtIdTypeName": "National ID"
    },
    {
      "govtIdTypeId": "2",
      "govtIdTypeName": "Passport"
    },
    {
      "govtIdTypeId": "3",
      "govtIdTypeName": "Alien ID"
    }
  ]
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.8 Master API for: Get Commodity Types

❖ *Use Cases*

Retrieves the list of available commodity types handled by the Electronic Warehouse Receipt System. This master data is used during warehouse receipt issuance, registration, and commodity tracking.

❖ **Service Request Name and URL**

URL	http://localhost:8888/api/master-data/commodity-types
Method	GET

❖ **Header**

Token

```
eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlZ3NDMD0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra
```

❖ **Response Description**

```
{
  "status": 200,
  "message": "Success",
  "result": [
    {
      "commodityTypeId": "CT001",
      "commodityTypeName": "Agricultural"
    },
    {
      "commodityTypeId": "CT002",
      "commodityTypeName": "Energy"
    }
  ]
}
```



```

    "commodityTypeId": "CT003",
    "commodityTypeName": "Metals"
  }
]
}

```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.9 Master API for: Get Commodity Names**❖ Use Cases**

Retrieves the list of all commodity names available under registered commodity types. This is used during warehouse receipt issuance, commodity pledging, and reporting processes

❖ Service Request Name and URL

URL	http://localhost:8888/api/master-data/commodity-names
Method	GET

❖ Header**Token**

```

eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJwcm15YW5rYSIsImF1ZCI6InByaXlhbWthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwiaXNjbG9jaXNzQzNTAzNTE4LCJpYXQiOiJlbnR0OTk5MTgsIm0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWw3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjth4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRjkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

```

❖ Response Description

```
{
  "status": 200,
  "message": "Success",
  "result": [
    {
      "commodityId": "CMD001",
      "commodityName": "Maize",
      "commodityTypeId": "CT001"
    },
    {
      "commodityId": "CMD002",
      "commodityName": "Wheat",
      "commodityTypeId": "CT001"
    },
    {
      "commodityId": "CMD003",
      "commodityName": "Green Gram",
      "commodityTypeId": "CT002"
    }
  ]
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.10 Master API for: Get Crop Year / Season

❖ Use Cases

Retrieves the list of available crop years and seasons to be used during commodity issuance, registration, and tracking. This ensures accurate historical and seasonal reporting.

❖ Service Request Name and URL

URL	http://localhost:8888/api/master-data/crop-year-seasons
Method	GET

❖ Header

Token

eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlNDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ Response Description

```
{
  "status": 200,
  "message": "Success",
  "result": [
    {
      "commodityId": "CMD001",
      "commodityName": "Maize",
      "commodityTypeId": "CT001"
    },
    {
      "commodityId": "CMD002",
```

```

    "commodityName": "Wheat",
    "commodityTypeId": "CT001"
  },
  {
    "commodityId": "CMD003",
    "commodityName": "Green Gram",
    "commodityTypeId": "CT002"
  }
]
}

```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.11 Master API for: Get Charge Headers**❖ Use Cases**

Retrieves the list of charge headers that define various types of charges (e.g., storage charges, inspection fees, handling charges) applicable during warehouse receipt processing, issuance, or pledging. This master is used for calculating charges dynamically based on configuration.

❖ Service Request Name and URL

URL	http://localhost:8888/api/master-data/charge-headers
Method	GET

❖ Header**Token**

eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcm15YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmljoxNzQzND

k5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOjE3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Response Description**

```
{
  "status": 200,
  "message": "Success",
  "result": [
    {
      "chargeHeaderId": "CH001",
      "chargeHeaderName": "Storage Charges"
    },
    {
      "chargeHeaderId": "CH002",
      "chargeHeaderName": "Inspection Fees"
    },
    {
      "chargeHeaderId": "CH003",
      "chargeHeaderName": "Handling Charges"
    }
  ]
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

5.12 Master API for: Get Unit Types

❖ Use Cases

Retrieves the list of available **unit types** used to measure commodities (e.g., Kilograms, Tons, Liters) during storage, issuance, and transaction operations in the eWRS.

❖ Service Request Name and URL

URL	http://localhost:8888/api/master-data/unit-types
Method	GET

❖ Header

Token

```
eyJhbGciOiJIUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmIjoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwiaXhwaWJoxNzQzNTAzNTE4LCJpYXQiOiJlZ3NDMD0OTk5MTgsImp0aSI6ImVIZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWw3M3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkj390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8IHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra
```

❖ Response Description

```
{
  "status": 200,
  "message": "Success",
  "result": [
    {
      "unitTypeId": "U001",
      "unitTypeName": "Kilogram"
    },
    {
      "unitTypeId": "U002",
```

```

    "unitTypeName": "Metric Ton"
  },
  {
    "unitTypeId": "U003",
    "unitTypeName": "Bag"
  }
]
}

```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6. LIST OF EXTERNAL SERVICES

6.1 API for: Save Depositor Details

❖ Use Cases

This API allows creation and saving of depositor details, such as personal identification, contact information, and administrative division mapping (county, sub-county, ward). It supports Individual or Entity depositor types.

❖ Service Request Name and URL

URL	http://localhost:8888/api/saveDepositor
Method	POST

❖ Header

Token

eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbmthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWZkIiwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlNDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-

zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-
PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-
m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-
EeORa

❖ *Sample Request*

```
{  
  "typeOfDepositor": "Individual",  
  "nameOfDepositor": "John Doe",  
  "mobileNumber": "+254712345678",  
  "emailAddress": "john.doe@example.com",  
  "postalCode": "00100",  
  "postalAddress": "P.O. Box 12345 - 00100 Nairobi",  
  "county": "Nairobi",  
  "subCounty": "Westlands",  
  "ward": "Parklands",  
  "nationality": "Kenyan",  
  "entityRegistrationNumber": "BRN123456789",  
  "governmentIssuedID": "National ID",  
  "idNumber": "12345678"  
}
```

❖ *Response Description*

```
{  
  "status": 200,  
  "message": "Depositor details saved successfully"  
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.2 API for: Get All Depositor Details

❖ Use Cases

This Api Retrieves depositor details by calling a third-party system. Useful for validating or pre-filling depositor data in the Electronic Warehouse Receipt System (eWRS).

❖ Service Request Name and URL

URL	http://localhost:8888/api/getDepositors
Method	GET

❖ Header

Token

eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmIjoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwiaXZlbnVlIjoiaXNzQzNTAzNTE4LCJpYXQiOiJlZ3NDMD0OTk5MTgsImp0aSI6ImVIZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8IHEOIBNXpq3dRJkiUFLfzdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ Response Description

```
{
  "depositors": [
    {
      "typeOfDepositor": "Individual",
      "nameOfDepositor": "John Doe",
      "mobileNumber": "+254712345678",
      "emailAddress": "john.doe@example.com",
      "postalCode": "00100",
      "postalAddress": "P.O. Box 12345 - 00100 Nairobi",
    }
  ]
}
```

```
"county": "Nairobi",
"subCounty": "Westlands",
"ward": "Parklands",
"nationality": "Kenyan",
"entityRegistrationNumber": "BRN123456789",
"governmentIssuedID": "National ID",
"idNumber": "12345678"
},
{
  "typeOfDepositor": "Company",
  "nameOfDepositor": "ABC Traders Ltd.",
  "mobileNumber": "+254798765432",
  "emailAddress": "info@abctraders.co.ke",
  "postalCode": "00200",
  "postalAddress": "P.O. Box 54321 - 00200 Nairobi",
  "county": "Mombasa",
  "subCounty": "Kisauni",
  "ward": "Bamburi",
  "nationality": "Kenyan",
  "entityRegistrationNumber": "BRN987654321",
  "governmentIssuedID": "Certificate of Incorporation",
  "idNumber": "C-654321"
},
{
  "typeOfDepositor": "Individual",
  "nameOfDepositor": "Jane Mwendu",
  "mobileNumber": "+254711223344",
  "emailAddress": "jane.mwendu@example.com",
  "postalCode": "00300",
  "postalAddress": "P.O. Box 98765 - 00300 Nairobi",
  "county": "Kisumu",
  "subCounty": "Kisumu Central",
  "ward": "Market Milimani",
  "nationality": "Kenyan",
  "entityRegistrationNumber": ""
```

```

    "governmentIssuedID": "National ID",
    "idNumber": "87654321"
  }
]
}

```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.3 API for: Get Depositor Details by Email ID**❖ Use Cases**

This Api Fetches the complete depositor details using the email address provided in the request. Useful for validating if a depositor already exists or retrieving their full profile.

❖ Service Request Name and URL

URL	http://localhost:8888/api/ depositor/details-by-email/{emailId}
Method	GET

❖ Header**Token**

```

eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbmthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlM0OTk5MTgsImpp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkj390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8IHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

```

❖ *Sample Request*

GET </api/depositor/details-by-email/john.doe@example.com>

❖ *Response Description*

```
{
  "status": "success",
  "message": "Depositor details retrieved successfully",
  "data": {
    "typeOfDepositor": "Individual",
    "nameOfDepositor": "John Doe",
    "mobileNumber": "+254712345678",
    "emailAddress": "john.doe@example.com",
    "postalCode": "00100",
    "postalAddress": "P.O. Box 12345 - 00100 Nairobi",
    "county": "Nairobi",
    "subCounty": "Westlands",
    "ward": "Parklands",
    "nationality": "Kenyan",
    "entityRegistrationNumber": "BRN123456789",
    "governmentIssuedID": "National ID",
    "idNumber": "12345678"
  }
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.4 API for: Get Issuance of warehouse Receipt

❖ Use Cases

This API retrieves the details of issued warehouse receipts based on a specific status query parameter (e.g., ConfirmationreceivefromDepositor). The response includes details of warehouse receipts, such as the commodity type, weight, status, associated documents, and other metadata related to the warehouse receipt

❖ Service Request Name and URL

URL	http://localhost:8888/api/issuance/getIssuanceDetailsByrecivedStatus?status=ConfirmationreceivefromDepositor
Meth od	GET

❖ Header

Token

eyJhbGciOiJIUzI1NiJ9.eyJzdWliOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbWthliwibmJmIjoxNzQzNDk5OTE4LCJyZ29wZSI6WyJyZWFKliwid3JpdGUxSWiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwiaXNjaXNjaXNzQzNTAzNTE4LCJpYXQiOiJlZ3NDMD0OTk5MTgsImp0aSI6ImVIZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkj390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAIAWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8IHEOIBNXpq3dRJkiUFLfzdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ Response Description

```
{
  "status": 200,
  "result": [
    {
      "intIssueanceWhId": "1",
      "parentReceiptId": "1",
      "intDepositorWhOperator": "8J733J3H57",
      "commodityType": "1",
      "commodityOrigin": "North East",
```

```
"commodityCode": "3223488",
"originalQuantity": "345.00",
"originalGrossWeight": "34.00",
"originalNetWeight": "234.00",
"currentQuantity": "45.00",
"currentNetWeight": "234.00",
"cropYear": "3",
"grade": "23",
"lotNumber": "34",
"qualityInspectionPath": "5731747718484785.pdf",
"weighingTicketPath": "5981747718490775.pdf",
"grnPath": "2151747718497792.pdf",
"receiptStatus": "ConfirmationreceivefromDepositor",
"oicStatus": "PendingatCentralRegistry",
"ceoStatus": "Pendingforregistration",
"paymentStatus": "Pending",
"vchWarehouseId": "WAR20250227001"
},
{
  "intIssueanceWhId": "2",
  "parentReceiptId": "2",
  "intDepositorWhOperator": "7M766J3H57",
  "commodityType": "1",
  "commodityOrigin": "North East",
  "commodityCode": "3223488",
  "originalQuantity": "345.00",
  "originalGrossWeight": "34.00",
  "originalNetWeight": "234.00",
  "currentQuantity": "45.00",
  "currentNetWeight": "234.00",
  "cropYear": "3",
  "grade": "23",
  "lotNumber": "34",
  "qualityInspectionPath": "5731747718484785.pdf",
  "weighingTicketPath": "5981747718490775.pdf",
```

```

    "grnPath": "2151747718497792.pdf",
    "receiptStatus": "ConfirmationreceivefromDepositor",
    "oicStatus": "PendingatCentralRegistry",
    "ceoStatus": "Pendingforregistration",
    "paymentStatus": "Pending",
    "vchWarehouseId": "WAR20250227001"
  }
]
}

```

Error Responses

```

{
  "status": "error",
  "message": "Invalid or missing issuelid"
}

```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.5 API for: Registration of Warehouse Receipt

❖ Use Cases

This API registers a warehouse receipt by uploading the certificate file associated with the given receiptId. It is primarily used by warehouse operators and administrators to validate and register warehouse receipts. Upon successful upload, the certificate file is stored and the receipt's registration status is updated.

❖ Service Request Name and URL

URL	http://localhost:8888/api/issuance/pushRegistrationCertificateByReceiptId/{receiptId}
Method	POST

❖ Header

Token

```
eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwiaXhwaWJjoxNzQzNTAzNTE4LCJpYXQiOiE3NDM0OTk5MTgslmp0aSI6ImVIZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWw3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkj390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomsIfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaaj8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0rA
```

❖ **Sample Response Template**

```
{
  "status": "success",
  "message": "Certificate uploaded successfully",
  "receiptId": "WR-120-2025",
  "fileName": "CERT_WR-120-2025_1716448394531.pdf"
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.6 API for: Get market-data

❖ Use Cases

Get current market price data of commodities in the system. This helps maintain real-time or daily price availability for accurate valuation and operations such as pledging, issuance, and trading.

❖ *Service Request Name and URL*

URL	http://localhost:8888/commodities/getMarketData
-----	---

Method	GET
--------	-----

❖ **Header****Token**

eyJhbGciOiJSUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlZ3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWw3M3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-zNivTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRjkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Response Description**

```
[
  {
    "id": 1,
    "timestamp": "2025-05-20",
    "openPrice": 190.65,
    "highPrice ": 158.49,
    "lowPrice": 155.98,
    "closingPrice": 157.97,
    "commodity_name": "Sorghum Five"
  },
  {
    "id": 2,
    "timestamp": "2025-05-20",
    " openPrice ": 160.12,
    " highPrice ": 162.5,
    " lowPrice ": 158.75,
    " closingPrice ": 161.3,
    "commodity_name": "Beans"
  }
]
```

Error Responses

- 404 Depositor not found with the given email ID

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found with the given email ID (No data for provided email ID)
- 500– Internal Server Error (Third-party service failure)

6.7 API for: Save Market Data**❖ Use Cases**

Update current market price data of commodities in the system. This helps maintain real-time or daily price availability for accurate valuation and operations such as pledging, issuance, and trading.

❖ Service Request Name and URL

URL	http://localhost:8888/commodities/saveMarket-data
Method	POST

❖ Header**Token**

eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwljoxNzQzNTAzNTE4LCJpYXQiOiJlE3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWw3M3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ Request Body

```
{
  "IssuanceId": 1,
  "commodityName": "Sorghum Five",
```

```

    "timestamp": "2025-05-20",
    "marketPrice": "223",
    "marketValue": "456",
    "openPrice": 190.65,
    "closingPrice": 157.97,
    "sellingPriceUpperLimit": 158.49,
    "sellingPriceLowerLimit": 155.98,
    "highPrice": 162.5,
    "lowhPrice": 158.75
  }

```

❖ **Response Description**

```

{
  "status": 200,
  "message": "Market data saved successfully"
}

```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.8 API for: Get Listing Price By receiptId

❖ **Use Cases**

This api used to Fetch Listing Price by Receipt ID in the Electronic Warehouse Receipt System (eWRS):.

❖ **Service Request Name and URL**

URL	http://localhost:8888/commodities/listing-price/{receiptId}
Method	GET

❖ **Header**

Token

eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmIjoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlZ3NDMD0OTk5MTgsImp0aSI6ImVIZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAIAWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8IHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Request Body**

GET /api/listing-price/WR-120-2025

❖ **Response Description**

```
{
  "status": "success",
  "message": "Listing price fetched successfully",
  "data": {
    "receiptId": "WR-120-2025",
    "commodityName": "Maize",
    "sellingPriceUpperLimit": 158.49,
    "sellingPriceLowerLimit": 155.98
  }
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.9 API for: Pledging of Warehouse Receipt

❖ **Use Cases**

This API allows a depositor to initiate a loan request by pledging a warehouse receipt with a financial institution. The loan details, such as amount, duration, and proposed

clearance date, are submitted for further processing.

❖ **Service Request Name and URL**

URL	http://localhost:8888/api/savePledging
Method	POST

❖ **Header**

Token

eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbmthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwizXhwIjoxNzQzNTAzNTE4LCJpYXQiOiJlE3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWw3M3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Request Body**

```
{
  "financialInstitution": "bank1",
  "dateOfPledging": "30 May, 2025",
  "proposedLoanAmount": 95000.55,
  "proposedDateOfLoanClearance": "24 October, 2025",
  "durationOfLoan": 4,
  "depositorId": "4M238M8V67",
  "issued": 1,
  "userId": 204,
  "userName": "Alice",
  "roleId": 6,
  "roleName": "Warehouse Operator"
}
```

❖ **Response Description**

```
{
```

```
"status": 200,
"message": "Pledging request submitted successfully"
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.10 API for: Loan Sanction

❖ Use Cases

This API fetches the loan sanction status and related details associated with a specific warehouse receipt or issuance based on the provided issuanceId . It is primarily used by authorized users such as financial institution officers and administrators to determine whether a loan has been sanctioned or rejected. Upon successful request, the API returns the loan status along with relevant sanction or rejection details for validation, processing, or reference.

❖ Service Request Name and URL

URL	http://localhost:8888/api/sanction-details
Method	GET

❖ Header

Token

```
eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6InByaXlhbWthliwibmJmljoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LCJpYXQiOiE3NDM0OTk5MTgsImp0aSI6ImVlZDkxZjQyLWlyMDQtNGJlYy04ZDFjLWw3M3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETljkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAlaWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjth4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra
```

❖ **Request Body**

```
{
  "wareHouseReceiptNo": "WR-124-2025",
  "loanId": 7
}
```

❖ **Response Description**

```
{
  "sanctionedLoanAmount": 85500,
  "approvedDateOfLoanClearance": "2026-06-12",
  "approvedDurationOfLoan": 12,
  "interestRate": 8,
  "loanStatus": "SANCTIONED",
  "rejectionReason": null
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.11 API for: Transfer to New Depositor❖ **Use Cases**

This API allows transfers a *Warehouse Receipt* to a new depositor while retiring the old depositor and saving the new depositor's details.

❖ **Service Request Name and URL**

URL	http://localhost:8888/api/issuance/saveTransfer
-----	---

Method	POST
--------	------

❖ **Header****Token**

eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbmthliwibmJmljoxNzQzNDk5OTE4LClzY29wZSI6WyJyZWFKliwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4liwiZXhwIjoxNzQzNTAzNTE4LClpYXQiOiJlbnR0cDovL2xvY2FsaG9zdDo4ODg4liJlYy04ZDZlLWM3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlep29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAiaWVPBjP97XO-zNivTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVbemV1WSq1ZnUeghYhEKMN-m32k3VYiso8amfJE_ndaij8lHEOIBNXpq3dRjkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Request Body**

```
{
  "receiptId": "WR-120-2025",
  "oldDepositorId": "DEP123456",
  "retirementStatus": true,
  "transferDate": "2025-05-20",
  "transferReason": "Change of ownership",
  "newDepositorDetails": {
    "typeOfDepositor": "Individual",
    "nameOfDepositor": "John Doe",
    "mobileNumber": "+254712345678",
    "emailAddress": "john.doe@example.com",
    "postalCode": "00100",
    "postalAddress": "P.O. Box 12345 - 00100 Nairobi",
    "county": "Nairobi",
    "subCounty": "Westlands",
    "ward": "Parklands",
    "nationality": "Kenyan",
    "entityRegistrationNumber": "BRN123456789",
    "governmentIssuedID": "National ID",
    "idNumber": "12345678"
  }
}
```



```
}
}
```

❖ **Response Description**

```
{
  "status": 200,
  "message": "Warehouse Receipt transferred to new depositor and old depositor marked as retired",
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)

6.12 API for: Retire Warehouse Receipt

❖ **Use Cases**

This API is used to retire a Warehouse Receipt (WR) after it has been settled (loan repaid, commodity withdrawn, etc.). It updates the status of the WR to indicate it is no longer active.

❖ **Service Request Name and URL**

URL	http://localhost:8888/api/receipt/retire
Method	POST

❖ **Header**

Token

```
eyJhbGciOiJIUzI1NiJ9.eyJzdWUiOiJwcmI5YW5rYSIsImF1ZCI6ImByaXlhbWthliwibmJmIjoxNzQzNDk5OTE4LCJzY29wZSI6WyJyZWZkIiwid3JpdGUiXSwiaXNzIjoiaHR0cDovL2xvY2FsaG9zdDo4ODg4IiwiaXZxhWljoXNzQzNTAzNTE4LCJpYXQiOiJlE3NDM0OTk5MTgsImp0aSI6ImVIZDkxZjQyLWlyMDQtNGJlYy00ZDFjLWw3NGI0ZWYyMTRhYyJ9.AwhcN6tVutxY7M1YLyQe6QtKUZZlepb29x5wiOETIjkjJ390w51RkpxlqJc8Z4uvRp0TJzxo4xOXDALCLzUus4eogHpmkq66HfxnQ-LDhKq1bnw-IgMtrvCJWrjwNiKCwh9F0LpzDkYPkV1UAIAWVPBjP97XO-zNlvTnkgomslfkGgaTGab5bfXwukjgURf3zi1KW2JJKGNC5GXf72zYWB-PBSdjtH4J6YPCdSt4s9p3uDVBemV1WSq1ZnUeghYhEKMN-
```

m32k3VYiso8amfJE_ndaij8lHEOlBNXpq3dRJkiUFLfzfdhGVAcqdto6Wdxw-iWo44qSOPBueDV-Ee0Ra

❖ **Request Body**

```
{
  "amountExpected": "6106137.25",
  "clientIdNumber": "12345",
  "currency": "KES",
  "billRefNumber": "e188ce5e-4320-4690-a4d3-d52f0ae97f30",
  "billDesc": "Payment for Commodity.",
  "clientName": "Depositor",
  "isretire": "true",
  "depositorId": "8J733J3H57",
  "issuanceId": 3,
  "userId": 204,
  "userName": "Alice",
  "roleId": 6,
  "roleName": "Warehouse Operator"
}
```

❖ **Response Description**

```
{
  "status": "success",
  "message": "Warehouse Receipt retired successfully"
}
```

Status Codes:

- 200 - OK
- 400 - Bad Request
- 401– Unauthorized (Invalid token)
- 404– Not Found (No data for provided ID)
- 500– Internal Server Error (Third-party service failure)