Ex.No.:11 SINGLE PASS ASSEMBLER

Date:

AIM:

To implement a single pass assembler in C language.

ALGORITHM:

- 1. Open and Read the input file
- 2. If the input line has the opcode "START" do the following
- 2.1 Find if there is any operand field after "START", initialize the LC to the operand value
- 2.2 Otherwise if there is no value in the operand field then LC is set to 0
- 3. Write the input line to the intermediate file
- 4. Do the following steps until the opcode is END
- 4.1 Check the Symbol table, if the symbol is not available then enter that symbol into the SYMTAB, along with the memory address in which it is stored. Otherwise, the error message should be displayed
- 4.2 If there is a opcode
- 4.2.1 If opcode is present in the OPTAB, then increment the LC by 3 and Start writing the location counter, opcode and operand fields of the corresponding statement to the output file, along with the object code.
- 4.2.2 If opcode is "WORD", then increment LC by 3;
- 4.2.3 If opcode is "BYTE", then increment LC by 1;
- 4.2.4 If opcode is "RESW" then increment LC by the integer equivalent of the operand value * 3;
- 4.2.5 If opcode is "RESB", then increment LC by the integer equivalent of the operand value
- 4.2.6 If there is no symbol/label in the operand field, then the operand address is assigned as zero and it is assembled with the object code of the instruction
- 4.2.7 Write the processed lines in the intermediate file along with their location counters
- 5. To find the length of the program, Subtract the starting address of the program from the final value of the LC

Close all the files and exit

PROGRAM:

```
#include<stdio.h>
#include<string.h>
int findInSYMTAB(char
findLabel[]){FILE *SYMTAB;
char label[30],addr[30];
SYMTAB=fopen("symtab.dat","r");
fscanf(SYMTAB,"%s%s",label,addr);
while(1){
if(feof(SYMTAB)){
fclose(SYMTAB);
break;
if(strcmp(findLabel,label)==0){fclose(
SYMTAB);
return atoi(addr);
fscanf(SYMTAB,"%s%s",label,addr);
int getMnemonicCode(char
mnemonic[]){if(strcmp(mnemonic,"LDA
")==0)
return 33;
else if(strcmp(mnemonic,"STA")==0)
return 44;
else if(strcmp(mnemonic,"LDCH")==0)
return 53;
else if(strcmp(mnemonic,"STCH")==0)
return 57;
else
return -1;
void main(){
FILE *INPUT,*OUTPUT,*SYMTAB,*INTERMEDIATE,*FINAL,*OBJ;
```



```
int LOCCTR, start=0, j=0, i, length, Tlength, count=0, final Address, start Addr;
char label[20],opcode[20],operand[20],address[20];
INPUT=fopen("input.dat","r");
OUTPUT=fopen("output.dat","w");
SYMTAB=fopen("symtab.dat","w");
fscanf(INPUT,"%s%s%s",label,opcode,operand);
if(strcmp(opcode, "START")==0){ start=atoi(opera
nd);
LOCCTR=start;
fprintf(OUTPUT,"t%st%st%sn",label,opcode,operand);
fscanf(INPUT,"%s%s%s",label,opcode,operand);
}else
LOCCTR=0;
while(strcmp(opcode,"END")!=0){j=0;
fprintf(OUTPUT,"%d",LOCCTR);
if(strcmp(label,"**")!=0)
fprintf(SYMTAB,"t%st%dn",label,LOCCTR);
while(strcmp(mnemonic[j],"END")!=0){ if(strcmp(
mnemonic[i],opcode)==0){ LOCCTR+=3;
j++;
if(strcmp(opcode,"WORD")==0)
LOCCTR+=3;
else if
(strcmp(opcode,"RESW")==0){ LOCCT
R=LOCCTR+(3* atoi(operand));
count+=(3* atoi(operand));
else if
(strcmp(opcode,"RESB")==0){LOCC
TR=LOCCTR+atoi(operand);
count+=atoi(operand);
else if (strcmp(opcode, "BYTE")==0){
```

```
LOCCTR=LOCCTR+(strlen(operand)-3);
else
{ printf("
");
fprintf(OUTPUT,"t%st%st%sn",label,opcode,operand);
fscanf(INPUT,"%s%s%s",label,opcode,operand);
fprintf(OUTPUT,"%d",LOCCTR);
fprintf(OUTPUT,"t%st%st%sn",label,opcode,operand);
printf("nn THE LENGTH OF THE PROGRAM IS %d",LOCCTR-start);
length=LOCCTR-start;
finalAddress=LOCCTR;
Tlength=length-count;
fcloseall();
INTERMEDIATE=fopen("output.dat","r");
OBJ=fopen("obj.dat","w");
FINAL=fopen("final.dat","w");
fscanf(INTERMEDIATE,"%s%s%s",label,opcode,operand);
startAddr=atoi(operand);
if(strcmp(opcode, "START")==0){ fprintf(FINAL, "%st%st%stn", label, opcode,
operand); fprintf(OBJ,"H^\%s^00\%s^00\%dn",label,operand,length);
fscanf(INTERMEDIATE,"%s%s%s%s",address,label,opcode,operand);
fprintf(OBJ,"T^\%06d^\%d^\",atoi(address),Tlength);
while(strcmp(opcode,"END")!=0){if(s
trcmp(label,"**")==0){
fprintf(OBJ,"%d%d^",getMnemonicCode(opcode),findInSYMTAB(operand));
fprintf(FINAL,"%st%st%st%st%d%dn",address,label,opcode,operand,getMnemonicC
ode(opcode),findInSYMTAB(operand));
fscanf(INTERMEDIATE,"%s%s%s%s",address,label,opcode,operand);
}
```

```
else
 if(strcmp(opcode,"BYTE")==0){ fprintf(FINAL,"%st%st%st
 %s",address,label,opcode,operand); for(i=2;i<(strlen(operand)-
 1);i++){ fprintf(OBJ,"%x",operand[i]);
 fprintf(FINAL,"%x",operand[i]);
 fprintf(FINAL,"n");
 fscanf(INTERMEDIATE,"%s%s%s%s",address,label,opcode,operand);
 }
 else
if(strcmp(opcode,"WORD")==0){fpri
ntf(OBJ,"%06x^",atoi(operand));
 fprintf(FINAL,"%st%st%st%st%06xn",address,label,opcode,operand,atoi(operand));
Name: Hariharan M
Register Number: 913121205028
21CS211-Operating Systems Laboratory Dept of IT
 fscanf(INTERMEDIATE,"%s%s%s%s",address,label,opcode,operand);
 }
 else { fscanf(INTERMEDIATE,"%s%s%s%s",address,label,opcode,opera
nd);
 }
 fprintf(FINAL,"%st%st%st%sn",address,label,opcode,operand);
 fprintf(OBJ,"nE^\%06dn",startAddr);
 fcloseall();
remove("output.dat");
 }
Input Files:
input.dat
** START 2000
** LDA FIVE
** STA ALPHA
** LDCH STRING
** STCH C1
ALPHA RESW 1
FIVE WORD 5
STRING BYTE C'HELLO'
C1 RESB 1
```

Roll No:21CSE107

** END **	
Name:R.K.Hariharan	Roll No:21CSE107

Output files

final.dat (output generated)

** START 2000

2000 ** LDA FIVE 332015

2003 ** STA ALPHA 442012

2006 ** LDCH STRING 532018

2009 ** STCH C1 572023

2015 FIVE WORD 5 000005

2018 STRING BYTE C'HELLO'48454c4c4f

2024 ** END **

symtab.dat (SYMTAB)

ALPHA 2012

FIVE 2015

STRING 2018

C1 2023

obj.dat (object code generated)

H^**^002000^0024

T^002000^20^332015^442012^532018^572023^000005^48454c4c4f

E^002000

Output:

a Minnoco, nama mo					
"NTURBOC3\BIN>TC "m" THE LENGTH OF "	THE PROGRAM I	S 24Abnormal	program ter	mination	
ull pointer assignmen			#5:5:4 5:5:5		
5 (5) (5) (5)					

Observation	
Record	
Total	
Initial	

RESULT:

Thus single pass assembler is implemented in C language.

Ex.No: 12a PASS ONE OF A TWO PASS ASSEMBLER

Date:

AIM:

To write a "c" program to implement pass one of a two pass assembler

ALGORITHM:

- 1. Open and Read the input file
- 2. If the input line has the opcode "START" do the following
- 2.1 Find if there is any operand field after "START", initialize the LOCCTR to the operand value
- 2.2 Otherwise if there is no value in the operand field then LOCCTR is set to 0
- 3. Write the input line to the intermediate file
- 4. Do the following steps until the opcode is END
- 4.1 If opcode is "WORD", then increment LOCCTR by 3;
- 4.2 If opcode is "BYTE", then increment LOCCTR by 1;
- 5. Write the processed lines in the intermediate file along with their location counters
- 6. To find the length of the program, Subtract the starting address of the program from the final value of the LOCCTR

Close all the files and exit

Program:

```
#include<stdio.h>
#include<string.h>
void main()
{
FILE *f1,*f2,*f3,*f4;
int lc,sa,l,op1,o,len;
char m1[20],la[20],op[20],otp[20];
Name: Hariharan M
Register Number: 913121205028
21CS211-Operating Systems Laboratory Dept of IT
f1=fopen("input.txt","r");
```

```
f3=fopen("symtab.txt","w");
fscanf(f1,"%s%s%d",la,m1,&op1);
if(strcmp(m1,"START")==0)
{
sa=op1;
lc=sa;
printf("\t%s\t%s\t%d\n",la,m1,op1);
}
else
1c=0;
fscanf(f1,"%s%s",la,m1);
while(!feof(f1))
{
fscanf(f1,"%s",op);
printf("\n%d\t%s\t%s\n",lc,la,m1,op);
if(strcmp(la,"-")!=0)
fprintf(f3,"\n%d\t%s\n",lc,la);
}
f2=fopen("optab.txt","r");
fscanf(f2,"%s%d",otp,&o);
while(!feof(f2))
if(strcmp(m1,otp)==0)
1c=1c+3;
```

```
break;
fscanf(f2,"%s%d",otp,&o);
}
fclose(f2);
if(strcmp(m1,"WORD")==0)
{
1c=1c+3;
else if(strcmp(m1,"RESW")==0)
op1=atoi(op);
lc=lc+(3*op1);
else if(strcmp(m1,"BYTE")==0)
\{ if(op[0] == '
X')
1c=1c+1;
else
len=strlen(op)-2;
1c=lc+len;
else if(strcmp(m1,"RESB")==0)
```

```
op1=atoi(op);
lc=lc+op1;
fscanf(f1,"%s%s",la,m1);
}
if(strcmp(m1,"END")==0)
{
printf("program length=\n%d",lc-sa);
fclose(f1);
fclose(f3);
Input Files:
input.txt
copy START 1000
LDA ALPHA
ADD ONE
SUB TWO
STABETA
ALPHA BYTE C'KLNCE
ONE RESB 2
TWO WORD 5
BETA RESW 1
_ END _
optab.txt
LDA 00
STA 23
ADD 01
```

Roll No:21CSE107

SUB 05

symtab.txt

1000 LDA

1000 ONE

1003 STA

1003 BYTE

1003 RESB

1003 WORD

1003 RESW

1003 END

OUTPUT:

```
C:\TURBOC3\BIN>TC
COPY START 1999
1000
       LDA
               ALPHA
1.000
       ONE
               SUB
1000
       STA
               BETA
               C'UCET
1000
       BYTE
1000
       RESB
               2
1000
       WORD
1000
       RESW
```

RESULT:

Thus the "c" program to implement pass one of a two pass assembler has been written and executed successfully

Ex.No: 12b PASS TWO OF TWO PASS ASSEMBLER

Date:

AIM:

To implement pass two of a two pass assembler in C language.

ALGORITHM:

- 1. Open and read the first line from the intermediate file.
- 2. If the first line contains the opcode "START", then write the label, opcode and operand field values of the corresponding statement directly to the final output file.
- 3. Do the following steps, until an "END" statement is reached.
- 3.1 Start writing the location counter, opcode and operand fields of the corresponding statement to the output file, along with the object code.
- 3.2 If there is no symbol/label in the operand field, then the operand address is assigned as zero and it is assembled with the object code of the instruction
- 3.3 If the opcode is BYTE, WORD, RESB etc convert the constants to the object code.
- 4. Close the files and exit

Program:

```
#include<stdio.h>
#include<conio.h>
#include<string.h>
void main()
char a[10],ad[10],label[10],opcode[10],operand[10],symbol[10],ch; int
st,diff,i,address,add,len,actual len,finaddr,prevaddr,j=0;
char mnemonic[15][15]={"LDA", "STA", "LDCH", "STCH"};
char code[15][15]={"33","44","53","57"};
FILE *fp1,*fp2,*fp3,*fp4;
clrscr();
fp1=fopen("ASSMLIST.DAT","w");
fp2=fopen("SYMTAB.DAT","r");
fp3=fopen("INTERMED.DAT","r");
fp4=fopen("OBJCODE.DAT","w");
fscanf(fp3,"%s%s%s",label,opcode,operand);
while(strcmp(opcode,"END")!=0)
prevaddr=address;
fscanf(fp3,"%d%s%s%s",&address,label,opcode,operand);
finaddr=address;
fclose(fp3);
fp3=fopen("INTERMED.DAT","r");
fscanf(fp3,"%s%s%s",label,opcode,operand);
if(strcmp(opcode, "START")==0)
```

```
fprintf(fp1,"\t%s\t%s\n",label,opcode,operand);
fprintf(fp4,"H^\%s^00\%s^00\%d\n",label,operand,finaddr);
fscanf(fp3,"%d%s%s%s",&address,label,opcode,operand);
st=address;
diff=prevaddr-st;
fprintf(fp4,"T^00%d^%d",address,diff);
while(strcmp(opcode,"END")!=0)
if(strcmp(opcode,"BYTE")==0)
fprintf(fp1,"%d\t%s\t%s\t%s\t",address,label,opcode,operand);
len=strlen(operand);
actual len=len-3;
fprintf(fp4,"^");
for(i=2;i<(actual len+2);i++)
itoa(operand[i],ad,16);
fprintf(fp1,"%s",ad);
fprintf(fp4,"%s",ad);
fprintf(fp1,"\n");
else if(strcmp(opcode,"WORD")==0)
len=strlen(operand);
itoa(atoi(operand),a,10);
fprintf(fp1,"%d\t%s\t%s\t00000%s\n",address,label,opcode,operand,a);
fprintf(fp4,"^00000%s",a);
else if((strcmp(opcode, "RESB")==0)||(strcmp(opcode, "RESW")==0))
fprintf(fp1,"%d\t%s\t%s\t%s\n",address,label,opcode,operand);
else
while(strcmp(opcode,mnemonic[j])!=0)j++;
if(strcmp(operand,"COPY")==0)
fprintf(fp1,"%d\t%s\t%s\t%s\t%s\0000\n",address,label,opcode,operand,code[i]);
else
rewind(fp2);
fscanf(fp2,"%s%d",symbol,&add);
while(strcmp(operand,symbol)!=0)
fscanf(fp2,"%s%d",symbol,&add);
fprintf(fp1,"%d\t%s\t%s\t%s\t%s\d\n",address,label,opcode,operand,code[i],add);
fprintf(fp4,"^%s%d",code[i],add);
fscanf(fp3,"%d%s%s%s",&address,label,opcode,operand);
fprintf(fp1,"%d\t%s\t%s\t%s\n",address,label,opcode,operand);
```

```
fprintf(fp4,"\nE^00\%d",st);
printf("\n Intermediate file is converted into object code");
fcloseall();
printf("\n\nThe contents of Intermediate file:\n\n\t");
fp3=fopen("INTERMED.DAT","r");
ch=fgetc(fp3);
while(ch!=EOF)
printf("%c",ch);
ch=fgetc(fp3);
printf("\n\nThe contents of Symbol Table :\n\n");
fp2=fopen("SYMTAB.DAT","r");
ch=fgetc(fp2);
while(ch!=EOF)
printf("%c",ch);
ch=fgetc(fp2);
printf("\n\nThe contents of Output file :\n\n");
fp1=fopen("ASSMLIST.DAT","r");
ch=fgetc(fp1);
while(ch!=EOF)
printf("%c",ch);
ch=fgetc(fp1);
printf("\n\nThe contents of Object code file :\n\n");
fp4=fopen("OBJCODE.DAT","r");
ch=fgetc(fp4);
while(ch!=EOF)
printf("%c",ch);
ch=fgetc(fp4);
fcloseall();
getch();
INPUT FILES:
INTERMED.DAT
COPY START 2000
2000 ** LDA FIVE
2003 ** STA ALPHA
2006 ** LDCH CHARZ
2009 ** STCH C1
2012 ALPHA RESW 1
2015 FIVE WORD 5
2018 CHARZ BYTE C'EOF'
2019 C1 RESB 1
2020 ** END **
SYMTAB.DAT
```

ALPHA 2012 FIVE 2015 CHARZ 2018 C1 2019

OUTPUT:

```
BOSBox 0.74-3, Cpu speed: max 100% cycles, Frameskip 0, Pro.
ALPHA
         2012
FIVE
CHARZ
        2015
         2018
     2019
C1
The contents of Output file :
        COPY
                START
2000
        **
                LDA
                        FIVE
                                 332015
2003
        жн
                STA
                        ALPHA
                                 442012
2006
        ж
                LDCH
                        CHARZ
                                 532018
2009
                STCH
                        C1
                                 572019
2012
2015
        ALPHA
                RESW
                                 000005
        FIUE
                MORD
                        C'EOF' 454f46
        CHARZ
2018
                BYTE
2019
                RESB
        C1
                        1
                END
2020
        HH
The contents of Object code file:
H^C0PY^00Z000^00Z0Z0
 ^002000^19^332015^442012^532018^572019^000005^454f46
```

Observation	
Record	
Total	
Initial	

RESULT:

Thus pass two of a two pass assembler is implemented in C language.