ECOMIN Planet



Ceiling tiles made from new generation bio-soluble mineral wool, clay and starch with excellent fire resistance and acoustic performance.

SYSTEM	C Exposed Grid System, demountable ceiling
Dimensions	600 x 600 mm, 625 x 625 mm, tolerances as per EN 13964
Thickness / Weight	nom. 13 mm (3.6 kg/m²)
Colour	White similar to RAL 9010
Edge details	SK



SK 15/24

TECHNICAL PERFORMANCE

Reaction to fire	A2-s1, d0 as per EN 13501-1
Sound absorption	as per EN ISO 354 α_w = 0.55 as per EN ISO 11654 NRC = 0.55 as per ASTM C 423
Light reflectance	Up to 88%
Thermal conductivity	λ = 0.052 - 0.057 W/mK as per DIN 52612
Humidity	Up to 70% RH



Knauf AMF Ceilings Ltd.
Thames House, 6 Church Street
Twickenham, Middlesex TW1 3NJ
Tel: 020 8892 3216, Fax: 020 8892 6866
sales@amfceilings.co.uk, www.amfceilings.co.uk

Due to reproduction processes colours shown in this catalogue may differ from the actual product colour. Product selection should always be made from AMF samples. All details and technical information stated in this brochure or other publicity material referring to AMF ceiling systems are based on test reports obtained under laboratory conditions. It is the responsibility of the customer to ensure that this data is suitable for the proposed application.

All information provided is current technical data. All relevant test reports, assessments and installation guidelines are to be considered. All system details conform with current technology and are based on the use and compatibility of AMF products and system components used in both internal and external tests. AMF accepts no liability or responsibility for use of third party components, or for any variations to conditions stipulated in test data.
We recommend not to mix production batches on jobs.

All technical data is subject to change without prior notice and is governed by AMF Terms and Conditions of Sales. This catalogue supersedes all previous editions. Errors and omissions excepted. Printing errors excepted.