



Exam 1Z0-808

Java SE 8 Programmer I

Version: 7.0

[Total Questions: 142]



1. Given the code fragment:

```

public static void main (String [] args) {
    String names [] = {"Thomas", "Peter", "Joseph");
    String pws [] = new String [3];
    int idx = 0;
    try {
        for (String n: names) {
            pwd [idx] = n.substring (2, 6);
            idx++;
        }
    } catch (Exception e) {
        System.out.println ("Invalid Name");
    }
    for (String p: pws) {
        System.out.println (p);
    }
}

```

What is the result?

- A. Invalid Name
- B. Invalid Nameomas
- C. Invalid Nameomasnullnull**
- D. omasterseph

Answer: C

2. Given the code fragment:

```

4. class X {
5.     public void printFileContent () {
6.         /* code goes here */
7.         throw new IOException ();
8.     }
9. }
10. public class Test {
11.     public static void main (String [] args) {
12.         X xobj = new X ();
13.         xobj.printFileContent ();
14.     }
15. }

```





Which two modifications should you make so that the code compiles successfully?

- A. At line 14, insert throw new IOException();
- B. Replace line 5 with public void printFileContent () throws IOException {
- C. Replace line 11 with public static void main (String [] args) throws Exception {
- D. Replace line 13 with:

```
try {
    xobj.printFileContent ();
}
catch (Exception e) {}
catch (IOException e) {}
```

- E. Replace line 7 with throw IOException ("Exception raised");

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

Answer: E

3. Given the code fragment:

```
public class Test{

    void readCard(int cardNo) throws Exception {
        System.out.println("Reading Card");
    }

    void checkCard(int cardNo) throws RuntimeException { // line n1
        System.out.println("Checking Card");
    }

    public static void main(String[] args) {
        Test ex = new Test();
        int cardNo = 12344;
        ex.checkCard(cardNo);                      //line n2
        ex.readCard(cardNo);                      //line n3
    }
}
```

What is the result?

- A. Reading CardChecking Card
- B. Compilation fails only at line n1.
- C. Compilation fails only at line n2.
- D. Compilation fails only at line n3.**



E. Compilation fails at both line n2 and line n3.

Answer: D

4. Given the code fragment:

```
public class Test {

    static int count = 0
    int i = 0;

    public void changeCount () {
        while (i<5) {
            i++;
            count++;
        }
    }

    public static void main (String [] args) {
        Test check1 = new Test ();
        Test check2 = new Test ();
        check1.changeCount ();
        check2.changeCount ();
        System.out. print (check1.count + " : " + check2.count);
    }
}
```

What is the result?

A. 5 : 5

B. 10 : 10

C. 5 : 10

D. Compilation fails.

Answer: B

Explanation: References:

5. Given the code fragment:

```
public static void main(String[] args) {
    LocalDate date = LocalDate.of(2012, 01, 32);
    date.plusDays(10);
    System.out.println(date);
}
```

What is the result?

A. 2012-02-10



B. 2012-02-11

C. Compilation fails

D. A DateTimeException is thrown at runtime.

Answer: C

6. Given the code fragment:

```
public class App {  
    public static void main(String[] args) {  
        String str1 = "Java";  
        String str2 = new String("java");  
        //line n1  
        {  
            System.out.println("Equal");  
        } else {  
            System.out.println("Not Equal");  
        }  
    }  
}
```

Which code fragment, when inserted at line n1, enables the App class to print Equal?

- A) String str3 = str2;
if (str1 == str3)
- B) if (str1.equalsIgnoreCase(str2))
- C) String str3 = str2;
if (str1.equals(str3))
- D) if (str1.toLowerCase() == str2.toLowerCase())

A. Option A

B. Option B

C. Option C

D. Option D

Answer: B

7. Which three statements are true about the structure of a Java class?

A. A public class must have a main method.

B. A class can have only one private constructor.



C. A method can have the same name as a field.

D. A class can have overloaded static methods.

E. The methods are mandatory components of a class.

F. The fields need not be initialized before use.

Answer: A,C,E

8. Given the code fragments:

A.java:

```
package p1;  
public class A {  
}
```

B.java:

```
package p1.p2;  
//line n1  
public class B {  
    public void doStuff () {  
        A b = new A ();  
    }  
}
```

C.java

```
package p3;  
//line n2  
public class C {  
    public static void main (String [] args) {  
        A o1 = new A ();  
        B o2 = new B ();  
    }  
}
```

Which modification enables the code to compile?

A. Replace line n1 with:`import p1.*;`Replace line n2 with:`import p1. p2.*;`

B. Replace line n1 with:`import p1. A;`Replace line n2 with:`import p1.*;`

C. Replace line n1 with:`import p1. A;`Replace line n2 with:`import p1. A;import p1. p2.B ;`

D. Replace line n1 with:`import p1;`Replace line n2 with:`import p1;import p1. p2;`

Answer: C



9. Given:

```

class A {
    public void test () {
        System.out.println ("A");
    }
}
class B extends A {
    public void test () {
        System.out.println ("B");
    }
}
public class C extends A {
    public void test () {
        System.out.println ("C");
    }
}

public static void main (String [] args) {
    A b1 = new A ();
    A b2 = new C ();
    b1 = (A) b2;
    A b3 = (B) b2;           //line n1
    A b3 = (B) b2;           //line n2
    b1.test ();
    b3.test ();
}
}

```

What is the result?

- A. AB
- B. AC
- C. CC
- D. A ClassCastException is thrown only at line n1.**
- E. A ClassCastException is thrown only at line n2.

Answer: B

10. Which code fragment causes a compilation error?

A. float flt = 100F;
 B. float flt = (float) 1_11.00;
 C. float flt = 100;
 D. double y1 = 203.22;
 float flt = y1;
 E. int y2 = 100;
 float flt = (float) y2;

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

Answer: D

11. Given the code fragment:

```
public static void main(String[] args) {
    try {
        int num = 10;
        int div = 0;
        int ans = num / div;
    } catch (ArithmaticException ae) {
        ans = 0                                // line n1
    } catch (Exception e) {
        System.out.println("Invalid calculation");
    }
    System.out.println("Answer = " + ans);      // line n2
}
```

What is the result?

A. Answer = 0

B. Invalid calculation

C. Compilation fails only at line n1.

D. Compilation fails only at line n2.

E. Compilation fails only at line n1 and line 2.

Answer: E



12. Given the following class:

```
public class Rectangle {  
    private double length;  
    private double height;  
    private double area;  
  
    public void setLength(double length) {  
        this.length = length;  
    }  
    public void setHeight(double height) {  
        this.height = height;  
    }  
    public void setArea() {  
        area = length*height;  
    }  
}
```

Which two changes would encapsulate this class and ensure that the area field is always equal to length * height whenever the Rectangle class is used?

- A. Call the setArea method at the end of the setHeight method.
- B. Call the setArea method at the beginning of the setHeight method.
- C. Call the setArea method at the end of the setLength method.
- D. Call the setArea method at the beginning of the setLength method.
- E. Change the setArea method to private.
- F. Change the area field to public.

Answer: A,E

13. Given the code fragment:

```
int n [] [] = {{1, 3}, {2, 4}};
for (int i = n.length-1; i >= 0; i--) {
    for (int y : n[i]) {
        System.out.print (y);
    }
}
```

What is the result?

A. 1324

B. 2413

C. 3142

D. 4231

Answer: C

14. Which statement is true about the switch statement?

A. It must contain the default section.

B. The break statement, at the end of each case block, is mandatory.

C. Its case label literals can be changed at runtime.

D. Its expression must evaluate to a single value.

Answer: D

15. Given the code fragment:

```

public class Person {
    String name;
    int age = 25;

    public Person(String name) {
        this();                                     //line n1
        setName(name);
    }

    public Person(String name, int age) {
        Person(name);                             //line n2
        setAge(age);
    }

    //setter and getter methods go here

    public String show() {
        return name + " " + age + " " + number ;
    }
    public static void main(String[] args) {
        Person p1 = new Person("Jesse");
        Person p2 = new Person("Walter",52);
        System.out.println(p1.show());
        System.out.println(p2.show());
    }
}

```

What is the result?

- A. Jesse 25Walter 52
- B. Compilation fails only at line n1
- C. Compilation fails only at line n2
- D. Compilation fails at both line n1 and line n2**

Answer: B

16. Given:

```

public class Test {
    public static int stVar = 100;
    public int var = 200;
    public String toString() {
        return var + ":" + stVar;
    }
}

```

And given the code fragment:



```
Test t1 = new Test();
t1.var = 300;
System.out.println(t1);
Test t2 = new Test();
t2.stVar = 300;
System.out.println(t2);
```

What is the result?

- A. 300:300200:300
- B. 300:100200:300**
- C. 300:00:300
- D. 200:300200:300

Answer: D

17. Given the definitions of the MyString class and the Test class:

MyString.java:

```
package p1;
class MyString {
    String msg;
    MyString(String msg) {
        this.msg = msg;
    }
}
```

Test.java:

```
package p1;
public class Test {
    public static void main(String[] args) {
        System.out.println("Hello " + new StringBuilder("Java SE 8"));
        System.out.println("Hello " + new MyString("Java SE 8"));
    }
}
```

What is the result?

- A) Hello Java SE 8
Hello Java SE 8
- B) Hello java.lang.StringBuilder@<<hashcode1>>
Hello p1.MyString@<<hashcode2>>
- C) Hello Java SE 8
Hello p1.MyString@<<hashcode>>
- D) Compilation fails at the Test class.

A. Option A

B. Option B

C. Option C

D. Option D

Answer: C

18. You are asked to develop a program for a shopping application, and you are given the following information:

Which definition of the Toy class adds a valid layer of abstraction to the class hierarchy?

- A) public abstract class Toy{
 public abstract int calculatePrice(Toy t);
 public void printToy(Toy t) { /* code goes here */ }
}
- B) public abstract class Toy {
 public int calculatePrice(Toy t) ;
 public void printToy(Toy t) ;
}
- C) public abstract class Toy {
 public int calculatePrice(Toy t);
 public final void printToy(Toy t){ /* code goes here */ }
}
- D) public abstract class Toy {
 public abstract int calculatePrice(Toy t) { /* code goes here */ }
 public abstract void printToy(Toy t) { /* code goes here */ }
}

A. Option A

B. Option B

C. Option C

D. Option D

Answer: A



19. Given the content of three files:

A.java:

```
public class A {  
    public void a() {}  
    int a;  
}
```

B.java:

```
public class B {  
    private int doStuff() {  
        private int x = 100;  
        return x++;  
    }  
}
```

C.java:

```
import java.io.*;  
package p1;  
class A {  
    public void main(String fileName) throws IOException {}  
}
```

Which statement is true?

- A. Only the A.java file compiles successfully.
- B. Only the B.java file compiles successfully.
- C. Only the C.java file compiles successfully.
- D. The A.java and B.java files compile successfully.
- E. The B.java and C.java files compile successfully.
- F. The A.java and C.java files compile successfully.

Answer: A

20. Given the following code for the classes MyException and Test:

```
public class MyException extends RuntimeException {}  
  
public class Test {  
    public static void main(String[] args) {  
        try {  
            method1();  
        }  
        catch (MyException ne) {  
            System.out.print("A");  
        }  
    }  
    public static void method1() { // line n1  
        try {  
            throw Math.random() > 0.5 ? new MyException() : new RuntimeException();  
        }  
        catch (RuntimeException re) {  
            System.out.print("B");  
        }  
    }  
}
```

What is the result?

- A. A
- B. B**
- C. Either A or B
- D. A B
- E. A compile time error occurs at line n1

Answer: B

21. Given:

```

class Vehicle {
    int x;
    Vehicle() {
        this(10); // line n1
    }
    Vehicle(int x) {
        this.x = x;
    }
}

class Car extends Vehicle {
    int y;
    Car() {
        super();
        this(20); // line n2
    }
    Car(int y) {
        this.y = y;
    }
    public String toString() {
        return super.x + ":" + this.y;
    }
}

```

And given the code fragment:

And given the code fragment:

```

Vehicle y = new Car();
System.out.println(y);

```

What is the result?

- A. 10:20
- B. 0:20
- C. Compilation fails at line n1
- D. Compilation fails at line n2**

Answer: D

22. Given the code snippet from a compiled Java source file:

```
public class MyFile
{
    public static void main (String[] args)
    {
        String arg1 = args[1];
        String arg2 = args[2];
        String arg3 = args[3];
        System.out.println("Arg is " + arg3);
    }
}
```

Which command-line arguments should you pass to the program to obtain the following output?

Arg is 2

A. java MyFile 1 3 2 2

B. java MyFile 2 2 2

C. java MyFile 1 2 2 3 4

D. java MyFile 0 1 2 3

Answer: A

23. Given the following class:

```
public class CheckingAccount {
    public int amount:
        // line n1
}
```

And given the following main method, located in another class:

```
public static void main (String [] args) {
    CheckingAccount acct = new CheckingAccount ();
    //line n2
}
```

Which three pieces of code, when inserted independently, set the value of amount to 100?

- A. At line n2 insert:
 amount = 100;
- B. At line n2 insert:
 This. amount = 100
- C. At line n2 insert:
 acct.amount = 100
- D. At line n1 insert:
 public CheckingAccount () {
 amount = 100;
 }
- E. At line n1 insert:
 public CheckingAccount () {
 this.amount = 100;
 }
- F. At line n1 insert:
 public CheckingAccount () {
 acct.amount = 100;
 }

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

F. Option F

Answer: B 

24. Given the following code:

```
public static void main(String[] args){  
    String[] planets = {"Mercury", "Venus", "Earth", "Mars"};  
  
    System.out.println(planets.length);  
    System.out.println(planets[1].length());  
}
```

What is the output?

A. 44

B. 35

C. 47



D. 54

E. 45

F. 421

Answer: E

25. Given the code fragment:

```
public static void main(String[] args) {  
    int ii = 0;  
    int jj = 7;  
    for (ii = 0; ii < jj - 1; ii = ii + 2) {  
        System.out.print(ii + " ");  
    }  
}
```

What is the result?

A. 2 4

B. 0 2 4 6

C. 0 2 4

D. Compilation fails

Answer: C

26. Given the code fragment:


```
public static void main(String[] args) {  
    StringBuilder sb = new StringBuilder(5);  
    String s = "";  
  
    if (sb.equals(s)) {  
        System.out.println("Match 1");  
    } else if (sb.toString().equals(s.toString())) {  
        System.out.println("Match 2");  
    } else {  
        System.out.println("No Match");  
    }  
}
```

What is the result?

A. Match 1

B. Match 2

C. No Match





D. A NullPointerException is thrown at runtime.

Answer: B

27. Given:

```
class Caller {  
    private void init () {  
        System.out.println("Initialized");  
    }  
  
    private void start () {  
        init();  
        System.out.println("Started");  
    }  
}  
  
public class TestCall {  
    public static void main(String[] args) {  
        Caller c = new Caller();  
        c.start();  
        c.init();  
    }  
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. InitializedStartedInitialized
- C. InitializedStarted
- D. Compilation fails.**

Answer: D

28. Given:

```
public class MyClass {  
    public static void main(String[] args) {  
        String s = "Java Duke";  
        int len = s.trim().length();  
        System.out.print(len);  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. 11
- C. 8
- D. 9**
- E. 10

Answer: D

29. Which three statements describe the object-oriented features of the Java language?

- A. Objects cannot be reused.
- B. A subclass can inherit from a superclass.**
- C. Objects can share behaviors with other objects.**
- D. A package must contain more than one class.
- E. Object is the root class of all other objects.**
- F. A main method must be declared in every class.

Answer: B,C,F

30. Given:

```

class Equal {
    public static void main (String [] args) {
        String str1 = "Java";
        String [] str2 = { "J", "a", "v", "a"};
        String str3 = "";
        for (String str : str2) {
            str3 = str3+str;
        }
        boolean b1 = (str1== str3);
        boolean b2 = (str1.equals (str3));
        System.out.print (b1+", "+b2);
    }
}

```

What is the result?

A. false, false

B. false, true

C. true, false

D. true, true

Answer: B

31. Given the code fragment:

```

13. List colors = new ArrayList();
14. colors.add("green");
15. colors.add("red");
16. colors.add("blue");
17. colors.add("yellow");
18. colors.remove(2);
19. colors.add(3, "cyan");
20. System.out.print(colors);

```

What is the result?

A. (green, red, yellow, cyan)

B. (green, blue, yellow, cyan)

C. (green, red, cyan, yellow)

D. AnIndexOutOfBoundsException is thrown at runtime.

**Answer: C**

32. Given the code fragment:

```
if (aVar++ < 10) {  
    System.out.println(aVar + " Hello World!");  
} else {  
    System.out.println(aVar + " Hello Universe!");  
}
```

What is the result if the integer aVar is 9?

- A. 10 Hello World!
- B. Hello Universe!
- C. Hello World!
- D. Compilation fails.

Answer: A

33. Given the code fragment:

```
public static void main (String[] args) {  
    String[] arr = {"Hi", "How", "Are", "You"};  
    List<String> arrList = new ArrayList<>(Arrays.asList(arr));  
    if (arrList.removeIf((String s) -> (return s.length() <= 2;))) {  
        System.out.println(s + " removed")  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. Hi removed
- C. An UnsupportedOperationException is thrown at runtime.
- D. The program compiles, but it prints nothing.

Answer: A

34. Given the code fragment:

```

public static void main(String[] args) {
    String[][] arr = {{"A", "B", "C"}, {"D", "E"}};
    for (int i = 0; i < arr.length; i++) {
        for (int j = 0; j < arr[i].length; j++) {
            System.out.print(arr[i][j] + " ");
            if (arr[i][j].equals("B")) {
                break;
            }
        }
        continue;
    }
}

```

What is the result?

- A. A B C
- B. A B C D E
- C. A B D E**
- D. Compilation fails.

Answer: C

35. Given:

```

System.out.println("5 + 2 = " + 3 + 4);
System.out.println("5 + 2 = " + (3 + 4));

```

What is the result?

- A) 5 + 2 = 34
5 + 2 = 34
- B) 5 + 2 + 3 + 4
5 + 2 = 7
- C) 7 = 7
7 + 7
- D) 5 + 2 = 34
5 + 2 = 7

- A. Option A
- B. Option B
- C. Option C
- D. Option D**

Answer: D



36. What is the name of the Java concept that uses access modifiers to protect variables and hide them within a class?

A. Encapsulation

B. Inheritance

C. Abstraction

D. Instantiation

E. Polymorphism

Answer: A

Explanation:

Using the private modifier is the main way that an object encapsulates itself and hide data from the outside world.

37. Given the code fragment:

```
int wd = 0;
String days[] = {"sun", "mon", "wed", "sat"};
for (String s:days) {
    switch (s) {
        case "sat":
        case "sun":
            wd -= 1;
            break;
        case "mon":
            wd++;
        case "wed":
            wd += 2;
    }
}
System.out.println(wd);
```

What is the result?

A. 3

B. 4

C. -1

D. Compilation fails.



**Answer: B**

38. Given:

```
public class Test {
    public static void main(String[] args) {
        if (args[0].equals("Hello") ? false : true) {
            System.out.println("Success");
        } else {
            System.out.println("Failure");
        }
    }
}
```

And given the commands:

`javac Test.java Java Test Hello`

What is the result?

A. Success

B. Failure

C. Compilation fails.

D. An exception is thrown at runtime

Answer: B

39. Given:

```
public class Test {
    public static final int MIN =1;
    public static void main (String [] args) {
        int x = args.length;
        if (checkLimit (x)) { //line n1
            System.out.println ("Java SE");
        } else {
            System.out.println ("Java EE");
        }
    }
    public static boolean checkLimit (int x) {
        return (x > = MIN) ? true : false;
    }
}
```

And given the commands:

`javac Test.java java Test`



What is the result?

- A. Java SE
- B. Java EE**
- C. Compilation fails at line n1.
- D. A NullPointerException is thrown at runtime.

Answer: A

40. Given the code fragment:

```
public static void main(String[] args) {  
    List<String> names = new ArrayList<>();  
    names.add("Robb");  
    names.add("Bran");  
    names.add("Rick");  
    names.add("Bran");  
  
    if (names.remove("Bran")) {  
        names.remove("Jon");  
    }  
    System.out.println(names);  
}
```

What is the result?

- A. [Robb, Rick, Bran]**
- B. [Robb, Rick]
- C. [Robb, Bran, Rick, Bran]
- D. An exception is thrown at runtime.

Answer: A

41. Given the code fragment:



```

class Employee {
    private String name;
    private int age;
    private int salary;

    public Employee (String name, int age) {
        setName (name)
        setAge (age)
        setSalary (2000);
    }
    public Employee (String name, int age, int salary) {
        setSalary (salary);
        this (name, age);
    }
    //getter and setter methods for attributes go here
    public void printDetails () {
        System.out.println (name + " : " + age + " : " + salary);
    }
}

```

Test.java

```

class Test {
    public static void main (String [] args {
        Employee e1 = new Employee ();
        Employee e2 = new Employee ("Jack, 50");
        Employee e3 = new Employee ("Chloe", 40, 5000);
        e1.printDetails ();
        e2.printDetails ();
        e3.printDetails ();
    }
}

```

Which is the result?

- A. Compilation fails in the Employee class.
- B. null : 0: 0Jack : 50 : 0Chloe : 40 : 5000
- C. null : 0 : 0Jack : 50 : 2000Chloe : 40 : 5000
- D. Compilation fails in the Test class.
- E. Both the Employee class and the test class fail to compile.**

Answer: E

42. Given: Acc.java:

```
package p1;
public class Acc {
    int p;
    private int q;
    protected int r;
    public int s;
}
```

Test.java:

```
package p2;
import p1.Acc;
public class Test extends Acc {
    public static void main(String[] args) {
        Acc obj = new Test();
    }
}
```

Which statement is true?

- A. Both p and s are accessible by obj.
- B. Only s is accessible by obj.**
- C. Both r and s are accessible by obj.
- D. p, r, and s are accessible by obj.

Answer: B

43. Given the code fragment from three files:



SalesMan.java:

```
package sales;
public class SalesMan { }
```

Product.java:

```
package sales.products;
public class Product { }
```

Market.java:

```
1. package market;
2. // insert code here
3. public class USMarket {
4.     SalesMan sm;
5.     Product p;
6. }
```

Which code fragment, when inserted at line 2, enables the code to compile?

- A) import sales.*;
- B) import java.sales.products.*;
- C) import sales;
import sales.products;
- D) import sales.*;
import products.*;
- E) import sales.*;
import sales.products.*;

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

Answer: E





44. Given the code fragment:

```
public static void main(String[] args) {
    ArrayList myList = new ArrayList();
    String[] myArray;
    try {
        while (true) {
            myList.add("My String");
        }
    }
    catch (RuntimeException re) {
        System.out.println("Caught a RuntimeException");
    }
    catch (Exception e) {
        System.out.println("Caught an Exception");
    }
    System.out.println("Ready to use");
}
```

What is the result?

- A. Execution terminates in the first catch statement, and caught a RuntimeException is printed to the console.
- B. Execution terminates in the second catch statement, and caught an Exception is printed to the console.
- C. A runtime error is thrown in the thread "main".**
- D. Execution completes normally, and Ready to use is printed to the console.
- E. The code fails to compile because a throws keyword is required.

Answer: C

45. Given:

```
public class Triangle {
    static double area;
    int b = 2, h = 3;
    public static void main(String[] args) {
        double p, b, h;          //line n1
        if (area == 0) {
            b = 3;
            h = 4;
            p = 0.5;
        }
        area = p * b * h;      //line n2
        System.out.println("Area is " + area);
    }
}
```

What is the result?





- A. Area is 6.0
- B. Area is 3.0
- C. Compilation fails at line n1
- D. Compilation fails at line n2.**

Answer: D

46. Given:

```
class Product {
    double price;
}

public class Test {
    public void updatePrice(Product product, double price) {
        price = price * 2;
        product.price = product.price + price;
    }
    public static void main(String[] args) {
        Product prt = new Product();
        prt.price = 200;
        double newPrice = 100;

        Test t = new Test();
        t.updatePrice(prt, newPrice);
        System.out.println(prt.price + " : " + newPrice);
    }
}
```

What is the result?

- A. 200.0 : 100.0
- B. 400.0 : 200.0
- C. 400.0 : 100.0**
- D. Compilation fails.

Answer: C

47. Given the following array:

```
int[] intArr = {8, 16, 32, 64, 128};
```

Which two code fragments, independently, print each element in this array?

- A)

```
for (int i : intArr) {
    System.out.print(intArr[i] + " ");
```
- B)

```
for (int i : intArr) {
    System.out.print(i + " ");
```
- C)

```
for (int i=0 : intArr) {
    System.out.print(intArr[i] + " ");
    i++;
```
- D)

```
for (int i=0; i < intArr.length; i++) {
    System.out.print(i + " ");
```
- E)

```
for (int i=0; i < intArr.length; i++) {
    System.out.print(intArr[i] + " ");
```
- F)

```
for (int i; i < intArr.length; i++) {
    System.out.print(intArr[i] + " ");
```

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

F. Option F

Answer: B,E

48. Given the code fragment:

```
public static void main(String[] args) {
    String date = LocalDate
        .parse("2014-05-04")
        .format(DateTimeFormatter.ISO_DATE_TIME);
    System.out.println(date);
}
```

What is the result?

- A. May 04, 2014T00:00:00.000
- B. 2014-05-04T00:00: 00. 000
- C. 5/4/14T00:00:00.000



D. An exception is thrown at runtime.

Answer: D

49. Given:

```
public class Test {  
    int x, y;  
  
    public Test(int x, int y) {  
        initialize(x, y);  
    }  
  
    public void initialize(int x, int y) {  
        this.x = x * x;  
        this.y = y * y;  
    }  
  
    public static void main(String[] args) {  
        int x = 3, y = 5;  
        Test obj = new Test(x, y);  
        System.out.println(x + " " + y);  
    }  
}
```

What is the result?

A. Compilation fails.

B. 3 5

C. 0 0

D. 9 25

Answer: B

50. Given:

```

class A {
    public A(){
        System.out.print("A ");
    }
}

class B extends A{
    public B(){ //line n1
        System.out.print("B ");
    }
}

class C extends B{

    public C(){ //line n2
        System.out.print("C ");
    }
    public static void main(String[] args) {
        C c = new C();
    }
}

```

What is the result?

- A. C B A
- B. C
- C. A B C**
- D. Compilation fails at line n1 and line n2

Answer: C

51. Given the code fragment:

```

int x = 100;
int a = x++;
int b = ++x;
int c = x++;
int d = (a < b) ? (a < c) ? a: (b < c )? b: c;
System.out.println(d);

```

What is the result?

- A. 100
- B. 101
- C. 102
- D. 103

E. Compilation fails**Answer: E**

52. Given the code fragment: int[] array = {1, 2, 3, 4, 5};

And given the requirements:

1. Process all the elements of the array in the order of entry.
 2. Process all the elements of the array in the reverse order of entry.
 3. Process alternating elements of the array in the order of entry. Which two statements are true?
- A. Requirements 1, 2, and 3 can be implemented by using the enhanced for loop.
- B. Requirements 1, 2, and 3 can be implemented by using the standard for loop.**
- C. Requirements 2 and 3 CANNOT be implemented by using the standard for loop.
- D. Requirement 1 can be implemented by using the enhanced for loop.**
- E. Requirement 3 CANNOT be implemented by using either the enhanced for loop or the standard for loop.

Answer: D,E

53. Given the code fragment:

```
public static void main(String[] args) {
    String[] arr = {"A", "B", "C", "D"};
    for (int i = 0; i < arr.length; i++) {
        System.out.print(arr[i] + " ");
        if (arr[i].equals("C")) {
            continue;
        }
        System.out.println("Work done");
        break;
    }
}
```

What is the result?

- A. A B C Work done
- B. A B C D Work done
- C. A Work done**
- D. Compilation fails

Answer: C



54. Given the code fragment:

```
public static void main (String [] args) {
    String myStr = "Hello World";
    myStr.trim ();
    int i1 = myStr.indexOf (" ");
    System.out.println (i1);
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. -1
- C. 5**
- D. 0

Answer: A

55. Given the code fragment:

```
public static void main(String[] args) {
    String str = " ";
    str.trim();
    System.out.println(str.equals("") + " " + str.isEmpty());
}
```

What is the result?

- A. true true
- B. true false
- C. false false**
- D. false true

Answer: C

56. Given the code fragment:

```
24. float var1 = (12_345.01 >= 123_45.00) ? 12_456 : 124_56.02f;
25. float var2 = var1 + 1024;
26. System.out.print(var2);
```

What is the result?

- A. An exception is thrown at runtime.
- B. Compilation fails.



C. 13480.0

D. 13480.02

Answer: C

57. Given:

```
class CD {  
    int r;  
    CD(int r){  
        this.r=r;  
    }  
}  
  
class DVD extends CD {  
    int c;  
    DVD(int r, int c) {  
        // line n1  
    }  
}
```

And given the code fragment:

```
DVD dvd = new DVD(10,20);
```

Which code fragment should you use at line n1 to instantiate the dvd object successfully?

- A) super.r = r;
 this.c = c;
- B) super(r);
 this(c);
- C) super(r);
 this.c = c;
- D) this.c = r;
 super(c);

A. Option A

B. Option B

C. Option C

D. Option D

Answer: C



58. Given the code fragment:

```
public static void main (String [ ] args) {  
    int [] stack = {10,20,30}  
    int size = 3;  
    int idx = 0;  
    /*line n1 */  
    System.out.print ("The Top element: " + stack [idx] );  
}
```

Which code fragment, inserted at line n1, prints The Top element: 30?

- A. do {
 idx++;
 } while (idx >= size);
- B. while (idx < size) {
 idx++;
 }
- C. do {
 idx++;
 } while (idx < size -1);
- D. do {
 idx++;
 } while (idx<= size);
- E. while (idx <= size -1) {
 idx++
 }

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

Answer: A

59. fragment:



```
1. class X {  
2.     public void printFileContent () {  
3.         /* code goes here */  
4.         throw new IOException();  
5.     }  
6. }  
7. public class Test {  
8.     public static void main(String[] args) {  
9.         X xobj = new X();  
10.        xobj.printFileContent();  
11.    }  
12. }
```

Which two modifications should you make so that the code compiles successfully?

- A) Replace line 8 with `public static void main(String[] args) throws Exception {`
- B) Replace line 10 with:
`try {
 xobj.printFileContent();
}
catch(Exception e) {}
catch(IOException e) {}`
- C) Replace line 2 with `public void printFileContent() throws IOException {`
- D) Replace line 4 with `throw IOException("Exception raised");`
- E) At line 11, insert `throw new IOException();`

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

Answer: A,C

60. Given the code fragments:



Person.java:

```
public class Person {
    String name;
    int age;

    public Person(String n, int a) {
        name = n;
        age = a;
    }

    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}
```

Test.java:

```
public static void checkAge(List<Person> list, Predicate<Person> predicate) {
    for (Person p : list) {
        if (predicate.test(p)) {
            System.out.println(p.name + " ");
        }
    }
}

public static void main(String[] args) {
    List<Person> iList = Arrays.asList(new Person("Hank", 45),
                                         new Person("Charlie", 40),
                                         new Person("Smith", 38));
    //line n1
}
```

Which code fragment, when inserted at line n1, enables the code to print Hank?

- A. checkAge (iList, () -> p. get Age () > 40);
- B. checkAge(iList, Person p -> p.getAge() > 40);
- C. checkAge (iList, p -> p.getAge () > 40);**
- D. checkAge(iList, (Person p) -> { p.getAge() > 40; });

Answer: C

61. Which two statements are true?

- A. Error class is unextendable.
- B. Error class is extendable.**
- C. Error is a RuntimeException.
- D. Error is an Exception.
- E. Error is a Throwable.**

Answer: B,C

62. Given the code fragment:



```

public class Test {
    public static void main(String[] args) {
        //line n1
        switch (x) {
            case 1:
                System.out.println("One");
                break;
            case 2:
                System.out.println("Two");
                break;
        }
    }
}

```

Which three code fragments can be independently inserted at line n1 to enable the code to print one?

- A. Byte x = 1;
- B. short x = 1;
- C. String x = "1";
- D. Long x = 1;
- E. Double x = 1;
- F. Integer x = new Integer ("1");

Answer: A,B,F

63. Which two are benefits of polymorphism?

- A. Faster code at runtime
- B. More efficient code at runtime
- C. More dynamic code at runtime
- D. More flexible and reusable code
- E. Code that is protected from extension by other classes

Answer: B,D

64. Given the code fragment:

```
String shirts[][] = new String[2][2];
shirts[0][0] = "red";
shirts[0][1] = "blue";
shirts[1][0] = "small";
shirts[1][1] = "medium";
```

Which code fragment prints red: blue: small: medium?

- A)

```
for (int index = 1; index < 2; index++) {
    for (int idx = 1; idx < 2; idx++) {
        System.out.print(shirts[index][idx] + ":");
    }
}
```
- B)

```
for (int index = 0; index < 2; ++index) {
    for (int idx = 0; idx < index; ++idx) {
        System.out.print(shirts[index][idx] + ":");

    }
}
```
- C)

```
for (String c : colors) {
    for (String s : sizes) {
        System.out.println(s + ":");

    }
}
```
- D)

```
for (int index = 0; index < 2;) {
    for (int idx = 0; idx < 2;) {
        System.out.print(shirts[index][idx] + ":");

        idx++;
    }
    index++;
}
```

A. Option A

B. Option B

C. Option C

D. Option D

Answer: D

65. Given:

```
public class Test {  
  
    public static void main(String[] args) {  
  
        String[][] chs = new String[2][];  
        chs[0] = new String[2];  
        chs[1] = new String[5];  
        int i = 97;  
  
        for (int a = 0; a < chs.length; a++) {  
            for (int b = 0; b < chs.length; b++) {  
                chs[a][b] = "" + i;  
                i++;  
            }  
        }  
  
        for (String[] ca : chs) {  
            for (String c : ca) {  
                System.out.print(c + " ");  
            }  
            System.out.println();  
        }  
    }  
}
```

What is the result?

- A. 97 9899 100 null null null
- B. 97 9899 100 101 102 103
- C. Compilation rails.
- D. A NullPointerException is thrown at runtime.
- E. An ArrayIndexOutOfBoundsException is thrown at runtime.

Answer: A

66. CORRECT TEXT

Given:

```

String stuff = "TV";
String res = null;

if (stuff.equals ("TV")) {
res = "Walter";
} else if (stuff.equals ("Movie") ) {
res= "White";
} else {
res= "No Result";
}

```

Which code fragment can replace the if block?

- A) stuff.equals ("TV") ? res= "Walter" : stuff.equals ("Movie") ? res = "White" : res = "No Result";
- B) res = stuff.equals ("TV") ? "Walter" else stuff.equals ("Movie")? "White" : "No Result";
- C) res = stuff.equals ("TV") ? stuff.equals ("Movie")? "Walter" : "White" : "No Result";
- D) res = stuff.equals ("TV")? "Walter" : stuff.equals ("Movie")? "White" : "No Result";**

Answer:

67. Given:

```

package clothing;
public class Shirt {
    public static String getColor() {
        return "Green";
    }
}

```

Given the code fragment:

```

package clothing.pants;
// line n1
public class Jeans {
    public void matchShirt() {
        //line n2
        if(color.equals("Green")) {
            System.out.print("Fit")
        }
    }
    public static void main (String[] args) {
        Jeans trouser = new Jeans();
        trouser.matchShirt();
    }
}

```

Which two sets of actions, independently, enable the code fragment to print Fit?

- A. At line n1 insert:import clothing.Shirt;At line n2 insert:String color = getColor();
- B. At line n1 insert:import clothing.*;At line n2 insert:String color = Shirt.getColor();**
- C. At line n1 insert:import static clothing.Shirt.getColor();At line n2 insert:String color = getColor();
- D. At line n1 no changes required.At line n2 insert:String color = Shirt.getColor();
- E. At line n1 insert:import clothing;At line n2 insert:String color = Shirt.getColor();

Answer: A

68. Given the code fragment:

```

int nums1[] = new int[3];
int nums2[] = {1, 2, 3, 4, 5};
nums1 = nums2;
for (int x : nums1) {
    System.out.print(x + ":");
}

```

What is the result?

- A. 1:2:3:4:5:**
- B. 1:2:3:
- C. Compilation fails.
- D. An ArrayOutOfBoundsException is thrown at runtime.



Answer: A

69. Given the code fragments:

```

Interface Exportable {
    Void export();
}

class Tool implements Exportable {
    protected void export () {           //line n1
        System.out.println("Tool::export");
    }
}

class ReportTool extends Tool implements Exportable {

    public void export() {             //line n2
        System.out.println("RTool::export");
    }

    public static void main(String[] args) {
        Tool aTool = new ReportTool();
        Tool bTool = new Tool();
        callExport(aTool);
        callExport(bTool);
    }

    public static void callExport (Exportable ex) {
        ex.export();
    }
}

```

What is the result?

- A. Compilation fails only at line n2.
- B. RTool::exportTool::export
- C. Tool::exportTool::export
- D. **Compilation fails only at line n1.**
- E. Compilation fails at both line n1 and line n2.

Answer: E

70. Given:



MainTest.java:

```
public class MainTest {
    public static void main(int[] args) {
        System.out.println("int main " + args[0]);
    }
    public static void main(Object[] args) {
        System.out.println("Object main " + args[0]);
    }
    public static void main(String[] args) {
        System.out.println("String main " + args[0]);
    }
}
```

and commands:

```
javac MainTest.java
java MainTest 1 2 3
```

What is the result?

- A. int main 1
- B. Object main 1
- C. String main 1**
- D. Compilation fails
- E. An exception is thrown at runtime

Answer: C

71. Which three are advantages of the Java exception mechanism?

- A. Improves the program structure because the error handling code is separated from the normal program function**
- B. Provides a set of standard exceptions that covers all the possible errors
- C. Improves the program structure because the programmer can choose where to handle exceptions**
- D. Improves the program structure because exceptions must be handled in the method in which they occurred
- E. Allows the creation of new exceptions that are tailored to the particular program being created**

Answer: A,C,D

72. Given:



```
public class SumTest {  
  
    public static void doSum(Integer x, Integer y) {  
        System.out.println("Integer sum is " + (x + y));  
    }  
  
    public static void doSum(double x, double y) {  
        System.out.println("double sum is " + (x + y));  
    }  
  
    public static void doSum(float x, float y) {  
        System.out.println("float sum is " + (x + y));  
    }  
  
    public static void doSum(int x, int y) {  
        System.out.println("int sum is " + (x + y));  
    }  
  
    public static void main(String[] args) {  
        doSum(10, 20);  
        doSum(10.0, 20.0);  
    }  
}
```

What is the result?

- A. int sum is 30float sum is 30.0
- B. int sum is 30double sum is30.0**
- C. integer sum is 30double sum is 30.0
- D. integer sum is 30float sum is 30.0

Answer: D

73. Which statement is true about Java byte code?

- A. It can run on any platform.
- B. It can run on any platform only if it was compiled for that platform.
- C. It can run on any platform that has the Java Runtime Environment.
- D. It can run on any platform that has a Java compiler.**
- E. It can run on any platform only if that platform has both the Java Runtime Environment and a Java compiler.

Answer: D

74. Given:

```
class Test {  
    public static void main (String [] args) {  
        int numbers [ ];  
        numbers = new int [2];  
        numbers [0] = 10;  
        numbers [1] = 20;  
  
        numbers = new int [4];  
        numbers [2] = 30;  
        numbers [3] = 40;  
        for (int x : numbers) {  
            System.out.print (" " + x) ;  
        }  
    }  
}
```

What is the result?

- A. 10 20 30 40
- B. 0 0 30 40**
- C. Compilation fails.
- D. An exception is thrown at runtime.

Answer: C

75. Given:

```

public class Fieldinit {
    char c;
    boolean b;
    float f;
    void printAll() {
        System.out.println ("c = " + c);
        System.out.println ("b = " + b);
        System.out.println ("f = " + f);
    }
    public static void main (String [] args) {
        FieldInit f = new FieldInit ();
        f.printAll ();
    }
}

```

What is the result?

- A. c=b = falsef = 0.0
- B. c= nullb = truef = 0.0
- C. c=0b = falsef = 0.0f
- D. c= nullb = falsef = 0.0F

Answer: C

76. Given the code fragment:

```

if (aVar++ < 10) {
    System.out.println(aVar + " Hello World!");
} else {
    System.out.println(aVar + " Hello Universe!");
}

```

What is the result if the integer aVar is 9?

- A. Compilation fails.
- B. 10 Hello Universe!
- C. 10 Hello World!
- D. 9 Hello World!

Answer: C



77. Given:

```
class C2 {  
    public void displayC2() {  
        System.out.print("C2");  
    }  
}  
interface I {  
    public void displayI();  
}  
class C1 extends C2 implements I {  
    public void displayI() {  
        System.out.print("C1");  
    }  
}
```

And given the code fragment:

```
C2 obj1 = new C1();  
I obj2 = new C1();  
  
C2 s = obj2;  
I t = obj1;  
  
t.displayI();  
s.displayC2()
```

What is the result?

- A. C2C2
- B. C1C2
- C. C1C1
- D. Compilation fails

Answer: A

78. Given the code fragment:

```
public static void main (String[ ] args) {  
    int data [ ] = {2010, 2013, 2014, 2015, 2014};  
    int key = 2014;  
    int count = 0;  
    for (int e: data) {  
        if (e! = key) {  
            continue:  
            count++;  
        }  
    }  
    System.out.print (count + "Found");  
}
```

What is the result?

- A. Compilation fails.
- B. 0 Found
- C. 1 Found
- D. 3 Found

Answer: D

79. Given the code fragment:

```
3. public static void main(String[] args) {  
4.     int iVar = 100;  
5.     float fVar = 100.100f;  
6.     double dVar = 123;  
7.     iVar = fVar;  
8.     fVar = iVar;  
9.     dVar = fVar;  
10.    fVar = dVar;  
11.    dVar = iVar;  
12.    iVar = dVar;  
13. }
```

Which three lines fail to compile?

- A. Line 7
- B. Line 8
- C. Line 9
- D. Line 10



E. Line 11

F. Line 12

Answer: A,D,F

80. Given the code fragment:

```
public static void main(String[] args) {
    int array[] = {10, 20, 30, 40, 50};
    int x = array.length;
    /* line n1 */
}
```

Which two code fragments can be independently inserted at line n1 to enable the code to print the elements of the array in reverse order?

- A. while (x > 0) {x--;System.out.print(array[x]);}
- B. do {x--;System.out.print(array[x]);} while (x >= 0);
- C. while (x >= 0) {System.out.print(array[x]);x--;}
- D. do {System.out.print(array[x]);--x;} while (x >= 0);
- E. while (x > 0) {System.out.print(array[--x]);}

Answer: B,E

81. Given the code fragment:

```
LocalDate date1 = LocalDate.now();
LocalDate date2 = LocalDate.of(2014, 6, 20);
LocalDate date3 = LocalDate.parse("2014-06-20", DateTimeFormatter.ISO_DATE);
System.out.println("date1 = " + date1);
System.out.println("date2 = " + date2);
System.out.println("date3 = " + date3);
```

Assume that the system date is June 20, 2014. What is the result?



- A) date1 = 2014-06-20
date2 = 2014-06-20
date3 = 2014-06-20
- B) date1 = 06/20/2014
date2 = 2014-06-20
date3 = Jun 20, 2014
- C) Compilation fails.
- D) A DateParseException is thrown at runtime.

A. Option A

B. Option B

C. Option C

D. Option D

Answer: D

82. You are asked to create a method that accepts an array of integers and returns the highest value from that array.

Given the code fragment:

```
class Test {
    public static void main (String [] args) {
        int numbers [] = {12, 13, 42, 32, 15, 156, 23, 51, 12};
        int max = findMax (numbers);
    }
/*line n1 */
    int max = 0;
    /* code goes here*/
    return max;
}
```

Which method signature do you use at line n1?

- A. public int findMax (int [] numbers)
- B. static int[] findMax (int max)
- C. static int findMax (int [] numbers)
- D. final int findMax (int [])

Answer: A





83. Given the code fragment:

```
public static void main(String[] args) {
    Short s1 = 200;
    Integer s2 = 400;
    Long s3 = (long) s1 + s2;           //line n1
    String s4 = (String) (s3 * s2);     //line n2
    System.out.println("Sum is " + s4);
}
```

What is the result?

- A. Sum is 600
- B. Compilation fails at line n1.
- C. Compilation fails at line n2.**
- D. A ClassCastException is thrown at line n1.
- E. A ClassCastException is thrown at line n2.

Answer: C

84. Given the code fragment:

```
abstract class Planet {
    protected void revolve() {                      //line n1
    }

    abstract void rotate();                         //line n2
}

class Earth extends Planet {
    void revolve() {                                //line n3
    }

    protected void rotate() {                        //line n4
    }
}
```

Which two modifications, made independently, enable the code to compile?

- A. Make the method at line n1 public.
- B. Make the method at line n2 public.
- C. Make the method at line n3 public.**
- D. Make the method at line n3 protected.**
- E. Make the method at line n4 public.

Answer: C,D





85. Given:

```
public class App {
    public static void main(String[] args) {
        int i = 10;
        int j = 20;
        int k = j += i / 5;
        System.out.print(i + " : " + j + " : " + k);
    }
}
```

What is the result?

- A. 10 : 30 : 6
- B. 10 : 22 : 22**
- C. 10 : 22 : 20
- D. 10 : 22 : 6

Answer: B

Explanation: Explanation

Your Code ...

```
1 public class App {
2     public static void main (String[] args) {
3         int i = 10;
4         int j = 20;
5         int k = j += i / 5;
6         System.out.print (i + " : " + j + " : " + k);
7     }
8 }
```

External Libraries ...

CommandLine Arguments ...

Interactive mode : OFF Version:

Stdin Inputs...

Result...

CPU Time: 0.20 sec(s), Memory: 32080 kilobyte(s) compiled and executed in 1.229 sec(s)

```
10 : 22 : 22
```

86. Given the code fragment:

```

public class Employee {
    String name;
    boolean contract;
    double salary;
    Employee() {
        // line n1
    }
    public String toString(){
        return name + ":" + contract + ":" + salary;
    }
    public static void main(String[] args) {
        Employee e = new Employee();
        // line n2
        System.out.print(e);
    }
}

```

Which two modifications, when made independently, enable the code to print joe:true: 100.0?

- A) Replace line n2 with:

```

e.name = "Joe";
e.contract = true;
e.salary = 100;

```

- B) Replace line n2 with:

```

this.name = "Joe";
this.contract = true;
this.salary = 100;

```

- C) Replace line n1 with:

```

this.name = new String("Joe");
this.contract = new Boolean(true);
this.salary = new Double(100);

```

- D) Replace line n1 with:

```

name = "Joe";
contract = TRUE;
salary = 100.0f;

```

- E) Replace line n1 with:

```

this("Joe", true, 100);

```

A. Option A

B. Option B

C. Option C



D. Option D

E. Option E

Answer: A,C

87. Given:

Base.java:

```
class Base {  
    public void test(){  
        System.out.println("Base ");  
    }  
}
```

DerivedA.java:

```
class DerivedA extends Base {  
    public void test(){  
        System.out.println("DerivedA ");  
    }  
}
```

DerivedB.java:

```
class DerivedB extends DerivedA {  
    public void test(){  
        System.out.println("DerivedB ");  
    }  
    public static void main(String[] args) {  
        Base b1 = new DerivedB();  
        Base b2 = new DerivedA();  
        Base b3 = new DerivedB();  
        b1 = (Base) b3;  
        Base b4 = (DerivedA) b3;  
        b1.test();  
        b4.test();  
    }  
}
```

What is the result?

A. BaseDerivedA

B. BaseDerivedB



C. DerivedBDerivedB

D. DerivedBDerivedA

E. A classcast Exception is thrown at runtime.

Answer: C

88. Given:

```

class X {
    static int i;
    int j;
    public static void main(String[] args) {
        X x1 = new X();
        X x2 = new X();
        x1.i = 3;
        x1.j = 4;
        x2.i = 5;
        x2.j = 6;
        System.out.println(
            x1.i + " " +
            x1.j + " " +
            x2.i + " " +
            x2.j);
    }
}

```

What is the result?

A. 3 4 5 6

B. 3 4 3 6

C. 5 4 5 6

D. 3 6 4 6

Answer: C

89. Which three statements are true about exception handling?

A. Only unchecked exceptions can be rethrown.

B. All subclasses of the RuntimeException class are recoverable.

C. The parameter in a catch block is of Throwable type.

D. All subclasses of the RuntimeException class must be caught or declared to be thrown.



E. All subclasses of the Exception class except the RuntimeException class are checked exceptions.

F. All subclasses of the Error class are checked exceptions and are recoverable.

Answer: C,E,F

90. Given the code fragment:

```
public static void main(String[] args) {  
    double discount = 0;  
    int qty = Integer.parseInt(args[0]);  
    //line n1;  
}
```

And given the requirements:

Which two code fragments can be independently placed at line n1 to meet the requirements?

- A) if (qty >= 90) { discount = 0.5; }
if (qty > 80 && qty < 90) { discount = 0.2; }
- B) discount = (qty >= 90) ? 0.5 : 0;
discount = (qty > 80) ? 0.2 : 0;
- C) discount = (qty >= 90) ? 0.5 : (qty > 80)? 0.2 : 0;
- D) if (qty > 80 && qty < 90) {
 discount = 0.2;
} else {
 discount = 0;
}
if (qty >= 90) {
 discount = 0.5;
} else {
 discount = 0;
}
- E) discount = (qty > 80) ? 0.2 : (qty >= 90) ? 0.5 : 0;

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

Answer: A,C

91. Given the code fragment:

```

public class Test {

    static int count = 0;
    int i = 0;

    public void changeCount() {
        while (i < 5) {
            i++;
            count++;
        }
    }

    public static void main(String[] args) {
        Test check1 = new Test();
        Test check2 = new Test();
        check1.changeCount();
        check2.changeCount();
        System.out.print(check1.count + " : " + check2.count);
    }
}

```

What is the result?

- A. 10 : 10
- B. 5 : 5
- C. 5 : 10
- D. Compilation fails

Answer: A

92. Given:

```

public class Test {
    public static void main(String[] args) {
        Test ts = new Test();
        System.out.print(isAvailable + " ");
        isAvailable= ts.doStuff();
        System.out.println(isAvailable);
    }
    public static boolean doStuff() {
        return !isAvailable;
    }
    static boolean isAvailable = false;
}

```

What is the result?

- A. Compilation fails.
- B. false true



C. true false

D. true true

E. false false

Answer: B

93. Given:

```
class Student {  
    String name;  
    public Student(String name) {  
        this.name = name;  
    }  
}  
  
public class Test {  
    public static void main(String[] args) {  
        Student[] students = new Student[3];  
        students[1] = new Student("Richard");  
        students[2] = new Student("Donald");  
        for (Student s : students) {  
            System.out.println(" " + s.name);  
        }  
    }  
}
```

What is the result?

A. nullRichardDonald

B. RichardDonald

C. Compilation fails.

D. An `ArrayIndexOutOfBoundsException` is thrown at runtime.

E. A `NullPointerException` is thrown at runtime.

Answer: A

94. Which one of the following code examples uses valid Java syntax?



A.

```
public class Boat {  
  
    public static void main (String [] args) {  
        System.out.println ("I float.");  
    }  
}
```

B.

```
public class Cake {  
    public static void main (String [] ) {  
        System.out.println ("Chocolate");  
    }  
}
```

C.

```
public class Dog {  
    public void main (String [] args) {  
        System.out.println ("Squirrel.");  
    }  
}
```

D.

```
public class Bank {  
    public static void main (String () args) {  
        System.out.println ("Earn interest.");  
    }  
}
```

A. Option A

B. Option B

C. Option C

D. Option D

Answer: A

95. Given:



```

class Vehicle {
    String type = "4W";
    int maxSpeed = 100;

    Vehicle(String type, int maxSpeed) {
        this.type = type;
        this.maxSpeed = maxSpeed;
    }
}

class Car extends Vehicle {
    String trans;

    Car(String trans) {           //line n1
        this.trans = trans;
    }

    Car(String type, int maxSpeed, String trans) {
        super(type, maxSpeed);
        this(trans);           //line n2
    }
}

```

And given the code fragment:

```

7. Car c1 = new Car("Auto");
8. Car c2 = new Car("4W", 150, "Manual");
9. System.out.println(c1.type + " " + c1.maxSpeed + " " + c1.trans);
10. System.out.println(c2.type + " " + c2.maxSpeed + " " + c2.trans);

```

What is the result?

- A. 4W 100 Auto4W 150 Manual
- B. Null 0 Auto4W 150 Manual
- C. Compilation fails only at line n1
- D. Compilation fails only at line n2
- E. Compilation fails at both line n1 and line n2

Answer: C

96. Given the code fragment:

```
4. public static void main(String[] args) {  
5.     boolean opt = true;  
6.     switch (opt) {  
7.         case true:  
8.             System.out.print("True");  
9.             break;  
10.        default:  
11.            System.out.print("****");  
12.        }  
13.        System.out.println("Done");  
14.    }
```

Which modification enables the code fragment to print TrueDone?

- A. Replace line 5 With String opt= "true";Replace line 7 with case "true":
- B. Replace line 5 with boolean opt = l;Replace line 7 with case 1=
- C. At line 9, remove the break statement.
- D. Remove the default section.

Answer: A

97. Given the code fragment:

```
int num[][] = new int[1][3];  
for (int i = 0; i < num.length; i++) {  
    for (int j = 0; j < num[i].length; j++) {  
        num[i][j] = 10;  
    }  
}
```

Which option represents the state of the num array after successful completion of the outer loop?

- A) num[0][0]=10
num[0][1]=10
num[0][2]=10
- B) num[0][0]=10
num[1][0]=10
num[2][0]=10
- C) num[0][0]=10
num[0][1]=0
num[0][2]=0
- D) num[0][0]=10
num[0][1]=10
num[0][2]=10
num[0][3]=10
num[1][0]=0
num[1][1]=0
num[1][2]=0
num[1][3]=0

A. Option A

B. Option B

C. Option C

D. Option D

Answer: A

98. Given:



```

interface Downloadable {
    public void download();
}

interface Readable extends Downloadable {          // line n1
    public void readBook();
}

abstract class Book implements Readable {           // line n2
    public void readBook() {
        System.out.println("Read Book");
    }
}

class EBook extends Book {                         // line n3
    public void readBook() {
        System.out.println("Read E-Book");
    }
}

```

And given the code fragment:

```

Book book1 = new EBook();
book1.readBook();

```

What is the result?

- A. Compilation fails at line n2.
- B. Read Book
- C. Read E-Book
- D. Compilation fails at line n1.
- E. **Compilation fails at line n3.**

Answer: B

99. The following grid shows the state of a 2D array:

0	0	
	X	0
	X	X

This grid is created with the following code:



```
char[][] grid = new char[3][3];
grid[1][1] = 'X';
grid[0][0] = 'O';
grid[2][1] = 'X';
grid[0][1] = 'O';
grid[2][2] = 'X';
grid[1][2] = 'O';
```

Which line of code, when inserted in place of //line n1, adds an X into the grid so that the grid contains three consecutive X's?

- A. grid[1][3] = 'X';
- B. grid[3][1] = 'X';
- C. grid[0][2] = 'X';
- D. grid[2][0] = 'X';**
- E. grid[1][2] = 'X';

Answer: C

100. Given:

```
public class Test {
    public static void main(String[] args) {
        int x = 1;
        int y = 0;
        if(x++ > ++y) {
            System.out.print("Hello ");
        } else {
            System.out.print("Welcome ");
        }
        System.out.print("Log " + x + ":" + y);
    }
}
```

What is the result?

- A. Hello Log 1:0
- B. Hello Log 2:1
- C. Welcome Log 2:1**
- D. Welcome Log 1:0



Answer: C

101. Given the code fragment:

```
Public static void main (String [] args) {  
    System.out.println ("Result A " + 0 + 1);  
    System.out.println ("Result B " + (1) + (2) );  
}
```

What is the result?

- A. Result A 1
 Result B 3
- B. Result A 01
 Result B 3
- C. Result A 01
 Result B 12
- D. Result A 1
 Result B 12

A. Option A

B. Option B

C. Option C

D. Option D

Answer: C

102. Given:

```

public class SumTest {

    public static void doSum(Integer x, Integer y) {
        System.out.println("Integer sum is " + (x + y));
    }

    public static void doSum(double x, double y) {
        System.out.println("double sum is " + (x + y));
    }

    public static void doSum(float x, float y) {
        System.out.println("float sum is " + (x + y));
    }

    public static void doSum(int x, int y) {
        System.out.println("int sum is " + (x + y));
    }

    public static void main(String[] args) {
        doSum(10, 20);
        doSum(10.0, 20.0);
    }
}

```

What is the result?

- A) int sum is 30
float sum is 30.0
- B) int sum is 30
double sum is 30
- C) Integer sum is 30
double sum is 30.0
- D) Integer sum is 30
float sum is 30.0

A. Option A

B. Option B

C. Option C

D. Option D

Answer: B



103. Given:

```
class Test int a1;
```



```

public static void doProduct(int a) { a = a * a;
}

public static void doString(StringBuilder s) { s.append(" " + s);
}

public static void main(String[] args) { Test item = new Test();
item.a1 = 11;
StringBuilder sb = new StringBuilder("Hello"); Integer i = 10;
doProduct(i); doString(sb); doProduct(item.a1);
System.out.println(i + " " + sb + " " + item.a1);
}
}

```

What is the result?

- A. 10 Hello Hello 11
- B. 10 Hello Hello 121
- C. 100 Hello 121
- D. 100 Hello Hello 121
- E. 10 Hello 11

Answer: B

104. Given:

```

interface Readable {
    public void readBook();
    public void setBookMark();
}

abstract class Book implements Readable { // line n1
    public void readBook() { }
    // line n2
}

class EBook extends Book { // line n3
    public void readBook() { }
    // line n4
}

```

And given the code fragment: Book book1 = new EBook();

Book1.readBook();



Which option enables the code to compile?

- A. Replace the code fragment at line n3 with:
abstract class EBook extends Book {
- B. Replace the code fragment at line n1 with:
class Book implements Readable {
- C. At line n2 insert:
public abstract void setBookMark ();
- D. At line n4 insert:
public void setBookMark () { }

A. Option A

B. Option B

C. Option C

D. Option D

Answer: A

105. Given:

```
public class MyField {
    int x;
    int y;
    public void doStuff(int x, int y) {
        this.x = x;
        y = this.y;
    }
    public void display () {
        System.out.print(x + " " + y + " : ");
    }
    public static void main(String[] args) {
        MyField m1 = new MyField();
        m1.x = 100;
        m1.y = 200;
        MyField m2 = new MyField();
        m2.doStuff(m1.x, m1.y);
        m1.display();
        m2.display();
    }
}
```

What is the result?





A. 100 0 : 100 200:

B. 100 0 : 100 0 :

C. 100 200 : 100 200 :

D. 100 200 : 100 0 :

Answer: B

106. Given the code fragment:

```
3. public static void main(String[] args) {  
4.     int x = 5;  
5.     while (isAvailable(x)) {  
6.         System.out.print(x);  
7.  
8.     }  
9. }  
10.  
11. public static boolean isAvailable(int x) {  
12.     return x-- > 0 ? true : false;  
13. }
```

Which modification enables the code to print 54321?

A. Replace line 6 with System.out.print(--x);

B. At line 7, insert x--;

C. Replace line 6 with --x; and, at line 7, insert system.out.print(x);

D. Replace line 12 With return (x > 0) ? false: true;

Answer: A



107. Given:

```
public class MarkList {  
    int num;  
    public static void graceMarks(MarkList obj4) {  
        obj4.num += 10;  
    }  
    public static void main(String[] args) {  
        MarkList obj1 = new MarkList();  
        MarkList obj2 = obj1;  
        MarkList obj3 = null;  
        obj2.num = 60;  
        graceMarks(obj2);  
    }  
}
```

How many MarkList instances are created in memory at runtime?

A. 1

B. 2

C. 3

D. 4

Answer: A

108. Given the code fragments:

A.java:

```
package p1;
public class A {
```

B.java:

```
package p1.p2;
//line n1
public class B {
    public void doStuff() {
        A b = new A ();
    }
}
```

C.java:

```
package p3;
//line n2
public class C {
    public static void main(String[] args) {
        A o1 = new A();
        B o2 = new B();
    }
}
```

Which modification enables the code to compile?

- A. Replace line n1 with:`import p1.A;`Replace line n2 with:`import p1.A;import p1.p2.B;`
- B. Replace line n1 with:`import p1;`Replace line n2 with:`import p1;import p1.p2;`
- C. Replace line n1 with:`import p1.A;`Replace line n2 with:`import p1.*;`
- D. Replace line n1 with:`import p1.*;`Replace line n2 with:`import p1.p2.*;`

Answer: D

109. Given:

```
class Patient {  
    String name;  
    public Patient (String name) {  
        this.name = name;  
    }  
}
```

And the code fragment:

```
8. public class Test {  
9.     public static void main (String [] args) {  
10.         List ps = new ArrayList ();  
11.         Patient p2 = new Patient ("Mike");  
12.         ps.add(p2);  
13.  
14.         // insert code here  
15.  
16.         if (f >= 0) {  
17.             System.out.print ("Mike Found");  
18.         }  
19.     }  
20. }
```

Which code fragment, when inserted at line 14, enables the code to print Mike Found?

- A. int f = ps.indexOf (p2)
- B. int f = ps.indexOf (Patient ("Mike"));
- C. int f = ps.indexOf (new Patient "Mike");
- D. Patient p = new Patient ("Mike");int f = ps.indexOf (p)

Answer: A

110. Given the code fragment:

```

public class Person {
    String name;
    int age = 25;

    public Person (String name) {
        this (); //                                //line n1
        setName(name);
    }
    public Person (String name, int age) {
        Person (name);                         //line n2
        setAge (age);
    }
    //setter and getter methods go here

    public String show () {
        return name + " " + age;
    }
    public static void main (String [] args) {
        Person p1 = new Person ("Jesse");
        Person p2 = new Person ("Walter", 52);
        System.out.println (p1.show ());
        System.out.println (p2.show ());
    }
}

```

What is the result?

- A. Compilation fails at both line n1 and line n2.
- B. Compilation fails only at line n2.
- C. Compilation fails only at line n1.
- D. Jesse 25Walter 52

Answer: D

111. Given:

```

public class Test {
    public static void main(String[] args) {
        boolean a = new Boolean(Boolean.valueOf (args[0]));
        boolean b = new Boolean(args[1]);
        System.out.println(a + " " + b);
    }
}

```

And given the commands: javac Test.java

java Test TRUE null What is the result?

- A. TRUE null
- B. true false**
- C. false false
- D. true true
- E. A ClassCastException is thrown at runtime.

Answer: D

112. Given the following code for a Planet object:

```
public class Planet {  
    public String name;  
    public int moons;  
  
    public Planet(String name, int moons) {  
        this.name = name;  
        this.moons = moons;  
    }  
}
```

And the following main method:

```
public static void main(String[] args) {  
    Planet[] planets = {  
        new Planet("Mercury", 0),  
        new Planet("Venus", 0),  
        new Planet("Earth", 1),  
        new Planet("Mars", 2)  
    };  
  
    System.out.println(planets);  
    System.out.println(planets[2]);  
    System.out.println(planets[2].moons);  
}
```

What is the output?



- A) planets
Earth
1
- B) [LPlanets.Planet;@15db9742
Earth
1
- C) [LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
1
- D) [LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
[LPlanets.Moon;@7852e922
- E) [LPlanets.Planet;@15db9742
Venus
0

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

Answer: C

113. Given the following main method:

```
public static void main(String[] args) {
    int num = 5;
    do {
        System.out.print(num-- + " ");
    } while (num == 0);
}
```

What is the result?

A. 5 4 3 2 1 0

B. 5 4 3 2 1





C. 4 2 1

D. 5

E. Nothing is printed

Answer: D

114. Given:

```

interface Readable {
    public void readBook();
    public void setBookMark();
}

abstract class Book implements Readable { // line n1
    public void readBook() { }
    // line n2
}

class EBook extends Book { // line n3
    public void readBook() { }
    // line n4
}

```

Which option enables the code to compile?

- A) Replace the code fragment at line n1 with:
class Book implements Readable {
- B) At line n2 insert:
public abstract void setBookMark();
- C) Replace the code fragment at line n3 with:
abstract class EBook extends Book {
- D) At line n4 insert:
public void setBookMark() { }

A. Option A

B. Option B

C. Option C**D. Option D****Answer** 

115. Given:



```
public class App {  
    int count;  
    public static void displayMsg () {  
        count++; // line n1  
        System.out.println ("Welcome +"Visit Count: "+count); // line n2  
    }  
    public static void main (String [] args) {  
        App.displayMsg (); // line n3  
        App.displayMsg (); // line n4  
    }  
}
```

What is the result?

- A. Compilation fails at line n3 and line n4.
- B. Compilation fails at line n1 and line n2.**
- C. Welcome Visit Count:1Welcome Visit Count: 2
- D. Welcome Visit Count:1Welcome Visit Count: 2

Answer: B

116. Given:

```
public class App {  
  
    public static void main(String[] args) {  
        Boolean[] bool = new Boolean[2];  
  
        bool[0] = new Boolean(Boolean.parseBoolean("true"));  
        bool[1] = new Boolean(null);  
  
        System.out.println(bool[0] + " " + bool[1]);  
    }  
}
```

What is the result?

- A. True false**
- B. True null
- C. Compilation fails
- D. A NullPointerException is thrown at runtime

Answer: A

117. Given:

```
public class Product {
    int id;
    String name;
    public Product(int id, String name) {
        this.id = id;
        this.name = name;
    }
}
```

And given the code fragment:

```
4. Product p1 = new Product(101, "Pen");
5. Product p2 = new Product(101, "Pen");
6. Product p3 = p1;
7. boolean ans1 = p1 == p2;
8. boolean ans2 = p1.name.equals(p2.name);
9. System.out.print(ans1 + ":" + ans2);
```

What is the result?

- A. true:true
- B. true:false
- C. false:true**
- D. false:false

Answer: C

118. Given:

```
public static void main(String[] args) {
    String ta = "A ";
    ta = ta.concat("B ");
    String tb = "C ";
    ta = ta.concat(tb);
    ta.replace('C', 'D');
    ta = ta.concat(tb);
    System.out.println(ta);
}
```

What is the result?

- A. A B C D
- B. A C D
- C. A B C C**
- D. A B D



E. A B D C

Answer: E

119. Given the code fragments:

```
class Student {  
    String name;  
    int age;  
}
```

And,

```
4. public class Test {  
5.     public static void main(String[] args) {  
6.         Student s1 = new Student();  
7.         Student s2 = new Student();  
8.         Student s3 = new Student();  
9.         s1 = s3;  
10.        s3 = s2;  
11.        s2 = null;  
12.    }  
13.}
```

Which statement is true?

- A. After line 11, three objects are eligible for garbage collection.
- B. After line 11, two objects are eligible for garbage collection.
- C. After line 11, one object is eligible for garbage collection.**
- D. After line 11, none of the objects are eligible for garbage collection.

Answer: C

120. Given the following two classes:

```
public class Customer {  
    ElectricAccount acct = new ElectricAccount();  
  
    public void useElectricity(double kWh) {  
        acct.addKWh(kWh);  
    }  
}  
  
public class ElectricAccount {  
    private double kwh;  
    private double rate = 0.07;  
    private double bill;  
  
    //line n1  
}
```

How should you write methods in the ElectricAccount class at line n1 so that the member variable bill is always equal to the value of the member variable kwh multiplied by the member variable rate?

Any amount of electricity used by a customer (represented by an instance of the customer class) must contribute to the customer's bill (represented by the member variable bill) through the method use Electricity method. An instance of the customer class should never be able to tamper with or decrease the value of the member variable bill.

- A) public void addKWh(double kWh) {
 this.kWh += kWh;
 this.bill = this.kWh*this.rate;
 }
- B) public void addKWh(double kWh) {
 if (kWh > 0){
 this.kWh += kWh;
 this.bill = this.kWh * this.rate;
 }
 }
- C) private void addKWh(double kWh) {
 if (kWh > 0) {
 this.kWh += kWh;
 this.bill = this.kWh*this.rate;
 }
 }
- D) public void addKWh(double kWh) {
 if(kWh > 0) {
 this.kWh += kWh;
 setBill(this.kWh);
 }
 }
 public void setBill(double kWh) {
 bill = kWh*rate;
 }

A. Option A

B. Option B

C. Option C

D. Option D

Answer ,C

121. Given the code fragment:

```

1. public class Test {
2.     public static void main(String[] args) {
3.         /* insert code here */
4.         array[0]=10;
5.         array[1]=20;
6.         System.out.print(array[0]+":"+array[1]);
7.     }
8. }
```

Which code fragment, when inserted at line 3, enables the code to print 10:20?

A. int[] array n= new int[2];

B. int[] array;array = int[2];

C. int array = new int[2];

D. int array [2] ;

Answer: B

122. Given:

```
public class App {

    String myStr = "7007";

    public void doStuff(String str) {
        int myNum = 0;
        try {
            String myStr = str;
            myNum = Integer.parseInt(myStr);
        } catch (NumberFormatException ne) {
            System.out.println("Error");
        }
        System.out.println(
            "myStr: " + myStr + ", myNum: " + myNum);
    }

    public static void main(String[] args) {
        App obj = new App();
        obj.doStuff("9009");
    }
}
```

What is the result?

A. myStr: 9009, myNum: 9009

B. myStr: 7007, myNum: 7007

C. myStr: 7007, myNum: 9009

D. Compilation fails

Answer: C

123. Given the code fragment:

```

public static void main(String[] args) {
    int[] arr = {1, 2, 3, 4};
    int i = 0;
    do {
        System.out.print(arr[i] + " ");
        i++;
    } while (i < arr.length - 1);
}

```

What is the result?

A. 1 2 3 4 followed by an `ArrayIndexOutOfBoundsException`

B. 1 2 3

C. 1 2 3 4

D. Compilation fails.

Answer: A

124. Given the code fragment:

```

LocalDate Time dt= LocalDateTime.of (2014, 7, 31, 1, 1);
dt.plusDays (30);
dt. plusMonths (1);
System.out.print (dt format (DateTimeFormatter. ISO_DATE) );

```

What is the result?

A. An exception is thrown at runtime.

B. 07-31-2014

C. 2014-07-31

D. 2014-09-30

Answer: C

125. Which statement will empty the contents of a `StringBuilder` variable named `sb`?

A. `sb. deleteAll ()`;

B. `sb. delete (0, sb. size ())`;

C. `sb. delete (0, sb. length ())`;

D. `sb. removeAll ()`;



Answer: C

126. Given:

```

class Animal {
    String type = "Canine";
    int maxSpeed = 60;

    Animal () {}

    Animal (String type, int maxSpeed) {
        this.type = type;
        this.maxSpeed = maxSpeed;
    }
}

class WildAnimal extends Animal {
    String bounds;

    WildAnimal (String bounds) {
        //line n1
    }

    WildAnimal (String type, int maxSpeed,
                //line n2
    )
}

```

And given the code fragment:

```

7. WildAnimal wolf = new WildAnimal ("Long");
8. WildAnimal tiger = new WildAnimal ("Feline", 80, "Short");
9. System.out.println (wolf.type + " " + wolf.maxSpeed + " " +
wolf.bounds);
10. System.out.println (tiger.type + " " + tiger.maxSpeed + " " +
tiger.bounds);

```

Which two modifications enable the code to print the following output?

Canine 60 Long





Feline 80 Short

- A. Replace line n1 with:`super ();this.bounds = bounds;`
- B. Replace line n1 with:`this.bounds = bounds;super ();`
- C. Replace line n2 with:`super (type, maxSpeed);this (bounds);`
- D. Replace line n1 with:`this ("Canine", 60);this.bounds = bounds`
- E. Replace line n2 with:`super (type, maxSpeed);this.bounds = bounds;`

Answer: A

127. Given:

```
public class TestScope {  
    public static void main(String[] args) {  
        int var1 = 200;  
        System.out.print(doCalc(var1));  
        System.out.print(" "+var1);  
    }  
    static int doCalc(int var1){  
        var1 = var1 * 2;  
        return var1;  
    }  
}
```

What is the result?

- A. 400 200
- B. 200 200
- C. 400 400
- D. Compilation fails.

Answer: A

128. Given the following class:

```
public class CheckingAccount {
    public int amount;
    public CheckingAccount(int amount) {
        this.amount = amount;
    }
    public int getAmount() {
        return amount;
    }
    public void changeAmount(int x) {
        amount += x;
    }
}
```

And given the following main method, located in another class:

```
public static void main(String[] args) {
    CheckingAccount acct = new CheckingAccount((int)(Math.random()*1000));
    //line n1
    System.out.println(acct.getAmount());
}
```

Which three lines, when inserted independently at line n1, cause the program to print a 0 balance?

- A. this.amount = 0;
- B. amount = 0;
- C. acct(0);
- D. acct.amount = 0;**
- E. acct.getAmount () = 0;
- F. acct.changeAmount(0);
- G. acct.changeAmount(-acct.amount);**
- H. acct.changeAmount(-acct.getAmount());**

Answer: A,C,D

129. Given the code fragment:

```
String[] strs = new String[2];
int idx = 0;
for (String s : strs) {
    strs[idx].concat(" element " + idx);
    idx++;
}
for (idx = 0; idx < strs.length; idx++) {
    System.out.println(strs[idx]);
}
```

What is the result?

- A. Element 0Element 1
- B. Null element 0Null element 1
- C. NullNull
- D. A NullPointerException is thrown at runtime.**

Answer: D

130. Which statement best describes encapsulation?

- A. Encapsulation ensures that classes can be designed so that only certain fields and methods of an object are accessible from other objects.**
- B. Encapsulation ensures that classes can be designed so that their methods are inheritable.
- C. Encapsulation ensures that classes can be designed with some fields and methods declared as abstract.
- D. Encapsulation ensures that classes can be designed so that if a method has an argument MyType x, any subclass of MyType can be passed to that method.

Answer: A

131. Given the following class declarations: Which answer fails to compile?

- A) `ArrayList<Animal> myList = new ArrayList<>();
myList.add(new Tiger());`
- B) `ArrayList<Hunter> myList = new ArrayList<>();
myList.add(new Cat());`
- C) `ArrayList<Hunter> myList = new ArrayList<>();
myList.add(new Tiger());`
- D) `ArrayList<Tiger> myList = new ArrayList<>();
myList.add(new Cat());`
- E) `ArrayList<Animal> myList = new ArrayList<>();
myList.add(new Cat());`

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

Answer: E

132. Given the code fragment:

```
7.  StringBuilder sb1 = new StringBuilder("Duke");
8.  String str1 = sb1.toString();
9.  // insert code here
10. System.out.print(str1 == str2);
```

Which code fragment, when inserted at line 9, enables the code to print true?

- A. String str2 = str1;**
- B. `String str2 = new String(str1);`
- C. `String str2 = sb1. toString ();`
- D. `String str2 = "Duke";`

Answer: B

133. Given the code from the Greeting.Java file:

```
public class Greeting {  
    public static void main(String[] args) {  
        System.out.println("Hello " + args[0]);  
    }  
}
```

Which set of commands prints Hello Duke in the console?

- A) javac Greeting
java Greeting Duke
- B) javac Greeting.java Duke
java Greeting
- C) javac Greeting.java
java Greeting Duke
- D) javac Greeting.java
java Greeting.class Duke

A. Option A

B. Option B

C. Option C

D. Option D

Answer: C

134. Given:

```
public class Vowel {  
    private char var;  
    public static void main(String[] args) {  
        char var1 = 'a';  
        char var2 = var1;  
        var2 = 'e';  
  
        Vowel obj1 = new Vowel ();  
        Vowel obj2 = obj1;  
        obj1.var = 'i';  
        obj2.var = 'o';  
  
        System.out.println(var1 + ", " +var2);  
        System.out.print(obj1.var + ", " +obj2.var);  
    }  
}
```

What is the result?

A. e, ei, o

B. a, ei, o

C. a, eo, o

D. e, eo, o

Answer: A

135. Given:

```

class Alpha {
    int ns;
    static int s;
    Alpha(int ns) {
        if (s < ns) {
            s = ns;
            this.ns = ns;
        }
    }
    void doPrint() {
        System.out.println("ns = " + ns + " s = " + s);
    }
}

```

And,

```

public class TestA {
    public static void main(String[] args) {
        Alpha ref1 = new Alpha(50);
        Alpha ref2 = new Alpha(125);
        Alpha ref3 = new Alpha(100);
        ref1.doPrint();
        ref2.doPrint();
        ref3.doPrint();
    }
}

```

What is the result?

- A) ns = 50 s = 125
ns = 125 s = 125
ns = 100 s = 125
- B) ns = 50 s = 125
ns = 125 s = 125
ns = 0 s = 125
- C) ns = 50 s = 50
ns = 125 s = 125
ns = 100 s = 100
- D) ns = 50 s = 50
ns = 125 s = 125
ns = 0 s = 125

A. Option A

B. Option B

C. Option C

D. Option D

**Answer: B**

136. Given the code fragment:

```
int a[] = {1, 2, 3, 4, 5};
for(XXX) {
    System.out.print(a[e]);
}
```

Which option can replace xxx to enable the code to print 135?

- A. int e = 0; e <= 4; e++
- B. int e = 0; e < 5; e += 2**
- C. int e = 1; e <= 5; e += 1
- D. int e = 1; e < 5; e+ =2

Answer: B

137. You are developing a banking module. You have developed a class named ccMask that has a maskcc method.

Given the code fragment:

```
class CCmask {
    public static String maskCC(String creditCard) {
        String x = "XXXX-XXXX-XXXX-";
        //line n1
    }

    public static void main(String[] args) {
        System.out.println(maskCC("1234-5678-9101-1121"));
    }
}
```

You must ensure that the maskcc method returns a string that hides all digits of the credit card number except the four last digits (and the hyphens that separate each group of four digits).

Which two code fragments should you use at line n1, independently, to achieve this requirement?

- A)

```
StringBuilder sb = new StringBuilder(creditCard);
sb.substring(15, 19);
return x + sb;
```
- B)

```
return x + creditCard.substring(15, 19);
```
- C)

```
StringBuilder sb = new StringBuilder(x);
sb.append(creditCard, 15, 19);
return sb.toString();
```
- D)

```
StringBuilder sb = new StringBuilder(creditCard);
StringBuilder s = sb.insert(0, x);
return s.toString();
```

A. Option A

B. Option B

C. Option C

D. Option D

Answer: B,C

138. Given the code fragment:

```
public static void main (String [] args) {
    ArrayList<Integer> points = new ArrayList<> ();
    points.add (1);
    points.add (2);
    points.add (3);
    points.add (4);
    points.add (null);
    points.remove (2);
    points.remove (null);
    System.out.println(points);
}
```

What is the result?

A. A NullPointerException is thrown at runtime.

B. [1, 2, 4]

C. [1, 2, 4, null]

D. [1, 3, 4, null]

E. [1, 3, 4]

F. Compilation fails.



Answer: F

139. Given the following classes:

```
public class Employee {
    public int salary;
}

public class Manager extends Employee {
    public int budget;
}

public class Director extends Manager {
    public int stockOptions;
}
```

And given the following main method:

```
public static void main(String[] args) {
    Employee employee = new Employee();
    Manager manager = new Manager();
    Director director = new Director();
    //line n1
}
```

Which two options fail to compile when placed at line n1 of the main method?

- A. employee.salary = 50_000;
- B. director.salary = 80_000;
- C. employee.budget = 200_000;
- D. manager.budget = 1_000_000;
- E. manager.stockOption = 500;
- F. director.stockOptions = 1_000;

Answer: C,E

140. Which two class definitions fail to compile?

- A. abstract class A3 {private static int i;public void doStuff(){}public A3(){}}
- B. final class A1 {public A1(){}}
- C. public class A2 {private static int i;private A2(){}}
- D. class A4 {protected static final int i;private void doStuff(){}}



E. final abstract class A5 {protected static int i;void doStuff(){}abstract void doIt();}

Answer: 

141. Given the following code:

```
int[] intArr = {15, 30, 45, 60, 75};  
intArr[2] = intArr[4];  
intArr[4] = 90;
```

What are the values of each element in intArr after this code has executed?

- A. 15, 60, 45, 90, 75
- B. 15, 90, 45, 90, 75
- C. 15, 30, 75, 60, 90**
- D. 15, 30, 90, 60, 90
- E. 15, 4, 45, 60, 90

Answer: C

142. Given the code fragment:

```
abstract class Toy {  
    int price;  
    // line n1  
}
```

Which three code fragments are valid at line n1?

- A. public static void insertToy() {/* code goes here */}**
- B. public abstract Toy getToy() {return new Toy();}
- C. public void printToy();
- D. public int calculatePrice() {return price;}**
- E. public abstract int computeDiscount();**

Answer: C,D,E