

Anagram

An **anagram** refers to a concept where you check if two strings contain the same characters in the same frequency but possibly in a different order.

To check if two strings are anagrams in C, follow the below steps,

i) Remove all non_alphabets from two strings.

ii) Find the length of the strings.

(If length of the two strings are equal, then follow the remaining steps.

If length of the strings are not equal, then strings are not in anagram format.)

iii) Convert both strings to any one case. (upper case/lowercase)

iv) Sort the strings either ascending or descending .

v) Finally compare two strings using strcmp . If the strings are equal means, strings are in anagram format , otherwise the strings are not in anagram format.

Example:

String 1: “12#&il @Ste 0\$ N4”.

String 2: “LS^90 !eni*t”.

step 1: After removing all non-alphabets from two strings,

String1: “ilSteN”.

String2: “LSenit”.

Step 2: Find the length of two strings.

(If length of the strings are equal, then follow the remaining steps.

If length of the strings are not equal, then strings are not in anagram format.)

Step 3: Convert the characters to any one case.

String 1: “ILSTEN”.

String 2: “LSENIT”.

Step 4: Sort the strings either ascending or descending format.

String 1: “EILNST”.

String 2: “EILNST”.

Step 5: Compare the strings using strcmp. If two strings are equal then the given strings are in **ANAGRAM** format , otherwise strings are not in anagram format.