



Step - 1 : Business Problem Understanding

In [1]:

```
1 import pandas as pd
2 import numpy as np
3 import matplotlib.pyplot as plt
4 import seaborn as sns
```

Step - 2 : Data Understanding

Load Data & Understand every variable

In [2]:

```
1 df = pd.read_excel("insurance.xlsx")
2 df.head()
```

Out[2]:

	age	sex	bmi	children	smoker	region	expenses
0	19	female	27.9	0	yes	southwest	16884.92
1	18	male	33.8	1	no	southeast	1725.55
2	28	male	33.0	3	no	southeast	4449.46
3	33	male	22.7	0	no	northwest	21984.47
4	32	male	28.9	0	no	northwest	3866.86

Dataset Understanding

In [3]:

```
1 df.shape
```

Out[3]:

(1338, 7)

In [4]:

```
1 df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1338 entries, 0 to 1337
Data columns (total 7 columns):
#   Column      Non-Null Count  Dtype
---  -
0   age         1338 non-null   int64
1   sex         1338 non-null   object
2   bmi         1338 non-null   float64
3   children    1338 non-null   int64
4   smoker      1338 non-null   object
5   region      1338 non-null   object
6   expenses    1338 non-null   float64
dtypes: float64(2), int64(2), object(3)
memory usage: 73.3+ KB
```

Exploratory Data Analysis



In [5]:

```
1 categorical=[]
2 continous=[]
3 check =[]
4
5 d_types = dict(df.dtypes)
6 for name , type in d_types.items():
7     if str(type) == 'object':
8         categorical.append(name)
9     elif str(type) == 'float64':
10        continous.append(name)
11    else:
12        check.append(name)
13
14 print("categorical features:",categorical)
15 print("continous features:",continous)
16 print("features to be checked:",check)
```

categorical features: ['sex', 'smoker', 'region']
continous features: ['bmi', 'expenses']
features to be checked: ['age', 'children']

In [6]:

```
1 d_types = dict(df.dtypes)
2 for name , type_ in d_types.items():
3     if str(type_) == 'object':
4         print(f"<===== {name} =====>")
5         print(df[name].value_counts())
```

<===== sex =====>
male 676
female 662
Name: sex, dtype: int64
<===== smoker =====>
no 1064
yes 274
Name: smoker, dtype: int64
<===== region =====>
southeast 364
southwest 325
northwest 325
northeast 324
Name: region, dtype: int64

In [7]:

```
1 df.describe()
```

Out[7]:

	age	bmi	children	expenses
count	1338.000000	1338.000000	1338.000000	1338.000000
mean	39.207025	30.665471	1.094918	13270.422414
std	14.049960	6.098382	1.205493	12110.011240
min	18.000000	16.000000	0.000000	1121.870000
25%	27.000000	26.300000	0.000000	4740.287500
50%	39.000000	30.400000	1.000000	9382.030000
75%	51.000000	34.700000	2.000000	16639.915000
max	64.000000	53.100000	5.000000	63770.430000

In [8]:

```
1 df.corr()
```

Out[8]:

	age	bmi	children	expenses
age	1.000000	0.109341	0.042469	0.299008
bmi	0.109341	1.000000	0.012645	0.198576
children	0.042469	0.012645	1.000000	0.067998
expenses	0.299008	0.198576	0.067998	1.000000

Step - 3 : Data Preprocessing



In [9]:

```
1 df.isnull().sum()
```

Out[9]:

```
age      0
sex      0
bmi      0
children 0
smoker   0
region   0
expenses 0
dtype: int64
```

In [10]:

```
1 #drop the region column
2 df.drop('region', axis=1,inplace=True)
```

In [11]:

```
1 # encoding sex column
2 df['sex'].replace({'female':0,'male':1}, inplace=True)
3
4 # encoding 'smoker' column
5 df['smoker'].replace({'no':0,'yes':1}, inplace=True)
```

In [12]:

```
1 X = df.drop('expenses', axis=1)
2 y = df['expenses']
```

In [13]:

```
1 from sklearn.model_selection import train_test_split
2 X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,random_state=9)
```

Step - 4,5 : Modelling & Evaluation

Lasso Regression with default parameters

In [14]:

```
1 # Modelling
2 from sklearn.linear_model import Lasso
3 lasso_base = Lasso()
4 lasso_base.fit(X_train,y_train)
5
6 #predictions
7 train_predictions = lasso_base.predict(X_train)
8 test_predictions = lasso_base.predict(X_test)
9
10 #evaluation
11 print("Train R2:",lasso_base.score(X_train,y_train))
12 print("Test R2:",lasso_base.score(X_test,y_test))
13
14 from sklearn.model_selection import cross_val_score
15 print("Cross Validation Score:",cross_val_score(lasso_base,X,y,cv=5).mean())
```

Train R2: 0.7433161675495346

Test R2: 0.775753862206219

Cross Validation Score: 0.746666487942885

Applying Hyperparameter tuning for Lasso Regression

In [15]:

```
1 from sklearn.model_selection import GridSearchCV
2
3 # model
4 estimator = Lasso()
5
6 # parameters & values
7 param_grid = {'alpha':[0.1,0.2,0.5,0.7,1,10,50,100,1000]}
8
9 #Identifying the best value of the parameter within given values for the given data
10 model_hp = GridSearchCV(estimator,param_grid,cv=5,scoring='neg_mean_squared_error')
11 model_hp.fit(X_train,y_train)
12 model_hp.best_params_
```

Out[15]:

```
{'alpha': 50}
```



Rebuilt Lasso Model using best hyperparameters

In [16]:

```
1 #Modelling
2 from sklearn.linear_model import Lasso
3 lasso_best = Lasso(alpha=50)
4 lasso_best.fit(X_train,y_train)
5
6 print("Intercept:",lasso_best.intercept_)
7 print("coefficients:",lasso_best.coef_)
8
9 #predictions
10 train_predictions = lasso_best.predict(X_train)
11 test_predictions = lasso_best.predict(X_test)
12
13 #Evaluation
14 print("Train R2:",lasso_best.score(X_train,y_train))
15 print("Test R2:",lasso_best.score(X_test,y_test))
16 print("Cross Validation Score:",cross_val_score(lasso_best,X,y,cv=5).mean())
```

Intercept: -11336.591469036648
coefficients: [256.68842008 -0. 303.91129506 408.88291866
23323.3694514]
Train R2: 0.743200050042114
Test R2: 0.7747832866417829
Cross Validation Score: 0.7468453212720682

Final Model

In [17]:

```
1 X = X.drop(X.columns[[1]],axis=1)
2 y = df["expenses"]
3
4 X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,random_state=9)
5
6 #Modelling
7 from sklearn.linear_model import Lasso
8 lasso_best = Lasso(alpha=100)
9 lasso_best.fit(X_train,y_train)
10
11 #predictions
12 train_predictions = lasso_best.predict(X_train)
13 test_predictions = lasso_best.predict(X_test)
14
15 #Evaluation
16 print("Train R2:",lasso_best.score(X_train,y_train))
17 print("Test R2:",lasso_best.score(X_test,y_test))
18 print("Cross Validation Score:",cross_val_score(lasso_best,X,y,cv=5).mean())
```

Train R2: 0.7428619489100416
Test R2: 0.7736501234643404
Cross Validation Score: 0.7465496996440132

Prediction on New Data

Data

In [18]:

```
1 input_data ={"age":31,
2              "sex":"female",
3              "bmi":25.74,
4              "children":0,
5              "smoker":"no",
6              "region":"northeast"}
```

preprocessing the data

In [19]:

```
1 df_test = pd.DataFrame(input_data,index=[0])
2
3 df_test.drop('region',axis=1, inplace=True)
4 df_test['sex'].replace({'female':0,'male':1}, inplace=True)
5 df_test['smoker'].replace({'no':0,'yes':1}, inplace=True)
6
7 transormed_data = df_test.drop(df_test.columns[[1]],axis=1)
```

predict



In [20]:

```
1 lasso_best.predict(transformed_data)
```

Out[20]:

```
array([4547.91555652])
```

"Data Science & AI"
by
Siva Rama Krishna