

Heterogeneous Graph Neural Network

Chuxu Zhang, Dongjin Song, Chao Huang, Ananthram Swami, Nitesh V. Chawla

KDD 2019

10/29/2019

CONTENTS

10/29/2019

- 1 **Background**
- 2 **HetGNN**
- 3 **Experiments**
- 4 **Conclusions**



CONTENTS



1

Background

2

HetGNN

3

Experiments


4

Conclusions



■ Graph-structured Data


- Graph-structured data are ubiquitous.
- Graph-structured data are flexible to model complex interactions.





■ Graph Neural Network




- Neural networks for processing graph-structured inputs.
- Flexible to characterize non-Euclidean data.
- For example, graph convolutional network and graph attention network.






Heterogeneous Graph

Multiple types of nodes or links



Rich semantic information

Meta-path: a relation sequence connecting two objects (e.g., Movie-Actor-Movie).



Movie-Director-Movie

Two movies directed by the same director.





Movie-Actor-Movie

Two movies are starred by the same actor.



Existing Graph Neural Networks focus on homogeneous graph

- ◆ incorporate heterogeneous structural (graph) information
- ◆ considering heterogeneous attributes or contents (e.g, text or image)



Few of them can jointly consider heterogeneous structural (graph) information as well as heterogeneous contents information of each node effectively.

CONTENTS

10/29/2019

1

Background

2

HetGNN


3

Experiments


4

Conclusions







HetGNN



- **C1 - sampling**
heterogeneous neighbors;
- **C2 - encoding**
heterogeneous contents;
- **C3 - aggregating**
heterogeneous neighbors.






■ C1 - **sampling** heterogeneous neighbors;


A heterogeneous neighbors sampling strategy based on random walk with restart (RWR):

Step-1: Sampling fixed length RWR, denoted as $RWR(v)$

Step-2: Grouping different types of neighbors. For each node type t , we select top k_t nodes from $RWR(v)$ according to frequency




C2 - encoding heterogeneous contents;



$$f_1(v) = \frac{\sum_{i \in C_v} \left[\overrightarrow{LSTM} \{ \mathcal{FC}_{\theta_x}(\mathbf{x}_i) \} \oplus \overleftarrow{LSTM} \{ \mathcal{FC}_{\theta_x}(\mathbf{x}_i) \} \right]}{|C_v|} \quad (1)$$

where $f_1(v) \in \mathbb{R}^{d \times 1}$ (d : content embedding dimension), \mathcal{FC}_{θ_x} denotes feature transformer which can be identity (no transformation), fully connected neural network with parameter θ_x , *etc.* The



■ C2 - **encoding** heterogeneous contents;

The LSTM is formulated as:

$$\begin{aligned} \mathbf{z}_i &= \sigma(\mathcal{U}_z \mathcal{F} C_{\theta_x}(\mathbf{x}_i) + \mathcal{W}_z \mathbf{h}_{i-1} + \mathbf{b}_z) \\ \mathbf{f}_i &= \sigma(\mathcal{U}_f \mathcal{F} C_{\theta_x}(\mathbf{x}_i) + \mathcal{W}_f \mathbf{h}_{i-1} + \mathbf{b}_f) \\ \mathbf{o}_i &= \sigma(\mathcal{U}_o \mathcal{F} C_{\theta_x}(\mathbf{x}_i) + \mathcal{W}_o \mathbf{h}_{i-1} + \mathbf{b}_o) \\ \hat{\mathbf{c}}_i &= \tanh(\mathcal{U}_c \mathcal{F} C_{\theta_x}(\mathbf{x}_i) + \mathcal{W}_c \mathbf{h}_{i-1} + \mathbf{b}_c) \\ \mathbf{c}_i &= \mathbf{f}_i \circ \mathbf{c}_{i-1} + \mathbf{z}_i \circ \hat{\mathbf{c}}_i \\ \mathbf{h}_i &= \tanh(\mathbf{c}_i) \circ \mathbf{o}_i \end{aligned} \tag{2}$$



■ C3 - **aggregating** heterogeneous neighbors.

A type-based neural network:

- (1) same type neighbors aggregation;
- (2) types combination.




■ C3 - aggregating heterogeneous neighbors.

(1) same type neighbors aggregation;

$$f_2^t(v) = \mathcal{AG}_{v' \in N_t(v)} \{f_1(v')\} \quad (3)$$

$$f_2^t(v) = \frac{\sum_{v' \in N_t(v)} \left[\overrightarrow{LSTM} \{f_1(v')\} \oplus \overleftarrow{LSTM} \{f_1(v')\} \right]}{|N_t(v)|} \quad (4)$$






■ C3 - aggregating heterogeneous neighbors.

(2) types combination.

$$\mathcal{E}_v = \alpha^{v,v} f_1(v) + \sum_{t \in O_V} \alpha^{v,t} f_2^t(v)$$



$$\mathcal{E}_v = \sum_{f_i \in \mathcal{F}(v)} \alpha^{v,i} f_i$$

$$\alpha^{v,i} = \frac{\exp \{ \text{LeakyReLU}(u^T [f_i \oplus f_1(v)]) \}}{\sum_{f_j \in \mathcal{F}(v)} \exp \{ \text{LeakyReLU}(u^T [f_j \oplus f_1(v)]) \}}$$



(5)

(6)



CONTENTS

10/29/2019

1

Background

2

HetGNN


3

Experiments

4

Conclusions





Link prediction results.
Split notation in data
denotes train/test data
split years or ratios.

Tasks: link prediction, recommendation,
node classification & clustering and
inductive node classification & clustering

$Data_{split}$	Metric	MP2V [4]	ASNE [15]	SHNE [34]	GSAGE [7]	GAT [31]	HetGNN
A-I ₂₀₀₃ (type-1)	AUC F1	0.636 0.435	0.683 0.584	0.696 0.597	0.694 0.586	0.701 0.606	0.714 0.620
A-I ₂₀₀₃ (type-2)	AUC F1	0.790 0.743	0.794 0.774	0.781 0.755	0.790 0.746	0.821 0.792	0.837 0.815
A-I ₂₀₀₂ (type-1)	AUC F1	0.626 0.412	0.667 0.554	0.688 0.590	0.681 0.567	0.691 0.589	0.710 0.615
A-I ₂₀₀₂ (type-2)	AUC F1	0.808 0.770	0.782 0.753	0.795 0.761	0.806 0.772	0.837 0.816	0.851 0.828
A-II ₂₀₁₃ (type-1)	AUC F1	0.596 0.348	0.689 0.643	0.683 0.639	0.695 0.615	0.678 0.613	0.717 0.669
A-II ₂₀₁₃ (type-2)	AUC F1	0.712 0.647	0.721 0.713	0.695 0.674	0.714 0.664	0.732 0.705	0.767 0.754
A-II ₂₀₁₂ (type-1)	AUC F1	0.586 0.318	0.671 0.615	0.672 0.612	0.676 0.573	0.655 0.560	0.701 0.642
A-II ₂₀₁₂ (type-2)	AUC F1	0.724 0.664	0.726 0.737	0.706 0.692	0.739 0.706	0.750 0.715	0.775 0.757
R-I _{5:5}	AUC F1	0.634 0.445	0.623 0.551	0.651 0.586	0.661 0.542	0.683 0.665	0.749 0.735
R-I _{7:3}	AUC F1	0.701 0.595	0.656 0.613	0.695 0.660	0.716 0.688	0.706 0.702	0.787 0.776
R-II _{5:5}	AUC F1	0.678 0.541	0.655 0.582	0.685 0.593	0.677 0.565	0.712 0.659	0.736 0.701
R-II _{7:3}	AUC F1	0.737 0.660	0.695 0.648	0.728 0.685	0.721 0.653	0.742 0.713	0.772 0.749