

ImmPort Shared Data API alignment

NIAID Blueprint Section 3 review. Confidence: **high**. Generated from the OpenAPI document, not from the docs HTML page.

Input

- **Docs page:** <https://docs.immport.org/apidocumentation/>
- **Spec followed:** <https://www.immport.org/data/query/v3/api-docs>
- **Format:** OpenAPI 3.0.1, title Shared Data API
- **Server:** <https://www.immport.org/data/query>
- **Operations:** 83, all GET

The docs page also links a Swagger UI HTML page. That page is not the machine-readable document. This report uses the v3/api-docs file.

Blueprint alignment

bp_jsonld_observed — **High**

Three unauthenticated samples returned HTTP 200 application/json with no @context:

- <https://www.immport.org/data/query/api/lookup/lkVisibilityCategory>
- <https://www.immport.org/data/query/api/lookup/lkVirusStrain>
- <https://www.immport.org/data/query/api/lookup/lkUserRoleType>

Next step: publish one unauthenticated example whose body includes @context. The spec declares application/ld+json on GET /api/study/json-ld/{studyAccession} and GET /api/study/cde/{studyAccession}, but both are authenticated and have no example id, so they were not called. A declared media type is not an observed JSON-LD body.

bp_resource_iris — **Medium**

47 paths use a verb-like segment: 45 under /api/lookup/..., plus GET /api/search/subject and GET /api/search/study.

Next step: use noun IRIs for those collections so the URL can serve as a JSON-LD @id.

Passed: bp_openapi_doc; bp_jsonld_declared (two responses offer application/ld+json); bp_get_retrieval (every operation is GET); bp_version_in_path (no version segment in the paths or server URL). info.version is v1, but that is not in the path.

Common practice

These are not Blueprint failures.

- **License:** info.license has no name or URL. Add one.

- **Examples:** 46 operations with a 2xx response include no example. Start with the JSON-LD study operation.
- **Errors:** 45 operations document no 4xx or 5xx response.
- **Pagination:** 56 collection GETs document no limit, offset, page, or cursor parameter.

Passed: contact, operation summaries, operation ids, and local \$refs.

Samples

URL	Status	Content type	JSON-LD @context
/api/lookup/lkVisibilityCategory	200	application/json	no
/api/lookup/lkVirusStrain	200	application/json	no
/api/lookup/lkUserRoleType	200	application/json	no

No credentials were sent. Authenticated study and result operations were not called.

Not checked

- HTML-embedded JSON-LD and a downloadable metadata index. The site was not crawled for them.
- Authenticated operations. No API key was sent.
- Table 1 names that appeared in the recorded schemas, examples, or sample bodies: citation, conditionsOfAccess. contentUrl also appeared; it is not itself a Table 1 element.

Overall

The Shared Data API is documented as OpenAPI 3.0.1, uses GET, and declares JSON-LD on two study operations. The highest-priority gap is that the only live responses this run could fetch were lookup JSON without @context. Fix that before the verb-like /lookup and /search paths. The practice gaps are documentation quality, not Blueprint misses.