

API alignment report

VEuPathDB service API page · NIAID Blueprint Section 3 · generated from niaid-bp-api-assess

Input

- **Source:** <https://veupathdb.org/service-api.html>
- **Kind:** docs (no spec hop)
- **Spec format:** none parsed. The page title is “WDK Rest Service (3.0)” and the HTML generator is raml2html 7.8.0. No OpenAPI or Swagger document was linked or parsed.
- **Confidence:** low. No OpenAPI or Swagger document was parsed.
- **Outside this rubric:** none. The page does not name GraphQL, SPARQL, or FHIR. RAML is machine-readable documentation, but Section 3’s documentation objective is OpenAPI/Swagger, and this run did not score the RAML as a substitute.

The analyzer did not produce an operation list. Practice checks that need a parsed spec are therefore not stated. This is not proof those practices are missing.

Blueprint alignment

Section 3 asks for JSON-LD (at least as an option), resource IRIs usable as @id, GET for retrieval, and an OpenAPI/Swagger document.

bp_openapi_doc — Medium

- **Evidence:** The documentation page has no parseable OpenAPI or Swagger document. Discovery stopped on this page: no linked .json / .yaml spec, no springdoc config, and no Swagger UI initializer.
- **Recommended next step:** Publish an OpenAPI 3 document for the WDK Rest Service and link it from this page (a converted RAML file is enough). Point the link at the spec itself, not only at this HTML rendering.

bp_resource_iris — Medium

- **Evidence:** The page states a verb-like path `POST /users/{user-id}/favorites/query`. The same path is the only verb-like path the analyzer recorded.
- **Recommended next step:** Replace `/favorites/query` with a resource IRI, for example `GET /users/{user-id}/favorites` with the query in optional parameters, or `POST /users/{user-id}/favorite-queries` if the call creates a stored query.

Passed: `bp_version_in_path`. The page did not state a `/v1/-` style segment. The “(3.0)” in the title was not treated as a path version.

Not stated (not a failure): `bp_jsonld_declared`, `bp_jsonld_observed`, `bp_get_retrieval`. The page does not declare `application/ld+json` or `@context`, and no unauthenticated sample was fetched. Absence from this

HTML page is not proof the live API lacks JSON-LD or uses the wrong HTTP method.

Common practice

These are not Blueprint failures. Every practice check is **not stated**, because no OpenAPI document was parsed: contact, license, summaries, operation ids, examples, error responses, pagination, and local \$refs. Do not read that list as a set of failures.

Recommended next step: once an OpenAPI document exists, re-run this assessment. Those checks cannot be scored from the HTML page alone.

Samples

sample_plan was empty. No absolute unauthenticated example GET was taken from the page, and the script does not invent path ids or send credentials. No live GET was made. This run does not say whether any response body contains @context.

Not checked

- HTML pages with embedded JSON-LD, and a downloadable metadata index. Both are Blueprint fallbacks. This run did not crawl the site for them.
- Authenticated operations. No API key was sent.
- Table 1 fields. observed_property_names is empty, so no Table 1 field is reported.
- The RAML source behind this HTML page, if it is published elsewhere. This run did not search the site for a .raml file.

Overall

Confidence is low: the service-api page is a human rendering of a RAML API, not an OpenAPI document, so most Section 3 checks could not be scored. The documentation gap is the one to fix first — publish OpenAPI and link it here — because the other objectives (JSON-LD, GET, resource IRIs) cannot be judged fairly until a machine-readable spec is in hand. The only resource-IRI miss this run can cite is `POST /users/{user-id}/favorites/query`. A landing-page JSON-LD check, if wanted, is `niaid-bp-metadata-extract`.