

offer the same user-context menu entry as Discord; an explicit user selector and user lookup can preserve the avatar operation without claiming identical placement.

Unified-demo combines configuration with CLI verb metadata. Preserve the configuration demonstration without echoing secrets. Its `__verb__` status/run metadata is a separate CLI integration feature: a Slack slash status command alone does not prove that integration has been ported. Either integrate with the project's supported jsverbs path or record that work as outstanding.

Poker

The poker library contains card parsing, deck construction, five-card scoring, best-hand selection and Hold'em advice. These algorithms are largely platform independent. Reuse their logic, while replacing Discord-specific state scoping and renderers. Scope a game to workspace, channel and user so two players do not overwrite each other.

Preserve deal, keep/redraw, score, reset, rank and action-advice commands, the quick-action buttons, and the rank/advice forms. Validate duplicate cards, invalid positions, repeated redraw and missing active game state. Modal success must show a result through an explicit follow-up or a result view; silently closing a scoring form loses an existing feature.

Support

Support includes ticket preview/status and thread fetch/join/leave/start. Slack threads are addressed by channel and root timestamp, not standalone Discord thread channel IDs. A new Slack thread starts when the bot posts a reply with `thread_ts`. Fetching uses `conversations.replies`. Do not equate joining/leaving a Slack channel with joining/leaving a thread: establish an actual platform counterpart before offering those operations.

The original deferred/edit/follow-up workflow requires both initial response handling and later visible updates. A response URL replacement capability can update an ephemeral interactive message; a normal channel message uses `chat.update`. The API contract must make the chosen delivery mode explicit.

Custom knowledge base and knowledge base

Custom-kb stores links, metadata and search results in SQLite. Port add/link, search/list, selection/refresh and suggestion workflows with the same durable semantics. URL and identity validation belongs in its store/domain functions. Use parameterized SQL and test duplicate URL updates as well as fresh inserts.

Knowledge-base has more state: capture, teach/remember forms, aliases, source references, verification/staleness/rejection, review queues, selected entries, search pagination and exports. Read `lib/store.js`, `capture.js`, `review.js`, `search.js`, and `reactions.js` before porting its endpoint. Slack source references use workspace, channel and message timestamp; Discord message URLs must be replaced with Slack permalinks or equivalent stored source identity.

Passive capture and reaction-triggered behavior require message and reaction events. Keep source identity and review actor fields. Test that one workspace's search cannot retrieve another workspace's records if the process or database is shared. Do not preserve Discord column names without documenting their new meaning; new Slack stores should use native names.