

UI showcase

The existing Slack showcase is the smallest message/button/modal demonstration. The Discord showcase also contains search, review selection, pagination, cards, confirmations, select variants and aliases. Recreate those workflows with Slack-native layouts and stable state IDs. Use user/conversation selects where the source asks for those entities. Role and mentionable controls need an explicitly documented semantic decision, not a mislabeled Slack control.

5. Proposed framework extensions

This section is a proposed API contract, not a statement that these methods already exist. Implement small capabilities as each port needs them. Keep Go SDK values and credentials private.

Message operations

Add explicit domain services for updating/deleting channel messages, ephemeral replies, response replacement, pins and conversation reads. Use channel/timestamp pairs and detached message payloads. Keep response URL replacement on the invocation capability; never expose the secret URL.

```
// Proposed API; implement and test before using in bot examples.
await ctx.slack.messages.update({channelId, ts, text, blocks});
await ctx.slack.messages.remove({channelId, ts});
await ctx.replaceReply({text, blocks});
const page = await ctx.slack.conversations.history({
  channelId, cursor, limit: 100
});
```

Service errors must distinguish missing scope, missing membership, rate limiting and unknown delivery outcome. Avoid unconditional retries on writes. For read pagination, expose enough error information for a user to retry intentionally rather than adding a generic job scheduler.

UI and interaction routing

Extend builders for static/user/conversation selects, context/image blocks, link buttons, confirmations and multiline text input. Fix optional-input placement. Add selectors to action blocks only when their allowed surface rules are understood. Submitted values require typed helpers for selected options/users/conversations, not an assumption that every field has value.

Add global/message shortcut registration and decoding. Their callback IDs select handlers and their trigger IDs can open modals. External options requests need a response-bearing ACK with the options payload. Their lifecycle must be tested independently from normal button actions.

Keep the current Go-owned receipt model. New ACK payload variants belong in its explicit response type and validation. Do not restore the deferred worker reservation/priority scheduler under the pretext of implementing selects.

Database and runtime capabilities

The pinned go-go-goja module includes a database module: `modules/database/database.go`. Inspect its constructor, configuration, transaction support and close behavior before registering it for Slack. Register only the intended module rather than enabling every implicit module.

Inspection must remain free of database mutations. Stores should initialize lazily on a real invocation or explicit runtime setup, and simulation should use a test database. Close the