

lazy store initialization. Prove inspect does not write and records survive closing/reopening a runtime.

6. **Simple and game bots.** Finish announcements, ping, hater, interaction-types, unified-demo and poker, including every equivalent interaction from the inventory.
7. **Data bots.** Port custom-kb and knowledge-base with durable state, review/search workflows and source references.
8. **Operational bots.** Port support, show-space, archive-helper and moderation with explicit platform differences and authorization.
9. **Showcase and qualification.** Complete the UI showcase parity matrix, update declarations/help/README, run all bot discovery/manifest/fixture checks and document remaining plan/token-dependent live tests.

A bot is complete only when its matrix has no unexplained missing equivalent. A conditional Enterprise API implementation can be tested with a transport mock and marked “live qualification requires Enterprise/admin token”; that is different from an absent implementation.

9. Tests that prove behavior

Use unit tests for pure card/date/formatting logic, host tests for routing and state, transport fixtures for Slack encoding, and integration tests for a representative multi-invocation workflow. Do not merely assert that a bot inspects: inspection executes declarations but does not exercise handlers.

A knowledge-base acceptance test creates a temporary SQLite file, submits a record, closes the host, opens another host against the same file, searches, reviews and exports the record. A poker test deals a game, redraws selected cards once and rejects a second redraw. A show-space test asserts that an unauthorized actor produces zero write operations.

An archive test supplies two history pages, verifies cursor propagation, renders the complete chronological output, and checks the bytes sent through the external-upload sequence. A moderation test must prove bot-owned deletion constraints rather than simulate arbitrary-message deletion success.

Run live tests only for explicitly authorized operations. Creating this ticket and implementing administrative methods does not authorize banning users, deleting real messages or publishing announcements. Offline mocks provide meaningful coverage without performing those operations.

10. First commands for an intern

From the repository root:

```
GOWORK=off go run ./cmd/slack-bot help slack-bot-guide
GOWORK=off go run ./cmd/slack-bot help slack-ui-dsl
GOWORK=off go run ./cmd/slack-bot bots list
GOWORK=off go run ./cmd/slack-bot bots inspect ui-showcase
GOWORK=off go run ./cmd/slack-bot bots simulate ui-showcase \
  --event-file examples/slack-bots/fixtures/ui-view.json
GOWORK=off go test ./internal/jsslack ./pkg/slackcli
```

On this workstation use `GOCACHE=/tmp/go-build-cache-slack-ui` if the normal cache is not writable. Local network fixture tests need loopback binding. Long-lived runners belong in tmux. Use explicit profile and bot names and inspect startup logs before interpreting a Slack response.