

Show-space

Show-space combines seed data, persistent show records, dates, role-based authorization, announcement posting, pins, cancellation, archiving and diagnostic commands. Port its pure date/catalog logic separately from Slack rendering and transport. Keep show state durable and preserve links to posted announcements using channel and timestamp strings.

Discord roles do not have identical Slack permissions. Configure allowed operator IDs and, where appropriate, explicit Slack user-group IDs. A matching user-group name is not proof of authorization. The debug workflows should explain resolved memberships and configured IDs without printing secrets. Do not let missing configuration default to unrestricted writes.

Announcement operations must use the returned message reference directly for pinning. Avoid the Discord example's fallback of listing recent messages and guessing the newly posted one: Slack's post response supplies the timestamp.

Archive helper and moderation

Archive-helper needs paginated channel/thread history, chronological rendering, source links and file output. Preserve author/time metadata and Markdown escaping. Stop pagination at the requested boundary or limit, handle empty pages, and keep cursors opaque. The existing Discord helper's before snowflake pagination does not translate directly into Slack's cursors and timestamp filters.

Slack file upload uses an external-upload sequence: request an upload URL, send bytes, then complete the upload. Archive generation must not stop at a message saying an archive was created; acceptance includes verifying the uploaded file content in the transport mock.

Moderation must distinguish lookup, bot-owned message changes, channel operations and workspace administration. Slack's `chat.delete` with a bot token can delete only that bot's messages; it cannot implement arbitrary Discord bulk deletion. User groups are not Discord roles. Workspace removal has an Enterprise/admin API with different credentials; channel kicking is a different action. Do not silently replace workspace bans/timeouts with channel removal.

Discord family	Native Slack operation or boundary
Guild/member info	Workspace/team and users APIs.
Channel info/topic	Conversations info and <code>setTopic</code> .
Pin/unpin/list pins	<code>pins.add</code> , <code>pins.remove</code> , <code>pins.list</code> .
Fetch message/history	Conversations history/replies with explicit access constraints.
Delete messages	Own-message <code>chat.delete</code> ; wider moderation is not granted by bot token.
Role membership	Explicit user-group workflow only where its semantics fit.
Kick workspace member	Admin users removal where plan and admin user token permit.
Ban/unban, timeout, channel slowmode	No assumed equivalent; document exact supported counterpart or lack of one.

The message-delete restriction is documented in the `chat.delete` reference. The `admin.users.remove` reference requires an Enterprise plan and an appropriate user token. Implementing an admin call does not authorize exercising it against the user's real workspace.