

Anna's Example Thesis

Anna Pedersen

21496350

B. Eng. Mechatronic Engineering Project Thesis
School of Civil and Mechanical Engineering
Curtin University

Semester 2 2025

67 Mountjoy Rd,
Nedlands,
WA 6009

January 6, 2026

The Head
School of Civil and Mechanical Engineering,
Curtin University,
Kent Street,
Bentley,
WA 6102

Dear Sir,

I submit this thesis entitled “*Anna’s Example Thesis*”, based on MXEN4005
Mechatronics Engineering Research Project 1 and MXEN4006 Mechatronics
Engineering Research Project 2, undertaken by me as part-requirement for the degree of
B. Eng. Mechatronic Engineering.

Yours faithfully,

Anna Pedersen
21496350

Acknowledgements

I would like to acknowledge and thank the contribution and support of , my Thesis Supervisor and .

Abstract

Mechanical wear and fatigue failure is one of the most significant costs in industrial nations.

Nomenclature

Symbol	Title	Unit(s)
a	Half Contact Width	mm
b	Effective Face Width	mm

Contents

Acknowledgements	i
Abstract	ii
Nomenclature	iii
List of Figures	iv
List of Tables	iv
1.0 Introduction	1
1.1 Subheading	1
1.1.1 This is a smaller heading	1
1.2 This is another big heading	1
2.0 Background	2
2.1 Cost of Wear and Fatigue	2
3.0 Experimental Procedure	3
3.1 Construction of temperature distribution model	3
4.0 Results and Discussion	4
4.1 Construction of Thermal distribution	4
5.0 Conclusion	5
6.0 Future Work	6
6.1 Analytical Validation of Control Simulation	6
7.0 Fun Stuff	7
Appendix A	9
Appendix B	10

List of Figures

List of Tables

Introduction

1.1 Subheading

This is the introduction to my thesis

It should be able to recognise **pictures** with and *without* captions and parse them

1.1.1 This is a smaller heading

Thesis already kinda sucks low key

1.2 This is another big heading

That was a dramatic space that I **want** kept.

Im not quite sure what else, maybe citations would also be cool.

Background

2.1 Cost of Wear and Fatigue

As stated in Fortescue's Annual 2024 Report, they had an annual revenue of

Experimental Procedure

3.1 Construction of temperature distribution model

When constructing the thermal model, the body temperature will be assumed to be between

Results and Discussion

4.1 Construction of Thermal distribution

Figures 13 and 14 show the thermal distribution over the FGZ-A Gear and Pinion. Where the areas highlighted in red show 200°C and the dark blue area over the rings shows 120°C, as depicted in Figure 15.

Conclusion

These simulations and models were able to validate an appropriate method to incorporate the thermal effects expected in a gearbox

Future Work

6.1 Analytical Validation of Control Simulation

This Analysis shows how to validate a control model with no thermal effects or pitting; this method can be used

Fun Stuff

this is loads of fun

References

- [1] E. Chailloux, P. Manoury, and B. Pagano, *Developing Applications with Objective Caml*. Paris, France: Éditions O'Reilly, 2000, online edition. [Online]. Available: <https://caml.inria.fr/pub/docs/oreilly-book/>
- [2] D. Rémy, *Using, Understanding, and Unraveling the OCaml Language: From Practice to Theory and Vice Versa*, Rocquencourt, France, 2001, course notes (APPSEM 2000). [Online]. Available: <https://gallium.inria.fr/~remy/cours/appsem/ocaml.pdf>

Appendix A

STUFF IN APPENDIX A

Appendix B

STUFF2